

Title (en)  
ANTIMICROBIAL PROTECTIVE LAYER, SUBSTRATE HAVING THE ANTIMICROBIAL PROTECTIVE LAYER, AND METHOD FOR PRODUCING THE SUBSTRATE HAVING THE ANTIMICROBIAL PROTECTIVE LAYER

Title (de)  
ANTIMIKROBIELLE SCHUTZ-SCHICHT, SUBSTRAT MIT DER ANTIMIKROBIELLEN SCHUTZ-SCHICHT UND VERFAHREN ZUM HERSTELLEN DES SUBSTRATS MIT DER ANTIMIKROBIELLEN SCHUTZ-SCHICHT

Title (fr)  
COUCHE DE PROTECTION ANTIMICROBIENNE, SUBSTRAT COMPORTANT LA COUCHE DE PROTECTION ANTIMICROBIENNE, ET PROCÉDÉ DE PRODUCTION DU SUBSTRAT COMPORTANT LA COUCHE DE PROTECTION ANTIMICROBIENNE

Publication  
**EP 4326824 A1 20240228 (DE)**

Application  
**EP 22734237 A 20220608**

Priority  
• EP 21180740 A 20210622  
• EP 2022065530 W 20220608

Abstract (en)  
[origin: CA3223316A1] The invention relates to an antimicrobial protective layer for protecting a substrate surface of a substrate, the protective layer having at least one antimicrobial reagent having a reagent coloring and at least one inert inorganic color pigment having a color-pigment coloring different from the reagent coloring, and the reagent concentration of the reagent in the protective layer and the color-pigment concentration of the inorganic color pigment in the protective layer being selected in such a way that a protective-layer coloring of the protective layer differs from the reagent coloring. The invention also relates to a substrate having the protective layer for protecting a substrate surface of the substrate. The object is, for example, an object of a public means of transportation or an object of an infrastructure installation used by multiple persons. In addition, the invention also relates to a method for producing the substrate having the protective layer, comprising the following method steps: a) providing a starting substrate having a starting-substrate surface and b) arranging the protective layer on the starting-substrate surface. By means of the invention, surfaces to be protected can be designed in any color. A spraying method is preferably used for the application. For flexible substrates (e.g. made of a nonwoven material), a roll-to-roll method can be used.

IPC 8 full level  
**A01N 59/16** (2006.01); **C09D 5/14** (2006.01); **C09D 7/61** (2018.01)

CPC (source: EP)  
**A01N 59/16** (2013.01); **C09D 5/14** (2013.01); **C09D 7/61** (2018.01); **C08K 3/013** (2018.01); **C08K 2003/0806** (2013.01); **C08K 2003/2262** (2013.01)

C-Set (source: EP)  
**A01N 59/16** + **A01N 25/10**

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

Designated validation state (EPC)  
KH MA MD TN

DOCDB simple family (publication)  
**EP 4108730 A1 20221228**; CA 3223316 A1 20221229; CN 117561310 A 20240213; EP 4326824 A1 20240228; WO 2022268506 A1 20221229

DOCDB simple family (application)  
**EP 21180740 A 20210622**; CA 3223316 A 20220608; CN 202280044899 A 20220608; EP 2022065530 W 20220608; EP 22734237 A 20220608