

Title (en)

SUPPORTING CONTAINERS WITH LASHING SYSTEM

Title (de)

STÜTZEN VON BEHÄLTERN MIT EINEM VERZURRSYSTEM

Title (fr)

SUPPORT DE RÉCIPIENTS AVEC SYSTÈME D'ARRIMAGE

Publication

EP 4331967 A1 20240306 (EN)

Application

EP 22193212 A 20220831

Priority

EP 22193212 A 20220831

Abstract (en)

A lashing system (1) for supporting containers (5, 8, 17) located on top of each other, wherein the lashing system (1) comprising at least an upper lashing element (19) and a lower lashing element (20), wherein the upper lashing element (19) is configured to be connected from an upper end to an upper container (5); the lower lashing element (20) is configured to be connected from an upper end to a lower container (8); at least part of at least one of the at least upper and/or lower lashing elements (19, 20) is flexible; and the at least one of the at least upper and/or lower lashing elements (19, 20) is configured to stretch lengthwise more than the other one of the at least upper and/or lower lashing elements (19, 20) when the lashing system (1) is in a tension position. Also a method is disclosed.

IPC 8 full level

B63B 25/24 (2006.01); **B63B 25/28** (2006.01)

CPC (source: CN EP)

B63B 25/24 (2013.01 - EP); **B63B 25/28** (2013.01 - EP); **B65D 90/0006** (2013.01 - CN); **B63B 2025/285** (2013.01 - EP)

Citation (search report)

- [XY] DK 201770664 A1 20190219 - MAERSK LINE AS [DK]
- [XI] US 2006280549 A1 20061214 - HSIEH JUNG-KUANG [TW]
- [A] US 2020255100 A1 20200813 - OH YOUNG HOAN [KR]
- [Y] DE 102011087042 B3 20130529 - GERMAN LASHING ROBERT BOECK GMBH [DE]

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

Designated validation state (EPC)

KH MA MD TN

DOCDB simple family (publication)

EP 4331967 A1 20240306; CN 117622725 A 20240301; TW 202421517 A 20240601

DOCDB simple family (application)

EP 22193212 A 20220831; CN 202310125603 A 20230215; TW 112102799 A 20230119