

Title (en)

VIG UNIT PRODUCTION COMPRISING USE OF A DISPENSER COMPRISING A COLLECTION SHEET

Title (de)

VIG-EINHEITSHERSTELLUNG MIT VERWENDUNG EINES SPENDERS MIT EINEM SAMMELBLATT

Title (fr)

PRODUCTION D'UNITÉ VIG COMPRENANT L'UTILISATION D'UN DISTRIBUTEUR COMPRENANT UNE FEUILLE DE COLLECTE

Publication

EP 4357576 A1 20240424 (EN)

Application

EP 22202431 A 20221019

Priority

EP 22202431 A 20221019

Abstract (en)

The present disclosure relates to a method of manufacturing a vacuum insulating glass unit (VIG). A plurality of spacers (2) are dispensed on a major surface (3a) a first glass sheet (3) by means of a dispenser (10) of a spacer dispensing system (200). The dispenser (10) comprises a housing (12) comprising a guidance space (13) placed opposite to an upper part (12a) of the housing (12) and a bottom part (12b) of the housing (12), a spacer outlet (16) arranged at the bottom part (12b) of the housing (12), and a collection sheet (15). The collection sheet (15) may e.g. be disc shaped, and comprises at least one collection hole (15a) extending between opposing major surfaces (15b, 15c) of the collection sheet (15). The collection sheet (15) is arranged in the guidance space (13). Therein the method moreover comprises the steps of: providing a relative rotational movement between the collection sheet (15) and the housing (12) around a rotation axis (RAX) by means of a drive motor (18) so that the collection hole (15a) collects a spacer (2) from a spacer supply, and providing a further, relative rotational movement between the collection sheet (15) and the housing (12) around the rotation axis (RAX) to align the collected spacer (2) in the collection hole (15a) opposite to the spacer outlet (16) to deliver the collected spacer (2) to the spacer outlet (16) and towards the surface (3a) of the glass sheet (3). Each of the plurality of spacers (2) in the spacer storage compartment (11) may have a spacer height (H1) extending between the contact surfaces (2a, 2b). Each of said spacers (2) may have a spacer width (W1), wherein the guidance space (13) has a height (H2) which is less than 1.4 times the spacer height (H1). The height (H2) of the guidance space (13) may be smaller than the spacer width (W1).

IPC 8 full level

E06B 3/66 (2006.01); **E06B 3/663** (2006.01); **E06B 3/673** (2006.01); **E06B 3/677** (2006.01)

CPC (source: EP)

E06B 3/6612 (2013.01); **E06B 3/66304** (2013.01); **E06B 3/67326** (2013.01); **E06B 3/6775** (2013.01); **E06B 3/67369** (2013.01)

Citation (applicant)

- WO 2019218901 A1 20191121 - LUOYANG LANDGLASS TECH CO LTD [CN]
- WO 2021208628 A1 20211021 - LUOYANG LANDGLASS TECH CO LTD [CN]
- CN 205258287 U 20160525 - LUOYANG LANDGLASS TECH CO LTD
- US 11396477 B2 20220726 - NONAKA MASATAKA [JP], et al
- CN 106045286 A 20161026 - LUOYANG LANDGLASS TECH CO LTD

Citation (search report)

[A] CN 203668209 U 20140625 - LUOYANG LANDGLASS TECH CO LTD

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC ME MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA

Designated validation state (EPC)

KH MA MD TN

DOCDB simple family (publication)

EP 4357576 A1 20240424

DOCDB simple family (application)

EP 22202431 A 20221019