

Title (en)
FLOW SENSOR AND METHOD USING TEMPERATURE TO IMPROVE MEASUREMENTS FOR LOW RATES

Title (de)
DURCHFLUSSSENSOR UND VERFAHREN ZUR VERBESSERUNG DER MESSUNGEN BEI NIEDRIGEN GESCHWINDIGKEITEN MITTELS TEMPERATUR

Title (fr)
CAPTEUR DE DÉBIT ET PROCÉDÉ UTILISANT LA TEMPÉRATURE POUR AMÉLIORER DES MESURES POUR DES VALEURS FAIBLES

Publication
EP 4363805 A1 20240508 (EN)

Application
EP 22832243 A 20220617

Priority

- DK PA202100690 A 20210627
- DK PA202200049 A 20220119
- DK 2022050134 W 20220617

Abstract (en)
[origin: WO2023274474A1] A flow sensor (1) configured to measure the flow (Q) of a fluid (26) flowing through a tubular structure (2) is disclosed. The flow sensor (1) comprises a first detection unit (34) that is configured to detect flows (Q) above a predefined lower flow level (QA) representing the lowest flow (QA) that can be measured by using the first detection unit (34). The flow sensor (1) comprises a second detection unit (36) that comprises: - a first temperature sensor (12) arranged and configured to detect the temperature (Ts) of the surroundings (the ambient temperature); - a second temperature (14) arranged and configured to detect the temperature (Tf) of the fluid (26); - a data processor (10) connected to the temperature sensors (12, 15 14). The second detection unit (36) is configured to estimate the flow (Q) below the lower flow level (QA) on the basis of the temperature difference between the surroundings and a fluid (26). The temperature difference between is measured by the first temperature sensor (12) and the second temperature sensor (14). The second detection unit (36) is configured to estimate the flow (Q) below the lower flow level (QA) on the basis of one or more measurements (M1, M2) made in a flow area (B2), in which the flow sensor (1) can detect the flow (Q) and in which the flow (Q) depends on the temperature difference (ΔT_{sf}). The one or more measurements (M1, M2) made in the flow-calibration-area (B2) are used to determine parameters required to determine how the flow (Q) depends on the temperature difference (ΔT_{sf}) in the flow-calibration-area (B2) and in the flow area (B1) below the flow-calibration-area (B2).

IPC 8 full level
G01F 1/66 (2022.01); **G01K 13/02** (2021.01)

CPC (source: DK EP US)
G01F 1/662 (2013.01 - EP US); **G01F 1/667** (2013.01 - EP US); **G01F 1/668** (2013.01 - US); **G01F 1/68** (2013.01 - DK); **G01F 1/6847** (2013.01 - EP US); **G01F 1/6882** (2013.01 - US); **G01F 7/00** (2013.01 - EP US); **G01F 15/14** (2013.01 - US); **G01F 1/668** (2013.01 - DK); **G01F 25/10** (2022.01 - EP)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

Designated validation state (EPC)
KH MA MD TN

DOCDB simple family (publication)
WO 2023274474 A1 20230105; AU 2022301224 A1 20230525; AU 2022303540 A1 20240104; AU 2022304000 A1 20240104; CA 3223300 A1 20230105; CA 3223307 A1 20230105; DK 181025 B1 20221004; DK 202200049 A1 20221004; EP 4363805 A1 20240508; EP 4363806 A1 20240508; JP 2024527311 A 20240724; JP 2024527312 A 20240724; US 2024142283 A1 20240502; US 2024151568 A1 20240509; WO 2023274475 A1 20230105; WO 2023274476 A1 20230105

DOCDB simple family (application)
DK 2022050134 W 20220617; AU 2022301224 A 20220617; AU 2022303540 A 20220617; AU 2022304000 A 20220617; CA 3223300 A 20220617; CA 3223307 A 20220617; DK 2022050135 W 20220617; DK 2022050136 W 20220617; DK PA202200049 A 20220119; EP 22832243 A 20220617; EP 22832245 A 20220617; JP 2023580350 A 20220617; JP 2023580381 A 20220617; US 202318395947 A 20231226; US 202318395972 A 20231226