



(11)

**EP 2 634 231 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention of the grant of the patent:  
**29.06.2022 Bulletin 2022/26**

(51) International Patent Classification (IPC):  
**C09K 3/30** <sup>(2006.01)</sup> **C09K 5/04** <sup>(2006.01)</sup>  
**C08J 9/14** <sup>(2006.01)</sup> **C07C 21/18** <sup>(2006.01)</sup>

(21) Application number: **13169895.3**

(52) Cooperative Patent Classification (CPC):  
(C-Sets available)  
**C09K 5/044; C07C 17/04; C07C 17/087;**  
**C07C 17/204; C07C 17/206; C07C 17/25;**  
**C07C 19/08; C07C 19/10; C07C 19/12;**  
**C07C 21/04; C07C 21/18; C08J 9/144; C08J 9/149;**  
**C09K 3/30; C09K 5/045;** (Cont.)

(22) Date of filing: **07.05.2009**

(54) **Compositions**

Zusammensetzungen

Compositions

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR**

(56) References cited:  
**WO-A2-2005/105947 US-A1- 2005 233 932**  
**US-A1- 2007 096 053 US-A1- 2007 197 842**  
**US-B1- 6 472 573**

(30) Priority: **07.05.2008 US 126810**

(43) Date of publication of application:  
**04.09.2013 Bulletin 2013/36**

(60) Divisional application:  
**22164142.6**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:  
**09743644.8 / 2 271 725**

(73) Proprietor: **The Chemours Company FC, LLC**  
**Wilmington DE 19801 (US)**

(72) Inventors:  
• **Mahler, Barry Asher**  
**Glen Mills, PA Pennsylvania 19342 (US)**  
• **Nappa, Mario Joseph**  
**Newark, DE Delaware 19711 (US)**

(74) Representative: **Heinemann, Monica**  
**Abitz & Partner**  
**Patentanwälte mbB**  
**Postfach 86 01 09**  
**81628 München (DE)**

- **Anonymous: "Standard for Specifications for Fluorocarbon Refrigerants", ARI, 1 January 2006 (2006-01-01), pages 1-15, XP055533296,**
- **James M Calm: "DOE/CE/23810-105 ARTI REFRIGERANT DATABASE DATA SUMMARIES -VOLUME 1: SINGLE-COMPOUND REFRIGERANTS", , 1 January 1999 (1999-01-01), page 34-36,168-170, 200-202,267,305,306,336,520-523,527, Retrieved from the Internet: URL:[http://www.ahrinet.org/App\\_Content/ahr/files/RESEARCH/Technical%20Results/MCLR-Program/ARTI%20Refrigerant%20Database%20Data%20summaries-Volume%20One-Single-compoun d%20Refrigerants-Calm-1999-DOE-CE-23810-10 5.pdf](http://www.ahrinet.org/App_Content/ahr/files/RESEARCH/Technical%20Results/MCLR-Program/ARTI%20Refrigerant%20Database%20Data%20summaries-Volume%20One-Single-compoun d%20Refrigerants-Calm-1999-DOE-CE-23810-10 5.pdf) [retrieved on 2019-10-16]**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

**EP 2 634 231 B1**

(52) Cooperative Patent Classification (CPC): (Cont.)

**C09K 5/048; C09K 21/08; H01B 3/56;**  
C08J 2203/14; C08J 2203/142; C09K 2205/12;  
C09K 2205/122; C09K 2205/126

C-Sets

**C07C 17/04, C07C 19/10;**  
**C07C 17/087, C07C 19/10;**  
**C07C 17/204, C07C 19/10;**  
**C07C 17/206, C07C 21/18;**  
**C07C 17/25, C07C 21/18**

**Description****BACKGROUND**

5 1. Field of the Invention.

[0001] The present disclosure relates to the field of compositions which may be useful as heat transfer compositions, aerosol propellants, foaming agents, blowing agents, solvents, cleaning agents, carrier fluids, displacement drying agents, buffing abrasion agents, polymerization media, expansion agents for polyolefins and polyurethane, gaseous dielectrics, extinguishing agents, and fire suppression agents in liquid or gaseous form. In particular, the present disclosure relates to compositions which may be useful as heat transfer compositions.

2. Description of Related Art.

15 [0002] New environmental regulations have led to the need for new compositions for use in refrigeration, air-conditioning and heat pump apparatus. Low global warming potential compounds are of particular interest.

**SUMMARY OF THE INVENTION**

20 [0003] Applicants have found that in preparing such new low global warming potential compounds, such as 1234yf, that certain additional compounds are present in small amounts.

[0004] Therefore, in accordance with the present invention, there is provided a composition comprising HFO-1234yf and at least one additional compound selected from the group consisting of HCFC-253fb, HCFC-234ab, HCFC-243fa, HCO-1130a, HCFC-1131, and HCFO-1242zf. The composition can contain less than about 1 weight percent of the at least one additional compound.

[0005] Compositions comprising HCFC-243db, HCFO-1233xf, and/or HCFC-244db are useful in processes to make HFO-1234yf. Therefore, compositions comprising 1234yf may contain some amount of HCFC-243db, HCFO-1233xf, and/or HCFC-244db, in addition to other compounds.

**BRIEF DESCRIPTION OF THE DRAWINGS**

[0006] FIG. 1 is a schematic drawing showing a reaction for producing HFO-1234yf from 243db.

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

35 [0007] HFO-1234yf has been suggested for use as a refrigerant, heat transfer fluid, aerosol propellant, foam expansion agent, among other uses. It has also, advantageously, been found that HFO-1234yf has a low global warming potential (GWP) as reported by V.C. Papadimitriou, et al. in Physical Chemistry Chemical Physics, 2007, volume 9, pages 1-13. Thus, HFO-1234yf is a good candidate for replacing the higher GWP saturated HFC refrigerants.

40 [0008] The present invention provides a composition comprising HFO-1234yf and at least one additional compound selected from the group consisting of HCFC-253fb, HCFC-234ab, HCFC-243fa, HCO-1130a, HCFC-1131, and HCFO-1242zf.

[0009] In one embodiment, the total amount of additional compound(s) in the composition comprising HFO-1234yf ranges from greater than zero weight percent to less than 1 weight percent.

45 [0010] The impurities present in the HCFC-243db, HCFO-1233xf, and HCFC-244bb can remain intact during the reaction to make HFO-1234yf.

[0011] The compositions disclosed herein comprising HFO-1234yf are useful as low global warming potential (GWP) heat transfer compositions, aerosol propellant, foaming agents, blowing agents, solvents, cleaning agents, carrier fluids, displacement drying agents, buffing abrasion agents, polymerization media, expansion agents for polyolefins and polyurethane, gaseous dielectrics, extinguishing agents, and fire suppression agents in liquid or gaseous form. The disclosed compositions can act as a working fluid used to carry heat from a heat source to a heat sink. Such heat transfer compositions may also be useful as a refrigerant in a cycle wherein the fluid undergoes a phase change; that is, from a liquid to a gas and back or vice versa.

50 [0012] Examples of heat transfer systems include but are not limited to air conditioners, freezers, refrigerators, heat pumps, water chillers, flooded evaporator chillers, direct expansion chillers, walk-in coolers, heat pumps, mobile refrigerators, mobile air conditioning units and combinations thereof.

55 [0013] As used herein, mobile refrigeration apparatus, mobile air conditioning or mobile heating apparatus refers to any refrigeration, air conditioner, or heating apparatus incorporated into a transportation unit for the road, rail, sea or

## EP 2 634 231 B1

air. In addition, mobile refrigeration or air conditioner units, include those apparatus that are independent of any moving carrier and are known as "intermodal" systems. Such intermodal systems include "containers" (combined sea/land transport) as well as "swap bodies" (combined road/rail transport).

**[0014]** As used herein, stationary heat transfer systems are systems associated within or attached to buildings of any variety. These stationary applications may be stationary air conditioning and heat pumps (including but not limited to chillers, high temperature heat pumps, residential, commercial or industrial air conditioning systems, and including window, ductless, ducted, packaged terminal, chillers, and those exterior but connected to the building such as rooftop systems). In stationary refrigeration applications, the disclosed compositions may be useful in equipment including commercial, industrial or residential refrigerators and freezers, ice machines, self-contained coolers and freezers, flooded evaporator chillers, direct expansion chillers, walk-in and reach-in coolers and freezers, and combination systems. In some embodiments, the disclosed compositions may be used in supermarket refrigerator systems.

**[0015]** The compounds making up the disclosed compositions are defined in Table 1.

TABLE 1

Code	Structure	Chemical name
	$\text{CH}_2=\text{CH}_2$	Ethylene
CFC-13	$\text{CF}_3\text{Cl}$	chlorotrifluoromethane
HFC-23	$\text{CHF}_3$	trifluoromethane
HCFC-133a	$\text{CF}_3\text{CH}_2\text{Cl}$	2-chloro-1,1,1-trifluoroethane
HFO-134	$\text{CHF}_2\text{CHF}_2$	1,1,2,2-tetrafluoroethane
HFO-134a	$\text{CF}_3\text{CH}_2\text{F}$	1,1,1,2-tetrafluoroethane
HFC-143a	$\text{CF}_3\text{CH}_3$	1,1,1-trifluoroethane
HFC-152a	$\text{CHF}_2\text{CH}_3$	1,1-difluoroethane
HFC-227ca	$\text{CF}_3\text{CF}_2\text{CHF}_2$	1,1,1,2,2,3,3-heptafluoropropane
HCFC-233ab	$\text{CF}_3\text{CCl}_2\text{CH}_2\text{Cl}$	1,2,2-trichloro-3,3,3-trifluoropropane
HCFC-234ab	$\text{CF}_3\text{CCl}_2\text{CH}_2\text{F}$	2,2-dichloro-1,1,1,3-tetrafluoropropane
HFC-236fa	$\text{CF}_3\text{CH}_2\text{CF}_3$	1,1,1,3,3,3-hexafluoropropane
HCFC-243fa	$\text{CF}_3\text{CH}_2\text{CHCl}_2$	3,3-dichloro-1,1,1-trifluoropropane
HCFC-243db	$\text{CF}_3\text{CHClCH}_2\text{Cl}$	2,3-dichloro-1,1,1-trifluoropropane
HCFC-244bb	$\text{CF}_3\text{CFCICH}_3$	2-chloro-1,1,1,2-tetrafluoropropane
HCFC-244db	$\text{CF}_3\text{CHClCH}_2\text{F}$	2-chloro-1,1,1,3-tetrafluoropropane
HFC-245fa	$\text{CF}_3\text{CH}_2\text{CHF}_2$	1,1,1,3,3-pentafluoropropane
HFC-245cb	$\text{CF}_3\text{CF}_2\text{CH}_3$	1,1,1,2,2-pentafluoropropane
HFC-245eb	$\text{CF}_3\text{CHFCH}_2\text{F}$	1,1,1,2,3-pentafluoropropane
HCFC-253fb	$\text{CF}_3\text{CH}_2\text{CH}_2\text{Cl}$	3-chloro-1,1,1-trifluoropropane
HFC-254fb	$\text{CF}_3\text{CH}_2\text{CH}_2\text{F}$	1,1,1,3-tetrafluoropropane
HCO-1130	$\text{CHCl}=\text{CHCl}$	E- and/or Z-1,2-dichloroethene
HCO-1130a	$\text{CCl}_2=\text{CH}_2$	1,1-dichloroethene
HCFC-1131	$\text{CHF}=\text{CHCl}$	E- and/or Z-1-chloro-2-fluoroethene
HFO-1141	$\text{CHF}=\text{CH}_2$	fluoroethene
HCFO-1223xd	$\text{CF}_3\text{CCl}=\text{CHCl}$	1,2-difluoro-3,3,3-trifluoropropene
HCFO-1233zd	$\text{CF}_3\text{CH}=\text{CHCl}$	E- and/or Z-1-chloro-3,3,3-trifluoropropene
HCFO-1233xf	$\text{CF}_3\text{CCl}=\text{CH}_2$	2-chloro-1,1,1-trifluoropropene
HFO-1234yf	$\text{CF}_3\text{CF}=\text{CH}_2$	2,3,3,3-tetrafluoropropene

(continued)

Code	Structure	Chemical name
HFO-1234ze	$\text{CF}_3\text{CH}=\text{CHF}$	E- and/or Z-1,3,3,3-tetrafluoropropene
HCFO-1242zf	$\text{CClF}_2\text{CH}=\text{CH}_2$	3-chloro-3,3-difluoropropene
HFO-1243zf	$\text{CF}_3\text{CH}=\text{CH}_2$	1,1,1-trifluoropropene (TFP)
HFO-1336	$\text{C}_4\text{H}_2\text{F}_6$	E- and/or Z-hexafluorobutene

**[0016]** HCFC-243db, HCFO-1233xf, and HCFC-244bb are available from specialty chemical manufacturers, including SynQuest Laboratories, Inc. (Alachua, FL, U.S.A.) or may be made as described herein. For instance, HCFC-243db, HCFO-1233xf, and HCFC-244bb may be prepared by non-catalytic chlorination of HFO-1243zf, as described in International Patent Application Publication No. WO2008/054782, published May 8, 2008. Also, HCFO-1233xf and HCFC-244bb may be prepared by catalytic fluorination of 243db as described in International Patent Application Publication No. WO2008/054781, published May 8, 2008. The additional compounds present in each disclosed composition will depend upon the method of manufacture.

**[0017]** In some embodiments, certain precursor compounds to HCFC-243db, HCFO-1233xf, or HCFC-244bb contain impurities that then may appear as additional compounds in the described compositions. In other embodiments, these precursor compounds may themselves react during the 243db formation to form additional compounds that then appear in the HCFC-243db compositions. In other embodiments, the reaction conditions under which the HCFC-243db, HCFO-1233xf, or HCFC-244bb are produced also produce by-products, by which is meant adventitious reaction pathways may occur simultaneously to produce compounds other than HCFC-243db, HCFO-1233xf or HCFC-244bb and the quantity and identity of these additional compounds will depend upon the particular conditions under which the HCFC-243db, HCFO-1233xf or HCFC-244bb are produced.

**[0018]** HFO-1234yf may be produced in a single step from HCFC-243db or the reaction sequence may be carried out in a step-wise manner. HCFO-1233xf may be produced from HCFC-243db and then HCFO-1233xf may be converted directly to HFO-1234yf. HCFC-244bb may be produced from HCFC-243db and then the HCFC-244bb may be converted to HFO-1234yf.

#### Fluorochlorination of HFO-1243zf

**[0019]** HFO-1243zf may be used to make HCFC-243db, HCFO-1233xf, HCFC-244db, and/or HFO-1234yf by fluorochlorination. HFO-1243zf is commercially available from E.I. DuPont de Nemours and Company (Wilmington, DE, USA).

**[0020]** The fluorochlorination reaction may be carried out in the liquid or vapor phase. For liquid phase reactions, the reaction of HFO-1243zf with HF and  $\text{Cl}_2$  may be conducted in a liquid-phase reactor operating in batch, semi-batch, semi-continuous, or continuous modes. In the batch mode, HFO-1243zf,  $\text{Cl}_2$ , and HF are combined in an autoclave or other suitable reaction vessel and heated to the desired temperature.

**[0021]** This reaction can be carried out in semi-batch mode by feeding  $\text{Cl}_2$  to a liquid-phase reactor containing HF and HFO-1243zf or by feeding HFO-1243zf and  $\text{Cl}_2$  to a liquid-phase reactor containing HF, or by feeding  $\text{Cl}_2$  to a mixture containing HF and reaction products formed by initially heating HFO-1243zf and HF. HF and  $\text{Cl}_2$  may be fed to a liquid-phase reactor containing a mixture of HFO-1243zf and reaction products formed by reacting HF,  $\text{Cl}_2$ , and HFO-1243zf. In the liquid-phase process, HF,  $\text{Cl}_2$ , and HFO-1243zf may be fed concurrently in the desired stoichiometric ratio to the reactor containing a mixture of HF and reaction products formed by reacting HF,  $\text{Cl}_2$ , and HFO-1243zf.

**[0022]** Suitable temperatures for the reaction of HF and  $\text{Cl}_2$  with HFO-1243zf in the liquid-phase reactor are from about 80°C to about 180°C or from about 100°C to about 150°C. Higher temperatures typically result in greater conversion of the HFO-1243zf.

**[0023]** A suitable molar ratio of HF to total amount of HFO-1243zf fed to the liquid-phase reactor is at least stoichiometric or from about 5:1 to about 100:1. The molar ratio of HF to HFO-1243zf may be from about 8:1 to about 50:1. A suitable molar ratio of  $\text{Cl}_2$  to total amount of HFO-1243zf fed to the liquid-phase reactor is from about 1:1 to about 2:1.

**[0024]** The reactor pressure in the liquid-phase process is not critical and in batch reactions is usually the autogenous pressure of the system at the reaction temperature. The pressure of the system increases as hydrogen chloride is formed by replacement of hydrogen substituents by chlorine, and by replacement of chlorine substituents by fluorine in the starting materials and intermediate reaction products. In a continuous process it is possible to set the pressure of the reactor in such a way that the lower boiling products of the reaction, such as HCl, HFO-1234yf ( $\text{CF}_3\text{CF}=\text{CH}_2$ ), E/Z-1234ze (E/Z- $\text{CF}_3\text{CH}=\text{CHF}$ ), and HFC-245cb ( $\text{CF}_3\text{CF}_2\text{CH}_3$ ), are vented from the reactor, optionally through a packed column or condenser. In this manner, higher boiling intermediates remain in the reactor and the volatile products are removed. Typical reactor pressures are from about 20 psig (239 kPa) to about 1,000 psig (6,994 kPa).

**[0025]** When the reaction is conducted using a liquid-phase process, catalysts which may be used include carbon,  $\text{AlF}_3$ ,  $\text{BF}_3$ ,  $\text{FeCl}_{3-a}\text{F}_a$  (where  $a = 0$  to  $3$ ),  $\text{FeX}_3$  supported on carbon,  $\text{SbCl}_{3-a}\text{F}_a$ ,  $\text{AsF}_3$ ,  $\text{MCl}_{5-b}\text{F}_b$  (where  $b = 0$  to  $5$  and  $M = \text{Sb}, \text{Nb}, \text{Ta},$  or  $\text{Mo}$ ), and  $\text{M}'\text{Cl}_{4-c}\text{F}_c$  (where  $c = 0$  to  $4$ , and  $M' = \text{Sn}, \text{Ti}, \text{Zr},$  or  $\text{Hf}$ ). Catalysts for the liquid phase process may also be  $\text{MCl}_{5-b}\text{F}_b$  (where  $b = 0$  to  $5$  and  $M = \text{Sb}, \text{Nb},$  or  $\text{Ta}$ ).

**[0026]** The reaction of HF and  $\text{Cl}_2$  with HFO-1243zf may also be carried out in the vapor phase. Typically a heated reactor is used. A number of reactor configurations are possible including horizontal or vertical orientation of the reactor as well as the sequence of reaction of the HFO-1243zf with HF and  $\text{Cl}_2$ . The HFO-1243zf may be initially vaporized and fed to the reactor as a gas.

**[0027]** HFO-1243zf may be contacted with HF, optionally in the presence of  $\text{Cl}_2$ , in a pre-reactor prior to reaction in the vapor-phase reactor. The pre-reactor may be empty or be filled with a suitable packing such as nickel-copper alloys commercially available from Special Metals Corp. (New Hartford, New York) under the trademark Monel<sup>®</sup>, (hereinafter "Monel<sup>®m</sup>") nickel-based alloys commercially available from Haynes International (Kokomo, Indiana) under the trademark Hastelloy<sup>®</sup>, (hereinafter "Hastelloy<sup>®m</sup>") or other nickel alloy turnings or wool, or other material inert to HCl and HF which allows efficient mixing of HFO-1243zf and HF vapor.

**[0028]** Suitable temperatures for the pre-reactor are from about  $80^\circ\text{C}$  to about  $250^\circ\text{C}$  or from about  $100^\circ\text{C}$  to about  $200^\circ\text{C}$ . Temperatures greater than about  $100^\circ\text{C}$  result in some conversion of the HFO-1243zf to compounds having a higher degree of fluorination. Higher temperatures result in greater conversion of the HFO-1243zf entering the reactor and a greater degree of fluorination in the converted compounds. Under these conditions, for example, a mixture of HF,  $\text{Cl}_2$ , and HFO-1243zf is converted to a mixture containing predominantly HCFC-243db and HCFC-244db ( $\text{CF}_3\text{CHClCH}_2\text{F}$ ).

**[0029]** The degree of fluorination reflects the number of fluorine substituents that replace chlorine substituents in the HFO-1243zf and their chlorinated products. For example, HCFC-253fb represents a higher degree of fluorination than HCC-250fb and HFO-1243zf represents a higher degree of fluorination than HCO-1240zf.

**[0030]** The molar ratio of HF to the total amount of HFO-1243zf in the pre-reactor can be from about the stoichiometric ratio of HF to the total amount of HFO-1243zf to about 50:1 or from about twice the stoichiometric ratio of HF to the total amount of HFO-1243zf to about 30:1. The molar ratio of HF to the total amount of HFO-1243zf can be present in the pre-reactor, and no additional amount of HF may be added to the vapor-phase reaction zone.

**[0031]** The HFO-1243zf may be contacted with  $\text{Cl}_2$  in a pre-reactor, optionally in the presence of HF, prior to reaction in the vapor-phase reactor.

**[0032]** Suitable temperatures for the pre-reactor can be from about  $80^\circ\text{C}$  to about  $250^\circ\text{C}$ , preferably from about  $100^\circ\text{C}$  to about  $200^\circ\text{C}$ . Under these conditions, at least a portion of HFO-1243zf is converted to HCFC-243db. Higher temperatures typically result in a higher degree of halogenation of the HFO-1243zf.

**[0033]** The degree of halogenation reflects the total number of halogen substituents (chlorine plus fluorine) in a halopropane and/or halopropene product. For example, HFO-1234yf has a higher degree of halogenation (i.e., 4) than does HFO-1243zf (i.e., 3).

**[0034]** The molar ratio of  $\text{Cl}_2$  to the total amount of HFO-1243zf can be from about 0.5:1 to about 2:1 or from about 1.1:1 to about 1:1.

**[0035]** The HFO-1243zf can be vaporized, optionally in the presence of HF, and fed to a pre-reactor or to a vapor-phase reactor along with HF and  $\text{Cl}_2$ .

**[0036]** Suitable temperatures for the vapor-phase reaction are from about  $120^\circ\text{C}$  to about  $500^\circ\text{C}$ . Temperatures of from about  $250^\circ\text{C}$  to about  $350^\circ\text{C}$  favor the formation of HFO-1234yf and HFC-245cb. Temperatures of from about  $350^\circ\text{C}$  to about  $450^\circ\text{C}$  favor the formation of HFO-1234ze, HFC-245fa, and HCFO-1233zd. At temperatures of from about  $250^\circ\text{C}$  to about  $450^\circ\text{C}$ , some HCFO-1233xf is also produced. Higher temperatures result in greater conversion of HFO-1243zf and higher degrees of fluorination and halogenation in the converted compounds.

**[0037]** Suitable reactor pressures for the vapor-phase reactor may be from about 1 to about 30 atmospheres. A pressure of about 15 to about 25 atmospheres may be advantageously employed to facilitate separation of HCl from other reaction products, and the suitable reaction time may vary from about 1 to about 120 seconds, preferably from about 5 to about 60 seconds.

**[0038]** The molar ratio of HF to the total amount of HFO-1243zf for the vapor-phase reaction can be from about the stoichiometric ratio of HF to the total amount of HFO-1243zf to about 50:1 or from about 10:1 to about 30:1.

**[0039]** A catalyst can be used in the reaction zone for the vapor-phase reaction of HF and  $\text{Cl}_2$  with HFO-1243zf. Chlorofluorination catalysts which may be used in the vapor phase reaction include carbon; graphite; alumina; fluorided alumina; aluminum fluoride; alumina supported on carbon; aluminum fluoride supported on carbon; fluorided alumina supported on carbon; magnesium fluoride supported on aluminum fluoride; metals (including elemental metals, metal oxides, metal halides, and/or other metal salts); metals supported on aluminum fluoride; metals supported on fluorided alumina; metals supported on alumina; and metals supported on carbon; mixtures of metals.

**[0040]** Suitable metals for use as catalysts (optionally supported on alumina, aluminum fluoride, fluorided alumina, or carbon) include chromium, iron, cobalt, nickel, ruthenium, rhodium, palladium, osmium, iridium, platinum, manganese,

rhodium, scandium, yttrium, lanthanum, titanium, zirconium, and hafnium, copper, silver, gold, zinc, and/or metals having an atomic number of 58 through 71 (i.e., the lanthanide metals). When used on a support, the total metal content of the catalyst can be from about 0.1 to about 20 percent by weight based on the total weight of the catalyst or from about 0.1 to about 10 percent by weight based on the total weight of the catalyst.

**[0041]** Suitable chlorofluorination catalysts for the vapor-phase reactions include chromium-containing catalysts including chromium(III) oxide ( $\text{Cr}_2\text{O}_3$ );  $\text{Cr}_2\text{O}_3$  with other metals such as magnesium halides or zinc halides supported on  $\text{Cr}_2\text{O}_3$ ; chromium(III) halides supported on carbon; mixtures of chromium and magnesium (including elemental metals, metal oxides, metal halides, and/or other metal salts) optionally supported on graphite; and mixtures of chromium and other metals (including elemental metals, metal oxides, metal halides, and/or other metal salts) optionally supported on graphite, alumina, or aluminum halides such as aluminum fluoride.

**[0042]** Chromium-containing catalysts are well known in the art. They may be prepared by either precipitation methods or impregnation methods as generally described by Satterfield on pages 87-112 in *Heterogeneous Catalysis in Industrial Practice*, 2nd edition (McGraw-Hill, New York, 1991).

**[0043]** Of note are chlorofluorination catalysts that comprise at least one chromium-containing component selected from the group consisting of crystalline alpha-chromium oxide where from about 0.05 atom % to about 6 atom % of the chromium atoms in the alpha-chromium oxide lattice are replaced by trivalent cobalt atoms, and crystalline alpha-chromium oxide where from about 0.05 atom % to about 6 atom % of the chromium atoms in the alpha-chromium oxide lattice are replaced by trivalent cobalt atoms which has been treated with a fluorinating agent. These catalysts, including their preparation, have been disclosed in U. S. Patent Application Publication US2005/0228202.

**[0044]** Optionally, the metal-containing catalysts described above can be pretreated with HF. This pretreatment can be accomplished, for example, by placing the metal-containing catalyst in a suitable container, and thereafter, passing HF over the metal-containing catalyst. Such container can be the reactor used to perform the chlorofluorination reaction. The pretreatment time can be from about 15 to about 300 minutes, and the pretreatment temperature can be from about 200°C to about 450°C.

**[0045]** Halopropane by-products that may be formed in the chlorofluorination reactions having higher degrees of halogenation and/or fluorination than pentafluoropropanes include  $\text{CF}_3\text{CCl}_2\text{CF}_3$  (CFC-216aa),  $\text{CF}_3\text{CClCF}_2\text{CF}_2$  (CFC-216ba),  $\text{CF}_3\text{CClCF}_2\text{CF}_3$  (CFC-217ba),  $\text{CF}_3\text{CF}_2\text{CClCF}_2$  (CFC-217ca),  $\text{CF}_3\text{CHF}_2\text{CF}_3$  (HFC-227ea),  $\text{CF}_3\text{CF}_2\text{CHF}_2$  (HFC-227ca),  $\text{CF}_3\text{CClCF}_2\text{CF}_2$  (HCFC-226ba),  $\text{CF}_3\text{CF}_2\text{CHClCF}_2$  (HCFC-226ca),  $\text{CF}_3\text{CHClCF}_2\text{CF}_3$  (HCFC-226da),  $\text{CF}_3\text{CCl}_2\text{CHF}_2$  (HCFC-225aa),  $\text{CF}_3\text{CClCF}_2\text{CHClCF}_2$  (HCFC-225ba),  $\text{CF}_3\text{CF}_2\text{CHCl}_2$  (HCFC-225ca),  $\text{CF}_3\text{CCl}_2\text{CClCF}_2$  (CFC-215aa),  $\text{CF}_3\text{CClCF}_2\text{CF}_2$  (CFC-215bb),  $\text{CF}_3\text{CCl}_2\text{CCl}_2\text{F}$  (HCFC-214ab),  $\text{CF}_3\text{CCl}_2\text{CHClCF}_2$  (HCFC-224aa), and  $\text{CF}_3\text{CClCF}_2\text{CHCl}_2$  (HCFC-224ba).

**[0046]** Halopropene by-products that may be formed in the chlorofluorination reactions having a higher degree of halogenation than tetrafluoropropenes include  $\text{CF}_3\text{CCl}=\text{CHCl}$  (HCFO-1223xd).

**[0047]** In cases where the product mixture produced by the processes described herein comprises (i) product compounds HFC-245cb, HFC-245fa, HFO-1234yf, HFO-1234ze, HCFO-1233zd and HCFO-1233xf, (ii) HF, HCl, and  $\text{Cl}_2$ , (iii) higher boiling by-products such as  $\text{CF}_3\text{CHClCH}_2\text{Cl}$  (HCFC-243db),  $\text{CF}_3\text{CHClCH}_2\text{F}$  (HCFC-244bb) and (iv) chlorinated by-products such as  $\text{C}_3\text{HCl}_3\text{F}_4$ ,  $\text{C}_3\text{HCl}_2\text{F}_3$ ,  $\text{C}_3\text{HClF}_6$ ,  $\text{C}_3\text{Cl}_3\text{F}_5$ , and  $\text{C}_3\text{Cl}_2\text{F}_6$ , the separation processes, such as distillation, may be employed to recover the product compounds from such a product mixture.

#### 40 Fluorination of HCFC-243db

**[0048]** HCFC-243db may be used to make HCFC-HCFO-1233xf, HCFC-244db, and/or HFO-1234yf by fluorination. These reactions are shown in FIG. 1. The fluorination reaction may be carried out in the liquid or vapor phase. For liquid phase reactions described herein, the reaction of HCFC-243db with HF may be conducted in a liquid-phase reactor operating in batch, semi-batch, semi-continuous, or continuous modes. In the batch mode, starting HCFC-243db and HF are combined in an autoclave or other suitable reaction vessel and heated to the desired temperature.

**[0049]** This reaction can be carried out in semi-batch mode by feeding HF to a liquid-phase reactor containing HCFC-243db or by feeding HCFC-243db to a liquid-phase reactor containing HF, or by feeding HF to a mixture containing HF and reaction products formed by initially heating HCFC-243db and HF. Alternatively, HF may be fed to a liquid-phase reactor containing a mixture of HCFC-243db and reaction products formed by the reaction of HF, and HCFC-243db. In another alternative of the liquid-phase process, HF, and HCFC-243db may be fed concurrently in the desired stoichiometric ratio to the reactor containing a mixture of HF and reaction products formed by reacting HF, and HCFC-243db.

**[0050]** Suitable temperatures for the reaction of HF with HCFC-243db in the liquid-phase reactor can be from about 80°C to about 180°C or from about 100°C to about 150°C. Higher temperatures typically result in greater conversion of the HCFC-243db.

**[0051]** A suitable molar ratio of HF to HCFC-243db fed to the liquid-phase reactor can be at least stoichiometric or from about 5:1 to about 100:1. The molar ratio of HF to HCFC-243db can also from about 8:1 to about 50:1.

**[0052]** The reactor pressure in the liquid-phase process is not critical and in batch reactions is usually the autogenous

pressure of the system at the reaction temperature. The pressure of the system increases as hydrogen chloride is formed by replacement of chlorine substituents by fluorine in the HCFC-243db and intermediate reaction products. In a continuous process it is possible to set the pressure of the reactor in such a way that the lower boiling products of the reaction, such as HCl,  $\text{CF}_3\text{CF}=\text{CH}_2$ , and *E/Z*- $\text{CF}_3\text{CH}=\text{CHF}$ , are vented from the reactor, optionally through a packed column or condenser. In this manner, higher boiling intermediates remain in the reactor and the volatile products are removed. Typical reactor pressures are from about 20 psig (239 kPa) to about 1,000 psig (6,994 kPa).

**[0053]** When the reaction is conducted using a liquid-phase process, catalysts which may be used include carbon,  $\text{AlF}_3$ ,  $\text{BF}_3$ ,  $\text{FeCl}_{3-a}\text{F}_a$  (where  $a = 0$  to 3),  $\text{FeX}_3$  supported on carbon,  $\text{SbCl}_{3-a}\text{F}_a$ ,  $\text{AsF}_3$ ,  $\text{MCl}_{5-b}\text{F}_b$  (where  $b = 0$  to 5 and  $M = \text{Sb, Nb, Ta, or Mo}$ ), and  $\text{M}'\text{Cl}_{4-c}\text{F}_c$  (where  $c = 0$  to 4, and  $M' = \text{Sn, Ti, Zr, or Hf}$ ). Catalysts for the liquid phase process can be  $\text{MCl}_{5-b}\text{F}_b$  (where  $b = 0$  to 5 and  $M = \text{Sb, Nb, or Ta}$ ).

**[0054]** The reaction of HF with HCFC-243db can be carried out in the vapor phase. Typically a heated reactor is used. A number of reactor configurations are possible including horizontal or vertical orientation of the reactor as well as the sequence of reaction of the starting materials with HF. The HCFC-243db may be initially vaporized and fed to the reactor as a gas.

**[0055]** Alternatively, the HCFC-243db may be contacted with HF in a pre-reactor prior to reaction in the vapor-phase reactor. The pre-reactor may be empty, but is preferably filled with a suitable packing such as nickel-copper alloys commercially available from Special Metals Corp. (New Hartford, New York) under the trademark Monel<sup>®</sup>, nickel-based alloys such as Hastelloy<sup>®</sup>, or other nickel alloy turnings or wool, or other material inert to HCl and HF which allows efficient mixing of HCFC-243db and HF vapor.

**[0056]** Suitable temperatures for the pre-reactor may be from about 80°C to about 250°C or from about 100°C to about 200°C. Temperatures greater than about 100°C result in some conversion of the HCFC-243db to compounds having a higher degree of fluorination. Higher temperatures result in greater conversion of the HCFC-243db entering the reactor and a greater degree of fluorination in the converted compounds. Under these conditions, for example, a mixture of HF and HCFC-243db is converted to a mixture containing predominantly HF, HCl, HCFC-243db, HCFC-244db ( $\text{CF}_3\text{CHClCH}_2\text{F}$ ), and HCFO-1233xf.

**[0057]** The degree of fluorination reflects the number of fluorine substituents that replace chlorine substituents in the HCFC-243db and their fluorinated products. For example, HFO-1234yf represents a higher degree of fluorination than HCFO-1233xf.

**[0058]** The molar ratio of HF to the total amount of HCFC-243db in the pre-reactor can be from about the stoichiometric ratio of HF to the total amount of HCFC-243db to about 50:1 or from about twice the stoichiometric ratio of HF to the total amount of HCFC-243db to about 30:1. Alternatively, the molar ratio of HF to the amount of HCFC-243db can be present in the pre-reactor, and no additional amount of HF may be added to the vapor-phase reaction zone.

**[0059]** The HCFC-243db and HF can be vaporized and fed to a pre-reactor or to a vapor-phase reactor.

**[0060]** Suitable temperatures for the vapor-phase reaction are from about 120°C to about 500°C. Temperatures in the range of from about 300°C to about 350°C favor the formation of HFO-1234yf and HFC-245cb and HCFO-1233xf. Temperatures in the range of from about 350°C to about 450°C favor the additional formation of HFO-1234ze, HFC-245fa, and HCFO-1233zd. Higher temperatures result in greater conversion of HCFC-243db and greater degrees of fluorination in the converted products. Reactor temperatures of from about 150°C to about 275°C favor the formation of HCFO-1233xf as the major product.

**[0061]** Suitable reactor pressures for the vapor-phase reactor may be from about 1 to about 30 atmospheres. A pressure of about 15 to about 25 atmospheres may be advantageously employed to facilitate separation of HCl from other reaction products, and the suitable reaction time may vary from about 1 to about 120 seconds, preferably from about 5 to about 60 seconds.

**[0062]** The molar ratio of HF to the amount of HCFC-243db for the vapor-phase reaction can be from about the stoichiometric ratio of HF to the amount of HCFC-243db to about 50:1 or from about 10:1 to about 30:1.

**[0063]** A catalyst can be used in the reaction zone for the vapor-phase reaction of HF with HCFC-243db. Fluorination catalysts which may be used in the vapor phase reaction include carbon; graphite; alumina; fluorided alumina; aluminum fluoride; alumina supported on carbon; aluminum fluoride supported on carbon; fluorided alumina supported on carbon; magnesium fluoride supported on aluminum fluoride; metals (including elemental metals, metal oxides, metal halides, and/or other metal salts); metals supported on aluminum fluoride; metals supported on fluorided alumina; metals supported on alumina; and metals supported on carbon; mixtures of metals.

**[0064]** Suitable metals for use as catalysts (optionally supported on alumina, aluminum fluoride, fluorided alumina, or carbon) include chromium, iron, cobalt, nickel, ruthenium, rhodium, palladium, osmium, iridium, platinum, manganese, rhenium, scandium, yttrium, lanthanum, titanium, zirconium, and hafnium, copper, silver, gold, zinc, and/or metals having an atomic number of 58 through 71 (i.e., the lanthanide metals). When used on a support, the total metal content of the catalyst can be from about 0.1 to about 20 percent by weight based on the total weight of the catalyst or from about 0.1 to about 10 percent by weight based on the total weight of the catalyst.

**[0065]** Typical fluorination catalysts for the vapor-phase reactions described herein include chromium-containing cat-

alysts including chromium(III) oxide ( $\text{Cr}_2\text{O}_3$ );  $\text{Cr}_2\text{O}_3$  with other metals such as magnesium halides or zinc halides supported on  $\text{Cr}_2\text{O}_3$ ; chromium(III) halides supported on carbon; mixtures of chromium and magnesium (including elemental metals, metal oxides, metal halides, and/or other metal salts) optionally supported on graphite; and mixtures of chromium and other metals (including elemental metals, metal oxides, metal halides, and/or other metal salts) optionally supported on graphite, alumina, or aluminum halides such as aluminum fluoride.

**[0066]** Chromium-containing catalysts are well known in the art. They may be prepared by either precipitation methods or impregnation methods as generally described by Satterfield on pages 87-112 in Heterogeneous Catalysis in Industrial Practice, 2nd edition (McGraw-Hill, New York, 1991).

**[0067]** Of note are fluorination catalysts that comprise at least one chromium-containing component selected from the group consisting of crystalline alpha-chromium oxide where from about 0.05 atom % to about 6 atom % of the chromium atoms in the alpha-chromium oxide lattice are replaced by trivalent cobalt atoms, and crystalline alpha-chromium oxide where from about 0.05 atom % to about 6 atom % of the chromium atoms in the alpha-chromium oxide lattice are replaced by trivalent cobalt atoms which has been treated with a fluorinating agent. These catalysts, including their preparation, have been disclosed in U. S. Patent Application Publication US2005/0228202.

**[0068]** Optionally, the metal-containing catalysts described above can be pretreated with HF. This pretreatment can be accomplished, for example, by placing the metal-containing catalyst in a suitable container, and thereafter, passing HF over the metal-containing catalyst. Such container can be the reactor used to perform the fluorination reaction described herein. Typically, the pretreatment time is from about 15 to about 300 minutes, and the pretreatment temperature is from about 200°C to about 450°C.

**[0069]** The product mixture may comprise HFC-245cb, HFC-245fa, HFO-1234yf, HFO-1234ze, HCFO-1233zd and HCFO-1233xf.

#### Fluorination of HCFO-1233xf

**[0070]** HCFO-1233xf may be used to make HCFC-HCFC-244bb, and/or HFO-1234yf by fluorination. These reactions are shown in FIG. 1.

**[0071]** The reaction of HCFO-1233xf to HCFC-244bb may be carried out in the liquid phase or in the vapor phase.

**[0072]** The reaction of HCFO-1233xf to HCFC-244bb may be carried out in batch mode or in a continuous mode.

**[0073]** A liquid phase reaction of HCFO-1233xf to HCFC-244bb may be carried out in the presence of a catalyst. The catalyst may be a Lewis acid catalyst. The catalyst may be a metal-halide catalyst. The catalyst may be at least one catalyst selected from the group consisting of antimony halides, tin halides, thallium halides, iron halides and combinations of two or more thereof. The catalysts may be at least one catalyst selected from antimony pentachloride ( $\text{SbCl}_5$ ), antimony trichloride ( $\text{SbCl}_3$ ), antimony pentafluoride ( $\text{SbF}_5$ ), tin tetrachloride ( $\text{SnCl}_4$ ), titanium tetrachloride ( $\text{TiCl}_4$ ), iron trichloride ( $\text{FeCl}_3$ ), and combinations thereof. The reaction may be carried out with any known fluorination catalyst for liquid phase reactions.

**[0074]** The reaction of HCFO-1233xf to HCFC-244bb may be carried out in the absence of catalyst.

**[0075]** A vapor phase reaction of HCFO-1233xf to HCFC-244bb may be carried out in the presence of a catalyst. The reaction can be carried out in the presence of a chromium-based catalyst, an iron-based catalyst, or combinations thereof. The chromium based catalyst can be a chromium oxide (e.g.  $\text{Cr}_2\text{O}_3$ ). The iron-based catalyst may be  $\text{FeCl}_3$  on carbon.

**[0076]** The vapor phase reaction of HCFO-1233xf to HCFC-244bb can be carried out in the absence of catalyst.

#### Dehydrochlorination of HCFC-244bb

**[0077]** Dehydrochlorination of HCFC-244bb can be used to prepare HFO-1234yf.

**[0078]** Dehydrochlorination of HCFC-244bb to HFO-1234yf can be carried out in the vapor phase.

**[0079]** Vapor phase dehydrochlorination can be carried out in the presence of catalyst. The catalyst can be selected from carbon and/or metal based catalysts. The catalyst may be selected from an activated carbon, a nickel-based catalyst, a palladium based catalyst, or any combination of these catalysts. The catalyst may be selected from the group consisting of Ni-mesh, palladium on carbon, palladium on aluminum oxide, or combinations thereof.

**[0080]** HFO-1234yf can be prepared by thermal dehydrochlorination of HCFC-244bb. This reaction may occur in the absence of a catalyst. HCFC-244bb can be introduced into a reaction vessel which temperature is maintained at a temperature high enough to effect the thermal dehydrochlorination of HCFC-244bb. The temperature can be high enough to effect the thermal dehydrochlorination of HCFC-244bb to a percent conversion of at least 50% or high enough to effect the thermal dehydrochlorination of HCFC-244bb to a percent conversion of at least 65% or high enough to effect the thermal dehydrochlorination of HCFC-244bb to a percent conversion of at least 80%. The temperature may be high enough to effect the thermal dehydrochlorination of HCFC-244bb to a percent conversion of at least 70% for at least 12 hours of continuous operation.

## EP 2 634 231 B1

[0081] HCFC-244bb can be introduced into a reaction vessel into a reaction vessel which temperature is maintained at a temperature in the range of from about 500 °C to about 700 °C or in the range from about 500 °C to about 650 °C. The temperature of the reaction vessel can be maintained at a temperature high enough to effect the pyrolysis of HCFC-244bb to HFO-1234yf with a selectivity of 80% or greater. The temperature of the reaction vessel can be maintained at a temperature high enough to effect the pyrolysis of HCFC-244bb to HFO-1234yf with a selectivity of 85% or greater.

[0082] The reaction zone can be a reaction vessel comprised of materials which are resistant to corrosion. These materials may comprise alloys, such as nickel-based alloys such as Hastelloy®, nickel-chromium alloys commercially available from Special Metals Corp. under the trademark Inconel® (hereinafter "Inconel™") or nickel-copper alloys commercially available from Special Metals Corp. (New Hartford, New York) under the trademark Monel®, or vessels having fluoropolymers linings.

[0083] The HCFC-244bb can be preheated in a vaporizer to a temperature of from about 30 °C to about 100 °C or preheated in a vaporizer to a temperature of from about 30 °C to about 80 °C.

[0084] An inert diluent gas can be used as a carrier gas for HCFC-244bb. The carrier gas can be selected from nitrogen, argon, helium or carbon dioxide.

### EXAMPLES

#### General Procedure for Product Analysis

[0085] The following general procedure is illustrative of the method used for analyzing the products of fluorination reactions. Part of the total reactor effluent was sampled on-line for organic product analysis using a gas chromatograph equipped with a mass selective detector (GC/MS). The gas chromatography utilized a 20 ft. (6.1 m) long x 1/8 in. (0.32 cm) diameter tube containing perfluorinated polyether sold under the trademark Krytox® by E. I. du Pont de Nemours and Company (hereinafter "DuPont") of Wilmington, Delaware on an inert carbon support. The helium flow was 30 mL/min ( $5.0 \times 10^{-7}$  m<sup>3</sup>/sec). Gas chromatographic conditions were 60°C for an initial hold period of three minutes followed by temperature programming to 200°C at a rate of 6°C/minute.

#### Preparation of 98%Chromium/2%Cobalt Catalyst

[0086] A solution of 784.30 grams Cr(NO<sub>3</sub>)<sub>3</sub>[9(H<sub>2</sub>O)] (1.96 moles) and 11.64 grams Co(NO<sub>3</sub>)<sub>2</sub>[6(H<sub>2</sub>O)] (0.040 mole) was prepared in 2000 mL of deionized water. The solution was treated dropwise with 950 mL of 7.4 M aqueous ammonia until the pH reached about 8.5. The slurry was stirred overnight at room temperature and then evaporated to dryness in air at 110-120°C. The dried catalyst was then calcined in air at 400°C for 24 hours prior to use.

### LEGEND

#### [0087]

243db is CF <sub>3</sub> CHClCH <sub>2</sub> Cl	244db is CF <sub>3</sub> CHClCH <sub>2</sub> F
245cb is CF <sub>3</sub> CF <sub>2</sub> CH <sub>3</sub>	245fa is CF <sub>3</sub> CH <sub>2</sub> CHF <sub>2</sub>
1234yf is CF <sub>3</sub> CF=CH <sub>2</sub>	1233xf is CF <sub>3</sub> CCl=CH <sub>2</sub>
1243zf is CH <sub>2</sub> =CHCF <sub>3</sub>	233ab is CF <sub>3</sub> CCl <sub>2</sub> CH <sub>2</sub> Cl
1233zd is E- and/or Z-CHCl=CHCF <sub>3</sub>	226ba is CF <sub>3</sub> CClFCHF <sub>2</sub>
1234ze is E- and/or Z-CHF=CHCF <sub>3</sub>	227ca is CF <sub>3</sub> CF <sub>2</sub> CHF <sub>2</sub>
1223xd is E- and/or Z-CF <sub>3</sub> CCl=CHCl	244bb is CF <sub>3</sub> CFCICH <sub>3</sub>
1141 is CHF=CH <sub>2</sub>	

### REFERENCE EXAMPLES 1-6

#### Chlorofluorination of HFO-1243zf

[0088] The 98% chromium/2% cobalt catalyst prepared above (21.4 grams, 15 mL, -12 to +20 mesh, (1.68 to 0.84 mm)) was placed in a 5/8" (1.58 cm) diameter Inconel® (Special Metals Corp. (New Hartford, New York)) nickel alloy reactor tube heated in a fluidized sand bath. The catalyst was pre-fluorinated by treatment with HF as follows. The catalyst was heated from 45°C to 175°C in a flow of nitrogen (50 cc/min) over the course of about 1.5 hours. HF was then admitted to the reactor at a flow rate of 50 cc/min for 1.3 hours at a temperature of 175°C. The reactor nitrogen

## EP 2 634 231 B1

flow was decreased to 20 cc/min and the HF flow increased to 80 cc/min; this flow was maintained for 0.3 hour. The reactor temperature was then gradually increased to 400°C over 1 hour. After this period, the HF and nitrogen flow was stopped and the reactor brought to the desired operating temperature. A flow of HF vapor, HFO-1243zf, and Cl<sub>2</sub> then started through the reactor. Part of the reactor effluent was analyzed by on line GC/MS.

**[0089]** The results of the chlorofluorination of HFO-1243zf over the 98/2 Cr/Co catalyst at various operating temperatures and indicated molar ratios of HF, HFO-1243zf and Cl<sub>2</sub> are shown in Table 2; analytical data is given in units of GC area %. The nominal catalyst bed volume was 15 cc; the contact time (CT) was 15 seconds. Examples 1 and 2 were carried out in the absence of the catalyst.

**TABLE 2 (Part A)**

Ex. No.	HF/1243/Cl <sub>2</sub> Ratio	T, °C	Chlorofluorination of HFO-1243zf						
			1243zf	243db	244db	1234yf	245cb	1233xf	
1*	10/1/4	140	3.0	54.2	9.8	5.7	0	1.4	
2a*	10/1/1	140	31.3	46.2	11.8	2.8	0	1.5	
3b*	10/1/1	300	5.9	0	0	5.9	22.2	30.7	
4c*	10/1/4	325	0	0	0	0	0	0	
5*	10/1/1	350	9.1	0	0	11.3	11.3	25.2	
6*	10/1/1	375	12.8	0	0	11.6	6.3	20.6	

**TABLE 2 (Part B)**

Chlorofluorination of HFO-1243zf

Ex. No.	HF/1243/Cl <sub>2</sub> Ratio	T, °C	1233zd	1234ze	245fa	1223xd	233ab	226ba	227ca
1*	10/1/4	140	7.7	-	-	1.0	6.3	0	0
2a*	10/1/1	140	1.4	-	-	0	1.3	0	0
3b*	10/1/1	300	4.1	2.1	1.3	20.2	0	0	0
4c*	10/1/4	325	0	0	0	0	0	23.8	13.9
5*	10/1/1	350	12.4	4.7	1.9	18.1	0	0.2	0
6*	10/1/1	375	17.6	6.5	2.3	16.1	0	0.2	0

a. 243db and 244db confirmed by <sup>1</sup>H and <sup>19</sup>F NMR.

b. 245cb and 1233xf confirmed by <sup>1</sup>H and <sup>19</sup>F NMR.

c. Additional products were 215aa, 216aa, 216ba, 225aa, 225ba, 226ca, 226da

\* Reference Example.

### REFERENCE EXAMPLES 7-11

#### Fluorination of HCFC-243db

**[0090]** The 98% chromium/2% cobalt catalyst prepared above (21.4 grams, 15 mL, -12 to +20 mesh, (1.68 to 0.84 mm)) was placed in a 5/8" (1.58 cm) diameter Inconel® nickel alloy reactor tube heated in a fluidized sand bath. The catalyst was pre-fluorinated by treatment with HF as follows. The catalyst was heated from 45°C to 175°C in a flow of nitrogen (50 cc/min) over the course of about 1.5 hours. HF was then admitted to the reactor at a flow rate of 50 cc/min for 1.3 hours at a temperature of 175°C. The reactor nitrogen flow was decreased to 20 cc/min and the HF flow increased to 80 cc/min; this flow was maintained for 0.3 hour. The reactor temperature was then gradually increased to 400°C over 1 hour. After this period, the HF and nitrogen flow was stopped and the reactor brought to the desired operating temperature. A flow of HF vapor and HCFC-243db (CF<sub>3</sub>CHClCH<sub>2</sub>Cl) was then started through the reactor. Part of the reactor effluent was analyzed by on line GC/MS.

**[0091]** The results of the fluorination of HFC-243db over the 98/2 Cr/Co catalyst at various operating temperatures and indicated molar ratios of HF and HCFC-243db are shown in Table 3; analytical data is given in units of GC area %. The nominal catalyst bed volume was 15 cc; the contact time (CT) was 15 seconds. Example 7 was carried out in the absence of the catalyst.

EP 2 634 231 B1

TABLE 3

Fluorination of HCFC-243db											
Ex. No.	HF/ 243 Ratio	Temp. (°C)	<u>1243 zf</u>	<u>243 db</u>	<u>244 db</u>	<u>1234 yf</u>	<u>245 cb</u>	<u>1233 xf</u>	<u>1233 zd</u>	<u>1234 ze</u>	<u>245 fa</u>
7*	5/1	140	0.1	88.4	7.4	0	0	3.9	0	0	0
8*	10/1	275	0	0.2	0.6	1.3	4.8	90.0	0	0.7	1.0
9*	20/1	325	0	0	0	19.1	11.4	61.7	2.3	3.1	1.9
10*	20/1	350	0	0	0	32.2	8.1	45.3	4.7	7.9	0.9
11*	20/1	400	0	0	0	17.9	6.6	36.3	19.7	14.4	3.6
* Reference Example											

REFERENCE EXAMPLE 12

Reaction of HFC-243db with HF in the presence of TaFs

**[0092]** A 210 mL Hastelloy® C tube was charged with 10.0 grams (0.0599 mole) of HCFC-243db and 25.4 grams (0.040 mole) of tantalum pentafluoride. The tube was then charged with 40.0 grams (2.0 moles) of hydrogen fluoride. The tube was warmed to 150°C and held at 149°C to 150°C for eight hours with shaking. The tube was then cooled to room temperature and treated with 100 mL of water. The contents of the tube were discharged and a small organic layer was collected and neutralized. The sample was 91.1% unconverted HCFC-243db; the GC-MS analysis of the converted products were as follows:

TABLE 4

Component	GC Area %
HFC-245cb	39.3
HFC-245fa	5.5
C <sub>3</sub> H <sub>3</sub> ClF <sub>4</sub>	9.2
C <sub>3</sub> H <sub>3</sub> ClF <sub>4</sub>	27.6
HCFC-253fb	2.9
HCFC-234ab	8.6
HCFC-243fa	6.9

REFERENCE EXAMPLE 13

Fluorination of HCFO-1233xf to HCFC-244bb

**[0093]** The contents of a small PTFE vial containing 20 grams of viscous SbF<sub>5</sub> were poured into a dry 400 mL Hastelloy® shaker tube. The tube was closed and was pressurized with nitrogen for leak testing. The shaker tube was then cooled to less than - 40 °C with dry ice, slowly vented, and then evacuated. 75 grams (3.75-moles) of anhydrous HF was condensed into the shaker tube followed by 165 grams (1.26-moles) of HCFO-1233xf. The shaker tube was placed in a barricade and shaking was started.

**[0094]** The shaker tube was agitated at ambient temperature (~20-23°C) and the pressure was 21 to 25 psig (144.79 to 172.37 kPa). After 2 hours, shaking was stopped and 150 mL of water was carefully pumped into the shaker tube. The tube was left overnight and then cooled to 0 to 5°C in an ice bath before depressurization and transferring the contents to a plastic container. The container was kept on ice.

**[0095]** The container contents were poured into a polypropylene separatory funnel containing some ice. The lower organic layer was light amber in appearance. The organic layer was separated into a media bottle made of a glass sold under the trademark of Pyrex® by Corning (Lowell, MA) (hereinafter "Pyrex®") containing ~50-mL of 4 molar (pH 7) phosphate buffer and ice (~100-mL). The organic layer was again separated and poured into a dry Pyrex® media bottle

## EP 2 634 231 B1

containing a small amount of anhydrous magnesium sulfate. Crude yield was 164.3 grams (about 120-mL, 86%).

**[0096]** GC/MS of the crude material showed that it was mostly HCFC-244bb. Other components included 0.13% 245cb, 0.09% 245eb, 0.16% 1233xf, and other byproducts totaling 12.2%.

### 5 REFERENCE EXAMPLE 14

#### Fluorination of HCFO-1233xf to HCFC-244bb

10 **[0097]** The contents of a small PTFE vial containing 20 grams of viscous  $SbF_5$  were poured into a dry 400-mL Hastelloy® shaker tube. The tube was closed and was pressurized with nitrogen for leak testing. The shaker tube was then cooled to less than - 40 °C with dry ice, slowly vented, and then evacuated. 53 grams (2.65 moles) of anhydrous HF was transferred into the shaker tube followed by 227 grams (1.74 moles) of HCFO-1233xf was condensed into the chilled shaker tube. The shaker tube was placed in the barricade and shaking was started.

15 **[0098]** The shaker tube was agitated at ambient temperature (~18-21°C) and the pressure was 16 to 20 psig (110.32 to 137.90 kPa). After 2 hours, shaking was stopped and 100 mL of water was carefully pumped into the shaker tube. The tube was left overnight and cooled to 0 to 5°C in an ice bath before venting and transferring the contents to a plastic container. The container was kept on ice.

20 **[0099]** The container contents were poured into a polypropylene separatory funnel containing some ice. The lower organic layer was light amber in appearance. The organic layer was separated into a Pyrex® media bottle containing about 50 mL of 4 molar (pH 7) phosphate buffer and ice (~100-mL). The organic layer was again separated and poured into a dry Pyrex® media bottle containing a small amount of anhydrous magnesium sulfate. Crude yield was 238.8 grams (about 170-mL, 91%).

25 **[0100]** GC/MS of the crude material indicated that it was mostly HCFC-244bb. Other components included 0.11% HFC-245cb, 0.10% HFC-245eb, 0.26% HCFO-1233xf, and other byproducts totaling 9.7%.

### REFERENCE EXAMPLE 15

**[0101]** Example 15 demonstrates the conversion of HCFC-244bb (2-chloro-1,1,1,2-tetrafluoropropane) to HFO-1234yf (2,3,3,3-tetrafluoropropene) in the absence of a catalyst.

30 **[0102]** An empty Inconel® tube (1/2 inch OD) with a heated zone of about 12 inches was heated to a temperature between 500°C and 626°C, and HFC-244bb was fed at 0.52 mL/hour through a vaporizer set at 40°C using a  $N_2$  sweep of 2.4 sccm ( $4.0 \times 10^{-8} m^3$ ). The reactor effluent was analyzed using an on-line GCMS, with the results being reported in mole percent.

TABLE 5

Temp., °C	Mole Percent								
	23	1141	143a	245cb	1234yf	254eb	244bb	1233xf	Unks
500*	0.2	0.1	0.0	0.4	14.2	1.0	82.6	1.2	0.0
550*	1.9	0.9	0.1	0.0	57.0	1.7	35.4	1.2	1.6
574*	2.7	1.1	0.1	0.0	77.0	1.9	13.0	1.4	2.8
603*	6.8	2.4	0.2	0.0	85.0	1.4	1.3	0.7	2.2
626*	6.9	2.0	0.2	0.0	82.5	0.7	0.2	1.4	5.9
* Reference Example									

### REFERENCE EXAMPLE 16

50 **[0103]** Example 16 demonstrates the conversion of HCFC-244bb (2-chloro-1,1,1,2-tetrafluoropropane) to HFO-1234yf (2,3,3,3-tetrafluoropropene) in the absence of a catalyst.

55 **[0104]** An empty Inconel® tube (1/2 inch OD) with a heated zone of about 12 inches was heated to 575°C, and HFC-244bb was fed at 0.35 mL/hour through a vaporizer set at 40°C using a  $N_2$  sweep of 3.6 sccm ( $6.0 \times 10^{-8} m^3$ ). The reactor was operated for a total of 19 hours continuously, and samples were taken periodically and analyzed to determine % conversion of HFC-244bb, and selectivity to HFO-1234yf. The reactor effluent was analyzed using an on-line GCMS, and the data in Table 6 below is an average of at least two on-line injections at a given condition; the percentages are mole percent.

TABLE 6

Hours	<u>23</u>	<u>1141</u>	<u>245cb</u>	<u>1234yf</u>	<u>254eb</u>	<u>244bb</u>	<u>1233xd</u>	<u>1223 (2 isomers)</u>	<u>Unk</u>
<u>3</u>	<u>1.9</u>	<u>0.8</u>	<u>0.1</u>	<u>68.8</u>	<u>3.5</u>	<u>17.9</u>	<u>5.1</u>	0.5	<u>1.3</u>
<u>4</u>	<u>1.4</u>	<u>0.7</u>	<u>0.0</u>	<u>61.5</u>	<u>4.2</u>	<u>22.7</u>	<u>7.4</u>	<u>1.1</u>	<u>1.0</u>
<u>8</u>	<u>0.0</u>	<u>0.3</u>	<u>0.0</u>	<u>61.1</u>	<u>2.6</u>	<u>15.0</u>	<u>14.1</u>	<u>3.9</u>	<u>2.8</u>
<u>12</u>	<u>0.0</u>	<u>0.5</u>	<u>0.0</u>	<u>60.1</u>	<u>2.0</u>	<u>13.7</u>	<u>16.4</u>	<u>6.0</u>	<u>1.3</u>
<u>15</u>	<u>0.9</u>	<u>0.3</u>	<u>0.0</u>	<u>66.9</u>	<u>1.7</u>	<u>14.5</u>	<u>12.0</u>	<u>2.7</u>	<u>1.0</u>
<u>19</u>	<u>0.0</u>	<u>0.7</u>	<u>0.0</u>	<u>67.4</u>	<u>0.0</u>	<u>7.0</u>	<u>16.6</u>	<u>8.2</u>	<u>0.0</u>

### REFERENCE EXAMPLE 17

**[0105]** Example 17 demonstrates the dehydrochlorination of HCFC-244bb (2-chloro-1,1,1,2-tetrafluoropropane) in the presence of an activated carbon catalyst.

**[0106]** An Inconel® tube (1/2 inch OD) was filled with 4 cc (1.99 gm) of acid washed PCB Polynesian coconut shell based carbon from Calgon (6-10 mesh). HFC-244bb was fed at 1.04 mL/hour through a vaporizer set at 40°C using a N<sub>2</sub> sweep of 2.4 sccm (4.0 x 10<sup>-8</sup> m<sup>3</sup>) giving a total contact time of about 32 seconds while controlling the reactor temperature at 400°C.

**[0107]** The data in Table 7 shows the reactor effluent composition in mole percent for this process run with an activated carbon catalyst to make HFC-1234yf via HCl elimination over the period of 7 hours of operation.

TABLE 7

Hours	<u>245cb</u>	<u>1234yf</u>	<u>245eb</u>	<u>1336</u>	<u>244bb</u>	<u>1233xf</u>	<u>Unk</u>
<u>1</u>	<u>0.0</u>	<u>52.2</u>	<u>0.2</u>	<u>0.0</u>	<u>22.4</u>	<u>10.3</u>	<u>14.9</u>
<u>2</u>	<u>0.0</u>	<u>44.5</u>	<u>0.2</u>	<u>0.1</u>	<u>24.6</u>	<u>13.4</u>	<u>17.3</u>
<u>3</u>	<u>0.0</u>	<u>38.0</u>	<u>0.2</u>	<u>0.2</u>	<u>31.9</u>	<u>14.8</u>	<u>15.0</u>
<u>4</u>	<u>0.0</u>	<u>25.9</u>	<u>0.2</u>	<u>0.1</u>	<u>41.8</u>	<u>15.7</u>	<u>16.3</u>
<u>5</u>	<u>0.0</u>	<u>15.5</u>	<u>0.3</u>	<u>0.1</u>	<u>49.4</u>	<u>17.9</u>	<u>16.7</u>
<u>6</u>	<u>0.5</u>	<u>7.1</u>	<u>0.3</u>	<u>0.1</u>	<u>53.8</u>	<u>18.0</u>	<u>20.2</u>
<u>7</u>	<u>0.6</u>	<u>2.9</u>	<u>0.3</u>	<u>0.1</u>	<u>54.2</u>	<u>17.3</u>	<u>24.5</u>

### Claims

1. A composition comprising HFO-1234yf and at least one additional compound selected from the group consisting of HCFC-253fb, HCFC-234ab, HCFC-243fa, HCO-1130a, HCFC-1131, and HCFO-1242zf.
2. The composition of claim 1 containing less than about 1 weight percent of the at least one additional compound.
3. The composition of claim 1 wherein the total amount of additional compound(s) ranges from greater than zero weight percent to less than 1 weight percent.
4. Use of the compositions of claim 1 as refrigerants.
5. Use of the compositions of claim 1 as a refrigerant in air conditioners, freezers, refrigerators, heat pumps, water chillers, flooded evaporator chillers, direct expansion chillers, walk-in coolers, heat pumps, mobile refrigerators, mobile air conditioning units and combinations thereof.
6. Use of the compositions of claim 1 as aerosol propellants.

7. Use of the compositions of claim 1 as foaming agents.
8. A method of using the compositions of claim 1 comprising the composition carrying heat from a heat source to a heat sink.
9. A method of using the composition of claim 1 as a refrigerant in a cycle comprising the composition undergoing a phase change from a liquid to a gas and back.

5

#### 10 Patentansprüche

1. Zusammensetzung, umfassend HFO-1234yf und mindestens eine zusätzliche Verbindung, ausgewählt aus der Gruppe, bestehend aus HCFC-253fb, HCFC-234ab, HCFC-243fa, HCO-1130a, HCFC-1131 und HCFO-1242zf.
2. Zusammensetzung nach Anspruch 1, die weniger als etwa 1 Gewichtsprozent der mindestens einen zusätzlichen Verbindung enthält.
3. Zusammensetzung nach Anspruch 1, wobei die Gesamtmenge der zusätzlichen Verbindung(en) im Bereich von mehr als null Gewichtsprozent bis weniger als 1 Gewichtsprozent liegt.
4. Verwendung der Zusammensetzungen nach Anspruch 1 als Kältemittel.
5. Verwendung der Zusammensetzungen nach Anspruch 1 als Kältemittel in Klimaanlage, Tiefkühltruhen, Kühlschränken, Wärmepumpen, Wasserkühlapparaten, überfluteten Verdampferkühlern, Direktexpansionskühlern, Kühlräumen, Wärmepumpen, fahrbaren Kühlanlagen, fahrbaren Klimageräten und Kombinationen davon.
6. Verwendung der Zusammensetzungen nach Anspruch 1 als Aerosol-Treibmittel.
7. Verwendung der Zusammensetzungen nach Anspruch 1 als Schaumbildner.
8. Verfahren zur Verwendung der Zusammensetzungen nach Anspruch 1, wobei die Zusammensetzung Wärme von einer Wärmequelle zu einer Wärmesenke leitet.
9. Verfahren zur Verwendung der Zusammensetzung nach Anspruch 1 als Kältemittel in einem Kreislauf, bei dem die Zusammensetzung eine Phasenänderung von einer Flüssigkeit zu einem Gas und zurück durchläuft.

15

20

25

30

35

#### Revendications

1. Composition comprenant du HFO-1234yf et au moins un composé additionnel sélectionné dans le groupe constitué du HCFC-253fb, du HCFC-234ab, du HCFC-243fa, du HCO-1130a, du HCFC-1131, et du HCFO-1242zf.
2. Composition selon la revendication 1 contenant moins d'environ 1 pour cent en poids de l'au moins un composé additionnel.
3. Composition selon la revendication 1, dans laquelle la quantité totale du(des) composé(s) additionnel(s) va de plus de zéro pourcent en poids à moins de 1 pourcent en poids.
4. Utilisation des compositions selon la revendication 1 comme agents réfrigérants.
5. Utilisation des compositions de la revendication 1 comme agent réfrigérant dans des conditionneurs d'air, des congélateurs, des réfrigérateurs, des pompes à chaleur, des refroidisseurs d'eau, des refroidisseurs évaporateurs immergés, des refroidisseurs à détente directe, des chambres froides, des pompes à chaleur, des réfrigérateurs mobiles, des unités mobiles de conditionnement d'air et des combinaisons de ceux-ci(celles-ci).
6. Utilisation des compositions selon la revendication 1 comme agents propulseurs d'aérosol.
7. Utilisation des compositions selon la revendication 1 comme agents moussants.

40

45

50

55

## EP 2 634 231 B1

8. Procédé d'utilisation des compositions selon la revendication 1 comprenant le transport de chaleur par la composition depuis une source de chaleur jusqu'à un puits de chaleur.
9. Procédé d'utilisation de la composition selon la revendication 1 comme agent réfrigérant dans un cycle comprenant la soumission de la composition à un changement de phase, passant d'un liquide à un gaz et inversement.

5

10

15

20

25

30

35

40

45

50

55




FIG. 1

**REFERENCES CITED IN THE DESCRIPTION**

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

**Patent documents cited in the description**

- WO 2008054782 A [0016]
- WO 2008054781 A [0016]
- US 20050228202 A [0043] [0067]

**Non-patent literature cited in the description**

- **V.C. PAPADIMITRIOU et al.** *Physical Chemistry Chemical Physics*, 2007, vol. 9, 1-13 [0007]
- **SATTERFIELD.** *Heterogeneous Catalysis in Industrial Practice*. McGraw-Hill, 1991, 87-112 [0042] [0066]