

(19)



(11)

EP 2 591 861 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
24.09.2014 Bulletin 2014/39

(51) Int Cl.:
B05B 11/00 (2006.01) **B65D 83/20** (2006.01)
B65D 83/22 (2006.01)

(21) Application number: **11188491.2**

(22) Date of filing: **09.11.2011**

(54) **Actuator cap for a fluid dispenser**

Betätigungskappe für einen Flüssigkeitsspender

Bouchon d'actionneur pour distributeur de liquides

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(43) Date of publication of application:
15.05.2013 Bulletin 2013/20

(73) Proprietors:

- **Unilever PLC**
London
Greater London EC4Y 0DY (GB)
Designated Contracting States:
CY GB IE MT
- **Unilever N.V.**
3013 AL Rotterdam (NL)
Designated Contracting States:

**AL AT BE BG CH CZ DE DK EE ES FI FR GR HR
HU IS IT LI LT LU LV MC MK NL NO PL PT RO RS
SE SI SK SM TR**

(72) Inventors:

- **Betts, Kassie Terra-Lynn**
Warwickshire CV34 4AB (GB)

- **Bilton, Simon Lewis**
Warwickshire CV34 4AB (GB)
- **Jones, Christopher John**
Warwickshire CV34 4AB (GB)
- **Kouyoumjian, Garen**
Warwickshire CV34 4AB (GB)
- **Caroen, Adrian Barclay**
London SW6 7NR (GB)

(74) Representative: **Whaley, Christopher et al**
Unilever PLC
Unilever Patent Group
Colworth House
Sharnbrook
Bedford, Bedfordshire MK44 1LQ (GB)

(56) References cited:
EP-B1- 1 248 731 WO-A1-2008/150810
WO-A2-2007/022422 DE-U1- 29 610 372
JP-U- S6 287 765 US-A- 4 542 837

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 2 591 861 B1

Description

[0001] The present invention is concerned with an actuator cap for a fluid container that allows the contents of the container to be sprayed without the cap having to be removed. The invention is of particular use in the field of home and personal care when it may be used as part of a hand held aerosol dispenser. A particular aspect of the invention is that the actuator enables the dispenser with which it is associated to be interchangeably converted between operative and inoperative states.

[0002] Sprays through actuator caps enabling conversion between operative and inoperative states, optionally for use with pressurised fluid containers, have been described in the prior art.

[0003] US 4,542,837 (Metal Box) and JPS6287765U disclose actuators having upper and lower rotatable parts which may be rotated between operative and inoperative positions.

[0004] EP 2,049,415 B1 (Valois) discloses a fluid dispensing head comprising actuator means for driving a pushbutton in axial displacement relative to the valve rod, the pushbutton being used to trigger dispensing.

[0005] DE 296 10 372 U1 (Holthoff Martin) discloses a fluid dispensing device having an actuator comprising upper and lower rotatable parts which may be rotated between operative and inoperative positions.

[0006] It is an object of the present invention to provide a robust, yet ergonomically attractive dispensing means for spraying fluid products, particularly products intended for application to the surface of the human body.

[0007] The invention is particularly suitable for applying cosmetic products to the surface of the human body, especially to the underarm regions of the human body.

[0008] In a first aspect of the present invention, there is provided an actuator cap for dispensing a fluid product, comprising a rotatable outer body and an associated actuator button, the outer body enclosing a non-rotatable chassis and an associated spray channel assembly, the latter comprising an outlet nozzle; the outer body and actuator button being rotatable between:

a first position in which the actuator button is non-elevated, the actuator button being incapable of depression in this position and

a second position in which the actuator button is elevated across its full length and width relative to top surface of the outer body, the actuator button still being capable of depression in this position; and

a third position in which the actuator button is elevated across its full length and width and tilted relative to top surface of the outer body, the button being capable of depression in this position;

rotation of the outer body in a first direction causing the actuator button, but not the spray channel assembly, to rise and rotate in this same direction, and rotation of the outer body in a second opposite direction causing the

actuator button, but not the spray channel assembly, to fall and rotate in this same opposite direction, and depression of the actuator button causing depression of the spray channel assembly, which in turn causes release of fluid product from an associated container through the spray channel assembly.

[0009] The actuator cap of the present invention is designed for use with a supply of fluid product, particularly fluid cosmetic product for use on the surface of the human body. The fluid product is supplied from a container to which the actuator cap is attached.

[0010] The actuator cap is particularly suitable for use with a pressurised aerosol canister containing the product to be dispensed.

[0011] A key feature of the invention is the rising actuator button. When the actuator button is not raised, the device is incapable of operation, giving it a safe transit and storage position. This position is additionally safe because the actuator button itself is protected from damage in this position, being surrounded by the outer body. There are also advantages with regard to stacking devices incorporating the 'closed' actuator button and associated fluid container.

[0012] A further benefit of the present invention is that the spray channel assembly, typically the most fragile element of spray through caps, is always enclosed by the actuator cap and does not itself need to rise through the cap in preparation for actuation. Designs in which the spray channel assembly needs to rise significantly to achieve activation are prone to stresses that the actuator caps of the present invention avoid.

[0013] When the actuator button is raised, this gives a visible and tactile indication to the user that the device is ready for operation. It also has the psycho-ergonomic benefit that it is the part that has changed, i.e. raised, that needs to be pressed for the device to be actuated.

[0014] The actuator cap has the further advantage that it is easily returned to its non-operable state.

[0015] In preferred embodiments, the actuator cap comprises means for driving rotation of the outer body towards completion. This can be to complete rotation to the primed position and/or rotation towards the fully closed position. This is typically achieved by means of leaf springs and/or rotational tension between non-circulation as described in more detail later.

[0016] Herein, references to the "device" are the actuator cap in combination with a container of the fluid to be dispensed.

[0017] Herein, orientation terms such as "horizontal/vertical" and "upper/lower" should be understood to refer to the actuator cap oriented in an upright manner as it would be on top of an upright aerosol can with which it is designed for use.

[0018] Herein, the "front" of the actuator cap refers to the face bearing the spray outlet; the "sides" are the faces orthogonal to this face and the "rear" is the face parallel to, but away from that bearing spray outlet. These terms have the same meaning (*mutatis mutandis*) when used

with reference to components of the actuator cap and relate to the actuator cap in its "primed" position.

[0019] Herein, the actuator cap should be understood to be "primed", i.e., ready for actuation, when the actuator button is in its raised and tilted position ready for depression.

[0020] The components of the actuator cap are typically made from plastic. The outer body and chassis may be made from polypropylene, as may the spray channel. The swirl chamber, if employed, is typically made using a spray insert preferably made from acetal.

[0021] The features described with reference to the following specific embodiment may be incorporated independently into the generic description given above and/or as given in the claims.

Figure 1 is a view of an actuator cap (1) according to the present invention.

Figure 2 is a view of the actuator cap (1) with the outer body (2) made invisible.

Figure 3 is a view of the actuator cap (1) with the outer body (2) and actuator button (3) made invisible.

Figures 4, 5, and 6 are views of the chassis (5) from above and to the side (Figure 4), from the top (Figure 5) and from the bottom (Figure 6).

Figure 7 is a view of the outer profile of the skirt (34) section of chassis (5) and how it differs from circular.

Figure 8 is a view of the outer body (2) from above, front, and side.

Figure 9 is a view of the outer body (2) from below and side and Figure 10 is a view of the outer body (2) from below.

Figure 11 is a view of the actuator button (3) from above, front and side and Figure 12 is a view of the actuator button (3) from below, front and side.

Figures 13, 14, and 15 are each views of the spray channel assembly (6); Figure 13 is a side view with the nozzle projecting to the left; Figure 14 is a side view with the nozzle projecting to the right and Figure 15 is a view from below and side, with slight offset to the rear.

[0022] Figure 1 shows an actuator cap (1) comprising a rotatable outer body (2), actuator button (3) and collar (4). The collar (4) is designed to fit over a pressurised fluid container (not shown) with which the actuator cap (1) is designed to be used. In this Figure, the actuator button (3) is in a raised and tilted position in preparation for actuation (*vide infra*). From this Figure and many of the others, it is clear that the overall cross-sectional

shape of the actuator (1), in a horizontal plane, is non-circular, having what might be termed a rounded rectangular shape. Both the collar (4) and the outer body (2) have this cross-sectional shape.

[0023] Figure 2 shows the actuator cap (1) of Figure 1 with the outer body (2) made invisible, revealing some of the internal features of the device. The collar (4) is part of a much more involved component, the chassis (5), more about which is said below. Many of the components of the chassis (5) sit on a platform (7) that is held in a raised position above the collar (4) by several connecting ribs (8 and 9), two of which (one illustrated, 9) are wider than the others and project outwards from the platform (7). The narrower connecting ribs (8), of which there are four (two shown), are recessed. These features are further illustrated in Figures 4, 5, and 6. These features are important to the interaction of the outer body (2) with the chassis (5) (*vide infra*). Visible in part in Figure 6 is the spray channel assembly (6).

[0024] Figure 3 illustrates the spray channel assembly (6) held snugly in the chassis (5). Figure 3 also shows one of two cam surfaces or drive ramps (10) present on the chassis (5) and one of two cam surfaces or return ramps (11) present on the spray channel assembly (6). These cam surfaces are key to the operation of the actuator (*vide infra*). Also shown is a low wall (12) of convoluted shape rises from the platform (7) of the chassis (5) and extends approximately two-thirds the way around the platform (7), close to but not at its periphery. This wall (12) is important in the rotational operation of the actuator (1) (*vide infra*).

[0025] Figure 4 illustrates several of the features of the chassis (5). Features not previously discussed are the screen (13) and blanking plate (14). The blanking plate (14) serves to block off the aperture (16) in the skirt (17) of the outer body (2) when the actuator (1) is in its fully closed position (*vide infra*). The screen (13) serves a similar purpose when the actuator (1) is part way between its fully closed and fully open positions. There is a cut away section (22) at the end of the screen (13) farthest from the blanking plate (14) in which an obscuring plate (23) of the spray channel assembly (6) sits when the actuator cap (1) is fully assembled (*vide infra*).

[0026] Also illustrated in Figure 4 are two cam surfaces or drive ramps (10 and 18). The drive ramps (10 and 18) protrude from the platform (7) and curve around facing portions of the edge of an aperture (26) in the chassis (5) (see Figure 5), increasing in height in an anticlockwise direction. One of these drive ramps (10) is shorter than the other (18), as a result of starting at a higher point up the wall (12), of which they are both continuations. The shorter drive ramp (10) is truncated at its top, terminating in a short horizontal section (19) anticlockwise from the ramped section. Leading in to each of the drive ramps (10 and 18) from an anticlockwise direction are flat sections (10A and 18A, respectively). The drive ramps (10 and 18) have the same slope and terminate at the same height above the platform (7). The drive ramps (10 and

18) serve to force the actuator button (3) upwards by interaction with drive lugs (20 and 21) projecting inwards from the actuator button (3) when the actuator button (3) is rotated by turning the outer body (2) anticlockwise (*vide infra*).

[0027] Also illustrated in Figure 4 is one of two retaining clips (33) that help hold the spray channel assembly (6) in place. These clips (also illustrated in Figures 5 and 6), have a top surface that slopes downwards towards the centre of aperture (26), this feature assisting the assembly of the actuator cap (1), in particular the insertion of the spray channel assembly (6) into the aperture (26) in the chassis (5).

[0028] The outer edge of the chassis (5) at its lower end is defined by the collar (4). Immediately above the collar (4) there is a short peripheral skirt (34) of almost circular profile. This skirt (34) projects upwards from a horizontal peripheral ledge (35) which links the bottom of the peripheral skirt (34) to the top of the collar (4). When the actuator cap (1) is assembled, the lower edge of the outer body (2) sits upon the peripheral ledge (35). Interaction between the inner surface of the outer body (2), which has "rounded rectangular" cross-section and the outer surface of the peripheral skirt (34), which has an almost but not quite circular profile (see Figure 7), leads to rotational tensioning. Tension is reduced when the "corners" of the outer body (2) are located adjacent to the outer edge of the peripheral skirt (34) at its wider points, such that the narrower cross-sectional dimensions of the outer body (2) are located adjacent to the skirt (34) where it has its narrower cross-sectional dimensions. These interactions tend to ease rotation of the outer body (2) towards its positions where the tensions are minimised. The design is such that these tensions are minimised when the actuator cap (1) is in its fully open or fully closed position; hence, the outer body (2) is encouraged towards these rotational positions when close thereto.

[0029] There are two slots (40) between the platform (7) and the peripheral ledge (35). These slots (40) comprise gaps existing in both vertical and horizontal planes. The vertical gap is constant across the full dimensions of the components, the platform (7) being held at the same height above the surrounding peripheral ledge (35) across all its extent. The radial gap between the platform (7) and the ledge (35) varies radially, decreasing steadily in width in a clockwise direction starting from the points adjacent to the clockwise edges of the wider connecting ribs (9). This may most clearly be seen in Figures 5 and 6. The decreasing width of the slots (40) in this plane is caused by a corresponding increase in the size of the platform (7). This variation in the radial width of the slots (40) has marked advantage in the balance between ease of manufacture and the in use robustness of the assembled actuator cap (1) (*vide infra*).

[0030] Figure 5 shows the path of the low wall (12) of convoluted shape that rises from the platform (7) of the chassis (5). This wall interacts with two leaf springs (24)

projecting downwards from the inside surface of the top wall (25) of the outer body (2) (*vide infra*). The lower ends of the leaf springs (24) sit outside of the low wall (12) and are tensioned when outside the sections of the wall (12) farthest from the centre (labelled 12A). The tension in the leaf springs (24) serves to drive rotation of the outer body (2) towards the positions in which the leaf springs (24) sit outside the sections of the wall (12) nearest to the centre (labelled 12B) when the rotational of the outer body (2) is such that the lower ends of the leaf springs (24) are located on sections of the wall (12) sloping between the sections farthest (12A) and nearest (12B) to the centre.

[0031] The location of the leaf springs (24) is such that their lower ends sit outside the sections of the low wall (12B) nearest to the centre of the chassis (5) when the actuator cap (1) is in its fully open or fully closed position; hence, the leaf springs serve to drive the outer body (2) towards these rotational positions when close thereto.

[0032] The chassis has a central aperture (26) into which the spray channel assembly (6) is designed to fit snugly. The aperture (26) is roughly circular in cross-section, but has distinct narrowed sections (27) that interact with narrowed sections on the body (28) (see Figure 15) of the spray channel assembly (6) to restrict rotation of the latter when in the aperture (26). From the edge of the central aperture (26), a wall (29) of varying height (most clearly seen in Figure 4) rises from the platform (7). The aforementioned drive ramps (10 and 18) are extensions of this wall (29) where it surrounds the narrowed sections (27) of the aperture (26). At these sections (27), the wall (29) has strengthening support struts (30) radiating outwards from its outer edge and abutting the platform (7), as illustrated in Figures 4 and 5. Each of the drive ramps (10 and 18) has a vertical edge (36), see Figure 4, at its anticlockwise extremity, this being important in the achieving spray release when the actuator cap (1) is primed (*vide infra*). At a location on the wall (29) radially matching the position of the cut-away section (22) at the end of the more externally located screen (13), the wall (29) has a concave cut (41) for retention of a cross-stem (42) of spray channel assembly (6) when at its lowest (dispensing) position (*vide infra*). The radial position of the concave cut (41) is shortly anticlockwise of the vertical edge (36) defining the anticlockwise extremity of the longer drive ramp (18), this drive ramp (18) radially matching the position of the more externally located screen (13).

[0033] Figure 6 shows a valve cup ring (31) which protrudes downwards from the underside of the chassis (5) and which fastens to the valve cup of an aerosol can when the actuator cap (1) is in use. The valve cup ring (31) has an internal bead (32) to help facilitate this fastening. Figure 6 also illustrates the underside of the connecting ribs (8 and 9). The narrower ribs (8) project radially from the outer edge of valve cup ring (31) to the inner edge of the peripheral skirt (34) and collar (4). The wider ribs (9) are comprised of curved peripheral sections

(9A) linking the edge of the platform (7) to the top edge of the peripheral skirt (34) and inwardly angled support projections (9B) connecting the outer edge of the valve cup ring (31) to the inner edge of the peripheral skirt (34) and the collar (4).

[0034] Figure 8 shows that the outer body (2) has an upper surface (25) and a skirt (17) dependent therefrom. In a front portion of the skirt (17) there is an aperture (16) for the spray channel assembly (6) to be able to discharge from when the actuator cap (1) is primed. The upper surface (25) and an upper rear part of the skirt (17) facing the aperture (16) have a cut-away segment for incorporation of the actuator button (3) (*vide infra*). The part cut-away from the upper surface (25) has parallel edges towards the sides and a roughly orthogonal, but outwardly curved, edge towards the front.

[0035] One of the two leaf springs (24) is part illustrated in Figure 8, as is one of two downward projections (37) from the middle of both parallel edges of the cut-away segment of the upper surface (25). There are also downward projections (38) from either side of the parallel edges of the cut-away segment that border the cut-away segment in the skirt (17). These downward projections (37 and 38) serve to help guide the actuator button (3).

[0036] Figure 8 also illustrates one of two retaining clips (39) that help hold the outer body (2) in place on the chassis (5). These clips (39) fit into the slots (40) between the platform (7) and the skirt (34) of the chassis (5) and are circumferentially bounded by the edges of the wider connecting ribs (9) between these features (see Figure 4). Rotation of the clips (39) between the bounds of the connecting ribs (9) is possible in part because of the recessed nature of the narrower connecting ribs (8) located in-between.

[0037] During the manufacture of the dispensing cap (1), the retaining clips (39) are pushed through the slots (40) in the chassis (5) where the latter have their maximum radial width (*vide supra*), this easing manufacture. This corresponds to a radial positioning of the outer body (2) relative to the chassis (5) as present when the actuator cap is in its primed position. Following insertion, the retaining clips (39) are rotated in the slots (40) in the chassis (5) to the position where the latter have their minimum radial width, this corresponding to a radial positioning of the outer body (2) relative to the chassis (5) as present when the actuator cap is in its fully closed position. This serves to provide a high strength link between the outer body (2) and the chassis (5) when it is most needed, the consumer typically receiving the actuator cap (1) in a fully closed condition, together with an associated aerosol can, and proceeding to mistakenly attempt to pull off the actuator cap (1), believing it to be a conventional over-cap.

[0038] Figure 9 illustrates that between the downward projections (37 and 38) from each side of the upper surface (25) of the outer body (2) bordering the cut-away segment thereof, there is a concave curved depression or yoke (43). These concave yokes (43) (only one visible

in Figure 9) serve an important function in conjunction with elements of the actuator button (3) (*vide infra*).

[0039] Figures 9 and 10 illustrate several of the strengthening features of the outer body (2). The leaf springs (24) are each reinforced by four support struts (44) projecting from their outer surfaces are bracing against the inside surface of the top wall (25).

[0040] The retaining clips (39) are each strengthened by three support struts (45) that project downwards from their lower surfaces and brace against the inside of the skirt (17) at its front and rear. Two of the support struts (45) for the retaining clips (39) are located at the edges of the retaining clips (39) and project upwards as well as downwards. These edge support struts (45) also serve as rotational stops when they come up against the edges of the wider connecting ribs (9) that define the edge of the slots (40) in the chassis (5) into which the retaining clips (39) are designed to fit. The retaining clip support struts (45) are chamfered on their lower edges to ease insertion of the clips (39) into the slots (40) in the chassis (5).

[0041] The downward projections (37) from the middle of both parallel edges of the cut-away segment of the upper surface (25) are strengthened by orthogonal walls (46) that project outwards from their rear edges. These orthogonal walls (46) also help to guide the actuator button (3) in its movement within the actuator cap (1) (*vide infra*).

[0042] The front segment of the upper surface (25) of the outer body (2) is reinforced on its inner side by four support ribs (47) running in parallel from front to back.

[0043] Figure 11 shows some of the top and side features of the actuator button (3). There is a finger pad (48) upon its top face (50) and pinions (49) (one shown) are symmetrically disposed upon its side walls (51). The top face (50) is of same dimensions as the cut-away segment of the top wall (25) of the outer body (2) and completely fills this aperture when the actuator cap (1) is in its fully closed position. During anticlockwise rotation, the top face (50) of the actuator button (3) rises from being in the same plane as the upper surface (25) of the outer body (2), when the cap (1) is fully closed, through a position in which the top face (50) is raised but parallel to the upper surface (25), to a fully open or primed position in which the top face (50) is raised and sloping upwards (rear to front) relative to the upper surface (25). In the latter two positions, the side walls (51) of the actuator button (3) are visible in part, the actuator button protruding from the top surface (25) of the outer body (2) in these positions.

[0044] The side walls (51) of the actuator button (3) bearing the pinions (49) are actually located towards the front and rear of the actuator cap (1) when it is in its fully closed position; however, anticlockwise rotation of the upper body (2) and associated actuator button (3) through 90° puts the device in its fully open or primed position, in which position the pinions (49) are located towards the sides of the actuator cap (1) as a whole.

During the aforementioned rotation, the pinions (49) move up the channels existing between the downward projections (37 and 38) from the middle and rear (respectively) of the parallel edges of the cut-away segment of the upper surface (25) of the outer body (2), guided in part by the orthogonal walls (46) projecting outwards from the rear edges of the middle projections (37), and when fully elevated, sit in the concave depressions or yokes (43) at the top of said channels. In this latter position, the final anticlockwise rotation of the upper body (2) and associated actuator button (3) causes the actuator button (3) to pivot about an axis through the through its pinions (49), resulting in the actuator button (1) becoming raised at its front edge (*vide infra*).

[0045] Key components of the actuator button (3) shown in Figure 12 are inward projecting drive lugs (20 and 21). Projecting from a downwardly projecting front plate (52) of the button (3) is the front drive lug (20). Projecting from the front-facing surface of an internal cross-wall (53) just behind the axis between the pinions (49) of the button (3) is the rear drive lug (21). The front-back positioning of the rear drive lug (21) is in the same vertical plane as the axis between the pinions (49).

[0046] The drive lugs (20 and 21) are of the same dimensions and face one another in the same front-back plane; however, the front drive lug (20) is located somewhat lower in the actuator button (3) than the rear drive lug (21). The front drive lug (20) sits on the longer drive ramp (18) of the chassis (5) and the rear drive lug (21) sits on the shorter drive ramp (10) of the chassis (5). When the actuator cap (1) is in its fully closed position, the actuator button (3) is level with the top wall (25) of the outer body (2) because the height difference between the front drive lug (20) and the rear drive lug (21) equates to the height difference at which the longer drive ramp (18) and the shorter drive ramp (10) commence. As anticlockwise rotation of the outer body (2) and associated the actuator button (3) commences, the actuator button (3) rises without slanting because the drive ramps (18 and 10) upon which the drive lugs (20 and 21) sit have the same slope. When the rear drive lug (21) reaches the horizontal section (19) of the shorter drive ramp (10), it does not rise further, unlike the front drive lug (20) which continues to rise further along the longer drive ramp (18), thereby producing a tilt in the actuator button (3), it being raised at the front at this rotational position.

[0047] When the drive lugs (20 and 21) have passed just beyond the end of their corresponding drive ramps (18 and 10), further anticlockwise rotation is prevented by the retaining clips (39) abutting the edges of the wider connecting ribs (9) spanning the slots (40) in the chassis (5). In this position, the actuator cap (1) is primed and the actuator button (3) may be depressed. The drive lugs (20 and 21) serve a second but equally important function during actuation. Having passed beyond the vertical edges (36) at the anticlockwise ends of their drive ramps (18 and 10), they are not blocked from depression. Downward force on the actuator button (3) causes the drive

lugs (20 and 21) to press down upon the spray channel assembly (6) and this leads to actuation and release of product through the spray channel assembly (6).

[0048] If the actuation button (3) were to be pressed centrally, depression would in theory occur in a balanced fore and aft manner, each of the drive lugs (20 and 21) bearing down on the actuation spray assembly (6) and thereby avoiding possible lateral stress on the valve stem associated with the spray channel assembly (6) (*vide infra*).

[0049] In reality, the consumer tends to press the actuator button (3) more towards its rear, behind the axis of the pinions (49). This causes the actuator button (3) to pivot on its front edge and for pressure to be applied to the spray channel assembly (6) through the rear drive lug (21) rather than the front drive lug (20). This leads to distinct mechanical advantage because pressure is brought to bear on the spray channel assembly (6) closer to the pivot point than where the pressure is actually applied. Indeed, it has been found that operation of actuator cap (1) in this manner can lead to an up to 1.6 times mechanical advantage. Fortunately, this "uneven" pressure application upon the spray channel assembly (6) is not transferred to the valve stem with which it is in use associated because the spray channel assembly (6) is held snugly in the aperture (26) in the intervening chassis (5).

[0050] Other components of the actuator button (3) are as follows. There is a rear wall (54) that is designed to fill the cut-away section in the upper rear part of the skirt (17) facing the aperture (16). There is a front wall (55). The downwardly projecting front plate (52) is a partial continuation of this front wall (55). The is a platform (56) extending forward from the front wall (55) and also outwards front the side walls (51) as flexible wing structures (57) which slope upwards as they extend outwards. The platform (56) and associated flexible wing structures (57) are designed to fit under the top wall (25) of the outer body (2) and the front-back angle of these features is such that they are in the same plane as the top wall (25) of the outer body (2) when the actuator button (3) is fully tilted and the actuator cap (1) is primed. In this position, the platform (56) and associated flexible wing structures (57) are pressed against the under surface of the top wall (25) of the outer body (2), flattening out the upward slope of the flexible wing structures (57).

[0051] In addition, the actuator button (3) has multiple (six) outward projecting strengthening ribs (58) on the upper surface of the part of the platform (56) extending forward from the front wall (55). The downwardly projecting front plate (52) has two support wedges (59) between it and the lower side of the platform (56) extending forward from the front wall (55). The internal cross-wall (53) has support ribs (60) projecting fore and aft. The side walls (51) each have a thin, outward-projecting, vertical rib (61) located just to the rear of the pinions (49). These ribs (61) lightly contact the inner faces of the downward projections (38) from the parallel edges of the segment

cut-away from the top wall (25) of the outer body (2) and help to prevent undesirable sideways roll of the actuator button (3) when it is depressed.

[0052] Figures 13 to 15 illustrate various aspects of the spray channel assembly (6). The main body (28) is of roughly circular cross-section, but has narrowed sections (28A) that fit within the narrowed sections of the aperture (26) in the chassis (5) (*vide supra*). Projecting outwards from the upper region of the main body (28) is a radial nozzle tube (62), terminating in the spray orifice (63). The spray issuing from the spray orifice (63) further atomised by a spray chamber (64) sitting at the end of the radial nozzle tube (62). The radial nozzle tube (62) slopes slightly upwards as it extends outwards. The spray orifice (63) is surrounded by the obscuring plate (23) that fills the cut away section (22) at the end of the screen (13) farthest from the blanking plate (14) of the chassis (5) (*vide supra*).

[0053] From the underside of the spray channel assembly (6) in the centre there protrudes a tubular stem socket (68), designed to accommodate the valve stem of an associated aerosol container. The stem socket (68) is in fluid communication with the spray orifice (63) through the spray chamber (64) and other internal channels not illustrated but common in the art.

[0054] From the outer surface of the main body (28) at its lower end, two retaining clips (69) protrude from the "non-narrowed" or wider segments (28B) of the main body (28), on opposite sides of said main body (28). These retaining clips (69) fit underneath the corresponding retaining clips (33) that protrude into the central aperture (26) of the chassis (5) (*vide supra*) and help to hold the spray channel assembly (6) and the chassis (5) together.

[0055] There are two return ramps (11 and 65) of the same slope curving around opposite outside surfaces of the main body (28). These return ramps (11 and 65) sit above the drive lugs (21 and 20, respectively) projecting inwards from the actuator button (3) and serve to force the actuator button (3) downwards when the outer body (2) is rotated clockwise. The return ramp (65) to the left of the spray orifice (63) is longer than the return ramp (11) to the right of the spray orifice (63), viewing the actuator cap (1) from the front. The length of the longer return ramp (65) corresponds to the length of the longer drive ramp (18) and the front (lower) drive lug (20) sits between these ramps. The length of the shorter return ramp (11) corresponds to the length of the shorter drive ramp (10) and the rear (higher) drive lug (20) sits between these ramps.

[0056] The return ramps (11 and 65) have flat sections (66 and 67) at their upper and lower ends (respectively). The gap between the lower flat sections (67) and the flat sections (10A and 18A) leading into the corresponding drive ramps (10 and 18) on the chassis (5) is slightly less than the height of the drive lugs (21 and 20) that is forced between them as the outer body (2) is rotated to its fully clockwise position. As the chassis (5) is in fixed axial

position, this causes an upward force on the spray channel assembly (6), resulting in a slight lifting of the stem socket (68) from the valve stem (not illustrated) with which it is associated in use, creating a "safety gap" when the actuator is in its closed position.

Claims

1. An actuator cap (1) for dispensing a fluid product, comprising a rotatable outer body (2) and an associated actuator button (3), the outer body (2) enclosing a non-rotatable chassis (5) and an associated spray channel assembly (6), the latter comprising an outlet nozzle (63); the outer body (2) and actuator button (3) being rotatable between:

a first position in which the actuator button (3) is non-elevated, the actuator button (3) being incapable of depression in this position and a second position in which the actuator button (3) is elevated across its full length and width relative to top surface of the outer body (2), the actuator button (3) still being incapable of depression in this position; and

a third position in which the actuator button (3) is elevated across its full length and width and tilted relative to top surface of the outer body (2), the button (3) being capable of depression in this position;

rotation of the outer body (2) in a first direction causing the actuator button (3), but not the spray channel assembly (6), to rise and rotate in this same direction, and rotation of the outer body (2) in a second opposite direction causing the actuator button (3), but not the spray channel assembly (6), to fall and rotate in this same opposite direction, and depression of the actuator button (3) causing depression of the spray channel assembly (6), which in turn causes release of fluid product from an associated container through the spray channel assembly (6).

2. An actuator cap (1) according to claim 1, wherein rotation of the outer body (2) in its first direction uncovers the outlet nozzle (63) of the spray channel assembly (6) and rotation of the outer in its second opposite direction covers the outlet nozzle (63).
3. An actuator cap (1) according to claim 1 or 2, wherein the rotation of the outer body (2) in its first direction causes the actuator button (3) to tilt upwards at the end closest to the outlet nozzle (63).
4. An actuator cap (1) according to any preceding claim, wherein the elevation of the actuator button (3) is achieved through cam means acting between the actuator button (3) and the chassis (5).

5. An actuator cap (1) according to claim 4, wherein the cam means comprise drive ramps (10 and 18) around a curved up-standing wall (12) within the chassis (5) and drive lugs (20 and 21) projecting inwards from the actuator button (3) that ride on said drive ramps (10 and 18). 5
6. An actuator cap (1) according to any preceding claim, wherein the lowering of the actuation button (3) is achieved through cam means acting between the actuator button (3) and the spray channel (6). 10
7. An actuator cap (1) according to claim 6, wherein the cam means for lowering the actuator button (3) comprise drive ramps (11 and 65) around a main body of the spray channel assembly (6) and drive lugs (20 and 21) projecting inwards from the actuator button (3) that ride below said drive ramps (11 and 65). 15
8. An actuator cap (1) according to any preceding claim, wherein the spray channel assembly (6) is held snugly in a central aperture (26) in the chassis (5). 20
9. An actuator cap (1) according to any preceding claim, wherein the chassis (5) comprises a slot (40) into which a retaining clip (39) from the outer body (2) fits to secure the chassis (5) and outer body (2) together. 25
10. An actuator cap (1) according to claim 9, wherein the outer body (2) is more easily fitted to the chassis (5) in a first relative rotational positioning and is harder to remove in a second relative rotational positioning. 30
11. An actuator cap (1) according to claim 10, wherein the fit of the retaining clip (39) into the slot (40) tightens on rotation from the first relative rotational positioning to the second. 35
12. An actuator cap (1) according to any preceding claim, comprising means for driving rotation of the outer body (2) towards completion. 40

Patentansprüche

1. Betätigungskappe (1) zum Ausgeben eines Fluidprodukts, die einen drehbaren äußeren Körper (2) und einen zugeordneten Betätigungsknopf (3) umfasst, wobei der äußere Körper (2) einen nicht drehbaren Rahmen (5) und eine dazugehörige Sprühkanalanordnung (6) einschließt, wobei letztere eine Austrittsdüse (63) umfasst; wobei der äußere Körper (2) und der Betätigungsknopf (3) drehbar sind zwischen: 50

einer ersten Position, in der der Betätigungsknopf (3) nicht angehoben ist, wobei der Betätigungsknopf (3) in dieser Position nicht niedergedrückt werden kann, und
 einer zweiten Position, in der der Betätigungsknopf (3) über seine gesamte Länge und Breite in Bezug auf die obere Fläche des äußeren Körpers (2) angehoben ist, wobei der Betätigungsknopf (3) in dieser Position noch immer nicht niedergedrückt werden kann, und
 einer dritten Position, in der der Betätigungsknopf (3) über seine gesamte Länge und Breite angehoben ist und in Bezug auf die obere Fläche des äußeren Körpers (2) geneigt ist, wobei der Knopf (3) in dieser Position niedergedrückt werden kann;
 wobei eine Drehung des äußeren Körpers (2) in einer ersten Richtung bewirkt, dass sich der Betätigungsknopf (3), aber nicht die Sprühkanalanordnung (6), hebt und in derselben Richtung dreht, und wobei eine Drehung des äußeren Körpers (2) in einer zweiten entgegengesetzten Richtung bewirkt, dass sich der Betätigungsknopf (3), aber nicht die Sprühkanalanordnung (6), senkt und in derselben entgegengesetzten Richtung dreht, und wobei das Niederdrücken des Betätigungsknopfs (3) bewirkt, dass die Sprühkanalanordnung (6) niedergedrückt wird, was wiederum bewirkt, dass das Fluidprodukt aus einem zugeordneten Behälter durch die Sprühkanalanordnung (6) freigegeben wird.

2. Betätigungskappe (1) nach Anspruch 1, wobei eine Drehung des äußeren Körpers (2) in seiner ersten Richtung die Austrittsdüse (63) der Sprühkanalanordnung (6) aufdeckt und eine Drehung des äußeren Körpers in seiner zweiten entgegengesetzten Richtung die Austrittsdüse (63) abdeckt.
3. Betätigungskappe (1) nach Anspruch 1 oder 2, wobei die Drehung des äußeren Körpers (2) in seiner ersten Richtung bewirkt, dass der Betätigungsknopf (3) an dem Ende, das am nächsten zu der Austrittsdüse (63) ist, aufwärts geneigt ist.
4. Betätigungskappe (1) nach einem der vorhergehenden Ansprüche, wobei die Hebung des Betätigungsknopfs (3) durch Nockenmittel erreicht wird, die zwischen dem Betätigungsknopf (3) und dem Rahmen (5) wirken.
5. Betätigungskappe (1) nach Anspruch 4, wobei die Nockenmittel Führungsrampen (10 und 18) um eine gekrümmte aufrechtstehende Wand (12) innerhalb des Rahmens (5) und Führungsansätze (20 und 21), die von dem Betätigungsknopf (3) nach innen hervorstehen und auf den Führungsrampen (10 und 18) laufen, umfassen. 55

6. Betätigungskappe (1) nach einem der vorhergehenden Ansprüche, wobei das Absenken des Betätigungsknopfs (3) durch Nockenmittel zwischen dem Betätigungsknopf (3) und dem Sprühkanal (6) erreicht wird. 5
7. Betätigungskappe (1) nach Anspruch 6, wobei die Nockenmittel zum Absenken des Betätigungsknopfs (3) Führungsrampen (11 und 65) um einen Hauptkörper der Sprühkanalanordnung (6) und Führungsansätze (20 und 21), die von dem Betätigungsknopf (3) nach innen vorstehen und auf den Führungsrampen (11 und 65) laufen, umfassen. 10
8. Betätigungskappe (1) nach einem der vorhergehenden Ansprüche, wobei die Sprühkanalanordnung (6) bündig in einer mittigen Öffnung (26) in dem Rahmen (5) gehalten wird. 15
9. Betätigungskappe (1) nach einem der vorhergehenden Ansprüche, wobei der Rahmen (5) einen Schlitz (40) umfasst, in den eine Halteklammer (39) von dem äußeren Körper (2) eingesetzt ist, um den Rahmen (5) und den äußeren Körper (2) aneinander zu befestigen. 20 25
10. Betätigungskappe (1) nach Anspruch 9, wobei der äußere Körper (2) in einer ersten relativen Dreheinstellung einfacher in den Rahmen (5) einsetzbar ist und in einer zweiten relativen Dreheinstellung schwerer zu entfernen ist. 30
11. Betätigungskappe (1) nach Anspruch 10, wobei das Einsetzen der Halteklammer (39) in den Schlitz (40) bei der Drehung von der ersten Dreheinstellung zu der zweiten gefestigt wird. 35
12. Betätigungskappe (1) nach einem der vorhergehenden Ansprüche, die Mittel zum Führen der Drehung des äußeren Körpers (2) zum Abschluss umfasst. 40

Revendications

1. Bouchon d'actionnement (1) pour la distribution d'un produit liquide, comportant un corps extérieur rotatif (2) et un bouton d'actionnement associé (3), le corps extérieur (2) entourant un châssis non-rotatif (5) et un ensemble de canal de pulvérisation associé (6), ce dernier comportant une buse de sortie (63) ; le corps extérieur (2) et le bouton d'actionnement (3) pouvant tourner entre : 45 50

une première position dans laquelle le bouton d'actionnement (3) n'est pas soulevé, le bouton d'actionnement (3) étant incapable d'être enfoncé dans cette position et une deuxième position dans laquelle le bouton d'actionnement (3) est 55

soulevé sur toute sa longueur et toute sa largeur par rapport à la surface supérieure du corps extérieur (2),
le bouton d'actionnement (3) étant toujours incapable d'être enfoncé dans cette position ; et une troisième position dans laquelle le bouton d'actionnement (3) est soulevé sur toute sa longueur et toute sa largeur et incliné par rapport à la surface supérieure du corps extérieur (2), le bouton (3) étant capable d'être enfoncé dans cette position ; une rotation du corps extérieur (2) dans une première direction amenant le bouton d'actionnement (3), mais pas l'ensemble de canal de pulvérisation (6), à monter et tourner dans cette même direction, et une rotation du corps extérieur (2) dans une deuxième direction opposée qui amène le bouton d'actionnement (3), mais pas l'ensemble de canal de pulvérisation (6), à descendre et tourner dans cette même direction opposée, et l'enfoncement du bouton d'actionnement (3) entraînant un enfoncement de l'ensemble de canal de pulvérisation (6), qui entraîne à son tour une libération de produit liquide d'un récipient associé à travers l'ensemble de canal de pulvérisation (6).

2. Bouchon d'actionnement (1) selon la revendication 1, dans lequel une rotation du corps extérieur (2) dans sa première direction découvre la buse de sortie (63) de l'ensemble de canal de pulvérisation (6) et une rotation de l'extérieur dans sa deuxième direction opposée recouvre la buse de sortie (63).
3. Bouchon d'actionnement (1) selon la revendication 1 ou 2, dans lequel la rotation du corps extérieur (2) dans sa première direction amène le bouton d'actionnement (3) à s'incliner vers le haut au niveau de l'extrémité la plus proche de la buse de sortie (63).
4. Bouchon d'actionnement (1) selon l'une quelconque des revendications précédentes, dans lequel l'élévation du bouton d'actionnement (3) est obtenue grâce à des moyens de came agissant entre le bouton d'actionnement (3) et le châssis (5).
5. Bouchon d'actionnement (1) selon la revendication 4, dans lequel les moyens de came comportent des rampes d'entraînement (10 et 18) autour d'une paroi verticale courbe (12) dans le châssis (5) et des pattes d'entraînement (20 et 21) qui dépassent vers l'intérieur par rapport au bouton d'actionnement (3) qui montent sur lesdites rampes d'entraînement (10 et 18).
6. Bouchon d'actionnement (1) selon l'une quelconque des revendications précédentes, dans lequel l'abaissement du bouton de mise en fonction (3) est obtenu grâce à des moyens de came agissant entre le bou-

ton d'actionnement (3) et le canal de pulvérisation (6).

7. Bouchon d'actionnement (1) selon la revendication 6, dans lequel les moyens de came destinés à abaisser le bouton d'actionnement (3) comportent des rampes d'entraînement (11 et 65) autour d'un corps principal de l'ensemble de canal de pulvérisation (6) et des pattes d'entraînement (20 et 21) qui dépassent vers l'intérieur par rapport au bouton d'actionnement (3) et qui montent au-dessous desdites rampes d'entraînement (11 et 65). 5
10
8. Bouchon d'actionnement (1) selon l'une quelconque des revendications précédentes, dans lequel l'ensemble de canal de pulvérisation (6) est maintenu de manière ajustée dans une ouverture centrale (26) dans le châssis (5). 15
9. Bouchon d'actionnement (1) selon l'une quelconque des revendications précédentes, dans lequel le châssis (5) comporte une fente (40) dans laquelle une agrafe de retenue (39) du corps extérieur (2) s'ajuste afin de fixer le châssis (5) et le corps extérieur (2) ensemble. 20
25
10. Bouchon d'actionnement (1) selon la revendication 9, dans lequel le corps extérieur (2) est plus facilement monté sur le châssis (5) dans un premier positionnement de rotation relative et est plus difficile à retirer dans un deuxième positionnement de rotation relative. 30
11. Bouchon d'actionnement (1) selon la revendication 10, dans lequel le montage de l'agrafe de retenue (39) dans la fente (40) se serre lors de la rotation depuis le premier positionnement de rotation relative jusqu'au deuxième. 35
12. Bouchon d'actionnement (1) selon l'une quelconque des revendications précédentes, comportant des moyens destinés à entraîner en rotation le corps extérieur (2) jusqu'à la fin. 40

45

50

55

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14





Fig. 15



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 4542837 A [0003]
- JP S6287765 U [0003]
- EP 2049415 B1 [0004]
- DE 29610372 U1 [0005]