

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) Publication number:

0 016 615
B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication of patent specification: **11.05.88**

(51) Int. Cl.⁴: **A 24 C 5/58, B 26 D 5/04**

(21) Application number: **80300776.4**

(22) Date of filing: **13.03.80**

(54) **Cutting head for a cigarette filter attachment machine.**

(30) Priority: **16.03.79 GB 7909301**
11.12.79 GB 7942620

(43) Date of publication of application:
01.10.80 Bulletin 80/20

(45) Publication of the grant of the patent:
11.05.88 Bulletin 88/19

(84) Designated Contracting States:
DE FR GB IT

(56) References cited:
GB-A- 785 417
GB-A- 878 556
US-A-3 777 607

(73) Proprietor: **Molins PLC**
2 Evelyn Street
Deptford, London SE8 5DH (GB)

(72) Inventor: **Dyett, Derek Henry**
2 Evelyn Street
Deptford, London SE8 5DH (GB)
Inventor: **Thorp, Neil**
2 Evelyn Street
Deptford, London SE8 5DH (GB)
Inventor: **Wood, Godfrey Allen**
2 Evelyn Street
Deptford London SE8 5DH (GB)

(74) Representative: **Hirsh, Ivan Yehudi et al**
Molins PLC Group Patent Department Haw Lane
Saunderton
GB-High Wycombe Bucks HP14 4JE (GB)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European patent convention).

Courier Press, Leamington Spa, England.

EP 0016615 B1

Description

This invention is concerned with a cutting head for a filter attachment machine, which is a machine for making filter cigarettes by joining filter portions to tobacco rods by means of uniting bands. These bands are cut from a web of filter attachment material which is often of cork-like appearance and is for that reason usually referred to as "cork".

A common form of cutting head comprises a rotary member carrying a number of circumferentially spaced knives which cooperate with anvil inserts in a drum carrying the cork web, each cut being achieved by a pinching action. There are normally fewer knives on the cutting head than anvils on the cork drum. Accordingly, each knife cooperates at different moments with different anvils. It is possible for the anvils to be slightly different distances from the axis of the cork drum; moreover, if the cork drum is heated, then those distances depend also on the temperature of the cork drum. It has therefore been a problem to achieve a constant overall cutting force, and some prior arrangements have also been unable to distribute the cutting force evenly along the knife during each cutting operation.

British patent specification No. 878556 solved the last-mentioned problem by arranging for each knife to be pivotable about its centre, and also allowed for radical adjustment of the pivot position for each knife. However, the cutting force could still vary when a particular knife cooperated with different anvils at slightly different distances from the axis of the cork drum.

British patent specification No. 785417 describes an arrangement in which the cutting force is limited by the resilience of a spring, and which also allowed a slight tilting motion of the entire integral part carrying the knife member. Similarly, in British patent specification No. 1000696, resilience of the shaft 5 carrying the knife member 6, limited the cutting force, while a flexible connecting disc 7 allowed for a slight tilting motion which tended to even out the cutting force along the knife. However, none of those prior arrangements constitutes an entirely satisfactory solution to the problems mentioned above.

According to the present invention, a cutting head for a cigarette filter attachment machine, for cutting a filter attachment web at regular intervals in cooperation with a cutting drum, comprises a rotary member which carries one or more knives and is itself mounted on a movable carrier so as to be movable towards and away from the cutting drum, and includes yieldable urging means for urging the rotary member towards the cutting drum, characterised in that the movable carrier is formed by two independently movable parts supporting respectively the opposite ends of the rotary member, and that said urging means is adapted to urge each part towards the cutting drum so that the knives on the rotary member act with substantially equal pressure along their entire lengths while cutting the web.

Each part of the carrier is preferably provided

with separate means for urging it towards the cutting drum. Each urging means preferably comprises a fluid-powered actuator.

The bearings at the ends of the cutting head may be ball bearings allowing slight tilting of the head axis with respect to the carriers, thus accommodating any slight lack of parallelism between the cutting edge of each knife and the cooperating anvil surface on the cutting drum. Each carrier preferably comprises an arm which carries one of the cutting head bearings at one end and is pivoted at the other end at a position such that the line between the pivot and the bearing is substantially at right angles to the direction in which the force of the actuator on the carrier is applied, which should be substantially radial.

The fluid-powered actuator (or each actuator) may be pneumatic; for example with a diaphragm on which the air pressure acts to transmit a force to a connecting rod extending from the centre of the diaphragm. Alternatively, the actuator (or each actuator) may be powered by hydraulic fluid, for example oil, in which case the pressure of the hydraulic fluid may be derived from an air pressure source acting through an intensifier; between the intensifier and the or each actuator there is preferably a restrictor to restrict the flow of hydraulic fluid at least in the direction towards the actuator, and preferably only in that direction.

Examples of cutting heads according to this invention are shown in the accompanying diagrammatic drawings. In these drawings, Figures 1 and 2 are diagrammatic views of cutting heads using respectively pneumatic and hydraulic actuators; Figure 3 shows a more complete design of a different head; Figure 4 is a longitudinal section through part of the cutting head; and Figure 5 is an enlarged cross-section on the line V—V in Figure 4.

Figure 1 shows part of a cutting drum 10 around which a filter attachment web is to be conveyed prior to cutting by means of a cutting head 11. The cutting head comprises a drum-like member 12 formed with, for example, five circumferentially spaced slots 13 containing knives 14.

Each knife 14 is capable of pivoting slightly with respect to the member 12 about a fulcrum 15; the knives are retained on the drum by flanged end plates 16 and 17.

A drive shaft 18 for the cutting head is mounted in ball bearings 19 and 20 within two separate carrier members 21 and 22. The position of each carrier member is controlled by a pneumatic actuator including a connecting rod 25 or 26 which is connected to the respective carrier member and to a diaphragm 27 or 28 in a surrounding cylindrical casing 23 or 24. Air at a controlled pressure is supplied to the actuators, on the side of the diaphragm opposite to the connecting rod, through a pipe 29 or 30 from a controllable source 31; the air pressure supplied to the respective cylinders may be separately controllable.

Control of the air pressure allows the cutting head to be moved towards the drum 10 through a variable distance. During use, this distance is set so that there is an appropriate amount of inter-

ference between each knife and the cutting drum during cutting, giving a cutting force dependent partly on the air pressure in the actuators and partly on the mass of the cutting head and the associated parts whose inertia will determine the force on the knife as they are moved slightly away from the cutting drum 10 during cutting. The mass of the cutting head and associated parts is preferably as small as possible to allow the cutting force to be determined to the greatest possible extent by the air pressure.

Conventional ball bearings permit slight tilting motion of the shaft with respect to the surrounding carrier. Such tilting motion in the present invention may be sufficient to allow the cutting head to accommodate any initial lack of parallelism between the cutting edge of each knife and the cooperating anvil surface on the cutting drum. In that case, each knife may be non-pivotably secured to the member 12, possibly with a resilient backing.

In the alternative arrangement shown in Figure 2, a cutting head 40 comprises a drum-like member 41 carrying knives 42. At each end of the cutting head there is a carrier member in the form of an arm 43 which is approximately tangential to the drum 45 and is pivoted by a pin 44 to a fixed framework (not shown) so that the cutting head is free to move towards and away from a cutting drum 45 around which a filter web attachment 46 passes in order to be cut at regular intervals.

Each of the carrier arms 43 is pivoted to an hydraulic actuator 47 by a pivot pin 48. The actuator comprises a cylinder 49 pivoted by a pin 50 to a fixed framework (not shown), a piston or diaphragm 51, and a connecting rod 52 which extends from the piston or diaphragm and is pivoted to the carrier 43 by a pin 48. Each of the actuators is powered by hydraulic fluid fed respectively through pipes 53 and 54 which meet at a junction 55 connected to a pressure intensifier 56 by a supply pipe 57. The pressure intensifier 56, which may be of any known type, includes a piston assembly 58 which separates the hydraulic fluid (contained in a smaller cylinder 59) from a larger diameter air chamber 60 into which compressed air is fed through an inlet pipe 61. In this way the hydraulic pressure is derived from air pressure, which can readily be obtained from a factory supply and need not be as great as the required hydraulic pressure. The air inlet 61 preferably includes a pressure control device of any known kind.

An adjustable restrictor 62 is included in the pipe 57. This may act bidirectionally, but is preferably unidirectional, allowing substantially unrestricted flow in one direction (from the junction 55 to the intensifier 56) and restricted flow in the reverse direction; an example of such a device is part FC1 made by Air Automation Ltd.

In place of the restrictor or other device 62 in the pipe 57 (or in addition thereto) a similar unidirectional or bi-directional restrictor may be fitted in each of the branch pipes 53 and 54.

An adjustable stop 63 is mounted on a station-

ary framework (not shown) to engage each lever 43 so as to limit movement of the cutting head in the direction towards the drum 45. In practice we have found that the stops 63 need not be set very accurately. They can be set so as to allow significant initial interference between the knives and the drum 45. However, a few seconds after the machine starts to run (during the usual slow start period), the cutting head moves away from the drum 45 and stabilises itself at a position in which there is just adequate interference to provide the necessary cutting force, which may typically be of the order of 120 pounds.

The pipes 53 and 54 are preferably resilient, or may include resilient sections, so that they can expand slightly to absorb the small surge of hydraulic fluid from the actuators during each cutting operation.

Each of the knives 42 on the cutting head is preferably resiliently mounted so that it can move radially into the drum 41 against the resistance of a backing spring, e.g. of elastomeric material, during each cut. Figures 4 and 5 show another possible arrangement.

The air pressure supplied to the intensifier 56 may be automatically controlled so as to increase as the machine speed decreases, thus moving the cutting head further towards the drum 10 during successive cuts; this increases the interference between the knife and drum and compensates for the lower inertia effect (slight movement back of cutting head during cutting) at low speeds of operation. The air pressure is preferably cut off or greatly reduced while the drum and the cutting head are running without web being in position on the drum; this saves unnecessary wear on the knives. A spring 64 in each cylinder 49 urges the piston 50 in the direction such as to lift the knives 42 clear of the drum 45.

Figure 3 shows a different arrangement which is basically like Figure 2. At each end of cutting head 65 there is a carrier arm (of which the near one is partly removed in Figure 3 for the sake of clarity) having ball bearings (not shown) supporting one end of a shaft 65A in the head 65. The arms 66 are both independently pivotally mounted on opposite ends of a pin 67.

Each arm 66 has an associated hydraulic actuator 68 (as in Figure 2), but unlike the arrangement shown in Figure 2, the cylinder of each actuator is rigidly mounted on a member 69 of which the near side is partly removed in the drawing to show the parts lying behind it. Each actuator has a piston rod carrying shoe 71 which engages in a slight recess in a hardened insert 72 in the corresponding arm 66. Hydraulic fluid under pressure is supplied to the actuator through pipe 73. In order to lift the cutting head slightly clear of the cutting drum (not shown) while the parts are rotating without web being fed between them, each arm 66 is engaged by a compression spring 74 carried by a part 75 of a fixed frame.

During use, the pin 67 is supported centrally in a socket in an upwardly extending lug 76 on a part

77 of a fixed frame. The pin is clamped in the socket by a central clamping arm 78 which is pivoted to the frame member 77 by a pin 79. At its other end the clamping arm 78 latches into a recess in the member 69 and is secured onto the latter by a bolt 80 which has its inner end pivoted to lugs 81 (on the member 69) by a pin 82. The bolt 80 passes through a longitudinal slot in the end of the arm 78, so that it can be swung clockwise off the arm once a nut 83 has been slackened. Thus the arm can be released to allow it to be swung anti-clockwise about its pivot 79 to release the pin 67. Furthermore, the member 69 is pivoted at each end (i.e. at positions beyond the respective ends of the cutting head 65) by coaxial pins 84; thus it can be moved clockwise about the pins 84 to carry the actuators away from the carrier arms 66 to allow the cutting head 65 to be removed.

Movement of the cutting head towards the cutting drum is limited by adjustable stops 75A engaging the arms 66.

Figures 4 and 5 show how each of five knives 85 may be resiliently mounted in slots in the cutting head 65. Only one end of the knife is shown in Figure 4, the other end being the same.

Each knife comprises a body 86 formed with a longitudinal groove in which a hardened cutting member 87 is secured, e.g. by brazing. At each end of the body 86 there is a flange 88 through which passes a screw 89 for securing the body in position. Below the body 86 there is a strip 90 of rubber-like material. This strip extends along the entire length of the body, apart from the flanges 88.

A spacer tube 91 around each screw 89 extends between the bottom of the groove containing the knife and a washer 92 engaged by the head 93 of the screw. The length of each tube 91 is such that, when the screw has been tightened, the rubber strip is precompressed to a predetermined extent. Thus the rubber strip provides a firm but resilient backing for the knife, allowing the knife to move inwards slightly during cutting, against the resistance of the rubber.

In any system according to this invention, there may be provision for slowly automatically increasing the fluid pressure to compensate for the decreasing sharpness of the knives.

Claims

1. A cutting head for a cigarette filter attachment machine, for cutting a filter attachment web (46) at regular intervals in cooperation with a cutting drum (45), comprising a rotary member (12; 41; 65) which carries one or more knives (14; 42; 85) and is itself mounted on a movable carrier (21; 22; 43; 66) so as to be movable towards and away from the cutting drum, and including yieldable urging means (23; 24; 47; 68) for urging the rotary member towards the cutting drum, characterised in that the movable carrier is formed by two independently movable parts (e.g. 21 and 22) supporting respectively the

opposite ends of the rotary member (12; 41; 65), and that said urging means is adapted to urge each part towards the cutting drum so that the knives (14; 42; 85) on the rotary member act with substantially equal pressure along their entire lengths while cutting the web.

2. A cutting head according to claim 1 in which there are separate urging means (e.g. 23 and 24) acting respectively on the two parts of the carrier.

3. A cutting head according to claim 2 in which each part of the carrier has a ball bearing or other bearing (19, 20) which supports the rotary member while allowing slight freedom for the axis of the rotary member to tilt with respect to the carriers.

4. A cutting head according to claim 3 in which each part of the carrier comprises an arm (43; 66) which has, at one end, a bearing supporting one end of the rotary member, and at the other end is pivotally mounted (at 44 or 67) to allow the rotary member to move towards and away from the cutting drum (45).

5. A cutting head according to claim 4 in which a line joining the pivot (44; 67) of each arm (43; 66) and the axis of the rotary member (41; 65) is substantially at right angles to the direction in which the force of each actuator (47; 68) on the corresponding arm is applied.

6. A cutting head according to any one of claims 1 to 5 in which the means for urging the carrier towards the cutting drum comprises at least one fluid-powered actuator (23, 24; 47; 68).

7. A cutting head according to claim 6, including a spring (74) for moving the rotary member (65) away from the cutting drum when no fluid pressure is supplied to the actuator or actuators (47; 68).

8. A cutting head according to claim 6 or claim 7 in which the actuator or each actuator (47; 68) is powered by hydraulic fluid.

9. A cutting head according to claim 8 in which the hydraulic fluid is fed to the actuator or actuators via a restrictor (62).

10. A cutting head according to claim 9 in which the restrictor (62) acts unidirectionally so as to allow substantially unrestricted flow of hydraulic fluid (or less restriction to the flow) in the direction away from the actuator or actuators.

11. A cutting head according to claim 9 or claim 10 in which the restrictor is adjustable.

12. A cutting head according to any one of claims 8 to 11 in which the hydraulic fluid pressure is derived from a source of air pressure via a pressure intensifier (56).

13. A cutting head according to any one of claims 8 to 12 in which at least one pipe conveying the hydraulic fluid to the actuator or actuators is flexible so as to be capable of expanding slightly under the effect of the hydraulic pressure.

14. A cutting head according to any one of claims 1 to 13 including means for automatically changing the fluid pressure during different periods of operation.

15. A cutting head according to any one of claims 1 to 14 in which the or each knife (14; 42; 85) is resiliently mounted.

Patentansprüche

1. Schneidkopf für eine Zigarettenfilteransetzmaschine zum Schneiden einer Filteransetzbahn (46) in regelmäßigen Abständen in Zusammenarbeit mit einer Schneidtrommel (45), mit einem drehbaren Teil (12; 41; 65), das ein oder mehrere Messer (14; 42; 85) trägt und an einem beweglichen Träger (21; 22, 43; 66) befestigt ist, um auf die Schneidtrommel zu und von dieser weg bewegbar zu sein, und einer nachgiebigen Druckeinrichtung (23; 24; 47; 68) zum Drücken des drehbaren Teils auf die Schneidtrommel zu, dadurch gekennzeichnet, daß der bewegliche Träger von zwei unabhängig bewegbaren Elementen (zB 21 und 22) gebildet wird, die jeweils die entgegengesetzten Enden des drehbaren Teils (12; 41; 65) abstützen, und daß durch die Druckeinrichtung jedes Element in Richtung der Schneidtrommel drückbar ist, so daß die Messer (14; 42; 85) am drehbaren Teil während des Schneidens der Bahn mit im wesentlichen gleichem Druck über ihrer gesamten Länge wirken.

2. Schneidkopf nach Anspruch 1, dadurch gekennzeichnet, daß getrennte Druckeinrichtungen (zB 23 und 24) vorgesehen sind, die jeweils auf die beiden Elemente des Trägers wirken.

3. Schneidkopf nach Anspruch 2, dadurch gekennzeichnet, daß jedes Element des Trägers ein Kugellager oder anderes Lager (19, 20) besitzt, das das drehbare Teil abstützt und hierbei der Achse des drehbaren Teils eine geringe Freiheit gestattet, bezüglich des Trägers zu kippen.

4. Schneidkopf nach Anspruch 3, dadurch gekennzeichnet, daß jedes Element des Trägers einen Arm einen Arm (43; 66) umfaßt, der an einem Ende ein Lager zum Abstützen eines Endes des drehbaren Teils besitzt und am anderen Ende (bei 44 oder 67) schwenkbar gelagert ist, damit das drehbare Teil sich zu und weg von der Schneidtrommel (45) bewegen kann.

5. Schneidkopf nach Anspruch 4, dadurch gekennzeichnet, daß eine Linie, die den Schwenkpunkt (44; 67) jedes Arms (43; 66) und die Achse des drehbaren Teils (41; 65) verbindet, im wesentlichen im rechten Winkel zu der Richtung liegt, in der die Kraft jeder Betätigungseinrichtung (47; 68) am entsprechenden Arm angelegt wird.

6. Schneidkopf nach einem der Ansprüche 1—5, dadurch gekennzeichnet, daß die Druckeinrichtung zum Drücken des Trägers in Richtung der Schneidtrommel mindestens eine strömungsmittelbetrieene Betätigungseinrichtung (23, 24; 47, 68) enthält.

7. Schneidkopf nach Anspruch 6, gekennzeichnet durch eine Feder (74) zum Bewegen des drehbaren Teils (65) weg von der Schneidtrommel, wenn der oder den Betätigungs-

einrichtungen (47, 68) kein Strömungsmittel zugeführt wird.

8. Schneidkopf nach Anspruch 6 oder 7, dadurch gekennzeichnet, daß die oder jede Betätigungseinrichtung (47; 68) durch ein Hydraulikmittel betrieben wird.

9. Schneidkopf nach Anspruch 8, dadurch gekennzeichnet, daß das Hydraulikmittel der Betätigungseinrichtung oder den Betätigungseinrichtungen über eine Drossel (62) zugeführt wird.

10. Schneidkopf nach Anspruch 9, dadurch gekennzeichnet, daß die Drossel (62) nur in eine Richtung wirkt, um in Richtung weg von der Betätigungseinrichtung oder den Betätigungseinrichtungen einen im wesentlichen ungedrosselten Hydraulikmittelstrom (oder geringere Drosselung des Stroms) zu erlauben.

11. Schneidkopf nach Anspruch 9 oder 10, dadurch gekennzeichnet, daß die Drossel einstellbar ist.

12. Schneidkopf nach einem der Ansprüche 8—11, dadurch gekennzeichnet, daß der Hydraulikmitteldruck aus einer Druckluftquelle über einen Druckverstärker (56) abgeleitet wird.

13. Schneidkopf nach einem der Ansprüche 8—12, dadurch gekennzeichnet, daß zumindest eine der Betätigungseinrichtung oder den Betätigungseinrichtungen Hydraulikmittel zuführende Rohrleitung elastisch ist, um sich unter der Wirkung des Hydraulikdrucks leicht ausdehnen zu können.

14. Schneidkopf nach einem der Ansprüche 1—13, gekennzeichnet durch eine Einrichtung zum automatischen Verändern des Strömungsmitteldrucks während unterschiedlicher Betriebsperioden.

15. Schneidkopf nach einem der Ansprüche 1—14, dadurch gekennzeichnet, daß das oder jedes Messer (14; 42; 85) nachgiebig gelagert ist.

Revendications

1. Tête de coupe pour machine de fixation de filtres pour cigarettes, pour découper un ruban de fixation de filtre (46), à intervalles réguliers, en coopération avec un tambour de coupe (45), comprenant un élément rotatif (12, 41, 65) qui porte un ou plusieurs couteaux (14; 42; 85) et qui lui-même monté sur un support mobile (21; 22; 43; 66) de manière à être mobile vers et à partir du tambour de coupe, et comprenant des moyens de sollicitation flexibles (23; 24; 47; 68) pour solliciter l'élément rotatif vers le tambour de coupe, caractérisé en ce que le support mobile est formé de deux parties mobiles indépendantes (par exemple 21 et 22), supportant respectivement les extrémités opposées de l'élément rotatif (12; 41; 65) et lesdits moyens de sollicitation sont concus de manière à solliciter chaque partie vers le tambour de coupe afin que les couteaux (14; 42; 85) de l'élément rotatif agissant selon une pression sensiblement égale sur toute leur longueur, lors de la découpe du ruban.

2. Tête de coupe selon la revendication 1, dans laquelle il existe des moyens de sollicitation séparés (par exemple 23 et 24) qui agissent respectivement sur les deux parties du support.

3. Tête de coupe selon la revendication 2, dans laquelle chaque partie du support comporte un palier à billes ou un autre palier (19; 20) qui supporte l'élément rotatif tout en permettant une légère liberté pour permettre à l'axe de l'élément rotatif d'osciller par rapport aux supports.

4. Tête de coupe selon la revendication 3, dans laquelle chaque partie du support comporte un bras (43; 66) qui comporte à une extrémité, un palier supportant une extrémité de l'élément rotatif et qui, à l'autre extrémité, est monté à rotation (en 47 ou 67), de manière à permettre à l'élément rotatif de se déplacer vers et à partir du tambour de coupe (45).

5. Tête de coupe selon la revendication 4, dans laquelle une ligne joignant l'axe (44; 67) de chaque bras (43; 66) et l'axe de l'élément rotatif (41, 65), est sensiblement perpendiculaire à la direction d'application de la force de chaque vérin (47; 68), sur le bras correspondant.

6. Tête de coupe selon l'une quelconque des revendications 1 à 5, dans laquelle les moyens pour solliciter le support vers le tambour de coupe comprennent au moins un vérin à commande par fluide (23; 24; 47; 68).

7. Tête de coupe selon la revendication 6, comprenant un ressort (74) pour déplacer l'élément rotatif (65) à partir du tambour de coupe, lorsqu'aucune pression de fluide n'est délivrée au vérin ou aux vérins (47; 68).

8. Tête de coupe selon la revendication 6 ou la

revendication 7, dans laquelle le vérin ou chaque vérin (47, 68), est actionné par un fluide hydraulique.

9. Tête de coupe selon la revendication 8, dans laquelle le fluide hydraulique est délivré au vérin ou aux vérins par l'intermédiaire d'un limiteur de débit (62).

10. Tête de coupe selon la revendication 9, dans laquelle le limiteur de débit (62) agit de façon unidirectionnelle de manière à permettre un débit sensiblement non limité de fluide hydraulique (ou une limitation réduite du débit dans une direction partant du vérin ou des vérins).

11. Tête de coupe selon la revendication 9 ou la revendication 10 dans laquelle le limiteur de débit est réglable.

12. Tête de coupe selon l'une quelconque des revendications 8 à 11, dans laquelle la pression du fluide hydraulique est obtenue à partir d'une source de pression d'air, par l'intermédiaire d'un amplificateur de pression (56).

13. Tête de coupe selon l'une quelconque des revendications 8 à 12, dans laquelle au moins une conduite amenant du fluide hydraulique au vérin ou aux vérins, est flexible de manière à pouvoir se dilater légèrement sous l'effet de la pression.

14. Tête de coupe selon l'une quelconque des revendications 1 à 13, qui comprend des moyens pour modifier automatiquement la pression du fluide pendant différentes périodes de fonctionnement.

15. Tête de coupe selon l'une quelconque des revendications 1 à 14, dans laquelle le ou chaque couteau (14; 42; 85) est monté élastiquement.

40

45

50

55

60

65

6



