

**EUROPEAN PATENT SPECIFICATION**

- ④ Date of publication of patent specification: **20.08.86**      ⑤ Int. Cl.<sup>4</sup>: **C 06 B 23/00, C 06 B 25/00**  
⑥ Application number: **82302633.1**  
⑦ Date of filing: **21.05.82**

⑧ **Gelatinized highly explosive composition and method of preparation.**

⑨ Priority: **01.06.81 US 268559**

⑩ Date of publication of application:  
**22.12.82 Bulletin 82/51**

⑪ Publication of the grant of the patent:  
**20.08.86 Bulletin 86/34**

⑫ Designated Contracting States:  
**CH DE FR GB IT LI SE**

⑬ References cited:  
**US-A-2 159 973**  
**US-A-3 423 256**  
**US-A-3 723 208**  
**US-A-3 821 041**  
**US-A-3 844 856**

⑭ Proprietor: **IRECO INCORPORATED**  
**Eleventh Floor Crossroads Tower**  
**Salt Lake City Utah 84144 (US)**

⑮ Inventor: **Cartwright, Richard Vance**  
**R.D.4, Box 93B Coykendall Road**  
**Sussex New Jersey (US)**  
Inventor: **Lees, Ronald Douglas**  
**Rt.1, 379 DD**  
**Bartlesville Oklahoma 74003 (US)**

⑯ Representative: **Ben-Nathan, Laurence Albert**  
**et al**  
**c/o MICHAEL BURNSIDE & PARTNERS 2**  
**Serjeants' Inn Fleet Street**  
**London EC4Y 1HL (GB)**


**EP 0 067 560 B1**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European patent convention).


## Description

This invention relates generally to the preparation of gelatinized high explosives. It relates particularly to the use of compatibility additives in explosive formulations which include a combination of metriol trinitrate and certain liquid nitrated polyols, and especially diethylene glycol dinitrate, as a replacement for nitroglycerine.


Gelation of nitroglycerine by nitrocellulose is easily accomplished and has long been standard practice in dynamite manufacture. However, it is desirable to replace nitroglycerine in dynamite with another component because of the notorious ability of nitroglycerine to produce headaches. A mixture of metriol trinitrate and diethylene glycol dinitrate has been found to be a very promising replacement for nitroglycerine in terms of ease of production, explosive performance and cost. US—A—3423256 discloses an explosive sensitizer composition wherein trimethylolethane trinitrate decreases the impact-sensitivity of the composition as compared to use of the liquid nitrated polyol alone while not decreasing the detonator sensitivity. However, gelation of the combination of metriol trinitrate and diethylene glycol dinitrate by nitrocellulose does not proceed at an acceptable rate under reasonable conditions of dynamite manufacture. US—A—2159973 discloses a process for adding an amide, preferably dimethylformamide, to an organic nitrate to accelerate gelatinization. This reference discloses as organic nitrates the use of nitroglycerine and tetranitroglycerine. US—A—2159973 discloses the acceleration of gelatinization by incorporating with the nitroglycerine an acid amide of a monobasic fatty acid or an alkyl derivative thereof. The acid amide disclosed has the formula



in which  $\text{R}_1$ ,  $\text{R}_2$ , and  $\text{R}_3$  consist either of hydrogen or an alkyl radical. For example, formamide and its alkyl derivatives are known to be desirable accelerants, in which case,  $\text{R}_1$  represents hydrogen. When  $\text{R}_1$  represents a  $\text{CH}_3$  group the accelerant will be acetamide or an alkyl derivative thereof.  $\text{R}_2$  and  $\text{R}_3$ , likewise, may represent either hydrogen or alkyl groups. Examples of compounds known to be advantageous for use as gelatinization accelerants include formamide ( $\text{H—CO—NH}_2$ ), acetamide ( $\text{CH}_3\text{—CO—NH}_2$ ), monomethylformamide



dimethylformamide



dimethylacetamide ( $\text{CH}_3\text{—CO—N—(CH}_3)_2$ ), diacetamide ( $(\text{CH}_3\text{—CO})_2\text{—NH}$ ), propionamide, butylamide, and many others. From this group, dimethylformamide is the preferred gelatinization accelerant.

Gelation of the nitrate ester in dynamite type formulation has a twofold purpose. First, the gel forms a hydrophobic protective coating on water sensitive solids such as ammonium nitrate and sodium nitrate. This coating effect is essential for imparting the water resistance which is needed in wet environments. Secondly, gelation is necessary to prevent separation of the liquid nitrate ester from the rest of the explosive. Separation would greatly reduce the explosive performance and could possibly produce a serious handling hazard because of contamination of the packaging material by the nitrate ester.

This invention provides a gelatinized high explosive composition comprising sensitizer composition gelatinized by nitrocellulose, said sensitizer composition consisting essentially of from 5 to 95% of a liquid nitrated polyol derived from an aliphatic polyol having from 2 to 6 alcoholic hydroxyl groups and from 2 to 10 carbon atoms, and from 95 to 5% of metriol trinitrate (trimethylol ethane trinitrate), characterized in that said composition includes between 0.05 and 0.20% by weight, based on said composition, of a polar compatibility additive selected from dimethylformamide, formamide, N,N-dimethylacetamide, N-methyl-2-pyrrolidone and dimethylsulfoxide.

This invention also provides a process of enhancing compatibility between nitrocellulose and an explosive sensitizer composition consisting essentially of from 5 to 95% of a liquid nitrated polyol derived

from an aliphatic polyol having from 2 to 6 alcoholic hydroxyl groups and from 2 to 10 carbon atoms, and from 95 to 5% of metriol trinitrate (trimethylol ethane trinitrate) characterized by adding between 0.05 and 0.20% by weight, of a polar compatibility additive selected from dimethylformamide, formamide, N,N-dimethylacetamide, N-methyl-2-pyrrolidone and dimethylsulfoxide. The resulting product has improved consistency and superior water resistance.

If desired, an inorganic oxidizer salt can be incorporated in the formulation.

In this invention, between 0.05% and 0.20% of the compatibility additive, preferably dimethylformamide, is required for dependable enhancement of gelation. Amounts of dimethylformamide in excess of 0.20% would not significantly improve gelation. In fact, amounts in excess of 0.20% would make water resistance worse because of the hydrophilic nature of dimethylformamide. Other polar additives can be used in place of dimethylformamide including formamide, N,N-dimethylacetamide, N-methyl 2-pyrrolidone and dimethylsulfoxide.

In the composition of this invention, since the metriol trinitrate is more impact sensitive than diethylene glycol dinitrate, the addition of diethylene glycol dinitrate actually lowers the overall impact sensitivity as compared to the disclosure of US—A—3423256, wherein the metriol trinitrate lessens the shock sensitivity of the nitrated polyol. The metriol trinitrate and diethylene glycol dinitrate are present in ratios between 95:5 and 5:95. Preferably the ratio should be between 40:60 and 60:40. More preferably, the metriol trinitrate and the diethylene glycol dinitrate are present in a ratio of about 50:50.

In the process of this invention, for best results, the nitrate esters, dimethylformamide and nitrocellulose should first be premixed separately from the other solid ingredients.

Although there are a number of nitrocellulose solvents, such as acetone and ethyl acetate, which can be added to a mixture of nitrocellulose and nitrate esters to induce gelation, these solvents are not included in the present invention. The quantities required would be high enough to result in a decrease in the explosive sensitivity of the dynamite to an unacceptably low level. The process of this invention will allow dynamite-type formulations which do not contain nitroglycerine, to be kept under water or in a wet environment between 2 and 20 times longer than dynamite-type formulations which do contain nitroglycerine.

The following examples, in the opinion of the inventors, represent preferred embodiments of this invention.

Examples 1—3

The amounts of ingredients used in these examples are based on the production of 5000 gram experimental batches. 500 grams each of metriol trinitrate and diethylene glycol dinitrate were first mixed with 25 grams of dynamite-grade nitrocellulose and the amount of dimethylformamide shown in Table I, below, for 5 minutes. The following dry ingredients were mixed together in a separate container: 1,239.5 grams of sodium nitrate, screened through a six mesh screen (33 mm opening); 143 grams balsa dust; 143 grams tamarind seed flour; 21.5 grams powdered chalk; and the amount of ammonium nitrate shown in Table I after being passed through a 10 mesh screen (1.7 mm opening). In the process of this invention, the liquid and dry ingredients were then mixed together for approximately 5 minutes. The mixtures were then packed into waxed paper shells, 203.2 mm in length and having a diameter of 31.75 mm.

The water resistance of the product was determined by finding the maximum length of time that a cartridge could be kept under 3.5 m of water and still be detonated by a number 6 blasting cap. The results of those tests are shown in Table I.

TABLE I

Example No.	Dimethylformamide,		Ammonium nitrate grams	Longest time for detonation, hours	Shortest time for failure, hours
	Grams	Percent			
Control	0	0	2428	1*	6
1	2.5	.05	2425.5	24	48
2	5.0	.10	2423	72	96
3	7.5	.15	2420.5	96	120*

\* Estimate.

These results show the effect of dimethylformamide as a compatibility additive in improving the water resistance of the formulations shown in Table I.

Examples 4—7

A series of experiments were conducted which disclosed an improvement in semi-gelatin consistency

with increasing use of dimethylformamide. A series of four 7,000 gram mixtures were prepared, each mixture containing equal amounts of diethylene glycol dinitrate and metriol trinitrate. In addition, 0.3% dynamite-grade nitrocellulose, 50% ammonium nitrate, screened through a 24 mesh screen (0.7 mm opening), 16.2% sodium nitrate screened through a 10 mesh screen (1.7 mm opening), 0.5% wood flour, 1.5% balsa dust, 2% tamarind flour, 10% sodium chloride, 0.5% powdered chalk, and 1.0% Alcoa 1651 aluminum was used. The amount of dimethylformamide in each test is shown in Table II.

The nitrate esters and dimethylformamide were first combined, and then nitrocellulose was then added and mixed for five minutes. The solid ingredients, with the exception of aluminum, were added slowly while stirring. The aluminum was then added and combined thoroughly by mixing for three minutes. The formulation was then packed into paper shells, each having a diameter of 31.75 mm.

Each cartridge shell was then unrolled, and a 76.2 mm length of the explosive material was cut. In the test, one end of each 76.2 mm stick of explosive was pushed against a hard surface until it assumed the shape of a mushroom. It was then inverted. If the mushroom disintegrated, the semi-gelatin quality was considered to be poor. Semi-gelatin quality was considered to be good if the integrity of the mushroom shape is maintained.

The results which were obtained are shown in Table II.

TABLE II

Example No.	Metriol trinitrate %	Diethylene glycol dinitrate %	Dimethylformamide %	Semi-gelatin quality
Control	9	9	0	Poor
4	8.975	8.975	0.05	Fair
5	8.950	8.950	0.10	Good
6	8.900	8.900	0.20	Good

These results demonstrate that the addition of dimethylformamide improves the consistency of the packed material. In turn, good consistency usually results in enhanced water resistance.

Gelation of a liquid polymer requires substantial polymer-solvent interaction. The polymer and solvent interact well if their polarities are well matched. It is believed that nitroglycerine and nitrocellulose have comparable polarities while the metriol trinitrate/diethylene glycol dinitrate mixture is appreciably less polar than nitrocellulose. However, dimethylformamide is a highly polar solvent as well as a solvent for nitrocellulose. Therefore, the addition of dimethylformamide to the metriol trinitrate/diethylene glycol dinitrate mixture can increase its overall average polarity to a point where it is comparable to that of nitrocellulose. In effect, the addition of dimethylformamide increases the affinity of nitrocellulose for the metriol trinitrate/diethylene glycol dinitrate combination and performs as a compatibility additive for these two constituents.

Dynamite-type formulations manufactured by the process of this invention are expected to have significant utility as a substitute for conventional dynamite, i.e., in mining, tunneling, ditching, construction, seismic exploration and other applications.

### Claims

1. A gelatinized high explosive composition comprising sensitizer composition gelatinized by nitrocellulose, said sensitizer composition consisting essentially of from 5 to 95% of a liquid nitrated polyol derived from an aliphatic polyol having from 2 to 6 alcoholic hydroxyl groups and from 2 to 10 carbon atoms, and from 95 to 5% of metriol trinitrate (trimethylol ethane trinitrate), characterized in that said composition includes between 0.05 and 0.20% by weight, based on said composition, of a polar compatibility additive selected from dimethylformamide, formamide, N,N-dimethylacetamide, N-methyl-2-pyrrolidone and dimethylsulfoxide.

2. An explosive composition in accordance with Claim 1 characterized by including in addition an inorganic oxidizer salt.

3. An explosive composition in accordance with Claim 1 or 2 characterized in that said nitrated polyol is diethylene glycol dinitrate and said diethylene glycol dinitrate and said metriol trinitrate are present in a ratio of between 60:40 and 40:60.

4. A process of enhancing compatibility between nitrocellulose and an explosive sensitizer composition consisting essentially of from 5 to 95% of a liquid nitrated polyol derived from an aliphatic polyol having from 2 to 6 alcoholic hydroxyl groups and from 2 to 10 carbon atoms, and from 95 to 5% of metriol trinitrate (trimethylol ethane trinitrate) characterized by adding between 0.05 and 0.20% by weight,

of a polar compatibility additive selected from dimethylformamide, formamide, N,N-dimethylacetamide, N-methyl-2-pyrrolidone and dimethylsulfoxide.

**Patentansprüche**

5

1. Gelatinierte Brisantsprengstoffzusammensetzung, enthaltend eine mit Nitrocellulose gelatinierte Sensibilisatorzusammensetzung, welche im wesentlichen aus 5 bis 95% eines flüssigen, nitrierten, sich von einem aliphatischen Polyol mit 2 bis 6 alkoholischen Hydroxylgruppen und 2 bis 10 Kohlenstoffatomen ableitenden Polyols und 95 bis 5% Metrioltrinitrat (Trimethyloläthantrinitrat) besteht, dadurch gekennzeichnet, dass besagte Zusammensetzung zwischen 0,05 und 0,20 Gew.-%, auf diese bezogen, eines polaren Verträglichkeitszusatzes enthält, den man unter Dimethylformamid, Formamid, N,N-Dimethylacetamid, N-Methyl-2-pyrrolidon und Dimethylsulfoxyd auswählt.

10

2. Sprengstoffzusammensetzung nach Anspruch 1, dadurch gekennzeichnet, dass sie ferner ein anorganisches Sauerstoffträgersalz enthält.

15

3. Sprengstoffzusammensetzung nach Anspruch 1 oder 2, dadurch gekennzeichnet, dass als solches nitriertes Polyol Diäthylenglykoldinitrat vorliegt und dessen Verhältnis zu besagtem Metrioltrinitrat zwischen 60:40 und 40:60 liegt.

20

4. Verfahren zur Erhöhung der Verträglichkeit zwischen Nitrocellulose und einer im wesentlichen aus 5 bis 95% eines flüssigen, nitrierten, sich von einem aliphatischen Polyol mit 2 bis 6 alkoholischen Hydroxylgruppen und 2 bis 10 Kohlenstoffatomen ableitenden Polyols und 95 bis 5% Metrioltrinitrat (Trimethyloläthantrinitrat) bestehenden Sprengstoffsensibilisatorzusammensetzung, dadurch gekennzeichnet, dass man zwischen 0,05 und 0,20 Gew.-% eines polaren, unter Dimethylformamid, Formamid, N,N-Dimethylacetamid, N-Methyl-2-pyrrolidon und Dimethylsulfoxyd ausgewählten Verträglichkeitszusatzes dazugibt.

25

**Revendications**

30

1. Composition d'explosif brisant gélatinisée comprenant une composition de sensibilisant gélatinisée par la nitrocellulose, cette composition de sensibilisant étant essentiellement constituée de 5 à 95% d'un polyol nitraté liquide obtenu à partir d'un polyol aliphatique ayant de 2 à 6 groupes hydroxyle alcooliques et de 2 à 10 atomes de carbone, et de 95 à 5% de trinitrate de métriol (trinitrate de triméthylol étane), caractérisée en ce que cette composition contient entre 0,05 et 0,20% en poids, par rapport à cette composition, d'un additif de compatibilité polaire choisi parmi le diméthylformamide, le formamide, le N,N-diméthylacétamide, la N-méthyl-2-pyrrolidone et le sulfoxyde de diméthyle.

35

2. Composition d'explosif suivant la revendication 1, caractérisée en ce qu'elle contient en outre un sel oxydant minéral.

40

3. Composition d'explosif suivant la revendication 1 ou 2, caractérisée en ce que le polyol nitraté est le dinitrate de diéthylène glycol et en ce que ce dinitrate de diéthylène glycol et le trinitrate de métriol sont présents dans un rapport entre 60:40 et 40:60.

45

4. Procédé pour augmenter la compatibilité entre la nitrocellulose et une composition de sensibilisant d'explosif essentiellement constitué de 5 à 95% d'un polyol nitraté liquide obtenu à partir d'un polyol aliphatique ayant de 2 à 6 groupes hydroxyle alcooliques et de 2 à 10 atomes de carbone et de 95 à 5% de trinitrate de métriol (trinitrate de triméthylol éthane), caractérisé en ce qu'on ajoute entre 0,05 et 0,20% en poids d'un additif de compatibilité polaire choisi parmi le diméthylformamide, le formamide, le N,N-diméthylacétamide, la N-méthyl-2-pyrrolidone et le sulfoxyde de diméthyle.

50

55

60

65