

⑫ **EUROPEAN PATENT SPECIFICATION**

- ⑬ Date of publication of patent specification: **17.12.86** ⑭ Int. Cl.⁴: **D 04 H 3/10**
⑮ Application number: **82105651.2**
⑯ Date of filing: **25.06.82**

⑰ **A stitch bonded fabric for reinforcing coated abrasive backings.**

- | | |
|---|---|
| ⑱ Priority: 31.08.81 US 297538 | ⑲ Proprietor: NORTON COMPANY
1 New Bond Street
Worcester Massachusetts 01606 (US) |
| ⑳ Date of publication of application:
09.03.83 Bulletin 83/10 | ㉑ Inventor: Darjee, Dhiraj Haribhaj
1 Summit Park
Ballston Lake New York (US) |
| ㉒ Publication of the grant of the patent:
17.12.86 Bulletin 86/51 | ㉓ Representative: Baillie, Iain Cameron et al
c/o Ladas & Parry Isartorplatz 5
D-8000 München 2 (DE) |
| ㉔ Designated Contracting States:
AT CH DE FR GB IT LI SE | |
| ㉕ References cited:
FR-A-2 228 876 | |

EP 0 073 313 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European patent convention).

Description

The present invention relates to stitch-bonded fabrics which are especially suitable for reinforcing the backings of coated abrasives.

5 Stitch-bonded fabrics in general have been known for at least the last twenty years. Furthermore, although stitch bonded fabrics have been used primarily for apparel, draperies, and similar non-industrial purposes, there have been some previous applications to industrial products. French Patent FR—A—
2 228 876, for example, teaches the use of such fabrics to reinforce rubber or polymer products, such as
10 conveyor belts, pipes, and tire carcasses. However, it has not been appreciated that such fabrics could confer special advantages when used as the reinforcing substrate for coated abrasive backings. Thus no fabrics explicitly suitable for such purposes were known to the applicant from prior art.

It has now been found that properly designed stitch bonded fabrics can serve very effectively to reinforce coated abrasive backings and overcome the following disadvantages associated with woven backings: (1) ready susceptibility to elongation under tensile stretch, as a result of removing some of the
15 yarn crimp inherently necessary in weaving, where the yarns which furnish the primary reinforcing strength to the backing must follow an undulatory path around other yarns in order to hold the fabric together; (2), ready susceptibility to destructive wear at the "knuckles", i.e., the points where yarns curve most sharply to pass over other yarns, and therefore are both stressed by curvature and closer to the surface of the coated abrasive where wear is more likely; and (3) the cost associated with the slow speed of
20 weaving, even with automatic looms.

In order to produce stitch-bonded fabric in large volume at low cost, it is necessary to use one of the special machines designed for such purposes. A wide variety of machines are available commercially, including those supplied under the trade name Malimo (short for MALIMO Type Malimo) by Unitechna Aushandelgesellschaft mbH of Karl Marx Stadt, DDR, those with the trade name Weft/Loc made by Liba
25 Maschinenfabrik GmbH, D-8674 Naila, FRG, and Raschel knitting machines. (A list of suppliers of Raschel machines is given on pages 31—38 of Volume 43, No. 35 of Knitting Times, the official publication of the National Knitted Outerwear Assoc., 51 Madison Avenue, New York, New York, 10010.)

These commercially available machines are normally limited to a maximum number of about one warp yarn per millimeter (mm) of fabric width. This limitation is believed to be necessary to accommodate a
30 sufficient number of stitch or loop forming devices in the machine to form bonds across the entire width of the fabric substantially simultaneously. Because conventional woven fabrics for coated abrasives mostly contain at least twice this many warp yarns, no simple adaptation of the woven fabric designs to the requirements of stitch bonding machines was feasible.

It should be noted that it is possible to feed more than one warp yarn through each of the machine
35 openings for such yarns provided in many of these machines. However, any such multiplicity of yarns fed through one opening will be bonded by the machine as if it were a single yarn. Thus the practical effect achieved by a multiplicity of yarns fed through one opening is essentially the same as that from using one plied yarn with a number of plies equal to the multiplicity of single unplied yarns. In both woven and stitch bonded fabrics, the results achieved from use of such plied yarns are not generally as satisfactory for fabric
40 cover and for the desirable combination of strength with flexibility as can be achieved with evenly spaced finer yarns which give the same total warp tensile strength.

As noted below, the preferred machines for the fabrics of the present invention are those of the Malimo type. A publication by the manufacturer of Malimo machines, VEB Nähwirkmaschinenbau Malimo, Karl Marx Stadt, DDR, No. 24-2/3, "Sewing-Knitting Machines MALIMO Technical Possibilities and
45 Technology", Part 2, (identified at the end as Ag 07/010/77. III 3 1 74/8900/77 1,0), describes the general range of operating conditions possible for machines of this particular type. The description of mechanical characteristics of Malimo machines given immediately below condenses from this publication those characteristics believed by the applicant to be most relevant to design of fabrics suitable for use in coated abrasives. In this condensation, the term "weft" has been changed to "fill" in accordance with common
50 United States practice, and the term "hook needle" has been shortened to "hook"; all other terms describing the mechanical parts of the machines have been taken directly from the referenced publication.

Malimo machines have three principal mechanical characteristics which limit the variety of fabric constructions available from them. The first of these limits is provided by a group of several matched mechanical structures which fix a maximum "gauge" or number of yarns per 25 mm of width for the warp
55 yarn and stitching yarn assemblies which can be used with the machine. Twelve possible gauges from 3 to 22 are available from the manufacturer.

The second of the principal mechanical limitations of the Malimo machine is its stitch length. This can be adjusted in 20 steps within a range of 0.7 to 5 mm. It should be noted that this nominal "stitch length" is actually the projected length in the direction of the warp yarns. When a tricot style stitch is used, as was the
60 case for the fabrics to be described here, the actual spatial orientation of the stitch is at a substantial angle to the warp yarns, and the actual length is correspondingly longer than the nominal length. In addition, because the stitch yarns form loops, the length of yarn consumed for each stitch is generally considerably longer than either the nominal or actual length. With the fabrics described below, stitch yarn length consumption was about four times warp yarn length consumption.

65 The third of the principal mechanical limitations of the machine is provided by the assemblies of hooks

which hold the fill yarns in tension until they can be stitched to the warp. Hook units are available in linear densities from 8 to 48 hooks per 25 mm. Under the normal conditions of use as contemplated by the instructions furnished by the manufacturer, no more than one bend of fill yarns around each hook is accommodated during fabric assembly operations.

5 It should be noted that it is an inherent characteristic of Malimo machines to lay fill yarns in two distinct groups of symmetric small angles on opposite sides of an imaginary line perpendicular to the warp yarn array. All fill yarns counts in this description are to be understood as including both of these fill yarns groups in the count.

The above referenced and incorporated Malimo publication gives some specifics of the construction of several fabrics suitable for other uses than coated abrasives. This is the largest such description of specific stitch-bonded fabrics known to applicant.

In accordance with the present invention, by careful selection and combination of particular types and sizes of yarn, and by the operation of commercially available machines outside the scope of the operating instructions furnished by their suppliers, it has been found possible to manufacture economical and effective fabrics for a wide variety of coated abrasives. In general, a satisfactory fabric will result if the warp yarn array has a tensile strength of at least 30 dekanewtons per centimeter of fabric width, the fill yarn array has a cover factor as defined below of at least 40%, and the stitching yarns have a tensile breaking strength of at least 0.5 dekanewtons each. For most purposes, this result is preferably attained by the use of warp arrays with yarns of high denier, high tenacity synthetic multifilament or glass in a number of at least 12 yarns per 25 mm of fabric width, fill yarn arrays of smaller denier texturized multifilament or staple synthetic yarn in a number of at least 64 per 25 mm of fabric length, and by fine denier stitch yarns with a breaking strength of at least 0.007 dekanewtons per denier.

Malimo machines with model numbers 14010 or 14011 were preferred for making the fabrics of the present invention. Liba machines and Raschel knitting machines make equally satisfactory fabrics but are limited to lower speeds of operation and thus are less economical.

It was considered desirable to provide reinforcing fabrics of my new type with tensile strengths at least equal to those of conventional coated abrasives with woven cloth substrates. Two of the most important classes of these conventional abrasives, commonly designated in the trade as X weight and Y weight, have tensile strengths of about 30 and 38 dekanewtons per centimeter (daN/cm) of width respectively. We have found that this level of tensile strength with stitch bonded fabrics can be achieved by using warp gauges from 12 to 22 with synthetic multifilament or glass yarns having breaking tenacities of at least 0.007 dekanewtons per denier. Using a coarser gauge can also achieve adequate tensile strength with high denier yarns.

Although high tenacity yarns are very effective in providing warp tensile strength, they provide relatively little cover or opportunity for facile mechanically aided adhesion of cloth finishing adhesives, which are needed to complete the final backings on which coated abrasives are to be made. I have found it possible to compensate for these deficiencies by using high linear densities of relatively small spun staple or textured multifilament fill yarns. The greater surface area per unit mass of these yarns, as compared with the warp yarns, provides superior possibilities for mechanical adhesion of the finishing adhesives and ready achievement of adequate cover, when combined with suitable processing techniques for the finishing.

An important feature of the invention, particularly useful for facilitating the achievement of adequate cover in the fabric, was our discovery that it was possible to produce fabrics having two or more fill yarns on each hook by operating outside the range of instructions furnished with the Malimo machine. If the machine gears were chosen so as to advance the fill yarn carrier, which is a mechanical part separate and distinct from the hook carriers, at half the minimum speed recommended by the manufacturer for the combination of hook spacing and number to fill yarns supplied, an average of two yarns would be retained by each hook. Alternatively, the speed of advance could be left the same, but the fill yarn carrier doubled in width. Similarly, advancing the carrier at one quarter of recommended speed or quadrupling its width would result in an average of four yarns retained per hook. Hooks 5 mm high were used for all constructions shown except those with 500 denier fill yarns; with these larger yarns and 7 mm size hooks gave better results. Medium size sliding needles and closing wires, 1.8 mm diameter stitching yarn guide holes, and round rather than oval retaining pins among the choices offered by the manufacturer were preferred for the fabrics shown. Both fill yarn carrier reeds and hook carriers with 32 openings per 25 mm were used for fabrics with 64 or 128 fill yarns per 25 mm, while carrier reeds and hook carriers with 24 openings per 25 mm were used for achieving 96 fill yarns per 25 mm.

Additional possibilities for adhesion and cover are provided by the stitch yarns. We have found synthetic multifilament yarns 77 to 244 dtex (70 to 220 denier) very satisfactory as stitch yarns for these fabrics. Aside from the resilience and flexibility needed in the stitch yarn to permit efficient operation of a stitch-bonding machine, the primary requisite from the stitch yarn for the ultimate coated abrasive is sufficient strength to resist rupture between the warp and fill arrays of yarns under use conditions. By experiment, 77 dtex (70 denier) polyester yarn with a breaking strength of at least 0.008 daN per denier was found to be adequate for most purposes. For coated abrasives to be used under extremely damage prone conditions, however, it was advantageous to use 122, 155, or even 244 dtex (110, 140, 220 denier) stitch yarns.

0 073 313

In general, shorter stitch lengths will give more uniform appearing fabrics, while longer stitch lengths will give more economy as a result of faster production speeds. For coated abrasive substrate fabrics, it has not been found advisable to use longer stitch lengths than 1.8 mm. The preferred range for most fabrics is 1.2 to 1.8 mm.

5 Each stitch normally forms a loop around only one warp yarn (unless more than one yarn is fed through a single opening as noted above), but the number of fill yarns inside a stitch loop can vary from none to several, depending on how many fill yarns happen to occupy the space inside the fixed stitch length. With long stitches and moderate fill yarn densities, a random pattern of short, relatively open spaces may often be observed in the fabric produced, as a result of greater or lesser than average number
10 of fill yarns being caught inside the loops of particular stitches. Within the limits described herein, this pattern has not been found to cause any difficulty in the coated abrasives produced with such fabrics as substrates.

Some non-limiting examples of specific fabric designs satisfactory for coated abrasives are shown in Table 1. All these fabrics were made with hook carriers having no more than 32 hooks per 25 mm.
15

20

25

30

35

40

45

50

55

60

65

TABLE 1
Some specific examples of stitch bonded fabrics useful for coated abrasive substrates

#	Fabric identification number	Warp array characteristics			Fill array characteristics			Stitch characteristics					
		Yarn fibre type	Yarn size ¹	Yarns per 25 mm	Tensile strength, daN/cm of width	Yarn fibre type	Yarn size ¹	Yarns per 25 mm	Tensile strength, daN/cm of width	Cover factor ²	Yarn fibre type	Yarn size ¹	Stitch length, mm
1		Polyester ³	1000/192	14	44	Polyester ⁴	170/33	64	15	40.7%	Polyester ⁵	77	1.2
2		Polyester ³	1300/192	14	57	Polyester ⁴	170/33	128	30	81.4%	Polyester ⁵	155	1.2
3		Polyester ³	840/140	18	48	Polyester ⁴	170/33	96	22	61.0%	Polyester ⁵	77	1.2
4		Polyester ³	1300/192	14	57	Polyester ⁶	443	96	48	90.0%	Polyester ⁷	166	1.2
5		Polyester ³	1300/192	14	57	Mixed ⁸	300	96	53	81.0%	Polyester ⁵	244	1.2
6		Polyvinyl alcohol ⁹	1000/200	14	44	Polyester ⁷	150/34	128	26	77.0%	Polyester ⁵	122	1.2
7		Polyvinyl alcohol ¹⁰	1200/200	14	62	Polyester ⁶	443	96	48	98.0%	Polyester ⁵	155	1.4
8		ECG-37 glass ¹¹	1207	14	30	Polyester ⁴	170/33	128	30	81.4%	Polyester ⁵	77	1.2
9		ECG-37 glass ¹¹	1207	14	30	Polyamide ¹²	500	64	53	70.0%	Polyester ⁵	244	1.2
10		ECH-25 glass ¹¹	1786	14	48	Mixed ⁸	300	96	53	81.0%	Polyester ⁵	244	1.8
11		Polyester ³	1300/192	14	57	Polyamide ¹²	500	64	53	70.0%	Polyester ⁵	244	1.2

corresponds to Example 1 of European Patent Application No. 81105516.9 filed July 14, 1981, (European Patent No. 45408). This application is accordingly limited to fabrics having a cover factor of greater than 40.7 percent.

1. The first number under this column give the yarn size in dtex. The number after the virgule (/), if any, gives the number of monofilaments in each yarn as specified by the manufacturer.
2. Cf. the specification for the method of calculating cover factor.
3. Type 68 Dacron (RTM) from DuPont was used.
4. Type 731 Texturized Fortrel (RTM) from Celanese was used.
5. Type 68 Dacron high-tenacity yarn from duPont was used.
6. Spun staple polyester, either duPont Type 54W or Celanese (RTM) Type 310 was used.
7. Type 56T Dacron texturized yarn from duPont was used.
8. A special yarn with a core of Dacron type 68L and an outer surface of spun cotton was used. About 30% of the total yarn weight was cotton.
9. Type 1225-7 Kuralon (RTM) from Kuraray Co. Ltd. (Japan) is used.
10. Type 1239 Kuralon from Kuraray Co. Ltd. (Japan) is used.
11. Yarn used was purchased from PPG Industries, Inc.
12. Type 439 Cordura (RTM) Nylon from duPont was used.

The cover factor for the full yarn array noted in Table 1 is the same as the value often called "fractional coverage" by others; i.e., the fraction of the total area enclosed within the borders of a sample of the fabric which is covered by the fill yarn array therein. In principle, this value could be easily calculated from a knowledge of the linear density and the diameter of the fill yarns: If n is the number of fill yarns per unit length of the fabric and d is the diameter of each yarn in the same units, the cover factor is $100nd\%$. In practice, measuring the diameter of yarn precisely is very difficult, and in conformance with common textile art practice, the cover factor used herein was determined by an indirect calculation making use of the density and dtex (denier) size of the yarn. (The mass m in grams of a one centimeter length of yarn is equal to the denier (D) divided by 9×10^5). The volume v in cubic centimeters of the same length of yarn is approximated as that of a cylinder of the same diameter, so that $v = (\pi d^2)/4$. By definition, the density $p = m/v$. Combining and rearranging these expressions gives % cover factor = $n(4D/90 \pi p)^{1/2}$.

The density of a yarn in turn depends on the fundamental density of the fibers which compose it and on how tightly the fibers are packed. The latter characteristic of the yarn is quantified as a packing fraction, which when multiplied by the fibers density gives the yarn density. The following values in gm/cm^3 for fiber density of the fill yarn fibers listed in Table 1 were taken: polyester, 1.3; cotton, 1.56; and polyamide, 1.14. Packing fractions taken were: textured polyamide, 0.80; textured polyester, 0.70; staple polyester, 0.59; and mixed yarn, 1.0.

It should be carefully noted that the calculations for cover factor noted above assume that the fill yarns are in position as laid out before stitching. Small variations from this value are expected after the fabric is stitched together. No attempt was made to calculate these latter variations, because they did not appear to affect the performance of coated abrasives made with the fabrics herein described as backing substrates. However, fabrics with fill cover factors of less than 40% as calculated above could not easily be finished suitably for receiving maker adhesive and grain coats in the process of making a coating abrasive with a conventionally continuous backing.

The fabrics specified in Table 1, or other fabrics constructed using the same principles, may be finished in a variety of ways to make suitable backings for coated abrasives. These backings in turn may be coated with any of the variety of maker adhesives, abrasive grits, and sizer adhesives, well known in the art. Some specific examples of these ways to use my invention are given below. The others will be readily apparent to those skilled in the art of manufacturing coated abrasives, upon considering the teachings herein in combination with those of the aforesaid copending application.

Example 1

Fabric of the construction with identification number 1 in Table 1 was used. This fabric was then saturated with a resin and acrylic latex composition to prepare it for frontfilling, backfilling, and coating with maker grain and size coat. A heat setting step is combined with the drying of the saturant. The fabric finishing steps will now be described in more detail.

Saturation and heat setting

Standard sizing rolls are employed to apply the following composition in the amount of 40 to 60 grams per square meter. The fill yarns side of the fabric was facing up.

Saturation composition.

Cymel (RTM) 482, available from American Cyanamid, a melamine-formaldehyde resin syrup, 80% solids, pH 8 to 9	160 parts
Beetle (RTM) 7238, available from American Cyanamid, a urea formaldehyde resin syrup, 65% solids	124 parts
water	120 parts
Aqueous solution containing 15% NH_4Cl and 24% 2-amino-2-methylpropanol	13 parts
5 to 7 parts pigment dispersions may be added to color backing	

Upon completion of the application of the saturant the fabric is dried on a tenter frame for at least 3 minutes in a hot air oven in which the temperature in the entry zone is 96°C ., and the temperature at the exit zone is 177°C . A tension of at least 3.5 Newtons per centimeter (N/cm) of width is maintained on the fabric during its travel through the oven. This process not only dries the saturant but also heat-sets the fabric.

Frontfill coating

The composition of the frontfill coating, applied to the fill yarn side in this example, but which can instead be applied to the warp yarn side if desired, is as follows:

0 073 313

- | | | |
|----|--|-----------|
| | (1) phenol-formaldehyde A stage resol resin syrup having a formaldehyde to phenol ratio of 1.5 and a solids content of 78% | 199 parts |
| 5 | (2) CaCO ₃ | 160 parts |
| | (3) sodium lauryl sulfate | 2 parts |
| 10 | (4) Hycar 2600×138, a latex of an acrylic acid ester polymer having a glass transition temperature of 25°C. available from B. F. Goodrich chemical company | 54 parts |

The front fill coating composition is applied with a knife in the amount of 150—165 dry grams per square meter (gm/m²), and water may be added as necessary to maintain the required viscosity for proper coating. The coated cloth is again dried on a tenter frame with a tension of at least 3.5 N/cm of width by passing through a hot air oven in which the entry temperature is 96°C. and the exit zone temperature is 150°C.

Backfill coating

To the side not coated with the frontfill is applied a backfill of the following composition:

- | | | |
|----|---|-----------|
| | (1) Beetle, 7238 urea formaldehyde resin syrup available from American Cyanamid | 133 parts |
| 25 | (2) Nopco (RTM) NXZ anti-foam agent, available from Nopco Chemical Co., Newark, New Jersey | 5.3 parts |
| | (3) UCAR (RTM) 131 adhesive, a polyethylene-polyvinyl acetate 60% aqueous dispersion, available from Union Carbide Corporation, having a pH of 4 to 6 | 133 parts |
| 30 | (4) air washed clay | 176 parts |
| | (5) aqueous solution containing 15% NH ₄ Cl and 24% 2-amino-2-methyl-propanol | 5.3 parts |
| 35 | (6) water to adjust viscosity to 11,000 cps at room temperature, as needed (pigment may be added if desired to color backing). | |

The composition is applied by knife coating in the amount of 140—165 gm/m² and dried in an oven having an entry zone temperature of 66°C. and an exit zone of 93°C.

The thus coated fabric is now ready for application of a maker coat of phenolic resin, the application of abrasive, and the application of an abrasive size coat, as is conventional and well known in the art. A suitable formulation to be applied to the front-sized side of the backing is as follows:

- | | | |
|----|---|-----------------------|
| | (1) phenol-formaldehyde alkaline catalyzed resol resin, F/P factor 2.08, pH 8.7, solids 78% in water | 7 parts |
| 50 | (2) phenol-formaldehyde alkaline catalyzed resol resin, F/P 0.94 pH 8.1, solids in H ₂ O 78% | 3 parts |
| | (3) CaCO ₃ | 1.54×
total solids |

To the adhesively coated fabric is then applied by conventional electrostatic means 520—550 gm/m² of grit 60 high purity aluminum oxide abrasive grain. The abrasive-adhesion coated backing member is then heated for 25 minutes at 77°C., 25 minutes at 88°C., and 47 minutes at 107°C. to provide a dry adhesive layer (about 260 gm/m²) and to anchor the abrasive grains in the desired orientation.

Afterwards, a size coat (about 160 gm/m² dry) of the same composition as the maker coat, except of lesser viscosity, is then applied according to usual techniques. The wet adhesive layer is then dried: 25 minutes at 52°C., 25 minutes at 57°C., 18 minutes at 82°C., 25 minutes at 88°C., and 15 minutes at 107°C., after which final cure at 110°C. for 8 hours is given. The coated abrasive material is then ready to be converted according to usual techniques, into belts, discs, and other desired abrasive products.

While the above example described finishing the backing of the abrasive coat on the fill side of the cloth, in other cases it may be more desirable to coat on the warp side.

Example 2

Cloth of the construction described with the identifying number 3 in Table 1 was coated by the dip and squeeze method with a two roll padder, using the following saturant:

5	Saturation formula	
	1. Water (tap)	183.3 parts
	2. Sodium Hydroxide (NaOH-solid flakes)	2.2 parts
10	3. Resorcinol	13.5 parts
	4. Formaldehyde, 37% aqueous solution	14.2 parts
	5. Hycar (RTM) 2600×138	81.3 parts
15	6. 2% by weight NaOH in water (Antifoam agent, if needed)	As needed

Mixing instructions

20 Dissolve item 2 in item 1 with stirring, then add item 3 and stir until dissolved. Add item 4 and stir for 5 minutes; weigh out item 5 into separate container and add item 6 while stirring to adjust pH to near that of the RF premix (about 9) then add premix into item 5 with gentle stirring. If foam develops during addition, add small portions of an antifoam agent. (Falcoban S, made by Fallek Chemical Corp., 460 Park Ave., New York, NY 10022, was suitable, but many others should work equally well. If foam develops during coating, additional antifoam may be added.) This mixture should be stirred for at least 15 minutes after the last

25 addition and held for 24 hours before use.

After coating, the fabric was held in a tenter frame to prevent width shrinkage and dried by passing for 3.75 minutes through an oven with an entry zone temperature of 135°C. and an exit zone temperature of 240°C. Sufficient saturant to give a dry add-on of 52±7 gm/m² was used.

30 After saturation and drying as described above, the fabric was backfilled, on the side where warp yarns are most prominently exposed, with the adhesive mixture noted below:

Resole phenol-formaldehyde resin with formaldehyde to phenol molar ratio of about 2.1—394 parts; Resole phenolic resin with F:P molar ratio about 0.95—282 parts; calcium carbonate (sized as described in U.S. Patent 2,322,156)—850 parts; Hycar 2600×138 acrylic latex (previously adjusted to a pH value of 8—9 with 10% aqueous sodium hydroxide solution)—102 parts.

35 In preparing this solution, the ingredients are added in the order listed, with continuous stirring. The adhesive is coated on the saturated fabric by a knife over roll technique in sufficient quantity to give 175—225 gm/m² of adhesive after drying. For drying, the coated fabric is again tented to eliminate any possible loss in width and is passed for 3.75 minutes through an oven with an entry zone temperature of 65°C. and an exit zone temperature of 107°C.

40 The backfilled fabric was then frontfilled on the opposite side from backfilling with the same adhesive composition as used for backfilling, in sufficient quantity to give 120—180 gm/m² of dried frontfill. Coating of frontfill could be accomplished either by knife or roll techniques with approximately equal facility. Oven conditions for drying frontfill were the same as for backfill, but satisfactory results in drying at this stage could be achieved without tenting if desired.

45 If any undesirable surface roughness was apparent on the finished fabric after completion of the steps above, it was calendered at a pressure of about 350 daN/cm of width, using conventional calender rolls heated to a temperature of 63°C.

The finished backing was then ready for making and sizing steps to convert it to a coated abrasive by conventional means as described briefly in Example 1.

50

Example 3

Fabric number 8 from Table 1 was used for this example. All other steps were the same as for Example 2.

55 Table 2 shows physical properties of the coated abrasives prepared in Examples 1—3 and compares them against the same measurements on commercial coated abrasive products with woven cloth backings. The tensile strength of the products described herein is closely comparable to the commercial products for Example 1 and superior for Examples 2 and 3. The burst strength, which is generally correlated with resistance to many environmental hazards during use of coated abrasives, is quite notably superior for Example 2 and closely comparable for the others. Elongation is higher for Examples 1 and 2 but lower or

60 comparable for Fabric 3.

65

0 073 313

TABLE 2
Comparison of physical properties of coated abrasives

5	Coated abrasive identification	Tensile strength ¹ (daN/cm) in direction of:		Percent elongation ¹ at tensile force shown (in daN/cm) in direction of:				Product burst strength ² , daN	
		Warp	Fill	Warp			Fill Break		
				18	26	35			Break
10	R 267, Grit 60 ³	49	15	1.2	2.5	4.3	7.5	15.0	116
15	Example 1	47	14	3.3	6.6	9.2	13.5	17.6	120
	Example 2	57	31	2.0	5.0	7.4	14.0	15.1	288
	Example 3	59	16	0.8	1.2	1.7	3.3	6.5	113
20	R 811, Grit 60 ³	44	13	0.9	1.7	3.0	5.0	18.8	116

¹ This measurement was carried out in accordance with ASTM D1682-64, except that the sample length was 25.4 cm rather than 7.6 cm and a fixed elongation speed of 12.7 cm/min was used irrespective of time to break.

² This value was measured with a Mullen Burst Tester, sold by Roehlen Industries, Chicopee, Massachusetts, USA.

³ Commercially available Y weight coated abrasives, sold by Norton Company, Worcester, Massachusetts.

Excessive elongation, specifically beyond the capacity for adjustment of the particular machine utilizing a coated abrasive belt, is undesirable, but otherwise elongation is not known to have any significant effect on the grinding performance. Thus very stretch-resistant warp yarns such as the glass of Example 3 can be used when needed, and the greater general toughness of a more easily stretched warp yarn type such as polyester can be advantageously used when the highest possible stretch resistance is not needed.

The adequacy of performance of the coated abrasives made by Examples 1—3 has been confirmed by actual grinding tests in both laboratory and field use.

It should be noted that by the term "yarn" used herein in the description and claims, we intend to include any continuous linear structures of any type of fiber twisted or laid together, whether made of natural or synthetic fibers, including a single monofilament. However, we do not consider unconsolidated short fibers to qualify as yarn for the purposes of my invention. Thus the fibers in mats or fleeces are not considered yarns by my definition. In particular, for "fill yarns" it is necessary for the structure so-called to be able to sustain tensile forces across the entire width of a fabric. Both fill and warp yarns, although possibly composed of twisted (and thus consolidated) short fibers, will normally be continuous for dimensions many times longer than the width of a fabric, often for hundreds of meters or more. Such continuity may of course be achieved by knotting or otherwise joining previously separate structures during the course of manufacturing a fabric.

50 **Claims**

1. A stitch bonded fabric, comprising:

(a) a warp yarn array;

(b) a fill yarn array disposed on one side of said warp yarn array and

(c) a plurality of stitch yarns, said stitch yarns being formed in loops around groups of individual yarn member of said warp and fill yarn arrays, whereby the two said yarn arrays are bonded together into a coherent fabric, characterized by the fact that the warp yarn array has a tensile strength of at least 30 dekanewtons per centimeter of fabric width;

the fill yarn array has a cover factor of greater than 40.7 percent; and

each stitching yarn has a tensile breaking strength of at least 0.5 dekanewtons.

2. A fabric according to claim 1, characterized by the fact that the number of stitch yarns is at least as great as the number of warp yarns.

3. A fabric according to claim 1 or 2, characterized by the fact that said warp yarn array consists of substantially uniformly spaced yarns in a number not greater than one per millimeter of width of the fabric.

4. A fabric according to any one of the preceding claims, characterized by the fact that at least half the

volume of the yarns of said warp yarn array consists of fibers of a polyester, polyamide, polyvinyl alcohol, or glass.

5. A fabric according to any one of the preceding claims, characterized by the fact that said fill yarn array comprises more than 25 yarns per centimeter of fabric length.

5 6. A fabric according to any one of the preceding claims, characterized by the fact that at least half the volume of the yarns of said fill yarn array consists of a spun staple polyester, texturized multifilament polyester, or texturized multifilament polyamide.

7. A fabric according to any one of the preceding claims, characterized by the fact that at least half the volume of said stitching yarns consists of fibers having a tensile breaking strength of at least 0.007 dekanewtons per denier.

8. A fabric according to any one of the preceding claims, characterized by the fact that at least half the volume of said stitch yarn consists of polyester.

9. A process for manufacturing a stitch bonded fabric comprising the steps of (a) holding a tensioned fill yarn array between sets of hooks spaced along both sides of a warp yarn array and (b) moving said fill yarn array, by moving the sets of hooks whereon it is held, into a position where said fill yarn array can be bonded, substantially simultaneously across the entire width of the fabric, to said warp yarn array by loops formed by yarns distinct from the yarns of said fill and warp yarn arrays, characterized by the fact that at least two yarns of said fill array are held on each hook of said sets of hooks.

10. A coated abrasive comprising an abrasive coating on a stitch-bonded fabric, characterized by the fact that said fabric is as defined in any one of claims 1—8.

Patentansprüche

25 1. Nähwirkware mit
 (a) einer Kettgarnanordnung;
 (b) einer auf einer Seite der Kettgarnanordnung vorgesehenen Quergarnanordnung; und
 (c) einer Mehrzahl von Nähgarnen, die Schlingen bilden, die Gruppen von einzelnen Garnen der Kett- und der Quergarnanordnung umgeben, so daß die beiden Garnanordnungen miteinander zu einer
 30 zusammenhängenden Flächengebilde verbunden sind, dadurch gekennzeichnet,
 daß die Kettgarnanordnung eine Zugfestigkeit von mindestens 40 Dekanewton pro cm Warenbreite hat,

daß die Quergarnanordnung einen Deckungsfaktor von mehr als 40,7 % hat und
 daß jedes Nähgarn eine Reißfestigkeit von mindestens 0,5 Dekanewton hat.

35 2. Ware nach Anspruch 1, dadurch gekennzeichnet, daß mindestens ebensoviele Nähgarne vorhanden sind wie Kettgarne.

3. Ware nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die Kettgarnanordnung aus im wesentlichen in gleichen Abständen voneinander angeordneten Garnen in einer Anzahl von nicht mehr als einem Garn pro mm Warenbreite besteht.

40 4. Ware nach einem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß die Garne der Kettgarnanordnung mindestens zur Hälfte ihres Volumens aus Fasern aus Polyester, Polyamid, Polyvinylalkohol oder Glas besteht.

5. Ware nach einem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß die Quergarnanordnung mehr als 25 Garne pro cm Warenlänge besitzt.

45 6. Ware nach einem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß mindestens die Garne der Quergarnanordnung mindestens zur Hälfte ihres Volumens aus einem gesponnenen Polyester-Stapelfasergarn, einem texturierten mehrfädigen Polyesterfasergarn, oder einem texturierten mehrfädigen Polyamidfasergarn bestehen.

7. Ware nach einem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß die Nähgarne mindestens zur Hälfte ihres Volumens aus Fasern bestehen, die eine Reißfestigkeit von mindestens 0,007 Dekanewton pro Denier haben.

8. Ware nach einem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß die Nähgarne mindestens zur Hälfte ihres Volumens aus Polyesterfasern bestehen.

9. Verfahren zum Herstellen einer Nähwirkware mit folgenden Schritten: (a) eine straffgespannte Quergarnanordnung wird zwischen Sätzen von Haken gehalten, die auf beiden Seiten einer Kettgarnanordnung vorgesehen sind, und (b) durch Bewegen der die Quergarnanordnung haltenden Sätze von Haken wird die Quergarnanordnung in eine Stellung bewegt, in der die Quergarnanordnung im wesentlichen gleichzeitig auf der ganzen Breite der Ware mit der Kettgarnanordnung durch Schleifen verbunden werden kann, die von Garnen gebildet werden, die von den Garnen der Quer- und der
 60 Kettgarnanordnung unterscheidbar sind, dadurch gekennzeichnet, daß auf jedem Haken der Sätze von Haken mindestens zwei Garne der Quergarnanordnung gehalten werden.

10. Beschichtetes Schleifmittel mit einem Schleifmittelüberzug auf einer Nähwirkware, dadurch gekennzeichnet, daß die Ware eine Ware nach einem der Ansprüche 1 bis 8 ist.

Revendications

1. Etoffe liée der des points de couture, comprenant:
 - (a) une série de fils de chaîne;
 - 5 (b) une série de fils de trame disposés sur un côté de ladite série de fils de chaîne et
 - (c) une série de fils de liaison, ces fils de liaison par couture étant formés en mailles autour de groupes de fils individuels de ladite chaîne et des fils de trame, de sorte que les deux séries de fils sont liées ensemble en une étoffe cohérente, caractérisée en ce que la série des fils de chaîne présente une résistance à la traction d'au moins 30 décanewtons/cm de largeur d'étoffe;
 - 10 la rangée des fils de trame présente un facteur de couverture supérieur à 40,7%; et chaque fil de couture présente une résistance à la rupture en traction d'au moins 0,5 décanewton.
2. Etoffe selon la revendication 1, caractérisé en ce que le nombre de fils de couture est au moins aussie grand que le nombre des fils de chaîne.
3. Etoffe selon la revendication 1 ou 2, caractérisée en ce que ladite série des fils de chaîne est constituée de fils espacés de façon sensiblement uniforme en un nombre ne dépassant pas un fil par mm de largeur de l'étoffe.
4. Etoffe selon l'une quelconque des revendications précédentes, caractérisée en ce qu'au moins la moitié des fils de ladite série de fils de chaîne est constituée en fils de polyester, polyamide, alcool polyvinylique ou verre.
5. Etoffe selon l'une quelconque des revendication précédentes, caractérisée en ce que ladite série des fils de trame comprend plus de 25 fils par cm de longueur d'étoffe.
6. Etoffe selon l'une quelconque des revendications précédentes, caractérisée en ce qu'au moins la moitié du volume des fils de la série des fils de trame consiste en fibres discontinues filées de polyester, en polyester multifilamentaire texturisé ou en polyamide multifilimentaire texturisé.
7. Etoffe selon l'une quelconque des revendications précédentes, caractérisée en ce qu'au moins la moitié du volume desdits fils de couture comprend des fibres ayant une résistance à la rupture en traction d'au moins 0,007 décanewton par denier.
8. Etoffe selon l'une quelconque des revendications précédentes, caractérisée en que qu'au moins la moitié du volume des fils de couture est en polyester.
9. Procédé de fabrication d'une étoffe liée par couture, comprenant les stades qui consistent (a) à maintenir une série de fils de trame tendus entre des jeux de crochets espacés sur les deux côtés de la série des fils de chaîne et (b) à mouvoir la série des fils de trame en déplaçant les jeux de crochets de sorte qu'on la maintient en position où la série des fils de trame peut être liée à peu près simultanément sur toute la largeur de l'étoffe, à la série des fils de chaîne par des mailles formées par des fils distincts des fils desdites séries de trame et de chaîne, caractérisé en ce qu'au moins deux fils de ladite série de trame sont maintenus sur chaque crochet desdits jeux de crochets.
10. Enduit abrasif comprenant un enduit abrasif sur une étoffe liée par couture, caractérisé en ce que ladite étoffe est telle que défini dans l'une quelconque des revendications 1 à 8.

40

45

50

55

60

65