1 Publication number:

0 110 522

(12)

EUROPEAN PATENT APPLICATION

Application number: 83306012.2

(51) Int. Cl.4: G 03 D 3/10

Date of filing: 04.10.83

Priority: 05.10.82 US 432859 05.10.82 US 432860

Applicant: PAKO CORPORATION, 6300 Olson Memorial Highway, Minneapolis, MN 55440 (US)

Date of publication of application: 13.06.84 Bulletin 84/24

Inventor: Shpits, Raisa, 3028 Ewing Avenue South, Minneapolis State of Minnesota 55416 (US) Inventor: Lundstrom, Robert W., 2330 Quinwood Lane, Minneapolls State of Minnesota 55441 (US) Inventor: Sannei, Benjamin H., 3120 idaho Avenue South, St. Louis Park State of Minnesota 55426 (US) inventor: Kaufmann, Kenneth M., 1605 Fairway Lane. Minneapolis State of Minnesota 55426 (US)

Designated Contracting States: DE FR GB


Inventor: Beer, Robert E., 3436 Georgia Avenue North. Minneapolis State of Minnesota, 55427 (US)

Date of deferred publication of search report: 21.01.87 Bulletin 87/4

Representative: Horton, Andrew Robert Grant et al. **BOULT, WADE & TENNANT 27 Furnival Street, London,** EC4A 1PQ (GB)

Processor and method for processing photographic film discs.

(20) for processing undeveloped photographic film discs (30) mounted on a spindle assembly (31) has a conveyor (52, 54, 62, 64) to intermittently convey the spindle assembly (31) along a generally horizontal conveyor path. The spindle assembly (31) is conveyed to a plurality of processing stations (60a-60h, 61a-61h) on the conveyor path, with each processing station having a processing tank (100-114). During processing, the processing tanks (100-114) pivot between an upward process position and a downward dump/transport position. In their upward process position, selected processing tanks are filled with processing fluids. When the spindle assembly (31) is positioned at one of the selected processing tanks (100-114) and that tank is in its upward process position and filled with processing fluid, portions of the film discs (30) on the spindle assembly (31) are contacted by the processing fluid. The spindle (31) and discs (30) are then rotated to uniformly contact the photographic images on the film discs (30) with the processing solution. While the conveyor (52, 54, 62, 64) advances the spindle assembly (31) to a next processing station, the processing tanks (100-114) are pivoted to their downward dump/transport position and the processing fluid is dumped from the selected processing tanks.



S



EUROPEAN SEARCH REPORT

Application number

EP 83 30 6012

Category	Citation of document with indication, where appropriate, of relevant passages		Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 3)		
		· •	10 0/2/11	+-	· LIOAT	
O,A	US-A-4 112 452	(D.L. PATTON)	1,2,5, 9,10	G O	3 D	3/10
	* Claims 3-7; fi	gures 1-4 *	9,10			
D,A	US-A-4 178 091	- (V.C. SOLOMON)	1,2,5,			
	* Claims 3-7; fi	gures 1-8 *	9,10			
A	FR-A-2 268 283 SUISSE S.A.)	- (ALUMINIUM	1			
	* Pages 6-11; fi	gures 1,2 *				
				TECHNICAL FIELDS SEARCHED (Int. Cl. 3)		
					LANGIL	ID (IIIt. G))
					3 D	3/10 13/04
	·					
		35-1-1				
	The present search report has b	een drawn up for all claims				
THE HAGUE		Date of completion of the sear 16-10-1986	BOEYI	BOEYKENS X J.W.		
Y : par	CATEGORY OF CITED DOCU rticularly relevant if taken alone rticularly relevant if combined w cument of the same category chnological background	JMENTS T: theory E: earlier after tl ith another D: docum L: docum	or principle under patent document, ne filing date nent cited in the ap nent cited for other	lying the but pub plication reasons	invent lished o	ion on, or