

12

EUROPEAN PATENT SPECIFICATION

45 Date of publication of patent specification: **12.04.89**

51 Int. Cl.⁴: **C 11 D 17/00**

21 Application number: **85108260.2**

22 Date of filing: **07.02.83**

80 Publication number of the earlier application in accordance with Art. 76 EPC: **0 086 614**

54 **Liquid detergent compositions.**

30 Priority: **05.02.82 GB 8203398**
13.04.82 GB 8210670
02.07.82 GB 8219227
23.12.82 GB 8236664

43 Date of publication of application:
05.02.86 Bulletin 86/06

45 Publication of the grant of the patent:
12.04.89 Bulletin 89/15

84 Designated Contracting States:
AT BE CH DE FR GB IT LI LU NL SE

50 References cited:
DE-A-2 921 366
GB-A- 930 394
GB-A-2 031 941
US-A-3 075 922
US-A-3 346 503
US-A-3 574 122
US-A-4 018 720

**The file contains technical information
submitted after the application was filed and
not included in this specification**

73 Proprietor: **Albright & Wilson Limited**
Albright & Wilson House Hagley Road West
Oldbury Warley West Midlands, B68 0NN (GB)

72 Inventor: **Akred, Brian John**
12 Cross Lane
Whitehaven Cumbria CA28 6TW (GB)
Inventor: **Messenger, Edward Tunstall**
Ramsey House Camerton
Workington Cumbria (GB)
Inventor: **Nicholson, William John**
24 Earls Road Bransty
Whitehaven Cumbria (GB)

74 Representative: **Savidge, Roger Gordon**
Madgwick et al
c/o Albright & Wilson Limited 1 Knightsbridge
Green
London SW1X 7QD (GB)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European patent convention).

Description

The present invention relates to novel, aqueous-based, pourable, fluid detergent compositions containing effective quantities of detergent builder. It is a divisional of Application No. 8303343.

Definition

The term "builder" is sometimes used loosely in the detergent art to include any non-surfactant whose presence in a detergent formulation enhances the cleaning effect of the formulation. More usually, however, the term is restricted to those typical "builders", which are primarily useful as a means of preventing or ameliorating the adverse effects on washing of calcium and magnesium ions e.g. by chelation, sequestering, precipitation or absorption of the ions, and secondarily as a source of alkalinity and buffering. The term "Builder" is used herein in the latter sense, and refers to additives which ameliorate the aforesaid adverse effects to a substantial extent. It includes sodium or potassium tripolyphosphate and other phosphate and condensed phosphate salts such as sodium or potassium orthophosphates, pyrophosphates, metaphosphates or tetrakisphosphate, as well as phosphonates such as acetodiphosphonates, amino tris methylene phosphonates and ethylenediamine tetramethylene phosphonates. It also includes alkali metal carbonates, zeolites and such organic sequestrants as salts of nitrilotriacetic acid, citric acid and ethylene diamine tetracetic acid, polymeric polycarboxylic acids such as polyacrylates and maleic anhydride based copolymers.

For the avoidance of doubt, "Builder" is used herein to include water soluble alkali metal silicates such as sodium silicate, but excludes additives such as carboxymethyl cellulose, or polyvinyl pyrrolidone whose function is primarily that of soil suspending or anti-redeposition agent.

"Electrolyte" is used herein in relation to a component of a liquid detergent composition to denote those non-surface active, water soluble, ionic compounds which dissociate at least partially in aqueous solution to provide ions, and which tend to lower the solubility or micellar concentration in the composition of the surfactants present by a "salting out" effect. It includes water soluble dissociable, inorganic salts such as, for example alkali metal or ammonium, chlorides, nitrates, phosphates, carbonates, silicates and polyphosphates, and also certain water soluble nonsurface active organic salts which desolubilise or "salt out" those surfactants which are present in the composition. It does not include salts of cations which form water insoluble precipitates with the surfactants present, or salts which, at the concentrations used, tend to give unacceptable crystallisation when the composition is stored.

"Hydrotrope" is used herein in relation to a component of a liquid detergent composition to denote any water soluble compound which tends to increase the solubility in the composition of the surfactants present. Typical Hydrotropes include urea and the alkali metal or ammonium salts of the lower alkyl benzene sulphonics such as sodium toluene sulphonate and sodium xylene sulphonate. Whether a given compound is an Electrolyte or a Hydrotrope may in some cases depend upon which surfactants are present in the particular liquid detergent composition.

As used herein "Soap" means an at least sparingly water soluble salt of a natural or synthetic aliphatic monocarboxylic acid, which salt has surfactant properties. The term includes sodium, potassium, lithium, ammonium and alkanolamine salts of C₈₋₂₂ natural and synthetic fatty acids, including stearic, palmitic, oleic, linoleic, ricinoleic, behenic and dodecanoic acids, resin acids and branched chain monocarboxylic acids.

The "Usual Minor Ingredients" includes those ingredients other than Water, Active Ingredients, Builders and Electrolytes which may be included in laundry detergent compositions, typically in proportions up to 5%, and which are compatible in the relevant Formulation with a pourable, chemically stable Non-sedimenting composition. The term includes antiredeposition agents, perfumes, dyes, optical brightening agents, Hydrotropes, solvents, buffers, bleaches, corrosion inhibitors, antioxidants, preservatives, scale inhibitors, humectants, enzymes and their stabilizers, bleach activators, and the like.

As used herein "Functional Ingredients" means ingredients which are required to provide a beneficial effect in the wash liquor and includes ingredients which contribute to the washing effectiveness of the composition e.g. surfactants, Builders, bleaches, optical brighteners, buffers, enzymes and antiredeposition agents, and also anti-corrosives but excludes water, solvents, dyes, perfume, Hydrotropes, sodium chloride, sodium sulphate, solubilisers and stabilisers whose sole function is to impart stability, fluidity or other desirable characteristics to a concentrated formulation.

"Payload", means the percentage of Functional Ingredients based on the total weight of the composition.

"Active Ingredients", means surface active materials.

All references herein to "Centrifuging", unless stated to the contrary, are to be construed as referring to centrifuging at 25°C for 17 hours at 800 times normal gravitational force.

The expression "Separable Phase" is used herein to denote phases which are each separable from the mixture to form a distinct layer upon Centrifuging. A single Separable Phase may comprise two or more thermodynamically distinct phases, which are not separable from each other on Centrifuging as in, for example, a stable emulsion.

"Dispersed" is used herein to describe a phase which is discontinuously distributed as discrete particles or droplets in at least one other phase. "Co-continuous" describes two or more interpenetrating

phases each of which extends continuously through a common volume, or else is formed of discreet elements which interact to form a continuous matrix tending to maintain the position and orientation of each element in relation to the matrix when the system is at rest. "Interspersed" describes two or more phases which are either Co-continuous or of which one or more is Dispersed in the other or others.

References to solid phases are to substances actually present in the composition in the solid state at ambient temperature, and including any water of crystallization or hydration unless the context requires otherwise. A "Solid Layer" is a solid, pasty or non-pourable gelatinous layer formed on Centrifuging.

"Total Water" refers to water present as liquid water in a predominantly aqueous phase, together with any other water in the composition, e.g. water of crystallisation or hydration or water dissolved or otherwise present in any predominantly non-aqueous phase. "Dry Weight" refers to residual weight after removal of Total Water and also of any solvent which has a boiling point below 110°C.

The term "Formulation" is used to describe the combination of ingredients which make up the Dry Weight of a composition. Thus the same Formulation may be exemplified by a number of compositions, differing in their Percentage Dry Weight.

All references herein to "Viscosities" unless otherwise stated are to the viscosity as measured on a cup and bob viscometer at 25°C after two minutes running using a 20 mm internal diameter flat bottomed cup, 92 mm long, and a 13.7 mm diameter bob, 44 mm long, with conical ends having a 45° horizontal angle, and 4mm diameter spindle, rotating at 350 rpm. The tip of the bob was 23mm from the base of the cup. This corresponds to Contraves "Rheomat 30" viscometer using measuring system C at speed setting 30. These conditions are unsuitable for measuring Viscosities greater than 12 Pascal Seconds at which partial loss of contact between the bob and the sample may arise.

"Pourable" as used herein means having a Viscosity of less than 11.5 Pascal Seconds.

"L₁" phase denotes a fluid, isotropic, micellar solution of surfactant in water, which occurs at concentrations between the critical micellar concentration and the first lyotropic mesophase, wherein the surfactant molecules aggregate to form spherical or rod shaped micelles.

"G" phase refers to a liquid crystal phase of the type, also known in the literature as "neat phase" or "lamellar phase" in which the surfactant molecules are arranged in parallel layers of indefinite extent separated by layers of water or an aqueous solution. The layers may be bilayers or interdigitated layers of surfactant. The "G" phase for any given surfactant or surfactant mixture normally exists in a narrow range of concentrations. Pure "G" phases can normally be identified by examination of a sample under a polarising microscope, between crossed polarisers. Characteristic textures are observed in accordance with the classic paper by Rosevear, JAOCS Vol. 31 P628 (1954) or in J. Colloid and Interfacial Science, Vol. 30 No. 4, P.500 (1969).

"Yield Points" whenever referred to herein are as measured on an RML Series II "DEER" (R.T.M.) Rheometer at 25°C.

All percentages, unless otherwise stated, are by weight, based upon the total weight of the composition.

References herein to "sedimentation" include references to upward as well as downward separation of solid particles. "Non-sedimenting" means not undergoing significant visible separation of phases after three months at room temperature under normal earth gravity.

Technical Background

Liquid detergents have hitherto been used mainly for light duty applications such as dish washing. The market for heavy duty detergents, e.g. laundry detergents, has been dominated by powders, due to the difficulty of getting an effective amount of surfactant and in particular of Builder into a stable liquid formulation. Such liquids should in theory be cheaper than powder detergents since they would avoid the need to dry and would in many instances replace the sulphate filler conventionally used in powder detergents with water. They also offer the possibilities of greater convenience and more rapid dissolution in wash water than powder. Attempts to provide solutions of the Functional Ingredients have been relatively unsuccessful commercially. One reason for this lack of success has been that the most commonly used and cost effective Functional Ingredients, e.g. sodium tripolyphosphate and sodium dodecyl benzene sulphonate, are insufficiently soluble in aqueous compositions. Potassium pyrophosphate and amine salts of the Active Ingredients which are more soluble, have been tried as alternatives but have not been found cost effective.

Unbuilt liquid detergents containing high levels of surfactant have been marketed for laundry use, but are unsuitable for hard water areas and have enjoyed only limited success.

A different approach is to attempt to suspend the excess Builder as a solid in the liquid solution of surfactant. The problem however has been to stabilise the system to maintain the Builder in suspension and prevent sedimentation. This has in the past required relatively sophisticated formulations, preventing realisation of the potential cost saving, and relatively low concentrations of solid Builder, giving limited washing effectiveness. This approach has been conditioned by certain assumptions: that the detergent should as far as possible be in solution; that the amount of suspended solid should be minimised to avoid difficulties in stabilising the suspension against sedimentation; and that special thickeners or stabilisers were essential to prevent sedimentation.

The products hitherto introduced commercially have suffered from certain serious drawbacks. In

particular, the individual compositions have been proved highly sensitive to relatively small variations in Formulation and manufacturing procedure. Departure from a particular composition, optimised within fairly narrow limits, generally results in instability and diminished shelf life. The formulator has therefore been restricted to particular ingredients and proportions, which have not included many of the most effective combinations of surfactants and Builder for laundry purposes.

Because no general adequate theoretical explanation for the stability of such systems has been proposed, it has not proved possible to predict which compositions will be stable and which unstable, or how to set about stabilising any given surfactant Builder combination which may be desired for reasons of washing effectiveness or cost. Each composition has had to be discovered by trial and error, and little flexibility has existed for adapting the individual compositions to special requirements.

Moreover, in general, the Payload has been undesirably low. In addition, the proportion of Builder to Active Ingredient has generally been less than is preferred for optimum washing, and expensive ingredients, not usually required in powder Formulations, have often been needed to increase the amount of Functional Ingredient in solution, and to inhibit sedimentation of the suspended solid.

Introduction of the Invention

We have now discovered that by observing certain conditions it is possible to formulate Non-sedimenting, Pourable, fluid, aqueous based detergent compositions which have novel structural features and which can employ as surfactant virtually any surfactant or surfactant combination which is useful in laundry applications, in desired optimum proportions with any of the commonly used detergent Builders. In general, compositions of our invention can be obtained, which contain substantially higher Payloads at effective Builder to surfactant ratio than have hitherto been attainable.

Preferred embodiments of our invention exhibit at least some of the following advantages compared with products marketed hitherto: Higher Payload; increased Builder to surfactant ratio; improved stability; lower cost due to use of cheaper ingredients and ease of production; satisfactory mobility; improved washing performance; "non-drip" characteristics, permitting the compositions to be added to the compartments of washing machines designed to operate with powders, without premature release; a consistency suitable for automatic dispensing; and the flexibility to select optimum surfactant combinations for the requirements of any particular market.

We have found that in general, contrary to what had been assumed in the art, the higher the amount of undissolved material the more stable the composition. We have discovered, in particular, that the lower the proportion of the Active Ingredients dissolved in the liquid aqueous phase, and the higher the proportion present as an Interspersed structure of solid or lamellar phase, the more readily can a Non-sedimenting, Pourable product be obtained at high Payloads. We have further discovered that most surfactants commonly used in powder detergents can have a stabilising effect on aqueous suspensions of Functional Ingredients, when present in certain novel structured states in the composition, which may, at high Payloads, be sufficient to stabilise the composition without the presence of special stabilisers, not otherwise required for the Formulation. We have also discovered that surfactants can be constrained to form an open three dimensional structure conferring stability on aqueous suspensions, by the presence of Electrolytes and by controlling the conditions of mixing. We have discovered that by applying the above principles it is possible to formulate laundry detergents as thixotropic gels which may contain suspended particles of solid Builder, which have particular advantages over conventional detergent suspensions.

The Prior Art

The prior art on liquid detergents is extremely voluminous. However, for the purpose of this invention the numerous references to light duty liquids and to unbuilt or built clear liquid laundry detergents in which all ingredients are present in solution may be disregarded. The Builder level in each case is substantially less than desirable.

Recent general summaries of the current state of the art include JAOCS (April 1981) P356A — "Heavy Duty Laundry Detergents" which includes a review of the typical commercially available liquid formulations, and "Recent Changes in Laundry Detergents" by Rutkowski, published in 1981 by Marcel Dekker Inc. in the Surfactant Science Series.

The two principle avenues of approach to the problem of formulating fully built liquid detergents, have been to emulsify a surfactant in an aqueous solution of Builder or to suspend a solid Builder in an aqueous solution or emulsion of surfactant.

The former approach is exemplified by U.S.P. 3235505, U.S.P. 3346503, U.S.P. 3351557, U.S.P. 3509059, U.S.P. 3574122, U.S.P. 3328309 and Canadian Patent 917031. In each of these patents an aqueous solution of a water soluble Builder is sufficiently concentrated to salt out the surfactant (usually a liquid non-ionic type) and the latter is dispersed in the aqueous medium as colloidal droplets, with the aid of various emulsifiers. In each case the system is a clear emulsion, which generally, contains relatively low levels of Builder, and which is undesirably expensive due to the cost of using soluble Builders.

The alternative approach is exemplified by B.P. 855893, B.P. 948617, B.P. 943271, B.P. 2028365, E.P. 38101, Australian P. 522983, U.S.P. 4018720, U.S.P. 3232878, U.S.P. 3075922 and U.S.P. 2920045. The formulations described in these patents separate, on Centrifuging, into a Solid Layer comprising the majority of the sparingly soluble Builder and an aqueous layer containing at least the majority of the Active

EP 0 170 091 B1

Ingredients. Commercial products corresponding to the example of Australian patent No. 522983 have been marketed recently in Australia. The stability of these compositions is generally highly sensitive to minor variations in Formulation. Most require expensive additives which are not Functional Ingredients.

E.P. 0079646, published after the filing date of the parent application, but claiming a priority date of 16th November 1981 describes and claims compositions containing a "salting out electrolyte" and an "auxiliary electrolyte". The latter is "an electrolyte of high lyotropic number" (i.e. a Hydrotrope as herein defined), whereas the "salting out electrolyte" corresponds to an Electrolyte as herein defined. Thus the earlier filed application describes the use of Hydrotropes to counteract the salting out effect of Electrolytes. The "auxiliary electrolytes" described are all expensive non-Functional additives which are required in substantial concentrations.

A different approach is to suspend solid builder in an anhydrous liquid non-ionic surfactant e.g. BP 1600981. Such systems are costly, restrictive with regard to choice of surfactant and give unsatisfactory rinsing properties.

Several patents describe emulsions in which the Builder is in the dispersed phase of an emulsion rather than in suspension. U.S.P. 4057506 describes the preparation of clear emulsions of sodium tripolyphosphate, and U.S.P. 4107067 describes inverse emulsions in which an aqueous solution of Builder is dispersed in a liquid crystal surfactant system.

Reference may also be made to the numerous patents relating to hard surface cleaners, in which an abrasive is suspended usually in an aqueous solution of surfactant, e.g. B.P. 2031455, U.S.P. 3281367 and U.S.P. 3813349. U.S.P. 3956158 describes suspensions of abrasive in a gel system of interlocking fibres of, e.g. asbestos or soap. However, the low levels of surfactant, absence of Builder and presence of high concentrations of abrasive, generally preclude these patents from being of any assistance in the formulating of laundry detergents.

Powder detergents are normally prepared by spray drying aqueous slurries, which may superficially resemble liquid detergent formulations, but which are not required to be stable to storage, and which, are prepared and handled at elevated temperatures. Such slurries are generally not Pourable at ambient temperature. Patents describing the preparation and spray drying of such slurry intermediates include U.S.P. 3639288 and W. German OLS 1567656.

Other publications of possible interest are:

Australian patent 507431, which describes suspensions of Builder in aqueous surfactant, stabilised with sodium carboxymethyl cellulose or clay as a thickening agent. However, the levels of Functional Ingredients, and in particular of Builder, in the formulations exemplified, are not sufficient for a fully acceptable commercial product;

U.S.P. 3039971 describes a detergent paste containing the Builder in solution;

Fr. Patent 2283951 describes suspensions of zeolite Builders in nonionic surfactant systems; the compositions are, however, stiff pastes rather than Pourable fluids;

B.P. 1506427 and B.P. 1468181 describe suspensions of Builder in aqueous surfactant, which are generally insufficiently stable for commercial purposes;

A.C.S. Symposium series No. 194 "Silicates in Detergents" describes the effect of silicates on liquid detergents.

It will be understood that each of the foregoing patent references was selected from the very extensive prior art, and relevant aspects highlighted with the aid of hindsight, using our knowledge of the invention as a guide to such selection and highlighting. The ordinary man skilled in the art at the time of our first claimed priority, and without foreknowledge of the applicant's invention, would not necessarily have selected those patents as being particularly significant or those aspects as being of special interest or relevance.

The foregoing summary does not therefore represent the overall picture of the art possessed by the ordinary skilled man. We believe that the latter has generally held the view, either that fully built liquid detergents containing sparingly soluble Builders were unattainable, or that progress towards such formulations would be by suspending the Builder in aqueous solutions of the surfactant, earlier, alternative approaches having failed.

The Invention

According to one embodiment the invention provides a fluid, aqueous based detergent composition comprising: a surfactant; a Builder, at least a proportion of said Builder being present as solid particles suspended in the composition; and a surfactant-desolubilising Electrolyte, said Electrolyte not comprising sodium sulphate in quantities in excess of its solubility in the composition at normal temperatures, but including any dissolved portion of surfactant-desolubilising Builder; and which is separable by Centrifuging at 800 times normal earth gravity for 17 hours at 25°C into at least two layers at least one of which layers is an aqueous layer characterised in that: said aqueous layer contains sufficient of said Electrolyte dissolved therein to contribute from 2 to 4.5 gm ions of alkali metal ion per litre to said aqueous layer; and the Payload is above the minimum at which the composition is Non-sedimenting and below the maximum at which the composition is Pourable.

According to a second embodiment our invention provides an aqueous, fluid detergent medium,

capable of suspending solid particulate Builders to form Pourable, Non-Sedimenting suspensions, and comprising water, surfactant and dissolved Electrolyte, wherein the said dissolved Electrolyte is sufficient to provide from 2 to 4.5 gm ions of alkali metal per litre in said medium and said surfactant is sufficient to form, in the presence of said Electrolyte, a vesicular and/or lamellar surfactant structure capable of supporting said builder.

In more detail, our invention provides Non-Sedimenting, Pourable, fluid detergent compositions comprising Active Ingredients and Dispersed solid Builder said compositions comprising at least one predominantly aqueous liquid phase and one or more other phases separable from said predominantly aqueous liquid phase by Centrifuging and containing Active Ingredient present in at least one of said one or more other phases, and a Builder, present in at least one of said one or more other phases, said one or more other phases being Interspersed with the predominantly aqueous phase, all of which compositions exhibit at least some, but not necessarily all, of the following characteristics: They are thixotropic; they are gels; they comprise a continuous, at least predominantly aqueous Separable Phase, containing dissolved Electrolyte, a Separable Phase containing a substantial proportion of the Active Ingredient as spheroids or vesicles Interspersed with said at least predominantly aqueous phase, and a Dispersed solid phase consisting at least predominantly of Builder; said one or more other phases are at least predominantly non-aqueous; the compositions have a high Payload of Functional Ingredients, typically greater than 20% by weight, e.g. 25 to 75%, more usually at least 30% preferably at least 35% most preferably at least 40% by weight; they contain a high ratio of Builder to Active Ingredient e.g. greater than 1:1 preferably 1.2:1 to 4:1; they contain more than 5 and preferably more than 8% by weight of Active Ingredients; the predominantly aqueous phase contains a concentration of less than 15%, preferably less than 8%, e.g. less than 2%, typically, in the case of nonionic surfactant or alkyl benzene sulphonates, less than 0.5% by weight dissolved Active Ingredients; the proportion by weight of Active Ingredient in the predominantly aqueous phase to total Active Ingredient in the composition is less than 1:1.5 preferably less than 1:2 e.g. less than 1:4; the at least one predominantly aqueous liquid phase contains sufficient Electrolyte to provide a concentration of at least 0.8, typically at least 1.2, preferably 2.0 to 4.5 gram ions per litre of total alkali metal and/or ammonium cations; the compositions contain at least 15% by weight, preferably more than 20% by weight of Builder; the Builder is at least predominantly sodium tripolyphosphate; the Builder comprises a minor proportion of alkali metal silicate, preferably sodium silicate; the bulk Viscosity of the composition is between 0.1 and 10 pascal seconds, preferably between 0.5 and 5 pascal seconds; the composition has a Yield Point preferably of at least 0.2 e.g. at least 0.5, preferably less than 20 e.g. 1 to 15 Newtons/sq.m; a phase containing Builder comprises solid particles having a maximum particle size below the limit at which the particles tend to sediment; the particles have, adsorbed on their surfaces at least one crystal growth inhibitor sufficient to maintain the solid particles below the limit at which the particles tend to sediment; the composition contains an agglomeration inhibitor sufficient to prevent flocculation or coagulation of the solid particles.

Classification by Centrifuging

Aqueous based liquid laundry detergents containing suspended solid builder can, in general, conveniently be classified by Centrifuging as hereinbefore defined.

Three principal types of laundry liquid having a continuous aqueous phase and dispersed solid are distinguishable, which will be hereinafter referred to as Group I, Group II and Group III suspensions.

The first Group of laundry suspensions is characteristic of the prior art discussed above which relates to suspensions of solid Builder in aqueous solutions or emulsions of surfactant. On Centrifuging as defined herein, Group I compositions separate into a Solid Layer consisting essentially of Builder, and a viscous liquid layer comprising water and surfactant. Formulation factors tending to form Group 1 compositions include the use of the more water soluble surfactants, such as alkyl ether sulphates, the presence of solubilising agents such as Hydrotropes and water miscible organic solvents, relatively low levels of Electrolyte and relatively low Payloads. Group 1 compositions normally display at least some of the following typical properties. The bulk viscosity of the composition is determined by, and is similar to, the viscosity of the aqueous liquid layer. The aqueous layer typically has a viscosity of from 0.1—1.0 pascal seconds. Viscosities of the compositions are generally also under 1 pascal second, e.g. 0.3 to 0.6 pascal seconds. The compositions usually have yield points of less than 0.4, often less than 0.1, Newton m^{-2} . This implies a relatively unstructured composition. This is confirmed by neutron scattering and x-ray diffraction studies and by electron microscopy. Subjection to high shear rate renders Group I compositions unstable.

Group II is essentially distinguished from Group I in that at least a substantial proportion of the surfactant is present in a Separable Phase, which is distinct from the predominantly aqueous liquid phase containing the Electrolyte. This Group is distinguished from Group III in that at least the major portion of the separable surfactant separates on Centrifuging as a liquid or liquid crystal layer.

Group II compositions typically show a three layer separation on Centrifuging, giving a non-viscous liquid aqueous layer (e.g. less than 0.1 pascal seconds, usually less than 0.02 pascal seconds), which contains Electrolyte but little or no surfactant, a viscous liquid layer which contains a major proportion of the Active Ingredients and a Solid Layer consisting predominantly of Builder.

Group II compositions have, typically, a very low Yield Point on being first prepared but become more gel like on ageing. The Viscosity of the composition is usually between 1 and 1.5 pascal seconds. The

compositions of this type show evidence of lamellar structure in X-ray and neutron diffraction experiments and by electron microscopy.

Most Centrifuged Group II compositions have the liquid or liquid crystal surfactant layer uppermost, but we do not exclude compositions in which the aqueous Electrolyte layer is uppermost or in which there are two or more Solid Layers distinguishable from each other, at least one of which may sediment upwardly, in relation to either or both liquid layers on Centrifuging.

One distinction of Group III from the other Groups is that at least a substantial proportion of the surfactant Centrifuges into a Solid Layer.

Group III compositions may Centrifuge into more than one Solid Layer. Normally both surfactant and Builder sediment downwardly on Centrifuging and the two phases are intermixed. However some Group III compositions may provide an upwardly sedimentary surfactant phase or more than one surfactant phase, at least one of which may sediment upwardly. It is also possible for some or all of the Builder to sediment upwardly.

The third Group of laundry liquids is typical of those compositions of the present invention prepared from those surfactants which are more sparingly soluble in the aqueous phase, especially anionic surfactants such as sodium alkyl benzene sulphonates, as well as mixtures of such surfactants with minor proportions of non-ionic surfactant. Group III compositions typically separate on Centrifuging into two layers. The first of which is an aqueous layer containing dissolved Electrolyte and the second is a Solid Layer comprising Builder and surfactant.

The rheological properties of Group III, typically, show the strongest evidence for structure. The Viscosity of the suspension is substantially greater than that of the aqueous layer, e.g. typically 1.2 to 2 Pascal seconds. The compositions generally have a fairly high Yield Point, e.g. greater than 1 Newton m^{-2} . On recovery after subjection to high shear stresses Group III compositions exhibit equal or greater stability and, often, increased Viscosity.

There is a gradual progression from Group I to Group III with some compositions having some properties characteristic of one group and some characteristic of another. Soap based compositions of our invention, for example, may show, in addition to a liquid layer and a Solid Layer, a small amount of a third layer which is liquid on Centrifuging, but have rheological properties characteristic of Group III.

Compositions at the borderline of Groups I and II are sometimes shear unstable but may be converted into more shear stable Group III compositions of the invention by addition of sufficient Electrolyte and/or by increasing Pay Load. Most Group I compositions may be converted into either Group II or III if sufficient Electrolyte is added. Conversely, Group II and Group III can generally be converted to Group I, by addition of Hydrotrope.

Classification by Diffraction and Microscopy

Compositions of our invention and of the prior art, have been examined by x-ray and neutron diffraction and by electron microscopy.

Samples for neutron diffraction studies were prepared using deuterium oxide in place of water. Water was kept to a minimum, although some ingredients, normally added as aqueous solutions (e.g. sodium silicate), or as hydrates, were not available in a deuterated form.

Deuterium oxide based compositions were examined on the Harwell small angle Neutron Scattering Spectrometer. Both deuterium oxide based and aqueous samples were also examined using a small angle x-ray diffractometer. Aqueous samples were freeze fracture etched, coated with gold or gold/palladium and studied under the Lancaster University Low Temperature Scanning Electron Microscope. Competitive commercial compositions, which are not, of course, available in a deuterated form, could not be examined by neutron scattering.

As in the case of Centrifuging, the three techniques described above all provide an indication of three broad categories of liquid detergent suspension, which appear to correspond generally to the Group I, Group II and Group III compositions, described under "Classification by Centrifuging".

The first category of composition, which included, generally those compositions belonging typically to Group I, was characterised under both neutron and x-ray analysis by high levels of small angle scattering and an absence of discrete peaks, corresponding to regular, repeating, structural features. Some compositions showed broad indistinct shoulders or humps, others a smooth continuum.

Small angle scattering is scattering very close to the line of the incident beam and is usually dominated by scattering from dilute dispersions of inhomogeneities in the composition. The shoulders or humps observed with some Group I compositions additionally show a form and angular displacement typical of concentrated micellar solutions of surfactant (L_1 phase).

Under the electron microscope typical Group I compositions gave a largely featureless granular texture with crystals of Builder distributed apparently at random. These results were consistent with the hypothesis based on their rheological properties that typical Group I compositions are relatively unstructured and lacking detectable lamellar features. However some members of Group I showed evidence under the electron microscope of spherical structures of approximately 5 microns diameter.

A different type of pattern was obtained from typical Group II compositions. These showed relatively low levels of small angle scattering near the incident beam, a peak typical of concentrated micellar solution (L_1 phase) and a sharply defined peak or peaks corresponding to a well defined lamellar structure. The

positions of the latter peaks were in a simple numerical ratio, with first, second and, sometimes, third order peaks usually distinguishable. The peaks were evidence of relatively broadly spaced lamellae (36—60 Angstrom). Under the electron microscope lamellar structures were visible.

Some Group III compositions gave relatively narrow and intense small angle scattering, together with distinct peaks indicative of a lamellar structure. The peaks were broader than in the case of typical Group II compositions, and second and third order peaks were not always separately distinguishable. In general the displacement of the peaks indicated a lamellar structure with the lamellae more closely spaced than in the case of typical Group II compositions (e.g. 2.6—3.6 nm (26—36 Angstrom)). Lamellar structures were clearly visible under the electron microscope. In other instances spheroidal structures could be observed.

10

Proposed Structure

We believe that the foregoing properties can most readily be explained by the hypothesis that our invention embodies a novel structure of matter in which solid Builder is suspended in a structured arrangement of solid surfactant hydrate, and/or of "G" phase surfactant in association with an L₁ phase micellar solution and/or of vesicles.

Certain embodiments of our invention are believed to comprise pourable gel systems in which there may be two or more Co-continuous or Interspersed phases. The properties of such compositions can be explained on the basis that they are thixotropic gels comprising a relatively weak three dimensional network of solid surfactant hydrate Interspersed with a relatively non viscous aqueous phase which contains dissolved Electrolyte, but little or no surfactant. The network prevents sedimentation of the network-forming solids, and any suspended discrete particles. The network forming solids may be present as platelets, sheets of indefinite extent, or fibres or alternatively, as asymmetric particles joined into or interacting to provide, a random mesh, which is Interspersed with the liquid. The structure is sufficiently stable to inhibit or prevent precipitation on storage and will also limit the extent of spreading of the gel on a horizontal surface, however the structure is weak enough to permit the compositions to be poured or pumped. The solid structure is composed at least predominantly of surfactant hydrate e.g. sodium alkyl benzene sulphonate or alkyl sulphate. Thus no other stabilising agent is required over that required in the end-use of the composition. Such gels may, in particular, exhibit a clay-like structure, sometimes referred to as a "house of cards" structure, with a matrix of plate shaped crystals orientated at random and enclosing substantial interstices, which accommodate the particles of builder. The solid surfactant may, in some instances be associated with, or at least partially replaced by "G" phase surfactant.

In other compositions there may be up to four thermodynamically distinct phases of which two are Separable Phases under the conditions herein defined.

The phases detected by diffraction comprise a lamellar phase, which is probably a "G" phase, but possibly in some instances surfactant hydrate or a mixture thereof with "G" phase, and Predominantly aqueous "L₁" micellar solution, together with the solid Builder. There is also a predominantly aqueous solution containing Electrolyte.

The Builder is suspended in a system which may comprise a network of "G" phase and/or spheroids or vesicles which may have an onion like structure, or outer shell, formed from successive layers of surfactant and which may contain at least one of the Predominantly aqueous phases, e.g. the Electrolyte solution, or more probably the "L₁" micellar solution. At least one of the predominantly aqueous phases is the continuous phase. Evidence for the presence of vesicles is provided by microscopy in the case of the compositions containing olefin and paraffin sulphonates.

Surfactants

The compositions of our invention preferably contain at least 5% by weight of surfactants. Preferably the surfactant constitutes from 7 to 35% by weight of the composition, e.g. 10 to 20% by weight.

The surfactant may for example consist substantially of an at least sparingly water-soluble, salt of sulphonic or mono esterified sulphuric acids e.g. an alkylbenzene sulphonate, alkyl sulphate, alkyl ether sulphate, olefin sulphonate, alkane sulphonate, alkylphenol sulphate, alkylphenol ether sulphate, alkylethanolamide sulphate, alkylethanolamide ether sulphate, or alpha sulfo fatty acid or its esters each having at least one alkyl or alkenyl group with from 8 to 22, more usually 10 to 20, aliphatic carbon atoms. Said alkyl or alkenyl groups are preferably straight chain primary groups but may optionally be secondary, or branched chain groups. The expression "ether" hereinbefore refers to polyoxyethylene, polyoxypropylene, glyceryl and mixed polyoxyethylene-oxy propylene or mixed glyceryl-oxyethylene or glyceryl-oxy propylene groups, typically containing from 1 to 20 oxyalkylene groups. For example, the sulphonated or sulphated surfactant may be sodium dodecyl benzene sulphonate, potassium hexadecyl benzene sulphonate, sodium dodecyl dimethyl benzene sulphonate, sodium lauryl sulphate, sodium tallow sulphate, potassium oleyl sulphate, ammonium lauryl monoethoxy sulphate, or monoethanolamine cetyl 10 mole ethoxylate sulphate.

Other anionic surfactants useful according to the present invention include fatty alkyl sulphosuccinates, fatty alkyl ether sulphosuccinates, fatty alkyl sulphosuccinates, fatty alkyl ether sulphosuccinates, acyl sarcosinates, acyl taurides, isethionates, Soaps such as stearates, palmitates, resinsates, oleates, linoleates, and alkyl ether carboxylates. Anionic phosphate esters may also be used. In each case the anionic surfactant typically contains at least one aliphatic hydrocarbon chain having from 8 to

22 preferably 10 to 20 carbon atoms, and, in the case of ethers one or more glyceryl and/or from 1 to 20 ethyleneoxy and or propyleneoxy groups.

Certain anionic surfactants, such as olefin sulphonates and paraffin sulphonates are commercially available only in a form which contains some disulphonates formed as by-products of the normal methods of industrial manufacture. The latter tend to solubilise the surfactant in the manner of a Hydrotape. However, the olefin and paraffin sulphonates readily form stable compositions which, on Centrifuging, contain a minor portion of the total surfactant in the aqueous phase, and which show evidence of spheroidal structures. These compositions are valuable, novel, laundry detergents and which accordingly constitute a particular aspect of the present invention.

Preferred anionic surfactants are sodium salts. Other salts of commercial interest include those of potassium, lithium, calcium, magnesium, ammonium, monoethanolamine, diethanolamine, triethanolamine and alkyl amines containing up to seven aliphatic carbon atoms.

The surfactant may optionally contain or consist of nonionic surfactants. The nonionic surfactant may be e.g. a C₁₀₋₂₂ alkanolamide of a mono or di-lower alkanolamine, such as coconut monoethanolamide. Other nonionic surfactants which may optionally be present, include ethoxylated alcohols, ethoxylated carboxylic acids, ethoxylated amines, ethoxylated alkylolamides, ethoxylated alkylphenols, ethoxylated glyceryl esters, ethoxylated sorbitan esters, ethoxylated phosphate esters, and the propoxylated or ethoxylated and propoxylated analogues of all the aforesaid ethoxylated nonionics, all having a C₈₋₂₂ alkyl or alkenyl group and up to 20 ethyleneoxy and/or propyleneoxy groups, or any other nonionic surfactant which has hitherto been incorporated in powder or liquid detergent compositions e.g. amine oxides. The latter typically have at least one C₈₋₂₂, preferably C₁₀₋₂₀ alkyl or alkenyl group and up to two lower (e.g. C₁₋₄, preferably C₁₋₂) alkyl groups.

The preferred nonionics for our invention are for example those having an HLB range of 7-18 e.g. 12-15.

Certain of our detergents may contain cationic surfactants, and especially cationic fabric softeners usually as a minor proportion of the total active material. Cationic fabric softeners of value in the invention include quaternary amines having two long chain (e.g. C₁₂₋₂₂ typically C₁₆₋₂₀) alkyl or alkenyl groups and either two short chain (e.g. C₁₋₄) alkyl groups, or one short chain and one benzyl group. They also include imidazoline and quaternised imidazolines having two long chain alkyl or alkenyl groups, and amido amines and quaternised amido amines having two long chain alkyl or alkenyl groups. The quaternised softeners are all usually salts of anions which impart a measure of water solubility such as formate, acetate, lactate, tartrate, chloride, methosulphate, ethosulphate, sulphate or nitrate. Compositions of our invention having fabric softener character may contain smectite clays.

Compositions of our invention may also contain amphoteric surfactant, which may be included typically in surfactants having cationic fabric softener, but may also be included, usually as a minor component of the Active Ingredients, in any of the other detergent types discussed above.

Amphoteric surfactants include betaines, sulphobetaines and phosphobetaines formed by reacting a suitable tertiary nitrogen compound having a long chain alkyl or alkenyl group with the appropriate reagent, such as chloroacetic acid or propane sultone.

Examples of suitable tertiary nitrogen containing compounds include: tertiary amines having one or two long chain alkyl or alkenyl groups, and optionally a benzyl group, any other substituent being a short chain alkyl group; imidazolines having one or two long chain alkyl or alkenyl groups and amidoamines having one or two long chain alkyl or alkenyl groups.

Those skilled in the detergent art will appreciate that the specific surfactant types described above are only exemplary of the commoner surfactants suitable for use according to the invention. Any surfactant capable of performing a useful function in the wash liquor may be included. A fuller description of the principal types of surfactant which are commercially available is given in "Surface Active Agents and Detergents" by Schwartz Perry and Berch.

Builders

The Builder, in preferred compositions of our invention is believed to be normally present, at least partially, as discrete solid crystallites suspended in the composition. The crystallites typically have a size of up to 60 e.g. 5 to 50 microns.

We have found that Formulations containing sodium tripolyphosphate as Builder, or at least a major proportion of sodium tripolyphosphate in admixture with other Builders, exhibit stability and mobility over a wider range of Dry Weight than corresponding Formulations with other Builders. Such Formulations are therefore preferred. Our invention, however, also provides compositions comprising other Builders such as potassium tripolyphosphate, carbonates, zeolites, nitrilo triacetates, citrates, metaphosphates, pyrophosphates, phosphonates, EDTA and/or polycarboxylates, optionally but preferably, in admixture with tripolyphosphate. Orthophosphates may be present, preferably as minor components in admixture with tripolyphosphate, as may alkali metal silicates.

The last mentioned are particularly preferred and constitute a feature of our preferred embodiments since they perform several valuable functions. They provide the free alkalinity desirable to saponify fats in the soil, they inhibit corrosion of aluminium surfaces in washing machines and they have an effect as Builders. In addition, they are effective as Electrolytes to "salt out" Active Ingredients from the

predominantly aqueous liquid phase thereby reducing the proportion of Active Ingredient in solution and improving the stability and fluidity of the composition. Accordingly, we prefer that compositions of our invention should contain at least 1% and up to 12.3% by weight of the composition preferably at least 2% and up to 10%, most preferably more than 3% and up to 6.5% e.g. 3.5 to 5% of alkali metal silicate, preferably sodium silicate measured as SiO_2 based on the total weight of composition.

Typically, the silicate used to prepare the above compositions has an $\text{Na}_2\text{O}:\text{SiO}_2$ ratio of from 1:1 to 1:2 or 1:1.5 to 1:1.8. It will however be appreciated that any ratio of Na_2O (or other base) to SiO_2 , or even silicic acid could be used to provide the silicate in the composition, and any necessary additional alkalinity provided by addition of another base such as sodium carbonate or hydroxide. Formulations not intended for use in washing machines do not require silicates provided that there is an alternative source of alkalinity.

The Builder normally constitutes at least 15% by weight of the compositions, preferably at least 20%. We prefer that the ratio of Builder to surfactant is greater than 1:1 preferably 1.2:1 to 5:1.

15 Electrolyte

The concentration of dissolved organic material and more particularly of Active Ingredients in the predominantly aqueous, liquid phase is preferably maintained at a low level. This may be achieved by selecting, so far as possible, surfactants which are sparingly soluble in the predominantly aqueous phase, and keeping to a minimum the amount of any more soluble surfactant which is desired for the particular end use. For a given surfactant system and Payload, we have found that it is generally possible to stabilise the system in accordance with an embodiment of our invention by including in the at least one predominantly aqueous phase a sufficient quantity of Electrolyte.

An effect of the Electrolyte is to limit the solubility of Active Ingredient in the at least one predominantly aqueous phase, thereby increasing the proportion of surfactant available to provide a solid, liquid crystal, or vesicular matrix which stabilises the compositions of our invention.

Preferably, the proportion of Electrolyte dissolved in the at least one predominantly aqueous phase is sufficient to provide a concentration of 2.0 to 4.5 gram moles per litre of alkali metal, alkaline earth metal and/or ammonium cations. The stability of the system may be further improved by ensuring so far as possible that the anions required in the composition are provided by salts which have a common cation, preferably sodium. Thus, for example, the preferred Builder is sodium tripolyphosphate, the preferred anionic surfactants are sodium salts of sulphated or sulphonated anionic surfactants and any anti-redeposition agent, e.g. carboxymethyl cellulose, or alkali, e.g. silicate or carbonate are also preferably present as the sodium salts. Sodium chloride, or other soluble inorganic sodium salts may be added to increase the Electrolyte concentration and minimise the concentration of Active Ingredients in the predominantly aqueous liquid phase. The preferred electrolytes, however, are sodium carbonate and sodium silicate.

Alkaline earth metals are only normally present when the Active Ingredients comprise surfactants, such as olefin sulphonates or nonionics which are tolerant of their presence.

US—A—4 018 720 describes compositions containing from 3 to 20% sulphate as a stabiliser. However, the compositions described contain sodium sulphate in excess of its solubility in the composition at normal temperatures, and exhibit unacceptable instability when stored.

It is possible, alternatively, but less preferably to choose salts of potassium or mixed cations.

Stabilising Suspended Solid

The particle size of any solid phase should be less than that which would give rise to sedimentation. The critical maximum limit to particle size will vary according to the density of the particles and the density of the continuous phase and the Yield Point of the composition.

Compositions of our invention preferably contain a particle growth inhibitor. The particle growth inhibitor is believed to function by adsorption onto the faces of suspended crystallites of sparingly soluble solids preventing deposition of further solid thereon from the saturated solution in the predominantly aqueous liquid phase. Typical particle growth inhibitors include sulphonated aromatic compounds. Thus for example, a sodium alkyl benzene sulphonate such as sodium dodecyl benzene sulphonate when present as a surfactant is itself a particle growth inhibitor and may be sufficient to maintain particles of, for example, Builder in the desired size range without additional stabilisers. Similarly, lower alkyl benzene sulphonate salts such as sodium xylene sulphonate or sodium toluene sulphonate have stabilising activity, as well as being conventionally added to liquid detergents as Hydrotropes. In our invention, however, the presence of the lower alkyl benzene sulphonates is less preferred. Sulphonated naphthalenes especially methyl naphthalene sulphonates are effective crystal growth inhibitors. They are not, however, normal ingredients of detergent compositions and therefore on cost grounds they are not preferred. Other particle growth inhibitors include water soluble polysaccharide derivatives such as sodium carboxymethyl cellulose, which is frequently included in detergent compositions as a soil anti-redeposition agent. We, therefore prefer that it should be present in minor amounts in compositions according to our invention, sufficient to perform its normal functions in detergent compositions and to assist in stabilising the suspension, but preferably not sufficient to increase so substantially the viscosity of the predominantly aqueous liquid phase as to impair the pourability of the composition.

EP 0 170 091 B1

Another group of particle growth inhibitors which may optionally be included in compositions according to our invention are the sulphonated aromatic dyes, especially the sulphonated aromatic optical brightening agents, which are sometimes included in powder Formulations.

Typical examples include 4,4'-bis (4-phenyl-1,2,3-triazol-2-yl-2,2'-stilbene disulphonate salts and 4,4'-diphenylvinylene-2,2'-biphenyl disulphonate salts. Such particle growth inhibitors may be included instead of, or more usually in addition to, for example, a sulphonated surfactant.

Other effective particle growth inhibitors include lignosulphonates and C₆₋₁₈ alkane sulphonate surfactants, which latter compounds may also be present as part of the surfactant content of the composition.

The presence of an agglomeration inhibitor is also preferred. The agglomeration inhibitor for use according to our invention may also conveniently be sodium carboxymethyl cellulose. It is preferred that the composition should include an effective agglomeration inhibitor which is chemically distinct from the particle growth inhibitor, despite the fact that, for example, sodium carboxymethyl cellulose, is capable of performing either function. It is sometimes preferred, when preparing the detergent composition to add the crystal growth inhibitor to the composition prior to the agglomeration inhibitor, and to add the agglomeration inhibitor subsequent to the solid phase, so that the crystal growth inhibitor is first adsorbed onto the solid particles to inhibit growth thereof and the agglomeration inhibitor is subsequently introduced to inhibit agglomeration of the coated particles.

Other agglomeration inhibitors which may less preferably be used include polyacrylates and other polycarboxylates, polyvinyl pyrrolidone, carboxy methyl starch and lignosulphonates.

The concentration of the crystal growth inhibitor and agglomeration inhibitor can be widely varied according to the proportion of solid particles and the nature of the dispersed solid as well as the nature of the compound used as the inhibitor and whether that compound is fulfilling an additional function in the composition. For example, the preferred proportions of alkyl benzene sulphonate are as set out hereinbefore in considering the proportion of surfactant. The preferred proportions of sodium carboxy methyl cellulose are up to 2.5% by weight of the composition preferably 0.5 to 2% by weight e.g. 1 to 2% although substantially higher proportions up to 3 or even 5% are not excluded provided they are consistent in the particular Formulation with a pourable composition. The sulphonated optical brighteners may typically be present in proportions of 0.05 to 1% by weight e.g. 0.1 to 0.3% although higher proportions e.g. up to 5% may less preferably be present in suitable compositions.

Alkalinity

The compositions of our invention are preferably alkaline, being desirably buffered with an alkaline buffer adapted to provide a pH above 8 e.g. above 9 most preferably above 10 in a wash liquor containing the composition diluted to 0.5% Dry Weight. They preferably have sufficient free alkalinity to require from 0.4 to 12 mls. preferably 3 to 10 mls. of N/10 HCl to reduce the pH of 100 mls. of a dilute solution of the composition, containing 0.5% Dry Weight, to 9, although compositions having higher alkalinity may also be commercially acceptable. In general lower alkalinities are less acceptable in commercial practice, although not excluded from the scope of our invention.

The alkaline buffer is preferably sodium triphosphosphate and the alkalinity preferably provided at least in part by sodium carbonate or sodium silicate.

Solubilisers

Hitherto, liquid detergent compositions have commonly contained substantial concentrations of Hydrotropes and/or organic water miscible hydroxylic solvents such as methanol, ethanol, isopropanol, glycol, glycerol, polyethylene glycol and polypropylene glycol. Such additives are often necessary to stabilise Group I compositions. However, in Group II and III compositions of the present invention, they may have a destabilising effect which often requires the addition of extra amounts of Electrolyte to maintain stability. They are, moreover, costly and not Functional Ingredients. They may, however, in certain circumstances, promote Pourability. We do not therefore totally exclude them from all compositions of our invention, but we prefer that their presence be limited to the minimum required to ensure adequate Pourability. If not so required we prefer that they be absent.

Payload

Selection of the appropriate Payload is generally important to obtain desired stability and Pourability. Optimum Payload may vary considerably from one type of Formulation to another. Generally speaking it has not been found possible to guarantee Non-sedimenting compositions below about 35% by weight Payload, although some types of Formulation can be obtained in a Non-sedimenting form below 30% Payload, and sometimes as low as 25% Payload. In particular we have obtained Soap based Formulations at concentrations below 25% Pay Load e.g. 24%. We do not exclude the possibility of making such Formulations at Payloads down to 20%.

Prior art references to stable compositions at low Payloads have either been limited to particular Formulations using special stabilisers, or have not provided sufficiently stable suspensions to satisfy normal commercial criteria.

For any given Formulation according to our invention a range of Payloads can be identified within

which the composition is both stable and Pourable. Generally below this range, sedimentation occurs and above the range the Formulation is too viscous. The acceptable range may be routinely determined for any given Formulation by preparing the suspension using the minimum water required to maintain a stirrable composition, diluting a number of samples to progressively higher dilutions, and observing the samples for signs of sedimentation over a suitable period. For some Formulations the acceptable range of Payloads may extend from 30%, or 35% to 60, or 70%, or even 75% by weight for others it may be much narrower, e.g. 40 to 45% by weight.

If no stable Pourable range can be determined by the above methods, the Formulation should be modified according to the teaching herein e.g. by the addition of more sodium silicate solution or other Electrolyte.

Typically Group III Formulations show an increase in Yield Point with increasing Payload. The minimum stable Payload for such typical Group III Formulations usually corresponds to a Yield Point of about 1—1.2 Newtons/m².

15 Preparation

Compositions of our invention can, in many instances be readily prepared by normal stirring together of the ingredients. However, some Formulations according to the invention are not fully stable unless the composition is subjected to more prolonged or vigorous mixing. In some extreme cases the solid content of product may require comminution in the presence of the liquid phase. The use of a colloid mill for the latter is not excluded, but is not generally necessary. In some instances mixing under high shear rate provides products of high viscosity.

The order and conditions of mixing the ingredients are often important in preparing a stable structured mixture according to our invention. Thus a system comprising: water, sodium dodecylbenzene sulphonate, coconut monoethanolamide, sodium tripolyphosphate, sodium silicate, sodium carboxymethyl cellulose and optical brightener at 45% Dry Weight was unstable when the compounds were mixed in the order described above, but when mixed with the coconut monoethanolamide and sodium tripolyphosphate added as the last of the Functional Ingredients, a stable composition was formed.

A method of preparation that we have found generally suitable for preparing stable mixtures from those Formulations which are capable of providing them, is to mix the Active Ingredients or their hydrates, in a concentrated form, with concentrated (e.g. 30 to 60%, preferably 45—50%) aqueous silicate solution, or alternatively, a concentrated solution of any other non-surfactant Electrolyte required in the Formulation. Other ingredients are then added including any anti-redeposition agents, optical brightening agents and foaming agents. The Builder, when not required to provide the initial Electrolyte solution, may be added last. During mixing, just sufficient water is added at each addition to maintain the composition fluid and homogeneous. When all the Functional Ingredients are present, the mixture is diluted to provide the required Pay Load. Typically, mixing is carried out at ambient temperature where consistent with adequate dispersion. Certain ingredients, e.g. non-ionic surfactants such as coconut monoethanolamide require gentle warming e.g. 40° for adequate dispersion. This degree of warming may generally be achieved by the heat of hydration of sodium tripolyphosphate. To ensure sufficient warming we prefer to add the tripolyphosphate in the anhydrous form containing a sufficiently high proportion of the high temperature rise modification commonly called "Phase I". The foregoing procedure is only one of several methods that may be satisfactorily used for all or most of the compositions of our invention. Some Formulations are more sensitive to the order and temperature of mixing than others.

45 Formulation Types

Typically, our Formulations may most conveniently be an anionic type (Type "A") in which the Active Ingredient preferably consists at least predominantly of sulphated or sulphonated anionic surfactant, optionally with a minor proportion of other surfactants such as non-ionic surfactant.

Considering type "A" Formulations according to our invention in more detail, we particularly distinguish high foaming sulphate or sulphonate Formulations and low foaming Formulations.

High foaming Formulations may typically be based on sodium C₁₀₋₁₄ straight or branched chain alkyl benzene sulphonate, alone or in admixture with a C₁₀₋₁₈ alkyl sulphate and/or C₁₀₋₂₀ alkyl 1—10 mole ether sulphate. Small amounts (e.g. up to 1% of the weight of the compositions) of Soap may be present to aid rinsing of the fabric. Nonionic foam boosters and stabilisers, such as C₁₂₋₁₈ acyl (e.g. coconut) monoethanolamide or diethanolamide or their ethoxylates, ethoxylated alkyl phenol, fatty alcohols or their ethoxylates may optionally be present as foam boosters or stabilisers, usually in proportions up to about 6% of the Dry Weight of the composition.

The sodium alkyl benzene sulphonate may be totally or partially replaced, in the above Formulations by other sulphonated surfactants including fatty alkyl xylene or toluene sulphonates, or by e.g. alkyl ether sulphates (preferably) or alkyl sulphates, paraffin sulphonates and olefin sulphonates, sulphocarboxylates, and their esters and amides, including sulphosuccinates and sulphosuccinamates, alkyl phenyl ether sulphates, fatty acyl monoethanolamide ether sulphates or mixtures thereof.

Preferably the sulphated or sulphonated anionic surfactant consists substantially of alkyl benzene sulphonate preferably sodium alkyl benzene sulphonate, e.g. C₁₀₋₁₄ alkyl benzene sulphonate. The

proportion of alkyl benzene sulphonate in the absence of foam boosters is preferably from 20 to 60% e.g. 30 to 55% of the Dry Weight of the composition.

Alternatively, the anionic surfactant may comprise a mixture of alkyl benzene sulphonate, and alkyl sulphate and/or alkyl ether sulphate and/or alkyl phenol ether sulphate in weight proportions of e.g. from 1:5 to 5:1 typically 1:2 to 2:1 preferably 1:1.5 to 1.5:1 e.g. 1:1. In the latter case the total anionic surfactant is preferably from 15 to 50% e.g. 20 to 40% of the Dry Weight of the compositions, in the absence of foam booster.

The alkyl sulphate, and/or alkyl ether sulphate for use in admixture with the alkyl benzene sulphonate typically has an average of from 0 to 5 ethyleneoxy groups per sulphate group e.g. 1 to 2 groups.

According to a preferred specific embodiment our invention provides a Pourable, Non-sedimenting, fluid detergent composition consisting essentially of water and: (A) from 10 to 20% based on the weight of the composition of Active Ingredients comprising a substantially linear sodium alkyl benzene sulphonate having from 10 to 20 aliphatic carbon atoms and optionally an alkyl ethoxy sulphate having an alkyl group with from 10 to 20 carbon atoms, and/or a minor proportion of a non-ionic surfactant and/or of a soap; (B) at least 15% of Builder partly present as solid and selected from condensed phosphates, zeolites, citrates, nitrilotriacetates, ethylenediamine tetracetates, orthophosphates and silicates, wherein at least 50% by weight of said Builder is sodium tripolyphosphate and said Builder further comprises at least 4.7%, based on the total weight of the composition, of sodium carbonate; (C) optionally up to 2.5% by weight of the composition, of carboxymethylcellulose; (D) optionally up to 1% by weight of the composition of optical brightening agent; and (E) optionally minor proportions of ingredients selected from enzymes, bleaches, antifoams, sepiolite clays, fragrances, cationic fabric softeners, dyes and sodium chloride.

According to a second preferred specific embodiment our invention provides a Pourable, Non-Sedimenting, fluid, liquid detergent composition consisting essentially of water and (A) from 10 to 20% based on the weight of the composition of a mixture of a substantially linear C_{10-18} alkyl benzene sulphonate and C_{10-20} alkyl 1-10 mole ethoxy sulphate; (B) at least 15% by weight of the composition of total Builder partly present as suspended solid, selected from sodium tripolyphosphate, zeolite, sodium carbonate, sodium silicate and mixtures thereof; (C) an aqueous Separable Phase containing sufficient dissolved Electrolyte selected from sodium tripolyphosphate, sodium carbonate, sodium silicate and mixtures thereof to provide from 2 to 4.5 gm ions per litre sodium in said phase; and (D) optionally any of the Usual Minor Ingredients; the Payload of said composition being above the minimum at which the composition is Non-sedimenting but below the maximum at which it is Pourable.

In an alternative Formulation the anionic surfactant consists substantially of alkyl sulphate and/or, alkyl ether sulphate. The total concentration of Active Ingredients in the absence of foam booster is preferably from 15 to 50% of the Dry Weight of the composition. Typically the Active Ingredients comprise an average of from 0 to 5 e.g. 0.5 to 3 ethyleneoxy groups per molecule of sulphated surfactant. The fatty alkyl chain length is preferably from 10 to 20°C, higher chain lengths being preferred with higher ethylene-oxy content.

The foregoing types may be varied by substituting for all or part of the anionic active content, any of the sulphated or sulphonated anionic surfactant classes hereinbefore specified.

Soap may be added to any of the foregoing detergent Formulations as an aid to rinsing the fabric. Soap is preferably present for this purpose in concentrations of from 0 to 6% preferably 0.1 to 4% e.g. 0.5 to 2% by Dry Weight of the composition. The amount of Soap is preferably less than 25% of the total sulphated and sulphonated surfactant, to avoid foam suppression; typically less than 10%.

Foam boosters and/or stabilisers may be incorporated in any of the foregoing types of high foam anionic detergent. The foam boosters or stabilisers are typically C_{10-18} alkyl nonionic surfactants such as coconut monoethanolamide or diethanolamide or their ethoxylates, alkyl phenol ethoxylates, fatty alcohols or their ethoxylates or fatty acid ethoxylates. The foam booster and/or stabiliser is added typically in proportions up to 20% of the Dry Weight of the composition e.g. 0.1 to 6% preferably 0.5 to 4%. The presence of foam booster and/or stabiliser may permit a reduction of total concentration of Active Ingredients in a high foam product. Typically, compositions comprising alkyl benzene sulphonate with a foam booster and/or stabiliser will contain from 15 to 40% of alkyl benzene sulphate based on the weight of the composition preferably 20 to 36% e.g. 25% with from 2 to 6% e.g. 4% of nonionic surfactant, the lower proportions of anionic surfactant being preferred with higher proportions of nonionic surfactant and vice versa. The other sulphated or sulphonated anionic surfactant Formulations discussed above may be similarly reduced in active concentration by inclusion of foam boosters and/or stabilisers.

The Builder is preferably sodium tripolyphosphate, optionally but preferably with a minor proportion of soluble silicate although the alternative Builders hereinbefore described may be employed instead, as may mixed Builders. The proportion of Builder in type "A" Formulations is usually at least 30% of the Dry Weight of the composition, preferably from 35% to 85% e.g. 40 to 80%. Builder proportions in the range 50 to 70% of Dry Weight are particularly preferred. The Builder to Active Ingredients ratio should desirably be greater than 1:1 preferably from 1.2:1 to 4:1 e.g. from 1.5:1 to 3:1.

Low foaming Formulations are generally dependent upon the presence of lower proportions of sulphated or sulphonated anionic surfactant than in the high foam types together with higher, but still minor, proportions of Soap, and/or the addition of non-ionic, silicone, or phosphate ester foam depressants.

Our invention therefore provides, according to a further specific embodiment, a Non-sedimenting

EP 0 170 091 B1

Pourable fluid, aqueous based detergent composition, comprising an at least predominantly aqueous phase containing Electrolyte in solution, and suspended particles of Builder, said composition comprising from 15 to 50% based on Dry Weight of Active Ingredient, at least 30% of Builder based on Dry Weight, a ratio of Builder to Active Ingredient greater than 1:1, and optionally the Usual Minor Ingredients, wherein the surfactant comprises from 15 to 50% based on the Dry weight of the composition of sulphated and/or sulphonated anionic surfactant and an effective amount of at least one foam depressant.

Preferably, the foam depressant is selected from Soap, in a proportion of from 20 to 60% based on the weight of sulphated or sulphonated anionic surfactant, C_{16-20} alkyl nonionic foam depressant in a proportion of up to 10% of the Dry Weight of the composition, C_{16-20} alkyl phosphate ester in a proportion of up to 10% of the Dry Weight of the composition and silicone antifoams.

The function of Soap as a foam depressant is dependant on the proportion of Soap to sulphated or sulphonated anionic surfactant. Proportions of 10% or less are not effective as foam depressants but are useful as rinse aids in high foaming detergent compositions. Foam depressant action requires a minimum proportion of about 20% of soap based on the sulphated and/or sulphonated surfactant. If the proportion of soap to sulphated/sulphonated surfactant in a type "A" detergent is above about 60% by weight, the foam depressant action is reduced. Preferably, the proportion of Soap is from 25 to 50% e.g. 30 to 45% of the weight of sulphated/sulphonated surfactant.

Low foaming detergents may contain, in addition to, or instead of soap, a nonionic foam depressant. This may, for example, be a C_{16-22} acyl monoethanolamide e.g. rape monoethanolamide, a C_{16-22} alkyl phenol ethoxylate, C_{16-22} alcohol ethoxylate or C_{16-22} fatty acid ethoxylate. Alternatively, or additionally, the composition may contain an alkali metal mono and/or di C_{16-22} alkyl phosphate ester. The nonionic or phosphate ester foam depressant is typically present in the Formulation in a proportion of up to 10%, preferably 2 to 8% e.g. 3 to 4% based on Dry Weight.

Silicone antifoams may also be used, as or as part of, the foam depressant. The effective concentration of these last in the Formulation is generally substantially lower than in the case of the other foam depressants discussed above. Typically, it is less than 2%, preferably less than 0.1%, usually 0.01 to 0.05% e.g. 0.02% of the Dry Weight of the Formulation.

Our Formulations preferably contain the Usual Minor Ingredients. Certain fabric softeners, such as clays, may be included, however cationic fabric softeners are not normally effective in anionic based Formulations, but may sometimes be included in specially formulated systems.

The type "B" Formulations of our invention comprise Soap as the principal active component. They may additionally contain minor amounts of nonionic or other anionic surfactants.

The typical percentage Dry Weight of type "B" Formulations may be rather lower than type "A", e.g. 20 to 60%, preferably 29 to 45%. The total proportion of Active Ingredients is usually between 10 and 55%, preferably 15 to 40% e.g. 20 to 30% of the Dry Weight of the composition. Builder proportions are typically 20 to 80% of Dry Weight. In general the mobility of type "B" Formulations can be improved by including sufficient water soluble inorganic Electrolyte, especially sodium silicate, in the Formulation.

High foam Soap Formulations may typically contain Active Ingredient consisting substantially of Soap, optionally with a minor proportion of a nonionic foam booster and/or stabilizer as described in relation to type "A" Formulations, and/or with sulphated anionic booster such as alkyl ether sulphate or alkyl ether sulposuccinate.

Low foam type B Formulations may contain a lower concentration of Soap together with minor proportions of sulphated and or sulphonated anionic surfactant, nonionic or phosphate ester foam depressants and/or silicone antifoams.

The relationship between sulphated and/or sulphonated anionic surfactants and Soap in a type "B" low foam Formulation is the converse of that in a type "A" low foam Formulation. In a type "B" Formulation, the sulphated and/or sulphonated anionic surfactant acts as foam suppressant when present in a proportion of from about 20 to about 60% of the weight of the Soap.

The nonionic, phosphate ester and silicone foam depressants are, conveniently, substantially as described in relation to type "A" detergents.

Type "B" detergents may contain any of the Usual Minor Ingredients. As in the case of type "A" Formulations, cationic fabric softeners are not normally included, but other fabric softeners may be present.

Non-ionic based detergents (type "C") represent a further aspect of the present invention. There has been a trend towards the use of non-ionic surfactants in laundry detergents because of the increasing proportion of man-made fibre in the average wash. Non-ionics are particularly suitable for cleaning man-made fibres. However, no commercially acceptable, fully built, non-ionic liquid detergent has yet been marketed.

Even in the detergent powder field, the choice and level of non-ionic surfactant has been restricted. Many of the detergent Formulations of our invention hereinbefore described have been designed to give stable, Pourable, fluid detergent compositions having a washing performance equivalent to existing types of powder Formulation, or to compositions which could readily be formulated as powders. However, it has not hitherto been possible to formulate certain types of potentially desirable nonionic based detergents satisfactorily, even as powders. This is because "solid" compositions containing sufficiently high proportions of the desired nonionic surfactant often form sticky powders which do not flow freely and may

give rise to packaging and storage problems. Such surfactants have therefore had to be restricted to below optimum proportions of detergent powders, or to low Pay Load, dilute, or light duty, liquid compositions.

Any of the nonionic surfactants hereinbefore described or any mixture thereof may be used according to this embodiment of the invention. Preferably, the surfactant comprises a C₁₂₋₁₈ alkyl group, usually straight chain, although branched-chain and/or unsaturated hydrocarbon groups are not excluded. Preferably, the nonionic surfactants present have an average HLB of 12 to 15.

The preferred nonionic surfactant in Type C Formulations is fatty alcohol ethoxylate.

For high foam type "C" Formulations, we prefer C₁₂₋₁₆ alkyl nonionics having 8 to 20 ethyleneoxy groups, alkyl phenol ethoxylate having 6-12 aliphatic carbon atoms and 8 to 20 ethyleneoxy groups together optionally with a minor proportion e.g. 0 to 20% of the Dry Weight of the composition of anionic surfactant preferably sulphated and/or sulphonated anionic e.g. alkyl benzene sulphonate, alkyl sulphate, alkyl ether sulphate, paraffin sulphonate, olefin sulphonate or any of the other sulphated or sulphonated surfactants described above, but not including substantial amounts of any foam depressant. The Formulation may however include a nonionic foam booster and/or stabiliser such as C₁₀₋₁₈ acyl monoethanolamide typically in proportions as described above in relation to type "A" Formulations. Preferably the non-ionic Active Ingredients together have an HLB of 12-15.

Low foam nonionic compositions according to our invention are especially preferred. They preferably comprise 10 to 40% based on Dry Weight of the composition of C₁₂₋₁₈ alkyl 5 to 20 mole ethyleneoxy, nonionic surfactants such as fatty alcohol ethoxylates, fatty acid ethoxylates or alkyl phenol ethoxylates, having a preferred HLB of 12 to 15. They optionally contain a minor proportion, e.g. up to 10% by weight of the composition of any of the anionic sulphated and/or sulphonated surfactants hereinbefore described in relation to type "A" detergents, and they contain a foam depressant such as a mono, di- or trialkyl phosphate ester or silicone foam depressant, as discussed hereinbefore in the context of low foaming type "A" detergents.

Type "C" Formulations may contain any of the Usual Minor Ingredients.

In particular, nonionic based detergents of our invention may incorporate cationic fabric softeners. The cationic fabric softeners may be added to type "C" Formulations, in a weight proportion based on the nonionic surfactant of from 1:1.5 to 1:4 preferably 1:2 to 1:3. The cationic fabric softeners are cationic surfactants having two long chain alkyl or alkenyl groups, typically two C₁₆₋₂₀ alkyl or alkenyl groups, preferably two tallowyl groups. Examples include di C₁₂₋₂₀ alkyl di (lower, e.g. C₁₋₃, alkyl) ammonium salts, e.g. di tallowyl dimethyl ammoniumchloride, di (C₁₆₋₂₀ alkyl) benzalkonium salts e.g. ditallowyl methyl benzyl ammonium chloride, di C₁₆₋₂₀ alkyl amido imidazolines and di C₁₆₋₂₀ acyl amido amines or quaternised amino amines, e.g. bis (tallow amido ethyl) ammonium salts.

Formulations containing cationic fabric softeners preferably do not contain sulphated or sulphonated anionic surfactants or soaps. They may however contain minor proportions of anionic phosphate ester surfactants e.g. up to 3% by weight of the composition preferably up to 2%. They may additionally or alternatively contain minor proportions (e.g. up to 3%, preferably 1 to 2% by weight of amphoteric surfactants such as betaines and sulphobetaines. They may also contain smectite clays, and the Usual Minor Ingredients.

Minor Ingredients

Compositions of the invention may contain the Usual Minor Ingredients. Principal of these are antiredeposition agents, optical brightening agents and bleaches.

The most commonly used antiredeposition agent in making detergents is sodium carboxymethyl cellulose (SCMC), and we prefer that this be present in compositions of this invention, e.g. in conventional amounts, e.g. greater than 0.1 but less than 5%, and more usually between 0.2 and 4%, especially 0.5 to 2% preferably 0.7 to 1.5%. Generally speaking SCMC is effective at concentrations of about 1% and we prefer not to exceed the normal effective concentrations very substantially, since SCMC in greater amounts can raise the viscosity of a liquid composition very considerably. At the higher limits discussed above e.g. 4-5% of SCMC, many Formulations cannot be obtained in a Pourable form at high Pay Loads.

Alternative antiredeposition and/or soil releasing agents include methylcellulose, polyvinylpyrrolidone, carboxymethyl starch and similar poly electrolytes, all of which may be used in place of SCMC, as may other water soluble salts of carboxymethyl cellulose.

Optical Brighteners (OBA's) are optional, but preferred ingredients of the compositions of our invention. Unlike some prior art formulations, our compositions are not dependent on OBA's for stability and we are therefore free to select any convenient and cost effective OBA, or to omit them altogether. We have found that any of the fluorescent dyes hitherto recommended for use as OBA's in liquid detergents may be employed, as may many dyes normally suitable for use in powder detergents. The OBA may be present in conventional amounts. However we have found that OBA's in some liquid detergent (e.g. type "C" formulations) tend to be slightly less efficient than in powder detergents and therefore may prefer to add them in slightly higher concentrations relative to the Formulation than is normal with powders. Typically concentrations of OBA between 0.05 and 0.5% are sufficient e.g. 0.075 to 0.3% typically 0.1 to 0.2%. Lower concentrations could be used but are unlikely to be effective, while higher concentrations, while we do not exclude them, are unlikely to prove cost effective and may, in some instances rise to problems of compatibility.

Typical examples of of OBA's which may be used in the present invention include:

ethoxylated 1,2-(benzimidazolyl) ethylene;

2-styrylnaphth[1,2d-]oxazole;

1,2-bis(5' methyl-2-benzoxazolyl)ethylene;

5 disodium-4,4'-bis(6-methylethanolamine-3-anilino-1,3,5-triazin-2''-yl)-2,2'-stilbene sulphonate;

N-(2-hydroxyethyl-4,4'-bis (benzimidazolyl)stilbene;

tetrasodium 4,4'-bis[4''-bis(2''-hydroxymethyl)-amino-6''(3''-sulphophenyl) amino-1'',3'',5''-triazin-2''-yl amino]-2,2'-stilbenedisulphonate;

disodium-4-(6''-sulphonaphtho[1',2'-d]triazol-2-yl)-2-stilbenesulphonate;

10 disodium 4,4'-bis [4''-(2'''-hydroxyethoxy)-6''-amino-1'',3'',5''-triazin-2''-yl amino] 2,2'-stilbenedisulphonate;

4-methyl-7-dimethyl aminocoumarin; and

alkoxylated 4,4'-bis-(benzimidazolyl) stilbene.

Bleaches may optionally be incorporated in liquid detergent compositions of our invention subject to chemical stability and compatibility. Encapsulated bleaches may form part of the suspended solid.

The action of peroxy bleaches in compositions of our invention may be enhanced by the presence of bleach activators such as tetra-acetyl ethylenediamine, in effective amounts.

Photoactive bleaches such as zinc or aluminium sulphonated phthalocyanin, may be present.

Perfumes and colourings are conventionally present in laundry detergents in amounts up to 1 or 2%, and may similarly be present in compositions of our invention. Provided normal care is used in selecting additives which are compatible with the Formulation, they do not affect the performance of the present invention.

Proteolytic and amylolytic enzymes may optionally be present in conventional amounts, together optionally with enzyme stabilizers and carriers. Encapsulated enzymes may be suspended.

25 Other Minor Ingredients include germicides such as formaldehyde, opacifiers such as vinyl latex emulsion and anticorrosives such as benzotriazole.

Compositions of our invention are, in general, suitable for laundry use and our invention provides a method of washing clothes or other soiled fabric by contacting and, preferably, agitating them in an aqueous wash liquor containing any composition of the invention as described herein. Low foam compositions herein described are in particular of use in automatic washing machines. The compositions may also be used in the washing of dishes, or the cleaning of hard surfaces, the low foam products being particularly suitable for use in dishwashing machines. These uses constitute a further aspect of the invention.

Compositions of our invention may, generally, be used for washing clothes in boiling water, or for washing at medium or cool temperatures, e.g. 50 to 80°C, especially 55 to 68°C, or 20 to 50°C especially 30 to 40°C, respectively. Typically the compositions may be added to the washwater at concentrations of between 0.05 and 3% Dry Weight based on the wash water preferably 0.1 to 2%, more usually 0.3 to 1% e.g. 0.4 to 0.8%.

The invention will be illustrated by the following examples:

40 wherein all figures relate to % by wt. based on total composition, unless otherwise stated.

Compositions of the Various Feedstocks Materials

1. Sodium C₁₀₋₁₄ linear alkyl benzene sulphonate

For all formulations the alkyl benzene sulphonate used was the sodium salt of the largely para-sulphonated "Dobane" JN material. (Dobane is a Registered Trade Mark).

45 The composition is as follows:—

C ₁₀	C ₁₁	C ₁₂	C ₁₃	C ₁₄	C ₁₅
13.0	27.0	27.0	19.0	11.0	1.0

50 This composition refers only to the alkyl chain length.

2. Coconut Monoethanolamide

Has the following composition:—

55 RCO(NHCH₂CH₂OH)

where R is as follows:—

C ₅	0.5%
C ₇	6.5%
C ₉	6.0%
C ₁₁	49.5%
C ₁₃	19.5%
C ₁₅	8.5%

65

EP 0 170 091 B1

	Stearic	C ₁₇	2.0%
	Oleic	C ₁₇	6.0%
5	Linoleic	C ₁₇	1.5%

3. Sodium alpha olefin sulphonate

This material is the sodium salt of sulphonated C₁₆/C₁₈ olefin having the following approximate composition.

10	55.0%	C ₁₆	Terminal olefin
	45.0%	C ₁₈	Terminal olefin

4. C₁₂₋₁₈ Alcohol + 8 moles Ethylene Oxide

This material is an average 8 mole ethylene oxide condensate of an alcohol of the following composition:—

	C ₁₀	3.0%
20	C ₁₂	57.0%
	C ₁₄	20.0%
25	C ₁₆	9.0%
	C ₁₈	11.0%

5. Sodium C₁₄₋₁₇ n-Alkane Sulphonate

30 This material was prepared by neutralising sulphonated C₁₄₋₁₇ normal paraffins with sodium hydroxide and contained 10% disulphonates based on total Active Ingredients.

6. Sodium C₁₂₋₁₈ Sulphate

This refers to the sodium salt of a sulphated fatty alcohol having the following composition:—

35	C ₁₀	3.0%
	C ₁₂	57.0%
	C ₁₄	20.0%
	C ₁₆	9.0%
40	C ₁₈	11.0%

7. Sodium Tripolyphosphate

This material was added as anhydrous Na₅P₃O₁₀ containing 30% Phase I.

45

8. Sodium Silicate

This material is added to Formulations as a viscous aqueous solution containing 47% solids with a Na₂O:SiO₂ ratio of 1:1.6.

50 9. Optical Brightener

The optical brightening agent for Examples 51 to 66 was the disodium salt of 4;4'-[di(styryl-2-sulphonic acid)] biphenyl which is marketed under the trademark "TINOPAL CBS-X". The optical brightener for Examples 1 to 50 was a mixture of the aforesaid Optical brightener with the disodium salt of 4;4'-[di(4-chlorostyryl-3-sulphonic acid)] biphenyl which mixture is marketed under the trademark "TINOPAL ATS-X".

55

Note

All alcohols and their ethylene oxide adducts referred to are straight chained and primary.

60 All the examples were prepared by adding the surfactant, usually as hydrated solid, to a 47% solution of the silicate. The other ingredients were then added in the order shown in the tables reading from top to bottom, except that the principal Builder was added last. At each stage, a small addition of water was made, whenever it was required in order to maintain a fluid homogeneous system. Finally, the composition was diluted to the desired percentage Dry Weight. The entire preparation was carried out as close as possible to ambient temperature consistent with adequate dispersion of the ingredients. In the case of examples 20, 65 21, 22 and 23, a concentrated aqueous solution of the electrolyte (i.e. sodium chloride, sodium carbonate

EP 0 170 091 B1

and potassium carbonate respectively) was used in place of the solution of silicate in the above procedure. In some instances, especially with relatively high melting non-ionic surfactants, such as coconut monoethanolamide, gentle warming e.g. to about 40°C was required to ensure complete dispersion. In all the Examples in which sodium tripolyphosphate was used in substantial amounts this temperature was

5 achieved by the heat of hydration without external heating.

	Eg. 1	Eg. 2	Eg. 3	Eg. 4	(a)	Eg. 5 (b)	(c)	Eg. 6	Eg. 7	Eg. 8
Sodium C ₁₀₋₁₄ linear alkyl benzene sulphonate	12.4	15.9	12.2	15.6	11.2	12.0	13.0	14.0	12.0	12.0
Coconut monoethanolamide	1.6	2.1	1.6	2.1	1.5	1.6	1.7	1.9	1.6	1.6
Sodium tripolyphosphate	26.0	19.1	25.6	18.7	26.2	28.0	30.4	32.7	28.0	28.0
Sodium Silicate	6.5	8.5	6.4	9.3	6.0	6.4	7.0	7.5	6.4	6.4
Sodium carboxymethyl cellulose	—	—	1.4	1.8	1.5	1.6	1.7	—	1.6	1.6
Optical Brightening Agent	—	—	0.2	0.2	0.15	0.16	0.17	0.18	—	0.16
Benzotriazole	—	—	—	—	—	—	—	—	—	0.007
Perfume	—	—	—	—	—	—	—	—	—	0.05
Water	to 100	to 100	to 100	to 100	to 100	to 100	to 100	to 100	to 100	to 100

	Eg. 9		Eg. 10		Eg. 11	Eg. 12
	(a)	(b)	(a)	(b)		
Sodium C ₁₀₋₁₄ linear alkyl benzene sulphonate	11.6	12.6	17.0	18.0	11.6	9.9
Coconut monoethanolamide	1.5	1.7	1.5	1.5	1.5	1.3
Sodium tripolyphosphate	30.2	32.7	25.5	27.0	25.7	23.1
Sodium Silicate	6.2	6.7	5.8	6.2	3.5	5.3
Sodium carboxymethyl cellulose	1.5	1.7	1.5	1.5	1.5	2.0
Optical Brightening Agent	0.15	0.17	0.16	0.17	0.13	0.14
Water	to 100	to 100	to 100	to 100	to 100	to 100

EP 0 170 091 B1

Components	Eg. 13	Eg. 14	Eg. 15	Eg. 16	Eg. 17	Eg. 18	Eg. 19
Triethanolamine C ₁₆₋₁₈ alkyl sulphate	9.0	—	—	—	—	—	—
Sodium C ₁₆₋₁₈ alkyl sulphate	—	10.0	—	—	—	—	—
Sodium salt of alpha sulpho C ₁₆₋₁₈ fatty acid methyl ester	—	—	8.5	—	—	—	—
Sodium salt of three mole ethoxylate of C ₁₆₋₁₈ alcohol sulphate	—	—	—	9.6	—	—	—
Disodium C ₁₆₋₁₈ alkyl sulphosuccinamate	—	—	—	—	10.8	—	—
Sodium salt of two mole ethoxylate of C ₁₂₋₁₄ alcohol sulphate	—	—	—	—	—	10.8	—
Sodium C ₉₋₁₃ linear alkylbenzene sulphate	—	—	—	—	—	—	12.0
Coconut monoethanol-amide	1.2	1.3	1.1	1.3	1.4	1.5	1.6
Sodium tripolyphosphate	21.0	23.4	19.8	22.5	25.3	25.3	28.1
Sodium silicate	4.8	5.4	4.5	5.1	5.8	5.9	6.5
Sodium carboxymethyl cellulose	1.2	1.3	1.1	1.3	1.4	1.5	1.6
Optical brightening agent	0.11	0.12	0.10	0.13	0.14	0.14	0.15
Water	to 100	to 100	to 100	to 100	to 100	to 100	to 100

Components	Eg. 20	Eg. 21	Eg. 22	(a)	Eg. 23 (b)	(c)	Eg. 24
Sodium C ₁₀₋₁₄ linear alkylbenzene sulphonate	12.1	12.1	12.1	15.0	17.0	18.0	12.5
Coconut monoethanol-amide	1.6	1.6	1.6	—	—	—	1.7
Sodium tripolyphosphate	28.2	28.2	28.2	16.7	18.9	20.0	29.1
Sodium silicate	—	—	—	3.3	3.8	4.0	—
Sodium chloride	6.2	—	—	—	—	—	—
Sodium carbonate	—	5.6	—	4.2	4.7	5.0	—
Potassium carbonate	—	—	7.3	—	—	—	—
Sodium carboxymethyl cellulose	1.6	1.6	1.6	1.3	1.5	1.6	1.7
Optical brightening agent	0.15	0.15	0.15	0.17	0.19	0.20	0.15
Water	to 100	to 100	to 100	to 100	to 100	to 100	to 100

EP 0 170 091 B1

Components	Eg. 25	Eg. 26	Eg. 27	Eg. 28	Eg. 29	Eg. 30	Eg. 31
Sodium C ₁₀₋₁₄ linear alkylbenzene sulphonate	11.2	10.2	16.1	15.0	13.3	10.2	14.2
Coconut monoethanolamide	1.5	1.3	2.2	1.9	1.8	1.4	1.9
Zeolite A	34.8	15.8	—	—	—	—	—
Trisodium Citrate	—	—	—	—	31.0	—	—
Trisodium nitrilo triacetate	—	—	30.6	14.0	—	—	—
Sodium Tripolyphosphate	—	15.8	—	14.0	—	15.8	33.1
Sodium Orthophosphate	—	—	—	—	—	8.8	—
Sodium silicate	6.0	5.5	8.8	8.0	7.1	5.4	3.8
Sodium carboxymethyl cellulose	1.5	1.3	2.2	1.9	1.8	1.4	1.9
Optical brightening agent	0.14	0.13	0.2	0.19	0.17	0.13	0.18
Water	to 100	to 100	to 100	to 100	to 100	to 100	to 100

Components	Eg. 32	Eg. 33
Sodium C ₁₀₋₁₄ linear alkylbenzene sulphonate	12.0	13.1
Coconut monoethanolamide	1.6	1.7
Sodium Tripolyphosphate	28.0	30.7
Sodium silicate	6.4	7.0
Sodium xylene sulphonate	—	5.5
Sodium carboxymethyl cellulose	1.6	1.7
Optical brightening agent	—	0.18
Detergent Enzymes (Esperase Slurry 8.0)	0.07	—
Water	to 100	to 100

EP 0 170 091 B1

Components	Eg. 34	Eg. 35	Eg. 36	Eg. 37	Eg. 38	Eg. 39	Eg. 40	Eg. 41
Triethanolamine C ₁₆₋₁₈ alkyl sulphate	7.9	—	—	—	—	—	—	—
Sodium C ₁₆₋₁₈ alpha olefin sulphonates	—	11.0	12.8	12.4	—	—	—	—
Sodium C ₁₄₋₁₇ n-alkane sulphonate	—	—	—	—	12.0	11.1	12.4	13.2
Coconut monoethanol-amide	1.1	1.5	1.7	1.7	1.6	1.5	1.7	1.7
Sodium tripolyphosphate	18.5	25.7	30.1	29.1	28.1	25.9	29.1	30.8
Sodium silicate	6.4	5.9	8.6	10.1	6.5	7.4	10.1	12.4
Sodium carboxymethyl cellulose	1.1	1.5	1.7	1.7	1.6	1.5	1.7	1.7
Optical brightening agent	0.10	0.14	0.17	0.16	0.16	0.14	0.16	0.16
Water	to 100	to 100	to 100	to 100	to 100	to 100	to 100	to 100

Components	(a)	Eg. 42 (b)	(c)	Eg. 43	Eg. 44	Eg. 45	Eg. 46
Sodium C ₁₀₋₁₄ linear alkylbenzene sulphonate	1.2	1.3	1.5	1.6	1.8	2.1	1.3
Sodium soap, based on a fatty acid of 274 Mean Molar Weight	3.7	4.0	4.6	5.2	5.9	6.4	6.6
Eleven moles ethoxylate of C ₁₆₋₁₈ alcohol	1.4	1.5	1.8	2.0	2.2	2.4	2.1
Sodium tripolyphosphate	13.9	15.0	17.4	20.0	22.6	24.8	19.8
Sodium silicate	3.0	3.3	3.8	5.0	6.0	7.8	3.8
Sodium carboxymethyl cellulose	0.8	0.9	1.0	1.1	1.3	1.3	1.2
Optical brightening agent	0.11	0.12	0.13	0.14	0.16	0.18	0.10
Water	to 100	to 100	to 100	to 100	to 100	to 100	to 100

EP 0 170 091 B1

Components	(a)	Eg. 47 (b)	(c)	Eg. 48
Sodium C ₁₀₋₁₄ linear alkylbenzene sulphonate	8.5	9.0	10.0	3.6
Fifteen moles ethoxylate of C ₁₆₋₁₈ alcohol	—	—	—	7.1
Sodium salt of a 50:50 mixed mono and di C ₁₆₋₁₈ alkyl phosphate	1.7	1.8	2.0	—
Sodium tripolyphosphate	25.5	27.0	29.0	24.9
Sodium silicate	5.1	5.4	6.0	3.6
Sodium carboxymethyl cellulose	1.4	1.4	1.6	0.7
Optical brightening agent	0.17	0.18	0.20	0.14
Silicone defoamer	—	—	—	0.02
Water	to 100	to 100	to 100	to 100

Components	(a)	Eg. 49 (b)	(c)	Eg. 50	Eg. 51	Eg. 52	Eg. 53	Eg. 54
Sodium salt of three mole ethoxylate of C ₁₂₋₁₅ alcohol sulphate	—	—	—	—	—	3.7	—	—
Sodium C ₁₀₋₁₄ linear alkylbenzene sulphonate	—	—	—	—	4.1	—	—	—
Coconut monoethanol-amide	1.8	2.1	2.3	2.6	—	—	—	—
Eight mole ethoxylate of C ₁₂₋₁₈ alcohol	5.8	6.6	7.5	—	8.2	7.5	10.8	4.6
2-tallow-1-methyl-1-(tallow-amidoethyl) imidazoline methyl sulphate	—	—	—	—	—	—	—	2.5
Sodium salt of a 50:50 mixed mono and di C ₁₆₋₁₈ alkyl phosphate	—	—	—	—	0.8	0.7	0.7	0.6
Fifteen moles ethoxylate of C ₁₆₋₁₈ alcohol	—	—	—	—	—	—	—	4.6
Five mole ethoxylate of C ₁₃₋₁₅ alcohol	—	—	—	8.3	—	—	—	—
Sodium tripolyphosphate	21.4	24.5	27.5	30.6	24.6	22.4	21.8	21.7
Sodium silicate	4.9	5.6	6.3	7.0	6.0	5.5	5.3	5.0
Sodium carboxymethyl cellulose	1.0	1.1	1.3	1.4	1.2	1.1	1.0	0.9
Optical brightening agent	0.11	0.12	0.14	0.15	0.13	0.12	0.11	—
Water	to 100	to 100	to 100	to 100	to 100	to 100	to 100	to 100

EP 0 170 091 B1

Components	Eg. 55	Eg. 56	Eg. 57	Eg. 58	Eg. 59
Sodium C ₁₀₋₁₄ Linear Alkyl Benzene Sulphonate	—	11.4	11.8	12.0	10.9
Sodium C ₁₂ branched chain Alkyl Benzene Sulphonate	11.4	—	—	—	—
Coconut monoethanol-amide	1.5	—	—	1.6	1.4
Coconut diethanolamide	—	1.5	—	—	—
Sodium ethylenediamine tetrakis (methenephosphonate)	—	—	—	0.25	2.3
Sodium Tripolyphosphate	26.7	26.7	27.6	28.0	25.5
Sodium Silicate	6.2	6.2	6.4	6.4	5.8
Sodium Carboxymethyl-cellulose	1.5	1.5	1.6	1.6	1.4
Optical Brightening Agent	0.15	0.15	0.15	0.15	0.13
Water	to 100	to 100	to 100	to 100	to 100

	Eg. 60	Eg. 61
Sodium C ₁₀₋₁₄ Linear alkyl benzene sulphonate	5.2	6.5
Sodium C ₁₆₋₁₈ Alkyl Sulphate	3.7	4.6
Sodium 1 mole ethoxy C ₁₄₋₁₅ alkyl ether sulphate	4.5	5.5
C ₁₂₋₁₈ alcohol 8 mole ethoxylate	1.5	1.9
Sodium Tripolyphosphate	—	29.6
Sodium silicate	18.6	—
Sodium carbonate	14.9	—
Sodium carboxymethylcellulose	1.5	1.8
Optical Brightening Agent	0.15	0.18
Water	to 100	to 100

EP 0 170 091 B1

		Eg. 62	Eg. 63	Eg. 64	Eg. 65
	Sodium C ₁₀₋₁₄ linear alkylbenzene sulphonate	—	—	11.5	10.9
5	Sodium C ₁₄₋₁₆ alkyl olefin sulphonate	17.9	17.9	—	—
	Sodium C ₁₆₋₁₈ alkyl sulphate	—	—	7.6	7.2
10	C ₁₂₋₁₈ alcohol 8 mole ethoxylate	2.7	2.7	2.9	2.7
	Sodium Tripolyphosphate	13.4	—	14.3	—
15	Zeolite A	—	13.4	—	13.6
	Sodium Silicate	8.9	8.9	9.6	9.0
	Sodium Carboxymethylcellulose	1.4	1.4	1.5	1.5
20	Optical Brightening Agent	0.14	0.14	0.15	0.15
	Water	to 100	to 100	to 100	to 100

Of the Examples, 1 and 2 represent a basic type A Formulation, 3 and 4 a type A formulation with SCMC and optical brightener, 5(a), (b) and (c) represent a type A Formulation at three different Pay Loads, 6 and 7 demonstrate that neither SCMC nor optical brightener is essential to obtain a Non-sedimenting Formulation; 8 contains anticorrosive and perfume; 9(a) and (b) illustrate a high Builder to Active ratio Formulation (3:1) at two Pay Loads, 10(a) and (b) illustrate a relatively low Builder to Active Formulation at two Pay Loads; 11 corresponds to a Non-sedimenting Formulation obtained by centrifuging the Formulation of Example 9 at low Payload for only three hours and decanting the supernatant liquor; 12 illustrates the effect of relatively high SCMC levels; 13 to 19 illustrate Type A Formulations with various anionic surfactants; 20 to 23 illustrate various Electrolytes, and 24 is a Formulation in which sodium tripolyphosphate is the sole Electrolyte; 25 to 30 illustrate various Builders and mixtures thereof; 31 is a high Builder to Active Formulation; 32 is an enzyme Formulation; 33 contains Hydrotrope; 34 has a triethanolamine salt of the surfactant; 35 to 37 illustrate olefin sulphonate and 38 to 41 paraffin sulphonate Formulations, in each case with successively increased Electrolyte; 42 to 45 illustrate type B formulations, 42 at three Pay Loads and 43 to 45 with increasing Electrolyte; 46 corresponds to Type B Formulation obtained after centrifuging 42 at low Pay Load for only three hours; 47 and 48 illustrate low foam Type A and C Formulations respectively; 49 to 53 illustrate various Type C Formulations; 54 is a Type C Formulation with cationic fabric softener; 55 illustrates a branched chain alkyl benzene sulphonate, 56 coconut diethanolamide and 57 a nonionic free formulation; 58 and 59 illustrate the use of phosphonate builders; 60 to 61 relate to formulations particularly adapted to different parts of the North American market, being respectively phosphate free and high phosphate; 62 to 65 are formulations adapted to the needs of certain Asian markets.

The comparative example represents a commercial Formulation currently being marketed in Australia, which corresponds to Australian Patent 522983. The comparative example was the material as purchased, except for the neutron scattering results which were carried out on samples prepared in accordance with the example of the patent to match the commercial Formulation as analysed and using deuterium oxide instead of water. The composition, by analysis was:

	%
Sodium C ₁₀₋₁₄ linear alkylbenzene sulphonate	12
Sodium salt of three mole ethoxylate of C ₁₂₋₁₅ alcohol sulphate	3
Sodium tripolyphosphate	15
Sodium carbonate	2.5
Optical brightener (Tinopal LMS)	0.5
Sodium carboxymethyl cellulose	1.0
Water	to 100

EP 0 170 091 B1

The above composition corresponded to that specified in the example of the Australian patent, except that the latter specifies the sodium carboxymethyl cellulose, together with perfume, colouring and substantive blueing agents as being "qs".

3. Example Test Results

The foregoing examples were subjected to various tests, the results of which are tabulated:

Note: The Phases separated from the centrifuge test are numbered from the bottom (i.e. the densest layer) upwards.

1 Angstrom (Å) = 0.1 nm.

Examples	1		2	
	1	2	1	2
1. Centrifuge Test Results				
i. No. of Phases Separated	1	2	1	2
ii. Description	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid
iii. Proportion (%)	80.9	19.1	-	-
iv. Surfactant content (%)	-	<0.1	-	-
v. Loss on Drying at 110 °C (%)	-	74.8	-	-
vi. Viscosity (Pa.S) at 20 °C	-	0.01	-	-
2. Classification (Group) by Centrifuging	III		III	
3. Viscosity (Pa.S)				
4. Yield Points (Newtons/m ² x 10)				
5. Neutron Diffraction Results				
i. Micellar scattering				
ii.a No. of other peaks				
b Description				
c Structural repeat distance (Å)				
iii. Suggested Structure				
6. X-ray Diffraction Results				
i. Micellar Scattering				
ii.a No. of other peaks				
b Description				
c Structural repeat distance (Å)				
iii. Suggested Structure				
7. Electron Microscopy Results				
Description				
8. Mobility	Pourable		Pourable	
9. Stability	No sedimentation over 12 months at ambient laboratory temperatures		No sedimentation over 12 months at ambient laboratory temperature	

EP 0 170 091 B1

Examples	3	4	5(a)
1.			
i.	1	1	1
ii.	2	2	2
	Opaque	Opaque	Opaque
	solid/paste	solid/paste	solid/paste
	clear	clear	clear
	thin	thin	thin
	liquid	liquid	liquid
iii.			75
iv.			25
v.			< 0.1
vi.			77.3
			0.01
2.	III	III	III
3.	-	-	1.70
4.			12
5.			
i.			Present - narrow
ii.a			one
b			narrow
c			33.4 Å
iii.			Lamellar hydrated solid
6.			
i.			
ii.a			
b			
c			
iii.			
7.			
i.			
ii.			
8.	Pourable	Pourable	Readily pourable
9.	No sedimentation over 12 months at ambient laboratory temperatures	No sedimentation over 12 months at ambient temperature	No sedimentation over 12 months at ambient temp.

EP 0 170 091 B1

Examples	5(b)		5(c)		6	
1.						
i.	1	2	1	2	1	2
ii.	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid
iii.	81.7	18.3	86	14%		
iv.		<0.1		<0.1		
v.		75.7		74%		
vi.		0.01		0.01		
2.	III		III		III	
3.	2.60		4.86		4.58	
4.	36		178			
5.						
i.			Present-narrow			
ii.a			two			
b			narrow, broad			
c			34.9 Å, 26.7 Å			
iii.			2 Discrete lamellar structures			
6.						
i.			Present			
ii.a			one			
b			narrow			
c			31 Å			
iii.			on ageing time two lamellar structures have merged			
7.						
i.						
ii. Lamellar Features						
8.	Pourable		Viscous but Pourable		Pourable	
9.	No sedimentation over 12 months at ambient also 3 months at 0° and 37°C		No sedimentation over 12 months at ambient temp.		No sedimentation over 12 months at ambient temp.	

EP 0 170 091 B1

Examples	7	8	9(a)
1.			
i.	1	1	1
ii.	Opaque	Opaque	Opaque
	solid/paste	solid/paste	solid/paste
	thin	thin	thin
	liquid	liquid	liquid
iii.			
iv.			
v.			
vi.			
2.	III	III	III
3.	3.04	2.84	4.00
4.			
5.			
i.			
ii.a			
b			
c			
iii.			
6.			
i.			
ii.a			
b			
c			
iii.			
7.			
i.			
ii.			
8.	Pourable	Pourable	Pourable
9.	No sedimentation over 12 months at ambient temp.	No sedimentation over 12 months at ambient temp.	No sedimentation over 12 months at ambient temp.

EP 0 170 091 B1

Examples	9(b)		10(a)		10(b)	
1.						
i.	1	2	1	2	1	2
ii.	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid
iii.						
iv.						
v.						
vi.						
2.	III		III		III	
3.	8.75		3.85		8.00	
4.						
5.						
i.						
ii.a						
b						
c						
iii.						
6.						
i.						
ii.a						
b						
c						
iii.						
7.						
i.						
ii.						
8.	Viscous but pourable		Pourable		Viscous but pourable	
9.	No sedimentation over 12 months at ambient temp.		No sedimentation over 12 months at ambient temp.		No sedimentation over 12 months at ambient temp.	

EP 0 170 091 B1

Examples	11		12		13	
1.	1		1		1	
	2		2		2	
ii.	Opaque	clear	Opaque	clear	Opaque	clear
	solid/paste	thin	solid/paste	thin	solid/paste	thin
		liquid		liquid		liquid
iii.						
iv.						
v.						
vi.						
2.	III		III		III	
3.	2.48		0.93			
4.					48	
5.						
i.						
ii.a						
b						
c						
iii.						
6.						
i.						
ii.a						
b						
c						
iii.						
7.						
i.						
ii.						
8.	Pourable		Readily pourable		Viscous but Pourable	
9.	No sedimentation over 12 months at ambient temp.		No sedimentation over 12 months at ambient temp.		No sedimentation over 12 months at ambient temp.	

EP 0 170 091 B1

Examples	14		15		16		
1.							
i.	1	2	1	2	1	2	3
ii.	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid	solid
iii.	92.4% (w/w)	7.6%			72 (vol/vol)	12	16
iv.		1.7%				0.3	
v.		80.7%				76.3	
vi.		0.01					
2.	III		III		III		
3.	1.95		3.00		2.97		
4.							
5.							
i.							
ii.a							
b							
c							
iii.							
6.							
i.							
ii.a							
b							
c							
iii.							
7.							
i.							
ii.							
8.	Pourable		Viscous but pourable		Pourable		
9.	No sedimentation over 12 months at ambient temp.		No sedimentation over 6 months at ambient temp.		No sedimentation over 6 months at ambient temp.		

EP 0 170 091 B1

Examples	17	18	19
1.			
i.	1	1	1
ii.	Opaque solid/paste	clear solid/paste	clear solid/paste
	thin liquid	viscous liquid	thin liquid
iii.	65.5	90 (vol/vol)	10
iv.	7.9		< 0.1%
v.	72.1		74.7%
vi.			0.01%
2.	III	III	III
3.	5.15	6.46	2.20
4.	-	4	36
5.			
i.		Present & includes peak	
ii.a		one	
b		very narrow	
c		57.6 Å	
iii.		Micellar + "G" Phase	
6.			
i.		very broad	
ii.a		two	
b		narrow at 50Å, broad at 26Å	
c		50 Å	
iii.		Micellar + "G" Phase	
7.			
i.			
ii.			
8.	Viscous but pourable	Viscous but pourable	Pourable
9.	No sedimentation over 10 months at ambient temp.	No sedimentation over 6 months at ambient temp.	No sedimentation over 6 months at ambient temp.

EP 0 170 091 B1

Examples	20		21	
1.				
i.	1	2	1	2
ii.	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid
iii.	78	22	75	25
iv.		0.1		0.4
v.		79.6		79.1
vi.		0.01		0.01
2.	III		III	
3.	4.28		2.48	
4.				
5.				
i.	Present			
ii.a	one			
b	sharp			
c	33.4 Å			
iii.	Lamellar hydrated solid			
6.				
i.	Present			
ii.a	one			
b	sharp			
c	32 Å			
iii.	Lamellar Hydrated solid			
7.				
i.				
ii.				
8.	Viscous but pourable		Pourable	
9.	No sedimentation over 12 months at ambient temp. also 3 months at 0 and 37°C		No sedimentation over 12 months at ambient temp. also 3 months at 0 and 37°C	

EP 0 170 091 B1

Examples	22	23 (a)	23 (b)
1.			
i.	1	1	1
ii.	Opaque solid/paste	Opaque solid/paste	Opaque solid/paste
	clear thin liquid	clear thin liquid	clear thin liquid
iii.	70		
iv.	0.1	0.1	0.1
v.	70.4	84	82.9
vi.	0.01	0.01	0.01
2.	III	III	III
3.	3.21	0.88	1.87
4.			
5.			
i.			
ii.a			
b			
c			
iii.			
6.			
i.			
ii.a			
b			
c			
iii.			
7.			
i.			
ii.			
8.	Pourable	Readily Pourable	Pourable
9.	No sedimentation over 12 months at ambient temp. also 3 months at 0 and 37°C	No sedimentation over 3 months at ambient temp.	No sedimentation over 12 months at ambient temp.

EP 0 170 091 B1

Examples	23(c)		24		25	
1.						
i.	1	2	1	2	1	2
ii.	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid
iii.			60 (vol/vol)	40		
iv.		0.1		0.1		
v.		80		84.6		
vi.		0.01		0.01		
2.	III		III		III	
3.	2.38		2.20		1.99	
4.						
5.						
i.			Present - narrow			
ii.a			one			
b			sharp			
c			34.5 Å			
iii.			lamellar hydrated solid			
6.						
i.			Present			
ii.a			one			
b			Sharp			
c			33 Å			
iii.			Lamellar hydrated solid			
7.						
i.						
ii.						
8.	Pourable		Pourable		Readily pourable	
9.	No sedimentation over 12 months at ambient temp.		No sedimentation over 9 months at ambient temp.		No sedimentation over 6 months at ambient temp.	

EP 0 170 091 B1

Examples	26	27	28
1.			
i.	1	2	3
ii.	Opaque solid/paste thin liquid	Opaque solid/paste thin liquid	Opaque solid/paste thin liquid
iii.		20(vol/vol) 35	45
iv.			74
v.			26
vi.			0.8
			58.5
2.	III	III	III
3.	1.31	6.91	8.46
4.			
5.			
i.			
ii.a			
b			
c			
iii.			
6.			
i.			
ii.a			
b			
c			
iii.			
7.			
i.			
ii.			
8.	Readily Pourable	Viscous but pourable	Viscous but pourable
9.	No sedimentation over 2 months at ambient temp.	No sedimentation over 9 months at ambient temp.	No sedimentation over 3 months at ambient temp.

EP 0 170 091 B1

Examples	29			30		31	
1.							
i.	1	2	3	1	2	1	2
ii.	Opaque solid/paste	clear thin liquid	solid	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid
iii.	50(vol/vol)	20	30			87	13
iv.							0.1
v.							75
vi.							0.01
2.		III			III		III
3.		3.11			0.33		6.50
4.							
5.							
i.							
ii.a							
b							
c							
iii.							
6.							
i.							
ii.a							
b							
c							
iii.							
7.							
i.							
ii.							
8.	Pourable			Readily Pourable		Viscous but pourable	
9.	No sedimentation over 1 months at ambient temp.			No sedimentation over 2 months at ambient temp.		No sedimentation over 12 months at ambient temp.	

EP 0 170 091 B1

Examples	32	33	34
1.			
i.	1	1	1
ii.	Opaque solid/paste	cloudy thin liquid	clear thin liquid
iii.	80	72	
iv.	0.1	27	
v.		45	
vi.	0.01	0.3	
2.	III	III	III
3.	2.63	7.0	1.10
4.			3
5.			
i.			
ii.a			
b			
c			
iii.			
6.			
i.			
ii.a			
b			
c			
iii.			
7.			
i.			
ii.			
8.	Pourable	Viscous but pourable	Readily pourable
9.	No sedimentation over 12 months at ambient temp.	No sedimentation over 9 months at ambient temp.	No sedimentation over 4 months at ambient temp.

EP 0 170 091 B1

Examples	35	36	37
1.			
i.	1	1	1
ii.	Opaque solid/paste	cloudy solid/paste	cloudy solid/paste
	viscous liquid	viscous liquid	viscous thin liquid
iii.	75(vol/vol)	85(vol/vol)	
iv.	25	15	
v.	16.7	15.0	
vi.	65.5	59.3	
	1	0.5	
2.	III	III	II
3.	3.70	6.36	3.74
4.	0.5 to 2	0.5 to 2	0.5 to 2
5.	very broad with super-		
i.	imposed peak		
ii.a	one		
b	narrow		
c	61 Å		
iii.	micellar phase + "G" Phase		
6.			
i.	Present		
ii.a	two		
b	sharp, sharp		
c	57, 38 Å		
iii.	micellar phase + "G" Phase		
7.			
i.			
ii.	Lamellar features some concentric structures		
8.	Viscous but pourable	Viscous but pourable	Pourable
9.	No sedimentation over 6 months at ambient temp.	No sedimentation over 9 months at ambient temp.	No sedimentation over 9 months at ambient temp.

EP 0 170 091 B1

Examples	38	39	40
1.			
i.	1 2	1 2	1 2 3
ii.	Opaque clear solid/paste viscous liquid	Opaque clear solid/paste viscous liquid	Opaque Opaque solid/paste gelled liquid solid
iii.	66 34	77 23	
iv.	12	10	4.4
v.	68	61	58.1
vi.	0.15	0.15	0.07
2.	III	III	III
3.	3.10	2.87	3.21
4.	0.5	0.5	0.5
5.			
i.	Present very broad		
ii.a	one		
b	broad		
c	31 Å		
iii.	Micellar + "G" Phase		
6.			
i.	Present very broad		
ii.a	one		
b	sharp		
c	28.5 Å		
iii.	Micellar + "G" Phase		
7.			
i.			
ii.			Lamellar and spheroidal features
8.	Pourable	Pourable	Pourable
9.	No sedimentation over 12 months at ambient temp.	No sedimentation over 9 months at ambient temp.	No sedimentation over 6 months at ambient temp.

EP 0 170 091 B1

Examples	41			42(a)		42 (b)	
1.							
i.	1	2	3	1	2	1	2
ii.	Opaque solid/paste	thin liquid	Opaque gelled solid	Opaque solid/paste	viscous clear liquid	Opaque solid/paste	clear thin liquid
iii.				58.0	42.0		
iv.							
v.							
vi.							
2.	III			III		III	
3.	4.10			0.73		0.97	
4.	4						
5.							
i.							
ii.a							
b							
c							
iii.							
6.							
i.							
ii.a							
b							
c							
iii.							
7.							
i.							
ii.							
8.	Viscous but pourable			Viscous but pourable		Viscous but pourable	
9.	No sedimentation over 4 months at ambient temp.			No sedimentation over 12 months at ambient temp.		No sedimentation over 12 months at ambient temp.	

EP 0 170 091 B1

Examples	42(c)	43	44
1.			
i.	1 2	1 2 3	1 2 3
ii.	Opaque clear solid/paste viscous liquid	Opaque clear Clear solid/paste thin viscous liquid liquid	Opaque clear clear solid/paste thin viscous liquid liquid
iii.			30(v/v) 60 10
iv.			
v.			
vi.			
2.	III	II	II
3.	1.72	1.19	2.74
4.			
5.			
i.			
ii.a			
b			
c			
iii.			
6.			
i.			
ii.a			
b			
c			
iii.			
7.			
i.			
ii.			
8.	Viscous but pourable	Viscous but pourable	Viscous but pourable
9.	No sedimentation over 12 months at ambient temp.	No sedimentation over 9 months at ambient temp.	No sedimentation over 9 months at ambient temp.

EP 0 170 091 B1

Examples	45			46		47 (a)	
1.							
i.	1	2	3	1	2	1	2
ii.	Opaque solid/ paste	clear thin liquid	clear viscous liquid	Opaque solid/paste	clear viscous liquid	Opaque solid/paste	clear thin liquid
iii.	40(v/v)	50	10			78.0	22
iv.							0.1
v.							80
vi.							0.01
2.	II			III		III	
3.	2.48			11.0		1.58	
4.							
5.							
i.							
ii.a							
b							
c							
iii.							
6.							
i.							
ii.a							
b							
c							
iii.							
7.							
i.							
ii.							
8.	Viscous but pourable			Viscous but pourable		Readily pourable	
9.	No sedimentation over 9 months at ambient temp.			No sedimentation over 4 months at ambient temp.		No sedimentation over 6 months at ambient temp.	

EP 0 170 091 B1

Examples	47 (b)		47 (c)		48		
1.							
i.	1	2	1	2	1	2	3
ii.	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid	waxy solid
iii.	80	20	82	18.0	31.9(v/v)	23.4	44.7
iv.		< 0.1		< 0.1		< 0.1	29.6
v.		79		76.6		67.1	50.2
vi.		< 0.01		< 0.01		< 0.01	
2.	III		III		III		
3.	2.31		3.65		5.95		
4.							
5.							
i.							
ii.a							
b							
c							
iii.							
6.							
i.							
ii.a							
b							
c							
iii.							
7.							
i.							
ii.							
8.	Pourable		Pourable		Viscous but pourable		
9.	No sedimentation over 12 months at ambient temp.		No sedimentation over 12 months at ambient temp.		No sedimentation over 12 months at ambient temp.		

EP 0 170 091 B1

Examples	49(a)		49(b)		49(c)	
1.						
i.	1	2	1	2	1	2
ii.	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid	Opaque solid/paste	clear thin liquid
iii.	76	24	77.5	22.5	80	20
iv.		0.1		0.1		0.1
v.		81		79.7		78%
vi.		0.01		0.01		0.01
2.	III		III		III	
3.	0.58		1.60		3.89	
4.						
5.						
i.			Very small			
ii.a			one			
b			very narrow			
c			65 Å			
iii.			Micellar + "G" Phase ("G" Predominates)			
6.						
i.			Very small			
ii.a			two			
b			Narrow at 54Å, & 28Å			
c			54 Å			
iii.			"G" Phase + some micellar			
7.						
i.						
ii.						
8.	Readily pourable		Pourable		Viscous but pourable	
9.	No sedimentation over 12 months at ambient temp.		No sedimentation over 12 months at ambient temp.		No sedimentation over 12 months at ambient temp.	

EP 0 170 091 B1

Examples	50	51	52
1.			
i.	1 2 3	1 2 3	1 2 3
ii.	Opaque clear clear solid thin oily paste liquid layer	Opaque clear cloudy solid thin viscous paste liquid liquid("G")	Opaque clear waxy solid thin solid paste liquid
iii.	59(v/v) 39 2	45(v/v) 19 36	36(v/v) 30 34
iv.		0.2 49	0.1 31.5
v.		72 48	82
vi.		0.01 1.0	0.01
2.	II	II	III
3.	11.40	4.42	1.42
4.		0.5	0.5
5.			
i.		narrow/strong	narrow/weak
ii.a		one	one
b		broad	narrow
c		54.2 Å	56.1 Å
iii.		Micellar + "G" Phase	"G" Phase see
6.			
i.		narrow	
ii.a		two	
b		narrow at 51Å & 26Å	
c		51 Å	
iii.		micellar "G" Phase	
7.			
i.			
ii.			Lamellar features
8.	Viscous but pourable	Viscous but pourable	Viscous but pourable
9.	No sedimentation over 12 months at ambient temp.	No sedimentation over 6 months at ambient temp.	No sedimentation over 4 months at ambient temp.

EP 0 170 091 B1

Examples	53			54			55	
1.								
i.	1	2	3	1	2	3	1	2
ii.	Opaque solid/ paste	clear thin liquid	waxy solid	Opaque solid/ paste	clear thin liquid	waxy solid	Opaque solid/ paste	clear thin liquid
iii.	43(v/v)	19	38	40(v/v)	27	33	76	24
iv.		< 0.1	32.9		< 0.2			0.05
v.		71.6	51.5		82.2			
vi.		< 0.01						
2.	III			III			III	
3.	1.80			1.86			2.43	
4.	< 0.5							
5.								
i.								
ii.a								
b								
c								
iii.								
6.								
i.								
ii.a								
b								
c								
iii.								
7.								
i.								
ii.								
8.	Pourable			Pourable			Pourable	
9.	No sedimentation over 4 months at ambient temp.			No sedimentation over 3 months at ambient temp.			No sedimentation over 1 month at laboratory ambient temp.	

EP 0 170 091 B1

Examples	56	57	58
1.			
i.	1	1	1
	2	2	2
ii.	Opaque	Opaque	Opaque
	clear	clear	clear
	solid/paste	solid/paste	solid/paste
	thin	thin	thin
	liquid	liquid	liquid
iii.	82.5	64.9	77.0
	17.5	35.1	23.0
iv.	0.02	0.3	0.4
v.			
vi.			
2.	III	III	III
3.	1.8	2.1	2.9
4.			
5.			
i.			
ii.a			
b			
c			
iii.			
6.			
i.			
ii.a			
b			
c			
iii.			
7.			
i.			
ii.			
8.	Pourable	Pourable	Pourable
9.	No sedimentation over 1 month at laboratory ambient temp.	No sedimentation over 1 month at laboratory ambient temp.	No sedimentation over 1 month at laboratory ambient temp.

EP 0 170 091 B1

Examples	59	60	61
1.			
i.	1	1	1
ii.	2	2	2
	Opaque	Opaque	Opaque
	clear	clear	clear
	solid/	solid/	solid/
	thin	thin	viscous
	paste	paste	liquid
iii.	73.0	5(v/v)	95.0
iv.	27.0	45	5.0
v.	0.1	0.05	26.2
vi.			
2.	III	III	III
3.	2.2	8.1	6.0
4.			
5.			
i.			
ii.a			
b			
c			
iii.			
6.			
i.			
ii.a			
b			
c			
iii.			
7.			
i.			
ii.			
8.	Pourable	Viscous but pourable	Viscous but pourable
9.	No sedimentation over 1 month at laboratory ambient temp.	No sedimentation over 1 month at laboratory ambient temp.	No sedimentation over 1 month at laboratory ambient temp.

EP 0 170 091 B1

Examples	62		63		64		
1.							
i.	1	2	1	2	1	2	3
ii.	Opaque solid/ paste	Cloudy viscous liquid	Opaque solid/ paste	Cloudy viscous liquid	Opaque solid/ paste	clear thin liquid	Solid/ paste
iii.	42.8	57.2	51.0	49.0	10(v/v)	40	50
iv.		21.3		22.5		0.01	
v.							
vi.							
2.	III		III		III		
3.	3.26		5.60		0.75		
4.							
5.							
i.							
ii.a							
b							
c							
iii.							
6.							
i.							
ii.a							
b							
c							
iii.							
7.							
i.							
ii.							
8.	Pourable		Pourable		Readily pourable		
9.	No sedimentation over 1 month at laboratory ambient temp.		No sedimentation over 1 month at laboratory ambient temp.		No sedimentation over 1 month at laboratory ambient temp.		

EP 0 170 091 B1

Example 65		
1.		
i	1	2
ii	Opaque solid paste	Clear thin liquid
iii	64.0	36.0
iv		0.2
v		
vi		
2.	III	
3.	0.56	
4.		
5.		
i		
ii	a	
	b	
	c	
iii		
6.		
i		
ii		
	a	
	b	
	c	
iii		
7.		
i		
ii		
8.	Readily Pourable	
9.	No sedimentation over 1 month at laboratory ambient temperatures	

EP 0 170 091 B1

Comparative Example A

1.		
i.	1	2
ii.	Opaque solid paste	Opaque viscous liquid
iii.	24	76
iv.		17.3
v.		77.0
vi.		0.26
2.		I
3.		0.3
4.		4
5.		very broad with superimposed peaks
i.		
ii. a	None	
b		-
c		-
iii.	con. micellar dispersion	
6.		
i.	very wide	
ii. a	one	
b	small	
c	20A	
iii.	conc. micellar dispersion	
7.		
i.		
ii.	Spheroidal features	
8.	Readily Pourable	
9.	No sedimentation over 12 months at ambient temperature	

Certain of the foregoing examples were tested for washing performance as follows:—

Series 1

Representative high foaming formulations were each compared with a standard powder formulation in machine washing tests on two different standard soiled fabric samples.

Example	Cotton	Polyester/Cotton	Conditions
31	95%	100%	Temp. 50°C
55	90%	70%	Water 300 ppm calcium carbonate
16	100%	100%	Time 30 min
33	95%	110%	Conc. = Equivalent effective Wash Solids
Powder Standard	100%	100%	

The term "Effective Wash Solids" refers to the sum of the Active Ingredient and Builder. The powder standard was used at 6 g/l and the Examples adjusted to give the same % Effective Wash Solids in the wash Liquor.

EP 0 170 091 B1

Series 2

Representative formulations of both high and low foaming types were tested against equal wt. dosage at three temperatures.

	Example	% Effective Wash Solids	40°	Cotton		Polyester/Cotton		
				60°	85°+	40°	60°	85°+
5	43 (c)	93	75	100	95	75	85	50
10	36	66	85	85	100	80	95	75
	50 (c)	93	110	110	95	180	200	200
15	Powder Standard	100	100	100	100	100	100	100

Conditions: Temp 40°, 60° and 85°C+
 Water 300 ppm hardness
 Time 30 mins.
 Conc. 6 gm/l (as received)

Series 3

In this series low foaming non-ionic based examples were tested against the powder standard.

	Example	% Effective Wash Solids	Cotton	Polyester/Cotton	Conditions	
					Temp.	50°C
25	52	70	110%	100%		
30	53	66	105%	90%	Water	300 ppm hardness
	54	61	115%	120%	Time	30 min
35					Conc.	6 g/l
					powder	11 g/l
40	Powder Standard	100	100%	100%		

Series 4

Two low foam non-ionic formulations were tested on naturally soiled fabric (15 successive washes with natural soiling).

Conditions: Temperature 50°C
 Water 300 ppm hardness (wash and rinse)
 Wash time 30 min
 Fabric 65:35 white polyester:cotton
 Concentration EQUAL WEIGHT i.e. 6 g/l

Results:
 Example

52 = 100% Std) Optical whitener efficiency

54 = 75% Std)

52 = 95—100%) Soil Removal and Deposition efficiency

54 = 95—100%)

The two examples were also compared against the three liquid laundry products which have performed best in our tests out of all those available commercially in Europe at the date of testing.

Both examples gave superior washing performance to all three commercial products.

Claims

1. A fluid, aqueous based detergent composition comprising: a surfactant; a Builder, at least a proportion of said Builder being present as solid particles suspended in the composition; and a dissolved surfactant-desolubilising Electrolyte, said Electrolyte not comprising sodium sulphate in quantities in excess of its solubility in the composition at normal temperatures, but including any dissolved portion of the surfactant desolubilising Builder; and which is separable by Centrifuging at 800 times normal earth gravity for 17 hours at 25°C into at least two layers at least one of which layers is an aqueous layer; characterised in that: said aqueous layer contains sufficient of said Electrolyte dissolved therein to contribute from 2 to 4.5 gram ions of alkali metal ion per litre to said aqueous layer; and the Payload of said composition is above the minimum at which the composition is Non-sedimenting and below the maximum at which it is Pourable.
2. A composition according to claim 1 which is separable by Centrifuging into a single liquid layer and a Solid Layer containing at least part of the solid Builder and of the surfactant.
3. A composition according to either of claims 1 and 2 containing at least 5% by weight of surfactant based on the total weight of the composition.
4. A composition according to any foregoing claim having a Payload greater than 25%.
5. A composition according to any foregoing claim wherein the Electrolyte contributes from 2 to 4.5 gram ions per litre of sodium and/or potassium ion to said aqueous layer.
6. A composition according to any foregoing claim wherein said Electrolyte contributes from 2 to 4.5 gram ions per litre of sodium ion to said aqueous layer.
7. A composition according to any foregoing claim wherein the ratio of the total Builder to the total surfactant is greater than 1.2:1.
8. A composition according to any foregoing claim having a Payload of at least 35% by weight.
9. A composition according to any foregoing claim having a Yield Point of at least 1 Newton per m².
10. A composition according to any foregoing claim having a weight ratio of Builder to surfactant of from 1.2:1 to 4:1.
11. A composition according to any foregoing claim wherein the Builder comprises sodium tripolyphosphate.
12. A composition according to any foregoing claim containing at least 15% by weight thereof of Builder.
13. A composition according to claim 12 containing at least 20% by weight thereof of Builder.
14. A composition according to any foregoing claim containing more than 8% by weight thereof of surfactant.
15. A composition according to any foregoing claim having a pH greater than 8 when dissolved in a wash liquor at a concentration of 0.5% Dry Weight.
16. A composition according to claim 15 having a pH greater than 10 when dissolved in a wash liquor at a concentration of 0.5% Dry Weight.
17. A composition according to any foregoing claim having sufficient free alkalinity to require 0.4 to 12 mls one-tenth Normal hydrochloric acid to reduce the pH of 100 ml of diluted composition at 0.5% Dry Weight to 9.
18. A composition according to claim 17 having sufficient free alkalinity to require from 3 to 10 mls. one-tenth normal hydrochloric acid to reduce the pH of 100 ml of diluted composition at 0.5% Dry Weight to 9.
19. A composition according to any foregoing claim wherein the surfactants comprise at least a major proportion of a sulphated and/or sulphonated anionic surfactant.
20. A composition according to any foregoing claim wherein said solid Builder comprises a condensed phosphate, phosphonate, carbonate, zeolite and/or orthophosphate.
21. A composition according to any foregoing claim, wherein said dissolved electrolyte consists essentially of carbonate, and an alkali metal condensed phosphate, orthophosphate, citrate, nitrilotriacetate, chloride and/or ethylenediamine tetracetate.
22. A composition according to any of foregoing claim wherein the total Builder comprises a major proportion by weight thereof, of sodium tripolyphosphate.
23. A composition according to any foregoing claim wherein the surfactants constitute from 10 to 20% of the weight of said composition.
24. A composition according to any foregoing claim wherein said surfactant comprises a mixture of a substantially linear C₁₀₋₁₄ alkyl benzene sulphonate and a C₁₀₋₂₀ alkyl 1 to 10 mole ethyleneoxy sulphate.
25. A composition according to any foregoing claim containing an effective amount of an antiredeposition agent.
26. A composition according to claim 25 wherein the antiredeposition agent is a carboxymethylcellulose.
27. A composition according to claim 26 containing from 0.5 to 2% by weight of said composition of alkali metal or ammonium carboxymethyl cellulose.
28. A composition according to any foregoing claim containing an effective amount of an optical brightening agent.

EP 0 170 091 B1

29. A Pourable, Non-Sedimenting, fluid, liquid detergent composition according to any foregoing claim consisting essentially of water and: (A) from 10 to 20% based on the weight of the composition of a mixture of substantially linear C₁₀₋₁₈ alkyl benzene sulphonate and C₁₀₋₂₀ alkyl 1—10 mole ethoxy sulphate; (B) at least 15% by weight of the composition of total Builder partly present as suspended solid, selected from sodium tripolyphosphate, zeolite, sodium carbonate, sodium silicate and mixtures thereof; (C) an aqueous Separable Phase containing sufficient dissolved Electrolyte selected from sodium tripolyphosphate, sodium carbonate, sodium silicate and mixtures thereof to provide from 2 to 4.5 gm mole per litre of sodium ion in said phase; and (D) optionally any of the Usual Minor Ingredients; the Payload of said composition being above the minimum at which the composition is Non-sedimenting but below the maximum at which it is Pourable.
30. A composition according to any of claims 24 and 29 wherein the weight ratio of said alkyl benzene sulphonate to said alkyl ether sulphate is between 5:1 and 1:5.
31. A composition according to any foregoing claim which, on recovery after exposure to high shear stress, exhibits increased viscosity.
32. A composition according to any foregoing claim, wherein the Electrolyte and Builder consist essentially of sodium tripolyphosphate and sodium carbonate.
33. A composition according to any foregoing claim wherein the proportion of sodium tripolyphosphate is from 14 to 32.7% of the weight of the composition.
34. A composition according to claim 33, wherein the proportion of sodium tripolyphosphate is greater than 15.8% by weight.
35. A composition according to any foregoing claim containing from 2.1 to 18% by weight of substantially linear sodium alkyl benzene sulphonate.
36. A composition according to claim 35 containing at least 9.0% by weight of sodium alkyl benzene sulphonate.
37. A composition according to claim 36 containing at least 9.9% by weight of sodium alkyl benzene sulphonate.
38. A composition according to claim 37 containing at least 11.2% by weight of sodium alkyl benzene sulphonate.
39. A composition according to claim 38 containing at least 12% by weight of alkyl benzene sulphonate.
40. A composition according to claim 39 containing at least 12.6% by weight alkyl benzene sulphate.
41. A composition according to any foregoing claim containing up to 9.6% by weight of sodium alkyl ether sulphate.
42. A composition according to any of claims 1 to 27 wherein said Electrolyte consists essentially of sodium carbonate and/or sodium silicate, and/or sodium tripolyphosphate.
43. A composition according to any foregoing claim wherein the Active Ingredients comprise a minor proportion of a non-ionic surfactant.
44. A composition according to any foregoing claim wherein the Electrolyte comprises a nitrate.
45. A composition according to any foregoing claim containing at least 5.6% by weight of sodium carbonate.
46. A method of washing clothes or other soiled fabric which comprises agitating them in an aqueous wash liquor containing a composition according to any foregoing claim.
47. A liquid detergent composition according to any foregoing claim of the type which comprises: an aqueous phase containing a mixture of dissolved Electrolytes comprising dissolved sodium tripolyphosphate, together with sodium carbonate and/or sodium silicate and at least 5% based on the weight of the composition of anionic surfactants selected from sodium linear alkyl benzene sulphonates, sodium alkyl ethoxy sulphates and mixtures thereof; solid sodium tripolyphosphate, suspended in said aqueous phase; and any of the Usual Minor Ingredients.
48. An improved composition according to claim 47 wherein the proportion of sodium carbonate is at least 5.6% by weight of the composition.
49. An aqueous, fluid detergent medium, capable of suspending solid particulate Builders to form Pourable, Non-Sedimenting suspensions, and comprising water, surfactant and dissolved surfactant-desolubilising Electrolyte, wherein said dissolved Electrolyte does not comprise sodium sulphate in excess of its solubility in the composition at normal temperatures, but is sufficient to provide from 2 to 4.5 gram ions of alkali metal per litre in said medium and said surfactant is sufficient to form, in the presence of said Electrolyte, a vesicular and/or lamellar surfactant structure capable of supporting said Builder.
50. An aqueous, fluid detergent medium according to claim 49 containing from 7 to 35% by weight of said medium of surfactant.
51. A composition according to either of claims 49 and 50, wherein said dissolved Electrolyte consists substantially of Builder.
52. A composition according to any of claims 49 to 51, wherein said Electrolyte consists substantially of sodium carbonate, sodium silicate, sodium citrate, sodium nitrilotriacetate, sodium phosphate, sodium pyrophosphate, a sodium polyphosphate, a sodium phosphonate or a mixture of any of the aforesaid Electrolytes.
53. A composition according to any of claims 49 to 52, wherein said surfactant consists substantially of

EP 0 170 091 B1

sodium linear alkyl benzene sulphonate or a mixture thereof with sodium alkyl ether sulphate, sodium alkyl sulphate, sodium paraffin sulphonate, sodium olefin sulphonate, non-ionic surfactants and/or Soap.

54. A composition according to any foregoing claim having a Viscosity less than 10 Pascal seconds.

55. A composition according to claim 54 having a Viscosity less than 5 Pascal seconds.

56. A composition according to any foregoing claim having a Viscosity greater than 0.1 Pascal seconds.

57. A composition according to claim 56 having a Viscosity greater than 0.5 Pascal seconds.

Patentansprüche

1. Flüssige Detergenzzusammensetzung auf wässriger Basis, enthaltend: eine oberflächenaktive Substanz; einen Builder, von dem zumindest ein Teil in der Zusammensetzung in Form fester Teilchen suspendiert ist; und einen gelösten, die oberflächenaktive Substanz desolubilisierenden Elektrolyt, der kein Natriumsulfat in Mengen über seiner Löslichkeit in der Zusammensetzung bei Normaltemperaturen enthält, jedoch jeden gelösten Teil des die oberflächenaktive Substanz desolubilisierenden Builders umfasst; und welche Zusammensetzung durch Zentrifugieren bei 800facher normaler Erdanziehung während 17 Stunden bei 25°C in mindestens zwei Schichten trennbar ist, von denen mindestens eine eine wässrige Schicht ist; dadurch gekennzeichnet, daß: diese wässrige Schicht genügend von dem darin gelösten Elektrolyt enthält, um 2 bis 4,5 Grammionen Alkalimetallion pro Liter in der wässrigen Schicht vorzusehen; und die Payload dieser Zusammensetzung oberhalb der minimalen Payload, bei der die Zusammensetzung nicht absetzend ist, und unterhalb der maximalen Payload ist, bei welcher die Zusammensetzung gießbar ist.
2. Zusammensetzung nach Anspruch 1, die durch Zentrifugieren in eine einzige flüssige Schicht und eine feste Schicht, die zumindest einen Teil des festen Builders und der oberflächenaktiven Substanz enthält, trennbar ist.
3. Zusammensetzung nach Anspruch 1 oder 2, die zumindest 5 Gew. -% der oberflächenaktiven Substanz bezogen auf das Gesamtgewicht der Zusammensetzung enthält.
4. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche mit einer Payload von mehr als 25%.
5. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher der Elektrolyt 2 bis 4,5 Grammionen pro Liter Natrium- und/oder Kaliumion in dieser wässrigen Schicht zur Verfügung stellt.
6. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher dieser Elektrolyt 2 bis 4,5 Grammionen pro Liter Natriumion in dieser wässrigen Schicht zur Verfügung stellt.
7. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher das Verhältnis von Gesamtbuilder zu gesamter oberflächenaktiver Substanz mehr als 1,2:1 beträgt.
8. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die eine payload von mindestens 35 Gew. -% hat.
9. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die eine Fließgrenze von mindestens 1 N/m² hat.
10. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die ein Gewichtsverhältnis von Builder zu oberflächenaktiver Substanz von 1,2:1 bis 4:1 hat.
11. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, in welcher der Builder Natriumtripolyphosphat enthält.
12. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die zumindest 15 Gew. -% Builder enthält.
13. Zusammensetzung nach Anspruch 12, die zumindest 20 Gew. -% Builder enthält.
14. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die mehr als 8 Gew. -% oberflächenaktiver Substanz enthält.
15. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die einen pH-Wert von über 8 hat, wenn sie mit einer Konzentration von 0,5% Trockengewicht in einer Waschlösung gelöst ist.
16. Zusammensetzung nach Anspruch 15, die einen pH-Wert von mehr als 10 hat, wenn sie mit einer Konzentration von 0,5% Trockengewicht in einer Waschflüssigkeit gelöst ist.
17. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die ausreichende freie Alkalinität hat, um 0,4 bis 12 ml einer 1/10 N Chlorwasserstoffsäure zur Herabsetzung des pH-Wertes von 100 ml verdünnter Zusammensetzung mit 0,5% Trockengewicht auf 9 zu erfordern.
18. Zusammensetzung nach Anspruch 17, die ausreichende freie Alkalinität hat, um 3 bis 10 ml einer 1/10 N Chlorwasserstoffsäure zur Herabsetzung des pH-Wertes von 100 ml verdünnter Zusammensetzung mit 0,5% Trockengewicht auf 9 zu erfordern.
19. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher die oberflächenaktiven Substanzen zumindest einen Hauptanteil eines sulfatierten und/oder sulfonierten anionischen oberflächenaktiven Mittels enthalten.
20. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher der feste Builder ein kondensiertes Phosphat, Phosphonat, Karbonat, einen Zeolith und/oder ein Orthophosphat enthält.
21. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher der gelöste

Elektrolyt im wesentlichen aus Karbonat und einem Alkalimetallsalz von kondensiertem Phosphat, Orthophosphat, Citrat, Nitrilotriacetat, Chlorid und/oder Ethylendiamintetraacetat besteht.

22. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher der gesamte Builder einen Hauptanteil bezogen auf sein Gewicht an Natriumtripolyphosphat enthält.

5 23. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher die oberflächenaktiven Substanzen 10 bis 20 Gew. -% der Zusammensetzung ausmachen.

24. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher die oberflächenaktive Substanz eine Mischung von im wesentlichen linearem C₁₀₋₁₄ Alkylbenzolsulfonat und einem C₁₀₋₂₀ Alkyl-1 bis 10 Mol-Ethylenoxy-sulfat enthält.

10 25. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die eine wirksame Menge eines Antiabsetzmittels enthält.

26. Zusammensetzung nach Anspruch 25, bei welcher das Antiabsetzmittel eine Carboxymethylzellulose ist.

27. Zusammensetzung nach Anspruch 26, die 0, 5 bis 2 Gew.-% der Zusammensetzung Alkalimetall- oder Ammoniumcarboxymethylzellulose enthält.

28. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die eine wirksame Menge eines optischen Aufhellers enthält.

29. Gießbare, nicht absetzende, fließfähige, flüssige Detergensenzusammensetzung gemäß irgendeinem der vorhergehenden Ansprüche, die im wesentlichen besteht aus Wasser und: (A) 10 bis 20% bezogen auf das Gewicht der Zusammensetzung einer Mischung von im wesentlichen linearem C₁₀₋₁₈ Alkylbenzolsulfonat und C₁₀₋₂₀-Alkyl-1 bis 10 Mol-Ethoxysulfat; (B) zumindest 15 Gew. -% der Zusammensetzung Gesamtbuilder, der zum Teil als suspendierter Feststoff, ausgewählt aus Natriumtripolyphosphat, Zeolith, Natriumkarbonat, Natriumsilikat und Mischungen derselben, vorliegt; (C) einer wässrigen Abtrennbaren Phase, die ausreichend gelösten Elektrolyt aus der Gruppe 25 Natriumtripolyphosphat, Natriumkarbonat, Natriumsilikat und Mischungen derselben enthält, um 2 bis 4,5 Gramm pro Liter Natriumion in dieser Phase vorzusehen; und (D) gegebenenfalls irgendeinen der üblichen Nebenbestandteile; wobei die Payload dieser Zusammensetzung über der minimalen Payload, bei der die Zusammensetzung nicht absetzend ist, jedoch unterhalb der maximalen Payload, bei welcher sie gießbar ist, liegt.

30. Zusammensetzung nach irgendeinem der Ansprüche 24 und 29, bei welcher das Gewichtsverhältnis des Alkylbenzolsulfonats zum Alkylethersulfat zwischen 5:1 und 1:5 liegt.

31. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die im Anschluß an die Einwirkung hoher Scherbeanspruchung eine erhöhte Viskosität zeigt.

32. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher der Elektrolyt und der Builder im wesentlichen aus Natriumtripolyphosphat und Natriumkarbonat bestehen.

33. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher der Anteil an Natriumtripolyphosphat bei 14 bis 32,7% des Gewichtes der Zusammensetzung liegt.

34. Zusammensetzung nach Anspruch 33, bei welcher der Anteil an Natriumtripolyphosphat bei über 15,8 Gew. -% liegt.

40 35. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die 2,1 bis 18 Gew. -% eines im wesentlichen linearen Natriumalkylbenzolsulfonats enthält.

36. Zusammensetzung nach Anspruch 35, die zumindest 9,0 Gew. -% Natriumalkylbenzolsulfonat enthält.

37. Zusammensetzung nach Anspruch 36, die zumindest 9,9 Gew. -% Natriumalkylbenzolsulfonat 45 enthält.

38. Zusammensetzung nach Anspruch 37, die zumindest 11,2 Gew. % Natriumalkylbenzolsulfonat enthält.

39. Zusammensetzung nach Anspruch 38, die zumindest 12 Gew. -% Alkylbenzolsulfonat enthält.

40. Zusammensetzung nach Anspruch 39, die zumindest 12,6 Gew. % Alkylbenzolsulfat enthält.

50 41. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die bis zu 9,6 Gew. -% Natriumalkylethersulfat enthält.

42. Zusammensetzung nach irgendeinem der Ansprüche 1 bis 27, bei welcher dieser Elektrolyt im wesentlichen aus Natriumkarbonat und/oder Natriumsilikat und/oder Natriumtripolyphosphat besteht.

43. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher die Aktiven Bestandteile eine untergeordnete Menge an nicht-ionischer oberflächenaktiver Substanz enthalten.

55 44. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, bei welcher der Elektrolyt ein Nitrat enthält.

45. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche, die zumindest 5,6 Gew. -% Natriumkarbonat enthält.

60 46. Verfahren zum Waschen von Stoffen oder anderer verunreinigter Ware, bei welchem diese in einer wässrigen Waschlösung bewegt wird, die eine Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche enthält.

47. Flüssige Detergensenzusammensetzung nach irgendeinem der vorhergehenden Ansprüche jener Art, die enthält: eine wässrige Phase, die eine Mischung gelöster Elektrolyte aufweist, die gelöstes 65 Natriumtripolyphosphat gemeinsam mit Natriumkarbonat und/oder Natriumsilikat und zumindest 5%

bezogen auf das Gewicht der Zusammensetzung anionischer oberflächenaktiver Substanzen, ausgewählt aus Natrium-linear-Alkylbenzolsulfonaten, Natriumalkylethoxysulfaten und Mischungen derselben, enthalten; festes Natriumtripolyphosphat, das in dieser wässrigen Phase suspendiert ist; und jedwede üblichen Nebenbestandteile.

5 48. Verbesserte Zusammensetzung nach Anspruch 47, bei welcher der Anteil an Natriumkarbonat bei mindestens 5,6 Gew. -% der Zusammensetzung liegt.

49. Wässriges flüssiges Detergensmedium, das imstande ist, feste teilchenförmige Builder zu suspendieren und gießbare nicht absetzende Suspensionen zu bilden, und Wasser, oberflächenaktive Substanz und gelösten Elektrolyt, der die oberflächenaktive Substanz desolubilisiert, enthält, wobei dieser
10 gelöste Elektrolyt kein Natriumsulfat im Überschuß über dessen Löslichkeit in der Zusammensetzung bei Normaltemperatur aufweist, jedoch ausreicht, um 2 bis 4,5 Grammionen Alkalimetall pro Liter in diesem Medium vorzusehen, und die oberflächenaktive Substanz ausreicht, um in Gegenwart dieses Elektrolyten eine bläschenförmige und/oder lamellare Struktur des oberflächenaktiven Mittels zu bilden, die imstande ist, den Builder zu tragen.

15 50. Wässriges, flüssiges Detergensmedium nach Anspruch 49, welches 7 bis 35 Gew. -% des Mediums an oberflächenaktiver Substanz enthält.

51. Zusammensetzung nach einem der Ansprüche 49 oder 50, bei welcher der gelöste Elektrolyt im wesentlichen aus Builder besteht.

52. Zusammensetzung nach irgendeinem der Ansprüche 49 bis 51, bei welcher der Elektrolyt im
20 wesentlichen aus Natriumkarbonat, Natriumsilikat, Natriumcitrat, Natriumnitritotriacetat, Natriumphosphat, Natriumpyrophosphat, einem Natriumpolyphosphat, einem Natriumphosphonat oder einer Mischung irgendwelcher der vorhergenannten Elektrolyten besteht.

53. Zusammensetzung nach irgendeinem der Ansprüche 49 bis 52, bei welcher die oberflächenaktive Substanz im wesentlichen aus Natrium-linear-Alkylbenzolsulfonat oder einer Mischung derselben mit
25 Natriumalkylethersulfat, Natriumalkylsulfat, Natriumparaffinsulfonat, Natriumolefinsulfonat, nicht-ionischen oberflächenaktiven Mitteln und/oder Seife besteht.

54. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche mit einer Viskosität von weniger als 10 Pa. sec.

55. Zusammensetzung nach Anspruch 54 mit einer Viskosität von weniger als 5 Pa. sec.

30 56. Zusammensetzung nach irgendeinem der vorhergehenden Ansprüche mit einer Viskosität größer als 0,1 pa. sec.

57. Zusammensetzung nach Anspruch 56 mit einer Viskosität von über 0,5 Pa. sec.

Revendications

35 1. Composition détergente fluide, à base aqueuse, comprenant: un tensioactif; un adjuvant, dont au moins une proportion est présente sous forme de particules solides en suspension dans la composition; et un électrolyte de désolubilisation du tensioactif, dissous, ledit électrolyte ne comprenant pas de sulfate de sodium en quantités dépassant sa solubilité dans la composition aux températures normales, mais
40 contenant une proportion dissoute quelconque de l'adjuvant de désolubilisation du tensioactif; et qui est séparable par centrifugation à 800 fois la pesanteur normale pendant 17 heures à 25°C, en au moins deux couches dont l'une au moins est une couche aqueuse; caractérisée en ce que ladite couche aqueuse contient une quantité suffisante d'électrolyte dissous pour apporter de 2 à 4,85 ions-g de métal alcalin par litre à ladite couche aqueuse; et la charge utile de ladite composition est supérieure au minimum auquel la
45 composition ne sédimente pas et inférieure au maximum auquel elle est coulable.

2. Composition selon la revendication 1, qui est séparable par centrifugation en une seule couche liquide et une couche solide contenant au moins une partie de l'adjuvant solide et du tensioactif.

3. Composition selon l'une ou l'autre des revendications 1 et 2, contenant au moins 5% en poids de tensioactif, par rapport au poids total de la composition.

50 4. Composition selon l'une quelconque des revendications précédentes, comportant une charge utile supérieure à 25%.

5. Composition selon l'une quelconque des revendications précédentes, dans laquelle l'électrolyte apporte de 2 à 4,5 ions-g par litre en ions sodium et/ou potassium à ladite couche aqueuse.

6. Composition selon l'une quelconque des revendications précédentes, dans laquelle ledit électrolyte
55 apporte de 2 à 4,5 ions-g par litre d'ions sodium à ladite couche aqueuse.

7. Composition selon l'une quelconque des revendications précédentes, dans laquelle le rapport de l'adjuvant total au tensioactif total est supérieur à 1,2:1.

8. Composition selon l'une quelconque des revendications précédentes, comportant une charge utile d'au moins 35% en poids.

60 9. Composition selon l'une quelconque des revendications précédentes, ayant une limite élastique d'au moins 1 Newton par m².

10. Composition selon l'une quelconque des revendications précédentes, ayant un rapport pondéral de l'adjuvant au tensioactif de 1,2:1 à 4:1.

65 11. Composition selon l'une quelconque des revendications précédentes, dans laquelle l'adjuvant comprend le tripolyphosphate de sodium.

EP 0 170 091 B1

12. Composition selon l'une quelconque des revendications précédentes, contenant au moins 15% de son poids d'adjuvant.
13. Composition selon la revendication 12, contenant au moins 20% de son poids d'adjuvant.
14. Composition selon l'une quelconque des revendications précédentes, contenant plus de 8% de son poids de tensioactif.
15. Composition selon l'une quelconque des revendications précédentes, ayant un pH supérieur à 8 lorsqu'elle est dissoute dans une liqueur de lavage à une concentration de 0,5% de poids sec.
16. Composition selon la revendication 15, ayant un pH supérieur à 10 lorsqu'elle est dissoute dans une liqueur de lavage à une concentration de 0,5% de poids sec.
17. Composition selon l'une quelconque des revendications précédentes, ayant une alcalinité libre suffisante pour nécessiter 0,4 à 12 ml d'acide chlorhydrique 0,1N pour réduire à 9 le pH de 100 ml de composition diluée à 0,5% de poids sec.
18. Composition selon la revendication 17, ayant une alcalinité libre suffisante pour nécessiter de 3 à 10 ml d'acide chlorhydrique 0,1N pour réduire à 9 le pH de 100 ml de composition diluée à 0,5% de poids sec.
19. Composition selon l'une quelconque des revendications précédentes, dans laquelle les tensioactifs comprennent au moins une proportion majeure d'un tensioactif anionique sulfaté et/ou sulfonaté.
20. Composition selon l'une quelconque des revendications précédentes, dans laquelle ledit adjuvant solide comprend un phosphate condensé, un phosphonate, un carbonate, une zéolite et/ou un orthophosphate.
21. Composition selon l'une quelconque des revendications précédentes, dans laquelle ledit électrolyte dissous est essentiellement constitué de carbonate et d'un phosphate condensé, orthophosphate, citrate, nitrilotriacétate, chlorure et/ou éthylène-diamine-tétraacétate de métal alcalin.
22. Composition selon l'une quelconque des revendications précédentes, dans laquelle l'adjuvant total comprend une proportion majeure de son poids de tripolyphosphate de sodium.
23. Composition selon l'une quelconque des revendications précédentes, dans laquelle les tensioactifs constituent de 10 à 20% du poids de ladite composition.
24. Composition selon l'une quelconque des revendications précédentes, dans laquelle ledit tensioactif comprend un mélange d'un alkyl(en C₁₀₋₁₄ essentiellement linéaire)benzène-sulfonate et d'un alkyl(en C₁₀₋₂₀)sulfate polyéthoxylé à 1—10 moles d'oxyde d'éthylène.
25. Composition selon l'une quelconque des revendications précédentes, contenant une quantité efficace d'un agent antiredéposition.
26. Composition selon la revendication 25, dans laquelle l'agent antiredéposition est une carboxyméthylcellulose.
27. Composition selon la revendication 26, contenant de 0,5 à 2%, du poids de ladite composition, de carboxyméthylcellulose de métal alcalin ou d'ammonium.
28. Composition selon l'une quelconque des revendications précédentes, contenant une quantité efficace d'un agent azurant optique.
29. Composition détergente liquide, fluide, coulable, qui ne sédimente pas, selon l'une quelconque des revendications précédentes, essentiellement constituée par de l'eau et: (A) de 10 à 20%, par rapport au poids de la composition, d'un mélange d'alkyl (en C_{10-C₁₈} essentiellement linéaire)benzène-sulfonate et d'alkyl(en C_{10-C₂₀})sulfate polyéthoxylé avec 1—10 moles d'oxyde d'éthylène; (B) au moins 15%, du poids de la composition, d'adjuvant total partiellement présent sous forme d'un solide en suspension, choisi parmi le tripolyphosphate de sodium, une zéolite, le carbonate de sodium, le silicate de sodium et leurs mélanges; (C) une phase aqueuse séparable contenant une quantité suffisante d'électrolyte dissous choisi parmi le tripolyphosphate de sodium, le carbonate de sodium, le silicate de sodium et leurs mélanges, pour fournir de 2 à 4,5 moles-g par litre d'ions sodium dans ladite phase; et (D) éventuellement n'importe quel ingrédient mineur habituel; la charge utile de ladite composition étant supérieure au minimum auquel la composition ne sédimente pas mais inférieure au maximum auquel elle est coulable.
30. Composition selon l'une quelconque des revendications 24 et 29, dans laquelle le rapport pondéral dudit alkylbenzène-sulfonate audit alkyléthersulfate est compris entre 5:1 et 1:5.
31. Composition selon l'une quelconque des revendications précédentes, qui présente, par récupération après exposition à une contrainte de cisaillement élevée, une viscosité accrue.
32. Composition selon l'une quelconque des revendications précédentes, dans laquelle l'électrolyte et l'adjuvant sont essentiellement constitués de tripolyphosphate de sodium et de carbonate de sodium.
33. Composition selon l'une quelconque des revendications précédentes, dans laquelle la proportion de tripolyphosphate de sodium est de 14 à 32,7% du poids de la composition.
34. Composition selon la revendication 33, dans laquelle la proportion de tripolyphosphate de sodium est supérieure à 15,8% en poids.
35. Composition selon l'une quelconque des revendications précédentes, contenant de 2,1 à 18% en poids d'alkyl(essentiellement linéaire)benzène-sulfonate de sodium.
36. Composition selon la revendication 35, contenant au moins 9,0% en poids d'alkylbenzène-sulfonate de sodium.
37. Composition selon la revendication 36, contenant au moins 9,9% en poids d'alkylbenzène-sulfonate de sodium.

EP 0 170 091 B1

38. Composition selon la revendication 37, contenant au moins 11,2% en poids d'alkylbenzène-sulfonate de sodium.

39. Composition selon la revendication 38, contenant au moins 12% en poids d'alkylbenzène-sulfonate.

5 40. Composition selon la revendication 39, contenant au moins 12,6% en poids d'alkylbenzène-sulfonate.

41. Composition selon l'une quelconque des revendications précédentes, contenant jusqu'à 9,6% en poids d'alkyléthersulfate de sodium.

42. Composition selon l'une quelconque des revendications 1 à 27, dans laquelle ledit électrolyte est
10 essentiellement constitué de carbonate de sodium et/ou de silicate de sodium, et/ou de tripolyphosphate de sodium.

43. Composition selon l'une quelconque des revendications précédentes, dans laquelle les ingrédients actifs comprennent une proportion mineure d'un tensioactif non ionique.

44. Composition selon l'une quelconque des revendications précédentes, dans laquelle l'électrolyte
15 comprend un nitrate.

45. Composition selon l'une quelconque des revendications précédentes, contenant au moins 5,6% en poids de carbonate de sodium.

46. Procédé de lavage de vêtements ou d'autres tissus salis, qui comprend leur agitation dans une
20 liqueur de lavage aqueuse contenant une composition selon l'une quelconque des revendications précédentes.

47. Composition détergente liquide selon l'une quelconque des revendications précédentes, du type qui comprend: une phase contenant un mélange d'électrolytes dissous comprenant du tripolyphosphate de sodium dissous, avec du carbonate de sodium et/ou du silicate de sodium, et au moins 5%, par rapport au poids de la composition, de tensioactifs anioniques choisis parmi les alkyl(linéaire)benzène-sulfonates
25 de sodium, les alkyléthoxysulfates de sodium et leurs mélanges; du tripolyphosphate de sodium solide en suspension dans ladite phase aqueuse; et n'importe lequel des ingrédients mineurs habituels.

48. Composition améliorée selon la revendication 47, dans laquelle la proportion de carbonate de sodium est d'au moins 5,6% du poids de la composition.

49. Milieu détergent fluide aqueux, capable de mettre en suspension des adjuvants particuliers
30 solides pour former des suspensions coulables, qui ne sédimentent pas, et comprenant de l'eau, un tensioactif et un électrolyte dissous de désolubilisation du tensioactif, dans lequel ledit électrolyte dissous ne comprend pas de sulfate de sodium en excès de sa solubilité dans la composition aux températures normales, mais est suffisant pour fournir de 2 à 4,5 ions-g de métal alcalin par litre dans ledit milieu, et ledit tensioactif est suffisant pour former, en présence dudit électrolyte, une structure tensioactive vésiculaire et/
35 ou lamellaire capable de supporter ledit adjuvant.

50. Milieu détergent fluide aqueux selon la revendication 49, contenant de 7 à 35%, du poids dudit milieu, de tensioactif.

51. Composition selon l'une ou l'autre des revendications 49 et 50, dans laquelle ledit électrolyte dissous est essentiellement constitué d'adjuvant.

52. Composition selon l'une quelconque des revendications 49 à 51, dans laquelle ledit électrolyte est
40 essentiellement constitué de carbonate de sodium, de silicate de sodium, de citrate de sodium, de nitrilotriacétate de sodium, de phosphate de sodium, de pyrophosphate de sodium, d'un polyphosphate de sodium, d'un phosphonate de sodium ou d'un mélange de n'importe lesquels des électrolytes sus-mentionnés.

53. Composition selon l'une quelconque des revendications 49 à 52, dans laquelle le tensioactif est
45 essentiellement constitué d'alkyl(linéaire)benzène-sulfonate de sodium, ou d'un mélange de ceux-ci, avec un alkyléthersulfate de sodium, un alkylsulfate de sodium, un paraffine-sulfonate de sodium, un oléfine-sulfonate de sodium, des tensioactifs non ioniques et/ou un savon.

54. Composition selon l'une quelconque des revendications précédentes, ayant une viscosité
50 inférieure à 10 Pa.s.

55. Composition selon la revendication 54, ayant une viscosité inférieure à 5 Pa.s.

56. Composition selon l'une quelconque des revendications précédentes, ayant une viscosité supérieure à 0,1 Pa.s.

57. Composition selon la revendication 56, ayant une viscosité supérieure à 0,5 Pa.s.

55

60

65