



(12)

## NEW EUROPEAN PATENT SPECIFICATION

(45) Date of publication of the new patent specification : **05.04.95 Bulletin 95/14**

(51) Int. Cl.<sup>6</sup> : **G03C 1/76, B05D 1/26,  
D21H 13/24**

(21) Application number : **85308401.0**

(22) Date of filing : **19.11.85**

(54) **Base paper for photographic prints.**

(30) Priority : **24.11.84 GB 8429729**

(43) Date of publication of application :  
**04.06.86 Bulletin 86/23**

(45) Publication of the grant of the patent :  
**25.01.89 Bulletin 89/04**

(45) Mention of the opposition decision :  
**05.04.95 Bulletin 95/14**

(84) Designated Contracting States :  
**BE CH DE FR GB IT LI NL SE**

(56) References cited :  
**DE-B- 1 098 656  
DE-B- 1 201 680  
FR-A- 1 359 975  
FR-A- 2 099 168  
GB-A- 862 205  
GB-A- 1 339 045  
GB-A- 1 519 597  
GB-A- 2 061 131  
GB-A- 2 110 116  
JP-A-54 152 084**

(56) References cited :  
**US-A- 3 454 419  
US-A- 3 560 227  
US-A- 3 673 050  
US-A- 4 211 825  
US-A- 4 343 858  
Kunststoff-Handbuch, Band 8 "Polyester",  
1973, p. 707  
Zeitschrift für wissenschaftliche Photo-  
graphie, Band 54, Heft 9-12, 1963, pp. 211-212  
Tappi, Vol. 56, No. 8, 1973, pp. 112-116**

(73) Proprietor : **JAMES RIVER GRAPHICS  
LIMITED  
28 Lincoln's Inn Fields  
London WC2A 3HH (GB)**

(72) Inventor : **Dunk, Paul  
50 Sandringham Court  
Slough  
Berkshire SL1 6JZ (GB)**

(74) Representative : **Raynor, Simon Mark et al  
Urquhart-Dykes & Lord  
Midsummer House  
411C Midsummer Boulevard  
Central Milton Keynes MK9 3BN  
Buckinghamshire (GB)**

**Description**

This invention relates to base paper for photographic prints and in particular to resin coated photographic base paper in which at least the face side resin coating is a multilayer coating.

5 The base paper used for photographic prints typically comprises a high quality paper substrate which has a coating on one or both sides. It acts to provide a suitable physical base structure for the image carrying layer(s), usually in one or more layers of gelatin based photographic emulsion. Originally such papers carried a surface coating of baryta (barium sulphate). In recent years such papers have been coated, usually on both sides with a layer of synthetic polymeric material, typically a polyolefin resin. The resin coating particularly provides protection to the paper from the relatively aggressive materials and conditions used in modern processing 10 especially of colour prints. Such paper is commonly known as photographic base paper often abbreviated to "photobase", and the polymer coated type as "resin coated photographic base paper" often abbreviated to "resin coated photobase". The uncoated paper is commonly referred to as "raw photobase".

15 The side of a sheet of photobase which is to be coated with the photographic emulsion is commonly known as the "face side" and the other side as the "wire side" (because it is this side that is in contact with the Fournier "wire" during papermaking). In resin coated photobase the coating of resin on the face side of the paper is known as the "face side resin coating" and that on the wire side of the paper the "wire side resin coating". The face side resin coating is typically pigmented to prevent (or at least reduce) the loss in photo-definition arising 20 from internal reflection of incident light in developed prints made from it. The pigment used is usually a white pigment such as titanium dioxide.

25 A number of earlier proposals refer to providing the face side resin coating as a multilayer resin coating. Thus, for example, French Patent Specification No. 2 099 168 of Fuji Photo Film describes a two layer coating in which the first (inner) layer is of polyethylene and is extrusion coated at a temperature of 320 to 350°C and a second (outer) layer of polyethylene is coated at 260 to 300°C. The intent is that by coating the inner layer at a high temperature atmospheric oxidation at such high temperature can be turned to advantage to increase 30 the adhesion between the resin coating and the base paper. British Specification No. 1 339 045 also of Fuji Photo Film has a two layer face side polyethylene resin coating in which the opacifying pigment is concentrated in the second (outer) layer. British Patent Specification 2 061 131 of Felix Schoeller is to photobase in which the face side resin coating has two layers in which the inner layer is not stabilised against oxidative degradation and the outer layer is so stabilised. Atmospheric oxidation of the inner layer can promote adhesion between the coating and the substrate.

35 An important property of photobase is its stiffness because the eventually produced photographic printing paper must not be too floppy. This is especially important where large prints are intended for hand processing, as for example in enlargements. A further reason for good stiffness is to reduce the tendency of sensitised print paper, which has gelatin based photographic emulsion layer(s) on it, to curl. In currently available resin coated photobase the major contribution to stiffness comes from the paper rather than the resin coating, because the typical resin, viz. low density polyethylene (LDPE), used for coating raw photobase has relatively 40 low stiffness. It is not regarded as practical to use substantially stiffer polymers for the face and/or wire side resin coatings because the resins which have adequate stiffness and are photographically acceptable have serious disadvantages e.g. they are too expensive or are difficult to pigment adequately or do not adhere adequately to the paper raw base. The stiffness of LDPE can be increased by inclusion of high density polyethylene (HDPE) but, in the face side resin coating, the maximum amount used is relatively small because it is prone to give rise to "gels". Gels are small regions of resin which are harder than the resin in the surrounding area. As they tend to protrude from the surface of the resin, they give rise to faults in the layer of photographic emulsion coated on top of the resin. The gain in stiffness that can be achieved in practice by blending HDPE and 45 LDPE in the face side resin is thus modest. Other stiff resins, such as polypropylene (PP) or polycarbonate (PC) cannot be satisfactorily blended with LDPE to form an homogeneous coating which adheres well to the base paper. The resin coating on the wire side of the photobase can contain a relatively high amount of HDPE because the presence of gels is less objectionable and, because the wire side resin does not need to be pigmented, there is less likelihood of forming gels in the absence or at low concentrations of a pigment like TiO<sub>2</sub>. This can be used to make a stiffer wire side coating to compensate for curl caused by the coating of a gelatin 50 based photographic emulsion on the photobase.

55 We have now surprisingly found that the provision of a thin layer of a relatively stiff polymer on top of the pigmented resin layer in the face side resin coating can give a substantial increase in the stiffness of the photobase.

The present invention accordingly provides resin coated photographic base paper comprising a substrate of paper carrying on its face side a composite coating comprising from 10 to 50 g.m<sup>-2</sup> of an extruded first coating layer of a low density polyethylene or a blend of low density and high density polyethylenes containing at

least 50% by weight of low density polyethylene, the first coating layer containing at least 5% by weight of opacifying pigment and, overlying the first coating layer and firmly bonded thereto, from 0.1 to 18 g.m<sup>-2</sup> of an extruded second coating layer of a polymer having a stiffness modulus of at least 2.0 GPa.

We have found it particularly beneficial as is referred to in more detail below to employ a polycarbonate resin layer as the second layer in the base paper of the invention which, accordingly, includes resin coated photographic base paper comprising a substrate of paper carrying on its face side a composite coating comprising from 10 to 50 g.m<sup>-2</sup> of an extruded first coating layer of a low density polyethylene or a blend of low density and high density polyethylenes containing at least 50% by weight of low density polyethylene, the first coating layer containing at least 5% by weight of opacifying pigment and, overlying the first coating layer and firmly bonded thereto, from 0.1 to 18 g.m<sup>-2</sup> of an extruded second coating layer of a polycarbonate resin.

Although the provision of such an overlying second layer on the face side resin coating can give a significant improvement in stiffness even when the wire side of the paper substrate is not resin coated, the invention specifically includes the provision of a polyolefin resin coating on the wire side of the paper. Such a wire side resin coating improves the resistance of the photobase to the ingress of developer and fixer solutions and chemicals used in making photographic prints. The wire side resin coating may also comprise more than one layer and, in particular, it can include an outer layer of a stiff polymer. The invention accordingly includes resin coated photographic base paper comprising a substrate of paper carrying on its face side a composite coating comprising from 10 to 50 g.m<sup>-2</sup> of an extruded first coating layer of a low density polyethylene or a blend of low density and high density polyethylenes containing at least 50% by weight of low density polyethylene, the first coating layer containing at least 5% by weight of opacifying pigment and, overlying the first coating layer and firmly bonded thereto, from 0.1 to 18 g.m<sup>-2</sup> of an extruded second coating layer of a polymer having a stiffness modulus of at least 2.0 GPa, in particular where the second coating layer is of a polycarbonate resin, and carrying on its wire side a coating of from 10 to 50 g.m<sup>-2</sup> of a polyolefin resin, optionally which wire side coating comprises from 10 to 50 g.m<sup>-2</sup> of a first wire side coating layer of an extruded polyolefin resin and overlying the first wire side coating layer and firmly bonded thereto, from 0.1 to 18 g.m<sup>-2</sup> of an extruded second wire side coating layer of a polymer having a stiffness modulus of at least 2.0 GPa, in particular where the second wire side coating layer is of a polycarbonate resin.

The second layer of the face side coating is of a polymer having a stiffness modulus of at least 2.0 GPa. Broadly LDPE has a modulus of about 0.23 GPa, HDPE of about 1.2 GPa, PP of about 1.4 GPa and PC of about 2.5 GPa. Stiffness moduli as referred to herein are those measured according to American Standard Test Method (ASTM) D 790-80. Because of its high stiffness polycarbonate is an especially good material for the second layer, and the use of polycarbonate for the second layer constitutes a specific and important aspect of this invention. As well as stiffness, the polymer used in the second layer must be substantially colourless, capable of being extruded typically at temperatures up to 300°C, substantially inert to light and in particular resistant to discolouration on exposure to light, it must not interfere with photographic emulsion and it must be substantially inert to the materials used in developing and fixing a photographic image. Polymers which could be used as the second layer include PC, mentioned above, polyamides such as Nylon 11, Nylon 6 and Nylon 66, and polyesters such as polyethylene terephthalate (PET) and polybutylene terephthalate (PBT). Polymers such as polystyrene and polyvinylchloride are generally not sufficiently heat and/or light stable to be suitable and the stabilizers commonly used currently are either not acceptable in photobase or reduce the stiffness of the polymer so much as to make it unsuitable.

The second layer of the stiff polymer may be of a single homopolymer, as described above, or it may be a co-polymer or a blend of polymeric materials having the required stiffness. Further, although reference is made to a single "second layer" of stiff polymer, it is possible that multiple layers of the same, or more usually differing compositions can be employed. Examples of such multiple layers within the second layer could include a clear stiff outer layer and a pigmented stiff inner layer or a stiff outer layer with an inner layer of a blend of the outer layer polymer with the first layer polymer e.g. to give a PC/PC + LDPE/LDPE structure for the face side resin coating with the LDPE and possibly the blend layer containing pigment. One reason for including a layer (or layers) of a polymer blend is to enhance the effective adhesion between the "first" and "second" layers. This, and other methods of enhancing adhesion, are discussed further below.

The second layer, of stiff polymer, is thin in that it constitutes an amount of 0.1 to 18 g.m<sup>-2</sup>, corresponding approximately, depending on the densities of the polymer used, to a thickness of 0.1 to 15 µm. The densities of some stiff polymers, referred to above, are HDPE 0.95, PP 0.9, PC 1.2 g.cm<sup>-3</sup>. Broadly, the heavier (thicker) the second layer the greater the improvement in stiffness. However, the stiff polymers, notably polycarbonate, are generally more expensive than the polyethylene used conventionally and, thus, the use of second layers containing less than 15 g.m<sup>-2</sup> polymer is desirable to save cost. We have not noticed any increased benefit by using more than about 10 g.m<sup>-2</sup> and this represents a practical maximum for improving stiffness in most cases. In practice it is difficult to consistently provide a second layer of less than about 1 µm, even using coextrusion,

as described below, although we have made samples (by coextrusion) with second layers as thin as about 0.1  $\mu\text{m}$  thick and which show significant improvement in stiffness. A practical thickness range of the second layer would be 3 to 10  $\mu\text{m}$  and particularly 4 to 8  $\mu\text{m}$ . In translating thickness to amount in  $\text{g.m}^{-2}$  allowance for the density of the second layer must be made especially for polycarbonate which has a higher density than the other stiff polymers specifically referred to above.

To maximise the benefit in increasing stiffness, it is important that the second layer of stiff polymer adheres well to the first layer. One possibility, that of using blends in an intermediate layer, has been referred to above. This can be done when the respective polymers can be blended to give an adequately homogenous and stable blend. Usually, the blend will have physical properties intermediate the individual components depending on the proportions. Another possibility is to provide an intermediate layer between the "first" and "second" coating layers of a polymer which strongly adheres to the first and second coating layers. Examples of suitable strongly adhesive polymers include ethylene-vinyl acetate copolymers (EVA), ethylene-acrylic acid copolymers (EAA), ethylene-methacrylic acid copolymers (EMA) and the ethylene-vinylacetate terpolymers, ethylene terpolymers and chemically modified polyolefin resins such as those sold under the trade designations CXA by DuPont, Modic by Mitsubishi and Plexar by Chemplex. The intermediate layer will typically be from 1 to 10  $\text{g.m}^{-2}$  and more commonly from 4 to 9  $\text{g.m}^{-2}$ . Usually, such strongly adhesive polymers have relatively low stiffness, typically somewhat less than that of LDPE, and it is particularly surprising that the inclusion of an intermediate layer of such a polymer appears not to have a significant adverse effect on the overall stiffness of the photobase. The intermediate layer may be of the strongly adhesive polymer in a blend with, for example, polyethylene. Such blends can contain up to 75% by weight of the other polymer given that the blend has appropriate properties. The use of such blends can be important especially where the intermediate layer is pigmented as pigments are usually used as masterbatches in e.g. low density polyethylene. The provision of a strongly adherent intermediate layer is considered to be a specific and important subsidiary feature of the invention. It is of particular value when the second layer is of polycarbonate resin.

The invention, accordingly, further includes resin coated photographic base paper comprising a substrate of paper carrying on its face side a composite coating comprising from 10 to 50  $\text{g.m}^{-2}$  of an extruded first coating layer of a low density polyethylene or a blend of low density and high density polyethylenes containing at least 50% by weight of low density polyethylene, the first coating layer containing at least 5% by weight of opacifying pigment, overlying the first coating layer, a second coating layer of from 0.1 to 18  $\text{g.m}^{-2}$  of a polycarbonate resin, and intermediate the said first and second coating layers, a layer of from 1 to 10  $\text{g.m}^{-2}$  of a polymer, which is strongly adhesive towards both the first and second layers, serving to firmly bond the said first and second layers where the photobase includes a wire side resin coating with a second coating layer of stiff polymer an intermediate layer of a strongly adhesive polymer can be included. When an intermediate layer of a strongly adhesive polymer is used it may, advantageously include a pigment, and in particular titanium dioxide, as described in more detail below.

A known problem in making resin coated photobase is in ensuring good adhesion between the resin coating and the raw paper base. Methods of overoming this difficulty are known but the use of a coextrusion technique in this invention opens up the possibility of deliberately coextruding a polymer layer between the pigmented LDPE first coating layer and the raw base which serves to ensure good adhesion. The coatweights used will typically be similar to those for the "intermediate" layer referred to above and will usually be from 1 to 10  $\text{g.m}^{-2}$ , more commonly from 4 to 9  $\text{g.m}^{-2}$ . The polymers which can be used for this include those indicated above as being suitable for inclusion in a strongly adhesive layer between the "first" and "second" coating layer. The use of such an adhesive layer between the pigmented LDPE and the raw paper base constitutes a specific subsidiary feature of this invention. It is also possible to include such a layer of a strongly adhesive polymer between the wire side polyolefin resin coating and the raw paper base.

The invention, accordingly, further includes resin coated photographic base paper comprising a substrate of paper carrying on its face side a composite coating comprising from 10 to 50  $\text{g.m}^{-2}$  of an extruded first coating layer of a low density polyethylene or a blend of low density and high density polyethylenes containing at least 50% by weight of low density polyethylene, the first coating layer containing at least 5% by weight of opacifying pigment, overlying the first coating layer, a second coating layer of from 0.1 to 18  $\text{g.m}^{-2}$  of a polycarbonate resin, and intermediate the base paper and the said first coating layer, a layer of from 1 to 10  $\text{g.m}^{-2}$  of a polymer, which is strongly adhesive towards both the base paper and the first coating layer, serving to firmly bond the said base paper and the first coating layer.

The effect of providing a thin second layer of a stiff polymer overlying a pigmented first layer in the face side resin coating is to increase the stiffness of the photobase. The increase in stiffness which might be expected from consideration of photobase according to this invention as a compound beam is difficult to assess precisely because it depends on assumptions on the behaviour of the various parts of the photobase and the interactions at the interfaces between polymer and polymer and paper. Nevertheless, from base-

line properties the increase observed is generally greater than would be expected. We cannot fully account for this but we think it is possible that the second layer, being thin, experiences a degree of orientation during extrusion and/or cooling which causes the second layer to have a higher stiffness than the polymer itself (published stiffness data being for test "plaques" typically several mm thick) or that the photobase is made stiffer by the composite structure.

However, these suggestions are not a complete explanation of the observed properties of photobase according to this invention. In particular, we cannot explain fully the behaviour of photobase where the second coating layer is of polycarbonate particularly at a coatweight of from 3 to 18 especially 4 to 10 g.m<sup>-2</sup>. Briefly we have found that the stiffness in the machine direction (MD) is increased but the stiffness in the cross-machine direction (CD) is increased to a proportionally greater extent. Further, the measured CD stiffness depends on the direction of bending. Thus when the polycarbonate is in tension the measured stiffness is significantly greater when the polycarbonate is in compression. The stiffness in the MD does not show any significant difference in this way. The effect of this phenomena is that photographic base paper according to the invention is more "square" and usually less liable to curl. These observations are very difficult to account for. The enhancement of overall stiffness can be even more marked when a composite multilayer wire side coating with a polycarbonate second layer is used as the enhancement of a CD stiffness for each polycarbonate coating will complement each other and, thus reduce or eliminate the anisotropy in CD stiffness.

The second layer can be unpigmented or pigmented with conventional opacifying pigment. However, the stiff polymers used in the second layer can be relatively difficult to coextrusion coat onto paper if they contain large amounts of pigment, e.g. greater than about 5%. Subject to this the amount of opacifying pigment can be similar to that used in the first layer. If used the opacifying pigment will normally be a white pigment typically titanium dioxide. There can be a benefit in using low pigment loadings in the second layer in that it can enable the use of higher pigment loadings in the first layer. This is discussed in more detail below.

In this invention the first layer is of LDPE or a blend of at least 50% by weight, and more usually at least 70% by weight, of LDPE with HDPE and contains opacifying pigment. The opacifying pigment is usually white, in which case it is almost invariably titanium dioxide and usually rutile, although it can be black e.g. carbon black as is used in making photobase for so-called "instant" prints. The overall amount of pigment is such as to give the desired degree of opacity and, as indicated above, the amount used is at least 5% by weight. When rutile titanium dioxide is used the amount is typically at least 8% by weight and commonly 12 to 15% by weight of the layer. In the present invention, as is noted briefly above, we have found that, using coextrusion coating, see below, significantly higher pigment loadings are possible in the first layer when the second layer is not heavily pigmented. An entirely unpredictable benefit arising from this possibility of increasing the concentration of pigment in the first layer is that it is practical to use anatase titanium dioxide as the opacifying pigment in high enough concentrations to make it attractive to use in photobase. Anatase has advantages over rutile when used as an opacifying pigment in resin coated photobase as it has a bluer tint than rutile (blue pigment e.g. ultramarine, is often included with rutile in the face side resin to make it more blue) and gives a brighter product. However, it is very difficult to use especially at concentrations which make it a good opacifying pigment and its inclusion is often deliberately avoided despite its advantages. The method of this invention enables the use of satisfactorily high concentrations of anatase to achieve good opacity and tint without the severe production problems usually encountered. When such higher pigment loadings are used the concentration of pigment can be up to 25% by weight and possibly higher e.g. up to 35% by weight.

As is noted above when a strongly adhesive intermediate layer is used it can be pigmented and the amount of pigment used will typically be similar to those used in the LDPE (first) layer.

The range of pigment content referred to above (typically 12 to 15% by weight) are typical of conventional resin coated photobase which has a face side resin coating thickness of from 20 to 40 µm. Because the method of present invention enables the use of higher concentration of pigment it is possible to use somewhat thinner pigmented layers than previously considered appropriate whilst maintaining opacity.

Other conventional additives can be included in the first layer. Examples include long term stabilizers such as the phosphonites described in UK Specification 2 048 278 and the polymeric hindered amine Chimassorb 944 used as described in European Patent Specification No. 0 085 523, optical brighteners and blue pigments such as ultramarine pigment which are included to enhance the visual brightness of the photobase.

The wire side polyolefin resin coating according to the invention can be of a conventional type for photobase. Typically it will be of LDPE or a blend of LDPE and HDPE which may include more than 50% by weight e.g. up to 75% by weight HDPE. The amount of the wire side coating will typically be from 5 to 50 and more commonly from 15 to 35 g.m<sup>-2</sup>. Whilst it is possible to include pigment in the wire side resin coating, it is not necessary or particularly advantageous to do so. When an overlying layer of stiff polymer and, optionally, an intermediate layer of strongly adhesive polymer are used the thickness of these layers will typically be similar to those for the face side resin coating.

The surface finish on both wire and face side resin coatings can be gloss, silk, stipple or other finish as desired. The maximum degree of gloss on the face side resin coating which can be obtained in the product and by the method of the present invention is higher than with equivalent currently commercially available materials. The improvement in the maximum degree of gloss is particularly noticeable when the second layer is 5 polycarbonate. Moreover, this improvement can be maintained at higher line speeds than are practical for producing gloss surfaces on LDPE coatings. This is an important practical advantage. The outer surface of the wire side resin can be further treated with a conventional coating to aid writability.

A further and entirely unexpected advantage in using a stiff polymer, specifically polycarbonate, second layer in the face side resin coating is that the incidence of pitting is reduced as compared with that obtained 10 with a pigmented LDPE monolayer. We do not understand why this result is obtained but it is important, particularly as it can be achieved with low coatweights of the second layer.

The advantages by the use of a second layer of stiff polymer and especially where the stiff polymer is 15 polycarbonate, are such that it may be commercially advantageous to use a relatively thin second layer of the stiff polymer. This could result in obtaining a lesser improvement in stiffness whilst taking advantage of the other improvements. A reason for adopting this type of compromise is the relatively high cost of stiff polymers e.g. currently polycarbonate costs about four times that of LDPE.

The photographic base paper of this invention is made by extrusion coating multiple layers of various polymeric resins onto paper. At least some of the layers are sufficiently thin that, using current technology, it would 20 be impractical and might not be possible to undertake commercial production by extruding such unsupported thin layers. This difficulty can be overcome by using a coextrusion coating method in which two or more coating layers are extruded through a single extrusion die and, thus, simultaneously coated onto the substrate. In practical operation, we expect that all layers (two or more) in the multi-layered coating will be coextruded in a single coating operation. Accordingly, the invention includes a method of making resin coated photographic base paper which comprises co-extruding onto the face side of a paper substrate a composite coating of from 10 to 25 50 g.m<sup>-2</sup> of a first layer of a low density polyethylene or a blend of low density and high density polyethylenes containing at least 50% by weight low density polyethylene, the first layer containing at least 5% by weight of opacifying pigment, and, disposed on the side of the first layer remote from the paper substrate from 0.1 to 18 g.m<sup>-2</sup> of a second layer of a polymer having a stiffness modulus of at least 2.0 GPa.

As will be clear from the description above, the second layer is particularly preferably of a polycarbonate 30 resin. The co-extruded structure can specifically include further layers such as a layer between the "first" and "second" coating layers of a polymer which is strongly adherent to the first and second layers. The invention further includes a method of making resin coated photographic base paper which comprises co-extruding onto the face side of a paper substrate a composite coating of first and second layers as set out above and, before 35 or after co-extruding the coating on the face side of the paper, extrusion coating a coating of from 10 to 50 g.m<sup>-2</sup> of a polyolefin resin onto the wire side of the paper substrate. The coating on the wire side of the substrate can be a multilayer coating, as is described above and when this is so it can be co-extruded in a manner similar to that described above for the face side resin.

The relative amounts of layers in the face side coating can be controlled by regulating the output of the corresponding extruders. Conventional co-extrusion equipment can be used provided that it can effect extrusion 40 at the temperatures used in making resin coated photobase which are typically 280 to 320°C which is rather higher than in other applications. The wire side resin coating can be extrusion or co-extrusion coated before or after the co-extrusion coating of the face side and can be carried out in line on a tandem coater or off line in a separate coating step.

Generally the adhesion between gelatin based photographic emulsion and the types of polymeric resin 45 used in photobase is not particularly good and the surface of the face side resin is treated e.g. by treatment with a corona discharge, to enhance adhesion of the emulsion. This technique can be applied to resin coated photobase of and made by the method of the present invention. Further, the enhanced adhesion between photobase and emulsion generated by corona treatment will decay over time but it is possible to apply an anti-adhesion decay agent to prevent this, typically, a solution of gelatin which generates a very thin layer of gelatin 50 of typically less than 1 g.m<sup>-2</sup> which adheres firmly to the photobase and provides a good bond with the photographic emulsion. The invention includes further treating corona treated photobase with an anti-adhesion decay agent, especially a solution of gelatin to form a very thin layer of gelatin thereon.

The invention includes photographic printing paper which comprises photobase of or made by the method 55 of the present invention carrying on top of the second layer a layer of a photographic emulsion. When present the layer of anti-adhesion decay agent will lie between the second layer and the layer of photographic emulsion.

The following Examples illustrate the invention. All parts or percentages are by weight unless otherwise stated.

The test methods used were as follows:

55 Stiffness (rigidity), two types of equipment were used the Kenley tester and the Lorentzen and Wettre tester.

56 The test methods are as follows:

57 5 Kenley rigidity.

58 A strip of paper 1.5 inches (38.1 mm) wide is clamped so that 2.25 inches (57.2 mm) of the strip protrudes vertically upwards from a horizontal lamp. A probe carrying a force sensor is positioned to move in a line 4 cm above the clamping plane, perpendicular to the mid-line along the test strip. The probe is moved to deflect the 10 test strip to a position such that the angle between the line connecting the probe tip and the clamp is 15° from the vertical, within a period from 2.5 to 30 seconds. The stiffness is the measured force at this position. The Kenley test instrument gives the result in grams force but are expressed herein as milliNewtons (mN). (The value obtained properly has the dimensions force x length<sup>-1</sup> but as the effective length is defined by the width of the test piece, Kenley rigidity is always quoted as the measured force).

15

16 Lorentzen and Wettre stiffness.

17 This test is carried out in a rectangular sample of paper 70 mm by 38.1 mm. The sample is clamped in 20 vertically disposed jaws with the long edges of the paper horizontal and the short edges vertical. The clamping jaws are mounted to be rotatable about a vertical axis. The paper is positioned to contact a vertically disposed knife edge, attached to a force sensor, and positioned 25 mm from the clamping locus in the plane of the paper surface. The clamping jaws are rotated, under machine control, through a preset angle (15°). The rigidity of the sample is the maximum force detected by the sensor. The instrument gives a digital reading in milliNewtons(mN). (As with the Kenley test instrument the result properly has dimensions of force x length<sup>-1</sup> but is always quoted as force as indicated by the readout.)

25

26 Example 1

27 30 178 g.m<sup>-2</sup> white photographic raw paper was extrusion coated on its face side with 40 g.m<sup>-2</sup> of various polymer coatings. For control purposes one coating was of pigmented LDPE only. Samples 1 and 2 were also comparative, comprising a first layer of pigmented LDPE containing 12.5% rutile titanium dioxide and a second layer of a moderately stiff unpigmented polymer. Sample 3 was an Example of the present invention. The coating was carried out using a 2-layer pilot co-extrusion coater at a line speed of 50 m.min<sup>-1</sup> using a gloss chill roll. Relative and total coatweights were controlled by adjusting the output of the two extruders. The various 35 materials used were as follows:

36

LDPE	from DOW Chemicals,Europe
HDPE	
PP	Tenite 4G7DP from Eastman Chemicals
PC	Lexan 1972-2 from General Electric Plastics
TiO <sub>2</sub>	Ampacet AW11485-S (masterbatch containing 50% TiO <sub>2</sub> in LDPE)

40 The amount of materials coated and the stiffness testing results are given in Table 1 below.

45

46 TABLE 1

Sample No.	First Layer g.m <sup>-2</sup>	Second Layer		Kenley Stiffness
		Polymer	g.m <sup>-2</sup>	
Control	40	—	—	18.8
1	36.6	HDPE	3.4	20.6
2	36.8	PP	3.2	20.2
3	39.9	PC	0.1	20.2

50

55 These results indicate that a substantial gain in stiffness can be achieved by including only a thin second layer of stiff polymer in the face side resin coating.

Example 2

Raw photographic base paper having a grammage of 170 g.m<sup>-2</sup> was resin coated on a pilot 2-layer co-extrusion coating line using a matt chill roll. Various coating structures were produced as set out in Table 2a below. The control structure was made by co-extruding pigmented LDPE in both extrusion channels of the co-extruder onto the new base paper to give effectively a monolayer. The three layer structures were made by first extruding a monolayer coating the raw base with the specified coatweight of pigmented LDPE and subsequently co-extrusion coating on top the specified EVA/PC layer. The photobase was subsequently mono-extrusion coated on the wire side with an unpigmented coating of 27 g.m<sup>-2</sup> of a 1:1 blend of LDPE and HDPE. The results of stiffness testing (Lorenzen and Wettre) are set out in Table 2b below. The polymers used in the face side resin coatings were as follows:

LDPE Escorin LD 252 from Esso Chemicals Ltd.  
 TiO<sub>2</sub> Ampacet AW11485-S  
 EVA Escorin VL 00909, an EVA colymer containing 9% units by wt  
 PC Lexan 1972-2

The pigmented EVA used was a blend of Escorin EVA (71.19%) and Ampacet masterbatch (28.9%).

Example 3

Raw photographic base paper having a grammage of 165 g.m<sup>-2</sup> was resin coated by co-extrusion using a gloss chill roll. Various coating structures were produced as described below with the coatweights (as measured on the product) given in Table 3a below.

The materials used were as follows:

LDPE Escorin LD 252  
 TiO<sub>2</sub> Ampacet AW 11485-S  
 HDPE from Dutch State Mines  
 EVA Escorin VL 00909  
 PC Lexan 1972-2

Pigmented resin layers were made up using appropriate amounts of unpigmented resin and of TiO<sub>2</sub> masterbatch.

The products made according to the invention had a face side coating comprising an inner layer of a pigmented blend of LDPE and HDPE (57.8% LDPE + 13.3% HDPE + 28.9% TiO<sub>2</sub> masterbatch in LDPE) an intermediate layer of pigmented EVA (71.1% EVA + 28.9% TiO<sub>2</sub> masterbatch in LDPE) and an outer layer of PC, and a wire side coating comprising an inner layer of a blend of 50% LDPE and 50% HDPE, an intermediate layer of unpigmented EVA and an outer layer of PC. The inner and intermediate layers on both sides of the photobase are difficult to distinguish from each other in the product. In Table 3a below the intended or "target" coatweights for the individual inner intermediate ("inter") and outer layers are given with the measured coatweight (derived from thickness measurement) of the inner and inter layers combined and of the outer layer, which can be distinguished by microscopic examination.

The results of stiffness and gloss testing are given in Table 3b below. Because both face and wire side coatings include a layer of polycarbonate the marked anisotropy of stiffness noted in Example 2 was not observed. The gloss measurements are comparative rather than absolute measurements because although the chill roll used was a gloss chill roll, its surface finish was somewhat variable, and this variation could be visually observed during coating, and the surface quality of the chill roll was inferior to the standard of gloss chill roll finish on production extrusion coaters for photobase. Despite this the product made by co-extrusion to give a polycarbonate layer on the exterior on the face side had superior gloss to the control. The products obtained were assessed for the occurrence of pits. The number and size of pits in the resin coating were both significantly smaller in the product made according to the invention as compared with the control. All the products of the invention showed no evidence of gels.

Two control samples were used in this Example. For comparing stiffness the control was of a standard commercial resin coated photobase for colour printing based on a 165 g.m<sup>-2</sup> raw base with a mono-extruded face side resin coating of 30 g.m<sup>-2</sup> of a pigmented blend of LDPE and HDPE) and a mono-extruded wire side resin coating of 30 g.m<sup>-2</sup> of an unpigmented blend of 50% LDPE and 50% HDPE. For comparing gloss and pitting the face side of 165 g.m<sup>-2</sup> raw photobase was mono-layer coated in the co-extrusion line with a 30 g.m<sup>-2</sup> coating of a pigmented blend of LDPE and HDPE (57.8% LDPE + 13.3% HDPE + 28.9% TiO<sub>2</sub> masterbatch in LDPE). Gloss measurements were made using a Mk2 Glossmeter with a 75° Glosshead (made by Sheen Instruments Ltd.). The meter produces a reading from 0% i.e. a matt black surface (the instrument is zeroed using the matt standard provided) and 100%. The scaling is set using a gloss standard (in this case a black

glass plate with a stated gloss of 97.8 using the 75° Glosshead).

TABLE 2a

5	Sample No.	Face side resin coating				intermediate layer				second layer			
		first layer			intermediate layer			second layer					
		Resin	Amount	% TiO <sub>2</sub>	Resin	Amount	% TiO <sub>2</sub>	Polymer	Amount	% TiO <sub>2</sub>			
	Control	LDPE	13.5	12.5	N/A	N/A	N/A	LDPE	13.5	12.5			
10	1	LDPE	13.5	16.7	EVA	6.75	16.7	PC	6.1	0			
	2	LDPE	10	22.5	EVA	8	22.5	PC	10.4	0			
	3	LDPE	10	22.5	EVA	5	22.5	PC	12.1	0			

TABLE 2b

15	Sample No.	Stiffness				Cross Direction			
		Machine Direction				Cross Direction			
		+	-	mean	diff	+	-	mean	diff
	Control	134.5	136.8	135.8	0	76.4	69.9	75.2	0
	1	145.0	143.7	144.3	+6.3	92.0	78.4	85.2	+13.3
20	2	152.9	155.2	154.0	+13.4	109.5	77.5	93.3	+24.1
	3	151.6	153.8	152.7	+12.4	109.4	78.4	93.9	+24.9

Key to Table

+ = face side resin in tension

- = face side resin in compression

diff = percentage difference between sample mean and control mean

25

TABLE 3a

30	Sample No.	Face Side				Wire Side			
		inner	inter	outer	inner	inter	outer		
1	target	18	8	4	18	8	4		
	actual		27.7	6.2		18.6	5.6		
2	target	18	6	6	18	6	6		
	actual		31.6	6.7		15.4	7.1		
35	target	18	4	8	18	4	8		
	actual		24.4	8.5		20.1	7.8		

TABLE 3b

40	Sample No.	Stiffness				Cross Direction				Gloss Rating		
		Machine Direction				Cross Direction				F.S.	W.S.	diff
		+	-	mean	diff	+	-	mean	diff	F.S.	W.S.	diff
	Control	—	—	139.5	0	—	—	78.6	0	87.4	82.6	0
45	1	150.5	145.2	147.9	+6.0	83.5	99.0	92.3	+17.4	96.1	90.5	+9.7
	2	165.0	156.4	160.7	+15.7	95.4	104.1	29.8	+27.0	94.3	97.5	+12.8
	3	170.7	162.1	166.4	+19.3	97.8	112.9	105.4	+34.0	90.2	95.8	+9.4

Key To Table

+ = face side resin in tension

- = face side resin in compression

diff = percentage difference between sample mean and control mean

F.S. = face side

W.S. = wire side

55

**Claims**

1. Resin coated photographic base paper comprising a substrate of paper carrying on its face side a composite coating comprising from 10 to 50 g.m<sup>-2</sup> of an extruded first coating layer of a low density polyethylene or a blend of low density and high density polyethylenes containing at least 50% by weight of low density polyethylene, the first coating layer containing at least 5% by weight of opacifying pigment and, overlying the first coating layer and firmly bonded thereto, from 0.1 to 18 g.m<sup>-2</sup> of an extruded second coating layer of a polymer having a stiffness modulus of at least 2.0 GPa.
10. 2. Photographic base paper as claimed in claim 1 wherein the second layer is of polycarbonate.
3. Photographic base paper as claimed in claim 1 or 2 wherein the second layer has a coatweight of from 1 to 15 g.m<sup>-2</sup>.
15. 4. Photographic base paper as claimed in claim 3 wherein the second layer has a coatweight of from 3 to 10 g.m<sup>-2</sup>.
5. Photographic base paper as claimed in any one of claims 1 to 4 which includes a layer, intermediate the said first and second coating layers, a layer of from 1 to 10 g.m<sup>-2</sup> of a polymer, which is strongly adhesive towards both the first and second layers, serving to firmly bond the said first and second layers.
20. 6. Photographic base paper as claimed in claim 5 wherein the intermediate layer is of ethylene-vinyl acetate copolymers (EVA), ethylene-acrylic acid copolymers (EAA), ethylene-methacrylic acid copolymers (EMA) and the ethylene-vinylacetate terpolymers, ethylene terpolymers and chemically modified polyolefin resins.
25. 7. Photographic base paper as claimed in any one of claims 1 to 6 which includes a layer, intermediate the base paper and the said first coating layer, a layer of from 1 to 10 g.m<sup>-2</sup> of a polymer, which is strongly adhesive towards both the base paper and the first coating layer, serving to firmly bond the said base paper and first coating layer.
30. 8. Photographic base paper as claimed in any one of claims 1 to 7 wherein the wire side of the base paper is coated with from 10 to 50 g.m<sup>-2</sup> of a polyolefin resin coating.
35. 9. Photographic base paper as claimed in claim 8 wherein the polyolefin resin of the wire side coating layer is LDPE or a blend of LDPE and HDPE.
10. 10. Photographic base paper as claimed in either claim 8 or claim 9 wherein the wire side coating comprises from 10 to 50 g.m<sup>-2</sup> of a first wire side coating layer of an extruded polyolefin resin and overlying the first wire side coating layer and firmly bonded thereto, from 0.1 to 18 g.m<sup>-2</sup> of an extruded second wire side coating layer of a polymer having a stiffness modulus of at least 2.0 GPa.
40. 11. Photographic base paper as claimed in claim 10 wherein the second wire side coating layer is from 3 to 10 g.m<sup>-2</sup> of polycarbonate.
45. 12. Photographic base paper as claimed in any one of claims 8 to 11 in which the wire side resin coating includes a layer, intermediate the base paper and the said first wire side coating layer, a layer of from 1 to 10 g.m<sup>-2</sup> of a polymer, which is strongly adhesive towards both the base paper and the first wire side coating layer, serving to firmly bond the said base paper and the first wire side coating layer.
50. 13. A method of making resin coated photographic base paper which comprises co-extruding onto the face side of a paper substrate a composite coating of first and second layers, the first coating layer being from 10 to 50 g.m<sup>-2</sup> of a low density polyethylene or a blend of low density and high density polyethylenes containing at least 50% by weight of low density polyethylene and containing at least 5% by weight of opacifying pigment, the second coating layer, overlying the first coating layer and being from 0.1 to 18 g.m<sup>-2</sup> of a polymer having a stiffness modulus of at least 2.0 GPa.
55. 14. A method as claimed in claim 13 wherein the second coating layer is of polycarbonate.
15. A method as claimed in either claim 13 or claim 14 wherein the wire side of the base paper is extrusion

coated with a coating-comprising a layer of from 10 to 50 g.m<sup>-2</sup> of a low density polyethylene or a blend of low density and high density polyethylene.

16. A method as claimed in claim 15 wherein the coating on the wire side is co-extrusion coated to provide a composite coating of first and second coating layers, the first wire side coating layer being the 10 to 50 g.m<sup>-2</sup> layer of polyethylene and the second wire side coating layer, overlying the first wire side coating layer and being from 3 to 10 g.m<sup>-2</sup> of polycarbonate.

10 **Patentansprüche**

1. Harzbeschichtetes photographisches Basispapier mit einem Substrat aus Papier, das auf seiner Vorderseite eine zusammengesetzte Beschichtung mit einer ersten extrudierten Beschichtungs-Schicht und mit einer über dieser liegenden, mit dieser fest verbundenen zweiten extrudierten Beschichtungs-Schicht trägt, wobei die erste Beschichtungs-Schicht ein Flächengewicht von 10 bis 50 g.m<sup>2</sup> aufweist und aus Polyäthylen niedriger Dichte oder aus einer Mischung von mindestens 50 Gew.-% Polyäthylen niedriger Dichte und Polyäthylen hoher Dichte ist, wobei die zweite Beschichtungs-Schicht ein Flächengewicht von 0,1 bis 18 g.m<sup>2</sup> aufweist und aus einem Polymer ist, das einen Steifigkeitsmodul von wenigstens 2,0 GPa besitzt.
2. Photographisches Basispapier nach Anspruch 1, **dadurch gekennzeichnet, daß** die zweite Schicht aus Polycarbonat ist.
3. Photographisches Basispapier nach einem der Ansprüche 1 oder 2, **dadurch gekennzeichnet, daß** die zweite Schicht ein Flächengewicht von 1 bis 15 g.m<sup>2</sup> aufweist.
4. Photographisches Basispapier nach Anspruch 3, **dadurch gekennzeichnet, daß** die zweite Schicht ein Flächengewicht von 3 bis 15 g.m<sup>2</sup> aufweist.
5. Photographisches Basispapier nach einem der Ansprüche 1 bis 4, **gekennzeichnet durch** eine weitere Schicht mit einem Flächengewicht von 1 bis 10 g.m<sup>2</sup> aus einem Polymer zwischen der genannten ersten und der genannten zweiten Beschichtungs-Schicht, wobei diese weitere Schicht sowohl gegenüber der ersten als auch der zweiten Schicht stark adhäsiv ist und welche zur festen Verbindung der genannten ersten und zweiten Schicht dient.
6. Photographisches Basispapier nach Anspruch 5, **dadurch gekennzeichnet, daß** eine Zwischenschicht aus Äthylen-Vinylacetat-Copolymer (EVA), Äthylen-Acryl-Acid Copolymer (EAA), Äthylen-Metacryl Acid Copolymer (EMA) und Äthylen-Vinylacetat Terpolymer, Äthylen Terpolymer und chemisch modifizierten Polyolefin-Harzen besteht.
7. Photographisches Basispapier nach einem der Ansprüche 1 bis 6, **dadurch gekennzeichnet, daß** es eine Schicht enthält, die zwischen dem Basispapier und der ersten Beschichtungs-Schicht liegt, einer Schicht zwischen 1 und 10 g.m<sup>2</sup> eines Polymers, die stark adhäsiv sowohl gegenüber dem Basispapier als auch der ersten Beschichtungs-Schicht ist, und die dazu dient, das Basispapier und die erste Beschichtungs-Schicht aneinander zu binden.
8. Photographisches Basispapier nach einem der Ansprüche 1 oder 7, **dadurch gekennzeichnet, daß** die Drahtseite des Basispapiers mit einer Polyolefin-Harzbeschichtung mit einem Flächengewicht von 10 bis 50 g.m<sup>2</sup> beschichtet ist.
9. Photographisches Basispapier nach Anspruch 8, **dadurch gekennzeichnet, daß** das Polyolefin Harz der Drahtseitenbeschichtungs-Schicht LDPE oder eine Mischung aus LDPE und HDPE ist.
10. Photographisches Basispapier nach einem der Ansprüche 8 oder 9, **dadurch gekennzeichnet, daß** die Drahtseitenbeschichtung eine erste Drahtseitenbeschichtungs-Schicht mit einem Flächengewicht von 10 bis 50 g.m<sup>2</sup> umfaßt, die aus einem extrudierten Polyolefin-Harz besteht und die die erste Drahtseitenbeschichtungs-Schicht überlagert und fest mit dieser verbunden ist, wobei eine zweite extrudierte Drahtseitenbeschichtungs-Schicht mit einem Flächengewicht von 0,1 bis 18 g.m<sup>2</sup> eines Polymers einen Steifigkeitsmodul von mindestens 2,0 GPa hat.

11. Photographisches Basispapier nach Anspruch 10, **dadurch gekennzeichnet, daß** die zweite Drahtseitenbeschichtungs-Schicht aus Polycarbonat mit einem Flächengewicht von 3 bis 10 gm<sup>2</sup> besteht.

5 12. Photographisches Basispapier nach einem der Ansprüche 8 oder 11, **dadurch gekennzeichnet, daß** die Drahtseitenbeschichtungs-Schicht eine Schicht umfaßt, die zwischen dem Basispapier und der ersten Drahtseitenbeschichtungs-Schicht liegt, eine Polymerschicht mit einem Flächengewicht von 1 bis 10 gm<sup>2</sup>, die stark adhäsiv gegenüber sowohl dem Basispapier als auch der ersten Drahtseitenbeschichtungs-Schicht ist, und die dazu dient, das Basispapier und die erste Drahtseitenbeschichtungs-Schicht fest aneinander zu binden.

10 13. Verfahren zur Herstellung von harzbeschichtetem photographischen Basispapier, das das Co-extrudieren einer Composit-Beschichtung in einer ersten und zweiten Schicht auf die Vorderseite umfaßt, wobei die erste Beschichtungs-Schicht aus einem Polyäthylen niedriger Dichte mit einem Flächengewicht von 10 bis 50 gm<sup>2</sup> besteht oder einer Mischung aus Polyäthylen niedriger und hoher Dichte, die zumindest 50 Gew.-% des Polyäthylens geringer Dichte und mindestens 5 Gew.-% eines opacifizierenden Pigmentes enthält, wobei die zweite Beschichtungs-Schicht, die die erste Beschichtungs-Schicht überlagert, aus einem Polymer mit einem Flächengewicht von 0,1 bis 18 gm<sup>2</sup> besteht, welches einen Steifigkeitsmodul von mindestens 2,0 GPa besitzt.

15 14. Verfahren nach Anspruch 13, **dadurch gekennzeichnet, daß** die zweite Beschichtungs-Schicht aus Polycarbonat besteht.

20 15. Verfahren nach Anspruch 13 oder 14, **dadurch gekennzeichnet, daß** die Drahtseite des Basispapiers mit einer Beschichtung extrusionsbeschichtet wird, die eine Schicht aus Polyäthylen niedriger Dichte umfaßt, mit einem Flächengewicht von 10 bis 50 gm<sup>2</sup> oder einer Mischung aus Polyäthylen niedriger und hoher Dichte.

25 16. Verfahren nach Anspruch 15, **dadurch gekennzeichnet, daß** die Beschichtung auf der Drahtseite durch Koextrusion beschichtet ist, um eine Komposit-Beschichtung aus einem ersten und einer zweiten Beschichtungs-Schicht vorzusehen, wobei die erste Drahtseitenbeschichtungs-Schicht eine Polyäthylen-Schicht mit einem Flächengewicht von 10 bis 50 gm<sup>2</sup> ist und die zweite Drahtseitenbeschichtungs-Schicht, welche die erste Drahtseitenbeschichtungs-Schicht überlagert, aus einem Polycarbonat mit einem Flächengewicht von 3 bis 10 gm<sup>2</sup> besteht.

35 **Revendications**

1. Papier support photographique enduit de résine, comprenant un support de papier, portant sur son côté endroit un revêtement composite comprenant de 10 à 50 g.m<sup>-2</sup> d'une première couche de revêtement extrudée d'un polyéthylène basse densité ou d'un mélange de polyéthylènes basse densité et haute densité 40 contenant au moins 50% en poids de polyéthylène basse densité, la première couche de revêtement contenant au moins 5% en poids de pigment opacifiant et, recouvrant la première couche de revêtement et liée solidement à celle-ci, de 0,1 à 18 g.m<sup>-2</sup> d'une seconde couche de revêtement extrudée d'un polymère présentant un module de rigidité d'au moins 2,0 GPa.

45 2. Papier support photographique selon la revendication 1, dans lequel la seconde couche est faite d'un polycarbonate.

3. Papier support photographique selon la revendication 1 ou 2 dans lequel la seconde couche possède un poids d'enduit allant de 1 à 15 g.m<sup>-2</sup>.

50 4. Papier support photographique selon la revendication 3, dans lequel la seconde couche possède un poids d'enduit allant de 3 à 10 g.m<sup>-2</sup>.

55 5. Papier support photographique selon l'une quelconque des revendications 1 à 4, qui comprend, entre les première et seconde couches de revêtement, une couche de 1 à 10 g.m<sup>-2</sup> d'un polymère, qui adhère fortement à la fois à la première et à la seconde couche, servant à lier solidement lesdites première et seconde couches.

6. Papier support photographique selon la revendication 5, dans lequel la couche intermédiaire est faite de copolymères éthylène-acétate de vinyle (EVA), copolymères éthylène-acide acrylique (EAA), copolymères éthylène-acide méthacrylique (EMA) et de terpolymères éthylène-acétate de vinyle, terpolymères de l'éthylène et résines de polyoléfines modifiées chimiquement.

5 7. Papier support photographique selon l'une des revendications 1 à 6, qui comprend, entre le papier support et la première couche de revêtement, une couche de 1 à 10 g.m<sup>-2</sup> d'un polymère, qui adhère fortement à la fois au papier support et à la première couche de revêtement, servant à lier solidement ledit papier support et ladite première couche de revêtement.

10 8. Papier support photographique selon l'une des revendications 1 à 7, dans lequel le côté envers du papier support est revêtu par 10 à 50 g.m<sup>-2</sup> d'un revêtement de résine de polyoléfine.

15 9. Papier support photographique selon la revendication 8, dans lequel la résine de polyoléfine de la couche de revêtement du côté envers est du LDPE ou un mélange de LDPE et de HDPE.

10 10. Papier support photographique selon l'une des revendications 8 ou 9, dans lequel le revêtement du côté envers comprend de 10 à 50 g.m<sup>-2</sup> d'une première couche de revêtement de côté envers en une résine de polyoléfine extrudée et recouvrant la première couche de revêtement de côté envers et liée solidement à celle-ci, de 0,1 à 18 g.m<sup>-2</sup> d'une seconde couche de revêtement de côté envers extrudée, d'un polymère présentant un module de rigidité d'au moins 2,0 GPa.

20 11. Papier support photographique selon la revendication 10, dans lequel la seconde couche de revêtement de côté envers est de 3 à 10 g.m<sup>-2</sup> de polycarbonate.

25 12. Papier support photographique selon l'une des revendications 8 à 11, dans lequel le revêtement de résine de côté envers comprend, entre le papier support et la première couche de revêtement de côté envers, une couche de 1 à 10 g.m<sup>-2</sup> d'un polymère, qui adhère fortement à la fois au papier support et à la première couche de revêtement de côté envers, servant à lier solidement ledit papier support et ladite première couche de revêtement de côté envers.

30 13. Procédé de fabrication d'un papier support photographique enduit de résine, qui consiste à co-extruder sur le côté endroit d'un support de papier, un revêtement composite constitué par une première et une seconde couche, La première couche de revêtement étant constituée par 10 à 50 g.m<sup>-2</sup> d'un polyéthylène basse densité ou d'un mélange de polyéthylènes basse densité et haute densité contenant au moins 50% en poids de polyéthylène basse densité, et contenant au moins 5% en poids de pigment opacifiant, la seconde couche de revêtement, recouvrant la première couche de revêtement, étant constituée par 0,1 à 18 g.m<sup>-2</sup> d'un polymère présentant un module de rigidité d'au moins 2,0 GPa.

35 14. Procédé selon la revendication 13, dans lequel la seconde couche de revêtement est faite d'un polycarbonate.

40 15. Procédé selon l'une des revendications 13 ou 14, dans lequel le côté envers du papier support est revêtu par extrusion à l'aide d'un revêtement comprenant une couche de 10 à 50 g.m<sup>-2</sup> d'un polyéthylène basse densité ou d'un mélange de polyéthylènes basse densité et haute densité.

45 16. Procédé selon la revendication 15, dans lequel le revêtement sur le côté envers est appliqué par co-extrusion pour donner un revêtement composite d'une première et d'une seconde couche de revêtement de côté envers, la première couche de revêtement de côté envers étant la couche de 10 à 50 g.m<sup>-2</sup> de polyéthylène et la seconde couche de revêtement de côté envers, recouvrant la première couche de revêtement de côté envers et étant constituée par 3 à 10 g.m<sup>-2</sup> de polycarbonate.

50

55