

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 225 946 B1

(12)

EUROPEAN PATENT SPECIFICATION(45) Date of publication of patent specification: **06.03.91** (51) Int. Cl.⁵: **C11C 1/00, C11C 1/08**(21) Application number: **85308858.1**(22) Date of filing: **05.12.85**

The file contains technical information submitted
after the application was filed and not included in
this specification

(54) **Method of producing oleic acid.**(43) Date of publication of application:
24.06.87 Bulletin 87/26(45) Publication of the grant of the patent:
06.03.91 Bulletin 91/10(84) Designated Contracting States:
BE CH DE FR GB LI NL

(56) References cited:

CHEMICAL ABSTRACTS, vol. 67, 1967, page
11183, no. 118408a, Columbus, Ohio, US; H.
GRYNBERG et al.: "Obtaining pure oleic acid
by using urea derivatives and crystallization
of sodium soaps"

JOURNAL OF THE AMERICAN OIL CHEMISTS'
SOCIETY, vol. 37, June 1960, pages 300-302,
Champaign, Illinois, US; L.J. RUBIN et al.:
"Pure oleic acid from olive oil"

(73) Proprietor: **NIPPON OIL AND FATS COMPANY,
LIMITED**
10-1, Yuraku-cho 1-chome
Chiyoda-ku Tokyo(JP)

(72) Inventor: **Suzuki, Masao**
2-25-406, Kasaya-Cho
Nishinomiya City Hyogo Pref.(JP)
Inventor: **Hashimoto, Kenichi**
3-25 Sumiyoshihigashi-Machi 1-Chome
Higashinada-Ku
Kobe City Hyogo Pref.(JP)
Inventor: **Satoh, Tadashi**
6-2 Higashinaruo-Cho 1-Chome
Nishinomiya City Hyogo Pref(JP)

(74) Representative: **Sheader, Brian N. et al**
Eric Potter & Clarkson St. Mary's Court St.
Mary's Gate
Nottingham NG1 1LE(GB)

EP 0 225 946 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

This invention relates to a method of producing a highly purified oleic acid from an oleic acid containing fatty acid mixture.

5 Oleic acid (cis-9-octadecenoic acid) is a typical unsaturated fatty acid constituting natural fats and oils or biological lipids, which is a very important substance in industry and biology.

Lately, it has been confirmed that highly purified oleic acid is colorless and odorless, excellent in the stability, high in the safety and has many excellent physical, chemical and physiological properties. For this end, such an oleic acid is actively and widely applied to fine chemical fields such as life science of
10 pharmaceuticals, cosmetics and foods, bioscience of biosensors and biosurfactants, electronics aiming at simulation of biological function and so on as well as presently developing high technologies.

However, commercially available oleic acid includes fatty acid homologues having different carbon number and double bond number, and has a purity as low as 60-90%, and contains various minor impurities. Therefore, the commercially available oleic acid is insufficient in the qualities such as color, odor,
15 stability, safety and the like and can not sufficiently develop performances inherent to oleic acid.

As a method of increasing a purity of a fatty acid, there have generally been known various methods such as solvent separation, emulsification separation, urea separation and the like from old times. Recently, there are applied chromatographies using an adsorbent, an ion exchange resin and the like. However, these methods are unsuitable in view of separation and refining levels, production capacity, production cost and
20 the like as an industrial means for producing high purified fatty acids.

An article in JOURNAL OF THE AMERICAN OIL CHEMISTS SOCIETY, Vol. 37, June 1960, Pages 300-302, Champaign Illinois, USA, by L J RUBIN et al entitled "Pure oleic acid from olive oil" discloses a process in which the olive oil was first hydrolysed to produce a fatty acid mixture, the fatty acid mixture was mixed with urea in an organic solvent, allowed to cool to room temperature. the resulting crystals filtered off
25 and washed well with a saturated solution of urea in methanol and the methanol removed from the filtrate. The residue was taken up in water, acidified with dilute hydrochloric acid and extracted with hexane. After the hexane layer had been washed well with water it was dried over anhydrous sodium sulphate and the solvent removed in vacuo to give fatty acids. The fatty acids were then saponified with sodium hydroxide, allowed to crystallise overnight and then subjected to an acid decomposition with an excess of 5%
30 hydrochloric acid. The oily upper layer which formed was extracted with hexane, the hexane layer was washed with water, dried and evaporated in vacuo to yield oleic acid.

In Chemical Abstracts, Vol 67, 1967, page 11183, No. 118408a, the same method is described as in the Journal of the American Oil Chemist's Society.

Moreover, there is a method wherein the purity of oleic acid is increased by subjecting poly-unsaturated
35 fatty acid such as linoleic acid, linolenic acid or the like to a partial hydrogenation, but this method has a problem of producing positional and geometrical isomers.

As the demand of oleic acid is increased with the diversification of applications, it is required to provide oleic acid having high purity and high quality.

It is, therefore, an object of the invention to produce a highly purified oleic acid from wider starting
40 materials by a simple process without producing positional and geometrical isomers.

According to the invention, there is the provision of a method of producing oleic acid, comprising the steps of:

- (a) dissolving an oleic acid containing fatty acid mixture and urea in an organic solvent and cooling them to separate and remove the resulting precipitated crystal therefrom;
- 45 (b) partially saponifying the fatty acid mixture contained in the organic solvent solution to separate a crystal by crystallization and separating the resulting crystal from the organic solvent;
- (c) subjecting the resulting crystal to an acid decomposition; and
- (d) removing the acid used in the said decomposition by washing with water:

characterised in that urea remaining in the organic solvent solution after step (a) forms an adduct with
50 an acid salt of oleic acid in step (b) to produce crystal used in step (c).

According to the invention, the step (a) is a step for removing higher saturated fatty acids having a carbon number of not less than 16 and monounsaturated fatty acids higher than oleic acid from the oleic acid containing fatty acid mixture. At the step (a), a small amount of urea inevitably remains in the resulting organic solvent solution. When the organic solvent solution is subjected to the step (b), the remaining urea
55 moderately forms an adduct with an acid salt of oleic acid to produce a hard and light powdery crystal, so that the crystallized state of the partially saponified fatty acid mixture is improved to facilitate the filtration of crystal obtained by crystallization, whereby the removal of polyunsaturated fatty acids such as linoleic acid and so on, monounsaturated fatty acids lower than oleic acid, lower saturated fatty acids and other

impurities can be performed efficiently. Thus, it is possible to produce a highly purified oleic acid.

As the oleic acid containing fatty acid mixture, use may be made of any mixtures containing oleic acid, an example of which includes fatty acids and mixtures thereof obtained by hydrolysis of fats and oils such as olive oil, sesame oil, rice bran oil, soybean oil, teaseed oil, camellia oil, corn oil, rapeseed oil, palm oil, peanut oil, safflower oil, sunflower oil, tallow, lard, chicken oil, mutton tallow, fish oil and the like. Further, the commercially available oleic acid containing impurities may be used as the starting material. Since the significance of the starting material is dependent upon the separation effect of impurities according to the invention, the starting material having a higher oleic acid content is generally advantageous, but the selection of the starting material is determined by the objective purity and quality of oleic acid and the kind and amount of impurities in the starting material.

As the organic solvent used in the step (a), use may be made of lower alcohols such as methanol, ethanol, n-propanol, isopropanol and the like and a mixed solvent consisting mainly of such a lower alcohol. The amount of the organic solvent used can not absolutely be determined in accordance with the composition of the starting fatty acids, objective purity and yield, set of crystallization number and the like, but it is preferably 0.5-10 times the weight of the starting fatty acids. When the amount of the organic solvent is less than 0.5 times by weight, the separation effect lowers, while when it exceeds 10 times by weight, the concentration of fatty acid lowers and the production efficiency reduces unfavorably.

The amount of urea used is determined by the composition of the starting fatty acids, objective purity and yield, crystallization temperature, amount of solvent and the like. Preferably, the amount of urea used is 3-50 times the total weight of saturated fatty acids having a carbon number of not less than 16 and monounsaturated fatty acids higher than oleic acid, which are contained in the starting fatty acids. When the amount of urea is less than 3 times by weight, the removal of saturated fatty acids and higher monounsaturated fatty acids is insufficient, while when it exceeds 50 times by weight, the yield of oleic acid lowers.

In the step (a), urea and oleic acid containing fatty acid mixture are dissolved in the organic solvent by warming and then gradually cooled down to a temperature of not more than 30°C, preferably within a temperature range of 20°C--20°C. Thus, the saturated fatty acids having a carbon number of not less than 16 and the monounsaturated fatty acids higher than oleic acid form crystalline adduct with urea, so that the resulting crystals are removed by the usual manner such as filtration, centrifugal separation or the like.

Generally, it is sufficient to operate the step (a) one time. However, the operation of the step (a) may be repeated when the removal of the saturated fatty acids having a carbon number of not less than 16 and the monounsaturated fatty acids higher than oleic acid is insufficient.

In the step (b), the organic solvent solution of the fatty acid mixture obtaining at the step (a) is first subjected to a partial saponification by adding alkaline chemicals such as hydroxides, carbonates and so on of lithium, sodium, potassium, ammonia and the like. In this way, an acid salt of oleic acid is formed by the partial saponification, which moderately forms an adduct with a small amount of urea remaining in the step (a) after the cooling to make a filterable crystal as a whole, so that the separation from components such as polyunsaturated fatty acids and so on is easy. The degree of saponification is within a range of from 20% of oleic acid contained to 60% of the total of the fatty acid mixture, preferably from 30% of oleic acid to 55% of the total of the fatty acid mixture. When the degree of saponification is less than 20% of oleic acid, the yield of the resulting oleic acid is low, while when it exceeds 60% of the total of the fatty acid mixture, not only the separation effect lowers, but also the crystallized state and filtrability are poor to decrease the purity of the resulting oleic acid.

The cooling temperature for crystallizing the acid salt of oleic acid is 10°C--30°C, preferably 5°C--20°C. When the cooling temperature is higher than 10°C, the yield of oleic acid lowers, while when it is lower than -30°C, the purity of oleic acid reduces.

The resulting acid salt crystal of oleic acid is separated from the solution containing polyunsaturated fatty acid and so on in the usual manner.

Moreover, the purity can be further increased by repeatedly subjecting the acid salt crystal of oleic acid to recrystallization.

As a solvent used in the repeated recrystallization for the acid salt of oleic acid, mention may be made of polar solvents such as methanol, ethanol, isopropanol, n-butanol, isobutanol, acetone, methyl ethyl ketone, diethyl ether, ethyl acetate, acetonitrile and so on, and a mixed solvent containing such polar solvents. In this case, the amount of the solvent used is preferably 1-10 times the weight of the acid salt of oleic acid.

The step (c) is a step wherein the acid salt of oleic acid is subjected to an acid decomposition by adding an acid to produce free oleic acid.

As the acid used in the acid decomposition, mention may be made of inorganic acids such as sulfuric

acid, hydrochloric acid, nitric acid, phosphoric acid, phosphorous acid, hypophosphorous acid, carbonic acid, boric acid and so on; and organic acids such as acetic acid, oxalic acid, malonic acid, succinic acid, malic acid, tartaric acid, citric acid and so on. The amount of the acid used is not less than an equivalent, preferably not less than 1.2 equivalents to the base forming the acid salt of oleic acid.

5 After the acid decomposition, the acid for the acid decomposition remaining in oleic acid is removed by washing with water. In this washing, the emulsification can be prevented by adding a diluted aqueous solution of a polybasic acid such as oxalic acid, citric acid or the like, whereby the acid decomposition for the slight amount of the remaining acid salt of oleic acid is performed completely.

Thus, the high purity oleic acid is obtained. Moreover, in order to remove minor impurities, the resulting
10 oleic acid may be subjected to an adsorbent treatment or distillation usually used in the refining of fatty acids.

As an adsorbent used in the adsorbent treatment, mention may be made of clay, activated clay, activated carbon, silica gel, alumina gel, silica-alumina gel, ion exchange resin, synthetic adsorbent and so on, which may be used alone or in admixture. The amount of the adsorbent used is dependent upon the
15 refining degree of oleic acid and the objective quality, but it is 0.1-5% by weight to oleic acid. In the adsorbent treatment, the temperature is not less than the melting point of oleic acid, preferably 30-80 °C, and the treating time is about 20 minutes to 2 hours.

On the other hand, the distillation is performed under a reduced pressure in an inert gas atmosphere in the usual manner. In this case, it is desirable to perform a low temperature distillation under a higher
20 vacuum.

According to the method of the invention, a highly purified oleic acid having a high level of qualities such as stability to oxidation, heat and acidic and basic chemicals, safety to cutaneous health and so on, which have never been attained in the prior art, can be obtained from wide starting materials by a simple process.

25 The thus obtained highly purified oleic acid has the following characteristics:

- (i) it is colorless and odorless with a high purity;
- (ii) it does not contain minor impurities such as oxidation products and the like resulting in the degradation of oleic acid;
- (iii) it is excellent in the stability to heat, oxidation and chemicals;
- 30 (iv) it is high in the safety to cutaneous health; and
- (v) it has special properties such as sharp polymorphism and the like.

By utilizing the above mentioned characteristics, oleic acid obtained according to the method of the invention can widely be employed in the fine chemical fields such as pharmaceuticals, cosmetics, biochemicals, electronics and so on as well as presently developing high technologies.

35 The following examples are given in illustration of the invention and are not intended as the limitations thereof. In examples, "%" means "% by weight" unless otherwise specified.

Example 1

40 After 1,242 g of urea was added and dissolved into 4,000 g of methanol under warming at 50 °C, 1,000 g of oleic sufflower oil distilled fatty acid warmed at 50 °C was added and dissolved therein. Next, the resulting solution was cooled from 50 °C to 10 °C with stirring over 4 hours, and the resulting precipitated crystal was centrifugally filtered off to obtain 5,212 g of a filtrate (content of fatty acids: 625 g, acid value:
45 198.5, content of urea: 232 g). This filtrate was added with 576 g of an aqueous solution containing 41.5 g of sodium hydroxide (corresponding to 45% of the equivalent of the contained fatty acid) at 40 °C and cooled to -7 °C with stirring over 6 hours to obtain 427 g of a crystal of acid salt of oleic acid (content of acid salt: 370 g) through filtration. The thus obtained crystal was added with 1,856 g of an aqueous solution containing 93 g of phosphoric acid (corresponding to 1.5 times the equivalent of the acid salt) which was
50 subjected to an acid decomposition with stirring at 90 °C for 2 hours. The thus obtained oleic acid layer was fully washed with an aqueous solution of 0.5% citric acid and dehydrated to obtain 356 g of a highly purified oleic acid (A).

Example 2

427 g of the acid salt crystal of oleic acid obtained in the same manner as in Example 1 was dissolved into 1,280 g of methanol containing 10% of water under warming at 40 °C and then cooled to -5 °C with

stirring over 5 hours to obtain 357 g of a crystal through filtration. This crystal was added with 1,690 g of an aqueous solution of 5% phosphoric acid, which was subjected to an acid decomposition with stirring at 90 ° C for 2 hours. The resulting oleic acid layer was fully washed with an aqueous solution of 0.5% citric acid and dehydrated to obtain 324 g of a highly purified oleic acid (B).

5

Example 3

The acid salt crystal of oleic acid obtained through recrystallization in the same manner as in Example 2 was dissolved into 1,071 g of methanol containing 13% of water under warming at 40 ° C and then cooled to -5 ° C with stirring over 5 hours to obtain 317 g of a crystal through filtration. This crystal was added with 1,574 g of an aqueous solution of 5% phosphoric acid, which was subjected to an acid decomposition with stirring at 90 ° C for 2 hours. The resulting oleic acid layer was fully washed with an aqueous solution of 0.5% citric acid and dehydrated to obtain 302 g of a highly purified oleic acid (c).

15

Example 4

Each of the highly purified oleic acids of Examples 1-3 was added with 0.5% of activated carbon, stirred at 50 ° C under nitrogen gas atmosphere for 1 hour and filtered to obtain each of more highly purified oleic acids (A1), (B1), and (C1).

20

Example 5

25

Each of the highly purified oleic acids of Examples 1-3 was distilled below 220 ° C at 1 mmHg while blowing a nitrogen gas to obtain each of more highly purified oleic acids (A2), (B2) and (C2).

The compositions and quality characteristics of the highly purified oleic acids obtained in Examples 1-5 according to the invention are shown in the following Table 1 together with those of commercially available oleic acids (a) and (b) as Comparative Examples.

30

35

40

45

50

55

Table 1(a)

Test item		Present invention										Comparative example		
		Oleic saf- flower oil distilled fatty acids	Fatty acids in filtrate after urea separation	Example 1	Example 2	Example 3	Example 4			Example 5			Commer- cially avail- able oleic acid (a)	Commer- cially avail- able oleic acid (b)
				(A)	(B)	(C)	(A1)	(B1)	(C1)	(A2)	(B2)	(C2)		
1 Composition of fatty acids (%)	C _{14:0}	0.1	0.2										3.1	2.6
	C _{16:0}	4.8	0.2										4.3	3.6
	C _{16:1}	0.1	0.2										7.8	6.4
	C _{18:0}	2.3											1.4	1.1
	C _{18:1 cis-w9}	77.1	78.4	99.2	99.9	more than 99.9	99.2	99.9	more than 99.9	99.2	99.9	more than 99.9	68.0	71.1
	C _{18:1 (isomer)}													
	C _{18:2}	14.2	19.8	0.8	0.1		0.8	0.1		0.8	0.1		5.5	0.8
	C _{18:3}	0.9	1.2										0.6	
	C _{20:0}	0.5											0.1	
others												3.5	3.8	

Table 1(b)

Test item	Present invention												Comparative example	
	Oleic saf- flower oil distilled fatty acids	Fatty acids in filtrate after urea separa- tion	Example 1	Example 2	Example 3	Example 4			Example 5			Commer- cially avail- able oleic acid (a)	Commer- cially avail- able oleic acid (b)	
			(A)	(B)	(C)	(A1)	(B1)	(C1)	(A2)	(B2)	(C2)			
2 Carbonyl value (meq/kg)	5.2		0.4	0.2	0.1	0.2	0.1	0	0	0.2	0	0	15.6	9.2
3 Odor intensity	7		1-2	1	0-1	0-1	0	0	0	0-1	0	0	10	8
4 Original color (APHA)	80		20	15	10	5	5	5	5	5	5	0	220	120
5 Heat color stability (APHA)	180		60	40	30	15	10	5	5	10	5	5	400	280
6 Thermal oxida- tion color stability (APHA)	350		80	60	50	40	30	25	40	25	15	15	>500	>500
7 Base color stability (APHA)	400		90	70	50	60	40	30	50	30	20	20	>500	>500
8 Acid color stability (APHA)	450		120	90	70	80	60	50	60	40	30	30	>500	>500
9 Oxidation stability (POV)	22.5		0.1	0	0	0	0	0	0	0	0	0	26.8	6.2
10 Skin irritation	positive		almost nega- tive	almost nega- tive	almost nega- tive	nega- tive	nega- tive	nega- tive	nega- tive	nega- tive	nega- tive	nega- tive	posi- tive	almost posi- tive

The test item 1 shows the composition of fatty acid mixture measured by a gas chromatography using a capillary column. Oleic acid is represented by $C_{18:1 \text{ cis-}\omega 9}$.

The test item 2 shows a content (milli equivalent/kg) of carbonyl compounds as typical minor impurities.

5 The test item 3 gives an odor index evaluated by an organoleptic test, wherein odorless is 0 and the odor intensity of the commercially available oleic acid (a) is 10, respectively.

In the test items 4 to 8, the larger the value of color, the larger the coloration degree and the poorer the quality.

10 The test item 5 shows a heat color stability of oleic acid after heated at 205°C in a nitrogen stream for 1 hour.

The test item 6 shows a thermal oxidation color stability of oleic acid after heated at 150°C in air for 3 hours.

15 The test item 7 shows a color stability of oleic acid against basic chemicals after oleic acid is added with an equimolar amount of diethanolamine and heated at 150°C for 2 hours while being stirred with nitrogen gas.

The test item 8 shows a color stability of oleic acid against acidic chemicals after oleic acid is added with 0.05% of paratoluenesulfonic acid and heated at 150°C for 1 hour while being stirred with nitrogen gas.

20 The test item 9 shows a peroxide value (milli equivalent/kg) after oleic acid is heated at 60°C for 5 hours while being stirred through aeration (300 ml/min). The larger the value, the poorer the oxidation stability.

The test item 10 shows a result of skin irritation test according to Kawai's method [The journal of Dermatology, vol 2, p 19 (1975)], wherein negative is no irritation, almost negative is weak irritation, almost positive is middle irritation and positive is strong irritation. This indicates the safety to cutaneous health.

25

Example 6

30 After 1,640 g of urea was added and dissolved into 5,000 g of methanol under warming at 60°C , 1,000 g of teaseed oil fatty acids warmed at 60°C was added and dissolved thereinto. Next, the resulting solution was cooled from 60°C to 8°C with stirring over 4 hours, and the resulting precipitated crystal was filtered off to obtain 6,196 g of a filtrate (content of fatty acid: 512 g, acid value: 192.2, and content of urea: 225 g). This filtrate was added with 703 g of an aqueous solution containing 35.1 g of sodium hydroxide (corresponding to 50% of the equivalent of the contained fatty acid) at 40°C and then cooled to -10°C with

35 stirring over 6 hours to obtain 418 g of crystals of the acid salt of oleic acid (content of acid salt: 361 g) through filtration. This crystal was added with 1,535 g of an aqueous solution of 3% hydrochloric acid, which was subjected to an acid decomposition with stirring at 90°C for 2 hours. The resulting oleic acid layer was fully washed with an aqueous solution of 0.5% malic acid and dehydrated to obtain 347 g of a highly purified oleic acid (D).

40

Example 7

45 The acid salt crystal of oleic acid obtained in the same manner as in Example 6 was dissolved into 1,254 g of methanol containing 12% of water under warming at 40°C and then cooled to -5°C with stirring over 5 hours to obtain 350 g of a crystal through filtration. This crystal was added with 1,230 of an aqueous solution of 3% hydrochloric acid, which was subjected to an acid decomposition with stirring at 90°C for 2 hours. The resulting oleic acid layer was fully washed with an aqueous solution of 0.5% malic acid and dehydrated to obtain 308 g of a highly purified oleic acid (E).

50

Example 8

55 Each of the highly purified oleic acids of Examples 6 and 7 was added with 3% of silica gel, stirred at 40°C under nitrogen gas atmosphere for 1 hour and filtered to obtain each of more highly purified oleic acids (D1) and (E1).

Example 9

Each of the highly purified oleic acids of Examples 6 and 7 was distilled in the same manner as in Example 5 to obtain each of more highly purified oleic acids (D2) and (E2).

The compositions and quality characteristics of the highly purified oleic acids obtained in Examples 6-9 according to the present invention are shown in the following Table 2.

Table 2(a)

Test item		Present invention							
		Teaseed oil fatty acid	Fatty acids in filtrate after urea separation	Example 6	Example 7	Example 8		Example 9	
				(D)	(E)	(D1)	(E1)	(D2)	(E2)
Composition of fatty acids (%)	C _{16:0}	8.5	0.3	0.1			0.1		
	C _{16:1}	0.1	0.2						
	C _{18:0}	2.6							
	C _{18:1 cis-w₉}	81.7	86.9	98.9	99.6	99.0	99.6	99.3	99.9
	C _{18:2}	6.5	11.6	1.0	0.4	0.9	0.4	0.7	0.1
	C _{18:3}	0.5	0.9						
	C _{20:0}	0.1							
	C _{20:1}	0.1							

Table 2(b)

Test item	Present invention							
	Teaseed oil fatty acid	Fatty acids in filtrate after urea separation	Example 6	Example 7	Example 8		Example 9	
			(D)	(E)	(D1)	(E1)	(D2)	(E2)
2 Carbonyl value (meq/kg)	10.3		0.9	0.4	0.7	0.3	0.2	0.1
3 Odor intensity	8		2	1	1	0-1	0	0
4 Original color (APHA)	400		40	20	15	10	10	5
5 Heat color stability (APHA)	>500		100	70	50	30	20	5
6 Thermal oxida- tion color stability (APHA)	>500		120	90	90	60	60	30
7 Base color stability (APHA)	>500		140	100	110	80	70	40
8 Acid color stability (APHA)	>500		180	120	140	90	90	60
9 Oxidation stability (POV)	16.7		0.2	0	0.1	0	0	0

Example 10

After 1,060 g of urea was added and dissolved into 3,000 g of methanol under warming at 60 °C, 1,000

g of olive oil fatty acids warmed at 60 °C was added and dissolved therein. Then, the resulting solution was cooled from 60 °C to 15 °C with stirring over 4 hours, and the resulting precipitated crystal was filtered off. The thus obtained filtrate was added and dissolved into 750 g of urea at 50 °C, and then cooled to 10 °C with stirring, and the resulting precipitated crystal was again filtered off to obtain 3,488 g of a filtrate
 5 (content of fatty acid: 447 g, acid value: 192.8 g, content of urea: 158 g). This filtrate was added with 372 g of an aqueous solution containing 38.8 g of potassium hydroxide (corresponding to 45% of the equivalent of the contained fatty acid) at 40 °C and then cooled to -10 °C with stirring over 6 hours to obtain 342 g of a crystal of the acid salt of oleic acid (content of acid salt: 289 g) through filtration. This crystal was added with 1,894 g of an aqueous solution of 10% citric acid, which was subjected to an acid decomposition with
 10 stirring at 90 °C for 2 hours. The resulting oleic acid layer was fully washed with an aqueous solution of 0.5% tartaric acid and dehydrated to obtain 278 g of a highly purified oleic acid (F).

Example 11

15 The acid salt crystal of oleic acid obtained in the same manner as in Example 10 was dissolved into 1,026 g of acetone containing 8% of water under warming at 50 °C and then cooled to -2 °C with stirring over 5 hours to obtain 276 g of a crystal through filtration. This crystal was added with 1,716 g of an aqueous solution of 10% citric acid, which was subjected to an acid decomposition with stirring at 90 °C for
 20 2 hours. The resulting oleic acid layer was well washed with an aqueous solution of 0.5% tartaric acid and dehydrated to obtain 252 g of a highly purified oleic acid (G).

Example 12

25 Each of the highly purified oleic acids obtained in Examples 10 and 11 was added with 2% of activated clay, stirred at 40 °C under nitrogen gas atmosphere for 30 minutes, and filtered to obtain each of more highly purified oleic acids (F1) and (G1).

Example 13

30 Each of the highly purified oleic acids obtained in Examples 10 and 11 was distilled in the same manner as in Example 5 to obtain each of more highly purified oleic acids (F2) and (G2).

35 The compositions and quality characteristics of the highly purified oleic acids obtained in Examples 10-13 are shown in the following Table 3.

40

45

50

55

Table 3(a)

Test item		Present invention									
		Olive oil fatty acids	Fatty acids in filtrate after two times of urea separation	Example 10		Example 11		Example 12		Example 13	
				(F)	(G)	(F1)	(G1)	(F2)	(G2)		
1 Composition of fatty acids (%)	C _{16:0}	10.4	0.4	0.1			0.1				
	C _{16:1}	0.7	1.4								
	C _{18:0}	3.1									
	C _{18:1 cis-w9}	77.2	81.4	98.7	99.5	98.7	99.5	99.1	99.8		
	C _{18:2}	7.4	14.9	1.2	0.5	1.2	0.5	0.9	0.2		
	C _{18:3}	0.9	1.8								
	C _{20:0}	0.3									

Table 3(b)

Test item	Present invention						
	Olive oil fatty acids	Fatty acids in filtrate after two times of urea separation	Example 10 (F)	Example 11 (G)	Example 12		Example 13
					(F1)	(G1)	(F2) (G2)
2 Carbonyl value (meq/kg)	7.2		0.8	0.4	0.7	0.3	0.1 0
3 Odor intensity	6		1-2	1	1	0-1	0 0
4 Original color (APHA)	350		40	20	10	5	10 5
5 Heat color stability (APHA)	>500		110	80	40	15	20 5
6 Thermal oxidation color stability (APHA)	>500		120	90	80	60	50 30
7 Base color stability (APHA)	>500		140	110	110	80	70 50
8 Acid color stability (APHA)	>500		170	120	120	90	80 60
9 Oxidation stability (POV)	17.2		0.2	0	0.2	0	0 0

As apparent from the above results, fatty acids other than oleic acid and minor impurities contained in the starting fatty acid mixture can almost completely be removed according to the invention. Further, the highly purified oleic acid according to the invention has a purity of approximately 100%, so that it is colorless and odorless and considerably excellent in the stability to heat, oxidation and chemicals and the safety to cutaneous health.

10 Claims

1. A method of producing oleic acid, comprising the steps of:
 - (a) dissolving an oleic acid containing fatty acid mixture and urea in an organic solvent and then cooling them to separate and remove the resulting precipitated crystal therefrom:
 - 15 (b) partially saponifying the fatty acid mixture contained in the organic solvent solution to separate a crystal by crystallization and separating the resulting crystal from the organic solvent:
 - (c) subjecting the resulting crystal to an acid decomposition; and
 - (d) removing the acid used in the acid decomposition by washing with water:
 characterised in that urea remaining in the organic solvent solution after step (a) forms an adduct with
 - 20 an acid salt of oleic acid in step (b) to produce the crystal used in step (c).
2. The method according to claim 1, wherein said fatty acid mixture in the step (a) is selected from hydrolyzates of fats and oils and commercially available oleic acid.
- 25 3. The method according to claim 1, wherein said urea in the step (a) is used in an amount of 3-50 times the total weight of saturated fatty acids having a carbon number of not less than 16 and monounsaturated fatty acids higher than oleic acid, which are contained in said fatty acid mixture.
4. The method according to claim 1, wherein said organic solvent in the step (a) is used in an amount of
 - 30 0.5-10 times the weight of said fatty acid mixture.
5. The method according to claim 1, wherein said cooling in the step (a) is carried out by cooling down to temperature of not more than 30° C.
- 35 6. The method according to claim 1, wherein said partial saponification in the step (b) is carried out by adding alkaline chemicals.
7. The method according to claim 1, wherein the degree of saponification in the step (b) is within a range of from 20% of oleic acid to 60% of the total of the fatty acid mixture contained in said organic solvent
 - 40 solution.
8. The method according to claim 6, wherein said alkaline chemicals are selected from hydroxides and carbonates of lithium, sodium, potassium and ammonia.
- 45 9. The method according to claim 1, wherein said crystallization of the step (b) is performed repeatedly.
10. The method according to claim 9, wherein said crystallization is carried out in the presence of a polar solvent or a mixed solvent thereof.
- 50 11. The method according to claim 1, wherein said step (c) is carried out with a inorganic or organic acid.
12. The method according to claim 11, wherein said inorganic acid is selected from sulfuric acid, hydrochloric acid, nitric acid, phosphoric acid, phosphorous acid, hypophosphorous acid, carbonic acid and boric acid.
- 55 13. The method according to claim 11, wherein said organic acid is selected from acetic acid, oxalic acid, malonic acid, succinic acid, malic acid, tartaric acid and citric acid.

14. The method according to claim 1, wherein after said step (c), the resulting oleic acid is subjected to an adsorbent treatment or a distillation.

5 Revendications

1. Procédé de production d'acide oléique, comportant les étapes consistant à :
 - (a) dissoudre un mélange d'acides gras contenant de l'acide oléique et de l'urée dans un solvant organique et le refroidir pour en séparer et en extraire les cristaux précipités qui en résultent;
 - 10 (b) saponifier partiellement le mélange d'acides gras contenu dans la solution de solvant organique pour séparer des cristaux par cristallisation et séparer les cristaux résultants d'avec le solvant organique;
 - (c) soumettre les cristaux résultants à une décomposition par un acide; et
 - (d) enlever l'acide utilisé dans ladite décomposition par lavage à l'eau;
 - 15 caractérisé par le fait que l'urée subsistant dans la solution du solvant organique après l'étape (a) forme un produit d'addition avec un sel acide de l'acide oléique dans l'étape (b) pour produire les cristaux utilisés dans l'étape (c).
2. Procédé selon la revendication 1, dans lequel on choisit ledit mélange d'acides gras dans l'étape (a)

20 parmi les hydrolysats de graisses et d'huiles et parmi les acides oléiques du commerce.
3. Procédé selon la revendication 1, dans lequel on utilise ladite urée dans l'étape (a) dans une proportion de 3-50 fois le poids total d'acide gras saturés présentant un nombre de carbones non inférieur à 16 et d'acides gras monoinsaturés d'ordre supérieur à l'acide oléique, qui sont contenus dans ledit mélange

25 d'acides gras.
4. Procédé selon la revendication 1, dans lequel on utilise ledit solvant organique dans l'étape (a) dans une proportion de 0,5-10 fois le poids dudit mélange d'acides gras.
- 30 5. Procédé selon la revendication 1, dans lequel ledit refroidissement dans l'étape (a) s'effectue en refroidissant à une température non supérieure à 30 ° C.
6. Procédé selon la revendication 1, dans lequel ladite saponification partielle dans l'étape (b) s'effectue en ajoutant des produits chimiques alcalins.
- 35 7. Procédé selon la revendication 1, dans lequel le degré de saponification dans l'étape (b) est sur la plage allant de 20% de l'acide oléique à 60% du total du mélange d'acides gras contenu dans ladite solution de solvant organique.
- 40 8. Procédé selon la revendication 6, dans lequel on choisit lesdits produits chimiques alcalins parmi les hydroxydes et les carbonates de lithium, de sodium, de potassium et d'ammonium.
9. Procédé selon la revendication 1, dans lequel ladite cristallisation de l'étape (b) s'effectue de façon répétitive.
- 45 10. Procédé selon la revendication 9, dans lequel ladite cristallisation s'effectue en présence d'un solvant polaire ou d'un mélange de tels solvants.
11. Procédé selon la revendication 1, dans lequel ladite étape (c) s'effectue avec un acide inorganique ou

50 organique.
12. Procédé selon la revendication 11, dans lequel on choisit ledit acide inorganique parmi l'acide sulfurique, l'acide chlorhydrique, l'acide nitrique, l'acide phosphorique, l'acide phosphoreux, l'acide hypophosphoreux, l'acide carbonique et l'acide borique.
- 55 13. Procédé selon la revendication 11, dans lequel on choisit ledit acide organique parmi l'acide acétique, l'acide oxalique, l'acide malonique, l'acide succinique, l'acide malique, l'acide tartrique et l'acide citrique.

14. Procédé selon la revendication 1, dans lequel, après ladite étape (c), l'acide oléique résultant est soumis à un traitement par adsorbant ou à une distillation.

5 Ansprüche

1. verfahren zur Herstellung von Oleinsäure, welches die folgenden Schritte umfaßt:
 - (a) Lösen einer Fettsäurenmischung, die Oleinsäure enthält, und Harnstoff in einem organischen Lösungsmittel und anschließendes Abkühlen der Lösung, um die ausgefallten Kristallite zu separieren und entfernen;
 - (b) teilweises Verseifen der Fettsäurenmischung, die in dem organischen Lösungsmittel gelöst ist, um einen Kristall durch Kristallisation zu separieren, und Trennung des gewonnenen Kristalls von dem organischen Lösungsmittel;
 - (c) Säureaustausch bei dem gewonnenen Kristall; und
 - (d) Entfernen der zum Säureaustausch verwendeten Säure durch Waschen mit Wasser; dadurch gekennzeichnet, daß Harnstoff, der in dem organischen Lösungsmittel nach dem Schritt (a) gelöst bleibt, im Schritt (b) mit einem sauren Salz der Oleinsäure eine Verbindung eingeht, die den Kristall bildet, der in Schritt (c) weiterbehandelt wird.
2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß im Schritt (a) als Fettsäurenmischung Hydrolysate von Fetten und Ölen oder käufliche Oleinsäure verwendet werden.
3. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß im Schritt (a) der Harnstoff in einer Menge eingesetzt wird, die das 3- bis 50fache der Gesamtmasse beträgt, die die gesättigten Fettsäuren mit einer Anzahl von Kohlenstoffatomen nicht kleiner als 16 und die einfach ungesättigten Fettsäuren höherer Ordnung als die Oleinsäure zusammen ausmachen.
4. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß im Schritt (a) das organische Lösungsmittel in einer Menge eingesetzt wird, die das 0,5- bis 10fache der Masse der Fettsäurenmischung beträgt.
5. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß im Schritt (a) das Abkühlen bis zu einer Temperatur erfolgt, die nicht höher als 30 °C ist.
6. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß im Schritt (b) die teilweise Verseifung durch Zugabe von alkalischen Chemikalien durchgeführt wird.
7. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß im Schritt (b) der Grad der Verseifung in einem Bereich zwischen 20 und 60 % liegt, wobei 20% der Grad der Verseifung der Oleinsäure und 60% der Grad der Verseifung der gesamten Fettsäurenmischung, die in dem organischen Lösungsmittel gelöst ist, ist.
8. Verfahren nach Anspruch 6, dadurch gekennzeichnet, daß als alkalische Chemikalien Hydroxide oder Carbonate von Lithium, Natrium, Kalium oder Ammoniak verwendet werden.
9. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß die Kristallisation von Schritt (b) wiederholt durchgeführt wird.
10. Verfahren nach Anspruch 9, dadurch gekennzeichnet, daß die Kristallisation in Anwesenheit eines polaren Lösungsmittels oder einer polaren Lösungsmittelmischung durchgeführt wird.
11. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß der Schritt (c) mit einer anorganischen oder organischen Säure durchgeführt wird.
12. Verfahren nach Anspruch 11, dadurch gekennzeichnet, daß als anorganische Säure Schwefelsäure, Salzsäure, Salpetersäure, Phosphorsäure, phosphorige Säure, Phosphorwasserstoffsäure, Kohlensäure oder Borsäure verwendet wird.
13. Verfahren nach Anspruch 11, dadurch gekennzeichnet, daß als organische Säure Essigsäure, Oxalsäu-

re, Malonsäure, Bernsteinsäure, Apfelsäure, Weinsäure oder Zitronensäure verwendet wird.

14. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß nach dem Schritt (c) die gewonnene Oleinsäure einer Absorptionsbehandlung oder einer Destillation unterzogen wird.

5

10

15

20

25

30

35

40

45

50

55