



**NEW EUROPEAN PATENT SPECIFICATION**

Date of publication of the new patent specification : **06.04.94 Bulletin 94/14**

Int. Cl.<sup>5</sup> : **A61C 5/10, A61C 13/08**

Application number : **87902829.8**

Date of filing : **15.04.87**

International application number :  
**PCT/SE87/00194**

International publication number :  
**WO 87/06451 05.11.87 Gazette 87/24**

**ARRANGEMENT FOR THE PRODUCTION OF INSERT BODIES FOR THE ARTIFICIAL REBUILDING OF TEETH AND HUMAN LIMBS, ETC.**

Priority : **23.04.86 SE 8601870**

Date of publication of application :  
**18.05.88 Bulletin 88/20**

Publication of the grant of the patent :  
**12.06.91 Bulletin 91/24**

Mention of the opposition decision :  
**06.04.94 Bulletin 94/14**

Designated Contracting States :  
**AT BE CH DE FR GB IT LI LU NL SE**

References cited :  
**EP-A- 7 462**  
**DE-A- 2 328 295**  
**DE-A- 2 947 684**  
**DE-A- 3 444 034**  
**DE-C- 2 818 967**  
**SE-B- 448 598**  
**Werkzeugmaschinen, Teubner Verlagsanstalt, Leipzig 1948, page 275**

References cited :  
**Bo Bergman et al., "A two year follow up study of Titanium crowns, Acta Odontol, Scand. 48 (1990), pages 113-117**  
**Matts Anderson et al., "Clinical results with Titanium crown fabricates with machine duplication and spark erosion", Acta Odontol, Scand.,47 (1989), pages 279-286**

Proprietor : **Nobelpharma AB**  
**Box 5190**  
**S-402 26 Göteborg (SE)**

Inventor : **GUSTAVSSON, Axel, Gerhard, Värne**  
**Gullebovägen 1**  
**S-691 44 Karlskoga (SE)**  
Inventor : **ANDERSSON, Knut, Matts, Greger**  
**Fack 45**  
**S-830 22 Faker (SE)**  
Inventor : **ANDERSSON, Karl, Elis, Morgan**  
**Koug stagarden**  
**S-830 30 Lit (SE)**

Representative : **Olsson, Gunnar**  
**Nobelpharma AB Box 5190**  
**S-402 26 Gothenburg (SE)**

**EP 0 267 227 B2**

## Description

### TECHNICAL FIELD

The present invention relates to an arrangement as defined in the first part of claim 1. Such a device is disclosed in DE-A-3444034

### BACKGROUND

The production of metal supporting bodies for dental crowns and similar has until now taken place as a general rule on a purely manual basis by skilled craftsmen. The dentist has used previously disclosed techniques to produce a desired cast impression of the residue(s) of the tooth concerned, whereupon a dental technician has used the cast impression to complete the production process by mechanical means. This previously disclosed procedure was possible provided that castable materials, such as gold, were used for the aforementioned metal supporting bodies, for example.

The desire to be able to use other materials or alloys in the production of bodies of the kind in question exists for a variety of reasons. It can be mentioned by way of example that there is a wish to be able to produce metal supporting bodies for dental crowns and supporting bodies for limbs, etc., in titanium and other hard materials or alloys.

### DESCRIPTION OF THE PRESENT INVENTION

#### TECHNICAL PROBLEM

The production of insert bodies in hard materials is costly to execute due to the fact that each insert body has its own characteristic shape which must be capable of being reproduced with comparatively high accuracy.

It is also difficult to find a solution to the problem of the efficient production of insert bodies with individual shapes at the same time as the production operation is subject to pricing pressures.

#### THE SOLUTION

The present invention has as its object amongst other things to propose an arrangement for the efficient production of bodies of the kind referred to above. The invention is specified in claim 1.

The first and second pairs of elements are arranged preferably in such a way that the longitudinal axes of the third and fourth elements face in the direction of the axes of rotation of the first and second elements at obtuse angles, which may preferably be of the order of 135°. In this case the longitudinally displaceable component part of the sensing device and/or its means of support should preferably be im-

parted with friction-reducing rotation.

A piston/piston rod connected to the aforementioned hydraulic piston or fluid piston can constitute an attachment point for a bearing component which supports the fourth element.

The novel arrangement can be used for the production of the graphite electrode for an electro-erosion apparatus which is used to produce a cavity inside a metal body of the kind in question. The wall of the cavity in this case can be of essentially the same shape as the outside of the metal body, resulting in a hollow, thin-walled and three-dimensional metal body.

The arrangement is also applicable in conjunction with the reduction of the base of the body in accordance with an outline marked by the dentist. The replica is made of or coated with an electrically conducting material to one side of the marked outline, whereas an electrically non-conducting material or coating is used to the other side of the marked outline. The aforementioned sensing device is thus able to function as an electrical reducing device which, with the help of actuating devices, guides the first and second pairs of elements towards and away from one another depending on whether the reducing device is sensing one side or the other of the marked outline.

### ADVANTAGES

It is possible, through what is proposed here, to achieve the accurate production of three-dimensional bodies with individual characteristic features. Efficient production can take place in large quantities and in series with extremely good reproducibility and accuracy.

The arrangement permits considerable freedom of choice with regard to materials, and by the appropriate choice of material the body can be subjected to the necessary accurate control procedures with regard to its dimensions. In the particular case of three-dimensional bodies intended for use inside the mouth, it is possible for production to take place using a material, such as titanium, which is resistant to corrosion by the fluids in the mouth and has no adverse biological effect on the tissues.

The use of the novel arrangement is particularly advantageous in those cases in which the metal bodies are to be provided with cavities. The cavity can be produced by a previously disclosed method by the use of electro-erosion apparatus with an appropriate electrode, for example made of graphite. This electrode (the tool) is given an external form which corresponds to the external form of the body with its individual characteristic features. The electrode is manufactured with dimensions which correspond to the external dimensions of the tooth residue. The metal body in question is given the same external form as the external form of the electrode, although it is made

slightly larger in order to permit a wall to be produced in the body. The arrangement permits extremely thin-walled bodies to be produced, which in this case is intended to denote wall thicknesses of, for example, 0.6-0.7 mm. The wall thickness may vary within a wide range, however.

According to the above description, the arrangement also permits the body to be cut off along a marked outline. This is of very great significance in those cases which involve the production of hollow bodies for use as supports in dental crowns. The interface between the support and the tooth residue is critical in this case and calls for a precisely shaped and extremely thin (sharp) edge.

### DESCRIPTION OF THE DRAWINGS

A preferred embodiment of a method and an arrangement which exhibit the significant characteristic features of the invention is described below with reference to the accompanying drawing, in which :

Fig. 1 shows in perspective view the most important component parts of the arrangement for the invention;

Fig. 2 shows in longitudinal section the function of a longitudinally displaceable component part contained in the arrangement according to Fig. 1; and

Fig. 3 shows in the form of a basic diagram the manner in which the arrangement is used for the purpose of shaping the lower edge of a three-dimensional body.

### BEST MODE OF CARRYING OUT THE INVENTION

A first pair of elements is represented in Fig. 1 by a first element 1 and a second element 2. The aforementioned elements 1, 2 are so arranged as to be capable of rotating about their respective axes of rotation 3 and 4. Their rotation is achieved with the help of a motor, for example a hydraulic motor, which is provided on its drive shaft 6 with a toothed driving wheel 7. The elements 1 and 2 are provided with bearing shafts 8 and 9 by means of which the elements are supported in a bearing housing 10 in a previously disclosed fashion, for example on ball bearings. The bearing shafts are provided with toothed wheels 11 and 12 which are in engagement with the driving wheel 7 of the motor 5, which driving wheel thus causes the elements 1 and 2 to rotate in the same direction 13 and 14. The toothed wheels are also arranged in such a way that the elements 1 and 2 rotate in synchronism.

The elements 1 and 2 are provided with clamping devices (chucks) 15 and 16 to enable holders 17 and 18 to be secured to the elements. The aforementioned holders are intended to secure supporting devices

19 and 20 for a three-dimensional body 21, the external contour of which is to be reproduced, and a blank 22 from which the three-dimensional body is to be made in, for example, titanium or a metal alloy, etc. The three-dimensional body (= the replica) and the blank are attached to their supporting devices 19 and 20 with the help of an adhesive and/or jointing devices, etc., and the supporting devices are retained in the holding devices by a previously disclosed clamping principle. The housing 10 is mounted on guides 23 and 24 so that the elements 1 and 2 are capable of longitudinal displacement along their axes of rotation 3 and 4 in directions indicated by the arrows 25. The longitudinal displacement is achieved with the help of a longitudinal displacement device 26, for example a hydraulic cylinder, the piston 27 of which is attached to the housing 10. The rate of longitudinal displacement is adapted to suit the particular manufacturing operation.

A second pair of elements contains a third element 28 and a fourth element 29. The third element 28 is securely arranged in the frame of the arrangement, which is symbolized by the designation 30 but is not specifically illustrated. The expression 'third element' shall be understood in its widest sense in this context and may be regarded as constituting an integral part of the aforementioned frame of the arrangement.

The third element constitutes a bearing component for a sensing device 31 which is capable of movement in relation to the frame of the third element. In the illustrative embodiment shown here, the device 31 has the form of a pin (needle) so arranged as to be capable of longitudinal displacement in the third element. The third element also provides support for a piston (hydraulic piston) 32 which is capable of longitudinal displacement, which piston acts as a servo piston in accordance with the following. An attachment 34 is arranged on a piston rod 33 belonging to the servo piston. The piston rod 33 is provided with an external thread 33a, onto which the attachment can be screwed via a matching internal thread in a transcurrent hole for the piston rod 33. Also arranged on the thread 33a of the piston rod is a nut 35 or similar which is rigidly anchored to the piston rod in such a way that the piston/piston rod can be displaced longitudinally by hand by means of the nut 35 or similar relative to the attachment (or vice versa). The nut 35 is provided with a scale 35a, by means of which the mutual displacement between the attachment and the piston rod can be determined. A rod 36 is supported in such a way as to be capable of longitudinal displacement in a corresponding hole in the third element 28 and is anchored at its one end to the attachment 34 in a hole 34a in the latter. The end surface 36a of the rod is exposed to an actuating pressure P' which can be applied temporarily. With the help of the pressure P' the attachment 34 can be forced

backwards relative to the element 28. This function can be utilized in the course of manufacture when the body is finished and when it is accordingly wished to withdraw the needle 31 and the tool 52 in a rearward sense away from the bodies 21 and 22. The pressure  $P'$  is applied via an inlet 34b in the attachment. In one embodiment the pressures  $P'$  and  $P$  are counterbalanced so that the attachment 34 assumes the desired relative position to the element 28. In another embodiment it is possible to make use of stop devices which limit the degree of insertion of the rod 36 into the element 28 by means of the pressure  $P$ . The pressure  $P'$  can be applied in this way by the 'on-off' principle.

At its end which faces away from the frame of the element 28, the piston rod 33 is capable of interacting with a counter-pressure piston 37 which is supported and force-operated in a bearing housing 38. The counter-force is produced with the help of a hydraulic pressure  $P$  in a fluid which is supplied to a connection line 39. A drainage line is indicated by the designation 40, and the drainage tank is represented by 41. The pin 31 is provided with a supporting component 43 which is supported in sliding bearings in the frame of the third element.

The mounting and the function of the pin are illustrated in more detail in Fig. 2. The front end 31 b of the pin is capable of interacting with the external contour 21 a of the replica 21. During the sensing operation the pin 31 will describe reciprocating longitudinal displacement movements as shown by the arrows 42. The supporting device for the pin 31 is indicated by the designation 43. The other end 31c of the pin extends into a hole 28a for the piston 32. The end 31c of the pin is capable of interacting with a constriction or an inlet 32a in the piston 32. The space 28a is connected via a fixed constriction 44 to a pressure line 45 for a fluid, for example hydraulic oil. The inside 32b of the piston consists of a hollow space which is connected to a drainage line 46 via a hole 32c. The piston areas, constrictions and pressures are selected so that the piston 32 is counter-balanced at all times through either side of the piston being acted upon by identical fluid pressure forces. Fluid (for example hydraulic oil) is able to flow in this position of equilibrium from the pressure line 45, into the space 28a, through the constriction 32a, into the internal space 32b, and out via the hole 32c to the drainage line. The fluid pressure generated in this way inside the space 28a is counter-balanced by the force from the counter-pressure piston 37 (see Fig. 1).

If, in the course of its continuous sensing of the external contour 21a, the pin is displaced in either of the directions 42, the end 31c of the pin will vary the size of the constriction 32a. The fluid pressure will be increased or reduced inside the space 28a. This variation in pressure causes the servo piston 32 to move in either direction 42. The piston will then endeavour

to assume the position of equilibrium indicated above at all times.

The pin 31 has its longitudinal axis 31a facing towards the axis of rotation 3, so that an obtuse angle  $\alpha$  is produced. In one preferred embodiment this angle is of the order of  $135^\circ$ . The choice of angle can, however, lie within the range from  $90^\circ$  to approximately  $170^\circ$ . Friction which reduces the sensitivity of the servo system can arise in the bearing 43 in this case. In order to eliminate the major proportion of this friction, the pin and its bearing are caused to rotate about their longitudinal axis 31a, in conjunction with which the direction of rotation is selected in order to achieve the aforementioned reduction in friction in the bearing 43.

According to Fig. 1, the rotation is achieved with the help of a motor 47 which, via a transmission device, for instance in the form of a belt 48, causes the pin and the bearing to rotate. The speed of rotation of the pin can be 1000 r/min, for example. The direction of rotation is indicated by the designation 49. The pressure tank for the fluid pressure is indicated by the designation 50, and the tank connected to the drainage line 46 is indicated by the designation 41.

The aforementioned element 29 is rigidly supported in the attachment 34 in such a way that the element 29 follows the movements of the servo piston and the attachment in the directions 51 of longitudinal displacement. The element supports a tool 52 which is capable of interacting with the blank 22, which tool may be in the form of a hard metal milling cutter 52 in the case of a blank made of titanium or some other hard alloy. The longitudinal axis 53 of the element 29 extends in the direction of the longitudinal axis 4 at an angle  $\beta$  which should preferably be of the same order of magnitude as the angle  $\alpha$ . The fourth element is provided with a clamping device (chuck) 54 for the tool 52. The tool is also caused to rotate, which is achieved with the help of a motor 55 and a device for transmitting the movement, in the present case in the form of a belt drive 56. The aforementioned belt drive is so arranged in this case as to permit the driving of the tool 52 to take place irrespective of the small longitudinal displacement movements which the fourth element 29 executes in the directions 51. The rotation of the tool 52 takes place with the help of the rotatably mounted shaft 57 of the element. The rotatable mounting can be executed in a previously disclosed manner by means of ball bearings 29a. The attachment 34 is secured with the help of one or more supports 58 in such a way that it exhibits torsional resistance.

The mode of operation of the equipment described above is as follows. The first and second elements 1 and 2 are caused to rotate, for example at 1000 r/min, at the same time as which they are displaced towards the pin 31 and the tool 52. During this displacement the pin is able to sense the contour 21

from its top 21a' to its base 21a". Depending on this sensing, the servo piston 32 in the rigidly arranged element 28 is caused to execute longitudinal displacement movements in accordance with the sensing by the pin 31. These movements are transmitted to the attachment 34 and thus to the element 29. The tool 52 accordingly executes a pattern of movements on the blank 22 which correspond to the contour sensed by the pin 31. A three-dimensional body corresponding to the replica 21 will thus be produced from the blank 22. Once the elements 1 and 2 have executed a longitudinal displacement movement which corresponds to the sensing of the pin 31 between 21 a' and 21a", the elements can be caused to move in the other direction 25 of longitudinal displacement, and the now finished body can be removed from the element 2 and can be replaced by a new blank, for example in the form of a titanium bar, etc. In order to provide a large unobstructed space around the blank, the needle and the tool, the attachment 34 can be pushed backwards by actuation applied via the surface 36a.

It is possible by the longitudinal adjustment of the attachment 34 relative to the piston rod 33 with the help of the nut 35 easily to achieve different sizes for the external dimensions of the finished three-dimensional body 22. Adjustments are easily made in this respect in such a way that the external contours of the finished body 22 are larger than, the same as, or smaller than the external contour of the replica 21, i.e. the individual body with its characteristic features. It is possible in this way to produce a first body with external dimensions which slightly exceed the size of the replica or the cast impression. This first body is executed from the blank selected for the body. It is also possible for a second body to be produced which has the same external contours as the replica or the cast impression. This second body can consist of graphite and can be used as a tool or electrode in an electro erosion apparatus of a previously disclosed kind.

As shown in Fig. 3, the arrangement can also be used to shape the manufactured body in question at its base. An outline 21c is marked on the replica for this purpose. To that side of the line which contains the top 21d of the replica, the replica is executed with an electrically non-conductive surface coating. To the other side 21e of the line, the replica is electrically conductive. A device 59 which is provided with a part 60 made of an electrically conductive material, but which is otherwise electrically non-conductive, is arranged in such a way as to be capable of being secured to the free end of the needle 31. The part 60 interacts with the external contour of the replica and is connected to a source of electrical energy, for example a battery, to one pole of which the part is connected. The other pole of the energy source or battery is connected to a change-over device 62, for example a

solenoid switch, which controls the flow of an actuating fluid M, M' to a two-position valve 63 of the 'on-off' type. In the first position (= the position shown in Fig. 3) one side 27a' of the piston 27a of the piston rod 27 is connected to the drainage receptacle 41. In the other position an actuating pressure  $P_1$  is connected to the same side 27a' of the piston 27a. The connection to the piston 27a passes via a fixed constriction 64. The change-over device (its electrical winding) is also connected to earth (the frame of the arrangement), which is symbolized by the connection component 65.

Through the arrangement described above, the direction of movement of the piston 27a will be varied immediately the sensing component 60 crosses the marked outline 21c from one area, for example 21d, to the other area, 21e, or vice versa. When the component 60 is in interaction with the electrically conductive component 21e, the circuit is closed via the negative pole of the battery, the component 60, the conductive component 21 e of the replica 21, the component 19, the frame of the arrangement, the winding in the device 62 and the positive pole of the battery. The change-over device is activated and causes the valve to move to its second position by means of the actuating fluid M, M'. The pressure  $P_1$  is applied to the side 27a' of the piston and produces an actuating pressure on the piston which exceeds a pressure  $P_2$  acting continuously on the piston. What this means is that the replica 21 is caused to move backwards relative to the component 60, which in this case crosses the marked outline 2f and enters into interaction with the electrically non-conductive material. The circuit is broken, and the effect of the actuating fluid M, M' is interrupted. The valve is returned to its initial position with the help of a return spring 63a. The side 27a' of the piston is connected to the drainage receptacle, and the piston rod is caused to move in its other direction, with the result that the part 21 of the replica is caused to move forwards, and the component 60 again crosses the marked outline 21c and enters into interaction with the electrically conductive material ; and so on.

The component part 60 will move with small deflections in such a way as to follow the marking 21c. The tool 52 executes corresponding movements and cuts or grinds away the body 22 along an imaginary line 22a which corresponds to the marking 21c.

The change-over device 62 and the valve 63 can be executed from previously disclosed component parts. The component part 59 can be of cylindrical form and can be applied to the pin 31 in a previously disclosed manner. The component part 60 can have the form of a washer secured, for example by glueing, to the component part 59.

In accordance with the novel method the first and second elements are caused to co-rotate and are displaced relative to the third and fourth elements.

The fourth element is controlled by the third element in such a way that the tool is caused to produce the desired machining of the blank. The tool executes a movement which corresponds to the external contour of the replica, in conjunction with which a tooth cap, an entire artificial tooth or a part of an artificial tooth, or some other mechanical body for some other purpose can be produced.

The valve arrangement for the needle 31 may be executed in a different, previously disclosed manner.

## Claims

1. An arrangement for the production of insert bodies for the artificial rebuilding of teeth and human limbs, or equivalent three-dimensional bodies for the human body having external contours with individually characteristic features; including a first pair of elements (1,2) in which a first element (1) is so arranged as to support a replica (a cast impression 21) of a body which is to be produced and a second element is so arranged as to support a blank (22) from which the body is to be produced and a second pair of elements (28,29), in which a third element (28) supports a sensing device (31) which is capable of interacting with the external contour (21a) of the replica and a fourth element (29) is so arranged as to support a tool (52) by means of which the blank is capable of being worked, the first and second pairs of elements (1,2 and 28,29) respectively are capable of being displaced relative to one another, and the fourth element (29) is capable of being controlled by the third element (28) in such a way that the tool executes movements which correspond to the shape of the external contour of the replica sensed by the sensing device, characterized in that said first and second pairs of elements are co-rotating and that the arrangement is such that the replica and the body are caused to rotate about the axes of rotation of the respective elements, in that the sensing device (31) contains a component part which moves in relation to the frame of the third element (28), said component being capable of longitudinal displacement, and which, via a servo system (32, 33), provides control of the fourth element (29) and thus of the tool (52) which is capable of interacting with the blank, and in that the servo system consists of a fluid piston (a hydraulic piston 32) which is acted upon on either side by fluid pressure, in that the longitudinally displaceable component part (31) is so arranged, depending on the variation in the longitudinal displacement, as to regulate a constriction (32a) in the fluid piston (32) and, together with a fixed constriction (44) provided in the third ele-

ment (38), as to vary the fluid pressure acting on one side of the piston, in such a way that a differential pressure is created across the piston, producing a corresponding displacement of the fluid piston.

2. An arrangement according to Patent Claim 1, **characterized** in that the longitudinal axes (31a, 53) of the third and fourth elements face in the direction of the axes of rotation (3, 4) of the first and second elements at obtuse angles ( $\alpha, \beta$ ), which should preferably be of the order of 135°.
3. An arrangement according to Patent Claims 2 or 3, **characterized** in that the moving, longitudinally displaceable component part (31) and/or its means of support are imparted with friction-reducing rotation.
4. An arrangement according to Patent Claim 1-3, **characterized** in that the fluid flow on that side of the fluid piston which is situated on the longitudinally displaceable component part leads from a pressure source (50) via the fixed and variable constrictions (44 and 32a) to the inside (32b) of the fluid piston, which is connected to a drainage receptacle (41).
5. An arrangement according to any of the Patent Claims 1-4, **characterized** in that a piston rod (33) which is part of said servo system provides an attachment point for a bearing component (34) which supports the fourth element (29).
6. An arrangement according to any of the Patent Claims 1-5, **characterized** in that, with the help of one and the same replica (21), a first body is capable of being produced from a first blank made of metal or a metal alloy, and a second body is capable of being produced from a second blank made of electrode material, for example graphite, and in that, through the relative positioning of the tool in relation to the blank, a difference in size is achieved between the first and the second bodies, such that the second body is smaller than the first body, in which case the second body is capable of being used as an electrode for the spark-machining of the first body in order to provide the latter with the form of a hollow body with a wall thickness which is governed by the relative positioning.
7. An arrangement according to any of the Patent Claims 1-6, **characterized** in that, for the purpose of reducing the base of the body in accordance with a marked outline, the replica (21) is electrically conductive to one side of the marked outline and is electrically non-conductive to the

other side of the marked outline, and in that the sensing device functions as an electrical reducing device which, with the help of the sensing device, guides the first and second pairs of elements towards and away from one another depending on whether the reducing device is sensing one side or another.

## Patentansprüche

1. Anordnung zur Herstellung von Formkörpern für die Rekonstruktion von Zähnen und menschlichen Gliedmaßen oder ähnlichen dreidimensionalen Formkörpern für den menschlichen Körper mit individuell gekennzeichneten Außenkonturen; mit einem ersten Paar von Elementen (1,2), von denen ein erstes Element (1) so angeordnet ist, daß es ein Modell (eine Abdruck-Prägung 21) eines herzustellenden Formkörpers trägt und ein zweites Element so angeordnet ist, daß es einen Rohling (22) trägt, aus dem der Formkörper hergestellt werden soll, und mit einem zweiten Paar von Elementen (28, 29), von denen ein drittes Element (28) einen mit der Außenkontur des Modells zusammenwirkenden Fühler (31) trägt und ein viertes Element (29) ein Werkzeug (52) zur Bearbeitung des Rohlings trägt, wobei das erste und zweite Paar von Elementen (1, 2 und 28, 29) jeweils relativ zueinander verschiebbar sind und wobei das vierte Element (29) durch das dritte Element (28) derart gesteuert wird, daß das Werkzeug Bewegungen ausführt, die der von dem Fühler erfüllten Form der Außenkontur des Modells entsprechen, dadurch **gekennzeichnet**, daß das erste und zweite Paar von Elementen synchron rotieren, und daß die Anordnung so ist, daß das Modell und der Formkörper zusammen um die Drehachsen der jeweiligen Elemente rotiert werden, daß der Fühler (31) einen Hauptteil beinhaltet, der sich in Bezug auf das Gestell des dritten Elements (28) bewegt, wobei dieser Teil longitudinal verschiebbar ist und über ein Servosystem (32, 33) eine Steuerung des vierten Elements (29) und demgemäß des Werkzeugs (52) bewirkt, welches mit dem Rohling zusammenwirkt, und daß das Servosystem aus einem Druckmittel (ein hydraulischer Kolben 32) besteht, auf den auf beiden Seiten Druckmitteldruck einwirkt, so daß das longitudinal verschiebbare Hauptteil (31) abhängig von der Änderung der Longitudinalverschiebung angeordnet ist, um eine Einschnürung (32a) im Druckmittelkolben (32) zu regulieren und zusammen mit einer in dem dritten Element (38) vorgesehenen, vorgegebenen Einschnürung (44) des Druckmitteldrucks, der an einer Seite des Kolbens angreift zu verändern, derart, daß ein Dif-

ferenzdruck über den Kolben geschaffen wird, der eine entsprechende Verschiebung des Druckmittelkolbens erzeugt.

2. Anordnung nach Anspruch 1, dadurch **gekennzeichnet**, daß die Längsachsen (31a, 53) des dritten und vierten Elements in Richtung der Drehachsen (3, 4) des ersten und zweiten Elements in stumpfen Winkeln ( $\alpha$ ,  $\beta$ ), die vorzugsweise in der Größenordnung von  $135^\circ$  sind, zeigen.
3. Anordnung nach den Ansprüchen 1 oder 2, dadurch **gekennzeichnet**, daß das bewegbare, longitudinal verschiebbare Hauptteil (31) und/oder seine Trägermittel mit reibungsreduzierender Drehung ausgestattet sind.
4. Anordnung nach einem der Ansprüch 1 bis 3, dadurch **gekennzeichnet**, daß der Druckmittelfluß auf der Seite des Druckmittelkolbens, die an dem longitudinal verschiebbaren Hauptteil angeordnet ist, von einer Druckquelle (50) über die vorgegebene und die veränderbare Einschnürung (44 und 32a) zur Innenseite (32b) des Druckmittelkolbens führt, der mit einem Ablauftank (41) verbunden ist.
5. Anordnung nach den Ansprüchen 1 bis 4, dadurch **gekennzeichnet**, daß eine Kolbenstange (33), die ein Teil des Servosystems ist, einen Befestigungspunkt für ein Lagerbauteil (34) enthält, die das vierte Element (29) trägt.
6. Anordnung nach den Ansprüchen 1 bis 5, dadurch **gekennzeichnet**, daß mit Hilfe von ein und dem selben Modell (21) ein erster Formkörper hergestellt werden kann aus einem ersten Rohling aus Metall oder einer Metalllegierung, und ein zweiter Formkörper hergestellt werden kann aus einem zweiten Rohling, der aus Elektrodenmaterial besteht, z.B. aus Graphit, und daß durch die relative Positionierung des Werkzeugs zum Rohling ein Unterschied in der Größe zwischen dem ersten und zweiten Formkörper erreicht wird, so daß der zweite Formkörper kleiner ist als der erste Formkörper, wobei in diesem Fall der zweite Formkörper als Elektrode für die Funkenerosionsbearbeitung des ersten Formkörpers verwendet werden kann, um diesen mit der Form eines Hohlkörpers mit einer Wanddicke, die durch die relative Positionierung bestimmt wird, zu versehen.
7. Anordnung nach den Ansprüchen 1 bis 6, dadurch **gekennzeichnet**, daß zum Zweck der Verkleinerung der Grundfläche des Formkörpers, entsprechend einer markierten Außenlinie, das

Modell (21) auf einer Seite der markierten Außenlinie elektrisch leitend ist und auf der anderen Seite der markierten Außenlinie elektrisch nichtleitend ist, und daß der Fühler als elektrische Verkleinerungseinrichtung funktioniert, die mit Hilfe des Fühlers die ersten und zweiten Paare von Elementen hin und weg voneinander bewegt je nach dem, ob die Verkleinerungseinrichtung die eine Seite oder die andere abtastet.

5

10

## Revendications

1. Dispositif pour la production de corps ou éléments rapportés pour la reconstitution artificielle de dents et de membres humains, ou de corps tridimensionnels équivalents ayant des contours extérieurs comportant des caractéristiques individuelles, ce dispositif comportant une première paire d'éléments (1, 2) dans laquelle un premier élément (1) est disposé de manière à supporter une réplique (empreinte 21 obtenue par coulée ou moulage) d'un corps qui est à produire, et un second élément est agencé de façon à supporter une ébauche (22) à partir de laquelle le corps est à produire et une seconde paire d'éléments (28, 29) dans laquelle un troisième élément (28) supporte un dispositif (31) palpeur ou détecteur, qui est capable d'interagir avec le contour extérieur (21a) de la réplique, et un quatrième élément (29) est agencé de façon à supporter un outil (52) permettant de travailler ou d'usiner l'ébauche ; les première et seconde paires d'éléments (1, 2 et 28, 29), respectivement, sont capables d'être déplacées l'une par rapport à l'autre, et en ce que le quatrième élément (29) est capable d'être commandé par le troisième élément (28) de façon que l'outil exécute des mouvements qui correspondent à la forme du contour extérieur de la réplique, forme décelée par le dispositif détecteur ou palpeur, dispositif caractérisé en ce que lesdites première et seconde paires d'éléments exécutent une co-rotation et en ce que l'agencement du dispositif est tel que la réplique et le corps doivent tourner autour des axes de rotation des éléments respectifs ; en ce que le dispositif (31) détecteur ou palpeur contient une partie qui se déplace, par rapport au cadre ou châssis du troisième élément (28), ladite partie étant capable d'exécuter un déplacement longitudinal et assurant, grâce à un servosystème (32, 33), la commande du quatrième élément (29) et ainsi la commande de l'outil (52) capable d'interaction avec l'ébauche, et en ce que le servosystème consiste en un piston fluide (piston hydraulique 32), sur l'un ou l'autre côté duquel agit une pression de fluide ; en ce que la pièce ou partie (31), pouvant se déplacer longitudinalement, est

15

20

25

30

35

40

45

50

55

agencée de façon à réguler, selon la variation de son déplacement longitudinal, une constriction (32a) ménagée dans le piston (32) et, avec une constriction fixe (44) réalisée dans le troisième élément (38) de façon à faire varier la pression du fluide agissant sur un côté du piston, de manière à créer une différence de pression de part et d'autre de ce piston, ce qui produit un déplacement correspondant du piston commandé par un fluide (piston fluide).

2. Dispositif selon la revendication 1, caractérisé en ce que les axes longitudinaux (31a, 53) des troisième et quatrième éléments sont dirigés vers les axes de rotation (3, 4) des premier et second éléments en formant des angles obtus ( $\alpha$ ,  $\beta$ ) qui doivent de préférence être de l'ordre de  $135^\circ$ .
3. Dispositif selon les revendications 1 ou 2, caractérisé en ce qu'une rotation destinée à diminuer le frottement est imprimée à la partie (31) mobile, pouvant se déplacer longitudinalement, et/ou à son organe de support.
4. Dispositif selon l'une quelconque des revendications 1 à 3, caractérisé en ce que l'écoulement de fluide, du côté du piston fluide qui est situé sur la partie déplaçable longitudinalement, s'effectue depuis une source (50) de pression, en passant par les constrictions fixe et variable (44 et 32a) jusqu'à l'intérieur (32b) du piston fluide, qui est relié à un réceptacle (41) de drainage ou d'évacuation.
5. Dispositif selon l'une quelconque des revendications 1 à 4, caractérisé en ce qu'une tige (33) de piston, qui fait partie dudit servosystème, constitue un point de fixation d'un dispositif auxiliaire (34) de portée, qui supporte le quatrième élément (29).
6. Dispositif selon l'une quelconque des revendications 1 à 5, caractérisé en ce que, à l'aide d'une seule et même réplique (21), on peut produire un premier corps à partir d'une première ébauche en métal ou un alliage de métal, et l'on peut produire un second corps à partir d'une seconde ébauche constituée d'un matériau d'électrode, par exemple en graphite ; et en ce que, grâce au positionnement relatif de l'outil par rapport à l'ébauche, on obtient une différence de taille entre les premier et second corps, de sorte que le second corps est plus petit que le premier corps, et dans ce cas le second corps peut servir d'électrode pour l'usinage par étincelage du premier corps afin de conférer à ce dernier la forme d'un corps creux ayant une épaisseur de paroi régie par le positionnement relatif.

7. Dispositif selon l'une quelconque des revendications 1 à 6, caractérisé en ce que, dans le but de diminuer la base du corps selon une ligne d'esquisse marquée, la réplique (21) est conductrice de l'électricité d'un côté de la ligne marquée et n'est pas conductrice de l'électricité de l'autre côté de la ligne marquée, et en ce que le dispositif palpeur ou détecteur joue le rôle d'un dispositif électrique réducteur qui, à l'aide du dispositif palpeur, guide les première et seconde paires d'éléments pour les rapprocher et les éloigner l'une de l'autre selon que le dispositif réducteur est en train de palper un côté ou l'autre.

5

10

15

20

25

30

35

40

45

50

55




Fig. 1

Fig. 2




Fig. 3

