

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 310 141 B2

(12)

NEW EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the opposition decision:
17.04.1996 Bulletin 1996/16

(51) Int. Cl.⁶: **B41J 31/00**

(45) Mention of the grant of the patent:
19.11.1992 Bulletin 1992/47

(21) Application number: **88116853.8**

(22) Date of filing: **10.07.1985**

(54) Multiple-use pressure-sensitive transfer recording media

Mehrfach zuverwendendes druckempfindliches Übertragungs- und Aufzeichnungsmedium

Matériau d'enregistrement sensible à la pression à usage multiple à transfert

(84) Designated Contracting States:
CH DE FR GB IT LI

(30) Priority: **13.07.1984 JP 146524/84**
18.09.1984 JP 195374/84

(43) Date of publication of application:
05.04.1989 Bulletin 1989/14

(62) Application number of the earlier application in
accordance with Art. 76 EPC: **85108569.6**

(73) Proprietor: **FUJI KAGAKUSHI KOGYO CO., LTD.**
Osaka-shi Osaka 555 (JP)

(72) Inventor: **Shini, Masami**
Itami-shi Hyogo-ken (JP)

(74) Representative: **Türk, Gille, Hrabal, Leifert**
Brucknerstrasse 20
D-40593 Düsseldorf (DE)

(56) References cited:

DE-C- 3 214 305 **DE-C- 3 307 432**
GB-A- 1 218 031

- **PATENT ABSTRACTS OF JAPAN**, volume 7, no. 116 (M-216) (1261) 20th May 1983; JP-A-58 36481 (RICOH K.K.) 03-03-1983
- **PATENT ABSTRACTS OF JAPAN**, volume 8, no. 47 (M-280) (1484) 2nd March 1984; JP-A-58 201 690 (RICOH K.K.) 24-11-1983
- **PATENT ABSTRACTS OF JAPAN**, volume 7, no. 193 (M-238) (1338) 24th August 1983; JP-A-58 92584 (RICOH K.K.) 01-06-1983
- Schulz "Die Kunststoffe", Carl Hanser Verlag, München 1959, P. 143
- K.F.Heinisch, "Kautschuk-Lexikon", Gentner Verlag, Stuttgart 1966, p.256

EP 0 310 141 B2

Description

The present invention is a divisional application of EP-application No. 85 108 569.6 (EP-A-0 168 045).

5 The present invention relates to a multiple-use pressure-sensitive transfer recording media. More particularly, it relates to a multiple-use pressure-sensitive transfer recording media for use in over-strike or multi-strike on impact type typewriters or printers.

10 In multi-strike operation, a recording media is advanced by a pitch of substantially the same as or somewhat longer than the character width with each strike and the direction of the travel of the recording media is switched upon each passage of the full length of the recording media. During a plurality of passes of the recording media, the same position thereof is struck plural times by the typeface or the like.

In over-strike operation, a recording media is advanced by a pitch of shorter than the character width, for instance, 1/5 of the character width, with each strike, so that a portion of each strike is effected over regions which have been previously struck and the same position of the recording media receives a plurality of impacts during a single pass. The recording media is discarded after only a single pass.

15 Such multiple-use pressure-sensitive transfer recording media which have been known heretofore include a recording media which comprises a foundation and a finely porous layer on the foundation, the porous layer being composed of minute porous particles and a binder material for bonding the porous particles to each other, and containing a liquid ink paste incompatible with the binder material (see Japanese Unexamined Patent Publication No. 58-29694).

20 The use of PVC/PVA copolymers as binders in multiple-use pressure sensitive recording materials is disclosed in for example JP-A-58-36481 and JP-A-58-201690.

In the case of conventional multiple-use pressure-sensitive transfer recording media of this type, it has been recognized that a liquid ink paste having a high viscosity of more than a certain value (4,000 cP) must be used. The reason therefor is that if a liquid ink paste having a lower viscosity is used to reduce the amount of the liquid ink paste remaining in the porous layer after repeated use of the same position of the recording media, which probably improves the over-strike or multi-strike capability, the ink paste penetrates readily into a receiving paper, which results in pale coloration or low optical density of the image and the distortion of the image due to spread or blot of the ink.

25 When a liquid ink paste having such a high viscosity is used, the coloration of the image obtained in the initial strike is improved, but the lowering of the optical density of the image is sharp and the unevenness of the image is marked with increasing number of strikes in the same position of the recording media, so that the number of times that the same position of the recording media can be used in continuous strikes is upmost 10.

30 Moreover, in the case of the above-mentioned multiple-use pressure-sensitive transfer recording media, the lowering of the optical density of the image with increasing number of strikes in the same position is less sharp than that in the case of a conventional multiple-use pressure-sensitive transfer recording media wherein no porous particles are used, whereby providing a better over-strike or multi-strike capability. However, the finely porous layer is readily broken upon impact of the typeface or the like so that portions of the porous layer are transferred to a receiving paper together with the liquid ink, which causes dark spots or stains in the image. An attempt wherein an adhesive layer is interposed between the foundation and the porous layer has been made, but the above drawback cannot be overcome even by such attempt.

40 It is an object of the present invention to provide a multiple-use pressure-sensitive transfer recording media which is capable of giving sharp and clear images without any unevenness for a multiplicity of strikes at the same position of the recording media and the same position of which can be used many times for transferring the ink onto a receiving paper.

Another object of the invention is to provide a multiple-use pressure-sensitive transfer recording media which has a finely porous layer which is not readily broken by impact upon repeated strikes at the same position and the same position of which can be used many times for transferring the ink onto a receiving paper.

45 Still another object of the invention is to provide a multiple-use pressure-sensitive transfer recording media which has both advantages mentioned above.

These and other objects of the invention will become apparent from the description hereinafter.

50 This is a divisional application from the parent application which provides a multiple-use pressure-sensitive transfer recording media which comprises a foundation and a finely porous layer provided on the foundation, said porous layer comprising minute porous particles and a binder material for bonding the porous particles to each other and containing a liquid ink paste substantially incompatible with the binder material, said liquid ink paste containing as a coloring agent a pigment, and an oil-soluble dye in a state that it is dissolved in a liquid fatty acid, and said liquid ink paste having a viscosity of not less than 300 cP and less than 4,000 cP at ordinary temperature.

55 The present invention provides a multiple-use pressure-sensitive transfer recording media which comprises a foundation and a finely porous layer provided on the foundation, said porous layer comprising minute porous particles and a binder material for bonding the porous particles to each other and containing a liquid ink paste substantially incompatible with the binder material, said binder material being a vinyl chloride-vinyl acetate copolymer comprising 4 to 7 parts by weight of vinyl chloride and 5 parts by weight of vinyl acetate and having an average degree of polymerization of 700 to 950.

One embodiment of the present invention is a multiple-use pressure-sensitive transfer recording media which comprises a foundation and a finely porous layer provided on the foundation, said porous layer comprising minute porous particles and a binder material for bonding the porous particles to each other and containing a liquid ink paste substantially incompatible with the binder material, said liquid ink paste containing as a coloring agent a pigment, and an oil-soluble dye in a state that it is dissolved in a liquid fatty acid, said liquid ink paste having a viscosity of not less than 300 cP and less than 4,000 cP at ordinary temperature, said binder material being a vinyl chloride-vinyl acetate copolymer comprising 4 to 7 parts by weight of vinyl chloride and 5 parts by weight of vinyl acetate.

The present invention is characterised in that a vinyl chloride-vinyl acetate copolymer containing 4 to 7 parts by weight of vinyl chloride per 5 parts by weight of vinyl acetate is used as the binder material for bonding the porous particles to each other.

The specific vinyl chloride-vinyl acetate copolymer has appropriate softness and toughness as the binder material for bonding the porous particles to each other. As a result, the obtained porous layer has appropriate softness and toughness without brittleness. Accordingly, the porous layer is not readily broken upon impact of typeface or the like for a multiplicity of strikes, which ensures repeated use of the same position of the recording media many times.

The multiple-use pressure-sensitive transfer recording media of the present invention is used preferably as an over-strike ribbon. Of course, it also is used preferably as a multi-strike ribbon.

The present invention now will be more particularly described.

In general, a multiple-use pressure-sensitive transfer recording media according to the present invention can be prepared in the following manner:

Components for a liquid ink paste including coloring agent, viscosity-adjusting agent and, optionally, wetting agent and the like were mixed to give a liquid ink paste. The liquid ink paste is mixed and blended with components for a finely porous layer including porous powder and binder material, and a volatile solvent. The thus obtained dispersion is applied onto one surface of a foundation in a coating amount (the value after dried, hereinafter the same) of 10 to 30 g/m², preferably 15 to 30 g/m² by means of a coater or the like and dried to form an ink-containing porous layer wherein the liquid ink paste is contained in a finely porous layer composed of the porous powder and the binder material.

A solution of an oil-soluble dye in a liquid fatty acid in combination with a pigment can be used as a coloring agent for the liquid ink paste for example.

The liquid fatty acid is preferably higher fatty acids, and mixtures thereof. Examples of the liquid fatty acid include, for instance, oleic acid, isostearic acid, and their analogues. The isostearic acid which can be used in the invention is a liquid isostearic acid which is composed of a major amount of isostearic acid and minor amounts of its homologues. Any liquid isostearic acid of technical grade can be used. Those liquid fatty acids may be used singly or as admixtures of two or more kinds thereof. The liquid fatty acid is used preferably in an amount of 1 to 30 % by weight on the basis of the total amount of the liquid ink paste.

Any usual oil-soluble dyes can be used in the present invention. Examples of the oil-soluble dye include, for instance, Nigrosine Base, Spirit Black, Special Black, Victoria Blue Base and Methyl Violet Base. Those oil-soluble dyes may be used singly or as admixtures of two or more kinds thereof. The oil-soluble dye is used preferably in an amount of 1 to 10 % by weight on the basis of the total amount of the liquid ink paste.

Examples of the coloring pigment used in the present invention are carbon blacks and black toner, and the like. Typical examples of the carbon black are Printex 25 (the commercial name of a coloring carbon black made by DEGUSSA), Mogul L (the commercial name of a coloring carbon black made by Cabot Corp.), RAVEN (the commercial name of a coloring carbon black made by Columbia & Carbon Corp.). Those pigments may be used singly or as admixtures of two or more kinds thereof. The pigment is used preferably in an amount of 1 to 40 % by weight, more preferably 20 to 40 % by weight, on the basis of the total amount of the liquid ink paste.

The liquid ink paste may include a wetting agent and a viscosity-adjusting agent in addition to the above-mentioned components.

Any usual wetting agent can be used in the present invention. Examples of the wetting agent are sorbitan fatty acid esters such as sorbitan monostearate, sorbitan monoisostearate and sorbitan monooleate, lecithin, and the like. Those wetting agents may be used singly or as admixtures of two or more kinds thereof. Preferably the wetting agent is used in an amount of 3 to 30 % by weight, more especially 5 to 25 % by weight, on the basis of the total amount of the liquid ink paste.

Any usual viscosity-adjusting agent can be used in the present invention. Examples of the viscosity-adjusting agent are vegetable oils such as rapeseed oil, soybean oil and castor oil; mineral oils such as vitrea oil and jet oil; coldproof plasticizers such as di(2-ethylhexyl) adipate (hereinafter referred to as "DOA"), di (2-ethylhexyl) sebacate (hereinafter referred to as "DOS") and di(2-ethylhexyl) azelate (hereinafter referred to as "DOZ"); hydrocarbons such as lipolube oil; and oligomers of α -olefins. Those viscosity-adjusting agents may be used singly or as admixtures of two or more kinds thereof. The viscosity-adjusting agent is used in such amount that the resulting liquid ink paste has a viscosity of not less than 300 cP and less than 4,000 cP, preferably from 300 to 3,600 cP (the value as measured at 25° C, hereinafter the same). Usually the viscosity-adjusting agent is used in an amount of 20 to 50 % by weight on the basis of the total amount of the liquid ink paste.

The binder material used in the present invention is a resinous material which is incompatible with the components of the liquid ink paste and compatible with the volatile solvent mentioned below, and possesses an adhesiveness against the porous particles mentioned below. Examples of the binder material are vinyl chloride-vinyl acetate copolymer, polyester resin, cellulose acetate butyrate, and the like. Those binder materials may be used singly or as admixtures of two or more kinds thereof. The binder material is used preferably in an amount of 1 to 5 parts by weight, more especially 2 to 3 parts by weight, per 10 parts by weight of the liquid ink paste.

The minute porous particles used in the present invention are preferably those which have an average porosity of 50 to 97 %, more especially 60 to 93 % and an average particle size of 1 to 20 μ . Examples of the porous particles include inorganic porous powders such as diatomaceous earth, zeolite, porous silica powder and carbon black, and organic porous powders such as foamed polyurethane powder. Those porous powders may be used singly or as admixtures of two or more kinds thereof. The porous powder is used preferably in an amount of 1 to 4 parts by weight, more especially 2 to 3 parts by weight, per 10 parts by weight of the liquid ink paste.

As the volatile solvent, there are used one or more solvents such as methyl ethyl ketone (hereinafter referred to as "MEK"), acetone, methyl isobutyl ketone, toluene, and isoparaffin hydrocarbon oils such as IP Solvent (commercial name of an isoparaffin made by IDEMITSU KOSAN CO., LTD.).

The preferred foundation used in the present invention is films having a thickness of 3 to 50 μ , including polyester film, polypropylene film and polyamide film.

The specific vinyl chloride-vinyl acetate copolymer containing 4 to 7 parts by weight of vinyl chloride per 5 parts by weight of vinyl acetate is used as the binder material for bonding the porous particles to each other. The reasons why such specific vinyl chloride-vinyl acetate copolymer is used are as follows: The preparation of a vinyl chloride-vinyl acetate copolymer having a vinyl chloride content of not more than 3 parts by weight per 5 parts by weight of vinyl acetate is very difficult. When a vinyl chloride-vinyl acetate copolymer having a vinyl chloride content of not less than 9 parts by weight per 5 parts by weight of vinyl acetate is used, the resulting porous layer becomes too hard, so that the porous layer is easily broken by impact in printing. In view of the above, a specific vinyl chloride-vinyl acetate copolymer containing 4 to 7 parts by weight of vinyl chloride per 5 parts by weight of vinyl acetate, which is easily prepared, is used, which permits the formation of a finely porous layer which is hardly broken.

Further, when the average degree of polymerization of the vinyl chloride-vinyl acetate copolymer is less than 700, the copolymer is poor in heat resistance so that the liquid ink paste flows out from the porous layer when the ambient temperature is more than 60° C. A copolymer having an average degree of polymerization of more than 950 is difficult in production. In view of the above, the average degree of polymerization of the copolymer is from 700 to 950, particularly from 800 to 900.

The above-mentioned specific vinyl chloride-vinyl acetate copolymer is used as a binder material preferably in an amount of 1 to 5 parts by weight, particularly 2 to 3 parts by weight, per 10 parts by weight of the liquid ink paste.

The liquid ink paste used in the present invention is not particularly limited. However, the liquid ink paste claimed in the parent application of the present divisional application is preferably used, since the lowering of the optical density of the obtained image with increasing number of strikes against the same position of the recording media is gentle.

The porous powder, foundation, the manner of preparing the ink-containing porous layer, and so on, which are used in present invention, may be the same as those in the parent application.

The present invention will now be more particularly described with reference to the following Examples. These Examples are intended to illustrate the invention and not be construed to limit the scope of the invention. In all Examples, "part" means part by weight

EXPERIMENT

The pressure-sensitive transfer recording media shown in Table 1 were produced.

Run Nos. 1 to 4 shown in Table 1 are directed to the ink paste claimed in the parent application of the present application. Each pressure-sensitive transfer recording media of Run Nos. 1 to 4 were produced as follows: An oil-soluble dye was mixed with a liquid fatty acid and the resulting mixture was heated to dissolve the dye into the liquid fatty acid. The obtained solution was mixed with the additional components of the liquid ink paste, i.e. pigment, wetting agent and viscosity-adjusting agent, and the components which constituted the porous layer, i.e. porous powder and binder material, and a volatile solvent. The obtained dispersion was applied onto a polyester film having a thickness of 7 μ by means of a coater and dried to give a pressure-sensitive transfer recording media having on one surface of the foundation an ink-containing porous layer in which a liquid ink paste composed of the dye solution, pigment, wetting agent and viscosity-adjusting agent was contained in a porous layer composed of the porous powder and binder material.

Run No. 5 shown in Table 1 is directed to a recording media as a comparison which had an ink-containing porous layer similar to that of the above-mentioned conventional pressure-sensitive transfer recording media.

With respect to each recording media of Run Nos. 1 to 5, printing test was carried out using an electronic typewriter AP500 made by Canon Inc. Each recording media was fitted in the ribbon cassette of the typewriter and printing was carried out repeatedly in such a manner that the same position of the ribbon was struck by the same typeface, while the

printing position on a recording paper (wood free paper) was changed with each strike. With respect to the printed images thus obtained, the value of print contrast signal (hereinafter referred to as "PCS") was measured by an optical character reader (Kidder model 082). The results are shown in Fig. 1. In the graph of Fig. 1, the PCS value is plotted as ordinate and the number of strikes at the same position of the recording media as abscissa.

5 As is clear from the graph shown in Fig. 1, in the case of the recording media of Run Nos. 1 to 4 the lowering of the optical density of the printed image with increasing number of strikes is noticeably gentle, as compared with the recording media of Run No 5 as a comparison, and the number of strikes that images having a PCS value of not less than 0.6 can be obtained was about two times that of the recording media of Run No. 5.

10 Moreover, there were produced recording media where each of the liquid ink pastes of Run Nos. 1 to 4 was contained in each of the porous layers A, B and C shown in Table 2. With respect to the recording media, the printing test was carried out in the same manner as above. As a result, each recording media exhibited the same printing ability as that of each corresponding recording media of Run Nos. 1 to 4 using the same liquid ink paste and there were almost

15

20

25

30

35

40

45

50

55

observed no influences resulting from the difference in the construction of the porous layer.

Table 1

Composition for liquid ink paste										
Liquid medium for dissolving dye			Oil-soluble dye		Pigment		Wetting agent		Viscosity-adjusting agent	
	Kind	Amount (part)	Kind	Amount (part)	Kind	Amount (part)	Kind	Amount (part)	Kind	Amount (part)
Run No.1	Oleic acid	4	Nigrosine Base EX (Note 2)	2	RAVEN 1255	4	Sorbitan monoiso-stearate	1	DOZ	9
Run No.2	Oleic acid	4	Nigrosine Base EX (Note 2)	2	Black toner	5	Sorbitan mono-oleate	4	DOA	5
Run No.3	Isostearic acid	8	Nigrosine Base EX (Note 2) Special Black EB	1 1	Black toner Prin-tex 25	8 4	Sorbitan monoiso-stearate	6	Rapeseed oil DOZ Vitrea oil	4 4 3
Run No.4	Isostearic acid	3	Nigrosine Base EX (Note 2)	1	Black toner Mogul L	5 3	Lecithin	3	Rapeseed oil DOS Lipolube oil	6 2 1
Run No.5	Polyoxy-ethylene sorbitol hexaoleate	8	Nigrosine Base EX (Note 2)	3	Carbon black Alkali Blue	3 1	Beef tallow fatty acid ester	1	Vitrea oil	3

- continued -

- continued -

	Viscosity of liquid ink paste at 25°C (cP)	Composition for porous layer (Note 1)						Coating amount after dried (g/m ²)
		Porous powder		Binder		Solvent		
		Kind	Amount (part)	Kind	Amount (part)	Kind	Amount (part)	
Run No.1	400	Diatomaceous earth (Note 3)	2	VC-VAC copolymer (Note 4)	2	MEK	18	20
Run No.2	1,000	ditto	2	ditto	2	MEK	18	22
Run No.3	2,000	ditto	2	ditto	2	MEK	18	20
Run No.4	3,500	ditto	2	ditto	2	MEK	18	19
Run No.5	6,000	ditto	2	ditto	4	Tolu-ene MEK	5 13	19

Note 1: The amount of each component means the number of parts per 10 parts of the liquid ink paste.

Note 2: Commercial name of Nigrosine Base made by Oriento Kagaku Kabushiki Kaisha

Note 3: Diatomaceous earth having an average particle size of 7 μ and an average porosity of 75 %

Note 4: Vinyl chloride-vinyl acetate copolymer having a vinyl chloride content of 87 % by weight

Table 2

Composition for porous layer (Note 1)							
	Porous powder		Binder material		Solvent		Coating amount (g/m ²)
	Kind	Amount (part)	Kind	Amount (part)	Kind	Amount (part)	
A	Diatomaceous earth (Note 2)	2	Cellulose acetate butyrate	2	MEK	14	20
B	ditto	2	Vinyl chloride-vinyl acetate copolymer (Note 3)	3	MEK	17	20
C	ditto	3	Polyester resin	3	MEK	19	20
Note 1: The amount of each component means the number of parts per 10 parts of the liquid ink paste shown in Table 1. 2: The same as described in Note 3 of Table 1. 3: The copolymer had a vinyl chloride content of 65 % by weight.							

Example 2

There were produced 90 kinds of pressure-sensitive transfer recording media (Run Nos. 6 to 95) by combining 6 kinds of liquid ink pastes (Nos. 1 to 6) shown in Table 3 with 15 kinds of porous layer compositions (Nos. 1 to 15) shown in Table 4 in the same manner as in Example 1. Each recording media had an ink-containing porous layer having a coating amount of 20 g/m² after dried on a polyester film having a thickness of 7 μ .

Among the liquid ink pastes shown in Table 3, the ink paste Nos. 1 to 4 fall within the scope of the parent application of the present invention and the ink paste Nos. 5 and 6 do not fall within the scope of the parent application of the invention. Among the porous layer compositions shown in Table 4, the composition Nos. 1 to 12 fall within the scope of the Embodiment of the present invention and the composition Nos. 13 to 15 do not fall within the scope of the Embodiment of the present invention.

With respect to the obtained recording media, printing test was carried out in the same manner as in Example 1. The results are shown in Table 5. In Table 5, "PCS X 100" means the value obtained by multiplying the PCS (VIS) value of the image obtained in the tenth strike, by 100, and "number of strikes" means the number of strikes that a portion of

the porous layer begins to be transferred.

Table 3

Liquid ink paste No.	Coloring agent		Wetting agent		Viscosity- adjusting agent		viscosity at 25°C (cp)
	Kind	Amount (part)	Kind	Amount (part)	Kind	Amount (part)	
1	Solution of 2 parts of Nigrosine Base EX in 4 parts of oleic acid Carbon black		Sorbitan mono- stearate	1	DOZ	9	400
		6					
		4					
2	Solution of 2 parts of Nigrosine Base EX in 4 parts of oleic acid Black toner		Sorbitan mono- oleate	4	DOA	5	1,000
		6					
		5					
3	Solution of 1 part of Nigrosine Base EX and 1 part of Special Black EB in 8 parts of iso- stearic acid Black toner Carbon black		Sorbitan monoiso- stearate	6	DOZ Rapeseed oil Vitrea oil	4	2,000
		10				6	
		8				3	
		4					

- continued -

- continued -

Liquid ink paste No.	Coloring agent		Wetting agent		Viscosity- adjusting agent		Viscosity at 25°C (cp)
	Kind	Amount (part)	Kind	Amount (part)	Kind	Amount (part)	
4	Solution of 1 part of Nigrosine Base EX in 3 parts of isostearic acid						
		4	Lecithin	3	DOS Rapeseed oil	2 6	2,000
5	Carbon black Black toner						
		3 5			Lipolube oil	1	
6	Alkali Blue toner Carbon Black						
		2 4	Non		Rapeseed oil Lanolin	5 5	Semi- solid
6	Alkali Blue toner Carbon Black						
		1 4	Non		Hydrophilic petrolatum	12	10,000

Table 4

Porous layer composition No.	Porous powder		Binder material		
	Kind	Amount (part) (Note 1)	Vinyl chloride-vinyl acetate copolymer		
			Ratio of vinyl chloride/ vinyl acetate (by weight)	Average degree of poly- merization	Amount (part) (Note 1)
1	Diatomaceous earth (Note 2)	2	4/5	760	2
2	ditto	2	5/5	780	2
3	ditto	2	6/5	830	2
4	ditto	2	7/5	930	2
5	Whitton SB (Note 3)	2	4/5	760	5
6	ditto	2	5/5	780	5
7	ditto	2	6/5	830	5
8	ditto	2	7/5	930	5

-- continued --

- continued -

Porous layer composition No.	Porous powder		Binder material		
	Kind	Amount (part) (Note 1)	Vinyl chloride-vinyl acetate copolymer		
			Ratio of vinyl chloride/ vinyl acetate (by weight)	Average degree of poly- merization	Amount (part) (Note 1)
9	Silica 300 (Note 4)	1	4/5	760	5
10	ditto	1	5/5	780	5
11	ditto	1	6/5	830	5
12	ditto	1	7/5	930	5
13	Diatomaceous earth (Note 2)	2	10/5	420	2
14	Whitton SB	2	10/5	420	5
15	Silica 300	1	10/5	420	5

Note 1: The amount of each component means the number of parts per 10 parts of the liquid ink paste.

2: The same as described in Note 3 of Table 1

3: Commercial name of calcium carbonate made by Shiraishi Calcium Kabushiki Kaisha

4: Commercial name of porous silica powder made by Nippon Aerosil Kabushiki Kaisha

Table 5

5

10

15

20

25

30

35

40

45

50

Run No.	Liquid ink paste No.	Porous layer composition No.	PCS X 100	Number of strikes
6	1	1	70	> 30
7	2	1	71	"
8	3	1	74	"
9	4	1	73	"
10	5	1	65	"
11	6	1	60	"
12	1	2	71	"
13	2	2	71	"
14	3	2	74	"
15	4	2	74	"
16	5	2	64	"
17	6	2	62	"
18	1	3	72	"
19	2	3	72	"
20	3	3	75	"
21	4	3	75	"
22	5	3	65	"
23	6	3	62	"
24	1	4	73	"
25	2	4	73	"
26	3	4	75	"
27	4	4	74	"
28	5	4	66	"
29	6	4	63	"
30	1	5	70	"
31	2	5	70	"
32	3	5	72	"
33	4	5	71	"
34	5	5	60	"
35	6	5	59	"
36	1	6	71	"
37	2	6	71	"

- continued -

55

- continued -

Run No.	Liquid ink paste No.	Porous layer composition No.	PCS X 100	Number of strikes
38	3	6	72	"
39	4	6	70	"
40	5	6	60	"
41	6	6	60	"
42	1	7	70	"
43	2	7	70	"
44	3	7	72	"
45	4	7	73	"
46	5	7	59	"
47	6	7	58	"
48	1	8	73	"
49	2	8	72	"
50	3	8	76	"
51	4	8	70	"
52	5	8	58	"
53	6	8	60	"
54	1	9	70	"
55	2	9	72	"
56	3	9	77	"
57	4	9	74	"
58	5	9	59	"
59	6	9	63	"
60	1	10	71	"
61	2	10	72	"
62	3	10	74	"
63	4	10	73	"
64	5	10	61	"
65	6	10	62	"
66	1	11	74	"
67	2	11	71	"
68	3	11	76	"
69	4	11	74	"

- continued -

- continued -

Run No.	Liquid ink paste No.	Porous layer composition No.	PCS X 100	Number of strikes
70	5	11	62	"
71	6	11	60	"
72	1	12	74	"
73	2	12	75	"
74	3	12	72	"
75	4	12	72	"
76	5	12	64	"
77	6	12	61	"
78	1	13	70	8
79	2	13	70	7
80	3	13	71	8
81	4	13	69	9
82	5	13	60	8
83	6	13	58	7
84	1	14	69	8
85	2	14	70	8
86	3	14	70	7
87	4	14	69	6
88	5	14	58	9
89	6	14	60	9
90	1	15	71	8
91	2	15	70	9
92	3	15	71	10
93	4	15	72	10
94	5	15	61	8
95	6	15	60	9

As is clear from the results in Table 5, in the case of the recording media of Run Nos. 6 to 77 according to Embodiment II of the invention, there occurred no spots or stains in the printed image, even when printing was repeated at the same position of the recording media not less than 30 times (for instance, 40 to 70 times). Further, the optical density of the image obtained by the 10th strike was high, i.e. ranging from 0.6 to a little less than 0.8. The optical density of the image obtained by the 30th strike ranged from 0.3 to 0.45.

In contrast thereto, in the case of the recording media of Run Nos. 78 to 95 wherein vinyl chloride-vinyl acetate copolymers having an excessively high vinyl chloride content which do not within the scope of Embodiment II of the invention were used as a binder material, a portion of the porous layer was transferred with the liquid ink onto a recording paper, even when printing was repeated less than ten times. As a result, for instance, in the case that the color of liquid ink was black, black spots or stains were produced in the printed image, which resulted in spoiling of the image, even though the image had a high optical density enough to be read.

Moreover, in the case of the recording media of Run Nos. 6 to 9, 12 to 15, 18 to 21, 24 to 27, 30 to 33, 36 to 39, 42 to 45, 48 to 51, 54 to 57, 60 to 63, 66 to 69 and 72 to 75 which fall within the scope of Embodiment III of the invention, any spots or stains resulting from the transfer of the porous layer per se were not produced when printing was repeated at the same position of the recording media not less than 30 times and the optical density of the image obtained in the 10th strike was high, i.e. ranging from 0.7 to a little under 0.8.

In addition to the ingredient or elements used in the Examples, other ingredients or elements can be used in the Examples as set forth in the specification to obtain substantially the same results.

Claims

1. A multiple-use pressure-sensitive transfer recording media which comprises a foundation and a finely porous layer provided on the foundation, said porous layer comprising minute porous particles and a binder material for bonding the porous particles to each other and containing a liquid ink paste substantially incompatible with the binder material, said binder material being a vinyl chloride-vinyl acetate copolymer comprising 4 to 7 parts by weight of vinyl chloride and 5 parts by weight of vinyl acetate and having an average degree of polymerization of 700 to 950.
2. The recording media of Claim 1, wherein the amount of the binder material and the amount of porous particles are from 1 to 5 part by weight and from 1 to 4 parts by weight, respectively, per 10 parts by weight of the liquid ink paste.
3. Use of a vinyl chloride-vinyl acetate copolymer comprising 4 to 7 parts by weight of a vinyl chloride and 5 parts by weight of vinyl acetate and having an average degree of polymerization of 700 to 950 as a binder material for porous particles in a multiple-use pressure sensitive transfer recording media.

Patentansprüche

1. Mehrfach zu verwendendes druckempfindliches Übertragungs- und Aufzeichnungsmedium, welches umfaßt: einen Träger und eine feine, poröse auf dem Träger bereitgestellte Schicht, wobei genannte poröse Schicht sehr kleine poröse Partikel und ein Binder-Material, um die porösen Partikel aneinander zu binden, umfaßt, und welche eine flüssige Tintenpaste, die im wesentlichen inkompatibel mit dem Bindermaterial ist, enthält, wobei genanntes Bindermaterial ein Vinylchlorid-Vinylacetat-Copolymer umfassend 4 bis 7 Gewichtsteile des Vinylchlorids und 5 Gewichtsteile des Vinylacetats ist und einen durchschnittlichen Polymerisationsgrad von 700 bis 950 hat.
2. Aufzeichnungsmedium nach Anspruch 1, worin die Menge des Bindermaterials und die Menge der porösen Partikel von 1 bis 5 Gewichtsteilen und von 1 bis 4 Gewichtsteilen ist, je für 10 Gewichtsteile der flüssigen Tintenpaste.
3. Verwendung eines Vinylchlorid-Vinylacetat-Copolymers, das 4 bis 7 Gewichtsteile Vinylchlorid und 5 Gewichtsteile Vinylacetat umfaßt und einen durchschnittlichen Polymerisationsgrad von 700 bis 950 hat, als Bindermaterial für poröse Partikel in einem mehrfach zu verwendenden druckempfindlichen Übertragungs- und Aufzeichnungsmedium.

Revendications

1. Support d'enregistrement par transfert sensible à la pression à usage multiple qui comporte une base et une couche finement poreuse qui se trouve sur la base, ladite couche poreuse comportant de minuscules particules poreuses et une matière liante pour lier ensemble les particules poreuses et contenant une pâte à encre liquide essentiellement incompatible avec la matière liante, ladite matière liante étant un copolymère chlorure de vinyle-acétate de vinyle comportant de 4 à 7 parties en poids de chlorure de vinyle et 5 parties en poids d'acétate de vinyle et ayant un degré moyen de polymérisation de 700 à 950.
2. Support d'enregistrement selon la revendication 1, où la quantité de la matière liante et la quantité des particules poreuses sont de 1 à 5 parties en poids et de 1 à 4 parties en poids, respectivement, pour 10 parties en poids de la pâte à encre liquide.

EP 0 310 141 B2

3. Emploi d'un copolymère chlorure de vinyle-acétate de vinyle comportant de 4 à 7 parties en poids de chlorure de vinyle et 5 parties en poids d'acétate de vinyle comme matière liante pour des particules poreuses dans un support d'enregistrement par transfert sensible à la pression à usage multiple.

5

10

15

20

25

30

35

40

45

50

55

FIG. 1

