

19



Europäisches Patentamt
European Patent Office
Office européen des brevets



11 Publication number: **0 317 101 B1**

12

EUROPEAN PATENT SPECIFICATION

45 Date of publication of patent specification: **01.12.93** 51 Int. Cl.⁵: **H01B 7/32, G01R 31/02**

21 Application number: **88310110.7**

22 Date of filing: **27.10.88**

54 **A security system and a signal-carrying member therefor.**

30 Priority: **19.11.87 GB 8727092**

43 Date of publication of application:
24.05.89 Bulletin 89/21

45 Publication of the grant of the patent:
01.12.93 Bulletin 93/48

84 Designated Contracting States:
AT BE CH DE ES FR GB GR IT LI LU NL SE

56 References cited:
EP-A- 0 049 104
EP-A- 0 120 479
GB-A- 378 634

73 Proprietor: **W.L. GORE & ASSOCIATES, INC.**
555 Paper Mill Road
P.O. Box 9206
Newark Delaware 19714(US)

72 Inventor: **MacPherson, Hugh**
12, Balfour Crescent
Milnathort
Kinross-shire Scotland(GB)

74 Representative: **McCallum, William Potter et al**
Cruikshank & Fairweather
19 Royal Exchange Square
Glasgow G1 3AE Scotland (GB)

EP 0 317 101 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

This invention relates to a security system for giving warning of attempted interference with an object to be protected. The system is particularly applicable to the protection of an elongate core, such as an electrical power or data-carrying core, optical fibres, or pipelines and tubes carrying air or other fluids.

In the case of a data-carrying core, such as telephone or computer lines, it is important to provide security from wire tapping or eavesdropping on confidential information carried by the core, and to protect data lines used for electronic transfer of money between financial institutions. Thus it is necessary not only to stop information being extracted but also to stop erroneous information being added or current information being changed.

The invention is also applicable to detecting imminent failure of a core which is fundamental to the safety or operation of a control system such as an aircraft hydraulic system or a missile fire control system.

It is known from US Patent 2691698 to provide a security telephone cable around which are wrapped two layers of metal foil spaced from each other by a layer of insulation. If the outer foil layer is interrupted or if the cable is cut through or pierced by an electrically conductive object, a warning signal can be produced. This system however is liable to be overcome by the use of a non-conductive cutting tool or probe. Moreover this cable is capable of being X-rayed by a potential intruder to enable its construction to be determined and thereby facilitate penetration.

According to the present invention there is provided a signal-carrying member for a security system comprising an elongate core surrounded by means capable of transmitting an electrical signal, and an electrically-insulating layer surrounding the core and said means capable of transmitting a signal, characterized by a semi-conductive layer surrounding the electrically-insulating layer, the semi-conductive layer incorporating throughout semi-conductive fibres which protrude from the semi-conductive layer when the semi-conductive layer is pierced, the thickness of the electrically-insulating layer being substantially less than the length of such protruding fibres whereby piercing of the semi-conductive layer and the electrically-insulating layer by an object entering from outside and moving towards the core will cause semi-conductive fibres from the semi-conductive layer to be pushed through the gap formed in the electrically-insulating layer by the object and form a conductive path between the semi-conductive layer and said means capable of transmitting a signal.

The invention will now be particularly described by way of example with reference to the accompanying drawings in which:

Figure 1 is a diagrammatic perspective view of a security system including a core surrounded by two semi-conductive layers separated by an insulating layer;

Figure 2 is part of a circuit diagram of a simple security system according to the present invention;

Figure 3 illustrates the production of a laminated tape comprising an insulating layer and a semi-conductive layer;

Figure 4 is a diagrammatic representation of the wrapping of the laminated tape of Figure 3 around a core;

Figure 5 is a diagrammatic representation of a complete cable incorporating the tape of Figure 3;

Figure 6 is a longitudinal section through part of the wrapping of a cable incorporating a double wrap of tape according to Figure 3;

Figure 7 is a longitudinal section through part of the wrapping of a cable incorporating a double wrap of a modified form;

Figure 8 is a section through a cable in accordance with the present invention;

Figure 9 is a circuit diagram of a simple security system according to the present invention;

Figure 10 is a circuit diagram of a more complex security system according to the present invention;

Figure 11 is a diagrammatic illustration of the wrapping of a cable for use with the circuit of Figure 10;

Figure 12 is a diagrammatic illustration of an alternative method of wrapping a cable;

Figure 13 is a longitudinal section through another embodiment of laminated tape for use in the system of the present invention;

Figure 14 is a section through the tape of Figure 13 after rolling;

Figure 15 is a section through a cable wrapped with three semi-conductive layers;

Figures 16 and 17 are sections through modified forms of the wrapped cable of Figure 16; and

Figure 18 is a circuit diagram of another form of the security system.

In Figure 1, there is shown a simple form of wrapped core forming a signal-carrying member which, together with a detector, forms a security system in accordance with the invention.

The core 10, which can be a fluid-carrying tube but usually will be an electric cable, is wrapped with a first semi-conductive layer 11, then with an electrically insulating layer 12, and thereafter with a second

semi-conductive layer 13, and around this an outer protective sheath 14 is formed. This represents a basic form of signal-carrying member 15. If however the core were provided with a conductive surface, for example a metal braid, itself forming a means capable of transmitting an electrical signal, the inner semi-conductive layer could be dispensed with. Nevertheless preferably the inner semi-conductive layer would still be retained.

In order to form a smooth wrapping, the semi-conductive layer and the insulation layer are both formed of tape which is wrapped helically around the core to 0.95 wraps, i.e. with a gap of 5% or thereabouts between turns to prevent overlap. Although each of the first three layers could be applied by extrusion, wrapping is the preferred method. The protective sheath is conveniently a 0.5mm PVC coating applied by extrusion.

The or each semi-conductive layer is made throughout of a fibrous material such that when a sharp object penetrates the wrapped layers surrounding the core the object will pull fragments of the outer semi-conductive layer 13 through the insulating layer 12 to touch, and so make electrical contact with, the inner semi-conductive layer 11. In order to have a high probability of a conductive path being made, the insulating layer 12 should be thinner than the mean length of the conductive fibres produced by pushing an object through the semi-conductive layer. The insulating layer 12 should therefore be no thicker than, and preferably is thinner than, the semi-conductive layer 13.

The preferred semi-conductive material is unsintered, carbon-loaded polytetrafluoroethylene (PTFE) tape having a volume resistivity of 1.0 ohm-cm or lower. The preferred insulating material is polyester film 0.001 inch (.0025 cm) maximum thickness coated with .0005 inch (.0013 cm) polyester adhesive. The insulating layer is wrapped to 1.1 wraps and subsequently sealed by passing the wrapped construction through an oven at 200 °C.

By making the layers as above, two resistive tracks are formed having a loop resistance of approximately 7k ohms per metre run. By terminating the layers at the far end with a resistor of value greater than 1 metre loop resistance, say 10k ohms, the total loop resistance may be monitored using a Wheatstone Bridge-type of device. Changes in the loop resistance will indicate a penetration of the layers, and measurement of this new loop resistance will indicate the distance along the core to the fault.

A simple circuit for the signal carrier of Figure 1 is shown in Figure 2 where the elongate resistors 11',13' formed by the inner and outer semi-conductive layers 11,13 are interconnected at one end by a resistor 16. At their opposite end the resistors are connected by a flying lead 17 to an electronic monitor 18. This monitor is capable of detecting a change in the total resistance of the resistors 11',13', 16 resulting from shorting across between the semi-conductive layers 11,13. The flying lead 17 is preferably a screened wire which filters high frequency signals. The monitor 18 is described in detail below.

Thus a simple detection system has been formed which will indicate penetration of the core wrapping by an object and hence potential failure of, or interference with, the core. Alternatively it can be used as a 'distance-to-fault' indicator, for example for underground cables.

Although the embodiment of Figure 1 would protect against accidental penetration, it could be overcome by a criminal of modest skill who was aware of its construction.

To provide a more secure system, an interleaved wrap can be used. The construction firstly has a semi-conductive layer 11 applied over the core 10 as in Figure 1. A laminate of insulating tape 12 and semi-conductive tape 13, as shown in Figure 3, is then formed. In the laminate, the semi-conductive tape 13 extends over slightly less than the half width of the insulating tape to one side of the centre line of the insulating tape 12, and is secured to the insulating tape by hot melt adhesive. The laminate is then wrapped helically with overlap as shown diagrammatically in Figure 4. The width of the insulating tape is chosen to give a nominal 2-wrap construction using the known theory of tape wrapping. The semi-conductive tape width is $(0.5W)-2\text{mm} \times W$ where W is the width in millimeters of the insulating tape. Thus a semi-conductive track is wrapped around a core such that each turn of semi-conductive tape is insulated from the next turn and is insulated above and below in one operation. In practice, the gap shown between each turn in Figure 4, for ease of illustration, is closed by fine adjustment of the wrapping angle.

Figure 5 illustrates a completely wrapped core using the laminated tape of Figure 3. It also demonstrates the preferable method of wrapping the outer semi-conductive layer 13 in the opposite direction to the inner semi-conductive layer 11.

The preferred material would be 0.001 inch (.0025 cm) thick polyester film coated with 0.0005 inch (.0013 cm) hot melt adhesive (polyester) for the insulation, and 0.003 inch (.0076 cm) thick semi-conductive PTFE tape, of the same electrical and mechanical properties as used in Figure 1, for the semi-conductive layer. The outer sheath may be made of any convenient thermoplastic material and preferably PVC or polyurethane.

The interleaved layer increases the difficulty of intentional interception compared to the Figure 1 construction, since the layers must be very carefully paired away to gain access to the core, without either cutting through the outer layer and causing an open circuit or shorting the two layers together. The construction of Figure 5 may be further complicated by adhering the layers together by coating the core in an adhesive before the first layer is applied, after the first layer, and after the second layer (interleaved) thus mechanically securing each layer to avoid the possibility of lifting the wraps and gaining access with a fine probe.

Alternatively, both first and second semi-conductive layers can be wrapped using the laminated tape of Figure 3. This further complicates the act of interception, particularly if adhesive is applied between the layers. The semi-conductive layer in Figure 4 will be thicker than that of Figure 1 because of the extra insulation thickness and would preferably be 0.005 inch (.013 cm) thick.

Figure 6 illustrates wrapping of the core with the laminated tape having the semi-conductive layer on the outside of the tape for both inner and outer wraps. This provides a double layer of insulating tape between the semi-conductive layers. In Figures 7 and 8, the second wrap is wound with the semi-conductive layer on the inside of the tape. This provides a single layer of insulating tape between the semi-conductive layers.

The monitor 18 is illustrated in Figure 9 which shows the conductor 20 of the flying lead connected to a terminal T_1 at $+V$ and the other conductor 21 of the flying lead connected through a variable resistor 22 of value R_x to a terminal T_2 at $-V$ volts. Comparator integrated circuits IC1 and IC2 are connected with the terminals T_1 and T_2 and with the resistor 22 and the line resistor, formed by the series connected resistors 11',13',16 and having resistance R , in a bridge circuit coupled at node A between resistors 13' and 22 and at B to an output device which may include relays. If R_x is set to the same resistance value R as the total loop resistance of the detection layers, and $+\Delta V$ and $-\Delta V$ are of equal and opposite very small values, such as ± 20 mv, then node 'A' is at zero volts, and the circuit works as a window comparator. Any small change to the loop resistance R will result in either IC1 or IC2 switching to give an output voltage at B. This in turn can be used to operate a relay or other latching device which can initiate an alarm.

Temperature fluctuations will affect the loop resistance of the detection layer, this being a well-known feature of semi-conductive plastics, and for a detection layer that has to work for long periods in large fluctuating temperatures it is necessary to incorporate some form of compensating circuit. For example, if resistor 22(R_x) in Figure 9 is replaced with a resistive element of the same material as the detection layer and is exposed to the environment of the detection layer, then the loop resistance of the detection layer and R_x will compensate for each other and Node 'A' will remain at zero volts.

Alternatively, a circuit such as that of Figure 10 can be used. In this system, two arms of the bridge are formed from the two semi-conductive layers, and a return 23 is taken from the far end at C to Node D at the input to IC1 and IC2. If the two layers are nominally of the same resistance and R_b is equal to the value of resistor 16 (R_c) then Node D is zero volts. In practice this return is a very fine insulated copper wire, preferably 32AWG or smaller, and is laid under the first layer as shown in Figure 11. This basic principle can be used with any of the preceding examples.

A further option to increase the detection layers resistance to attack is to apply a third semi-conductive layer as in Figure 12 where the copper return wire 23 is replaced by a semi-conductive layer 24. This considerably enhances the detection of intentional interception since a third semi-conductive layer introduces a number of variations utilising all the designs shown and thus offers a high level of design uncertainty to any interceptor.

Further modifications of the detection layer are provided by introducing a multiplicity of semi-conductive elements. This may, of course, be done by adding more layers and incorporating a further randomness such that any intentional interceptor does not know the exact design of the layers.

Another way of incorporating a multiplicity of semi-conductive elements is to segment the semi-conductive tape into separate parallel spaced elements. The elements are laid as shown in Figure 13, and compressed between plain rollers to produce a tape as in Figure 14. If a malleable material is used such as unsintered PTFE for both the semi-conductive elements and the insulating tape, the new tape is homogeneous in appearance and is easily handled as a single tape.

When this tape is applied as an intermediary layer and laid up as in Figure 15, a highly complex detection layer is produced. The layers are applied as follows:

First layer	30	Semi-conductive tape	0.95 wraps,
Second layer	32	Insulating tape	0.95 wraps,
Third layer	33	Hybrid tape	0.95 wraps,
Fourth layer	34	Insulating tape	0.95 wraps,
Fifth layer	35	Semi-conductive tape	0.95 wraps,
Sixth layer	36	Thermoplastic extrusion	

The preferred material for all the tapes is PTFE and the insulating tapes are preferably 0.0025 inch (.006 cm) thick and semi-conductive tapes 0.005 inch (.0013 cm) thick.

If a further insulating layer 37 is added followed by one more semi-conducting element 38 as in Figure 16, a very effective 'trip wire' system can be incorporated. This element may be of narrow dimension (less than 1 mm) and attempts to remove a section of the outer jacket, would cause a high probability of cutting this element. To increase this probability, adhesive is applied to the outer surface of this element such that it is bonded to the inner surface of the thermoplastic extruded jacket.

Alternatively, two semi-conductive elements may be applied over the outer insulating layer as in Figure 17. These two elements are spaced apart and are preferably bonded to the extruded jacket. When the two elements have different potential, it becomes virtually impossible to remove a section of the jacket even if prior knowledge of the design is available.

In order to demonstrate the electrical operation of this design, reference is made to Figures 17 and 18. In the circuit of Figure 18, three resistive arms XX', YY' and ZZ' are connected together at one end, XX' and YY' being interconnected via a resistor 40 of value Rc. YY' and ZZ' are directly interconnected at node C. The opposite end of XX' is connected via lead 41 to terminal T₁ at +V volts. The opposite end of YY' is connected via lead 42 at node D to IC1 and IC2 and the opposite end of ZZ' is connected via lead 43 and resistor 44 of value Rb to terminal T₂ at -V volts.

The null position is set close to zero volts and preferably not exactly zero but of the order of + or - 100 mV. In order to achieve this, balance arms XX' and ZZ' are approximately equal and Rc is equal to Rb. Rb is adjustable to finely tune the circuit. Therefore, node C is close to zero volts and node D is close to zero volts since the input impedance of the comparator circuits is very high.

Referring to Figure 17, the semi-conductive elements of the inner conductive layer 31 is indicated by E₁, the elements of the hybrid third layer 33 by E₂-E₇, the element of the fifth layer 35 by E₈ and the two outermost elements by E₉ and E₁₀.

If elements E₁ and E₈ are connected to form arm YY' of Figure 18, elements E₂,E₃,E₆ and E₁₀ are connected in parallel to form arm XX' and elements E₄,E₅,E₇ and E₉ are connected in parallel to form arm ZZ', the circuit will be in balance. If any one or more elements is open circuit or if any two elements from different arms are shorted together, then the circuit will imbalance and the alarm will sound. By incorporation of a switching circuit 45 to vary the connections, a pre-selected programme may be used which will confront any interceptor with a random pattern of terminations.

If the elements in the hybrid layer are made very narrow (less than 1mm wide) a great number of permutations can be pre-set into the detection layer. Another advantage of this system is that a situation may occur whereby an alarm is sounded due to a very small incision in the detection layer and the affected elements may be switched out, leaving the rest of the detection layer operational and thus continuing to provide cover until a repair can be effected.

Claims

1. A signal-carrier member for a security system comprising an elongate core (10) surrounded by means capable of transmitting an electrical signal (11), and an electrically-insulating layer (12) surrounding the core (10) and said means capable of transmitting a signal (11), characterized by a semi-conductive layer (13) surrounding the electrically-insulating layer (12), the semi-conductive layer (13) incorporating throughout semi-conductive fibres which protrude from the semi-conductive layer when the semi-conductive layer is pierced, the thickness of the electrically-insulating layer (12) being substantially less than the length of such protruding fibres whereby piercing of the semi-conductive layer (13) and the electrically-insulating layer (12) by an object entering from outside and moving towards the core will cause semi-conductive fibres from the semi-conductive layer (13) to be pushed through the gap formed in the electrically-insulating layer (12) by the object and form a conductive path between the semi-conductive layer (13) and said means capable of transmitting a signal (11).

2. A signal-carrier member according to claim 1 wherein said means capable of transmitting an electrical signal is an inner semi-conductive layer (11) surrounding the core (10) and separated from the first mentioned outer semi-conductive layer (13) by said electrically-insulating layer (12).
- 5 3. A signal-carrier member according to claim 1 wherein said electrically-insulating layer comprises a helical winding of insulating tape (12) carrying a semi-conductive tape (13) over less than half the width of the insulating tape, the semi-conductive tape (13) forming said semi-conductive layer.
- 10 4. A signal-carrier member according to claim 2 having thereon at least two helical windings of insulating tape (12) carrying semi-conductive tape (11, 13) over less than half the width of the insulating tape, the two windings of the semi-conductive tape (11, 13) forming said inner and outer semi-conductive layers.
- 15 5. A signal-carrier member according to claim 2 or claim 4 to which a resistance-bridge-type detector (18) is connected, each semi-conductive layer forming at least part of one arm of the resistance bridge (11', 13').
- 20 6. A signal-carrier member according to claim 5 wherein an insulated wire (23) extends within at least one of the windings and is connected to the outer ends of the semi-conductive layers (11', 13') and to a terminal of the detector (18).
- 25 7. A signal-carrier member according to claim 5 wherein a fixed resistor (16) is connected in series with one semi-conductive layer (11') and a variable resistor is connected in series with the other semi-conductive layer (13').
- 30 8. A signal-carrier member according to claim 5 having one or more further wrappings of semi-conductive tape (35), the various semi-conductive tapes (31, 33, 35) being interconnected to form more than two arms of equal resistance and connected to the detector.
- 35 9. A signal-carrier member according to claim 8 wherein the semi-conductive tapes (E1, E8; E2, E3, E6, E10; E4, E5, E7, E9) which are interconnected to form one of said arms (YY'; XX'; ZZ') are selected from different wrapping layers.
- 40 10. A signal-carrier member according to claim 3 or claim 4 wherein the or each insulating tape winding is wound from an insulating tape (12) carrying thereon two or more parallel spaced semi-conductive tapes (13).
- 45 11. A signal-carrier member according to claim 5 having a switching device (45) electrically connected between the semi-conductive layers and the detector (18) and operable at will to vary the electrical connections between the said layers and the detector (18).

Patentansprüche

1. Signalführendes Element für ein Sicherheitssystem, umfassend einen langgestreckten Kern (10), umgeben von Mitteln, die ein elektrisches Signal (11) zu übertragen vermögen, und eine elektrisch isolierende Schicht (12), die den Kern (10) und die ein Signal übertragen könnenden Mittel (11) umgibt, gekennzeichnet durch eine die elektrisch isolierende Schicht (12) umgebende halbleitende Schicht (13), wobei die halbleitende Schicht (13) sie durchsetzende halbleitende Fasern beinhaltet, die von der halbleitenden Schicht vorstehen, wenn die halbleitende Schicht durchstoßen wird, wobei die Dicke der elektrisch isolierenden Schicht (12) wesentlich weniger beträgt als die Länge derartiger vorstehender Fasern, wodurch ein Durchstoßen der halbleitenden Schicht (13) und der elektrisch isolierenden Schicht (12) durch einen von außen eintretenden und sich in Richtung auf den Kern bewegenden Gegenstand zur Folge hat, daß halbleitende Fasern aus der halbleitenden Schicht (13) durch den in der elektrisch leitenden Schicht (12) von dem Gegenstand gebildeten Spalt gestoßen werden und einen leitenden Pfad zwischen der halbleitenden Schicht (13) und den ein Signal übertragenden Mitteln (11) bilden.
- 55 2. Signalführendes Element nach Anspruch 1, bei dem die Mittel, die ein elektrisches Signal zu übertragen vermögen, eine innere halbleitende Schicht (11) sind, welche den Kern (10) umgibt und von der zuerst erwähnten äußeren halbleitenden Schicht (13) durch die elektrisch isolierende Schicht (12)

getrennt ist.

3. Signalführendes Element nach Anspruch 1, bei dem die elektrisch isolierende Schicht eine spiralförmige Wicklung aus einem Isolierband (12) aufweist, welches ein halbleitendes Band (13) über weniger als der halben Breite des Isolierbands trägt, wobei das halbleitende Band (13) die halbleitende Schicht bildet.
4. Signalführendes Element nach Anspruch 2, auf dem mindestens zwei schraubenförmige Wicklungen eines Isolierbandes (12) vorgesehen sind, welches ein halbleitendes Band (11, 13) über weniger als der halben Breite des Isolierbands trägt, wobei die beiden Wicklungen des halbleitenden Bandes (11, 13) die innere und die äußere halbleitende Schicht bilden.
5. Signalführendes Element nach Anspruch 2 oder Anspruch 4, an dem ein Detektor vom Widerstandbrückentyp (18) angeschlossen ist, wobei jede halbleitende Schicht mindestens einen Teil eines Zweigs der Widerstandsbrücke (11', 13') bildet.
6. Signalführendes Element nach Anspruch 5, bei dem ein Isolierdraht (23) in zumindest einer der Wicklungen verläuft und an die äußeren Enden der halbleitenden Schichten (11', 13') und an einen Anschluß des Detektors (18) angeschlossen ist.
7. Signalführendes Element nach Anspruch 5, bei dem ein fester Widerstand (16) in Reihe zu einer halbleitenden Schicht (11') und ein veränderlicher Widerstand in Reihe zu der anderen halbleitenden Schicht (13) angeschlossen ist.
8. Signalführendes Element nach Anspruch 5 mit einer oder mehreren weiteren Wicklungen aus halbleitendem Band (37), wobei verschiedene halbleitende Bänder (31, 32, 35) derart miteinander verbunden sind, daß sie mehr als zwei Zweige gleichen Widerstands bilden und an den Detektor angeschlossen sind.
9. Signalführendes Element nach Anspruch 8, bei dem die halbleitenden Bänder (E1, E8; E2, E3, E6, E10; E4, E5, E7, E9), die zur Bildung eines der Zweige (YY', XX'; ZZ') verschaltet sind, aus verschiedenen Wicklungsschichten ausgebildet sind.
10. Signalführendes Element nach Anspruch 3 oder Anspruch 4, bei dem die oder jede Isolierbandwicklung aus einem Isolierband (12) gewickelt ist, welches auf sich zwei oder mehr parallel beabstandete Halbleiterbänder (13) trägt.
11. Signalführendes Element nach Anspruch 5 mit einer Schalteinrichtung (45), die elektrisch zwischen die halbleitenden Schichten und den Detektor (18) geschaltet ist und nach Belieben betätigbar ist, um die elektrischen Verbindungen zwischen den Schichten und dem Detektor (18) zu variieren.

Revendications

1. Un élément porteur de signaux destiné à un système de sécurité comprenant un noyau allongé (10) entouré par un moyen susceptible de transmettre un signal électrique (11), et une couche électriquement isolante (12) entourant le noyau (10) et ledit moyen (11) susceptible de transmettre un signal, caractérisé par une couche semi-conductrice (13) entourant la couche électriquement isolante (12), la couche semi-conductrice (13) incorporant partout des fibres semi-conductrices qui font saillie de la couche semi-conductrice lorsque la couche semi-conductrice est percée, l'épaisseur de la couche électriquement isolante (12) étant sensiblement inférieure à la longueur de ces fibres en saillie, grâce à quoi un percement de la couche semi-conductrice (16) et la couche électriquement isolante (12) par un objet entrant de l'extérieur et se déplaçant vers le noyau amène des fibres semi-conductrices de la couche semi-conductrice (13) à être poussées à travers l'intervalle formé par l'objet dans la couche électriquement isolante (12) et à former un trajet conducteur entre la couche semi-conductrice (13) et ledit moyen (11) susceptible de transmettre un signal.
2. Un élément porteur de signaux selon la revendication 1 dans lequel ledit moyen susceptible de transmettre un signal électrique est une couche semi-conductrice (11) entourant le noyau (10) et

séparée de la couche semi-conductrice extérieure (13) mentionnée en premier lieu par ladite couche électriquement isolante (12).

- 5 3. Un élément porteur de signaux selon la revendication 1 dans lequel ladite couche électriquement isolante comprend un enroulement en hélice d'un ruban isolant (12) portant un ruban semi-conducteur (13) sur moins de la moitié de la largeur du ruban isolant, le ruban semi-conducteur (13) formant ladite couche semi-conductrice.
- 10 4. Un élément porteur de signaux selon la revendication 2 comportant au moins deux enroulements en hélice de ruban isolant (12) portant un ruban semi-conducteur (11, 13) sur moins de la moitié de la largeur du ruban isolant, les deux enroulements du ruban semi-conducteur (11, 13), formant lesdites couches semi-conductrices intérieure et extérieure.
- 15 5. Un élément porteur de signaux selon la revendication 2 ou la revendication 4 auquel est relié un détecteur 18 du type pont de résistances, chaque couche semi-conductrice formant au moins une partie d'une branche du pont à résistances (11', 13').
- 20 6. Un élément porteur de signaux selon la revendication 5 dans lequel un fil isolé (23) s'étend à l'intérieur d'au moins l'un des enroulements et est relié aux extrémités extérieures des couches semi-conductrices (11', 13') et à une borne du détecteur (18).
- 25 7. Un élément porteur de signaux selon la revendication 5 dans lequel une résistance fixe (16) est reliée en série à une couche semi-conductrice (11') et une résistance variable est reliée à l'autre couche semi-conductrice (13').
- 30 8. Un élément porteur de signaux selon la revendication 5 comportant une ou plusieurs enveloppes additionnelles de ruban semi-conducteur (35), les divers rubans semi-conducteurs (31, 33, 35) étant reliés entre eux afin de former plus de deux branches de résistances égales et reliées au détecteur.
- 35 9. Un élément porteur de signaux selon la revendication 8 dans lequel les rubans semi-conducteurs (E1, E8; E2, E3, E6, E10; E4, E5, E7, E9) qui sont reliés entre eux de manière à former l'une desdites branches (YY'; XX'; ZZ') sont choisis dans différentes couches d'enveloppe.
- 40 10. Un élément porteur de signaux selon la revendication ou la revendication 4 dans lequel l'enroulement de ruban isolant ou chacun d'eux est enroulé à partir d'un ruban isolant (12) qui porte deux rubans semi-conducteurs parallèles espacés (13) ou davantage.
- 45 11. Un élément porteur de signaux selon la revendication 5 comprenant un dispositif commutateur (45) relié électriquement entre les couches semi-conductrices et le détecteur (18) et manoeuvrable à volonté pour faire varier les liaisons électriques entre lesdites couches et le détecteur (18).
- 50
- 55




FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.




FIG. 5.




FIG. 6.




FIG. 7.




FIG. 8.




FIG. 9.




FIG.10.




FIG.II.




FIG. 12.




FIG. 13.




FIG. 14.




FIG.15.




FIG.16.




FIG.17.




FIG.18.