(f) Publication number:

**0 325 242** A3

(12)

## **EUROPEAN PATENT APPLICATION**

(2) Application number: 89100866.6

(s) Int. Cl.4: C 21 C 7/10

22 Date of filing: 19.01.89

(30) Priority: 21.01.88 JP 9675/88

43 Date of publication of application: 26.07.89 Bulletin 89/30

(84) Designated Contracting States: DE FR GB IT

B Date of deferred publication of search report: 14.02.90 Bulletin 90/07

Applicant: NKK CORPORATION
1-2, 1-chome, Marunouchi Chiyoda-ku
Tokyo (JP)

(72) Inventor: Ishii, Toshio c/o Patents & License & Quality Standards department NKK CORPORATION 1-21-chome, Marunouchi Chiyoda-ku Tokyo (JP)

Okubo, Yutaka c/o Patents & License & Quality Standards Department NKK CORPORATION 1-21-chome, Marunouchi Chiyoda-ku Tokyo (JP)

Fukuda, Shuzo c/o Patents & License & Quality Standards Department NKK CORPORATION 1-21-chome, Marunouchi Chiyoda-ku Tokyo (JP)


Kawai, Yoshihiko c/o Patents & License & Quality Standards Department NKK CORPORATION 1-2 1-chome, Marunouchi Chiyoda-ku Tokyo (JP)

(74) Representative: Füchsle, Klaus, Dipl.-Ing. et al Hoffmann . Eitle & Partner Patentanwälte Arabellastrasse 4 D-8000 München 81 (DE)

(54) Method for refining molten steel in a vacuum.

A method for refining molten steel in a vacuum comprises an immersion process, wherein two immersion nozzles (5) (6) arranged at the lower portion of a vacuum vessel (4) are immersed in molten steel (2) in a ladle (1); a dissolving process, wherein gases are dissolved in molten steel by blowing gases containing at least gas soluble in the molten steel from a gas blow-in opening (3) arranged in a ladle (1) in the molten steel; a first degassing process, wherein the molten steel is degassed by keeping the the vacuum vessel evacuated, having the molten steel circulated between the ladle and the vacuum vessel by injecting gases containing at least an inert gas from the middle (7) of the rising tube (5) and blowing gases containing at least gas soluble in the molten steel from a gas blow-in opening (3) arranged in the ladle (1); and a second degassing process, wherein the molten steel is degassed by keeping the vacuum vessel evacuated, stopping a gas blow-in from the gas blow-in opening (3) arranged in the ladle (1) and having the molten steel circulated between the ladle and the vacuum vessel by injecting gases containing at least an inert gas from the middle (7) of the rising tube (5) in the molten steel (1).

FIG.1



EP 0 325 242 A3

Bundesdruckerei Berlin

## **EUROPEAN SEARCH REPORT**

EP 89 10 0866

Category	Citation of document with in	Relevant to claim	CLASSIFICATION OF THE	
X	PATENT ABSTRACTS OF 43 (C-152)[1188], 19			C 21 C 7/10
Y	PATENT ABSTRACTS OF 53 (C-154)[1198], 31 JP-A-57 200 514 (NII 08-12-1982 * Whole article *	rd March 1983; &	1-22	
Y	PATENT ABSTRACTS OF JAPAN, vol. 10, no.31 (C-327)[2088], 6th February 1986; & JP-A-60 184 619 (SUMITOMO KINZOKU KOGYO K.K.) 20-09-1985 * Whole article *		1-22	
Y	DE-B-1 222 090 (W. * Figure; claims *	-1 222 090 (W.C. HERAEUS) gure; claims *		
Y	US-A-3 320 053 (LEHMANN)  * Figures 1,2; column 2, line 43 - column 3, line 6 *		1	TECHNICAL FIELDS SEARCHED (Int. Cl.4)  C 21 C C 22 B
Α	GB-A- 954 214 (W.C. HERAEUS)			6 22 8
A	PATENT ABSTRACTS OF 118 (C-167)[1263], JP-A-58 37 112 (KAW 04-03-1983			
	The present search report has b			
Place of search THE HAGUE  Date of completion of the search  09-11-1989		OBF	Examiner ERWALLENEY R.P.L.I.	
CATEGORY OF CITED DOCUMENTS  T: the E: ea X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category L: do A: technological background O: non-written disclosure &: m		NTS T: theory or print E: earlier patent after the filir other D: document cit L: document cit	y or principle underlying the invention or patent document, but published on, or the filing date ment cited in the application nent cited for other reasons ber of the same patent family, corresponding	