



⑫ **EUROPEAN PATENT SPECIFICATION**

④⑤ Date of publication of patent specification :  
**04.03.92 Bulletin 92/10**

⑤① Int. Cl.<sup>5</sup> : **E04D 3/363, E04D 3/362,**  
**B21D 39/02**

②① Application number : **89304807.4**

②② Date of filing : **11.05.89**

⑤④ **Metal sheeting.**

③⑩ Priority : **13.05.88 GB 8811397**

⑦③ Proprietor : **BRITISH ALCAN ALUMINIUM plc**  
**Chalfont Park,**  
**Gerrards Cross, Buckinghamshire, SL9 0QB**  
**(GB)**

④③ Date of publication of application :  
**15.11.89 Bulletin 89/46**

⑦② Inventor : **Bayley, Michael John**  
**Fagnall Cottage Fagnall Lane Winchmor Hill**  
**Amersham Buckinghamshire HP7 OPQ (GB)**  
Inventor : **Buxton, Peter Godfrey**  
**8 Gosling Grove**  
**Downley Buckinghamshire (GB)**  
Inventor : **Saini, Tarlochan Singh**  
**229 Rochford Gardens**  
**Slough Berkshire (GB)**

④⑤ Publication of the grant of the patent :  
**04.03.92 Bulletin 92/10**

⑧④ Designated Contracting States :  
**AT BE CH DE ES FR GB GR IT LI LU NL SE**

⑤⑥ References cited :  
**DE-A- 2 136 584**  
**GB-A- 817 238**  
**GB-A- 899 446**  
**US-A- 3 394 524**  
**US-A- 3 511 011**

⑦④ Representative : **Adams, William Gordon et al**  
**RAWORTH, MOSS & COOK 36 Sydenham**  
**Road**  
**Croydon Surrey CR0 2EF (GB)**

**EP 0 342 044 B1**

Note : Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

## Description

This invention relates to metal sheeting.

Metal profiled sheets are frequently used as roof panels and for other building cladding purposes. It is well known to provide a metal sheet which is pre-formed with integral ribbing so that it may readily be interlocked at adjoining edges with a similar sheet and which may be fastened to a support without the fastening means being exposed to the environment or being on the visible side of the sheet. These products may include separate fixing clips and involve on site roll forming to close the interlocking seams. All such products are usually referred to as "raised seam cladding". Many examples of such profiled sheets are known and they are frequently roll-formed from an aluminium alloy as well as other metallic materials. Usually each sheet has a first upstanding hook formation along one edge and a second upstanding formation along an opposite edge of the sheet with a hook receiving part and a valley in the plane of the sheet through which fasteners can be passed. When the sheets are interlocked the first formation of one sheet hooks on to the hook receiving part of an adjoining sheet and covers the valley and its fasteners. From their outer surfaces the sheets then present a generally flat appearance having spaced apart upstanding ribs with no fasteners visible. These ribs are usually referred to as "raised seam".

In general, when used as roof panels, the sheets need to be fully supported on a pre-prepared flat surface and are not strong enough to span any worthwhile distance between supporting purlins. It is however clearly desirable to provide sheets that can be supported at intervals, as between spaced apart purlins, and it is further desirable that the sheet should be wider so that the spacing between the raised seams is increased. In addition the sheets should be strong enough to support snow loads, wind loads both in pressure and suction and so that, for example, operatives can walk on them.

We have found that there are conflicting factors between, on the one hand, increasing the strength and stiffness of the sheet and, on the other hand, ensuring adequate locking against suction forces under high wind conditions.

US-A 4,423,581 shows a metal sheeting system in which a metal sheet is formed with a central web extending laterally towards lateral edges having an outer surface facing in an outer direction, a hook formation along one said lateral edge projecting in the outer direction and facing away from the central web, a hook receiving formation along an opposed said lateral edge projecting in the outer direction and facing toward the central web, the hook receiving formation having a valley portion extending laterally toward the opposed lateral edge away from a hook receiving portion of the receiving formation, the

arrangement being such that the sheet can be fastened directly to a support without the interposition of separate clips. This sheeting system however is arranged so that the hook formation hooks under the hook receiving formation which results in a connection between sheets which is awkward to fit, requires the engaging sheet to be lifted at a large angle making it subject to excessive windage and when connected performs badly against suction forces under high wind conditions. This latter problem requires clamping bars to be provided.

It is therefore an object of the present invention to provide an improved interlocking metal sheet which has good strength characteristics and improved interlocking formations.

Accordingly the present invention is characterised in that the hook formation of one sheet can hook over the upstanding hook receiving formation of an adjoining sheet and cover its valley wherein latching means act between the formations to latch them together subsequent to their being hooked together and wherein after such latching said one sheet can be rotated about the hook receiving formation of the other sheet through at least 25° to unlatch the sheet and before the formations can be unhooked.

The rotation preferably occurs without significant distortion of the material of either sheet.

Preferably upon said relative rotation the latching action ceases to function, and further rotation through at least 10° is required before the formations can be disengaged.

The above and other aspects of the present invention will now be described with reference to the accompanying drawing in which:-

Fig. 1 is a transverse section through a metal sheet,

Fig. 2 is a view similar to Fig. 1 showing part of two sheets distorted by suction forces, and

Fig. 3 is a similar section, to a larger scale, of an interconnection between two metal sheets.

Referring to Fig. 1 a roll-formed aluminium alloy sheet 1 has along one side edge 2 a first, hook, formation indicated generally at 3 which is upstanding from the outer surface 4 of the sheet. At its other side edge 5 the sheet has a second, hook receiving, formation indicated generally at 6 and a valley 7. The formations 3 and 6 are separated by a web 8 which is coplanar with the floor 9 of the valley 7. A number of stiffening ribs 8b may be formed in the sheet.

The hook formation 3 comprises a sloping part 10, a wall 11 approximately at right angles to the web 8, a flat 12 and downwardly and inwardly projecting parts 13 and 14 constituting a hook having a curved part 15. As shown the outer end of the part 14 is curved to be approximately parallel with the wall 11 and to allow run-out on the edge of the sheet material on roll forming.

The hook receiving formation 6 comprises a slop-

ing part 16 the upper end 16b of which is approximately at right angles to the web 8 and is then folded at a part 17 which, together with the wall 16b defines a hook receiving formation as will be described later. The lower end of the folded part 17 is formed as a hollow bead 18 and the rolled material of the sheet is then formed as a platform 19 with a recess 20, a side wall 21 approximately at right angles to the web 8 leading to the valley 7, the floor 9 of which has an upwardly turned part 22 and a lip 23 at the same angle to the web 8 as the sloping part 10. The lip 23 allows run out of the edge of the sheet material on roll forming.

Fig. 3 shows how the hook formation 3 engages over the hook receiving part 6 of an adjoining sheet. In Fig. 3 the same reference numerals have been used except that for the "adjoining" sheet suffixes "a" have been added to each reference numeral.

It will be assumed that the sheet 1a is already mounted on suitably spaced-apart purlins (not shown) and secured thereto through the valley floor 9a. The fixings used can be conventional and may be arranged to accommodate longitudinal expansion of the sheet 1a. The sheet 1 is then held with its web 8 approximately vertically and its hook formation 3 engaged around the bead 18a. The sheet 1 is then pivoted to the position shown in cross-hatched lines in Fig. 3 and secured to the purlins. In this position the sloping part 10 engages with the lip 23a and the wall 11, the flat 12, the part 13 and the curved part 15 respectively embrace the upper part of the side wall 21a, the platform 19a, the part 17a and the curved part 15a. Sealing material (not shown) may be disposed in the recess 20a. The dimensions of the formations 3 and 6 are such that the upper part of the formation 2 is a "latching fit" over the upper part of the formation 6.

As mentioned above we have found that conflicting requirements exist in increasing the strength of the sheets without at the same time increasing the risk that suction forces under high wind conditions will tear off one of the sheets. When the sheets are mounted on spaced-apart purlins this reduces the number of edge fastenings that can be used.

Although innately higher strength aluminium alloys than are usually employed can be used this does not, of itself, increase the strength of the sheets sufficiently. Increasing the height of the "raised seams" constituted by the formations 3 and 6 does significantly increase the strength of the sheets and enables them to be unsupported across suitably spaced purlins. However such a change significantly alters the pattern of distortion of the "other" sheet 1a raised by suction forces on the web 8a resulting from wind flow across the outer surfaces 4 and 4a of the sheets. This change tends to make easier the lateral separation of the formations.

As shown in Fig. 2, wind flow across the outer surfaces 4 and 4a can cause high suction forces to be

applied to the webs of the sheets and lift these webs so that their formations 3 and 6 distort and move laterally to disengage the formations 3 and 6.

With the present invention the close, "latching fit", engagement between the upper parts of the formations ensures that the wall 11 constitutes latching means for the hook by its close fit against the upper part of the side wall 21a. As shown in Fig. 3 the edge of the sheet 1 can rotate about the bead 18a through successive positions indicated at A, B, C and D before reaching the position E shown as a solid line. During the movement A to approximately C the wall 11 rides up the side wall 21a and retains its latching action. At the approximate position C the corner between the sloping part 10 and the wall 11 rides over the corner between the side wall 21a and the platform 19a. As a result of the "latching fit" referred to above this transition occurs suddenly. In positions D and E the hook still remains engaged since the outer end of the part 14 remains in engagement with a part of the bead 18a which extends parallel with the upper end of the sloping part 16. Once a sheet has been distorted to the extent represented in position E the strains to which it is subjected are extremely complex and not readily predictable. However it would be expected that position E represents the point at which the edge of the sheet 1 will move laterally and the formations will disengage.

In position C the chain line 25 represents the angle between the edge of the web 8 and the line of the web 8a. The angle defined is G.

In position E the chain line 24 represents the angle between the edge of the web 8 and the line of the web 8a. The angle defined is F. The precise angle F reached for position E is determined by the detailed dimensions of the upper parts of the formations 3 and 6, the width of the web 8 and the thickness of the sheet. We have found the following criteria achieve good results:-

Height of the formations 3 and 6 a minimum of 10% (preferably 12.5%) of the total sheet width. This is to achieve a basic stiffness to the whole profile so as to allow it to support the imposed loads.

Length of the vertical wall 11 between 20% to 30% (preferably 24%) of the height of the rib formation 3 and 6.

Centre of radius of tip of the hook receiving formation in the range 10 to 20% (preferably 14%) below the top of the rib formation 6.

Distance of centre of radius of tip of hook receiving formation to vertical wall 11 when assembled in the range 3.75% to 6.25% (preferably 5%) of the total formation width.

Sheet thickness lies in the range of 0.15% to 0.25% of total formation width.

The angle G is in the range 25° to 30° (preferably 28°).

The angle F is in the range 10° to 35° greater than

angle G (preferably 30°).

By using a high strength aluminium alloy such as 3105 or 3004 in standard roofing sheet thicknesses and tempers and by increasing the height of the raised seams the basic strength of sheets 500 mm wide can be increased sufficiently to enable the sheets to span purlins with spacings in excess of 2.0 m and still readily support snow and wind loads both in pressure and suction and carry the weight of an operative between the purlins. By utilising the latching feature of the present invention the disadvantages of increasing the height of the seams can be obviated and increased protection given against suction induced by wind force.

It will be understood that with the interlocking formations described above then should the sheet 1 be rotated through an angle significantly greater than the angle F (position E) the sheets will again interlock as the part 14 extends upwardly behind the folded part 17. Depending upon the dimensions of these parts this re-engagement is likely to occur with an angle F of about 75°.

#### Claims

1. A metal sheet (1) formed with a central web (8) extending laterally towards lateral edges having an outer surface (4) facing in an outer direction, a hook formation (3) along one said lateral edge (2) projecting in the outer direction and facing away from the central web, a hook receiving formation (6) along an opposed said lateral edge (5) projecting in the outer direction and facing toward the central web, the hook receiving formation (6) having a valley portion (7) extending laterally toward the opposed lateral edge (5) away from a hook receiving portion (18) of the receiving formation (6), the arrangement being such that the sheet can be fastened directly to a support without the interposition of separate clips characterised in that the hook formation (3) of one sheet can hook over the hook receiving formation (6) of an adjoining sheet, and cover its valley wherein latching means (11-17, 19,21) act between the formations to latch them together subsequent to their being hooked together and wherein after such latching the said one sheet can be rotated about the hook receiving formation of the other sheet through at least 25° to unlatch the sheet and before the formations can be unhooked.

2. A metal sheet according to claim 1 in which said rotation occurs without significant distortion of the material of either sheet.

3. A metal sheet according to claim 1 in which upon said relative rotation the latching action ceases to function, and further rotation through at least 10° is required before the formations can be disengaged.

4. A metal sheet according to any one of claims

1 to 3 in which the hook formation (3) comprises a sloping part (10) extending upwardly away from the sheet (1), a wall (11) at the outer end of the sloping part being approximately at right angles to the sheet, a flat portion (12) extending away from the wall and generally downwardly and inwardly projecting parts (13, 14) constituting a hook having a lower curved part (15).

5. A metal sheet according to claim 4 in which the outer end of said parts (14) is curved to be approximately parallel with the wall so as to allow run-out on the edge of the sheet material when the latter is roll formed.

6. A metal sheet according to claim 4 in which when the sheets are interlocked the base of the sloping part. (10) of the hook formation (3) sheet (1) abuts the valley (7) of the hook receiving formation (6) of the adjoining sheet.

7. A metal sheet according to any one of the preceding claims in which the hook receiving formation (6) comprises a sloping part (16) the upper end (16b) of which is approximately at right angles to the sheet and is then folded (17) so that the folded part and the upper end define a hook.

8. A metal sheet according to claim 7 in which, above the hook the sheet is formed with a platform (19) having a side wall (21) approximately at right angles to the sheet which side wall extends downwardly to form a part of said valley.

9. A metal sheet according to claim 8 in which the floor (9a) of the valley has an upwardly turned part (22a) and a lip (23a) at the same angle to the sheet as the sloping part.

10. A metal sheet according to any one of the claims 1 to 7 in which, above the hook the sheet is formed, with a platform (19) having a longitudinal recess (20) thereon.

#### Patentansprüche

1. Ein metallisches Verkleidungselement (1), bestehend aus einem mittigen Steg (8), der sich lateral in Richtung lateraler Kanten erstreckt und eine äußere Oberfläche (4), welche in eine äußere Richtung weist, eine Hakenausbildung (3) entlang einer (2) der lateralen Kanten, welche in die äußere Richtung vorspringt und von dem mittigen Steg wegweist, und eine Hakenaufnahme-Ausbildung (6) entlang der gegenüberliegenden lateralen Kante (5) hat, welche in die äußere Richtung vorsteht und in Richtung des mittigen Steges weist, wobei die Hakenaufnahme-Ausbildung (6) einen Talabschnitt (7) hat, der lateral in Richtung der gegenüberliegenden lateralen Kante (5) und von einem Hakenaufnahme-Abschnitt (18) der Hakenaufnahme-Ausbildung (6) weg verläuft, wobei die Anordnung derart ist, daß das Verkleidungselement direkt auf einer Stützunterlage ohne

die Zwischenschaltung von separaten Befestigungsmitteln befestigt werden kann, dadurch gekennzeichnet, daß die Hakenausbildung (3) von einem Verkleidungselement mit der Hakenaufnahme-Ausbildung (6) des anschließenden Verkleidungselementes verhakht werden kann und dessen Talabschnitt überdeckt, wobei Riegelvorrichtungen (11-17, 19, 21) zwischen den Ausbildungen wirken, um diese nach dem Verhaken miteinander zu verriegeln und wobenach einem derartigen Verriegeln das eine Verkleidungselement um die Hakenaufnahme-Ausbildung des anderen Verkleidungselementes um einen Betrag von wenigstens 25° drehbar ist, um das Verkleidungselement zu entriegeln, bevor die Ausbildungen enthakt werden können.

2. Ein metallisches Verkleidungselement nach Anspruch 1, wobei die Drehung ohne wesentliche Verformung des Materials von jedem Verkleidungselement stattfindet.

3. Ein metallisches Verkleidungselement nach Anspruch 1, wobei bei der Relativedrehung die Verriegelungswirkung in ihrer Funktion aufgehoben wird und eine weitere Drehung um wenigstens 10° benötigt wird, bevor die Ausbildungen voneinander gelöst werden können.

4. Ein metallisches Verkleidungselement nach einem der Ansprüche 1 bis 3, wobei die Hakenausbildung (3) einen schräg verlaufenden Teil (10), der sich von dem Verkleidungselement (1) nach oben weg erstreckt, eine Wand (11) am äußeren Ende des schräg verlaufenden Teils wenigstens annähernd im rechten Winkel zu dem Verkleidungselement, einen flachen Abschnitt (12), der sich von der Wand weg erstreckt und im wesentlichen nach unten verläuft und nach innen vorstehende Teile (13, 14) aufweist, welche einen Haken mit einem unteren gekrümmten Teil (15) bilden.

5. Ein metallisches Verkleidungselement nach Anspruch 4, wobei das äußere Ende der Teile (14) gekrümmt ist, um annähernd parallel mit der Wand zu sein, um ein Auslaufen an der Kante des Verkleidungselement-Materials zu ermöglichen, wenn letzteres durch Rollen geformt wird.

6. Ein metallisches Verkleidungselement nach Anspruch 4, wobei beim Verriegeln der Verkleidungselemente untereinander die Basis des schräg verlaufenden Teiles (10) der Hakenausbildung (3) eines Verkleidungselementes (1) an dem Tal (7) der Hakenaufnahme-Ausbildung (6) des benachbarten Verkleidungselementes anschlägt.

7. Ein metallisches Verkleidungselement nach einem der vorhergehenden Ansprüche, wobei die Hakenaufnahme-Ausbildung (6) einen schräg verlaufenden Teil (16) aufweist, dessen oberes Ende (16b) annähernd im rechten Winkel zu dem Verkleidungselement ist und nachfolgend gefaltet (17) ist, so daß der gefaltete Teil und das obere Ende einen Haken definieren.

8. Ein metallisches Verkleidungselement nach Anspruch 7, wobei oberhalb des Hakens das Verkleidungselement eine Plattform (19) hat mit einer Seitenwand (21) in annähernd rechtem Winkel zu dem Verkleidungselement, wobei die Seitenwand nach unten sich erstreckt, um einen Teil des Tales zu bilden.

9. Ein metallisches Verkleidungselement nach Anspruch 8, wobei der Boden (9a) des Tales einen nach oben verlaufenden Teil (22a) und eine Lippe (23a) im gleichen Winkel zu dem Verkleidungselement wie der schräg verlaufende Teil aufweist.

10. Ein metallisches Verkleidungselement nach einem der Ansprüche 1 bis 7, wobei oberhalb des Hakens das Verkleidungselement mit einer Plattform (19) mit einer in Längsrichtung verlaufenden Ausnehmung (20) darin ausgebildet ist.

## Revendications

1. Feuille métallique (1) comportant une âme centrale (8) s'étendant latéralement vers des bords latéraux et possédant une surface extérieure (4) tournée vers l'extérieur, une partie formant crochet (3) le long de l'un desdits bords latéraux (2) faisant saillie vers l'extérieur et tournée à l'écart de l'âme centrale, une partie de réception de crochet (6) le long du bord latéral opposé (5) faisant saillie vers l'extérieur et tournée vers l'âme centrale, la partie de réception de crochet (6) comprenant une portion de vallée (7) s'étendant latéralement vers le bord latéral opposé (5) à l'écart d'une portion de réception de crochet (18) de la partie de réception de crochet (6), l'agencement étant tel que la feuille peut être fixée directement à un support sans interposition d'attaches séparées, caractérisée par le fait que la partie formant crochet (3) d'une feuille peut s'accrocher sur la partie de réception de crochet (6) d'une feuille adjacente, et recouvrir sa vallée, des moyens de verrouillage (11-17, 19, 21) agissant entre les parties pour les verrouiller mutuellement après leur accrochage mutuel, et après un tel accrochage l'une des feuilles peut être tournée autour de la partie de réception de crochet de l'autre feuille sur au moins 25° pour déverrouiller la feuille avant que les parties puissent être décrochées.

2. Feuille métallique selon la revendication 1, dans laquelle ladite rotation se produit sans distorsion notable du matériau de l'une ou l'autre feuille.

3. Feuille métallique selon la revendication 1, dans laquelle lors de ladite rotation relative, le verrouillage cesse de produire ses effets et une autre rotation sur au moins 10° est nécessaire avant que les parties puissent être dégagées l'une de l'autre.

4. Feuille métallique selon l'une quelconque des revendications 1 à 3, dans laquelle la partie formant crochet (3) comporte une portion inclinée (10) s'étendant vers le haut à l'écart de la feuille (1), une paroi

(11) à l'extrémité extérieure de la portion inclinée étant disposée sensiblement à angle droit par rapport à la feuille, une portion plane (12) s'étendant à l'écart de la paroi et des portions (13, 14) faisant saillie sensiblement vers le bas et vers l'intérieur constituant un crochet possédant une portion inférieure incurvée (15).

5

5. Feuille métallique selon la revendication 4, dans laquelle l'extrémité extérieure desdites portions (14) est incurvée de manière à être approximativement parallèle à la paroi de manière permettre un dégagement sur le bord du matériau de la feuille lorsque celle-ci est formée par laminage.

10

6. Feuille métallique selon la revendication 4, dans laquelle lorsque les feuilles sont interverrouillées la base de la portion inclinée (10) de la partie formant crochet (3) d'une feuille (1) vient en butée contre la vallée (7) de la partie de réception de crochet (6) de la feuille adjacente.

15

7. Feuille métallique selon l'une quelconque des revendications précédentes, dans laquelle la partie de réception de crochet (6) comprend une portion inclinée (16) dont l'extrémité supérieure (16b) se trouve sensiblement à angle droit par rapport à la feuille et est ensuite repliée (17) de manière que la portion repliée et l'extrémité supérieure définissent un crochet.

20

25

8. Feuille métallique selon la revendication 7, dans laquelle au-dessus du crochet la feuille comporte une plateforme (19) possédant une paroi latérale (21) approximativement à angle droit par rapport à la feuille, ladite paroi latérale s'étendant vers le bas pour constituer une portion de ladite vallée.

30

9. Feuille métallique selon la revendication 8, dans laquelle le fond (9a) de la vallée possède une portion tournée vers le haut (22a) et une lèvre (23a) formant, par rapport à la feuille, le même angle que la portion inclinée.

35

10. Feuille métallique selon l'une quelconque des revendications 1 à 7, dans laquelle, au-dessus du crochet, la feuille comprend une plateforme (19) possédant sur elle un renforcement longitudinal (20).

40

45

50

55

