11) Publication number:

0 351 893 A3

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 89117529.1

(51) Int. Cl.5: G03G 15/16, G03G 15/00

2 Date of filing: 27.05.87

Priority: 28.05.86 JP 79541/86 U 13.10.86 JP 242597/86 28.11.86 JP 281698/86

- 43 Date of publication of application: 24.01.90 Bulletin 90/04
- © Publication number of the earlier application in accordance with Art.76 EPC: 0 247 602
- Designated Contracting States:
 DE FR GB NL
- Date of deferred publication of the search report: 11.07.90 Bulletin 90/28

- 71) Applicant: MITA INDUSTRIAL CO. LTD. 2-28, 1-chome, Tamatsukuri Chuo-ku Osaka 540(JP)
- 2 Inventor: Takamatsu, Junichi 36-2 Shin-machi Hannan-cho Sennan-gun Osaka-fu(JP) Inventor: Akiyama, Kazunori 6-1-504 Satsukigaoka Minami Suita-shi Osaka-fu(JP)
- 7a Representative: Patentanwälte Beetz sen. Beetz jun. Timpe Siegfried Schmitt-Fumian- Mayr
 Steinsdorfstrasse 10
 D-8000 München 22(DE)


[54] Image-forming machine.

(57) An image-forming machine comprising a rotating drum (26) having a photographic material formed on its peripheral surface, an electrostatic latent imageforming zone for forming a latent electrostatic image on the photographic material, a developing zone for developing the latent electrostatic image to a toner image, a transfer zone (52) for transferring the toner image to a sheet material and a peeling zone (144) for peeling the sheet material from the photographic material, said zones being arranged along the peripheral surface of the rotating drum (26) in this en sequence as viewed in the rotating direction (28) of the rotating drum (26), and a charge eliminating device (56) disposed in the peeling zone (144) so as to be positioned opposite to the peripheral surface of 00

the rotating drum (26), the sheet material (P) peeled from the peripheral surface of the rotating drum (26) in the peeling zone (144) being conveyed through a conveying passage (94) extending at substantially the same level as the lowermost site of the rotating drum (26), or below said lowermost site; wherein the transfer zone (52) is arranged in a region within an angle, α , of from -90 to 0 degree, from the lowermost site of the rotating drum (26) as viewed in the rotating direction of the rotating drum (26), and the peeling zone (144) is arranged in a region within an angle, β , of from -45 to 10 degrees from the lowermost site of the rotating drum (26) as viewed in the rotating direction of the rotating drum.

EP 0 351







EUROPEAN SEARCH REPORT

EP 89 11 7529

Category	Citation of document with in of relevant par	ndication, where appropriate, ssages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.4)	
A	PATENT ABSTRACTS OF 10 (P-168)[1155], 10 JP-A-57 168 257 (HI 16-10-1982	JAPAN, vol. 7, no. 4th January 1983; &	1,2	G 03 G G 03 G	
A	US-A-4 579 441 (HA * Column 5, lines 2		1,2		
A	PATENT ABSTRACTS OF 57 (P-434)[2114], 7 JP-A-60 201 372 (FU 11-10-1985	JAPAN, vol. 10, no. th March 1986; & JI XEROX K.K.)	1,2		
D,A	PATENT ABSTRACTS OF 257 (P-316)[1694], & JP-A-59 126 571 (21-07-1984	24th November 1984;	1		
A	GB-A-2 119 715 (RI * Abstract; figure		1		
Α	DE-A-3 111 779 (TO	KYO SHIBAURA DENKI	1	TECHNICAL FIELDS SEARCHED (Int. Cl.4)	
	K.K.) * Figure 1 *			G 03 G G 03 G G 03 G	15/00
TU	The present search report has be Place of search E HAGUE	peen drawn up for all claims Date of completion of the search 29-03-1990	CIG	Examiner GOJ P.M.	
Y: pai do A: tec	CATEGORY OF CITED DOCUME rticularly relevant if taken alone rticularly relevant if combined with an cument of the same category chnological background in-written disclosure	E : earlier patent after the filing other D : document cite L : document	document, but pu date d in the applicati l for other reason	blished on, or on as	