



⑫

EUROPEAN PATENT APPLICATION

⑬ Application number: 90302956.9

⑮ Int. Cl.⁵: B28B 1/26

⑭ Date of filing: 20.03.90

⑬ Priority: 20.03.89 JP 31896/89

⑭ Date of publication of application:
26.09.90 Bulletin 90/39

⑮ Designated Contracting States:
DE ES FR GB IT SE

⑯ Date of deferred publication of the search report:
02.05.91 Bulletin 91/18

⑬ Applicant: INAX CORPORATION
6 Koiehonmachi 3-chome
Tokoname-Shi Aichi(JP)


⑭ Inventor: Kohmura, Kuniyoshi, c/o Enokido
Kojo
Inax Corporation, No. 77 Minatocho 3-chome
Tokoname-shi, Aichi(JP)
Inventor: Ito, Takeshi, c/o Enokido Kojo
Inax Corporation, No. 77 Minatocho 3-chome
Tokoname-shi, Aichi(JP)
Inventor: Murata, Kazushige, c/o Enokido Kojo
Inax Corporation, No. 77 Minatocho 3-chome
Tokoname-shi, Aichi(JP)

⑭ Representative: Charlton, Peter John et al
ELKINGTON AND FIFE Beacon House 113
Kingsway
London WC2B 6PP(GB)

⑯ Liquid-tight slip-casting molds and method for production thereof.

⑰ A mold (1) for cast-molding a slip under pressure is provided. The mold comprises a divisible casting mold (1) including at least two mold portions (8,9) to form a slip-depositing mold cavity (18) when mated together; a sealing material layer (11) attached onto at least the whole mating filter surface (16) of at least one mold portion to be mated; and a resilient material layer (10) attached onto one of the sealing material layer (11) and another mating filter surface (16), along slip-depositing divisible surfaces (12) of the filter layers (2); whereby the mold portions (8,9) mated together are provided with a resilient liquid-tight zone (14) between the mating filter surfaces (16). The mold is readily produced by coating at least the whole mating filter surfaces (16) of at least one mold portion (8,9) to be mated with a sealing compound; applying a releasing material between the mating mold portions (8,9), mating the mold portions, and hardening the sealing compound to provide a sealing material layer (11); and then bonding a resilient material sheet (10) onto one of

the resulting sealing material layer (11) and another mating filter surface (16), along slip-depositing divisible surfaces (12) of the filter layers.





EP 90 30 2956

DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (Int. Cl.5)		
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)		
A	FR-A-2 349 773 (DOWTY SEALS LTD) * The whole document * ---	1,2,8,9	B 28 B 1/26		
A	US-A-3 993 727 (R.A. SKRILETZ) * The whole document, in particular column 8, lines 46-66; figure 1 * ---	1,3,4,8 -10			
A	GB-A- 792 351 (SHENANGO CHINA INC.) * Page 2, lines 84-93; fig. * ---	1,3,4			
A	FR-A-2 601 896 (TOTO LTD) * The whole document * ---	1,3,4,8 -10			
A	GB-A- 468 641 (J. JAMES) * The whole document * ---				
A	PATENT ABSTRACTS OF JAPAN, vol. 5, no. 205 (E-88)[877], 25th December 1981; & JP-A-56 124 237 (TOKYO SHIBAURA DENKI K.K.) 29-09-1981 -----		TECHNICAL FIELDS SEARCHED (Int. Cl.5)		
			B 28 B B 29 C F 16 J B 22 F		
The present search report has been drawn up for all claims					
Place of search	Date of completion of the search	Examiner			
THE HAGUE	19-02-1991	GOURIER P.A.			
CATEGORY OF CITED DOCUMENTS					
X : particularly relevant if taken alone	T : theory or principle underlying the invention				
Y : particularly relevant if combined with another document of the same category	E : earlier patent document, but published on, or after the filing date				
A : technological background	D : document cited in the application				
O : non-written disclosure	L : document cited for other reasons				
P : intermediate document	& : member of the same patent family, corresponding document				