



(12) **EUROPEAN PATENT APPLICATION**

(21) Application number: **90308425.9**

(51) Int. Cl.⁵: **H01H 13/14**

(22) Date of filing: **31.07.90**

(30) Priority: **27.09.89 US 413032**

(43) Date of publication of application:
24.04.91 Bulletin 91/17

(84) Designated Contracting States:
DE FR GB IT


(71) Applicant: **Hewlett-Packard Company**
Mail Stop 20 B-O, 3000 Hanover Street
Palo Alto, California 94304(US)

(72) Inventor: **Schroeder, Christopher Karl**
3914 Mesa Drive
Oceanside, CA 92056(US)
Inventor: **Torgerson, Curt N.**
9947 Paseo Montril
San Diego, California 92103(US)

(74) Representative: **Colgan, Stephen James et al**
CARPMAELS & RANSFORD 43 Bloomsbury
Square
London WC1A 2RA(GB)

(54) **Long traveling button switch with enhanced user feedback.**

(57) A pushbutton switch including a keycap (11) having a keycap top (11a) and a keycap plunger (11b), a retaining bezel (13) for guiding the keycap plunger and limiting the displacement thereof, a deformable elastomeric switch button (17) supporting a contact pad, and a printed circuit contact pattern (23) engageable by the contact pad when the switch button is deformed by the downward displacement of the keycap plunger. The deformation of the button switch tactile feedback, while impact of the keycap top against the retaining bezel provides audible feedback. The pushbutton switch is configured to limit the downward displacement of the keycap plunger to avoid excessive force on the printed circuit board.



LONG TRAVELING BUTTON SWITCH WITH ENHANCED USER FEEDBACK

BACKGROUND OF THE INVENTION

The disclosed invention is directed generally to a keyboard pushbutton switch, and more specifically is directed to a keyboard pushbutton switch having a long travel, and enhanced tactile and audible feedback, and improved contact reliability.

Pushbutton switches are utilized in keyboards for calculators, device control panels, and the like. A known pushbutton switch structure includes a dome-shaped metallic contact which contactively engages contacts on a printed circuit board when deformed by actuation of an associated keycap. The deformation of the metallic dome provides both tactile feedback and audible feedback.

An important consideration with a pushbutton switch having a metallic dome contact is the relatively small contact area provided by the deformed dome, which makes such switches susceptible to non-closure due to dust and dirt contamination. In order to increase reliability, some metallic dome pushbutton switches are individually packaged for insertion in printed circuit boards. Such switches can be more expensive and bulkier.

Another consideration with metallic dome pushbutton switches is transmission of the keypress force to the printed circuit board, which if excessive could cause damage.

A further consideration with pushbutton switches having metallic dome contacts is a limitation on the amount of key travel imposed by the metallic dome. Relatively longer key travel provides for a more comfortable keypress.

SUMMARY OF THE INVENTION

It would therefore be an advantage to provide a keyboard pushbutton switch structure having a reliably large contact area.

Another advantage would be to provide a keyboard pushbutton switch structure which reduces the amount of keypress force transmitted to the printed circuit board utilized therewith.

A further advantage would be to provide a keyboard pushbutton switch structure provides which provides for sufficient key travel.

The foregoing and other advantages are provided by the invention in a pushbutton switch structure that includes a manually depressable keycap having a keycap top and a keycap plunger, a resiliently deformable elastomeric switch button aligned with and engageable by the keycap plunger,

a contact pattern supported on a printed circuit board located beneath the switch button, a contact element supported by the deformable switch button for contacting the contact pattern pursuant to deformation of the deformable switch button by downward displacement of the keycap plunger, and a retaining bezel for guiding and limiting the displacement of the keycap plunger. The deformation of the button switch tactile feedback, while impact of the keycap top against the retaining bezel provides audible feedback.

BRIEF DESCRIPTION OF THE DRAWING

The advantages and features of the disclosed invention will readily be appreciated by persons skilled in the art from the following detailed description when read in conjunction with the drawing wherein:

FIG. 1 is a schematic exploded perspective illustration of a pushbutton switch in accordance with the invention.

FIG. 2 is an elevational sectional view illustrating the pushbutton switch of FIG. 1 with the keycap plunger in the non-actuated position and exerting a slight preload on the switch dome.

FIG. 3 is an elevational sectional view illustrating the pushbutton switch of FIG. 1 with the keycap plunger sufficiently displaced to cause deformation of the switch dome and contactive closure of the switching elements.

FIG. 4 is an elevational sectional view illustrating the pushbutton switch of FIG. 1 with the keycap plunger sufficiently displaced to cause audible feedback from the impact of the keycap top on the retaining bezel.

DETAILED DESCRIPTION OF THE DISCLOSURE

In the following detailed description and in the several figures of the drawing, like elements are identified with like reference numerals.

Referring now to FIG. 1, shown therein is a pushbutton switch assembly that includes a keycap 11 having a keycap top 11a and a keycap plunger 11b. The keycap plunger 11a is slidably engaged and retained in a guiding and retaining bezel 13 which, for example, is integrally formed with other bezels in a bezel structure 15. By way of example, the keycap plunger includes barb-like tabs for engaging the bottom portions of the bezel 13 to limit

the upward displacement of the keycap.

An elastomeric dome switch button 17 is located beneath the keycap 11. By way of example, the switch button 17 is integrally formed in an elastomeric sheet 19, comprising rubber, for example, with other switch buttons. The elastomeric sheet 19 rests on a printed circuit board 21 having a conductive pattern 23 aligned with the switch button 17. By way of example, the conductive pattern 23 can comprise interleaved conductive traces to provide redundant contact elements. The printed circuit board 21 is attached to the bezel structure 15 to prevent relative displacement thereof.

The elastomeric dome switch button 17 comprises a conical side wall 17a secured to the elastomeric sheet 19 at its lower boundary. A horizontal top wall 17b is formed on the upper boundary of the conical side wall 17a, and a circular ridge 17c is formed on the top wall 17b. A cylindrical bump 17d of shorter height than the circular ridge 17c is formed in the center of the top wall 17b. The thicknesses of the top wall 17b, the circular ridge 17c, and the central bump 17d are greater than the thickness of the conical side wall so that the conical side wall resiliently deforms more easily than the thicker elements.

A conductive pad 25, comprising, for example, a carbon impregnated elastomer, is attached to the underside of the top wall 17b generally in alignment with the bump 17c.

The keycap 11, the bezel 13, and the bezel structure 15 are configured to provide a slight preload on the switch button 17 when the keycap 11 is not actuated, as shown in FIG. 2. Further, the keycap 11 and bezel 13 are configured so that the bottom of the keycap top is against the top of the bezel 13 when the switch button 17 is fully deformed, which transfers further force to the bezel 13.

The pushbutton switch operates as follows. The user presses the top of the keycap top 11a to displace the keycap 11 downwardly. The conical side wall 17a collapses just before the contact pad 25 engages the conductive pattern 23 on the printed circuit board, which causes a distinct variation in the resistance felt by the user's finger. In particular, the sudden collapse of the conical side wall 17a reduces the resistance on the keycap which, pursuant to the keypress force, then travels quickly to impact the bezel 13 and produce an audible feedback click. FIG. 3 shows the contact pad 25 against the conductive pattern 23 just after the conical side wall has collapsed, and FIG. 4 shows the keycap at its downward travel limit against the bezel 13.

As particularly shown in FIG. 4, when the keycap 11 is fully depressed against the bezel 13, the side wall 17a is collapsed, and the top wall 17b

is slightly deformed around the contact pad 23, but does not touch the printed circuit board 19. Any keypress force applied to the keycap beyond that required to collapse the side wall 17a and deform the top wall as shown in FIG. 4 will be transmitted to the bezel 13 and not to the printed circuit board 19. In particular, the keycap 11, the bezel 13, and the switch button 17 are configured so that a limited amount of force is transmitted to the printed circuit board, for example, an amount determined to be sufficient to assure appropriate contact between the contact pad 25 and the conductive pattern 23. In this manner, contact is assured while preventing excessive forces on the printed circuit board 21.

The keycap travel and the nature of the tactile feedback are selected to provide for a comfortable keypress that provides a distinct indication that contact has been made.

The keycap travel is determined by the difference between (a) the top to bottom height of the retaining bezel 13, and (b) the distance on the keycap plunger 11b between the barb-like tabs and the underside of the keycap top 11a. In conjunction with selection of keycap travel, the distance between the contact pad 23 and the printed circuit conductive pattern should be selected so that appropriate contact is assured while avoiding the application of excessive force when the keycap is fully depressed.

The nature of the tactile feedback, which is the force-to-displacement characteristic of the switch button 17, is determined by the thickness of the conical sidewall 17a, the thickness of the top wall 17b, the outside diameter of the top wall 17b, and the inside diameter of the lower boundary of the conical sidewall 17a.

The foregoing has been a disclosure of a push-button switch assembly that advantageously utilizes elastomeric switch buttons and provides tactile feedback as well as mechanically produced audible feedback. Further, the disclosed pushbutton switch allows for implementation of an appropriate comfortable keycap travel.

Although the foregoing has been a description and illustration of specific embodiments of the invention, various modifications and changes thereto can be made by persons skilled in the art without departing from the scope and spirit of the invention as defined by the following claims.

Claims

1. A switch structure comprising:
a manually depressable keycap having a keycap top and a keycap plunger, said keycap being configured for upward and downward displacement;

resiliently deformable means engageable by said keycap plunger for yieldingly and deformably resisting downward displacement of said keycap plunger, said deformable means providing tactile feedback when deformed by the downward displacement of the keycap plunger; 5

first contact means supported on a substrate located beneath said keycap plunger;

second contact means supported by said deformable means for contactively engaging said first contact means pursuant to deformation of said deformable means; and 10

retaining means for guiding and limiting the downward displacement of said keycap plunger, and for providing audible feedback when said keycap has reached its downward displacement limit. 15

2. The switch structure of Claim 1 wherein said resiliently deformable means comprises an elastomeric switch button having a top that is engaged by said keycap plunger. 20

3. The switch structure of Claim 2 wherein said second contact means comprises a contact pad secured to the underside of the elastomeric dome.

4. The switch structure of Claim of Claim 3 wherein said second contact means comprises conductive traces on a printed circuit board. 25

5. The switch structure of Claim 4 wherein said retaining means comprises a retaining bezel which engages said keycap top to limit the downward displacement of said keycap plunger. 30

6. The switch structure of Claim 5 wherein said keycap, said retaining bezel, and said elastomeric switch button are configured to limit the downward displacement of said keycap plunger to avoid excessive force on the printed circuit board. 35

7. A pushbutton switch comprising:

a keycap having a keycap top and a keycap plunger configured for upward and downward displacement;

an elastomeric switch button engageable by downward displacement of said keycap plunger; 40

a conductive pattern supported on a printed circuit board beneath said elastomeric switch button;

a conductive pad on the underside of said elastomeric switch button for contactively engaging said conductive pattern pursuant to deformation of said elastomeric button switch; and 45

a retaining bezel for guiding and limiting the downward displacement of said keycap plunger to provide audible feedback and to prevent excessive force on the printed circuit board. 50





FIG. 3





FIG. 4





EUROPEAN SEARCH REPORT

EP 90 30 8425

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
Y	US-A-3 668 356 (KEKAS) * column 1, lines 47-75; column 2, lines 13-73; column 3, lines 27-34; figures 1A,B,2A-C * -- --	1-3,7	H 01 H 13/14
A		6	
Y	DE-U-8 401 137 (DEUTSCHE FERNSPRECHER) * page 5, first paragraph - page 7, last paragraph; figure * -- --	1-3,7	
A	DE-U-8 105 649 (SIEMENS) * whole document * -- --	1,7	
A	US-A-4 496 803 (SMITH) * column 3, lines 19-64; figures 1,6 * -- -- --	1,7	
The present search report has been drawn up for all claims			
Place of search		Date of completion of search	Examiner
Berlin		09 January 91	NIELSEN K G
<div>CATEGORY OF CITED DOCUMENTS</div> <div>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention</div> <div>E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document</div>			