



11) Publication number:

0 430 081 A3

(12)

EUROPEAN PATENT APPLICATION

21) Application number: 90122336.2

(51) Int. Cl.⁵: **H05H** 3/02

(22) Date of filing: 22.11.90

(30) Priority: 22.11.89 JP 301832/89

Date of publication of application: 05.06.91 Bulletin 91/23


Designated Contracting States:
AT BE CH DE DK ES FR GB GR IT LI LU NL SE

Date of deferred publication of the search report:

30.10.91 Bulletin 91/44

- 7) Applicant: EBARA CORPORATION 11-1, Haneda Asahi-cho Ohta-ku Tokyo(JP)
- Inventor: Nagai, Kazutoshi c/o Ebara Research Co. Ltd., 4-2-1, Honfujisawa Fujisawa-shi, Kanagawa-ken(JP)
- Representative: Wagner, Karl H. et al WAGNER & GEYER European Patent Attorneys Gewürzmühlstrasse 5 W-8000 München 22(DE)

- 54) Fast atom beam source.
- (57) A fast atom beam source comprises a evacuated cylinder, an anode set at one end or an intermediate portion of the cylinder, a cathode with fast atom emission orifices on it, and set at the other end of the cylinder, and a DC high voltage power supply for generating gas discharge by applying a high voltage between the anode and the cathode. A slit is provided on inside wall of the cylinder and a reservoir for oil or low-melting point metal is connected to the slit. A heater is set on the reservoir for vapourizing the oil or low-melting point metal. It supplies vapor of oil or low-melting point metal into the cylinder. Many ions of oil or low melting point metal are generated in glow through gas (the oil, vapor or the metal vapor) discharge by high voltage applying. They are accelerated towards the cathode. Then, they are neutralized after collision with the vapor of oil or low-melting point metal remaining near the cathode and are emitted from the orifices on the cathode. They constitute a fast atom beam. During such operation, the vapor of oil or low-melting point metal enters the cylinder through the slit and maintains an equilibrium condition of gas density in the cylinder. Thus, an automatic supply of the gas consumed as a fast atom beam is effected without any gas feeding device or any gas adjusting device.





EUROPEAN SEARCH REPORT

EP 90 12 2336

A		h indication, where appropriate,	Re	levant	CLASSIFICATION OF THE
Α		vant passages	to	claim	APPLICATION (Int. Ci.5)
	US-A-3 005 121 (J. GEOR * Columns 1-2; figure 1 *	GE)	1	1	H 05 H 3/02
Α	NUCLEAR INSTRUMENTS & METHODS IN PHYSICS F B33, nos 1-4, 2nd June 198 NL; F. SHIMOKAWA et al.: ' * Page 867; figure 1 *	8, pages 867-870, Amsterd	dam,		
Α	US-A-3 523 210 (M.P. ERN * Abstract; figures 1-2; claim -	•	1		
Α	US-A-4 328 667 (D.R. VAL * Figures 11,12; column 4, la paragraph 1 *		1		
А	US-A-4 516 052 (P.D. PRE * Column 4, lines 17-32; figu	· · · · · · · · · · · · · · · · · · ·	1		
					TECHNICAL FIELDS SEARCHED (Int. CI.5)
					H 05 H 3/00 H 01 J 27/00 H 05 H 1/00 H 01 J 37/00 F 03 H 1/00
	The present search report has b	een drawn up for all claims			
	Place of search Date of completion of		earch		Examiner
	The Hague	19 August 91			HULNE S.L.
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same catagory A: technological background O: non-written disclosure			E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding		