



11) Publication number:

0 507 070 A3

## EUROPEAN PATENT APPLICATION

(21) Application number: **92103073.0** 

(51) Int. Cl.5: **B30B** 1/32

② Date of filing: 24.02.92

(12)

30 Priority: 28.02.91 IT MI910523

43 Date of publication of application: 07.10.92 Bulletin 92/41

Designated Contracting States:
CH DE ES FR GB LI

Date of deferred publication of the search report: 09.12.92 Bulletin 92/50

71) Applicant: Brasca, Carlo
Via Puccini 13
I-20085 Locate di Triulzi (Milano)(IT)
Applicant: Brasca, Daniele

Via Puccini 13 I-20085 Locate di Triulzi (Milano)(IT)

Inventor: Brasca, Carlo Via Puccini 13

I-20085 Locate di Triulzi (Milano)(IT)

Inventor: Brasca, Daniele


Via Puccini 13

I-20085 Locate di Triulzi (Milano)(IT)

Representative: Modiano, Guido et al c/o Modiano & Associati S.r.l. Via Meravigli,
 16
 I-20123 Milano(IT)

- (54) Combined pneumatic-hydraulic press head with high actuation speed.
- (57) The combined pneumatic-hydraulic press head (1) includes a body (2) inside which a substantially cylindrical main chamber (3) is defined; the chamber (3) accommodates a main piston (4) and a secondary piston (5) so that they can slide along an axial direction (3a). The main piston (4) has a stem (4a) which protrudes from an axial end (6) of the main chamber (3), and the secondary piston (5) is spaced from the main piston (4) on the side opposite to the stem (4a). The two pistons (4,5) sealingly divide the main chamber (3) into three chambers: two end chambers (14,15), which can be connected to a source of compressed air or to the atmosphere in order to move the two pistons (4,5) along the axis (3a) of the main chamber (3) during the approach of the main stem (4a) or spacing motion with respect to the part to be treated (8), and an intermediate chamber (16) which contains a liquid. An actuation stem (19) is furthermore accommodated in the main chamber (3) and sealingly passes through the secondary piston (5). A partition (20) is arranged in the intermediate chamber (16), is rigidly fixed to the walls of the main chamber and is crossed by a passage (21) for the actuation stem (19). The press is actuated by pushing the actuation stem (19)

through the passage (21) toward the main piston (4) so as to increase the pressure in the region of the intermediate chamber (16) which is located between the main piston (4) and the partition (20).





## **EUROPEAN SEARCH REPORT**

EP 92 10 3073

EP-A-0 355 780 (E. R  * column 9, line 53 figures *  DE-A-2 017 007 (K. G  * claims; figure *  FR-A-2 384 977 (STOR MASCHINENFABRIK EMIL  * figure 1 *  GB-A-2 175 648 (G. S  * figures *  US-A-4 961 317 (M. W  * column 10, line 5 figures *	- column 10, line 25; EISEL) EN- UND SCHENKER AG) MEETS) OLFBAUER)	1,4-9, 14-15  2-3, 10-13  1,4-9, 14-15  1,5-9, 14-15	B30B1/32
figures *  DE-A-2 017 007 (K. G  * claims; figure *  FR-A-2 384 977 (STOR  MASCHINENFABRIK EMIL  * figure 1 *  GB-A-2 175 648 (G. S  * figures *  US-A-4 961 317 (M. W  * column 10, line 5	EISEL)  EN- UND SCHENKER AG)  MEETS)  CLFBAUER)	10-13 1,4-9, 14-15 1,5-9, 14-15	
* claims; figure *  FR-A-2 384 977 (STOR MASCHINENFABRIK EMIL * figure 1 *  GB-A-2 175 648 (G. S * figures *  US-A-4 961 317 (M. W * column 10, line 5	EN- UND SCHENKER AG) MEETS) OLFBAUER)	1,4-9, 14-15 1,5-9, 14-15	
* claims; figure *  FR-A-2 384 977 (STOR MASCHINENFABRIK EMIL * figure 1 *  GB-A-2 175 648 (G. S * figures *  US-A-4 961 317 (M. W * column 10, line 5	EN- UND SCHENKER AG) MEETS) OLFBAUER)	1,5-9, 14-15	
FR-A-2 384 977 (STOR MASCHINENFABRIK EMIL * figure 1 *  GB-A-2 175 648 (G. S * figures *  US-A-4 961 317 (M. W * column 10, line 5	SCHENKER AG) MEETS) OLFBAUER)	14-15	
MASCHINENFABRIK EMIL * figure 1 *  GB-A-2 175 648 (G. S * figures *  US-A-4 961 317 (M. W * column 10, line 5	SCHENKER AG) MEETS) OLFBAUER)	14-15	
* figures * US-A-4 961 317 (M. W * column 10, line 5	 OLFBAUER)	_	
* column 10, line 5	OLFBAUER) - column 11, line 8;	1.10	1
1 Igui es			TECHNICAL FIELDS
		10-13	B30B F15B
AKTIEBOLAGET)		2-3	1135
The present search report has bee	n drawn up for all claims		
Place of search HE HAGUE	Date of completion of the search OS OCTOBER 1992		Examiner VOUTSADOPOULOS K.
ATEGORY OF CITED DOCUMENT cularly relevant if taken alone cularly relevant if combined with anoth	T: theory or princip E: earlier patent do after the filing d are D: document cited	ole underlying the cument, but publicate in the application	invention ished on, or
	EP-A-0 023 030 (E. R * the whole document FR-A-995 204 (ALLMÄN AKTIEBOLAGET) * the whole document  The present search report has bee Place of search HE HAGUE  ATEGORY OF CITED DOCUMENT icularly relevant if taken alone	EP-A-0 023 030 (E. RAPP)  * the whole document *  FR-A-995 204 (ALLMÄNNA SVENSKA ELEKTRISKA AKTIEBOLAGET)  * the whole document *   The present search report has been drawn up for all claims  Place of search HE HAGUE  Date of completion of the search HE HAGUE  CATEGORY OF CITED DOCUMENTS  CATEGORY OF CATEG	EP-A-0 023 030 (E. RAPP)  * the whole document * FR-A-995 204 (ALLMÄNNA SVENSKA ELEKTRISKA 2-3  AKTIEBOLAGET)  * the whole document *  The present search report has been drawn up for all claims  Place of search HE HAGUE  Date of completion of the search O8 OCTOBER 1992  CATEGORY OF CITED DOCUMENTS  cularly relevant if taken alone cularly relevant if combined with another ment of the same category nological background written discoure  E: earlier patent document, but publication D: document cited in the application L: document cited for other reasons mological background written discoure  E: member of the same patent family