



(1) Publication number:

0 551 930 A3

EUROPEAN PATENT APPLICATION

(21) Application number: 93104130.5

(51) Int. Cl.5: **B25B** 15/00

2 Date of filing: 03.11.89

③ Priority: 14.11.88 US 270000

Date of publication of application:21.07.93 Bulletin 93/29

© Publication number of the earlier application in accordance with Art.76 EPC: **0 369 655**

Designated Contracting States:
AT BE CH DE ES FR GB GR IT LI LU NL SE

Date of deferred publication of the search report: 18.08.93 Bulletin 93/33 Applicant: Black & Decker Inc. Drummond Plaza Office Park 1423 Kirkwood Highway Newark Delaware 19711(US)


Inventor: Chaconas, Peter Constantine 4340 Butler Road Glyndon, Maryland 21071(US)

Representative: Wetters, Basil David Peter et al Emhart Patents Department Lyn House 39 The Parade Oadby, Leicester LE2 5BB (GB)

(54) Screwdriver bit for phillips-head fasteners.

(57) A modified Phillips-type screwdriver bit is disclosed that is fully compatible with a standard Phillips-head fastener, and is designed to significantly increase the level of torque that can be applied to the fastener while at the same time substantially reducing the cam-out forces normally produced by a standard Phillips screwdriver-bit. These results are accomplished by the use of a driver having a cross-shaped recess formed in the head thereof, and having associated therewith an axis and including a bit portion symmetrical about any plane containing the axis of the driver and adapted for insertion into said recess which comprises radially symmetrical wing means having generated side surfaces and defining roots therebetween for rotationally driving said fastener on said side surfaces in the same manner in both rotational directions. Preferably said wing means comprise four equally radially spaced bit wings defined by generated side surfaces that in turn define an included angle between adjoining bit wings that progressively increases from a first predetermined angle at the base of said bit wings to a second greater predetermined angle at an axially spaced distance therefrom. The radially outwardly facing surfaces of said bit wings may be tapered toward a common point at an angle relative to the axis of said bit portion substantially equal to the

Phillips-standard wing angle. The roots of said bit portion are preferably oriented relative to said bit axis at an angle substantially equal to the Phillips-standard root angle.



EUROPEAN SEARCH REPORT

ΕP 93 10 4130

Application Number

Category	Citation of document with in of relevant pa	ndication, where appropriate, ssages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
(FR-A-2 469 250 (P.D	•	1-4,10,	B25B15/00
(* page 3, line 11 -	line 14; figures *	7-9,12, 13,16	
'	US-A-3 658 105 (J.B. * the whole documen	•	8,9,12, 13	
	the whole document "			
(US-A-2 389 129 (J.H * page 3, left colu figure 7 *	.BISHOP) mn, line 10 - line 22;	7,16	
(GB-A-446 714 (PHILL * page 3, line 51 -	IPS SCREW COMPANY) line 57; figure 3 *	1,10	
(TEAD & COMPANY LIMITED) line 53; figure 3 *	1,10	
A	US-A-4 625 598 (F.WOLFRAM) * abstract; claim 1; figures 8-11 * * column 2, line 64 - column 3, line 13 *		1	
				TECHNICAL FIELDS SEARCHED (Int. Cl.5)
\	US-A-2 764 197 (C.T	.TORRESEN)	5,6,14, 15	B25B
	* figure 3 *			
;				
	The present search report has b	een drawn up for all claims		
		Date of completion of the search 29 JUNE 1993		Examiner MAJERUS H.M.P.
X : par	CATEGORY OF CITED DOCUMENT ticularly relevant if taken alone	E : earlier patent do after the filing d	cument, but publ late	e invention lished on, or
Y: par	ticularly relevant if combined with and ument of the same category	ther D: document cited L: document cited	in the application for other reasons	
A: tec	hnological background n-written disclosure	& : member of the s		

EPO FORM 1503 03.82 (P0401)