

19



Europäisches Patentamt
European Patent Office
Office européen des brevets



11 Publication number:

0 564 719 A1

12

EUROPEAN PATENT APPLICATION

21 Application number: **92201034.3**

51 Int. Cl.⁵: **C11D 1/08**

22 Date of filing: **10.04.92**

43 Date of publication of application:
13.10.93 Bulletin 93/41

84 Designated Contracting States:
**AT BE CH DE DK ES FR GB GR IT LI LU NL PT
SE**

71 Applicant: **THE PROCTER & GAMBLE
COMPANY**
One Procter & Gamble Plaza
Cincinnati Ohio 45202(US)

72 Inventor: **Vanweelssenaers, Noel**
Reigerstraat 12
B-1840 Londerzeel(BE)
Inventor: **Lievens, Luc**
Hugo Lefevrestraat 40
B-9300 Aalst(BE)

74 Representative: **Canonici, Jean-Jacques et al**
**Procter & Gamble European Technical
Center N.V.**
Temselaan 100
B-1853 Strombeek-Bever (BE)

54 **Process for manufacture of a high active detergent composition containing succinic acid.**

- 57 A process for making a concentrated liquid detergent composition comprising the steps of :
- i) mixing succinic anhydride, water and an alkaline catalyst, wherein the ratio of succinic anhydride to water is at least 4:1,
 - ii) allowing an exothermic hydrolysis reaction to take place in a buffer tank ,and
 - iii) mixing the resulting highly active, partly neutralised succinic acid with other detergent ingredients

EP 0 564 719 A1

Background

Succinic acid and its salts are known ingredients of detergent compositions. They are used for their surface active and hydrotropic properties as well as calcium and magnesium binding capacity.

They are easily processed directly into a detergent liquid or slurry by in situ hydrolysis of the corresponding succinic anhydride, and subsequent neutralisation.

This hydrolysis typically requires a considerable excess of water and the presence of solvents (eg. lower alcohols), in an alkaline environment in order to make the hydrolysis reaction move rapidly to completion.

There is now a trend to more concentrated detergents containing very little water. As the water level is decreased in the hydrolysis step the rate of reaction decreases and undesirable side reactions between the anhydride and the solvents forming, for example esters, start to become significant.

Various prior art has dealt with detergent compositions containing succinic acid. These applications are in general, dilute.

GB-A-2 049 723, published December 31, 1980, discloses a composition containing partly neutralised succinic acid with one of its salts such that the pH is in the range from 5.5 to 8.0. It describes liquid compositions containing 3%-50% by weight of the partly neutralised succinic acid.

EP 0 028 850, published May 5, 1981, discloses a liquid detergent composition containing succinates and a low level of alkyl benzene sulphonate, for improved storage stability. The application mentions the neutralisation of the acid or anhydride in situ, but there is no mention of high active compositions.

GB 1 285 582, published August 16, 1972, discloses a composition substantially containing 25-90% succinic acid, which may be derived from the anhydride, and 10-75% nonionic surfactant. There is no disclosure of a suitable process for making such compositions.


However, none of the prior art deals with the problem of making a highly concentrated solution of succinic acid which is suitable for further processing into a concentrated liquid detergent. There is a need for a process of hydrolysis of succinic anhydrides which can be carried out effectively in an environment in which very little water is present.

The present invention provides a new process for hydrolysis of the succinic anhydride to yield a solution of at least 85% by weight of partly neutralised succinic acid. The process can be carried out in situ, continuously or batch-wise, and offers a flexible process for making a concentrated liquid detergent.

Summary of the Invention

A process for making a concentrated liquid detergent composition which comprises

(A) succinic acid



where R is an alk(en)yl moiety with C10-C20 X,Y are independently H,Na,K, alkanolamine and (B) water,

characterised in that succinic anhydride, water and an alkaline catalyst are:

- i) mixed in a ratio of succinic anhydride to water (B) of not less than 4:1 in order to start an exothermic hydrolysis reaction
- ii) held in a buffer tank, and
- iii) mixed with other detergent ingredients.


Detailed Description of the Invention

The present invention provides a process for the hydrolysis of succinic anhydride to succinic acid in the presence of a small excess of water. The process takes place in the presence of an alkali which catalyses the reaction and partly neutralises the succinic acid. Firstly the succinic anhydride, water and alkali are intimately mixed, either by passing through static mixers, or, preferably, in a high shear mixer. The mixture is then stored in a buffer tank (which may be in-line in a continuous process) until the exothermic hydrolysis reaction is substantially completed. The resulting high active partly neutralised succinic acid may then be

stored or transferred directly into a batch tank or continuous process for further processing to a concentrated liquid detergent.

THE SUCCINIC ANHYDRIDE

Any succinic anhydride of the general formula:



is suitable for use in the present invention. The choice of R will be made by the detergent formulator.


A particularly preferred chain is when:

R is $\text{CH}_3-(\text{CH}_2)_n-\text{CH}=\text{CH}-\text{CH}_2-$ and $n=8-10$ or mixtures thereof.

THE ALKALI

Any suitable alkali may be used including sodium hydroxide, potassium hydroxide, monoethanolamine and ammonia. Preferred are sodium hydroxide and potassium hydroxide. The ratio of hydroxide present : hydroxide needed for stoichiometric neutralisation, should be 0.15 or less.

The alkali may be added to the succinic acid in the form of a solution (typically 50% aqueous solution of either sodium or potassium hydroxide). Extra water may also be added in order to ensure complete hydrolysis by the following reaction:



However total water which is present (both added and with the aqueous alkali) should be limited in order to avoid diluting the final composition, and to avoid an excessively long reaction time. It has been found that the ratio of succinic anhydride to water should be not less than 4:1 by weight.

THE HYDROLYSIS PROCESS

The reactants are brought together and mixed, preferably in a high shear mixer. Suitable mixers include Pentax (trade name), supplied by Bran and Luebbe, Germany; Dispax (trade name), supplied by Janke and Kunkel, and mixers supplied by Karg and Fryma. This mixture is then pumped into buffer tank where the hydrolysis reaction will proceed. Preferably the buffer tank already contains an amount of succinic acid which itself promotes rapid hydrolysis of the mixture. In a most preferred embodiment, the buffer tank is in-line in a continuous process and gives a residence time sufficient for hydrolysis to be substantially completed. In this embodiment of the invention the buffer tank contains at all times a mixture of succinic acid, water, alkali and partly neutralised succinic anhydride. The hydrolysis reaction is exothermic, and the temperature rises, preferably to about 90°C .

The buffer tank should be gently stirred or agitated in order to keep the reactants mixed. In the case of a continuous process the buffer tank should be designed to give a residence time of from 2 to 30 minutes, preferably from 5 to 20 minutes.

The high active succinic acid made according to the above ratios and process has a pH of less than 5.5, preferably about pH4.5 when it is diluted to a 0.5% aqueous solution. Furthermore, after hydrolysis the ratio of partly neutralised succinic acid to water will not be less than about 6:1 by weight.

START-UP AND SHUT-DOWN PROCEDURE

When a continuous process is in use as described hereinabove, the process is shutdown by firstly closing the supply of water and alkali to the mixer. The supply of succinic anhydride is allowed to continue until all water and alkali have been flushed through the mixer then this supply is also shut-down. This procedure ensures that no hydrolysis continues in the mixer whilst not in use.

Preferably not all of the succinic acid is flushed through the buffer tank. This means that when the supplies of succinic anhydride, water and alkali are switched on for start-up, there is still some acid in the buffer tank to "seed" the hydrolysis reaction.

During the period that the process is not operating, the buffer tank should be maintained at an elevated temperature (typically 60-80 °C) in order to prevent solidification of the succinic acid/anhydride mix.

FURTHER PROCESSING

The highly active, partly neutralised succinic acid made by the present invention may subsequently be added to other detergent ingredients including surfactants, builders, chelants, enzymes and softening clays, in order to make a finished liquid detergent composition. An example of this is given hereinbelow.

Preferably the high active succinic acid is mixed with compatible detergent ingredients which allow its temperature to be reduced below 60 °C, before it is mixed with lower alcohols. Such short chain alcohols may be present in the final formulation as solvents, examples include ethanol, propanol, propane diol and glycerol. If the succinic acid and such solvents are present at temperatures in excess of 60 °C, then undesirable side products such as esters may be formed. An intermediate composition may be formed which is a stable, pumpable liquid at temperatures below 60 °C. This intermediate composition preferably consists of at least 40% by weight of partly neutralized succinic acid.

Example 1

Dodecyl/tetradecyl succinic anhydride	300 kg/hour
Potassium hydroxide (50% aq. soln.)	20 kg/hour
Water	40 kg/hour

Succinic anhydride, potassium hydroxide solution and water are supplied at ambient temperature from metering pumps at the rates described above, into a Pentax KMF8 (Trade Mark) high shear mixer.

This mixture is transferred directly from the outlet port of this mixer into the bottom of a buffer tank. The buffer tank has a diameter of about 0.4m and a height of about 0.8m, giving a residence time of about 17 minutes. The temperature in the buffer tank rises to 92 °C as the exothermic hydrolysis reaction takes place.

The reacted material leaving from the top of the buffer tank has a composition of:

Dodecyl/tetradecyl succinic acid (partly neutralised)	90%
Water	10%

and, when diluted to give a aqueous solution of 0.5% by weight, has a pH of 4.5.

In this example, the high active, partly neutralised succinic acid is mixed with a nonionic surfactant in the ratio of 1:1. The surfactant is supplied at ambient temperature and the resulting mix has a temperature of 55 °C. The resulting mixture is a stable, pumpable intermediate composition at this temperature.


A finished composition is made by mixing the acid/ surfactant mixture with other detergent ingredients as follows (all given as % by weight):

Succinic acid/nonionic surfactant	18
Ethanol & 1,2 propane diol	12
Sodium hydroxide	9*
Alkyl benzene sulphonic acid	12
Sodium alkyl sulphate	2
Citric acid	7
Enzymes and minors	1
Miscellaneous (suds suppressor, perfume etc.)	1
Water	to balance to 100%

*Level of sodium hydroxide may be varied in order to give finished pH8

Claims

1. A process for making a concentrated liquid detergent composition which comprises
(A) succinic acid



where R is an alk(en)yl moiety with C10-C20

X,Y are independently H,Na,K, alkanolamine

and (B) water,

characterised in that succinic anhydride, water and an alkaline catalyst are:

- i) mixed in a ratio of succinic anhydride to water (B) of not less than 4:1 in order to start an exothermic hydrolysis reaction
- ii) held in a buffer tank, and
- iii) mixed with other detergent ingredients.

2. A process according to claim 1 which is continuous and in which the reactants have a residence time of at least 5 minutes in the buffer tank.

3. A process according to claim 1 or 2 characterised in that the alkaline catalyst is sodium hydroxide or potassium hydroxide, in a ratio of:

hydroxide present : hydroxide needed for stoichiometric neutralisation,
of 0.15 or less.

4. A process according to any of claims 1 to 3 where:

R is CH₃-(CH₂)_n-CH=CH-CH₂- and n=8-10 or mixtures thereof.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 92 20 1034

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
Y	SU-A-130 040 (R.W.OBLOSHENKO ET AL.) * page 1, formula * * german translation * ---	1	C11D1/08
Y,D	EP-A-0 028 850 (UNILEVER NV) * page 4, line 8 - line 11 * * claims * ---	1	
A,D	GB-A-2 049 723 (KAO SOAP CO LTD) * page 1, line 40 * * page 2, line 4 - line 12 * * claims * ---	1	
A	PATENT ABSTRACTS OF JAPAN vol. 10, no. 4 (C-322)(2061) 9 January 1986 & JP-A-60 163 838 (KAO SEKKEN KK) 26 August 1985 * abstract * -----	1	
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			C11D C07C C07D
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 11 NOVEMBER 1992	Examiner PELLI-WABLAT B.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			