

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets




(11) Publication number:

**0 574 998 A1**

(12)

**EUROPEAN PATENT APPLICATION**(21) Application number: **93201683.5**(51) Int. Cl.<sup>5</sup>: **A47L 9/28**(22) Date of filing: **11.06.93**(30) Priority: **19.06.92 EP 92201787**(43) Date of publication of application:  
**22.12.93 Bulletin 93/51**(84) Designated Contracting States:  
**DE ES FR GB IT SE**(71) Applicant: **PHILIPS ELECTRONICS N.V.**  
**Groenewoudseweg 1**  
**NL-5621 BA Eindhoven(NL)**(72) Inventor: **Dekker, Jan Hendrik, c/o Int.**  
**Octrooibureau B.V.**  
**Prof. Holstlaan 6**  
**NL-5656 AA Eindhoven(NL)**  
Inventor: **Damstra, Ate Klaas, c/o Int.**  
**Octrooibureau B.V.**  
**Prof. Holstlaan 6**  
**NL-5656 AA Eindhoven(NL)**(74) Representative: **Schoonheijm, Harry Barend et al**  
**INTERNATIONAAL OCTROOIBUREAU B.V.**  
**Prof.Holstlaan 6**  
**NL-5656 AA Eindhoven (NL)**(54) **Vacuum cleaner and suction tube for use with a vacuum cleaner.**

(57) A vacuum cleaner comprises a housing (100) provided with an electric motor (110) and with an electronic circuit (120) for controlling the electric motor (110), which housing (100) is constructed for the connection of a suction tube (200) with a remote control circuit (210) for controlling the electronic circuit (120), the electronic circuit (120) being adapted to control the electric motor (110) both in the presence and in the absence of the suction tube (200).

**FIG.2****EP 0 574 998 A1**

The invention relates to a vacuum cleaner comprising a housing provided with an electric motor and with a electronic circuit for controlling the electric motor, which housing is constructed for the connection of a suction tube with a remote control circuit for controlling the electronic circuit.

The invention also relates to a suction tube for use with such a vacuum cleaner.

Such a vacuum cleaner is suitable for general domestic use.

Such a vacuum cleaner is commercially available from Philips Electronics N.V. under the type number HR 6780 at the time of filing of the present document. The relevant commercially available vacuum cleaner comprises a suction tube with a remote control circuit adapted to switch on/off the electric motor of the vacuum cleaner and an electric motor of a brush, which brush can be fitted onto a suction nozzle forming part of the suction tube.

A drawback of such a vacuum cleaner is that the electric motor of the vacuum cleaner cannot be switched on/off when the suction tube provided with the remote control circuit is not coupled to the vacuum-cleaner housing.

It is an object of the invention to provide a vacuum cleaner which can be switched on when the suction tube is not coupled to the housing.

A vacuum cleaner in accordance with the invention is characterised in that the electronic circuit is adapted to control the electric motor both in the presence and in the absence of the suction tube. With the relevant circuit constructed in accordance with the invention a vacuum cleaner is obtained which has several advantages in comparison with the above-mentioned commercially available vacuum cleaner. A first advantage of the circuit constructed in accordance with the invention is that a clogged suction tube can be coupled to the vacuum-cleaner housing in a reverse manner. In this way the suction tube can be unclogged. A second advantage of the circuit constructed in accordance with the invention is that a defect of the remote control circuit of the suction tube does not render the vacuum cleaner unserviceable. A third advantage of the circuit constructed in accordance with the invention is that the vacuum cleaner can be provided with a connection to which the suction tube can be coupled to provide a blower function.

An embodiment of a vacuum cleaner in accordance with the invention is characterised in that the housing has a first and a second supply voltage terminal, a conduction path *via* the suction tube is established between the electronic circuit and the first supply voltage terminal when the suction tube is present, and a conduction path *via* the housing is established between the electronic circuit and the first supply voltage terminal when the suction

tube is absent. In the present embodiment a supply voltage appearing on the supply voltage terminals is supplied indirectly or directly to the electronic circuit depending upon the presence or absence of the suction tube. In the present embodiment the indirect supply is effected through the conduction path *via* the suction tube and the direct supply is effected through the conduction path *via* the housing. Switching over between the relevant conduction paths is achieved in a simple way when the housing and the suction tube are coupled by means of a coupling comprising at least one electrical connector which mechanically provides the conduction path *via* the suction hose when the suction tube is present and the conduction path *via* the housing when the suction tube is absent.

An embodiment of a vacuum cleaner in accordance with the invention is characterised in that a conduction path *via* the housing is established between the electronic circuit and the first supply voltage terminal when the suction tube is present. The present embodiment is advantageous in particular because the electronic circuit is coupled directly to the supply voltage terminals both when the suction tube is present and when it is absent. As a result of the direct coupling the electronic circuit is constantly supplied with the supply voltage from the supply voltage terminals, the conduction path *via* the suction tube not being used as a power-supply line but as a monitoring line. By means of the monitoring line the electronic circuit is informed whether the suction tube is present or absent. If the conduction path *via* the suction tube is used as a monitoring line the direct coupling reduces the likelihood of faults in the electronic circuit, in particular when the fault is caused by a supply voltage failure.

An embodiment of a vacuum cleaner in accordance with the invention is characterised in that the electronic circuit comprises a subcircuit for detecting the presence of the suction tube. In the embodiments described before the present embodiment the electronic circuit need not comprise the subcircuit because the object of the invention can be achieved, for example, by the mechanical switching means provided in the coupling. However, the electronic circuit comprising the subcircuit can have a further advantage. To visualise the detection the relevant embodiment may be characterised further in that the housing comprises a display, which display is coupled to the electronic circuit to indicate the presence and the absence of the suction tube, the housing provided with the display having the further advantage that a defect of the coupling between the housing and the suction tube can be detected. The display may then indicate the absence of the suction tube although the coupling has been established.

A suction tube for use with a vacuum cleaner in accordance with the invention is characterised in that the remote control circuit comprises means for detecting the presence or absence of the suction tube. The relevant means are capable not only of indicating the presence of the suction tube when the electric motor of the vacuum cleaner has been switched off by means of the remote control circuit but also of indicating the absence of the suction tube when the suction tube is disconnected from the housing, for example as a result of a coupling defect, in the case of a switched-on electric motor. Without the relevant means the design of the electronic circuit is the decisive factor with respect to the detection of a disconnected suction tube.

An embodiment of a suction tube for use with a vacuum cleaner in accordance with the invention is characterised in that said means comprise a first and a second resistor, the detection of the presence or absence of the suction tube by the electronic circuit being based on a difference in resistance value. This embodiment may be characterised further in that the remote control circuit comprises a switch which in a first position is capable of coupling the first supply voltage terminal and the electronic circuit *via* the first resistor, and in a second position is capable of coupling the first supply voltage terminal and the electronic circuit *via* the second resistor. As a result of the difference in resistance the first and the second resistor cause a difference in a voltage drop produced across the resistors, the detection by the electronic circuit being based on this difference.

The above and other (more detailed) features of the invention will be described more elaborately with reference to the accompanying drawings, in which

Figure 1A shows a prior-art vacuum cleaner,

Figure 1B shows an electronic circuit arrangement of a prior-art vacuum cleaner,

Figure 2 shows an electronic circuit arrangement for a vacuum cleaner in accordance with the invention, and

Figure 3 shows a modified electronic circuit arrangement for a vacuum cleaner in accordance with the invention.

In these Figures like parts bear the same reference numerals.

Figure 1A shows a prior-art vacuum cleaner. The vacuum cleaner comprises a housing 100 accommodating an electric motor 110 and an electronic circuit 120 for controlling the electric motor 110, and a suction tube 200 connected to the housing 100 and provided with a remote control circuit 210 for controlling the electronic circuit 120. For controlling the electronic circuit 120 the suction tube 200 has been provided with electrical wiring which extends from the remote control circuit 210

to the housing 100 of the vacuum cleaner, the suction tube 200 and the housing 100 being coupled to one another by means of a coupling provided by electrical connectors. In the housing 100 wiring has been provided from the coupling to the electronic circuit 120 and the electric motor 110.

Figure 1B shows an electronic circuit arrangement of a prior-art vacuum cleaner, for example the vacuum cleaner which is commercially available from Philips Electronics N.V. under the type number HR 6780 at the time of filing of the present document. The electronic circuit arrangement comprises a part accommodated in the housing 100 and comprising the electric motor 110 and the electronic circuit 120, and a part accommodated in the suction tube 200 and comprising the remote control circuit 210. The electronic circuit 120 comprises a control circuit 121 and a triac 122, the control circuit 121 being adapted to control the triac 122 for the purpose of controlling the electric motor 110, and the coupling between the housing 100 and the suction tube 200 comprises two connectors 141 and 142 which form part of the electronic circuit 120 and two connectors 221 and 222 which form part of the remote control circuit and cooperate with the first-mentioned connectors. In addition to the control circuit 121, the triac 122 and the two connectors 141 and 142 the electronic circuit 120 comprises a first supply voltage terminal 131 and a second supply voltage terminal 132, which supply voltage terminals are coupled to a mains supply lead, not shown. The remote control circuit 210 accommodated in the suction tube 200 and the control circuit 121 are serially coupled between the supply voltage terminals 131 and 132 and the electric motor 110 and the triac 122 are also serially coupled between these terminals, the control circuit 121 being switched on/off by the remote control circuit 210 when the suction tube 200 is present. For the purpose of switching on/off the remote control circuit comprises a switch 211 coupled between two connectors 221 and 222. Since the control circuit 121 is powered *via* the remote control circuit 210 the electric motor 110 cannot be switched on when the suction tube 200 with the remote control circuit 210 is not coupled to the housing 100.

Figure 2 shows an electronic circuit arrangement for a vacuum cleaner in accordance with the invention, which arrangement differs from that in Fig. 1B in that the supply voltage terminal 131 is connected to the control circuit 121 *via* a conduction path which extends through the housing 100. In comparison with that shown in Fig. 1B the arrangement shown in Fig. 2 has the advantage that the control circuit 121 can switch on the electric motor 110 in the absence of the suction tube. The control circuit 121, which forms part of the elec-

tronic circuit 120, is supplied directly with a supply voltage appearing on the supply voltage terminals 131 and 132, while the conduction path which in Fig. 2 extends between the supply voltage terminal 131 and the control circuit 121 *via* the suction tube is a monitoring path, the direct supply being advantageous in order to preclude faults in the electronic circuit. The control circuit 121 is preferably adapted to receive a logic "high" signal if the vacuum cleaner is switched off, and a logic "low" signal if the vacuum cleaner is switched on. This preference results from the fact that in the absence of the suction tube the control circuit 121 receives a logic "low" signal, so that on the basis of the applied signal the vacuum cleaner is switched on. If the control circuit 121 comprises a further switch the relevant switch can take over the on/off function of the remote control circuit in the absence of the suction tube 200. The control circuit 121 may also comprise a known motor control device with a plurality of power settings.

Fig. 3 shows a modification of the electronic circuit arrangement for a vacuum cleaner in accordance with the invention. In comparison with the arrangement shown in Fig. 2 the modification has the advantage that the electronic circuit detects whether the suction tube is present. In order to obtain this advantage the switch 211 of the remote control circuit 210 has a first position, in which a first conduction path between the supply voltage terminal 131 and the control circuit 121 is established, and a second position, in which a second conduction path between the supply voltage terminal 131 and the control circuit 121 is established, and the remote control circuit has a first resistor 212 included in the first conduction path and a second resistor 213 included in the second conduction path. Both in the first position and in the second position the resistors 212 and 213 form part of a voltage divider, for which voltage divider the electronic circuit comprises a resistor 123 coupled between the connector 142 and the supply voltage terminal 132. In the first position of the switch 211 a voltage is applied to the control circuit 121 by means of the voltage divider formed by the resistors 212 and 123, as a result of which voltage the electric motor 110 is switched on. In the second position of the switch 211 a voltage is applied to the control circuit 121 by means of the voltage divider formed by the resistors 213 and 123, as a result of which voltage the electric motor 110 is switched off. In order to obtain a difference between the voltages switching over of the switch 211 should be accompanied by a resistance variation and on/off function of the electric motor 110 is determined by a resistance variation, which resistance variation is detected by the subcircuit 124 of the control circuit 121. For the purpose of detection

the subcircuit 124 may be realised, for example, by means of a comparator circuit. Summarizing, by means of the electronic circuit 120 shown in Fig. 3 and the remote control circuit 210 in Fig. 3 the control circuit 121 can detect whether the suction tube 200 is present and whether the electric motor 110 should be switched on. A further difference between the arrangement shown in Fig. 3 and that shown in Fig. 2 is constituted by the display 150 which forms part of the electronic circuit 120 and which is driven by the control circuit 121 to indicate the presence or absence of the suction tube 200. The display 150 has the advantage that a defect of the remote control circuit 210 can be detected simply. Indeed, in spite of the coupling established between the housing 100 and the suction tube 200 the display 150 may indicate that the suction tube 200 is absent. In addition to said difference Fig. 3 shows how an electric motor of a brush can be controlled, which brush can be fitted onto a nozzle forming part of the suction tube 200. In order to control this electric motor the remote control circuit 210 comprises a connector 223, which forms part of the coupling and which cooperates with a connector 143 included in the electronic circuit, a switch 214, and two connectors 213 and 232. If the switch 211 is in the first position the electric motor of the brush belonging to the suction tube 200 can be switched on/off by means of the switch 214, the electric motor being connected between the two connectors 213 and 232. The use of the brush is known from the vacuum cleaner which is commercially available from Philips Electronics N.V. under the type number HR 6780 at the time of filing of the present document.

The invention is not limited to the electronic circuit arrangements shown herein. Within the scope of the invention several modifications are conceivable to the expert. For example, as already stated in the present document, the vacuum cleaner may be provided with a coupling comprising electrical connectors, which coupling provides mechanical switching over between a supply line extending through the housing and a supply line extending through the suction tube. However, in the present case the electronic circuit is not constantly supplied with a supply voltage appearing across the supply voltage terminals. Moreover, the vacuum cleaner may be provided with a coupling which allows a suction tube without a remote control circuit to be connected, the electric motor being switched on/off by means of a switch forming part of the electronic circuit.

## Claims

1. A vacuum cleaner comprising a housing (100) provided with an electric motor (110) and with

an electronic circuit (120) for controlling the electric motor (110), which housing (100) is constructed for the connection of a suction tube (200) with a remote control circuit (210) for controlling the electronic circuit (120), characterised in that the electronic circuit (120) is adapted to control the electric motor (110) both in the presence and in the absence of the suction tube (200).

5

10

2. A vacuum cleaner as claimed in Claim 1, characterised in that the housing (100) has a first and a second supply voltage terminal (131, 132), a conduction path *via* the suction tube (200) is established between the electronic circuit (120) and the first supply voltage terminal (131) when the suction tube (200) is present, and a conduction path *via* the housing (100) is established between the electronic circuit (120) and the first supply voltage terminal (131) when the suction tube (200) is absent.

15

20

3. A vacuum cleaner as claimed in Claim 2, characterised in that a conduction path *via* the housing (100) is established between the electronic circuit (120) and the first supply voltage terminal (131) when the suction tube (200) is present.

25

4. A vacuum cleaner as claimed in Claim 3, characterised in that the electronic circuit (120) comprises a subcircuit (124) for detecting the presence of the suction tube (100).

30

5. A vacuum cleaner as claimed in Claim 4, characterised in that the housing (100) comprises a display (150), which display (150) is coupled to the electronic circuit (120) to indicate the presence and the absence of the suction tube (200).

35

40

6. A suction tube for use with a vacuum cleaner as claimed in Claim 5, characterised in that the remote control circuit (210) comprises means (212, 213) for detecting the presence or absence of the suction tube (200).

45

7. A suction tube as claimed in Claim 6, characterised in that said means comprise a first and a second resistor (212, 213), the detection of the presence or absence of the suction tube (200) by the electronic circuit (120) being based on a difference in resistance value.

50

8. A suction tube as claimed in Claim 7, characterised in that the remote control circuit (220) comprises a switch (211) which in a first position is capable of coupling the first supply

55

voltage terminal (131) and the electronic circuit (120) *via* the first resistor (212), and in a second position is capable of coupling the first supply voltage terminal (131) and the electronic circuit (120) *via* the second resistor (213).





FIG.1




FIG. 2




FIG. 3



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number

EP 93 20 1683

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
A	PATENT ABSTRACTS OF JAPAN vol. 14, no. 109 (C-695)19 December 1990 & JP-A-13 14 539 ( MATSUSHITA ELECTRIC IND CO LTD ) * abstract *	1	A47L9/28
A	--- PATENT ABSTRACTS OF JAPAN vol. 14, no. 109 (C-695)18 December 1989 & JP-A-13 13 033 ( TOKYO ELECTRIC CO LTD ) * abstract *	1	
A	--- US-A-4 987 637 (L.A. ZUMMER) * the whole document *	1	
A	--- EP-A-0 136 357 (MATSUSHITA ELECTRIC IND CO LTD) * page 8, line 6 - page 14, line 4; figures 5-9 *	1	
A	--- DE-A-3 442 583 (C. VOHRER) * abstract *	1	
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			A47L
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 27 AUGUST 1993	Examiner M. VANMOL
<b>CATEGORY OF CITED DOCUMENTS</b> X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... & : member of the same patent family, corresponding document			