



⑫

EUROPEAN PATENT APPLICATION

⑬ Application number: 93870075.4

⑮ Int. Cl. 5: C11D 17/06, C11D 3/37,
C11D 3/22

⑯ Date of filing: 30.04.93

⑰ Date of publication of application:
02.11.94 Bulletin 94/44

⑲ Designated Contracting States:
AT BE CH DE DK ES FR GB GR IE IT LI LU NL
PT SE

⑳ Applicant: THE PROCTER & GAMBLE
COMPANY
One Procter & Gamble Plaza
Cincinnati Ohio 45202 (US)

㉑ Inventor: Donoghue, Scott John
52 Glenthorn Road
Jesmond, Newcastle upon Tyne NE12 9HN
(GB)
Inventor: Fitzgibbon, Kay Emma
11 Ennismore Court,
Station Road
Benton, Newcastle upon Tyne NE12 9PF
(GB)
Inventor: France, Paul Amaat Raymond

Gerard

Patrijzenlaan 36, Bus 2
B-3010 Kessel-Lo (BE)
Inventor: Hall, Robin Gibson
192 Cartington Terrace
Heaton, Newcastle upon Tyne NE6 (GB)
Inventor: Wilkinson, Carole Patricia Denise
rue du Prévot 95
B-1050 Ixelles (BE)
Inventor: York, David William
10 Ladywell Way
Ponteland, Newcastle upon Tyne (GB)
Inventor: Schmitt, John Christian
Talsperrenstrasse 66
D-5350 Euskirchen, Kirchheim (DE)

㉒ Representative: Canonici, Jean-Jacques et al
Procter & Gamble European Technical
Center N.V.
Temselaan 100
B-1853 Strombeek-Bever (BE)

㉓ Structuring liquid nonionic surfactants prior to granulation process.

㉔ A process for making a granular laundry detergent component or composition having a bulk density of at least 650 g/l, by dissolving a structuring agent in a nonionic surfactant, said structuring agent comprising a polymer, to form a pumpable premix and finely dispersing said premix with an effective amount of powder at a given operating temperature wherein the premix has a viscosity of at least 350 mPas when measured at said operating temperature and at a shear rate of 25s⁻¹. Preferred structurants comprise polymers having more than one functional hydroxyl group, especially polyvinyl alcohols, polyhydroxyacrylic acid polymers, and polymers such as polyvinyl pyrrolidone and PVNO, as well as sugars, artificial sweeteners and their derivatives. The premix is then processed into a granular detergent by any suitable process. Fine dispersion mixing, agglomeration, or spraying the premix onto a granular base product are preferred.

Another aspect of the present invention is components or compositions comprising nonionic surfactant and structuring agents.

Background of the Invention

The present invention relates to improving storage stability and physical properties of granular detergents which are rich in nonionic surfactant.

5 It is most useful with nonionic surfactants which are liquid at ambient temperature, and are therefore mobile. Without a suitable structurant, the nonionic surfactant tends to leak from the powder and soak into the cardboard container which forms an unsightly stain. Although it is possible to avoid this problem by using lower levels of nonionic surfactant in the composition, or by selecting nonionic surfactants which have a higher solidification temperature, this limits the flexibility of formulation.

10 The use of nonionic surfactants in granular detergent applications has been widely discussed in the prior art. The following references describe various processes and compositions for making granules which comprise nonionic surfactants.

15 US 3 868 336, published 25th February, 1975 discloses the use of a powder premix comprising perborate, tripolyphosphate, nonionic surfactant and polyvinyl alcohol. The premix is dry added to other detergent components.

GB 2 137 221, published 3rd October, 1984 discloses a nonionic premix which comprises dissolved polyvinyl pyrrolidone (PVP) and soil release polymer. The premix is sprayed on to an absorbant detergent carrier particle. The PVP is used as a stabiliser for the soil release polymer.

20 EPA 0 215 637, published on 25th March, 1987 discloses the use of sugars and derivatives as structurants of spray dried detergent powders. Although nonionic surfactant may be present in such powders it is incorporated at relatively low levels (1.5% - 4% in examples 1 to 5). Furthermore the spray dried powder has a low bulk density (324 - 574 g/l).

25 EPA 0 513 824, published 19th November, 1992, describes a process for granulating nonionic detergent and the use of a surface coating agent having a particle size of less than 10 micrometers to give a powder having a high content of nonionic surfactant (10-60%) and a bulk density of 0.6 to 1.2 g/ml. The use of polymers including polyethylene glycol, polyvinyl alcohol, polyvinyl pyrrolidone and carboxymethyl cellulose is disclosed (page 13, lines 17-18). However, the benefits of using any of these polymers to structure or thicken the nonionic surfactant is not disclosed.

30 WO 92 6160, published on 16th April, 1992. This application describes (example 14) a granular detergent composition prepared by fine dispersion mixing in an Eirich RV02 mixer of a paste which comprises N-methyl glucose amide and nonionic surfactant in the presence of sodium carbonate and zeolite. There is no suggestion to use polymers as structuring agents.

35 One aspect of the present invention is a process for making granular nonionic detergent agglomerates having a bulk density of at least 650 g/l and which comprise higher levels of nonionic surfactant than those of the prior art, but do not have problems of mobile nonionic surfactants (i.e. nonionic surfactants with low solidification temperatures) leaking from the granules and soaking into the carton.

40 This problem is addressed by structuring the liquid nonionic surfactant before the dispersion and/or granulation process. This is done by dissolving a structuring agent which comprises a polymer in the nonionic surfactant. Preferred structuring agents are polymers, especially polymers having more than one functional hydroxyl group, especially polyvinyl alcohols, polyhydroxyacrylic acid polymers, and polymers such as polyvinyl pyrrolidone and PVNO. Also useful as components of the structuring agent are sugars and artificial sweeteners and their derivatives.

45 It is a further aspect of the present invention to provide a process for incorporating sticky materials into detergent granules while still maintaining desirable physical properties including free-flowing particles which have a good resistance to caking. Sticky materials if present at or close to the surface of the granules have a negative effect on flow properties. These materials also tend to gel upon contact with water which prevents effective dispensing of the granules from the dispensing drawer of a washing machine or from a dispensing device which is added to the wash with soiled load. In this aspect of the present invention these problems are overcome by using sticky materials as structuring agents of the nonionic surfactants thereby 50 improving the surface properties of the granules.

In a further aspect of the invention, high bulk density granular detergent compositions and components are provided which comprise nonionic surfactants and structuring agents.

Summary of the Invention

55 A process for making a granular laundry detergent component or composition having a bulk density of at least 650 g/l, by dissolving a structuring agent in a nonionic surfactant, said structuring agent comprising a polymer, to form a pumpable premix and finely dispersing said premix with an effective amount of powder

at a given operating temperature wherein the premix has a viscosity of at least 350 mPas when measured at said operating temperature and at a shear rate of 25s^{-1} . Preferred structurants comprise polymers having more than one functional hydroxyl group, especially polyvinyl alcohols, polyhydroxyacrylic acid polymers, and polymers such as polyvinyl pyrrolidone and PVNO, as well as sugars, artificial sweeteners and their derivatives. The premix is then processed into a granular detergent by any suitable process. Fine dispersion mixing, agglomeration, or spraying the premix onto a granular base product are preferred.

Another aspect of the present invention is components or compositions comprising nonionic surfactant and structuring agents.

10 Detailed Description of the Invention

The process aspect of the present invention comprises two essential steps. The first process step is the formation of a nonionic surfactant premix which comprises a structuring agent. The second process step is the processing of the surfactant premix into the form of a granular detergent having the desired physical properties of bulk density, flow properties and storage characteristics.

The first process step of the invention is the preparation of a structured nonionic surfactant premix. This premix comprises two essential components which will be described in more detail below. These components are the nonionic surfactant and the structuring agent. In the first process step the structuring agent is dissolved in the nonionic surfactant.

20 The second process step may be based upon any of the techniques of forming granules which are known to the man skilled in the art. However, the most preferred granulation techniques for use in the present invention are fine dispersion of the structured nonionic surfactant paste in the presence of powders. One example of such a process is to pump or spray the surfactant paste into a high shear mixer. The high shear conditions in the mixer break up the surfactant paste into small droplets and distribute those droplets onto and around the powder. The process is often described as "agglomeration".

25 Another example of such a process is to spray the surfactant paste onto a powder under low shear conditions (such as a rotating drum). In this case the energy to break the paste into fine droplets comes at the spray nozzle, and in the low shear mixer the droplets are absorbed on to the surface, or into the pores of the powder. Preferred granulation processes are described in more detail below.

30 For the purposes of the invention described herein, the term structuring has been used to mean thickening or raising the solidification point of the nonionic surfactant, or both of these. It is an essential feature of the present invention that the viscosity of the premix is greater than 350 mPas when measured at the operating temperature and at a shear rate of 25s^{-1} .

35 The operating temperature, as defined herein, is the temperature of the surfactant paste at the point which is sprayed or dispersed onto the powders during the granulation step of the process.

A pumpable paste is defined herein to mean a paste which has a viscosity of less than 100 000 mPas when measured at 25s^{-1} at the required operating temperature. Preferably the viscosity of the paste will be less than 60 000 mPas, and even more preferably less than 40 000 mPas.

40 Nonionic Surfactant

Suitable nonionic surfactants include compounds produced by the condensation of alkylene oxide groups (hydrophilic in nature) with an organic hydrophobic compound, which may be aliphatic or alkyl aromatic in nature. The length of the polyoxyalkylene group which is condensed with any particular hydrophobic group can be readily adjusted to yield a water-soluble compound having the desired degree of balance between hydrophilic and hydrophobic elements.

45 Particularly preferred for use in the present invention are nonionic surfactants such as the polyethylene oxide condensates of alkyl phenols, e.g., the condensation products of alkyl phenols having an alkyl group containing from about 6 to 16 carbon atoms, in either a straight chain or branched chain configuration, with from about 4 to 25 moles of ethylene oxide per mole of alkyl phenol.

50 Preferred nonionics are the water-soluble condensation products of aliphatic alcohols containing from 8 to 20 carbon atoms, in either straight chain or branched configuration, with an average of from 1 to 25 moles of ethylene oxide per mole of alcohol. Particularly preferred are the condensation products of alcohols having an alkyl group containing from about 9 to 15 carbon atoms with from about 2 to 10 moles of ethylene oxide per mole of alcohol; and condensation products of propylene glycol with ethylene oxide. Most preferred are condensation products of alcohols having an alkyl group containing from about 12 to 15 carbon atoms with an average of about 3 moles of ethylene oxide per mole of alcohol.

Many of the nonionic surfactants which fall within the definitions given above have are liquid at temperatures below 40°C (that is to say the solidification temperature is below 40°C). The present invention has been found to be particularly useful for such nonionic surfactants.

5 Structuring Agent

Although any structuring agent may be chosen which has the effect of raising the viscosity or "stickiness" of the surfactant premix to the required operating window and / or increasing the solidification temperature of the premix, it has been found that structuring agents which comprise at least one polymer 10 are particularly useful.

Preferably at least one of the components of the structuring agent is a polymer having an average molecular weight of at least 2000, and preferably at least 10000.

The group of polymers useful as structuring agents in the present invention includes the group of polymers which are derived from monomers having at least one hydroxyl functional group such as polyvinyl 15 alcohols, polyethylene glycol and polyhydroxyacrylic acid polymers and mixtures and derivatives of these. Other polymers which are useful components of the structuring agent include polyvinyl pyrrolidone, PVNO.

The structuring agent may also comprise other ingredients. One group of such ingredients which have been found to be particularly useful comprises the group of sugars and artificial sweeteners and their derivatives.

20 The group of sugars useful in the present invention includes fructose, lactose, dextrose, sucrose, saccharin and sorbitol.

One particularly preferred group of structuring agents is the derivatives of sugars such as polyhydroxy fatty acid amides. Such derivatives may be prepared by reacting a fatty acid ester and an N-alkyl 25 polyhydroxy amine. The preferred amine for use in the present invention is N-(R1)-CH₂(CH₂OH)₄-CH₂-OH and the preferred ester is a C₁₂-C₂₀ fatty acid methyl ester. Most preferred is the reaction product of N-methyl glucamine (which may be derived from glucose) with C₁₂-C₂₀ fatty acid methyl ester.

Methods of manufacturing polyhydroxy fatty acid amides have been described in WO 92 6073, published on 16th April, 1992. This application describes the preparation of polyhydroxy fatty acid amides in the presence of solvents.

30 In a highly preferred embodiment of the invention N-methyl glucamine is reacted with a C₁₂-C₂₀ methyl ester. It also says that the formulator of granular detergent compositions may find it convenient to run the amidation reaction in the presence of solvents which comprise alkoxylated, especially ethoxylated (EO 3-8) C₁₂-C₁₄ alcohols (page 15, lines 22-27). This directly yields nonionic surfactant systems which are preferred in the present invention, such as those comprising N-methyl glucamide and C₁₂-C₁₄ alcohols 35 with an average of 3 ethoxylate groups per molecule.

Polyhydroxy fatty acid amides are also active in the washing process as surfactants in their own right.

Other ingredients which have been found to be useful as components of the structuring agent include phthalimide, para-toluene sulphonamide, and maleimide.

The ratio of nonionic surfactant to structuring agent will vary according to exactly which nonionic 40 surfactant and which structurant is chosen. Any ratio may be used in the present invention provided that a premix having a viscosity of at least 350 mPas when measured at the operating temperature and a shear rate of 25s⁻¹ is produced. Typically ratios of nonionic surfactant to structuring agent in the range of 20:1 to 1:1 have been found to be particularly suitable, and preferably from 5:1 to 2:1.

45 Normally the detergent compositions made according to the present invention may include a wide range of other ingredients and components which are known to the man skilled in the art to have a function in the washing process. Typical examples of such ingredients which may be used in detergent compositions are given below. Granulation Processes

An essential step of the present invention is the process of forming granules which comprise the 50 surfactant premix described above. Many processes for granulating surfactant pastes are known to the man skilled in the art. One of these processes is spray drying of a slurry containing the surfactant. However, this is not a preferred process in the present invention because it does not generally yield a powder with a high bulk density, and further processing is needed in order to increase the bulk density. A process which is more suited to the present invention is that of fine dispersion mixing or agglomeration. In this process a 55 powder having a relatively small particle size is mixed with a finely dispersed paste which causes the powder to stick together (or agglomerate). The result is a granular composition which generally has a particle size distribution in the range of 250 to 1200 micrometers and has a bulk density of at least 650 g/l. In the present invention the surfactant premix is used as the paste which is finely dispersed with an effective amount of powder in a suitable mixer. Suitable mixers for carrying out the fine dispersion mixing

are described in more detail below. Any suitable powder may be chosen by mixing one or more of the ingredients listed below which may be conveniently handled in powder form. Powders comprising zeolite, carbonate, silica, silicate, sulphate, phosphate, citrate, citric acid and mixtures of these are particularly preferred.

5 It has further been found that a particularly preferred embodiment of the present invention is to spray water on to the detergent granules after the granulation step. In this embodiment of the invention at least one of the powders used should be an anhydrous powder which may be fully or partially hydrated when it comes into contact with water. A similar process has been described in GB 2 113 707, published on 10th
10 August 1983. This application describes a process in which anhydrous powders such as phosphate, carbonate, borate or sulphate are metered into a high shear mixer (a K-G Schugi [Trade name] Blender-Agglomerator) together with a liquid surfactant and water. The amount of water added is sufficient to completely hydrate the hydratable salts. The resulting agglomerates are fed into a low shear mixer having a longer residence time in order for the hydration reaction to proceed.

15 In the process of the present invention, in contrast, it is highly preferred to add the water into the low shear mixer, after the agglomerates have been formed. Without wishing to be bound by theory, it is believed that adding the water after the initial formation of the agglomerates promotes hydration at the surface of the agglomerates which gives rise to the desired physical characteristics.

20 Most preferred in the process of the present invention is the use of anhydrous sodium carbonate, or anhydrous sodium citrate, or mixtures of these. The anhydrous salts are agglomerated in the presence of a structured nonionic surfactant premix and then water is sprayed on to the resulting agglomerates in a low shear mixer. The agglomerates are finally dried in a fluid bed dryer.

25 Still another process which is suited to the present invention is that of preparing a granular detergent powder and spraying the surfactant premix onto that powder. The base powder may be made by any one of the processes known to the man skilled in the art, including spray drying, granulation, (including agglomeration). Preferably different processes which are suited to the preparation of different components will be used, and then the components will be mixed together, for example by dry mixing in a rotating drum or a low shear mixer. In a preferred embodiment of the invention the surfactant premix is sprayed onto the base powder in the rotating drum or low shear mixer.

30 Suitable pieces of equipment in which to carry out the fine dispersion mixing or granulation of the present invention are mixers of the Fukae^R FS-G series manufactured by Fukae Powtech Kogyo Co., Japan; this apparatus is essentially in the form of a bowl-shaped vessel accessible via a top port, provided near its base with a stirrer having a substantially vertical axis, and a cutter positioned on a side wall. The stirrer and cutter may be operated independently of one another and at separately variable speeds. The vessel can be fitted with a cooling jacket or, if necessary, a cryogenic unit.

35 Other similar mixers found to be suitable for use in the process of the invention include Diosna^R V series ex Dierks & Söhne, Germany; and the Pharma Matrix^R ex T K Fielder Ltd., England. Other mixers believed to be suitable for use in the process of the invention are the Fuji^R VG-C series ex Fuji Sangyo Co., Japan; and the Roto^R ex Zanchetta & Co srl, Italy.

40 Other preferred suitable equipment can include Eirich^R, series RV, manufactured by Gustau Eirich Hardheim, Germany; Lödige^R, series FM for batch mixing, series Baud KM for continuous mixing/agglomeration, manufactured by Lödige Maschinenbau GmbH, Paderborn Germany; Drais^R T160series, manufactured by Drais Werke GmbH, Mannheim Germany; and Winkworth^R RT 25 series, manufactured by Winkworth Machinery Ltd., Berkshire, England.

45 The Littleford Mixer, Model #FM-130-D-12, with internal chopping blades and the Cuisinart Food Processor, Model #DCX-Plus, with 7.75 inch (19.7 cm) blades are two examples of suitable mixers. Any other mixer with fine dispersion mixing and granulation capability and having a residence time in the order of 0.1 to 10 minutes can be used. The "turbine-type" impeller mixer, having several blades on an axis of rotation, is preferred. The invention can be practiced as a batch or a continuous process.

50 Further Processing Steps

55 The granular components or compositions described above may be suitable for use directly, or they may be treated by additional process steps. Commonly used process steps include drying, cooling and/or dusting the granules with a finely divided flow aid. In addition the granules may be blended with other components in order to provide a composition suitable for the desired end use.

Any type of mixer or dryer (such as fluid bed dryers) may be found to be suitable for this purpose.

The finely divided flow aid, if used, may be chosen from a wide variety of suitable ingredients such as zeolite, silica, talc, clay or mixtures of these.

Compositions

Another aspect of the present invention is the composition of detergent components comprising nonionic surfactant. Components having a bulk density of greater than 650 g/l and comprising from 10% to 50% by weight of nonionic surfactant and from 5% to 30% by weight of one of the structuring agents listed above fall within the scope of the present invention. The ratio of nonionic surfactant to structuring agent will vary according to exactly which nonionic surfactant and which structurant is chosen. Any ratio may be used in the present invention provided that a premix having a viscosity of at least 350 mPas when measured at the operating temperature and a shear rate of 25s^{-1} is produced. Typically ratios of nonionic surfactant to structuring agent in the range of 20:1 to 1:1 have been found to be particularly suitable, and preferably from 5:1 to 2:1.

Other ingredients which may be used in making the compositions of the present invention will be described below.


Normally the granular detergent will also contain other optional ingredients. Examples of such ingredients which are commonly used in detergents are given in more detail hereinbelow

Anionic Surfactants

Alkyl Ester Sulfonate Surfactant

Alkyl Ester sulfonate surfactants hereof include linear esters of $\text{C}_8\text{-C}_{20}$ carboxylic acids (i.e. fatty acids) which are sulfonated with gaseous SO_3 according to "The Journal of the American Oil Chemists Society" 52 (1975), pp. 323-329. Suitable starting materials would include natural fatty substances as derived from tallow, palm oil, etc.

The preferred alkyl ester sulfonate surfactant, especially for laundry applications, comprises alkyl ester sulfonate surfactants of the structural formula:



35 wherein R^3 is a $\text{C}_8\text{-C}_{20}$ hydrocarbyl, preferably an alkyl, or combination thereof, R^4 is a $\text{C}_1\text{-C}_6$ hydrocarbyl, preferably an alkyl, or combination thereof, and M is a cation which forms a water soluble salt with the alkyl ester sulfonate. Suitable salt-forming cations include metals such as sodium, potassium, and lithium, and substituted or unsubstituted ammonium cations, such as monoethanolamine, diethanolamine, and triethanolamine. Preferably, R^3 is $\text{C}_{10}\text{-C}_{16}$ alkyl, and R^4 is methyl, ethyl or isopropyl. Especially preferred are the methyl ester sulfonates wherein R^3 is $\text{C}_{14}\text{-C}_{16}$ alkyl.

Alkyl Sulfate Surfactant

Alkyl sulfate surfactants hereof are water soluble salts or acids or the formula ROSO_3M wherein R preferably is a $\text{C}_{10}\text{-C}_{24}$ hydrocarbyl, preferably an alkyl or hydroxyalkyl having a $\text{C}_{10}\text{-C}_{20}$ alkyl component, more preferably a $\text{C}_{12}\text{-C}_{18}$ alkyl or hydroxyalkyl, and M is H or a cation, e.g., an alkali metal cation (e.g., sodium, potassium, lithium), or ammonium or substituted ammonium (e.g., methyl-, dimethyl-, and trimethyl ammonium cations and quaternary ammonium cations, such as tetramethyl-ammonium and dimethyl piperdinium cations and quaternary ammonium cations derived from alkylamines such as ethylamine, diethylamine, triethylamine, and mixtures thereof, and the like). Typically, alkyl chains of C_{12-16} are preferred for lower wash temperatures (e.g., below about 50°C) and C_{16-18} alkyl chains are preferred for higher wash temperatures (e.g., above about 50°C).

Alkyl Alkoxylated Sulfate Surfactant

55 Alkyl alkoxylated sulfate surfactants hereof are water soluble salts or acids of the formula $\text{RO(A)}_m\text{SO}_3\text{M}$ wherein R is an unsubstituted $\text{C}_{10}\text{-C}_{24}$ alkyl or hydroxyalkyl group having a $\text{C}_{10}\text{-C}_{24}$ alkyl component, preferably a $\text{C}_{12}\text{-C}_{20}$ alkyl or hydroxyalkyl, more preferably $\text{C}_{12}\text{-C}_{18}$ alkyl or hydroxyalkyl, A is an ethoxy or

propoxy unit, m is greater than zero, typically between about 0.5 and about 6, more preferably between about 0.5 and about 3, and M is H or a cation which can be, for example, a metal cation (e.g., sodium, potassium, lithium, calcium, magnesium, etc.), ammonium or substituted-ammonium cation. Alkyl ethoxylated sulfates as well as alkyl propoxylated sulfates are contemplated herein. Specific examples of 5 substituted ammonium cations include methyl-, dimethyl-, trimethylammonium and quaternary ammonium cations, such as tetramethyl-ammonium, dimethyl piperidinium and cations derived from alkanolamines such as ethylamine, diethylamine, triethylamine, mixtures thereof, and the like. Exemplary surfactants are C₁₂-C₁₈ alkyl polyethoxylate (1.0) sulfate, C₁₂-C₁₈E(1.0)M, C₁₂-C₁₈ alkyl polyethoxylate (2.25) sulfate, C₁₂-C₁₈E(2.25)M, C₁₂-C₁₈ alkyl polyethoxylate (3.0) sulfate C₁₂-C₁₈E(3.0), and C₁₂-C₁₈ alkyl polyethoxylate (4.0) sulfate C₁₂-C₁₈E(4.0)M, wherein M is conveniently selected from sodium and potassium.

Other Anionic Surfactants

Other anionic surfactants useful for detergents purposes can also be included in the laundry detergent 15 compositions of the present invention. These can include salts (including, for example, sodium, potassium, ammonium, and substituted ammonium salts such as mono-, di- and triethanolamine salts) of soap, C₉-C₂₀ linear alkylbenzenesulphonates, C₈-C₂₂ primary or secondary alkanesulphonates, C₈-C₂₄ olefinsulphonates, sulphonated polycarboxylic acids prepared by sulphonation of the pyrolyzed product of alkaline earth metal citrates, e.g., as described in British patent specification No. 1,082,179, C₈-C₂₄ alkylpolyglycolethersulfates 20 (containing up to 10 moles of ethylene oxide); acyl glycerol sulfonates, fatty oleyl glycerol sulfates, alkyl phenol ethylene oxide ether sulfates, paraffin sulfonates, alkyl phosphates, isethionates such as the acyl isethionates, N-acyl taurates, alkyl succinamates and sulfosuccinates, monoesters of sulfosuccinate (especially saturated and unsaturated C₁₂-C₁₈ monoesters) diesters of sulfosuccinate (especially saturated and unsaturated C₆-C₁₄ diesters), acyl sarcosinates, sulfates of alkylpolysaccharides such as the sulfates of 25 alkylpolyglucoside, branched primary alkyl sulfates, alkyl polyethoxy carboxylates such as those of the formula RO(CH₂CH₂O)_kCH₂COO-M⁺ wherein R is a C₈-C₂₂ alkyl, k is an integer from 0 to 10, and M is a soluble salt-forming cation. Resin acids and hydrogenated resin acids are also suitable, such as rosin, hydrogenated rosin, and resin acids and hydrogenated resin acids present in or derived from tall oil. Further examples are given in "Surface Active Agents and Detergents" (Vol. I and II by Schwartz, Perry and Berch). 30 A variety of such surfactants are also generally disclosed in U.S. Patent 3,929,678, issued December 30, 1975 to Laughlin, et al. at Column 23, line 58 through Column 29, line 23 (herein incorporated by reference).

When included therein, the laundry detergent compositions of the present invention typically comprise from about 1 % to about 40 %, preferably from about 3 % to about 20 % by weight of such anionic surfactants.

35 Other Surfactants

The laundry detergent compositions of the present invention may also contain cationic, ampholytic, zwitterionic, and semi-polar surfactants, as well as nonionic surfactants other than those already described 40 herein, including the semi-polar nonionic amine oxides described below.

Cationic detergents suitable for use in the laundry detergent compositions of the present invention are those having one long-chain hydrocarbyl group. Examples of such cationic surfactants include the ammonium surfactants such as alkyldimethylammonium halogenides, and those surfactants having the formula :



wherein R¹ is an alkyl or alkyl benzyl group having from about 8 to about 18 carbon atoms in the alkyl chain, each of R², R³, R⁴ is independently C₁-C₄ alkyl, C₁-C₄ hydroxy alkyl, benzyl, and -(C₂H₄)_xH where x 50 has a value from 2 to 5, and X⁻ is an anion. Not more than one of R₂, R₃, R₄ should be benzyl.

The preferred alkyl chain length for R¹ is C₁₂-C₁₅, particularly where the alkyl group is a mixture of chain lengths derived from coconut or palm kernel fat, or is derived synthetically by olefin build up or OXO alcohols synthesis. Preferred groups for R₂, R₃, R₄ are methyl and hydroxyethyl groups, and the anion X may be selected from halide, methosulphate, acetate and phosphate ions. Examples of suitable quaternary 55 ammonium compounds for use herein are:

- coconut trimethyl ammonium chloride or bromide
- coconut methyl dihydroxyethyl ammonium chloride or bromide
- decyl triethyl ammonium chloride or bromide

5 decyl dimethyl hydroxyethyl ammonium chloride or bromide
 C12-14 dimethyl hydroxyethyl ammonium chloride or bromide
 myristyl trimethyl ammonium methyl sulphate
 lauryl dimethyl benzyl ammonium chloride or bromide
 lauryl methyl (ethenoxy)₄ ammonium chloride or bromide

The above water-soluble cationic components of the compositions of the present invention, are capable of existing in cationic form in a 0.1% aqueous solution at pH10.

10 Other cationic surfactants useful herein are also described in US Patent 4,228,044, Cambre, issued October 14, 1980, incorporated herein by reference.

When included therein, the laundry detergent compositions of the present invention typically comprise from 0 % to about 25 %, preferably from about 3 % to about 15 % by weight of such cationic surfactants.

15 Ampholytic surfactants are also suitable for use in the laundry detergent compositions of the present invention. These surfactants can be broadly described as aliphatic derivatives of secondary or tertiary amines, or aliphatic derivatives of heterocyclic secondary and tertiary amines in which the aliphatic radical can be straight- or branched chain. One of the aliphatic substituents contains at least 8 carbon atoms, typically from about 8 to about 18 carbon atoms, and at least one contains an anionic water-solubilizing group e.g. carboxy, sulfonate, sulfate. See U.S. Patent No. 3,929,678 to Laughlin et al., issued December 30, 1975 at column 19, lines 18-35 (herein incorporated by reference) for examples of ampholytic 20 surfactants.


When included therein, the laundry detergent compositions of the present invention typically comprise from 0 % to about 15 %, preferably from about 1 % to about 10 % by weight of such ampholytic surfactants.

25 Zwitterionic surfactants are also suitable for use in laundry detergent compositions. These surfactants can be broadly described as derivatives of secondary and tertiary amines, derivatives of heterocyclic secondary and tertiary amines, or derivatives of quaternary ammonium, quaternary phosphonium or tertiary sulfonium compounds. See U.S. Patent No. 3,929,678 to Laughlin et al., issued December 30, 1975 at columns 19, line 38 through column 22, line 48 (herein incorporated by reference) for examples of zwitterionic surfactants.

30 When included therein, the laundry detergent compositions of the present invention typically comprise from 0 % to about 15 %, preferably from about 1 % to about 10 % by weight of such zwitterionic surfactants.

35 Semi-polar nonionic surfactants are a special category of nonionic surfactants which include water-soluble amine oxides containing one alkyl moiety of from about 10 to about 18 carbon atoms and 2 moieties selected from the group consisting of alkyl groups and hydroxyalkyl groups containing from about 1 to about 3 carbon atoms; water-soluble phosphine oxides containing one alkyl moiety of from about 10 to about 18 carbon atoms and 2 moieties selected from the group consisting of alkyl groups and hydroxyalkyl groups containing from about 1 to about 3 carbon atoms.

40 Semi-polar nonionic detergent surfactants include the amine oxide surfactants having the formula :



45 wherein R³ is an alkyl, hydroxyalkyl, or alkyl phenyl group or mixtures thereof containing from about 8 to about 22 carbon atoms; R⁴ is an alkylene or hydroxyalkylene group containing from about 2 to about 3 carbon atoms or mixtures thereof; x is from 0 to about 3; and each R⁵ is an alkyl or hydroxyalkyl group containing from about 1 to about 3 carbon atoms or a polyethylene oxide group containing from about 1 to about 3 ethylene oxide groups. The R⁵ groups can be attached to each other, e.g., through an oxygen or nitrogen atom, to form a ring structure.


50 There amine oxide surfactants in particular include C₁₀-C₁₈ alkyl dimethyl amine oxides and C₈-C₁₂ alkoxy ethyl dihydroxy ethyl amine oxides.

55 When included therein, the laundry detergent compositions of the present invention typically comprise from 0 % to about 15 %, preferably from about 1 % to about 10 % by weight of such semi-polar nonionic surfactants.

Builders and Other Optional Ingredients


Sodium aluminosilicate may take many forms. One example is crystalline aluminosilicate ion exchange material of the formula

5



wherein z and y are at least about 6, the molar ratio of z to y is from about 1.0 to about 0.4 and z is from about 10 to about 264. Amorphous hydrated aluminosilicate materials useful herein have the empirical formula

10



wherein M is sodium, potassium, ammonium or substituted ammonium, z is from about 0.5 to about 2 and y is 1, said material having a magnesium ion exchange capacity of at least about 50 milligram equivalents of CaCO_3 hardness per gram of anhydrous aluminosilicate. Hydrated sodium Zeolite A with a particle size of from about 1 to 10 microns is preferred.

15


The aluminosilicate ion exchange builder materials herein are in hydrated form and contain from about 10% to about 28% of water by weight if crystalline, and potentially even higher amounts of water if amorphous. Highly preferred crystalline aluminosilicate ion exchange materials contain from about 18% to about 22% water in their crystal matrix. The crystalline aluminosilicate ion exchange materials are further characterized by a particle size diameter of from about 0.1 micron to about 10 microns. Amorphous materials are often smaller, e.g., down to less than about 0.01 micron. Preferred ion exchange materials have a particle size diameter of from about 0.2 micron to about 4 microns. The term "particle size diameter" herein represents the average particle size diameter by weight of a given ion exchange material as determined by conventional analytical techniques such as, for example, microscopic determination utilizing a scanning electron microscope. The crystalline aluminosilicate ion exchange materials herein are usually further characterized by their calcium ion exchange capacity, which is at least about 200 mg equivalent of CaCO_3 water hardness/g of aluminosilicate, calculated on an anhydrous basis, and which generally is in the range of from about 300 mg eq./g to about 352 mg eq./g. The aluminosilicate ion exchange materials herein are still further characterized by their calcium ion exchange rate which is at least about 2 grains $\text{Ca}^{++}/\text{gallon}/\text{minute}/\text{gram}/\text{gallon}$ of aluminosilicate (anhydrous basis), and generally lies within the range of from about 2 grains/gallon/minute/gram/gallon to about 6 grains/gallon/minute/gram/gallon, based on calcium ion hardness. Optimum aluminosilicate for builder purposes exhibit a calcium ion exchange rate of at least about 4 grains/gallon/minute/gram/gallon.

20

The amorphous aluminosilicate ion exchange materials usually have a Mg^{++} exchange of at least about 50 mg eq. CaCO_3/g (12 mg Mg^{++}/g) and a Mg^{++} exchange rate of at least about 1 grain/gallon/minute/gram/gallon. Amorphous materials do not exhibit an observable diffraction pattern when examined by Cu radiation (1.54 Angstrom Units).

25

Aluminosilicate ion exchange materials useful in the practice of this invention are commercially available. The aluminosilicates useful in this invention can be crystalline or amorphous in structure and can be naturally occurring aluminosilicates or synthetically derived. A method for producing aluminosilicate ion exchange materials is discussed in U.S. Pat. No. 3,985,669, Krummel et al., issued Oct. 12, 1976, incorporated herein by reference. Preferred synthetic crystalline aluminosilicate ion exchange materials useful herein are available under the designations Zeolite A, Zeolite B, Zeolite M and Zeolite X. In an especially preferred embodiment, the crystalline aluminosilicate ion exchange material has the formula



30

wherein x is from about 20 to about 30, especially about 27 and has a particle size generally less than about 5 microns.

Other ingredients which are known for use in the components and compositions may also be used as optional ingredients in the present invention.

35

The granular detergents of the present invention can contain neutral or alkaline salts which have a pH in solution of seven or greater, and can be either organic or inorganic in nature. The builder salt assists in providing the desired density and bulk to the detergent granules herein. While some of the salts are inert, many of them also function as detergency builder materials in the laundering solution.

Examples of neutral water-soluble salts include the alkali metal, ammonium or substituted ammonium chlorides, fluorides and sulfates. The alkali metal, and especially sodium, salts of the above are preferred. Sodium sulfate is typically used in detergent granules and is a particularly preferred salt. Citric acid and, in general, any other organic or inorganic acid may be incorporated into the granular detergents of the present 5 invention as long as it is chemically compatible with the rest of the agglomerate composition.

Other useful water-soluble salts include the compounds commonly known as detergent builder materials. Builders are generally selected from the various water-soluble, alkali metal, ammonium or substituted ammonium phosphates, polyphosphates, phosphonates, polyphosphonates, carbonates, silicates, borates, and polyhydroxysulfonates. Preferred are the alkali metal, especially sodium, salts of the above.

10 Specific examples of inorganic phosphate builders are sodium and potassium tripolyphosphate, pyrophosphate, polymeric metaphosphate having a degree of polymerization of from about 6 to 21, and orthophosphate. Examples of polyphosphonate builders are the sodium and potassium salts of ethylene diphosphonic acid, the sodium and potassium salts of ethane 1-hydroxy-1,1-diphosphonic acid and the sodium and potassium salts of ethane, 1,1,2-triphosphonic acid. Other phosphorus builder compounds are 15 disclosed in U.S. Pat. Nos. 3,159,581; 3,213,030; 3,422,021; 3,422,137; 3,400,176 and 3,400,148, incorporated herein by reference.

Examples of nonphosphorus, inorganic builders are sodium and potassium carbonate, bicarbonate, sesquicarbonate, tetraborate decahydrate, and silicate having a molar ratio of SiO_2 to alkali metal oxide of from about 0.5 to about 4.0, preferably from about 1.0 to about 2.4.

20 As mentioned above powders normally used in detergents such as zeolite, carbonate, silica, silicate, citrate, phosphate, perborate, etc. and process acids such as starch, can be used in preferred embodiments of the present invention.

Polymers

25 Also useful are various organic polymers, some of which also may function as builders to improve detergency. Included among such polymers may be mentioned sodium carboxy-lower alkyl celluloses, sodium lower alkyl celluloses and sodium hydroxy-lower alkyl celluloses, such as sodium carboxymethyl cellulose, sodium methyl cellulose and sodium hydroxypropyl cellulose, polyvinyl alcohols (which often also 30 include some polyvinyl acetate), polyacrylamides, polyacrylates and various copolymers, such as those of maleic and acrylic acids. Molecular weights for such polymers vary widely but most are within the range of 2,000 to 100,000.

Polymeric polycarboxylate builders are set forth in U.S. Patent 3,308,067, Diehl, issued March 7, 1967. Such materials include the water-soluble salts of homo- and copolymers of aliphatic carboxylic acids such as 35 maleic acid, itaconic acid, mesaconic acid, fumaric acid, aconitic acid, citraconic acid and methylenemalonic acid.

Other Optionals Ingredients

40 Other ingredients commonly used in detergent compositions can be included in the components and compositions of the present invention. These include color speckles, bleaching agents and bleach activators, suds boosters or suds suppressors, antitarnish and anticorrosion agents, soil suspending agents, soil release agents, dyes, fillers, optical brighteners, germicides, pH adjusting agents, nonbuilder alkalinity sources, hydrotropes, enzymes, enzyme-stabilizing agents, and perfumes.

45 Examples

In these examples the following abbreviations have been used:

C25E3:	C12-15 alkyl ethoxylate, with an average of 3 ethoxy groups per molecule
50 GA:	N-methyl glucamide
C25AS:	C12-15 alkyl sulphate
C45AS:	C14-15 alkyl sulphate
C25AE3S:	C12-15 alkyl ethoxy sulphate, with an average of 3 ethoxy groups per molecule
PVP:	Polyvinyl Pyrrolidone
55 PVNO:	Polyvinyl Pyridine N oxide

TABLE 1

	Ex	1	2	3	4	5	6	7
	C25E3	80	75	67	67	46	46	46
	PVP	20	25	33	33			
	PVNO					13	13	13
	lactose					11		
	dextrose						11	
	sucrose							11
	water					30	30	30
	Operating Temp. (°C)	30	30	15	15	20	20	20
	Viscosity (mPas)	900	1300	2000	2000	23000	23000	23000
		8	9	10	A			
	C25E3	75	67	86	97.5			
	GA	12.5	11					
	PVP		22	14	2.5			
	PVNO	12.5						
	Operating Temp. (°C)	40	40	20	20			
	Viscosity (mPas)	24000	15000	380	50			

45 Example 1

The C25E3/PVP paste defined in Table 1 was sprayed into a Loedige CB mixer [Trade Name] at a rate of 1120 kg/hr and at a temperature of 30 °C. At the same time zeolite A was added to the mixer at a rate of 50 1340 kg/hr, as well as anhydrous carbonate 1340 kg/hr.

Dispersion of the paste premix and high intensity mixing of the premix and the powders occurred in the Loedige mixer. The residence time was approximately eight seconds.

The resulting mixture was fed into a Loedige KM mixer [Trade Name] and distinct agglomerates were formed. Two high speed choppers in the first half of the Loedige KM mixer prevented a high proportion of 55 oversize agglomerates being formed.

In the second half of the Loedige KM mixer water was sprayed on to the agglomerates at a rate of 225 kg/hr promoting the hydration of the carbonate in the agglomerate.

After the water spray on, a mixture of zeolite and silica was added at a rate of 160 kg/hr.

The agglomerates leaving the Loedige KM mixer were then passed through a fluid bed cooler / elutriator

The resulting agglomerates had excellent physical properties including flowability, and were found to be physically stable under stressed storage conditions.

5 Example 2

The process of example 1 was repeated using the components listed in Table 1.

Example 3

10

The process of example 1 was repeated using the components listed in Table 1 and at an operating temperature of the paste premix of 15 °C.

Example 4

15

The process of example 3 was repeated using the components listed in Table 1, with the Zeolite A being replaced by anhydrous citrate, and the rate of water addition being increased to 190 kg /hr.

Example 5

20

The C25E3/PVNO/lactose paste defined in Table 1 was sprayed into a Loedige CB mixer [Trade Name] at a rate of 1400 kg/hr and at a temperature of 20 °C. At the same time zeolite A was added to the mixer at a rate of 1200 kg/hr, as well as anhydrous carbonate 1200 kg/hr.

The remainder of the process was carried out as in example 1 with water being sprayed on to the 25 agglomerates at a rate of 200 kg/hr.

Examples 6-10

The process of example 5 was repeated using the components listed in Table 1.

30 In each of the examples 2 to 10, a free flowing granular products were produced which were found to be physically stable under stressed storage conditions.

Comparative Example A

35 The process of example 5 was repeated using the components listed in Table 1. Due to the lower viscosity of the surfactant premix it was not possible to make granules having the desired particle size or physical properties.

Claims

40

1. A process for making a granular laundry detergent component or composition having a bulk density of at least 650 g/l comprising the steps of ;
 - a) dissolving a structuring agent, said structuring agent comprising a polymer, in a nonionic surfactant to form a pumpable premix; and
 - b) finely dispersing said premix with an effective amount of powder characterised in that the fine dispersing of the premix is carried out at an operating temperature at which the premix has a viscosity of at least 350 mPas when measured at said operating temperature and at a shear rate of 25s^{-1} .
- 50 2. A process according to claim 1 wherein the structuring agent comprises at least one ingredient having more than one hydroxyl functional group.
3. A process according to claim either of the claims 1 or 2 wherein the structuring agent comprises at least one ingredient chosen from the group comprising , polyvinyl pyrrolidone, PVNO, polyvinyl alcohols, polyhydroxyacrylic acid polymers, and mixtures of these.
- 55 4. A process according to either of claims 2 or 3 wherein the structuring agent comprises at least one ingredient chosen from the group comprising dextrose, lactose, sucrose, saccharin and derivatives,

including polyhydroxy fatty acid amides.

5. A process according to any of the previous claims wherein the structuring agent comprises at least one ingredient chosen from the group comprising phthalimide, para-toluene sulphonamide, maleimide and mixtures of these
6. A process according to any of the previous claims characterised in that the structuring agent is a polymer having a molecular weight of at least 2000.
- 10 7. A process according to any of the previous claims wherein the granular laundry detergent component or composition comprises at least 10% by weight of nonionic surfactant.
- 15 8. A process according to any of the previous claims in which the powder in step b) is chosen from the group comprising zeolite, silica, carbonate, silicate, sulphate, phosphate, citrate, citric acid or mixtures of these
9. A process for making a granular laundry detergent component or composition comprising the steps of ;
 - a) dissolving a structuring agent, said structuring agent comprising a polymer, in a nonionic surfactant to form a premix
 - 20 b) mixing said premix with an effective amount of powder by spraying said premix onto said powder in a low shear mixer or a rotating drum characterised in that the premix is sprayed at an operating temperature at which said premix has a viscosity of at least 350 mPas when measured at said operating temperature and at a shear rate of 25s^{-1} .
- 25 10. A process according to claim 9 in which the powder in step b) is a granular detergent which comprises particles prepared by spray drying, agglomeration, or mixtures of these.
11. A process for making a granular laundry detergent component or composition having a bulk density of at least 650 g/l comprising the steps of ;
 - a) dissolving a structuring agent in a nonionic surfactant to form a pumpable premix; and
 - 30 b) finely dispersing said premix with an effective amount of powder characterised in that the fine dispersing of the premix is carried out at an operating temperature at which the premix has a viscosity of at least 350 mPas when measured at said operating temperature and at a shear rate of 25s^{-1} , and that at least some of said powder is in a hydratable form; and
 - c) spraying water on to the product of step b)
- 35 12. A detergent component or composition having a bulk density of at least 650 g/l comprising:
 - i) from 10% to 50% by weight of a nonionic surfactant
 - ii) from 5% to 30% by weight of a structuring agent which is chosen from the group comprising sugars and artificial sweeteners, polyvinyl alcohols, polyhydroxyacrylic acid polymers, and their derivatives; and polyvinyl pyrrolidone, PVNO, phthalimide, para-toluene sulphonamide, maleimide, and mixtures of these.
- 40 13. A detergent component or composition according to claim 12 wherein the ratio of the nonionic surfactant to the structuring agent is from 20:1 to 1:1.
14. A detergent component or composition according to either of claims 12 or 13 wherein the nonionic surfactant comprises an ethoxylated alcohol, the alcohol having a chain length of from 8 to 20 carbon atoms, and an average of from 1 to 25, preferably from 2 to 10 ethoxy groups per molecule of alcohol.
- 50 15. A detergent component or composition according to claim 14 wherein the nonionic surfactant is a liquid at temperatures below 40°C .



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 93 87 0075

DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
D, Y	EP-A-0 513 824 (KAO CORPORATION) * page 8, line 28 - line 54 * * page 11, line 14 - line 22; claims 1-2, 13 * ---	1-4, 6-9, 12, 14-15	C11D17/06 C11D3/37 C11D3/22
D, Y	EP-A-0 215 637 (UNILEVER NV) * abstract * * page 3, line 58 - line 62 * ---	2-4, 6, 12, 14-15	
Y	EP-A-0 364 881 (HENKEL KOMMANDITGESELLSCHAFT AUF AKTIEN) * abstract * * page 3, line 40 - page 4, line 9 * ---	1, 7-9	
A	EP-A-0 508 034 (THE PROCTER AND GAMBLE COMPANY) * page 5, line 15 - line 17; claims 1-7 * ---	12-15	
A	DE-A-1 957 456 (KAO SOAP CO LTD) * claims 1-5 * -----	12-15	TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			A61K C11D
The present search report has been drawn up for all claims			
Place of search	Date of completion of the search	Examiner	
BERLIN	27 OCTOBER 1993	SIATOU E.	
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone	Y : particularly relevant if combined with another document of the same category		
A : technological background	O : non-written disclosure		
P : intermediate document			