

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 644 518 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
06.02.2002 Bulletin 2002/06

(51) Int Cl.7: **G08G 1/127**, G08G 1/0967

(21) Application number: **94850145.7**

(22) Date of filing: **29.08.1994**

(54) **Method in a mobile system, for example a system for short-range communication**

Verfahren in einer mobilen Anlage, zum Beispiel in einer Kommunikationsanlage geringer Reichweite

Procédé dans un système mobile, par exemple un système de communication à faible portée

(84) Designated Contracting States:
DE FR GB IT NL

(30) Priority: **14.09.1993 SE 9302983**

(43) Date of publication of application:
22.03.1995 Bulletin 1995/12

(73) Proprietor: **TELIA AB**
123 86 Farsta (SE)

(72) Inventors:
• **Wichtel, Erik**
S-217 47 Malmö (SE)
• **Andersson, Torbjörn**
S-223 61 Lund (SE)

(74) Representative: **Akerman, Marten Lennart**
Albihns Malmö AB Box 4289
203 14 Malmö (SE)

(56) References cited:

EP-A- 0 242 099 **EP-A- 0 501 058**
US-A- 5 173 710

- **PROCEEDINGS OF THE VEHICLE NAVIGATION AND INFORMATION SYSTEMS CONFERENCE, DEARBORN, OCT. 20 - 23, 1991, vol. PART 2, 1 October 1991, INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS, pages 923-928, XP000357197 WALL N: "INTEGRATED COMMUNICATIONS ARCHITECTURE FOR ROAD TRANSPORT INFORMATICS"**
- **VTC 1994. 'CREATING TOMORROW'S MOBILE SYSTEMS'. 1994 IEEE 44TH VEHICULAR TECHNOLOGY CONFERENCE (CAT. NO.94CH3438-9), PROCEEDINGS OF IEEE VEHICULAR TECHNOLOGY CONFERENCE (VTC), vol. 1, 8 - 10 June 1994, STOCKHOLM, SWEDEN, pages 396-400, XP002001655 WICHTEL E ; AKKE M ; ANDERSSON T : "Virtual beacons for RTI/IVHS data distribution "**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 644 518 B1

Description

TECHNICAL FIELD

[0001] The present invention relates to a method for a mobile system, for example the RTI system which is a system for short-range communication between a vehicle and the roadside. The mobile system comprises mobile units and beacons (radio beacons), by means of which information on traffic, for example vehicle traffic, can be executed in dependence on information transferred from the mobile units to the said beacons, and vice versa, when the mobile units are passing the latter.

PRIOR ART

[0002] The RTI system, for example, is based on data communication between a vehicle and the roadside. The data communication requires a new infrastructure built around beacons with short range.

[0003] In the publication "Integrated Communication Architecture for Road Transport Informatics, second international conference on beacon navigation and information systems, N Wall et al. 1991, volume 2, pages 923 - 928, ISBN: 07800304888", different ways of introducing an RTI system by integrating existing systems, for example RDS-TNC, GSM-based SOKRATES, beacon systems and so forth are discussed. A virtual RTI system based on an infrastructure with a multiplicity of communication systems including GSM, beacons and satellites is also briefly disclosed. However, the virtual network is only discussed superficially.

[0004] In European Patent Specification EP 172 320 913 a method for locating a mobile telephone is specified. The fixed base stations transmit identity signals and precise timing pulses from their fixed locations. The signal transfer occurs either as a response to an interrogation signal from the mobile or automatically at predetermined time intervals. The mobile unit can utilize internally stored tables of positions of the fixed base stations when calculating its own positions. The method is intended to be used for monitoring and controlling vehicle traffic. The method entails that high costs for setting up a new fixed infrastructure for traffic monitoring can be avoided.

[0005] European Patent Specification 242,099 describes a method for locating a vehicle, for example in the case of the theft of a car. A unit in the vehicle calculates the position of the vehicle with the aid of a GPS system. This position is transmitted to a central monitoring station via a mobile telephone system if a break-in is detected or if a change in position is detected.

[0006] American Patent Specification US 5,043,736 discloses a cellular locating system. The system consists of a portable locating unit which can be used both as mobile telephone and for global positioning. The unit has a receiver for receiving signals from a global positioning system (GPS) and circuits for calculating the po-

sition. The position thus obtained is then transmitted to the central unit via a mobile telephone system. The central unit contains a capability for correlating the position obtained with a stored digital map in order to place the user at his current location on the map.

[0007] As prior art, reference can also be made to American Patent Specification US 4,701,760 which describes a method for positioning vehicles and for making possible communication between the vehicles and a central unit. The coordinates of the vehicles are determined with the aid of an omega network and corrected when control beacons are passed.

[0008] In the publication "Integration of GPS and Dead-reckoning Navigation Systems, second international conference on beacon navigation and information systems, W Kao, 1991, volume 2, pages 635 - 643, ISBN: 780304888", a positioning system is described which utilizes both GPS and dead-reckoning for improving the accuracy in, for example, a traffic monitoring/road guidance system.

[0009] It is thus known to position vehicles by different means and to transfer position data and other data between the vehicles and a central unit by different means. In the known cases, the position determination and data transfer occur via other media than fixed beacons. It is thus known to utilize an existing positioning system for determining the position of a vehicle and then to transfer this position via an existing communication network of, for example, cellular type to a centrally placed unit. The position information is correlated with a centrally stored database containing terrain maps, for example a digital map.

DESCRIPTION OF THE INVENTION

[0010] The invention can be used, inter alia, in RTI (Road Transport Informatics) systems which to a large extent will probably be built on data access through beacon systems, that is to say special systems for short-range access between a vehicle and the roadside. The range of a beacon is 10 - 500 metres depending on the technology used. Beacon systems are not continuous and do not have a hand-over capability which thus entails patchy coverage with areas without coverage in-between.

[0011] The data structure in a beacon system is adapted to the discontinuous coverage. On passing a beacon, the vehicle receives a standard set of data which describes the traffic environment of the nearest surrounding area. The vehicle reports the traffic situation on the route most recently travelled which is then used by the beacon system for updating the traffic situation. Individual transactions for a range of applications can also be carried out.

[0012] Applications and hardware in the car will most probably be produced specially for beacon systems. The equipment will only function in areas with a welldeveloped beacon system. The development of a beacon

infrastructure is costly and can only be justified in areas with a large population base. Apart from parts of Stockholm and Göteborg, all of Sweden can be considered to be sparsely populated in this connection.

[0013] For reasons of infrastructure costs, beacon systems cannot be developed in all parts of the country where there is need. The pace of development is limited by the will to take economic risks. Nor will customers buy the system or subscribe to it before the extent of development is good and there is adequate application access.

[0014] GSM offers an attractive alternative medium for area coverage when the user population is moderate. The use of GSM has been investigated, inter alia, in the so-called SOKRATES project which has an information structure which is radically different from the structure of short-range communication systems. In order to introduce SOKRATES, new services must also be introduced in GSM (broadcast, or respectively a low-quality mass uplink for statistical data collection etc.). However, standardization organizations have no plans to introduce these functions in a foreseeable time.

[0015] Since SOKRATES is wholly based on cellular technology, the narrow frequency band of the cellular system limits capacity. The invention intends, inter alia, to solve the problems specified above.

SOLUTION

[0016] According to the invention, a method for communicating within the coverage area of an RTI system is suggested. Upon passing a stationary element placed at a position on the roadside, a mobile unit comprised in a vehicle exchanges road and traffic information with said stationary element. The method comprises the step of defining an arbitrary additional position within said coverage area as having the desired property that, when any mobile unit passes said additional position, road and traffic information transfer between said mobile unit and the fixed part of the RTI system is initiated. This desired property is obtained by storing a plurality of predetermined additional positions, and information on road and traffic for each of said additional positions, in a central storing unit provided in the RTI-system, and communicating by using a mobile telephony system between the central storing unit and a mobile unit when the mobile unit passes any one of the said predetermined additional positions.

[0017] Hence at least some of the beacons of the mobile system are of a virtual type, by which is meant that positions which represent the said virtual beacons are specified in the system, preferably in the centrally placed elements of the system, and that an alternative medium, for example a cellular mobile telephone system which can be of a known type, cooperates in order to access data between a respective mobile unit and a respective virtual beacon.

[0018] Preferably, virtual beacons are placed out in

the mobile system, during its development phase, in less traffic-and/or use-intensive areas of the total coverage area of the mobile system. With increased traffic or, respectively, use in the said areas, the virtual beacons are replaced by real beacons, which saves frequency in the area(s) where the replacement occurs.

[0019] Alternatively, a number of operable parallel mobile systems are included which are allocated to competitors or are complementary to one another. The complementary systems can operate with a common basic database and be directed, with matching services, to interested parties, for example petrol firms which then obtain the opportunity, through the system, of marketing, for example information sections which emphasise their own product, for example a hotel, goods or petrol, and are priced free.

[0020] Preferably, similar or the same data structures are used both for real and virtual beacons. In the case with a real beacon, the data are stored locally in the affected beacon, which is placed at the roadside or in the vicinity of the road. In the case with virtual beacons, the data are stored centrally since the local node does not exist in reality. When the virtual beacon is replaced by a real beacon, the centrally stored data are transferred to the real beacon, that is to say the data are executed locally. Even if the main part of all communication takes place with a virtual beacon, some of the services affected can utilize the characteristics of the cellular carrier system whereby it becomes possible for the virtual beacon system to utilize advantages which are associated both with the beacon-oriented system and the cellular system.

[0021] Virtual beacons included in the system are placed outside the areas of the system with the most traffic or greatest traffic load.

[0022] The position function is in control when contact is established between a respective mobile unit and respective virtual beacon which entails that a significant proportion of the RTI traffic in heavily loaded geographic areas is avoided or alternatively that designation of real beacons can take place. RTI traffic can thus be directed towards base stations with less loading and a more even total loading structure be achieved in the cellular system, for example the GSM system.

ADVANTAGES

[0023] Through that which has been proposed above, the investment risk for real beacons can be minimized before market acceptance and service maturity are attained. Coverage is attained in areas which cannot economically justify real beacons. Contributions to for example GSM development in sparsely populated areas can be obtained through this new type of traffic, as well as an increased traffic data base in sparsely populated areas as a shortterm situation. All locations with lack of capacity are provided with real beacons so that competition between RTI and call customers does not need to

be experienced. A virtual beacon system can be given a very high capacity increase for RTI, partly due to the fact that virtual beacons are placed where the carrying system has lower capacity utilization and partly through implementing real beacons where the communication requirement is high.

[0024] In principle, virtual beacon systems can be tailored for larger customers. The flexibility is considerable as compared with traditional beacon systems. Virtual beacon systems can be operated, for example in Sweden, but also in networks of operators of other countries within Europe, assuming that the carrying system is GSM.

[0025] The invention supplements beacon-based systems with functional capabilities in areas without beacons. Functionalities which were lost by there not being any beacon coverage are replaced, and such functionalities can be position determination and data access. The SOKRATES project has the aim of providing the same functionality with, for example, GSM access as does the beacon system. The problem with SOKRATES is, however, that the data and application structures are in principle different from beacon systems. Separate database and application infrastructures must be built up if the system is to be put into operation. Vehicles which wish to use both beacon-based applications and SOKRATES must have double sets of processor and display units in the vehicles. This takes up space and costs money, apart from the fact that it is impractical to handle, for example, two parallel road guidance systems in one and the same vehicle. SOKRATES requires new GSM functions which are not going to be introduced within the foreseeable future.

DESCRIPTION OF THE FIGURE

[0026] An arrangement in which the inventive method may be performed will be described below, at the same time referring to the attached drawing, in which

the figure shows in basic diagram form a coverage area of a mobile system where virtual beacons are set up in first partial areas and real beacons are set up in a second partial area.

[0027] In the figure, a coverage area of a beacon-oriented system according to the invention is shown by 1. The coverage area comprises a number of partial areas A, B and C where so-called virtual beacons VB have been set up. The said partial areas A, B and C are areas which have least traffic loading and utilization. Area D is highly loaded from the point of view of traffic and provided with real beacons RB. Mobile units are moving within the areas and a first mobile unit has been specified by M1 in area D. On passing a real beacon, information or data relating to traffic loading in the nearest surrounding area are transferred from the real beacon to the mobile unit M1. The mobile unit M1 in turn transfers information about the driving of the mobile unit, traffic conditions etc. to the real beacon RB. The majority

of data received is stored locally in the totality of real beacons RB. However, there is a connection to a higher-level unit RB' which is connected to all the real beacons for certain information exchange in the system.

[0028] The virtual beacons VB naturally lack local anchorage in the same way as the real beacons etc. which is why all data relating to traffic intensity, loading are stored centrally, preferably in a central higher-level unit VB' which is common to all the beacons in the different partial areas. Each partial area can per se have a separate higher-level VB'. The said virtual beacons VB are stored in the central unit VB' where the virtual beacons are represented through positions, the geographic positions, which they have been allocated in the different areas A, B and C. When mobile units M2 pass a respective virtual beacon VB, data information is to be exchanged in corresponding manner between the respective mobile unit and the respective virtual beacon. Access and transmission take place at frequencies which belong to a cellular mobile telephony system which is located in the area of the beacon-oriented system. The cellular system has been symbolized by 2 in the figure and can consist of a mobile telephone system known per se, preferably the GSM system. In the illustrative example, the beacon-oriented system consists of the so-called RTI system.

[0029] In the virtual beacon-oriented system, the virtual beacons can be exchanged, increased in number, reduced in number or replaced with the said real beacons RB, in each case depending on a change in the traffic intensity, traffic loadings, vehicle types and so forth. In accordance with the figure, one or more control elements RB' and RB" can be arranged for the said real beacons.

[0030] The invention is not limited to the examples above but can be subjected to modifications within the scope of the subsequent patent claims.

Claims

1. A method for communicating within the coverage area (1) of an RTI system, between a mobile unit (M1, M2) comprised in a vehicle, and a stationary element (RB) placed at a position on the roadside, the mobile unit exchanging road and traffic information with the stationary element when passing said position, the method comprising the step of defining an arbitrary additional position (VB) within said coverage area as having the desired property that, when any mobile unit (M1, M2) passes said additional position (VB), road and traffic information transfer between said mobile unit and the fixed part of the RTI system is initiated, this desired property being obtained by the steps of:
 - storing a plurality of predetermined additional positions (VB), and information on road and

- traffic for each of said additional positions (VB), in a central storing unit (VB') in the RTI system;
- communicating by using a mobile telephony system between the central storing unit and a mobile unit when the mobile unit passes any one of the said predetermined additional positions. 5
2. The method as recited in claim 1, comprising the steps of: 10
- communicating information between mobile units (M1, M2) and the central storing unit (VB') via the mobile telephony system at less traffic- or use-intensive areas of a total coverage area of the RTI system and, when traffic or use of the system increases, 15
 - placing out a new stationary element (RB) at the stored additional position (VB) of the area with increased traffic or use; 20
 - downloading, from the central storing unit (VB'), the stored information for said additional position (VB) into said new stationary element (RB);
 - communicating information between mobiles and the new stationary element at the position of said new stationary element. 25
3. The method as recited in any of the preceding claims, comprising the step of selecting such additional positions as covered by the RTI system in areas where the capacity utilisation of the mobile telephony system is low. 30
4. The method as recited in any of the previous claims, comprising the step of using beacons as stationary elements (RB) in the RTI system. 35
5. The method as recited in any of the previous claims, comprising the step of using a GSM mobile telephony system for transmitting information between mobile units and the central storing unit in the RTI system. 40

Patentansprüche 45

1. Verfahren zum Kommunizieren innerhalb des Abdeckgebietes (1) eines RTI-Systems zwischen einer in einem Fahrzeug enthaltenen Mobileinheit (M1, M2) und einem stationären Element (RB), das an einer Position am Straßenrand angeordnet ist, wobei die Mobileinheit beim Vorbeifahren an der Position Straßen- und Verkehrsinformationen mit dem stationären Element austauscht, wobei das Verfahren den Schritt aufweist, eine willkürliche Zusatzposition (VB) innerhalb des Abdeckgebietes dahingehend zu definieren, daß diese die gewünschte Eigenschaft hat, daß beim Vorbeifahren 50
- 55

irgendeiner Mobileinheit (M1, M2) an der Zusatzposition (VB) die Übertragung von Straßen- und Verkehrsinformationen zwischen der Mobileinheit und dem ortfesten Teil des RTI-Systems eingeleitet wird, wobei diese gewünschte Eigenschaft erhalten wird durch die Schritte:

- Speichern einer Anzahl von vorgegebenen Zusatzpositionen (VB) sowie Straßen- und Verkehrsinformationen für jede dieser Zusatzpositionen (VB) in einer zentralen Speichereinheit (VB') in dem RTI-System;
 - Kommunizieren mittels eines Mobiltelefonsystems zwischen der zentralen Speichereinheit und einer Mobileinheit, wenn die Mobileinheit irgendeine dieser vorgegebenen Zusatzpositionen passiert.
2. Verfahren nach Anspruch 1, mit den Schritten:
- Kommunizieren von Informationen zwischen Mobileinheiten (M1, M2) und der zentralen Speichereinheit (VB') über das Mobiltelefonsystem in Bereichen mit geringerer Verkehrs- oder Benutzungsintensität innerhalb des gesamten Abdeckgebietes des RTI-Systems, und, im Falle einer Zunahme des Verkehrs oder der Benutzung des Systems
 - Aufstellen eines neuen stationären Elementes (RB) an der gespeicherten Zusatzposition (VB) des Bereiches mit Verkehrs- oder Benutzungszunahme;
 - Herunterladen der gespeicherten Informationen für die Zusatzposition (VB) von der zentralen Speichereinheit (VB') in das neue stationäre Element (RB);
 - Kommunizieren von Informationen zwischen Mobileinheiten und dem neuen stationären Element an der Position des neuen stationären Elementes.
3. Verfahren nach einem der vorangehenden Ansprüche, mit dem Schritt des Auswählens solcher, von dem RTI-System abgedeckter Zusatzpositionen in Bereichen, in denen die Kapazitätsausnutzung des Mobiltelefonsystems niedrig ist.
4. Verfahren nach einem der vorangehenden Ansprüche, mit dem Schritt der Verwendung von Richtstrahler als stationäre Elemente (RB) in dem RTI-System.
5. Verfahren nach einem der vorangehenden Ansprüche, mit dem Schritt der Verwendung eines GSM-Mobiltelefonsystems zur Übertragung von Informationen zwischen Mobileinheiten und der zentralen Speichereinheit in dem RTI-System.

Revendications

1. Procédé permettant d'effectuer une communication à l'intérieur de la zone de couverture (1) d'un système RTI, entre une unité mobile (M1, M2) comprise dans un véhicule et un élément fixe (RB) placé en une certaine position sur le côté de la route, l'unité mobile échangeant des informations concernant la route et la circulation avec l'élément fixe lorsqu'elle passe devant ladite position, le procédé comprenant l'opération consistant à définir une position supplémentaire (VB) arbitraire à l'intérieur de la zone de couverture comme ayant la propriété voulue que, lorsqu'une unité mobile (M1, M2) quelconque passe devant la position supplémentaire (VB), un transfert d'informations concernant la route et la circulation entre l'unité mobile et la partie fixe du système RTI est déclenché, cette propriété voulue étant obtenue par les opérations consistant :

- à ranger plusieurs positions supplémentaires (VB) préfixées et des informations concernant la route et la circulation pour chacune des positions supplémentaires (VB), dans une unité de mémoire centrale (VB') faisant partie du système RTI ;
- à effectuer une communication en utilisant un système de téléphonie mobile entre l'unité de mémoire centrale et une unité mobile lorsque l'unité mobile passe devant l'une quelconque des positions supplémentaires préfixées.

2. Procédé tel que défini à la revendication 1, comprenant les opérations consistant :

- à effectuer la communication d'informations entre des unités mobiles (M1, M2) et l'unité de mémoire centrale (VB') par l'intermédiaire du système de téléphonie mobile à l'endroit de zones à circulation ou utilisation moins intense d'une zone de couverture totale du système RTI et, lorsque la circulation ou l'utilisation du système s'accroît,
- à placer un nouvel élément fixe (RB) à l'endroit de la position supplémentaire (VB) mise en mémoire de la zone à circulation ou utilisation accrue ;
- à télécharger, de l'unité de mémoire centrale (VB') jusque dans le nouvel élément fixe (RB), les informations mises en mémoire pour ladite position supplémentaire (VB) ;
- à effectuer la communication d'informations entre des mobiles et le nouvel élément fixe à l'endroit de l'emplacement du nouvel élément fixe.

3. Procédé tel que défini dans l'une quelconque des revendications précédentes, comprenant l'opération consistant à sélectionner des positions supplé-

mentaires qui sont couvertes par le système RTI dans des zones où l'utilisation de capacité du système de téléphonie mobile est faible.

4. Procédé tel que défini dans l'une quelconque des revendications précédentes, comprenant l'opération consistant à utiliser des balises en tant qu'éléments fixes (RB) dans le système RTI.

5. Procédé tel que défini dans l'une quelconque des revendications précédentes, comprenant l'opération consistant à utiliser un système de téléphonie mobile GSM pour transmettre des informations entre des unités mobiles et l'unité de mémoire centrale faisant partie du système RTI.

