



(11) Publication number : **0 670 227 A1**

(12)

## EUROPEAN PATENT APPLICATION

(21) Application number : **95301241.6**

(51) Int. Cl.<sup>6</sup> : **B41N 1/24**

(22) Date of filing : **27.02.95**

(30) Priority : **28.02.94 JP 29785/94**

(43) Date of publication of application :  
**06.09.95 Bulletin 95/36**

(84) Designated Contracting States :  
**DE FR GB**

(71) Applicant : **RISO KAGAKU CORPORATION**  
**20-15, Shinbashi 2-chome,**  
**Minato-ku**  
**Tokyo (JP)**




(72) Inventor : **Watanabe, Hideo, c/o Riso Kagaku Corp.**  
**20-15, Shinbashi 2-chome,**  
**Minato-ku**  
**Tokyo (JP)**  
Inventor : **Okuda, Sadanao, c/o Riso Kagaku Corp.**  
**20-15, Shinbashi 2-chome,**  
**Minato-ku**  
**Tokyo (JP)**

(74) Representative : **Jenkins, Peter David**  
**PAGE WHITE & FARRER**  
**54 Doughty Street**  
**London WC1N 2LS (GB)**

(54) **Stencil for printing sheet and process for stencil-making the same.**

(57) Disclosed is a stencil printing paper and a process for perforating and engraving the same having the advantages in that the production of the stencil printing paper is easy, the resulting production cost can be thereby reduced and there is no generation of any problem at a time of stencil-making. In a stencil printing paper constituted by laminating a solvent-soluble resin layer to a porous substrate the present invention comprises a stencil printing paper containing an acetalized polyvinyl alcohol having an acetalization degree of 1 - 70 mol% and a process for perforating and engraving the stencil printing paper by a mixed solvent containing water and an alcohol type solvent.

**FIG. 1**



The present invention relates to a stencil printing sheet and a method for stencil-making the same. Specifically, it relates to a stencil printing sheet having a solvent-soluble resin layer and its stencil-making method.

As a stencil printing sheet, a heat-sensitive stencil sheet has been conventionally been known which is obtained by superposing a thermoplastic resin film on a porous substrate and adhering to each other. As for methods for preparing a heat-sensitive stencil sheet, there have been known the following methods, for example, (1) a method for stencil-making by using a heat-generating device of a flush lamp, infrared lamp or others, superposing a hand-written manuscript or preliminarily prepared manuscript on a heat-sensitive sheet, and melting and perforating a thermoplastic resin film by the generated heat from the device described above, (2) a method for stencil-making by using a thermal head for generating a letter image information converted into an electric signal as a dotting heat, bringing a heat-sensitive stencil sheet in contact with the thermal head, and melting and perforating the thermoplastic resin film. However, since the methods for stencil-making described above requires a series of complicated processes for bringing a light-absorbed and heat-generated manuscript or thermal head in contact with a heat-sensitive stencil sheet, conveying the heat to the thermoplastic resin film in the heat-sensitive stencil sheet to melt the thermoplastic resin film, and subsequently contracting the melted material so as to perforate the thermoplastic resin film, there were some problems, for example, (1) a perforation failure is produced due to the bad contact between a thermoplastic resin film and a manuscript or thermal head for absorbing the heat; (2) adhesion failure is produced due to the nonuniformity in contact pressure of the thermal head, or shrinkage is produced in the heat-sensitive stencil sheet; (3) transfer failure of the heat-sensitive stencil sheet is produced by the melted material of the thermoplastic resin being adhered to the thermal head; (4) printing failure is produced since the melted material is left in the perforated portion and the passage of the ink is prevented; and others.

In recent years, a further improvement in quality of heat-sensitive stencil sheet is demanded. It is demanded to provide such a heat-sensitive stencil sheet that satisfies the smoothness of a thermoplastic resin film, the separating property of the thermoplastic resin film from the manuscript or thermal head, the melting property and the shrinkability of a thermoplastic resin film heat due to heat, the adhesive strength between a thermoplastic resin film and a porous substrate, and the mechanical strength and abrasion of the porous substrate, and therefore, the condition for producing heat-sensitive stencil sheet becomes complicated and there was the problem that the production cost was accordingly increased.


It is, accordingly, an aim of the present invention to solve the above-mentioned problems in the prior art and provide such a heat-sensitive stencil sheet and a sheet-making method thereof as to be thereby produced easily and in a low cost, and generate no problems at a time of stencil-making as well.

The present invention provides a stencil printing sheet which comprises a porous substrate and a solvent-soluble resin film laminated thereon wherein the solvent-soluble resin film contains an acetalized polyvinyl alcohol at an acetalization degree of 1 - 70 mol%.

The present invention also provides a process for stencil-making of a stencil printing sheet consisting of a porous substrate and a solvent-soluble resin film laminated thereon, which comprises perforating the stencil printing sheet by dissolving the solvent-soluble resin film with a mixed solvent of water and an alcohol type solvent.

The solvent-soluble resin film in the present invention contains an acetalized polyvinyl alcohol at an acetalization degree of 1 - 70 mol%, preferably 3 - 50 mol%, as a main component. If the degree of acetalization in polyvinyl alcohol is less than 1 mol%, the stencil printing sheet is inferior in its water resisting property, and if it exceeds 70 mol%, the stencil printing sheet is reduced in oil resistance. Since it contains such an acetalized polyvinyl alcohol as a main component, ink resisting property of the stencil printing sheet to water-soluble ink, oily ink, emulsion ink and other is improved.

As an acetalized polyvinyl alcohol, formal resins, butyral polymers and the like represented by the following general formula (1) may be preferably used.



In the formula, R represents a hydrogen atom or alkyl group, 1 is defined in the range of 1 - 70 mol%, m is defined preferably in the range of 1 - 10 mol%, and n is defined preferably in the range of 1 - 90 mol%, respec-

tively. The ratios of 1, m and n are appropriately chosen depending upon the flexibility of the resin film, its compatibilities to other resins, its solubilities into other solvents, and so forth.

The solvent-soluble resin film can contain besides the acetalized polyvinyl alcohol described above, a thermoplastic resin or thermosetting resin soluble in a solvent, such as water or an organic solvent as well, so long as the water resisting property and oil resistance thereof at a time of printing are not prevented.

As for an organic solvent-soluble resin, there is exemplified polyethylene, polypropylene, polyisobutylene, polystyrene, polyvinyl chloride, polyvinylidene chloride, polyvinyl fluoride, polyvinyl acetate, acryl resin, polyacrylonitrile, polyamide, polyimide, petroleum resin, phenolic resin, amino resin, epoxy resin, polyester, polycarbonate, polyurethane, polysulfone, silicone resin, alkyd resin, melamine resin or the like. These resins may be used independently, in a form of an admixture of a plurality of resins or in a form of a copolymer of their monomers as well.

As for a water-soluble resin, a resin soluble in water or in a water-miscible solvent, there is exemplified methyl cellulose, carboxymethyl cellulose, hydroxyethyl cellulose, polyvinyl pyrrolidone, polyethylene-polyvinyl alcohol copolymer, polyethylene oxide, polyvinyl ether, polyacrylamide, starch, dextrin, alginic acid, ascorbic acid, water-base urethane or the like. These resins may be used independently, in an admixture of a plurality of resins, or in a form of a copolymer of their monomers as well.

Furthermore, dyestuffs, pigments, fillers, binders and curing agents can be contained in the solvent-soluble resin film in addition to the resin components described above.

The thickness of the solvent-soluble resin film is usually in the range of 0.1 - 100  $\mu\text{m}$ , and preferably, in the range of 1 - 50  $\mu\text{m}$ , from the standpoints of strength of the resin film and perforation ability thereof depending upon a solvent.

As a porous substrate used in the present invention, there is exemplified Japanese paper and fibers cloth using natural fibers such as Manila hemp, pulp, Mitsumata (*Edgeworthia papyrifera* Sieb.), Kozo (*Broussonetia kazinoki* Sieb.), synthetic fibers, such as that of polyester, nylon, vinylon, acetate fiber or the like, a thin leaf paper using metallic fiber, glass fiber, non-woven cloth or the like. These porous substrates can be independently or in the combination of two or more kinds thereof. Each basis weight of these porous substrate is usually, in the range of 1 - 20  $\text{g/m}^2$  and preferably, in the range of 5 - 15  $\text{g/m}^2$ , from the standpoints of the strength of the paper and the permeability of the ink. Also, the thickness of the porous substrate is usually, in the range of 5 - 100  $\mu\text{m}$ , and preferably, in the range of 10 - 50  $\mu\text{m}$ , from the standpoints of the strength of the paper and the permeability of the ink.

The stencil printing sheet of the present invention is comprised by laminating a solvent-soluble resin film on a porous substrate.

The stencil printing sheet of the present invention can be produced by e.g., a process (1) for laminating a solvent-soluble resin film to a porous substrate with an adhesive or sticking agent, a process (2) for applying a heat-adhesion to a resin film and a porous substrate, a process (3) for coating a resin solution dissolved or dispersed into a solvent on a porous substrate and then drying the same, a process (4) for coating a solvent or dispersed resin solution on a separating substrate and drying to form a resin film, superposing a porous substrate on the formed resin film and peeling off the separating substrate, and other processes. Organic solvents, in addition to water or alcohol type solvent, can be used and properly chosen depending upon the drying property, working property, coating property and others when the stencil printing sheet is produced.

Since a stencil printing sheet of the present invention has a solvent-soluble resin film, once the resin film is brought in contact with a solvent which dissolves the resin film, the resin film in the contacted portion starts dissolving into the solvent and then, the resin film dissolves in the solvent up to its saturation in solubility. The solution which dissolved the resin film permeates into the interior of the porous substrate and the resin film corresponding to of this portion is perforated. Since the solution which dissolved the resin film permeates into the porous substrate, the dissolved component is not left in the perforated portion of the resin film and does not obstruct the perforation. Furthermore, the perforating property of the resin film can be adjusted by controlling the solubility of the solvent to the resin film and the quantity of the contacting solvent.

As a solvent which dissolves the solvent-soluble resin film on the stencil printing sheet of the present invention, a mixed solvent containing water and an alcohol type solvent is used as a main component. As a solvent such alcohol type, monohydric alcohol, polyhydric alcohol, aliphatic saturated or unsaturated alcohol, alicyclic alcohol, aromatic alcohol, heterocyclic alcohol or the like are used. As a specific example, there is exemplified methyl alcohol, ethyl alcohol, isopropyl alcohol, n-propyl alcohol, butyl alcohol, isoamyl alcohol, hexyl alcohol, octyl alcohol, decyl alcohol, stearyl alcohol, allyl alcohol, cyclohexanol, benzyl alcohol, furfuryl alcohol, ethylene glycol, diethylene glycol, propylene glycol, 1,4-butanediol, 1,5-pentanediol, ethylene chlorohydrin, carbitol, glycerine, hydrobenzoin, benzpinacol, cyclopentane-1,2-diol or the like.

Also, the above-mentioned mixed solvent with water may also contain other organic solvents, such as those of aliphatic hydrocarbon type, aromatic hydrocarbon type, ketone type, ester type, ether type, aldehyde

type, carboxylic acid type, fatty ester type, amine type, low molecular heterocyclic compounds, oxide type and the like. Specifically, hexane, heptane, octane, benzene, toluene, xylene, acetone, methyl ethyl ketone, ethyl acetate, propyl acetate, ethyl ether, tetrahydrofuran, 1,4-dioxane, formic acid, acetic acid, propionic acid, formaldehyde, acetaldehyde, methylamine, ethylenediamine, dimethylformamide, pyridine, ethylene oxides and others are exemplified.

Also, these solvents may contain dyestuffs, pigments, fillers, binders, hardeners, antiseptics, swelling agents, surfactants, pH controllers and others, if necessary.

The stencil-making of the stencil sheet of the present invention may be carried out by bringing a means, such as a brush pen impregnated with a water base solvent, in contact with a resin film directly soluble in the water base solvent, but it is preferable to stencil-make by supplying the water base solvent to the resin film in a non-contact condition by an ejecting device of the water base solvent so as to perforate it. As for a solvent ejecting means, there is exemplified such an apparatus that a nozzle, a slit, an injector, a porous material, a porous film or the like is connected to a liquid feed pump, a piezoelectric element or heating element so as to eject the solvent intermittently or continuously, in a dot or in a line form corresponding to each letter and picture image signal.

According to the present invention, it is possible to carry out the stencil-making of the stencil printing sheet in a non-contact condition with the resin film to a stencil-making apparatus, there is no generation of wrinkles at a time of stencil-making. Also, differently from a conventional heat-sensitive stencil sheet, no molten material is left the perforated portion and a brilliant printed matters can be obtained. Furthermore, the stencil printing sheet of the invention can be produced without need of any separating property, abrasion and mechanical strength of the sheet as required in the conventional heat-sensitive stencil sheet.

The stencil printing sheet obtained by the process of the invention can be applied to a general stencil printing process to obtain a printed matter. For example, a printed matter can be obtained by mounting an ink on a perforated stencil printing sheet, passing the ink through each portion perforated by press rolls, reduced pressure means or squeegee rolls and transcribing the ink to a printing paper.

Since the stencil printing sheet of the present invention is excellent in brilliant printed matters, water resisting property and oil resistance can be obtained even in use of any type of ink, such as an oily ink usually used in stencil printing, water-base ink, water-in-oil emulsion ink, oil-in-water emulsion ink, and others, by using such a printing ink as used in a conventional printing as an oily ink, a water-base ink, an oil-in-water (W/O) type emulsion ink, a water-in-oil (O/W) type emulsion ink and others can be used.

Embodiments of the present invention will now be described by way of example only with reference to the accompanying drawings, in which:-

FIG. 1 is a sectional model view showing a stencil printing sheet as a preferred embodiment of the invention;

FIG. 2 is an explanatory view showing a perforation of the stencil printing sheet of FIG. 1;

FIG. 3 is a diagram showing a production process of a stencil printing sheet as an alternative preferred embodiment of the invention; and

FIG. 4 is an explanatory view showing a perforation of the stencil printing sheet of FIG. 3.

The invention will be given specifically with reference to examples in the following. It should be understood, however, that these examples do not limit the scope of the present invention.

In these figures, reference characters 1 to 19 means the following:

1. polyester fiber cloth;
2. solvent-soluble resin film;
3. polyester fiber;
4. stencil printing sheet;
5. ejecting solvent;
6. contacting solvent;
7. resin solution for dissolving resin film and adhering to polyester fiber;
8. perforated portion in resin film; 9 and 10. ejection means;
11. solvent-soluble resin film;
12. polyester sheet;
13. Japanese paper;
14. adhesive or sticking agent immersed in Japanese paper;
15. stencil printing sheet;
16. ejecting solvent;
17. contacting solvent;
18. resin solution permeated into Japanese paper;
19. perforated resin film.

## Example 1

A polyester fiber cloth having a sieve opening of 280 mesh was immersed in a resin solution consisting of the following resin composition, picked up from it and dried off. Then, a resin film of 3  $\mu\text{m}$  in thickness was provided in the gap of the mesh to give a stencil sheet.

Butyral resin	10 parts by weight
(polyvinyl alcohol having a butyralization degree of 40 mol%)	
Methyl ethyl ketone	50 parts by weight
Toluene	20 parts by weight
1,4-dioxane	20 parts by weight

An aqueous solution consisting of the following composition was ejected in a letter shape to the stencil printing sheet described above from an ejecting means provided with a nozzle of 8 dots/mm and a piezoelectric element connected thereto, and the polyvinyl alcohol film at the ejected portion was dissolved and perforated.

Ethyl alcohol	50 parts by weight
Ethylene glycol	10 parts by weight
Ethyl acetate	10 parts by weight
water	30 parts by weight

Subsequently, a black ink (HI-MESH, trademark of Riso Kagaku Corporation) for use in a portable stencil printing device, PRINT GOKKO (trademark of RISO Kagaku Corporation) was mounted on the side of the polyester fiber cloth of the engraved stencil printing sheet, and the other side was superposed on a printing sheet to carry out printing by squeegeeing the ink by a blade, resulting in printing brilliantly the similar letters to those of the perforated portions.

FIG. 1 shows a sectional model view of a stencil printing sheet obtained in Example 1, in which (A) shows a sectional model view of a polyester fiber cloth 1, (B) shows a sectional model view of a stencil printing sheet 4 forming a solvent-soluble resin film 2 on a polyester fiber 3, and (C) shows a perspective view illustrating a stencil printing sheet 4 in a model form, respectively.

FIG. 2 is an explanatory view showing a perforation of a stencil printing sheet. (A) of FIG. 2 is a model view showing stencil-making and once solvents 5 and 6 are ejected from a solvent ejection means 9 and the ejected solvent is brought into contact with the surface of the stencil printing sheet 4, the solvent-soluble resin film at the contacted portion is dissolved and perforated. In the drawing, 7 represents a resin solution which dissolved the resin film and adhered to the polyester fiber cloth, and 8 represents a perforated portion of the resin film, respectively. (B) of FIG. 2 is a perspective view showing a perforated stencil printing sheet in a model form.

## Example 2

A resin solution consisting of the following composition was coated by a roll coater on a separating paper treated with silicone and dried off to obtain a solvent-soluble resin film of 3  $\mu\text{m}$  in thickness thereon.

Formal resin	10 parts by weight
(Polyvinyl alcohol having a formalization degree of 20 mol%)	
Methyl ethyl ketone	30 parts by weight
Isopropyl alcohol	50 parts by weight
1,4-dioxane	10 parts by weight

Then, an adhesive solution consisting of the following composition was coated on a Japanese paper having

a basis weight of 12 g/m<sup>2</sup> and dried off. Subsequently, the thus obtained solvent-soluble resin film on the separating paper was superposed on the adhesive layer on the Japanese paper and the separating paper was peeled off to give a stencil printing sheet.

5

Ethylene - vinyl acetate copolymer	20 parts by weight
Toluene	80 parts by weight

10

A mixed solvent having the following composition was ejected in a letter shape on the surface of the resin film of this stencil printing sheet from the similar means as shown in Example 1 and the resin film in the ejected portions was dissolved to perforate the stencil printing sheet, resulting in stencil-making.

15

Isopropyl alcohol	30 parts by weight
Glycerine	10 parts by weight
Water	60 parts by weight

20

While a printing paper was superposed on the Japanese paper of the stencil sheet and a black oily ink was mounted on the other surface of the stencil sheet, the ink was squeegeed by a blade. Brilliant letters in the same shape as the perforated portion were printed in the printing paper by means of PRINT GOKKO PG-10 (trademark of Riso Kagaku Corporation).

### Example 3

25

A resin solution consisting of the following composition was coated by a roll coater on a polyester sheet of 30  $\mu$ m in thickness and dried off to obtain a solvent-soluble resin film of 2  $\mu$ m in thickness thereon.

30

Formal resin	10 parts by weight
(Polyvinyl alcohol having a formalization degree of 10 mol%)	
Tetrahydrofuran	20 parts by weight
Isopropyl alcohol	30 parts by weight
Water	40 parts by weight

35

40

Then, an adhesive solution consisting of the following composition was coated with the similar adhesive solution to that of Example 2 on a Japanese paper having a basis weight of 12 g/m<sup>2</sup> and dried off. Subsequently, the thus obtained solvent-soluble resin film on the polyester sheet was superposed on the adhesive layer on the Japanese paper and the polyester sheet was peeled off to give a stencil printing sheet.

Then, by replacing the ink in the ink jet printer with a mixed solvent having the following composition, the solvent was ejected to the stencil printing sheet described above from the nozzle of this ink jet printer while making it corresponded to the letters and images prepared by a personal computer and transited them to the solvent-soluble resin film, resulting in stencil-making by perforating the stencil sheet.

45

Isopropyl alcohol	30 parts by weight
Diethylene glycol	10 parts by weight
Water	60 parts by weight

50

When the thus engraved stencil printing paper is printed in similar to that of Example 2, good printed matters were obtained of the stencil paper.

FIG. 3 shows a view of a production process for a stencil printing paper in Example 3. In FIG. 3(A), a solvent-soluble resin film 11 is formed on a polyester sheet 12, and in FIG. 3(B), an adhesive or sticking agent layer 14 is formed on a Japanese paper 13. In FIG. 3(C), the solvent-soluble resin film 11 and the adhesive or sticking agent are superposed on each other and the polyester sheet 12 on the solvent-soluble resin film 11 is peeled off to give a stencil printing sheet 15.

55

FIG. 4 is an explanatory view showing a perforation of a stencil printing sheet. In the drawing, a solvent

16 is ejected from a solvent ejection means 10 and the ejected solvent is brought in contact with the surface of the stencil printing sheet. The contacting solvent 17 dissolves the resin film at the contacted portion. The dissolved solution 18 permeates into the interior of the Japanese paper and the contacted portion is perforated, resulting in giving a perforated resin film 19.

#### Example 4

A resin solution consisting of the following composition was coated by a roll coater on a polyethylene film treated with silicone and dried off to obtain a solvent-soluble resin film of 30  $\mu\text{m}$  in thickness thereon.

Formal resin	10 parts by weight
(Polyvinyl alcohol having a formalization degree of 10 mol%)	
Acetone	10 parts by weight
Ethyl alcohol	50 parts by weight
Water	30 parts by weight

Then, a polyester fiber cloth having an opening sieve of 200 mesh was immersed in an adhesive solution consisting of the following composition, picked up therefrom and dried off. This and the above-mentioned soluble resin film were superimposed on each other and left in a thermo-statt at 40°C overnight.

Acryl resin	20 parts by weight
Isocyanate	5 parts by weight
Toluene	45 parts by weight
Ethyl acetate	30 parts by weight

Then, the polyester film was peeled off from the resin film to give a stencil printing sheet. Subsequently, a water-base ink was ejected onto the solvent-soluble film of the above-mentioned stencil printing sheet by a commercially available word processor of an ink jet type, and transited to the solvent-soluble resin film to perforate it. The thus engraved stencil printing sheet was set to the printing drum of a commercial stencil printing machine, RISOGRAPH RC115 (trademark of RISO KAGAKU CORPORATION) and the printing was carried out to give the similar brilliant letters and images to those recorded by the ink jet word processor used in stencil-making.

#### Comparative Example 1

A stencil printing sheet was prepared and a stencil-making was carried out thereon by following the similar procedure to that in Example 1 except that the solvent-soluble resin film in Example 1 was altered to the following resin composition.

Butyral resin	10 parts by weight
(polyvinyl alcohol having a butyralization degree of 80 mol%)	
Methyl ethyl ketone	50 parts by weight
Toluene	40 parts by weight

This engraved stencil printing sheet was printed in the similar manner to that of Example 1. However, the resin film of other areas than the perforated portion started dissolving by the oily component of the ink, resulting in giving unclear printed matters.

## Comparative Example 2

A stencil printing paper was prepared and a stencil-making was carried out thereon by following the similar procedure to that in Example 4 except altering the solvent-soluble resin film in Example 4 to the following resin composition.

Polyvinyl alcohol	10 parts by weight
Ethyl alcohol	50 parts by weight
Water	30 parts by weight


This engraved stencil printing sheet was printed in the similar manner to that of Example 4. However, the resin film of other areas than the perforated portion started dissolving by the water component of the ink, resulting in giving unclear printed matters.

According to the stencil printing sheet of the present invention, since the stencil printing sheet of the present invention can be perforated by a solvent in its non-contact condition, there is no generation of any wrinkles and the like. Since no residues are left in the perforated portion, brilliant pictures can be obtained. Furthermore, since there is no need of considering the separability, antifriction, mechanical characteristics and the like to the thermal head as a case in the prior art, the resulting production becomes easy and the production cost can be reduced as well. Moreover, the solvent-soluble resin layer has water-resisting property and oil resistant, resulting in providing brilliantly printed matters by an oily ink, water-base ink, emulsion ink or the like.

In addition, since a mixed solvent of water and alcohol type solvent is used when the stencil-making is carried out according to the process of the present invention, the resulting environmental safety is improved thereby.

## Claims

1. A stencil printing sheet which comprises a porous substrate and a solvent-soluble resin film laminated thereon, wherein said solvent-soluble resin film contains an acetalized polyvinyl alcohol having an acetalization degree of 1 - 70 mol%.
2. A stencil printing sheet according to claim 1, wherein said acetalized polyvinyl alcohol has an acetalization degree of 3 - 50 mol%.
3. A stencil printing sheet according to claim 1, wherein said acetalized polyvinyl alcohol is represented by the following formula:



wherein R represents a hydrogen atom or alkyl group, 1 is defined in the range of 1 - 70 mol%, m is defined in the range of 1 - 10 mol%, and n is defined in the range of 1 - 90 mol%.

4. A process for stencil-making of a stencil printing sheet consisting of a porous substrate and a solvent-soluble resin film laminated thereon, which comprises perforating said stencil printing sheet by dissolving said solvent-soluble resin film with a mixed solvent of water and an alcohol type solvent.



FIG. 1




FIG. 2




FIG. 3





FIG. 4





European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 95 30 1241

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	GB-A-707 160 (A.B. DICK COMPANY) * page 2, line 107 * ---	1-4	B41N1/24
E	EP-A-0 648 615 (RISO KAGAKU CORPORATION) * page 3, line 11 * ---	1-4	
E	EP-A-0 642 929 (RISO KAGAKU CORPORATION) * page 3, line 11 * ---	1-4	
E	EP-A-0 642 930 (RISO KAGAKU CORPORATION) * page 3, line 8 * ---	1-4	
T	'Encyclopedia of polymer science and technology', JOHN WILEY & SONS Volume 14, 1971 * page 210, line 10 - line 14 * ---	1	
A	EP-A-0 108 509 (PILOT MAN-NEN-HITSU) * the whole document * ---	1	
A	GB-A-255 361 (DAVID GESTETNER) * the whole document * -----	1	<b>TECHNICAL FIELDS SEARCHED (Int.Cl.6)</b>  B41N
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>13 July 1995</b>	Examiner <b>Rasschaert, A</b>
<b>CATEGORY OF CITED DOCUMENTS</b> X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... & : member of the same patent family, corresponding document			

EPO FORM 1503 03.92 (P04C01)