

# **Europäisches Patentamt**

# **European Patent Office**

#### Office européen des brevets



(11) **EP 0 721 133 A3** 

#### (12)

### **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3: 04.12.1996 Bulletin 1996/49

(43) Date of publication A2: 10.07.1996 Bulletin 1996/28

(21) Application number: 95119099.0

(22) Date of filing: 05.12.1995

(51) Int. Cl.<sup>6</sup>: **G03C 1/76**, G03G 5/10, G02B 27/28


- (84) Designated Contracting States:

  DE FR GB
- (30) Priority: 08.12.1994 US 351995
- (71) Applicant: EASTMAN KODAK COMPANY Rochester, New York 14650-2201 (US)
- (72) Inventors:
  - Blazey, Richard N.,
     c/o Eastman Kodak Co.
     Rochester, New York 14650-2201 (US)

- Tsou, Andy H.,
   c/o Eastman Kodak Co.
   Rochester, New York 14650-2201 (US)
- (74) Representative: Blickle, K. Werner, Dipl.-Ing. et al KODAK AKTIENGESELLSCHAFT Patentabteilung 70323 Stuttgart (DE)

#### (54) Control of non-contact interference fringes in photographic films

A photographic optical system for substantially eliminating non-contact interference fringes in a photographic film comprises: (a) a source of polarized electromagnetic radiation, the radiation being characterized by a wavelength and an incident polarization angle; and (b) a photographic film capable of optical communication with the source and serving to transmit or reflect a portion of the radiation, the film comprising a silver halide emulsion layer on a birefringent support, the support being characterized by a thickness, an emulsion layer interface, an air interface, and birefringence that is dependent on the wavelength of the radiation; wherein the radiation wavelength and incident polarization angle and the support thickness and birefringence are selected such that radiation which penetrates the film and reflects from the air interface exits the support at the emulsion layer interface polarized at an angle substantially perpendicular to the incident polarization angle; whereby the photographic film may be imaged by the source of polarized electromagnetic radiation substantially without formation of non-contact interference fringes. In a process for eliminating non-contact interference fringes, a film that includes a support having a selected thickness and birefringence is exposed by polarized light characterized by a wavelength and an incident polarization angle. Photographic development processing of the exposed film produces an image substantially without fringes.





# **EUROPEAN SEARCH REPORT**

Application Number EP 95 11 9099

A A	US-A-4 711 838 (GRZESI * column 3, line 54 - GB-A-2 156 089 (CANON) * page 2, line 74 - 1 * figure 2 * US-A-5 069 758 (HERBEI * column 3, line 46 -	column 4, line 51  ne 101 * 	* 1	G03C1/76 G03G5/10 G02B27/28
A	* page 2, line 74 - 1 <sup>3</sup> * figure 2 *  US-A-5 069 758 (HERBEI	ne 101 * 	1	GUZBZ//ZO
		 OT)		
Α	* figure 4 *		1	
	EP-A-0 457 577 (XEROX) * column 3, line 2 - * figure 4 *	ine 39 *	1	
Α	EP-A-0 601 501 (FUJI) * page 5, line 44 - page 5	age 7, line 37 *	1	
				TECHNICAL FIELDS SEARCHED (Int.Cl.6)
				G03C G03G G01C
	The present search report has been	drawn up for all claims		
	Place of search	Date of completion of the search		Examiner
	BERLIN	19 September	1996   Luc	ck, W
X : part Y : part doct A : tech	CATEGORY OF CITED DOCUMENTS icularly relevant if taken alone icularly relevant if combined with another ment of the same category nological background written disclosure	E : earlier pate after the fi D : document L : document e	cited in the applicationited for other reasons	olished on, or