



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 776 274 B9**

(12) **CORRECTED EUROPEAN PATENT SPECIFICATION**

Note: Bibliography reflects the latest situation

(15) Correction information:
Corrected version no 1 (W1 B1)
Corrections, see page(s) 7

(51) Int Cl.:
B42C 3/00 (1968.09) **B42C 9/00** (1968.09)

(48) Corrigendum issued on:
15.03.2006 Bulletin 2006/11

(86) International application number:
PCT/US1995/008751

(45) Date of publication and mention
of the grant of the patent:
02.10.2002 Bulletin 2002/40

(87) International publication number:
WO 1996/005065 (22.02.1996 Gazette 1996/09)

(21) Application number: **95926266.8**

(22) Date of filing: **13.07.1995**

(54) **METHOD AND APPARATUS FOR APPLYING A COATING MATERIAL TO SHEETS**

VERFAHREN UND VORRICHTUNG ZUM AUFBRINGEN EINER BESCHICHTUNG AUF BÖGEN
PROCEDE ET DISPOSITIF DE DEPOT D'UNE COUCHE DE MATIERE SUR DES FEUILLES

(84) Designated Contracting States:
DE FR GB IT

(30) Priority: **17.08.1994 US 291610**

(43) Date of publication of application:
04.06.1997 Bulletin 1997/23

(60) Divisional application:
02076789.3 / 1 234 682
02076790.1 / 1 234 683

(73) Proprietor: **MINNESOTA MINING AND
MANUFACTURING COMPANY**
St. Paul,
Minnesota 55133-3427 (US)

(72) Inventors:
• **VOGEL, Mark, S.**
Saint Paul, MN 55133-3427 (US)

- **TSUJIMOTO, Kim, K.**
Saint Paul, MN 55133-3427 (US)
- **STIFTER, Gregory, F.**
Saint Paul, MN 55133-3427 (US)
- **PIERRE, Bernard, F.**
Saint Paul, MN 55133-3427 (US)
- **LERICHE, Frederic, P., A.**
Saint Paul, MN 55133-3427 (US)

(74) Representative: **Warcoin, Jacques et al**
Cabinet Régimbeau
20, rue de Chazelles
75847 Paris cedex 17 (FR)

(56) References cited:
EP-A- 0 163 127 **EP-A- 0 258 353**
EP-A- 0 684 974

EP 0 776 274 B9

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

Technical Field

[0001] The present invention relates to a method for applying coating material, for example pressure-sensitive adhesive, to a plurality of individual sheets, for example sheets of paper.

Background of the Invention

[0002] It is necessary in certain fields to apply coating material to paper and, conventionally, the coating is applied to a web of paper from a roll rather than to individual sheets. For example, in the case of so-called repositionable notes, it is known to apply a primer material to one side of a web of paper and a low adhesion backsize (or release) material to the other side of the web, and then to apply the repositionable adhesive on top of the primer material. The web is dried between coatings and re-wound, and the coated roll is subsequently cut into sheets which are used to produce the notes.

[0003] A process for the production of repositionable notes, in which coating materials are applied successively to a paper web, is described in WO-A-87/05315.

[0004] In some cases, it is desirable to apply coating materials to cut sheets rather than to a web of paper. For example, in the production of repositionable notes it is desirable to have the option of using a stack of pre-printed sheets as the supply source, instead of a plain paper web, to increase the flexibility of the production process. Difficulties can arise, however, in applying certain coating materials to individual repositionable notes, the application of the repositionable adhesive to individual sheets can present problems and, with a view to overcoming those problems, it is proposed in pending U.S. Patent Application Serial No. 08/196,490 filed February 15, 1994 entitled "Method and Apparatus for Applying a Coating Material to Sheets", that the individual sheets should be overlapped in end to end relation in a web-like (i.e. pseudo-web) configuration and that coating materials, including the repositionable adhesive, should be applied to the overlapped sheets. Following the application of the coating materials, the sheets are stacked and trimmed to form pads of repositionable notes.

[0005] However, it has been found that existing systems for applying a coating material to sheets, including the aforementioned U.S. Patent Application Serial No. 08/196,490, while having their own utility, are not as effective or efficient as desired in coating some materials onto certain sheets materials. Therefore, an improved method and apparatus for applying a coating material onto sheets is desired.

[0006] Document EP-0 684 974 which enters in the prior art under Art 54(3) EPC discloses a method for applying a coating material to sheets different from the method of instant invention.

Summary of the Invention

[0007] The present invention provides a method according to claim 1. The method includes the steps of, in one embodiment, said intermediate carrier is non-reactive to radio frequency radiation and step (e) comprises the phase of exposing the water-based coating material to radio frequency radiation

[0008] In one embodiment, the method further includes, after step (f), the step of (g) continuously detaching the sheet members coated with the coating material from the intermediate carrier.

[0009] In another embodiment of the invention, step (g) includes the step of applying a lower than atmospheric pressure to the sheet members on a side opposite the intermediate carrier to detach the sheet members from the intermediate carrier.

[0010] The present invention may be performed by means of an apparatus for applying a water-based coating material to a plurality of sheet members. In one embodiment, the apparatus includes a conveyor for conveying a plurality of the sheet members in overlapped end to end relation along a path. The apparatus further includes a dispenser for controllably dispensing a quantity of the water-based coating material at a desired rate and an intermediate carrier supported adjacent the dispenser. The intermediate carrier has a transfer surface extending the path of the sheet members, wherein the transfer surface is adapted for contact with the overlapped sheet members along the path. The transfer surface is presented to the dispenser for receiving the coating material at a location spaced from the contact with the overlapped sheet members. The intermediate carrier is advancable to transfer the coating material from the dispenser to the overlapped sheet members. The intermediate carrier is non-reactive to radio frequency radiation. A source of radio frequency radiation is directed towards the water-based coating material on the transfer surface of the intermediate carrier to reduce the water content of the coating material prior to transfer of the coating material from the intermediate carrier to the overlapped sheet members.

[0011] In another embodiment the apparatus includes a conveyor for conveying a plurality of the sheet members in overlapped end to end relation along a path and a die for controllably dispensing a quantity of the water-based coating material at a desired rate. An intermediate carrier is provided having a transfer surface extending to said path of the sheet members, wherein the transfer surface is adapted for contact with the overlapped sheet members along the path. The transfer surface is presented to the dispenser for receiving the coating material at a location spaced from the path of the overlapped sheet members. The intermediate carrier is advancable to transfer the coating material from the dispenser to the overlapped sheet members. The apparatus further includes a dryer directed towards the water-based coating material on the transfer surface of the intermediate carrier

to reduce the water content of the coating material on the intermediate carrier to a desired level.

[0012] In yet another embodiment, the apparatus is provided for use with a system for applying a water-based coating material to a plurality of sheet members. The system includes a conveyor for conveying a plurality of the sheet members in overlapped end to end relation along a path, and a dispenser for controllably dispensing a quantity of the water-based coating material at a desired rate, and further includes an intermediate carrier supported adjacent the dispenser, the intermediate carrier having a transfer surface extending to the path of the sheet members, wherein the transfer surface is adapted for contact with the overlapped sheet members along the path. The transfer surface is presented to the dispenser for receiving the coating material at a location spaced from the path of the overlapped sheet members. The intermediate carrier is advancable to transfer the coating material from the dispenser to the overlapped sheet members. This embodiment includes a detachment roller located adjacent the path of the sheet members and adapted for contact with the sheet members after application of the coating material. The detachment roller is connected to a source of vacuum and adapted to apply the vacuum to the sheet members for detaching the sheet members from the intermediate carrier.

Brief Description of the Drawings

[0013] Embodiments of the invention will be described, by way of example, with reference to the accompanying drawings, wherein like structure is referred to by like numerals in the several views, and in which:

Figure 1 is a schematic side view of apparatus which includes a coating station, in accordance with the method of the invention;

Figure 2 is a schematic top view of the apparatus shown in Figure 1;

Figure 3 is a diagrammatic side view of a part of the apparatus shown in Figure 1;

Figure 4 is an enlarged partial view in the direction of the arrow 4 in Figure 3;

Figure 4A is a side view of the coating roller and smoothing stripe of Figure 4;

Figure 5 is a greatly-enlarged view of part of Figure 4;

Figure 6 is a diagrammatic side view of a modified version of the apparatus shown in Figure 1;

Figure 7 is a more detailed view of part of the apparatus shown in Figure 6;

Figure 8 is an enlarged partial view similar to Figure 4 in the direction of the arrow 8 in Figure 6;

Figure 9 is a cross-section of one of the components of the apparatus shown in FIGs. 1 and 6; and

Figure 10 is a photomicrograph illustrating a repositionable adhesive which has been manually applied to the transfer belt of the apparatus as shown in Figure 1 or Figure 6.

Detailed Description of the Invention

[0014] The system shown schematically in Figures 1 and 2 is particularly adapted for use in the production of repositionable notes from sheets of any suitable substrate material (for example: paper, polymeric film including, but not limited to, polypropylene, polyester and polyethylene), or metallic foil and, in particular, is for use in the application to individual sheets of a primer material, a low adhesion backsize (LAB) material, and, subsequently a repositionable adhesive so that the sheets can be used to form repositionable notes. Zinc-oxide based primers are useful in conjunction with the method and apparatus of the present invention, as well as primers described in U.S. Patent Nos. 4,598,112 and 4,822,670, the contents of which are incorporated herein by reference. A LAB that may be employed in conjunction with the method and apparatus of the present invention is described in co-pending United States patent Application Serial No. 08/040,876, filed March 31, 1994 and commonly assigned to the Assignee of the present invention, the contents of which are incorporated herein by reference. In the following description, it will be assumed that the sheets (which may be pre-printed) are of paper.

[0015] The system shown in Figure 1 has a paper path entry 1 which receives a succession of paper sheet members (not shown) from any suitable source, for example a stack (not shown). The paper may be any suitable paper, such as the paper utilized to construct the Post-it® brand repositionable notes available from Minnesota Mining and Manufacturing Company ("3M") of St. Paul, Minnesota. The paper sheets may be provided in any suitable size (including, but not limited to standard sizes such as A2, A4 and 8.5 inches by 11 inches), as well as thickness, but the paper is preferably between 45 grams per square meter (gsm) to 90 gsm, and is most preferably at about 70 gsm such sheets define a leading end edge, a trailing end edge, and longitudinal side edges, as well as opposing major surfaces.

[0016] From the paper path entry 1, the sheets travel in the direction indicated by the directional arrow 2 through a double coating station 3, a sheet overlapping station 4, a dryer 5, a sheet guiding section 6.

[0017] The double coating station 3, together with the overlapping station 4, is the subject of a co-pending patent application filed of even date herewith, entitled "Method and Apparatus for Applying a Coating Material to Sheets", and commonly assigned to the Assignee of the present invention, and the contents of that co-pending application are incorporated herein by reference. As described in the above indicated co-pending patent application, a plurality of individual sheets S sequentially passing through the double coating station 3 are coated on one major surface (the upper major surface as seen in Figure 1) with a primer material and on the opposing major surface with an LAB material and are then overlapped, in the overlapping station 4, in a weblike configuration in end to end relation in which an end portion of each sheet

S overlies an end portion of an adjacent sheet S. That pseudo-web of overlapped sheets then moves into the dryer 5 in which water is removed from the primer and LAB coating on the sheets. The dried sheets S are then side registered in the guiding section 6 (or alternative guiding section 6' shown in Figures 3 and 6) so that they are aligned with each other before entry into the adhesive coating station 7 of the present invention.

[0018] Alternatively, the sheets may be independently coated with a suitable LAB and primer (or other desired coating) by any suitable process, stored and then subsequently provided to the apparatus of the present invention in overlapped end to end relation.

[0019] Adhesive coating station 7 receives the overlapped sheets S at input 8a along a path 8b to a paper path exit 8c. Preferably, the sheets are overlapped so that the trailing edge of each sheet overlies the leading edge of the next sequential sheet. The control and synchronization of the drives of the various stations may be performed by a central electronic control unit (not shown), for example a Siemens PLC 135. The paper path 8b is provided by a conveyor (as shown in Figure 1) or the like that receives the pseudo-web of sheets and conveys the sheets from input 8a to exit 8c at a desired rate.

[0020] The coating station 7 applied a coating material, which is preferably a pressure-sensitive adhesive, to the overlapped sheets on their respective exposed portion of the major surfaces which have already been coated with primer. The adhesive may be a pressure-sensitive adhesive, and preferably is a repositionable microsphere pressure-sensitive adhesive, for example as described in U.S. Patent No. 4,495,318 to Howard, or U.S. Patent No. 3,691,140 to Silver, and may be a water-based adhesive. For instance, the adhesive used in conjunction with the present invention may be a microsphere pressure sensitive adhesive (such as is used in the manufacture of Post-it® brand repositionable notes from the Minnesota Mining and Manufacturing Company ("3M") of St. Paul, Minnesota). Such adhesive compositions are described in European Patent No. 439,941; U.S. Patent Nos. 5,045,569; 4,166,152; 3,691,140; 3,857,731; and Re 24,906, the contents of all of which are incorporated herein by reference. Adhesives for use with the present invention also include film-forming materials known in the art, including those containing organic solvents.

[0021] The adhesive is applied by contacting the sheets with an adhesive-coated intermediate carrier 20. In the illustrated embodiment of the invention, the intermediate carrier takes the form of a transfer belt 20 that is an endless belt entrained around rollers 21, at least one of which is driven so that the belt advances in the direction of the arrow 2. Alternatively, other arrangements may be employed, including, for example, a cylindrical drum in contact with both the dispenser and the path of the sheet member. Although the intermediate carrier will be hereinafter referred to as a transfer belt, it is to be understood that the present invention is not limited thereto.

[0022] As the transfer belt 20 moves (preferably at approximately the same rate of advance of the conveyor 8b conveying the sheets S), it passes a coating mechanism 23, a dryer 24 and a transfer station 25, each of which will be described in greater detail below. Preferably, the adhesive is then dried at least partially (i.e. the moisture content is reduced to a desired level), in the dryer 24 before being transferred to the overlapped sheets at the transfer station 25. For instance, the moisture content of the water-based adhesive may be approximately 50%-80% prior to drying and 0%-50% after drying. Preferably, substantially all of the moisture is removed during the drying process. It is one of the advantages of the present invention, as compared to the above identified co-pending United States patent application Serial No. 08/196,460, that the adhesive may be substantially completely dried and still be effectively transferred from the transfer belt to the paper sheet, as is described herein elsewhere in greater detail.

[0023] The coating mechanism 23 applies at least one longitudinal stripe of pressure-sensitive adhesive to the transfer surface 20b of the transfer belt. One embodiment of the coating mechanism 23 is shown in greater detail in Figure 3. The adhesive is coated onto the belt 20 by a reverse rotating gravure roller 28 which extends across the width of the belt and contacts the belt at the coating station 7. At least one gravure ring 29 (Figure 4) of cells or cavities is formed in the surface of the roller, each ring extending around the roller at the desired location of an adhesive stripe on the belt. In Figure 4, three gravure rings 29 are shown, providing three longitudinal adhesive stripes 36 on the belt 20, but that is not essential. An enlarged view of the cells 30 in one of the rings 29 is shown in Figure 5, from which it can be seen that each cell generally has the form of an inverted truncated pyramid. Typically, there would be about twenty-four pattern lines 30A of cells per centimeter length of a ring 29. The particular gravure pattern shown in Figure 5 is not essential and can be changed, if found advantageous, to alter the distribution of adhesive within the stripes 36.

[0024] The adhesive which is to be applied to the belt 20 by the roller 28 is supplied by a pump 31 from a tank 32 to a trough 33 at the coating mechanism 23. A metering roller 34 dips into the adhesive in the trough and, as it rotates, the metering roller picks up adhesive which it then transfers to the reverse rotating gravure roller 28 and, in particular, to the cells in the ring(s) 29. One or more doctor blades (such as at 35 in Figure 3) engage the roller 28 to remove any excess adhesive and ensure that all the adhesive on the roller is contained only within the cells 30, thereby ensuring that the adhesive will be transferred in the stripes 36 when the roller contacts the belt 20. If the roller 28 rotates in the same direction as the movement of the belt 20, the adhesive coating process is a direct gravure coating process. If the roller 28 rotates in an opposite rotational direction as the movement of the belt 20, the coating process is a reverse gravure coating process. Although either arrangement may

be employed as part of the present invention, unless otherwise specified, the process shown and described herein shall be a reverse gravure process. Further, it is within the spirit and scope of the present invention to eliminate the metering roller 34 and place the roller 28 in direct contact with the adhesive in the trough. In all other respects, the method and apparatus of the present invention would operate as hereinelsewhere described.

[0025] In one embodiment of the present invention where reverse gravure coating is employed, it has been found advantageous to smooth the layer of adhesive applied to the gravure rings 29 prior to transfer of the adhesive to the transfer belt 20. In the illustrated embodiment of the invention (as shown in Figures 4 and 4A with respect to one of the gravure rings) a smoothing strip 29a is positioned for sliding contact with the adhesive on the gravure ring as the gravure ring rotates to apply the adhesive. It has been found that in some applications, the distribution of the adhesive microspheres is enhanced. That is, when the smoothed adhesive is coated on the paper sheet S, the exposed surface of the adhesive is more uniform and exhibits more controllable and uniform adhesive strengths. Preferably, the strip 29a is a flexible, polymeric stripe, and most specifically, the strip is a strip of polyester approximately 0.0011 inches in thickness.

[0026] As an alternative, depending on the intended use of the sheets to which the adhesive is applied, the adhesive can be transfer coated across the whole width of the belt rather than in discrete stripes. Typically, the gravure roller 28 rotates at approximately the same speed as the belt 20 and in the same direction (i.e. clockwise as seen in Figure 3) so that the coating mechanism functions as a reverse roll coating system, but that is not essential.

[0027] One embodiment of the transfer belt 20 is shown in cross-section in Figure 9. In the illustrated embodiment, the transfer belt includes a base layer 20a that is preferably a commercially available fiberglass fabric belt, such as is available for J.P. Steven, North Carolina, and is preferably 0.004 inches in thickness. The belt base layer 20a is coated on front and back major surfaces 20b, 20c with 0.003 inch thick layers 20d, 20e (for a total thickness for the belt 20 of approximately 0.010 inches) of a dispersion of a silicone rubber solution, G.E. SE-100 available from Silicone Products Division of General Electric Co. of Waterford, New York at a 6% solids with 78% benzoyl peroxide in water as a catalyst. Both coatings 20d, 20e are knife coated and oven dried at 360°F, 60 yards/hour. The silicone layers enhance release of the adhesive from the belt to the sheets S. The outermost surfaces 20g, 20h of the silicone layers 20d, 20e form the transfer surfaces for receipt of the adhesive.

[0028] Although a smooth transfer surface may be employed, the transfer surfaces are preferably textured or nonvoluted. Most preferably, the textured surface takes the form of a pattern of indentations that impose a complementary pattern in the adhesive stripes transferred from the belt to the sheets of papers at the transfer nip

25A.

[0029] A preferred form of the pattern of indentations is shown enlarged in Figure 10 and generally comprises an array of indentations 20j. The indentations 20j overly corresponding indentations 20g in the surfaces 20b, 20c of the base layer 20a. The indentations 20g in the base layer may be formed during the process of weaving the fiberglass layer. Alternatively, the pattern of indentations 20g may be embossed or otherwise imposed on the surface of the backing layer.

[0030] When the pressure-sensitive adhesive is a microsphere adhesive, the distribution of the microspheres in the pattern shown in Figure 10 is found to be very even, resulting in improved adhesion. Each indentation 20j receives one or more microspheres from the gravure roller. Preferably, the indentations 20j have a width of from 40 microns to 200 microns, and most preferably, a width of approximately 100 microns, and a depth of from 50 microns to 100 microns. Preferably, the indentations 20j described above are spaced approximately 10-30 microns in a rectangular array. The adhesive tends to "wet out" on the surfaces 20h, 20i due to the silicone layers 20d, 20e and retain the microspheres in the indentations 20g. Consequently, the adhesive is transferred to the sheets while maintaining the pattern shown in Figure 10.

[0031] It is also preferable that the layers 20d, 20e be of the same thickness, and that both major surfaces 20h, 20i include the indentations 20j, so that, if necessary, the transfer belt 20 may be reversed to present surface 20c for increased usage of the belt. Of course, a transfer belt 20 may employed that includes a silicone layer and indentations on only one major surface, if desired, such as for cost reasons.

[0032] When a gravure roller is used to apply the adhesive stripes to the belt as described above with reference to Figures 3 and 4, the pattern in the adhesive stripes is further influenced by the form of the gravure pattern and the latter should be chosen with a view to enhancing the even distribution of the microspheres.

[0033] Although the above description refers to the sheets as being paper, they could (as already mentioned) be formed of other materials, for example: polymeric films or metallic foils. When the sheets are paper, they are preferably fed through the apparatus with what is known in the art as the "machine direction" of the paper aligned with the machine process direction (i.e. generally parallel to directional arrow 2 along paper path 8b). In that way, any tendency for the sheets to curl or wrinkle can be further attenuated. Papers of different weights and textures can be used if desired. Typically, sheets of size A2 and weight 70 gsm would be used, but the apparatus is readily adaptable to handle sheets of size A4 and weights within the range 70 gsm to 90 gsm and could also handle sheet S weights as low as 45 gsm.

[0034] Paper is commonly formed by accumulating paper fibers on a wire mesh or screen and compressing the accumulated fibers between the screen and a "felt" or cloth layer opposite the screen layer. This produces pa-

per having a "wire" side and a "felt" side. It has also been found advantageous to convey the sheets S through the apparatus of the present invention with the "wire" side presented for coating of the release material and the "felt" side presented for coating of the primer and ultimately for coating of the adhesive.

[0035] The belt 20 with the adhesive stripes 36 then passes through the dryer 24 in which the adhesive stripes are dried at least partially (i.e. ranging from 0%-50%). This is done to improve the adherence of the adhesive to the sheets. In one embodiment of the invention, the dryer 24 is preferably a radio-frequency dryer, for example a particularly adapted version of the Model No. SPW 12-73 manufactured by Proctor Strayfield Ltd. of Berkshire, England operated, typically, at about 27 Mhz, or alternatively, at about 30 Mhz. The dryer is about 2.5 m long in the direction of travel of the belt and has an exhaust 50 through which the interior of the dryer is vented with the aid of a fan 51. The dryer is provided with a control unit (not shown) which adjusts the power of the dryer in accordance with the line speed of the coating apparatus. That control unit may, for example, be a Siemens PLC 55-95U interconnected with the central electronic control unit of the whole apparatus

[0036] A radio-frequency dryer requires that the material of the transfer belt 20 be non-reactive (i.e. transparent or otherwise not affected by the radio frequency radiation to a degree that adversely affects the operation of the method and apparatus of the present invention) to radio frequency radiation, such as the embodiment of the transfer belt described hereinabove and shown in Figures 9 and 10. This arrangement offers the advantage that the adhesive is dried without the transfer belt being significantly heated, thereby eliminating any heat transfer from the belt to the coating mechanism 23 and then to the adhesive which could cause the adhesive to coagulate before it has been applied to the belt 20. A radio-frequency dryer also offers the advantages of comparative simplicity and lower energy consumption. Further, the transfer belt 20 requires no prolonged pre-heating to a particular operating temperature and the adhesive is released readily from the belt for transfer to the sheets at the coating station.

[0037] However, it will be understood that other forms of transfer belt can be used that are incompatible with a radio frequency dryer (i.e. are not transparent or inert to radio frequency radiation). For example, the transfer belt may comprise a metal substrate with a coating of silicone rubber on each side. Other types of dryers that may be employed in the present invention, for example, include an infra-red heater, or a hot air dryer. However, if the dryer causes the belt 20 and then the coating mechanism 23 to become heated it may be necessary to cool the adhesive and the transfer belt to reduce the risk of the adhesive coagulating.

[0038] At the transfer station 25 (also shown in Figure 3), the adhesive-coated belt 20 passes through a transfer nip 25A comprising a transfer roller 37 and a counter-

pressure or nip roller 38. The overlapped sheets from the guiding section 6 (with an alternative guiding section 6' shown in Figure 3 and also in Figure 6) of the apparatus are also directed through the transfer nip 25A and are supported by the counterpressure roller 38 against the transfer roller 37 and consequently against the belt 20 so that adhesive is transferred from the belt to the sheets. Immediately downstream of the transfer nip 25A, the sheets are detached from the belt 20, such as by a vacuum roller 39 and are carried away from the transfer nip on a vacuum conveyor 40 to the paper path exit 8c. For the purposes of this invention, the term "vacuum" refers to any less than atmospheric pressure that, when applied to the sheet members on a major surface opposite the transfer belt, is sufficient to detach the sheets from the transfer belt. Of course, other means, including mechanical grippers, may be employed to detach the sheets from the transfer belt, if desired. Once detached, the sheets may then be stacked and trimmed to form pads of repositionable notes.

[0039] The detachment system may be of any suitable type. For example, the vacuum conveyor 40 may be a metallic belt which passes around, and forms a single complete assembly with the vacuum roller 39 as in the delaminating and transfer system available from Honeycomb Systems, Valmet S.a.r.l. of Mulhouse, France. Alternatively, the vacuum roller 39 which removes sheets from the belt 20 may be completely separate from the vacuum conveyor 40, as illustrated in Figures 6 and 7 described below. As shown in the drawings, the vacuum conveyor 40 extends at an angle away from the transfer belt 20. When the conveyor is used with a vacuum roller 39, as shown in Figures 3, 6, and 7, that angle may be 3 or 4 degrees, but if the vacuum roller 39 is omitted, a smaller angle (about 2 degrees) may be employed.

[0040] A modified version 7' of the apparatus shown in Figure 1 is shown in Figure 6. Corresponding parts of the apparatus carry the same reference numerals as in Figure 1. The double coating station 3 as shown in Figure 6 differs slightly from the shown in Figure 1 in that the lower station 12 is located slightly downstream of the upper station 11 so that the primer and LAB materials will not be applied absolutely simultaneously. Downstream of the double coating station, as in Figure 1, the sheets S pass through an overlapping station 4 (including an air knife 41 for changing the direction of the overlap); a dryer 5 and a guiding station 6 before reaching the adhesive coating station 7'.

[0041] The adhesive coating station 7' shown in Figure 6, and in greater detail in Figure 7, is generally similar to that shown in Figure 1, except that the coating mechanism 23 uses at least one coating die 42 to apply the pressure-sensitive adhesive to the belt 20 instead of the gravure roller 28. Each coating die has a die slot (not shown) directed towards the belt, through which a stripe 44 (Figure 8) of adhesive is applied directly to the belt. The dies are spaced across the belt at the desired locations of the adhesive stripes. Each die 42 has a respective

supply line 45, including a respective pump 46 of any suitable type and a filter 47 through which adhesive is supplied to the die from a reservoir 48. The rate at which adhesive is coated onto the belt 20 is readily adjusted by changing the speed of the pumps 46 which are driven under the control of the central electronic control unit of the apparatus in dependence on the line speed of the apparatus.

[0042] Die coating of the adhesive stripes, as illustrated in Figures 6 and 7, enables the location of the adhesive stripes on the belt 20, and hence on the paper sheets to be more easily adjusted and increases the flexibility of the coating process. However, alternatively, a single die may be provided with a slot that is divided to apply the adhesive at the desired locations across the width of the transfer roll.

[0043] As already mentioned, the vacuum roller 39 which removes sheets from the belt 20 following the transfer of the adhesive stripes 44 at the transfer nip 25A is separate from the vacuum conveyor 40 in the apparatus shown in Figure 6. It could, however, form a complete assembly with the vacuum conveyor as explained above with reference to Figure 1. Further, it is within the spirit and scope of the present invention, that the vacuum roller 39, with or without the vacuum conveyor 40, may be independently employed with any apparatus for coating a coating material onto a pseudo web of overlapped sheets, including, for instance, the aforementioned system disclosed in co-pending United States Patent Application Serial No. 08/196,490.

[0044] The present invention has now been described with respect to several embodiments thereof. It will be apparent to those skilled in the art that many changes may be made in the embodiments described without departing from the scope of the invention. Thus, the scope of the present invention should not be limited to the processes described herein, but rather by the language of the claim.

Claims

1. A method for applying water-based coating material to a plurality of paper sheet members (S), each sheet member having a machine direction, opposing ends and sides and major surfaces, comprising the steps of:

- (a) arranging the plurality of sheet members (S) in sequential end to end overlapping relation ;
- (b) conveying the overlapped sheet members along a path wherein the machine direction of the paper sheet members is aligned with said path so as to attenuate curling and wrinkling of the sheet members;
- (c) providing an intermediate carrier (20) having a transfer surface in contact with the overlapped sheet members along the path ;

(d) applying the water-based coating material to the transfer surface of the intermediate carrier at a location spaced from the path of the sheet members;

(e) reducing the water content of the coating material to a desired level ; and

(f) advancing the intermediate carrier to progressively apply the reduced water content coating material to one of the major surfaces of each of the overlapped sheet members through contact between the intermediate carrier and the sheet members.

Patentansprüche

1. Verfahren zum Auftragen von Beschichtungsmaterial auf Wasserbasis auf mehrere Papierblatt-Teile (S), von denen jedes eine Maschinenrichtung, einander gegenüberliegende Enden und Seiten und Hauptflächen aufweist, mit den folgenden Schritten:

(a) Anordnen der mehreren Blatt-Teile (S) in sequentieller endweiser Überlappungsrelation;

(b) Fördern der einander überlappenden Blatt-Teile entlang eines Wegs, wobei die Maschinenrichtung der Papierblatt-Teile derart mit dem Weg ausgerichtet ist, dass ein Verwerfen und Knittern der Blatt-Teile unterdrückt wird;

(c) Bereitstellen eines Zwischenträgers (20) mit einer Transferfläche, die sich entlang dem Weg in Kontakt mit den einander überlappenden Blatt-Teilen befindet;

(d) Auftragen des Beschichtungsmaterials auf Wasserbasis auf die Transferfläche des Zwischenträgers an einer im Abstand von dem Weg der Blatt-Teile befindlichen Stelle;

(e) Reduzieren des Wassergehalts des Beschichtungsmaterials auf ein gewünschtes Niveau; und

(f) Vorbewegen des Zwischenträgers zum progressiven Auftragen des den reduzierten Wassergehalt aufweisenden Beschichtungsmaterials auf eine der Hauptflächen jeder der einander überlappenden Blatt-Teile zwischen den Zwischenträger und die Blatt-Teile hindurch.

Revendications

1. Procédé de dépôt d'une matière de revêtement à base d'eau sur une pluralité d'éléments de feuille de papier (S), chaque élément de feuille ayant une direction machine, des extrémités et des bords opposés et des surfaces principales, comprenant les étapes consistant à :

(a) disposer la pluralité d'éléments de feuille (S)

en relation bout à bout avec chevauchement d'extrémités ;

(b) acheminer les éléments de feuille en chevauchement le long d'un axe, où la direction machine des éléments de feuille de papier est alignée avec ledit axe, de façon à atténuer le gon- 5
dolage et le plissage des éléments de feuille ;

(c) fournir un véhicule intermédiaire (20) ayant une surface de transfert en contact avec les éléments de feuille en chevauchement le long de 10
l'axe ;

(d) déposer la matière de revêtement à base d'eau sur la surface de transfert du véhicule intermédiaire à un endroit éloigné de l'axe des éléments de feuille ; 15

(e) réduire la teneur en eau de la matière de revêtement au niveau désiré ; et

(f) avancer le véhicule intermédiaire pour déposer progressivement la matière de revêtement à teneur réduite en eau sur l'une des surfaces 20
principales de chaque élément de feuille en chevauchement entre le véhicule intermédiaire et les éléments de feuille.

25

30

35

40

45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 4A




FIG. 5




FIG. 6








FIG. 10