

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 924 065 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
23.06.1999 Bulletin 1999/25

(51) Int Cl.⁶: **B41C 1/10**

(21) Application number: **98204092.5**

(22) Date of filing: **04.12.1998**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

- **Vermeersch, Joan**
2640 Mortsel (BE)
- **Hendrikx, Peter**
2640 Mortsel (BE)
- **Van Aert, Huub**
2640 Mortsel (BE)

(30) Priority: **19.12.1997 EP 97204045**

(71) Applicant: **AGFA-GEVAERT N.V.**
2640 Mortsel (BE)

(74) Representative: **Ramon, Charles Lucien**
Agfa-Gevaert N.V.
Dienst Intellectuele Eigendom 3800
Septestraat 27
2640 Mortsel (BE)

(72) Inventors:

- **Van Damme, Marc**
2640 Mortsel (BE)

(54) **A heat sensitive non-ablatable wasteless imaging element for providing a lithographic printing plate**

(57) According to the present invention there is provided a heat-sensitive non-ablatable wasteless imaging element for providing a lithographic printing plate, hav-

ing on a support as top layer an image forming layer comprising a heat-switchable binder, characterized in that said image forming layer becomes more hydrophobic under the influence of heat

EP 0 924 065 A1

Description

FIELD OF THE INVENTION

5 **[0001]** The present invention relates to a heat sensitive non-ablatable wasteless imaging element.

[0002] More specifically the invention is related to a heat sensitive non-ablatable wasteless imaging element for preparing a lithographic printing plate which requires no dissolution processing.

BACKGROUND OF THE INVENTION

10 **[0003]** Lithography is the process of printing from specially prepared surfaces, some areas of which are capable of accepting lithographic ink, whereas other areas, when moistened with water, will not accept the ink. The areas which accept ink define the printing image areas and the ink-rejecting areas define the background areas.

15 **[0004]** In the art of photolithography, a photographic material is made imagewise receptive to oily or greasy inks in the photo-exposed (negative-working) or in the non-exposed areas (positive-working) on a hydrophilic background.

[0005] In the production of common lithographic printing plates, also called surface litho plates or planographic printing plates, a support that has affinity to water or obtains such affinity by chemical treatment is coated with a thin layer of a photosensitive composition. Coatings for that purpose include light-sensitive polymer layers containing diazo compounds, dichromate-sensitized hydrophilic colloids and a large variety of synthetic photopolymers. Particularly diazo-sensitized systems are widely used.

20 **[0006]** Upon imagewise exposure of the light-sensitive layer the exposed image areas become insoluble and the unexposed areas remain soluble. The plate is then developed with a suitable liquid to remove the diazonium salt or diazo resin in the unexposed areas.

25 **[0007]** Alternatively, printing plates are known that include a photosensitive coating that upon image-wise exposure is rendered soluble at the exposed areas. Subsequent development then removes the exposed areas. A typical example of such photosensitive coating is a quinone-diazide based coating.

30 **[0008]** Typically, the above described photographic materials from which the printing plates are made are exposed in contact through a photographic film that contains the image that is to be reproduced in a lithographic printing process. Such method of working is cumbersome and labor intensive. However, on the other hand, the printing plates thus obtained are of superior lithographic quality.

35 **[0009]** Attempts have thus been made to eliminate the need for a photographic film in the above process and in particular to obtain a printing plate directly from computer data representing the image to be reproduced. However the above mentioned photosensitive coatings are not sensitive enough to be directly exposed to a laser. Therefore it has been proposed to coat a silver halide layer on top of the photosensitive coating. The silver halide can then directly be exposed by means of a laser under the control of a computer. Subsequently, the silver halide layer is developed leaving a silver image on top of the photosensitive coating. That silver image then serves as a mask in an overall exposure of the photosensitive coating. After the overall exposure the silver image is removed and the photosensitive coating is developed. Such method is disclosed in for example **JP-A- 60- 61 752** but has the disadvantage that a complex development and associated developing liquids are needed.

40 **[0010]** **GB- 1 492 070** discloses a method wherein a metal layer or a layer containing carbon black is provided on a photosensitive coating. This metal layer is then ablated by means of a laser so that an image mask on the photosensitive layer is obtained. The photosensitive layer is then overall exposed by UV-light through the image mask. After removal of the image mask, the photosensitive layer is developed to obtain a printing plate. This method however still has the disadvantage that the image mask has to be removed prior to development of the photosensitive layer by a cumbersome processing.

45 **[0011]** Furthermore methods are known for making printing plates involving the use of imaging elements that are heat-sensitive rather than photosensitive. A particular disadvantage of photosensitive imaging elements such as described above for making a printing plate is that they have to be shielded from the light. Furthermore they have a problem of sensitivity in view of the storage stability and they show a lower dot crispness. The trend towards heat mode printing plate precursors is clearly seen on the market.

50 **[0012]** **EP-A- 444 786**, **JP- 63-208036**, and **JP- 63-274592** disclose photopolymer resists that are sensitized to the near IR. So far, none has proved commercially viable and all require wet development to wash off the unexposed regions. **EP-A- 514 145** describes a laser addressed plate in which heat generated by the laser exposure causes particles in the plate coating to melt and coalesce and hence change their solubility characteristics. Once again, wet development is required.

55 **[0013]** A somewhat different approach is disclosed in **US-P- 3 787 210**, **US-P- 3 962 513**, **EP-A- 001 068** and **JP- 04-140191**. Heat generated by laser exposure of a donor sheet is used to physically transfer a resinous material from the donor to a receptor held in intimate contact with the donor. Provided the receptor surface has suitable hydrophilic

properties, it can then be used as a printing plate. This method has the advantage of not requiring wet processing, but in order to achieve realistic write-times, a high power YAG (or similar) laser is required, which has restricted the usefulness of the method

[0014] On the other hand polymer coatings which undergo a change in surface properties in response to light exposure are known in the art. **WO- 92/09934** discloses imaging elements including coatings that become hydrophilic as a result of irradiation, and **WO- 92/02855** describes coatings that become tacky as a result of irradiation. In both cases, the coatings comprise an acid-sensitive polymer and a photochemical source of strong acid, and in both cases the preferred acid-sensitive polymer is derived from a cyclic acetal ester of acrylic or methacrylic acid, such as tetrahydropyranyl (meth)acrylate.

[0015] **WO- 92/02855** discloses that the acid-sensitive polymer is blended with a low-Tg polymer to produce a coating that is initially non-tacky, but on irradiation undergoes phase separation as a result of chemical conversion of the acid-sensitive polymer, and becomes tacky. Although the possibility of laser exposure is mentioned, no details are given, and there is no disclosure of IR-sensitivity, only UV/visible. However the same materials were the subject of a paper entitled "Advances in Phototackification" presented as Paper 1912-36 at the 1993 IS & T/SPIE Conference, Symposium on Electronic Science and Technology, in which it was further disclosed that the photoacid generator could be replaced by an IR dye (specifically a squarilium dye with thiopyrylium end groups) and exposure effected with a diode laser device. The dye in question is not known to have acid-generating properties. This technology is the subject of **US-P- 5 286 604**.

WO- 92/09934 discloses that an acid-sensitive polymer is optionally blended with one or more photoacid generators. Subsequent to imagewise exposure to UV/visible radiation, the exposed areas are preferentially wettable by water, and the coatings may function as lithographic printing plates requiring no wet processing. There is no disclosure of laser address.

EP-A- 652 483 discloses a lithographic printing plate requiring no dissolution processing which comprises a substrate bearing a heat-sensitive coating, which coating becomes relatively more hydrophilic under the action of heat. Said system yields a positive working printing plate. An analogous system, however yielding a negative working printing plate is not known.

DD- 217 914 discloses the preparation of a lithographic plate by irradiation with a laser of a non-light sensitive hydrophilic material, coated on an anodic aluminium support, which can comprise dyes or other additions, wherein the aluminium oxide layer is coloured with a dye, which absorbs at the wavelength of the laser.

DD- 213 530 discloses a method for the preparation of printing plates for flexographic and lithographic printing by irradiation with a laser of layers comprising spectral sensitizers wherein spectral sensitizers are used whose spectrum changes by irradiation.

US-P- 4 034 183 discloses a process for the production of a planographic printing form in which a carrier coated with a hydrophilic layer composed of a non-light-sensitive compound is imagewise exposed, the improvement comprising imagewise exposing the layer to laser radiation of an intensity and for a period such that the exposed areas are rendered hydrophobic and oleophilic, whereby the printing form obtained may be used for printing in a planographic printing machine without further treatment.

GB-A- 2 203 438 discloses a photosensitive and heat-sensitive polymer having conjugated polyenes and sulfonic acid groups and an absorbance ratio of specified bands of at least 0.6.

US-P- 4 081 572 discloses a method for preparing a printing master comprising (a) providing a self-supporting master substrate, (b) providing a specific hydrophilic polymer, (c) coating said substrate with said polymer, and (d) selectively thermally converting said polymer to a hydrophobic condition in image configuration.

JP- 60 132 760 discloses the surface of a plate material comprising an oleophilic polymer which is made hydrophilic to form a non-image part which is, in turn, irradiated with a laser to selectively remove a hydrophilic functional group to obtain the desired printing plate.

OBJECTS OF THE INVENTION

[0016] It is an object of the invention to provide a non-ablative imaging element for preparing a lithographic printing plate requiring no dissolution processing which is negative working.

[0017] It is also an object of the invention to provide a non-ablative imaging element for preparing a lithographic printing plate requiring no dissolution processing which shows a good ink-uptake in the exposed areas and no scumming in the non-exposed areas.

SUMMARY OF THE INVENTION

[0018] According to the present invention there is provided a heat-sensitive non-ablatable wasteless imaging element for providing a lithographic printing plate, having on a support as top layer an image forming layer comprising a heat-

switchable binder, characterized in that said image forming layer becomes more hydrophobic under the influence of heat

DETAILED DESCRIPTION OF THE INVENTION

[0019] The image forming layer which becomes more hydrophobic under the influence of heat comprises a heat-switchable binder and optionally a compound capable of transferring light into heat. A heat-switchable binder is a polymer or copolymer which under the influence of heat undergoes a polarity transfer from hydrophilic to hydrophobic or vice versa. According to the present invention a switchable binder is used which is hydrophilic before heating and becomes hydrophobic by heating. This surface polarity difference is sufficient to prepare a classical offset printing plate. Preferably the switchable binders according to the invention are polymers or copolymers which contain pendant polar functions. These polar functions may be carboxylic acids, sulphonic acids, phosphonic acids and phenols or their salts. As counter ion can be used sodium, potassium, ammonium, or tetraalkylammonium ion. Also traces of alkali can be used such as traces of triethylamine and pyridine. These hydrophylic functions react under the influence of heat with other functional groups forming a hydrophobic structure.

[0020] A more preferred switchable binder according to the invention is a binder containing maleic acid, which binder is hydrophilic and which yields under the influence of heat a binder containing maleic anhydride which binder is hydrophobic. Also more preferred switchable binders according to the invention are binders containing fumaric acid, itaconic acid, 3-or 4-vinylphthalic acid, cis-1,2,3,6-tetrahydrophthalic acid or cis-5-norbornene-endo-2,3-dicarboxylic acid. Said acids can be mixed in one copolymer. Not only the diacids but also the monoalkyl esters and their salts are more preferred. Examples of such half-esters are monobutyl maleate copolymers, monoisopropyl maleate copolymers, maleic acid 2-butoxy ethyl ester copolymer, maleic acid isobutylester copolymers and maleic acid isooctyl ester copolymers. These halfesters can also be used in combination with the corresponding dicarboxylic substance in one copolymer or they can be mixed with each other or with another dicarboxylic acid or salt into one copolymer.

[0021] Not only copolymers obtained by copolymerization of e.g. maleic acid but also polymers derivatives obtained by grafting e.g. maleic acid on unsaturated polyolefines are very suitable switchable polymers.

[0022] Preferably a switchable binder according to the invention is a copolymer preferably containing an acrylate, a methacrylate, a vinyl halide, a vinyl ester, a vinyl ether such as n-butyl-, isobutyl-, and 2-chloroethyl vinyl ether and olefines such as propylene, isobutylene and 1-octadecene. More preferably is a compound selected from the group consisting of methyl vinyl ether copolymer, ethene copolymer and styrene copolymer. Most preferably said binder is a copolymer containing maleic acid and vinyl methyl ether.

[0023] The ratio of the dicarboxylic monomer to comonomer can be 100:0 to 20:80, or sufficient for its structure or state (i.e. anhydride or otherwise) to affect the overall solubility of the top layer. Typically the ratio is near 50:50 due to a tendency toward alternating copolymerization. The molecular weight is generally between 5,000 up to 70,000 weight average molecular weight, preferably between 10,000 and 40,000 g/mol.

[0024] The image forming layer may comprise more than one switchable polymer although that is not preferred. The image forming layer may also comprise a further binder to enhance the hydrophilic or hydrophobic properties of said layer.

[0025] As hydrophilic binder there may be used hydrophilic (co)polymers such as for example, homopolymers and copolymers of acrylamide, methylol acrylamide, methylol methacrylamide, acrylic acid, methacrylic acid, hydroxyethyl acrylate, hydroxyethyl methacrylate or maleic anhydride/vinylmethylether copolymers. The hydrophilicity of the (co) polymer or (co)polymer mixture used is preferably the same as or higher than the hydrophilicity of polyvinyl acetate hydrolyzed to at least an extent of 60 percent by weight, preferably 80 percent by weight. A preferred hydrophilic binder is polyvinylalcohol.

[0026] As hydrophobic binder there may be used a water insoluble polymer such as a cellulose ester, a copolymer of vinylidene chloride and acrylonitrile, poly(meth)acrylates and polyvinylchloride. Preferred hydrophobic binders are hydrophobic binders as used in conventional positive or negative working PS-plates e.g. novolac, polyvinyl phenols, carboxy substituted polymers etc. Typical examples of these polymers are described in **DE-A- 4 007 428**, **DE-A- 4 027 301** and **DE-A- 4 445 820**.

[0027] The image forming layer or a layer just underlying said layer preferably includes a compound capable of converting light into heat. Suitable compounds capable of converting light into heat are preferably infrared absorbing components although the wavelength of absorption is not of particular importance as long as the absorption of the compound used is in the wavelength range of the light source used for image-wise exposure. Particularly useful compounds are for example dyes and in particular infrared absorbing dyes and pigments and in particular infrared absorbing pigments. Examples of infrared absorbing dyes are disclosed in **EP-A- 97 203 131.4**. Examples of infrared absorbing pigments are carbon black, metal carbides, borides, nitrides, carbonitrides, bronze-structured oxides and oxides structurally related to the bronze family but lacking the A component e.g. $WO_{2.9}$. It is also possible to use conductive polymer dispersion such as polypyrrole or polyaniline-based conductive polymer dispersions. Said compound capable of converting light into heat is preferably present in the top layer but can also be included in an underlying layer.

[0028] It is clear that said compound capable of converting light into heat is necessarily present in the imaging element according to the invention when said imaging element is imaged by exposure with light.

[0029] Said compound capable of converting light into heat is present in the imaging element preferably in an amount between 1 and 25 % by weight of the total weight of the image forming layer, more preferably in an amount between 2 and 20 % by weight of the total weight of the image forming layer. The compound capable of converting light into heat is most preferably present in the imaging element in an amount to provide an optical density at a wavelength between 800 nm and 1100nm of at least 0.35.

[0030] Furthermore this IR-sensitive layer is preferably a visible light- and UV-light desensitised layer. This preferably visible light- or UV-light desensitised layer does not comprise photosensitive ingredients such as diazo compounds, photoacids, photoinitiators, quinone diazides, sensitisers etc. which absorb in the wavelength range of 250nm to 650nm. In this way a daylight stable printing plate can be obtained.

[0031] The image forming layer is preferably applied in an amount between 0.1 and 10 g/m², more preferably in an amount between 0.5 and 5 g/m².

[0032] The support may be as well a hydrophobic as a hydrophilic support and as well a rigid as a flexible support

[0033] In the imaging element according to the present invention, the support can be an anodised aluminum. A particularly preferred support is an electrochemically grained and anodised aluminum support

[0034] According to another embodiment in connection with the present invention, the support is a flexible support, such as paper or plastic film. As flexible support in connection with the present embodiment it is particularly preferred to use a plastic film e.g. substrated polyethylene terephthalate film, cellulose acetate film, polystyrene film, polycarbonate film etc... The plastic film support may be opaque or transparent.

[0035] It is particularly preferred to use a polyester film support to which an adhesion improving layer has been provided. Particularly suitable adhesion improving layers for use in accordance with the present invention comprise a hydrophilic binder and colloidal silica as disclosed in **EP-A- 619 524**, **EP-A- 620 502** and **EP-A- 619 525**. Preferably, the amount of silica in the adhesion improving layer is between 200 mg per m² and 750 mg per m². Further, the ratio of silica to hydrophilic binder is preferably more than 1 and the surface area of the colloidal silica is preferably at least 300 m² per gram, more preferably at least 500 m² per gram.

[0036] Between the support and the top layer the imaging element can contain other layers such as subbing layers and antihalo layers.

[0037] Irrespectively if the imaging element contains a dye according to the invention or not, the imaging element optionally contains between the support and the top layer a reflective layer. Said reflective layer can be any layer which reflects the IR-irradiation but is preferably aluminum with a high visual density e.g. vacuum deposited aluminum

[0038] The imaging element can be prepared by applying the different layers according to any known technique. Alternatively said imaging element may be prepared on the press with the support already on the press by a coater or coaters placed in the immediate vicinity of the press.

[0039] Imaging in connection with the present invention can be done with a thermal head. Preferably an image-wise scanning exposure is used involving the use of a laser, more preferably of a laser that operates in the infrared or near-infrared, i.e. wavelength range of 700-1500 nm. Most preferred are laser diodes emitting in the near-infrared. Exposure of the imaging element can be performed with lasers with a short as well as with lasers with a long pixel dwell time. Preferred are lasers with a pixel dwell time between 0.005 µs and 20 µs.

[0040] After the exposure the imaging element is ready to be used as a lithographic printing plate.

[0041] In another embodiment of the invention the exposure of the imaging element can be carried out with the imaging element already on the press. A computer or other information source supplies graphics and textual information to the printhead or a laser via a lead.

[0042] The printing plate of the present invention can also be used in the printing process as a seamless sleeve printing plate. This cylindrical printing plate which has as diameter the diameter of the print cylinder is slid on the print cylinder instead of applying in a classical way a classically formed printing plate. More details on sleeves are given in "Grafisch Nieuws" ed. Keesing, 15, 1995, page 4 to 6.

[0043] The following examples illustrate the present invention without limiting it thereto. All parts and percentages are by weight unless otherwise specified.

EXAMPLES 1


[0044] 0.35 g of GANTREZ AN 139 BF (a copolymer of vinylmethylether, maleic acid and maleic acid anhydride, commercially available from GAF, USA) and 0.0365 g of IR-absorbing dye IR-1 are dissolved in 4.5 g of a solvent mixture consisting for 44% of THF, 34 % of methoxypropanol and 22 % of methyl ethyl ketone. Said solution was coated onto an aluminum substrate to a wet coating thickness of 16 µm resulting after drying in a dry layer with a thickness of 1.15 g/m².

This imaging element was exposed on a CREO 3244 Trendsetter (tradename of CREO, Canada) at 2400 dpi, operating

at a drum speed of 40 rpm and a laser output of 11 watt.

After exposing the imaging element a printing plate is obtained, which was used to print on a GTO 52 press (trade name of Heidelberg Germany) using K + E 197 ink (trade name of Kast und Ehringer, Germany) and a fountain solution comprising 5 % G648 (trade name of Agfa-Gevaert, Belgium) and 10 % isopropyl alcohol. Good prints were obtained, i.e. prints with good ink-uptake in the exposed areas and no scumming in the non-exposed areas.

IR-1



EXAMPLE 2

[0045] 0.35 g of GANTREZ AN 139 BF (a copolymer of vinylmethylether, maleic acid and maleic acid anhydride, commercially available from GAF, USA) and 0.0365 g of IR-absorbing dye IR-1 are dissolved in 4.5 g of a solvent mixture consisting for 44% of THF, 34 % of methoxypropanol and 22 % of methyl ethyl ketone. Said solution was coated onto a subbed polyethylene terephthalate substrate to a wet coating thickness of 16 μm resulting after drying in a dry layer with a thickness of 1.15 g/m².

This imaging element was exposed on a CREO 3244 Trendsetter (tradename of CREO, Canada) at 2400 dpi, operating at a drum speed of 40 rpm and a laser output of 11 watt.

After exposing the imaging element a printing plate is obtained, which was used to print on a GTO 52 press (trade name of Heidelberg Germany) using K + E 197 ink (trade name of Kast und Ehringer,

Germany) and a fountain solution comprising 5 % G648 (trade name of Agfa-Gevaert, Belgium) and 10 % isopropyl alcohol. Good prints were obtained, i.e. prints with good ink-uptake in the exposed areas and no scumming in the non-exposed areas.

Claims

1. A heat-sensitive non-ablatable wasteless imaging element for providing a lithographic printing plate, having on a support as top layer an image forming layer comprising a heat-switchable binder, characterized in that said image

forming layer becomes more hydrophobic under the influence of heat, said heat-switchable binder having pendant hydrophilic groups being a (co)polymer containing monomeric units selected from the group consisting of maleic acid, fumaric acid, itaconic acid, 3-or 4-vinylphthalic acid, cis-1,2,3,6-tetrahydrophthalic acid, cis-5-norbornene-endo-2,3-dicarboxylic acid and their half esters.

- 5 2. A heat-sensitive non-ablatable wasteless imaging element for making lithographic printing plates according to claim 1 wherein said heat-switchable binder having pendant hydrophilic groups is a copolymer further containing monomeric units selected from the group consisting of vinyl methyl ether, ethene and styrene..
- 10 3. A heat-sensitive non-ablatable wasteless imaging element for making lithographic printing plates according to claim 1 or 2 further comprising a compound capable of converting light to heat.
- 15 4. A heat-sensitive non-ablatable wasteless imaging element for making lithographic printing plates according to claim 3 wherein said compound capable of converting light to heat is an infrared absorbing dye.
- 20 5. A heat-sensitive non-ablatable wasteless imaging element for making lithographic printing plates according to claim 3 wherein Said compound capable of converting light to heat is an infrared absorbing pigment.
- 25 6. A heat-sensitive non-ablatable wasteless imaging element for making lithographic printing plates according to claim 3 wherein the compound capable of converting light to heat is present in an amount of 1 to 25 % by weight of the total weight of the image forming layer.
7. A heat-sensitive non-ablatable wasteless imaging element for making lithographic printing plates according to claim 3 wherein the compound capable of converting light to heat is present in an amount to provide an optical density between the wavelenghts of 800 nm to 1100 nm of at least 0.35.
8. A method for providing a lithographic plate by imaging a heat-sensitive non-ablatable wasteless imaging element according to any of claims 1 to 7.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 20 4092

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
D,A	GB 2 203 438 A (ASAHI CHEMICAL IND) 19 October 1988 * page 3, line 5 - line 117; claims 1,7,17,18 *	1	B41C1/10
D,A	US 4 034 183 A (ULIG FRITZ) 5 July 1977 * column 4, line 5 - line 9; claims * * page 4, line 38 - line 42 * * column 2, line 51 - line 57 * * column 3, line 13 - line 14 * * column 3, line 56 - line 62 *	1	
D,A	PATENT ABSTRACTS OF JAPAN vol. 009, no. 294 (M-431), 20 November 1985 & JP 60 132760 A (ASAHI KASEI KOGYO KK), 15 July 1985 * abstract *	1	
D,A	US 4 081 572 A (PACANSKY THOMAS J) 28 March 1978 * the whole document *	1	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B41C
Place of search		Date of completion of the search	Examiner
THE HAGUE		20 April 1999	Rasschaert, A
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 20 4092

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20-04-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2203438 A	19-10-1988	JP 2572222 B	16-01-1997
		JP 63249695 A	17-10-1988
		JP 2572224 B	16-01-1997
		JP 63257690 A	25-10-1988
		JP 2572228 B	16-01-1997
		JP 63262288 A	28-10-1988
		JP 2532244 B	11-09-1996
		JP 63283989 A	21-11-1988
		JP 2704870 B	26-01-1998
		JP 63302092 A	08-12-1988
		JP 2704872 B	26-01-1998
		JP 63309441 A	16-12-1988
		JP 1016689 A	20-01-1989
		JP 2704873 B	26-01-1998
		JP 1018635 A	23-01-1989
		JP 2553570 B	13-11-1996
		DE 3811423 A	20-10-1988
		FR 2613498 A	07-10-1988
		FR 2619227 A	10-02-1989
		US 4965322 A	23-10-1990
		US 5025266 A	18-06-1991
		US 5187047 A	16-02-1993
US 4034183 A	05-07-1977	DE 2448325 A	15-04-1976
		AU 8544575 A	07-04-1977
		BE 834322 A	08-04-1976
		BR 7506524 A	17-08-1976
		CA 1066948 A	27-11-1979
		FR 2287715 A	07-05-1976
		GB 1530287 A	25-10-1978
		JP 1289129 C	14-11-1985
		JP 51063704 A	02-06-1976
		JP 60012939 B	04-04-1985
		NL 7511807 A,B,	13-04-1976
US 4081572 A	28-03-1978	NONE	