(11) **EP 0 955 487 A3**

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3: **08.08.2001 Bulletin 2001/32**

(51) Int CI.7: **F16H 21/12**

(43) Date of publication A2: **10.11.1999 Bulletin 1999/45**

(21) Application number: 99303572.4

(22) Date of filing: 07.05.1999

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 08.05.1998 ZA 9803914

(71) Applicant: Metal Box South Africa Limited Sandton, Gauteng 2146 (ZA)

(72) Inventor: Bajic, Milan Killarney, 2193 Gauteng (ZA)


(74) Representative:

Watkin, Timothy Lawrence Harvey et al Mewburn Ellis, York House, 23 Kingsway London, WC2B 6HP (GB)

(54) A motion transfer mechanism

(57) A transfer mechanism (10) for transferring rotary motion at one location to rotary motion at a second, distant location includes a first connecting element (18) having a first end (18.1), which is fixedly connectable to a rotatable member (12) to rotate therewith, in use, and having an opposed end (18.2); and a first linkage assembly (22), having a first end (22.1) which is connected to the opposed end of the first connecting element and an opposed end (22.2) which is constrained to be displaceable reciprocally along a predetermined axis (26). The mechanism also includes an elongate connecting assembly (30), a first end of which is connected to said opposed end of the first linkage assembly (22.2), so that its movement is also constrained along said predeter-

mined axis and at least one further linkage assembly (34), a first end of which is connected to the elongate connecting assembly (30) at a predetermined connection point, the point being spaced from the first linkage assembly and also lying on the predetermined axis (26). The mechanism yet further includes a second connecting element (36) having a first end connected to an opposed end of the further linkage assembly (34), the second connecting element having an opposed end (36.2) which is fixedly connectable, in use, to a second rotatable element (40) so that rotation of the first rotatable element is transferred via the connecting elements, the linkage assemblies and the connecting assembly to identical rotational movement of the second rotatable element.





EUROPEAN SEARCH REPORT

Application Number

EP 99 30 3572

	DOCUMENTS CONSIDERED	O TO BE RELEVANT		
Category	Citation of document with indicatio of relevant passages	n, where appropriate,	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.CI.6)
X A	US 4 186 614 A (HAMLIN 5 February 1980 (1980-0) * figures 1,3 *		1,9,10, 12 2,11	F16H21/12
				TECHNICAL FIELDS SEARCHED (Int.Cl.6)
				F16H G05G
	The present search report has been dr	•		
Place of search		Date of completion of the search		Examiner
X : parti Y : parti docu A : tech O : non-	THE HAGUE ATEGORY OF CITED DOCUMENTS icularly relevant if taken alone clularly relevant if combined with another unent of the same category inological background —written disclosure mediate document	T: theory or princi E: earlier patent c after the filing c D: document cite L: document cite &: member of the document	ple underlying the locument, but publicate in the application of the for other reasons	ished on, or

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 99 30 3572

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-06-2001

	Patent document cited in search report		Publication date	Patent family member(s)	Publication date
	US 4186614	Α	05-02-1980	NONE	
5459					
O FORM P0459					

3

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82