

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 971 049 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

12.01.2000 Bulletin 2000/02

(51) Int. Cl.⁷: **C23F 11/08**, C23F 11/10

(21) Application number: **98304911.5**

(22) Date of filing: **23.06.1998**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**

Designated Extension States:

AL LT LV MK RO SI

(71) Applicant: **BetzDearborn Inc**

Trevose, PA 19053-6783 (US)

(72) Inventors:

- **Reichgott, David W.**
Seattle, WA 98177 (US)
- **Anderson, Sydia B.**
Doylestown, PA 18901 (US)

• **Cady, Michael A.**

Yardley, Pa 19067 (US)

• **May, Roger C.**

Glenside, PA 19038 (US)

• **Monino, Anita G.**

Horsham, PA 19044 (US)

(74) Representative:

W.P. Thompson & Co.

Coopers Building,

Church Street

Liverpool L1 3AB (GB)

(54) **Methods of inhibiting corrosion using halo-benzotriazoles**

(57) The use of halo-benzotriazoles as corrosion inhibitors in aqueous systems is disclosed. Halo-benzotriazoles such as chloro-tolyltriazole and bromo-tolyltriazole were found to be more effective corrosion inhibitors than tollyltriazole in the presence of chlorine.

EP 0 971 049 A1

Description**FIELD OF THE INVENTION**

5 [0001] The present invention relates to the control of corrosion in aqueous systems. More particularly, the present invention relates to the inhibition of corrosion of steel and copper alloys in aqueous systems through application of halo-benzotriazoles to the aqueous system.

BACKGROUND OF THE INVENTION

10 [0002] The use of triazoles for inhibiting the corrosion of copper and iron alloys in a wide variety of aqueous and non-aqueous systems is well known. In industrial cooling water systems, benzotriazole and tolyltriazole are used most often. Tolyltriazole is generally preferred because of its lower cost. Triazoles are film forming materials that provide efficient coverage of metal or metal oxide surfaces in a system thereby providing protection against corrosive elements present
15 in an aqueous system. In addition to the film forming tendency of various azoles, they also precipitate soluble, divalent copper ions. The precipitation prevents transport of copper ions to ferrous surfaces, where galvanic reactions between copper ions and iron atoms leads to pitting corrosion of the ferrous metal.

[0003] While the use of azoles for corrosion inhibition is widespread, there are drawbacks to their use, specifically with tolyltriazole. The most important drawbacks are experienced when azoles are used in combination with oxidizing halo-
20 gens. Oxidizing halogens such as elemental chlorine, bromine, their hypohalous acids, or their alkaline solutions (i.e., solutions of hypochlorite or hypobromite ion) are the most common materials used to control microbiological growth in cooling water systems. When copper or iron alloys that have previously been protected with azoles are exposed to an oxidizing halogen, corrosion protection breaks down. After breakdown, it is difficult to form new protective films in tolyltriazole treated cooling systems that are being chlorinated, particularly continuously chlorinated. Very high dosages of
25 tolyltriazole are frequently applied in an attempt to improve performance, often with limited success.

[0004] The degradation of protection of azole films in the presence of oxidizing halogens is well-documented in the literature. For example, R. Holm, et al., concluded that hypochlorite penetrates an intact triazole film, leading to higher corrosion rates, and that secondly, hypochlorite attacks the prefilmed triazole surface, disrupting or degrading the film (53rd Annual Meeting of the International Water Conference) Paper No. IWC-92-40, 1992). Lu, et al., also studied inter-
30 actions of triazole films with hypochlorite on copper and copper alloy surfaces ("Effects of Halogenation on Yellow Metal Corrosion: Inhibition by Triazoles", Corrosion, 50, 422 (1994)). Lu, et al., concluded:

(a) prefilmed tolyltriazole on copper and brass surfaces undergoes decomposition during chlorination;

35 (b) the stability of prefilmed tolyltriazole on copper and brass to NaOCl was improved when tolyltriazole was added to the hypochlorite solution;

(c) clean (i.e., non-prefilmed) copper surfaces did not develop good protective films when placed in solutions containing mixtures of tolyltriazole and NaOCl.

40 [0005] Thus, the combination of tolyltriazole with NaOCl did not produce a composition capable of efficient film formation and corrosion inhibition.

[0006] The nature of the reaction products when azoles are exposed to oxidizing halogens in a cooling water system is not clear. The literature teaches that a compound is formed when chlorine and tolyltriazole are combined in cooling
45 waters, and that it responds to analytical tests for chlorine. For example, Vanderpool, et al., state that chlorine reacts reversibly with tolyltriazole to produce N-chloro-tolyltriazole. They specifically state, "presumably this compound is not itself an inhibitor." Rather, they teach that it is readily hydrolyzed to the original tolyltriazole and hypochlorous acid so that free tolyltriazole becomes available for corrosion inhibition ("Improving the Corrosion Inhibitor Efficiency of Tolyltriazole in the Presence of Chlorine and Bromine", NACE Corrosion/87, Paper No. 157 (1987)). Hollander and May stated
50 they were able to isolate 1-chloro-tolyltriazole from stored, more highly concentrated solutions, but they also teach that "at low concentrations (less than 10 mg/L) rapid hydrolysis made it impossible to isolate the chloro adducts." Based upon proton NMR analysis, the material Hollander and May isolated was chloro-tolyltriazole.

[0007] Another observation is that a very characteristic odor is present whenever tolyltriazole and chlorine are combined in cooling waters.

55 [0008] In contrast, the present authors have shown that chloro-tolyltriazole does not respond to analytical tests for chlorine, despite extended boiling. And solutions of chloro-tolyltriazole, surprisingly, do not produce the characteristic odor. Thus chloro-tolyltriazole is clearly different from the tolyltriazole-chlorine reaction product that forms in-situ in cooling water systems.

[0009] There are also references in the literature to 5-chlorobenzotriazole (i.e., CAS number [94-97-3]). In "The Water Drop", Volume I No. 2, 1985, Puckorius & Associates state that chlorinated tolyltriazole is effective as a corrosion inhibitor and cite R.P. Carr as a reference. A literature review of published work by Carr indicates that he actually teaches that reactions between tolyltriazole and chlorine do not occur under cooling water conditions ("The Performance of
 5 Tolyltriazole in the Presence of Sodium Hypochlorite Under Simulated Field Conditions", NACE Corrosion/83 Paper No. 283, 1983). In this Corrosion/83 paper, Carr does discuss the inhibiting action of a chloro-azole but it is a reference to earlier literature and specifically to the action of 5-chlorobenzotriazole and related aryl substituted azoles in sulfuric acid solutions ("Effects of Substituted Benzotriazole on the Electrochemical Behavior of Copper in H₂SO₄", Wu et al., Corrosion, Volume 37, No. 4, 223 (1981)). Since the 1985 Puckorius reference, there has been widespread use of tolyltriazole in chlorinated cooling systems with well established performance difficulties, indicating a continuing, unsolved
 10 problem in the art.

[0010] Other problems are well-known when tolyltriazole and oxidizing halogens are combined in cooling waters. These include a loss in the extent of precipitation of transition metal ions such as copper, thus leading to improved transport and galvanic corrosion, a change in the response of the standard spectrophotometric test for tolyltriazole,
 15 leading to unintentional overfeed, and the objectionable odor mentioned above. This odor can be sensed even when the cooling water originally contained 1 ppm tolyltriazole, or less. Since cooling water often passes over cooling towers, evaporation and drift release the objectionable odor to the local environment.

[0011] The present inventors believe that the odorous material is N-chloro-tolyltriazole, that it forms OCl⁻ reversibly with tolyltriazole in dilute solution, and that it is absent in the final product when the reaction is run in concentrated solution, i.e.,
 20



The present inventors have found no evidence of reversion of chloro-tolyltriazole to either the odorous intermediate or
 25 to tolyltriazole. Nor is there any evidence of reactions between hypochlorite and chloro-tolyltriazole in dilute aqueous solutions.

SUMMARY OF THE INVENTION

[0012] The present inventors have discovered that halo-benzotriazoles such as chloro-tolyltriazole and bromo-tolyltriazole are more effective than tolyltriazole in inhibiting corrosion in aqueous systems. The halo-benzotriazoles are substantially more effective than tolyltriazole in the presence of chlorine. Furthermore, when chloro-tolyltriazole is exposed to chlorine, an objectionable odor does not form and the quantity of chlorine that is required to produce a residual in the aqueous system is reduced.
 30

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0013] The present inventors have discovered that halo-benzotriazoles such as chloro-tolyltriazole and bromo-tolyltriazole are more effective than tolyltriazole in inhibiting corrosion in aqueous systems. The halo-benzotriazoles are substantially more effective corrosion inhibitors than tolyltriazole in the presence of chlorine. The efficacy of the present invention is surprising given the prior knowledge that chlorination of an azole treated system leads to degradation of corrosion inhibition performance. Furthermore, the halo-benzotriazoles of the present invention are not subject to the formation of objectionable odors when exposed to chlorine as is tolyltriazole, the quantity of chlorine that is required to produce a residual in the aqueous system is notably reduced in comparison to systems treated with tolyltriazole, and
 45 the treatment is effective in the presence of sulfide ions.

[0014] It was discovered that the ex-situ preparation of a halo-benzotriazole provided a corrosion inhibitor which exhibited a surprising and unexpected activity when compared to a treatment comprising a mixture of a benzotriazole and a halogen. The results of the studies of the present invention clearly show that mere mixtures of a benzotriazole and a halogen in a cooling water system do not provide the corrosion inhibiting effect of the addition of a halo-benzotriazole prepared ex-situ. As further evidence of the surprising activity of an ex-situ prepared halo-benzotriazole, the present inventors found that the chlorine demand of a system treated in accordance with the present invention was significantly reduced. Furthermore, in systems treated in accordance with the present invention the objectionable odor common to systems treated with a triazole and halogen was absent.
 50

[0015] The halo-benzotriazoles of the present invention can include chloro-, fluoro-, bromo- and iodo- as well as haloalkyl (trifluoromethyl) benzotriazoles. Preferred are chloro-tolyltriazole and bromo-tolyltriazole. The azole may include tolyltriazole, benzotriazole, butylbenzotriazole, mercaptobenzothiazole and the like. The preferred azole is tolyltriazole.
 55

[0016] The preferred benzotriazole, tolyltriazole, is such that the preferred halo-benzotriazole is chloro-tolyltriazole or

bromo-tolyltriazole. The preparation of the preferred chloro-tolyltriazole can be by any suitable means. Examples of preparation methods include but are not limited to reactions with hypochlorite, N-chlorosuccinimide, and other chlorinating agents. A method of forming chloro-tolyltriazole is through the reaction of tollyltriazole with hypochlorite, in which case the final reaction mixture is an alkaline solution that can be used with or without further modification. Alternatively, chloro-tolyltriazole can be formed through the reaction of tollyltriazole with hypochlorite in acetic acid solutions, (i.e., hypochlorous acid) and then isolated as a solid. For convenience of application, the solid can be redissolved in alcohols such as methanol or 2-propanol, aqueous solutions of alcohols or strong alkaline solutions such as sodium hydroxide or potassium hydroxide.

[0017] The preparation of bromo-tolyltriazole can be by any suitable means. Examples of preparation methods include but are not limited to reactions with hypobromite, bromine, and other brominating agents. A method of forming bromo-tolyltriazole is through the reaction of tollyltriazole with bromine in an aqueous solution and then isolating it as a solid. For convenience of application, the solid can be dissolved in a strong alkaline solution such as sodium hydroxide or potassium hydroxide.

[0018] In treating an aqueous system in accordance with the present invention, the chloro-tolyltriazole (hereinafter Cl-TTA) is preferably fed continuously to the water. A preferred treatment concentration ranges from about 0.5 to 10 parts per million, most preferably at about 3 parts per million. Continuous feed is not, however, a requirement. The chloro-tolyltriazole can be fed at a concentration sufficient to form a protective film and thereafter feed can be discontinued for extended periods of time.

[0019] The halo-benzotriazole treatment of the present invention can be used in combination with other corrosion and/or deposit inhibiting treatments known in the art including but not limited to phosphates, phosphonates, acrylic homo- and copolymers, chelants, and oximes.

[0020] The present invention will now be further described with reference to a number of specific examples which are to be regarded solely as illustrative and not as restricting the scope of the present invention.

Examples

Example 1

[0021] The preparation of the solid samples was as follows:

[0022] Tollyltriazole (hereinafter TTA) (30 g, 0.225 mol) was dissolved in aqueous acetic acid (60 mL, 1:1 ratio) by heating to 32°C. Sodium hypochlorite (366 g, 5.25% sodium hypochlorite as a bleach solution) was added while maintaining the reaction temperature at ~ 20°C. Following the addition, the reaction mixture was stirred at room temperature for 24 hours. A sticky precipitate formed during this time. The solid was filtered and taken into methylene chloride. The solid that did not dissolve was filtered and identified as a mixture of Cl-TTA with minor amounts of TTA and dichloro-tolyltriazole (di-Cl-TTA). The methylene chloride was removed to obtain a yellow solid which was identified as a mixture of Cl-TTA with minor amounts of di-Cl-TTA. Unless noted, this latter solid was used in the following Examples.

Example 2

[0023] A slurry of TTA (50 g, 0.376 mol) in 25 g of water was warmed to 35°C Sodium hypochlorite (27.9 g, 0.376 mol, added as 226.8 g of a 12.3% sodium hypochlorite solution) was added over a period of 2 hours. After the addition, the reaction was kept at 45°C for one hour. During the addition the pH of the reaction mixture increased to 12 and the solids dissolved. The final product was analyzed by ¹H and ¹³C NMR and LC-UV and found to be composed of 81.9% Cl-TTA, 8.8% residual TTA, and 9.3% di-Cl-TTA based on the relative areas in the UV spectra.

[0024] On dilution to 1 to 100 ppm azole, with or without pH adjustment to about 7.2, there was no odor from the halo-benzotriazole solution of the present invention.

Example 3

[0025] In the schemes below, TTA was present at 100 ppm, in contrast to Example 2 where the initial slurry contained about 200,000 ppm. "x" denotes a stoichiometric ratio.

Scheme 1

pH=7

slow

TTA+1.1xNaOCl<----->odorous solution ----->Cl-TTA(ppt odorous)

Scheme 2

pH=11.8

pH=8.2

TTA+1.1xNaOCl<----->solution, no odor----->Cl-TTA(ppt odorous)

Example 4

[0026] Cl-TTA, prepared as a solid according to Example 1, was dissolved in methanol and charged to a simulated cooling water solution. The solution contained 319 ppm Ca (calculated as CaCO_3), 7 ppm Mg (calculated as CaCO_3), 190 ppm NaHCO_3 , 882 ppm Na_2SO_4 , 1184 ppm NaCl , 5 ppm Cl-TTA, and 2.4 ppm of hydroxyethylidene diphosphonic acid (HEDP). Hypochlorite was absent. The solution was maintained at 120°F by an admiralty brass heater tube and at pH=7.2 to 7.5 by a pH controller equipped to feed sulfuric acid on demand. The solution was recirculated past the heater and past both admiralty and copper/nickel alloy corrosion rate meters (CRM). After 1 hour the solution was drained and replaced by an identical solution with no Cl-TTA. This solution was fed to overflow which replenished the system with fresh solution at a rate of about 4% by volume per hour. This system was maintained under these conditions continuously until the bright admiralty tube was tarnished, at which point the experiment was terminated. Comparisons were made to identical experiments with TTA and benzotriazole.

TABLE I

Admiralty Tube Appearance			
Pretreatment	40 hours	94 hours	336 hours
CI-TTA	Bright	Bright	Tarnished
TTA	Bright	Tarnished	*
Benzotriazole	Tarnished	*	*

*Experiment previously terminated.

TABLE II

Pretreatment	Admiralty Corrosion Rate (mpy)			Cu/Ni Corrosion Rate (mpy)		
	40 hrs.	94 hrs.	336 hrs.	40 hrs.	94 hrs.	336 hrs.
CI-TTA	0.2	0.3	0.5	0.7	0.4	0.8
TTA	<0.1	2.2	*	N/A	5.2	*
Benzotriazole	1.3	*	*	2.0	*	*

*Experiment previously terminated.

Example 5

[0027] Corrosion tests were carried out in the apparatus described in Example 4 with water containing 500 ppm Ca, 250 ppm Mg, 25 ppm Malk, 15 ppm o-PO₄, 3 ppm tetrapotassium pyrophosphate, 10 ppm of a 3:1, low molecular weight, acrylic acid/allyl 2-hydroxypropyl sulfonate ether copolymer, 2.4 ppm HEDP, a 3ppm of either CI-TTA or TTA. The pH was maintained at 7.2 with a blended mixture of air and carbon dioxide at 120° F for 18 hours. Electrochemical corrosion rates were measured using admiralty brass (ADM) and low carbon steel (LCS) working electrodes. All tests also had both admiralty and LCS coupons in contact with the solution. The method differed from Example 4 in that the azole was fed continuously at 3 ppm during these experiments. The azole was supplied by dissolving the solid in potassium hydroxide solution and then diluting it into the feedwater for the system. Each experiment was duplicated: once with an admiralty brass heated tube, and once with a low carbon steel heated tube. Corrosion rates were measured as in Example 4 from admiralty and LCS working electrodes, and by weight changes of admiralty and LCS coupons. Rates for the coupons were measured for the initial day of each run, and a "differential" rate was calculated for the remaining days of the run by offsetting the initial rate from the overall rate.

TABLE III

CRM Corrosion Rates: Values at end of six days (mpy)				
	LCS Heated Surface		ADM Heated Surface	
	CI-TTA	TTA	CI-TTA	TTA
LCS	0.2	0.4	0.45	0.75
ADM	0.00	0.00	0.05	0.07

TABLE IV

Gravimetric Coupon Corrosion Rates (mpy) (First day and differential rates)				
	LCS Heated Surface		ADM Heated Surface	
	CI-TTA	TTA	CI-TTA	TTA
Day 1 LCS	4.6	3.0	3.4	2.9
Day 6 LCS (diff.)	0.25	0.33	0.25	0.25
Day 1 ADM	1.9	2.1	1.6	1.8
Day 6 ADM (diff)	0.00	0.20	0.00	0.10

Example 6

[0028] The method of Example 5 was followed, except a solution of sodium hypochlorite was added after 20 hours and continued for an additional 72 hours. The feed rate of the sodium hypochlorite was controlled to produce a "chlorine residual" of about 0.1 to 0.3 ppm as Cl_2 using a standard DPD spectrophotometric test on the recirculating water. For the experiment with Cl-TTA, the feed rate of the sodium hypochlorite was about 30% of that required for TTA. For TTA, the characteristic odor was detected immediately after the first hypochlorite was added. With Cl-TTA, there was no odor upon initiating hypochlorite addition, and only a trace was sensed just prior to concluding the four day run.

TABLE V

CRM Corrosion Rates: Values at 90 hour mark (mpy)		
	LCS Heated Surface	
	Cl-TTA	TTA
LCS	0.5	2.3
ADM	0.06	0.02

TABLE VI

Gravimetric Corrosion Rates (mpy)		
	LCS Heated Surface	
	Cl-TTA	TTA
Day 2 to 4 LCS	1.1	2.6
Day 4 LCS (diff.)	0.4	1.4
Day 2 to 4 ADM	1.1	1.2
Day 4 ADM (diff.)	0.15	0.85

Example 7

[0029] Solutions of azole at 6 ppm were made in deionized water, and the pH was adjusted to 7.0. Cu^{+2} ion was added (0.1 ppm from cupric sulfate) and the pH was again adjusted to 7.0. A sample was digested with nitric acid, analyzed for copper, and a second sample was filtered (0.2 micron pore size), digested, and analyzed for copper. The ratio was expressed as "% soluble Cu":

TABLE VII

Sample	% Soluble Cu
TTA	15
TTA+NaOCl	90
Cl-TTA	13

Example 8

[0030] Admiralty brass corrosion coupons and working electrodes were coated with a sulfide layer by exposing the metal to a sodium sulfide solution for 18 hours. These samples were rinsed and dried. Corrosion tests were carried out in aqueous solutions in stirred beakers containing 500 ppm Ca, 250 ppm Mg, 25 ppm Mank, 15 ppm o-PO_4 , 3 ppm tetra-

potassium pyrophosphate, 10 ppm of a 3:1, low molecular weight, acrylic acid/allyl 2-hydroxypropyl sulfonate ether copolymer, 2.4 ppm HEDP, and the pH was maintained at 7.2 with a blended mixture of air and carbon dioxide at 120°F for 18 hours. Electrochemical corrosion rates were measured using admiralty brass or low carbon steel working electrodes. All tests also had both admiralty and LCS coupons in contact with the solution.

- 5 **[0031]** Each solution was tested with and without addition of sodium hypochlorite (added after 1 hour exposure). In a separate, but otherwise identical experiment, clean low carbon steel working electrodes were used in place of the sulfide-exposed admiralty brass, but the sulfide-exposed brass coupons were present as a source of copper. At the conclusion of the experiment, a sample of the supernatant solution was taken and analyzed for copper. Analyses were taken with and without filtration through a 0.2 micron membrane filter.

TABLE VIII

Azole	NaOCl (ppm)	Admiralty Brass	Low Carbon Steel		
		Corrosion Rate (mpy)	Corrosion Rate (mpy)	Copper (ppm)	
				Unfiltered	Filtered
none	0	1.01	5.4	0.354	0.103
3 ppm TTA	0	0.07	1.2	0.014	0.014
3 ppm Cl-TTA	0	0.06,0.05	1.0	0.005	0.004
none	2.0	2.09	5.2	0.417	0.059
3 ppm TTA	2.0	0.45	2.6	0.133	0.066
3 ppm Cl-TTA	2.0	0.13	1.7	0.086	0.039

Example 9

- 30 **[0032]** A synthetic sea water was formulated from deionized water plus 1010 ppm Ca as CaCO_3 , 5226 ppm Mg (as CaCO_3), 18971 ppm Cl, 2660 ppm SO_4 , 117 ppm M-alkalinity (as CaCO_3), 5 ppm azole (see below), and the pH was maintained at 7.8 with a blended mixture of air and carbon dioxide at 100°F.

[0033] Admiralty brass electrodes were exposed to this medium for 1 hour and then they were transferred to identical water with no azole present. Electrochemical corrosion rates were measured for 18 hours.

TABLE IX

Azole	Mean Electrochemical Corrosion Rate (mpy)
Benzotriazole	40
5-Butylbenzotriazole	15
Tolyltriazole	6
Chloro-tolyltriazole	3.2

Example 10

- 50 **[0034]** Sodium hypochlorite (12.2%, 204.9 g, 0.336 mol) was added over 90 minutes to a stirring slurry of benzotriazole (40 g, 0.336 mol) in 30 g of water at room temperature. Following the addition, the reaction mixture was held at 45-50°C for one hour. Upon cooling, a precipitate formed. A clear yellow solution was obtained after adjusting the pH to 11. The final product was analyzed by LC/MS and ^{13}C and ^1H NMR and found to be composed of 54.6% chloro-benzotriazole (Cl-BZT), 23.9% residual benzotriazole, and 21.5% di-chloro-benzotriazole (di-Cl-BZT).

Example 11

[0035] Bromine (12.5 g, 0.078 mol) was added to a stirring slurry of TTA (10 g, 0.075 mol) in 66 g of water in a reactor

protected from light, while maintaining the temperature at <25°C. After the addition, the reaction mixture was held at 35-40°C for one hour. Upon cooling, adjusting the pH to 11-12 did not produce a clear solution. The small amount of precipitate that formed upon standing was removed by filtration, the pH of the filtrate was adjusted to neutral, and the resulting precipitate filtered. This solid was characterized by LC/MS and ¹³C and ¹H NMR and found to be composed of 90.5% bromo-tolyltriazole (Br-TTA), 4.9% residual TTA, and 4.2% di-bromo-TTA.

Example 12

[0036] The method of Example 8 was followed, using samples from Examples 2, 11 and 12 at 1 to 4 ppm total actives. The following were the 18 hour averaged electrochemical corrosion rates:

TABLE X

Azole	Conc. (ppm)	Source	NaOCl	Average Corrosion Rate (mpy)
Cl-BZT	1	Ex. 11	none	0.21
	2			0.09
	4			0.03
Cl-BZT	1	Ex. 11	2 ppm	0.55
	2			0.25
	4			0.09
Cl-TTA	1	Ex. 2	none	0.14
	2			0.09
	4			0.08
Cl-TTA	1	Ex. 2	2 ppm	0.58
	2			0.24
	4			0.09
Br-TTA	1	Ex. 12	none	0.17
	2			0.11
	4			0.07
Br-TTA	1	Ex. 12	2 ppm	0.45
	2			0.16
	4			0.09
TTA	1		none	0.13
	2			0.14
	4			(n/a)
TTA	1		2 ppm	(n/a)
	2			0.45
	4			0.27

[0037] The above examples show that the halo-benzotriazoles of the present invention are effective corrosion inhibitors even in the presence of chlorine.

[0038] While the present invention has been described with respect to particular embodiments thereof, it is apparent that numerous other forms and modifications of this invention will be obvious to those skilled in the art. The appended claims and this invention generally should be construed to cover all such obvious forms and modifications which are within the true spirit and scope of the present invention.

Claims

- 5 1. A method of inhibiting corrosion of metal surfaces contacted by an aqueous system being treated with a halogen comprising adding to said aqueous system being treated with a halogen an amount, effective for the purpose of inhibiting corrosion of a halo-benzotriazole prepared ex-situ said aqueous system in combination with at least one other aqueous system treatment material.
- 10 2. A method as claimed in claim 1, wherein said other aqueous system treatment material comprises corrosion inhibiting treatments, deposit inhibiting treatments and mixtures thereof.
3. A method as claimed in claim 2 wherein said corrosion inhibiting treatment, deposit inhibiting treatments and mixtures thereof comprise phosphates, phosphonates, acrylic monopolymers, acrylic copolymers, chelants, oximes, biocides and mixtures thereof.
- 15 4. A method as claimed in any one of the preceding claims, wherein said halo-benzotriazole comprises mono-halo-benzotriazoles, di-halo-benzotriazoles and mixtures thereof.
- 20 5. A method of forming a corrosion inhibiting layer on a metal surface in contact with an aqueous system being treated with a halogen comprising adding to said aqueous system, an amount effective for the purpose of inhibiting corrosion, of a halo-benzotriazole prepared ex-situ said aqueous system in combination with at least one other aqueous system treatment material.
- 25 6. A method as claimed in claim 5, wherein said other aqueous system treatment material comprises corrosion inhibiting treatments, deposit inhibiting treatments and mixtures thereof.
7. A method as claimed in claim 6 wherein said corrosion inhibiting treatments, deposit inhibiting treatments and mixtures thereof comprise phosphates, phosphonates, acrylic monopolymers, acrylic copolymers, chelants, oximes, biocides and mixtures thereof.
- 30 8. A method as claimed in claim 5, 6 or 7, wherein said halo-benzotriazole comprises mono-halo-benzotriazoles, di-halo-benzotriazoles and mixtures thereof.
- 35 9. A method of inhibiting copper ion transport in an aqueous system being treated with a halogen in contact with metal surfaces including copper comprising adding to said aqueous system an amount effective for the purpose of inhibiting corrosion of a halo-benzotriazole prepared ex-situ said aqueous system in combination with at least one other aqueous system treatment material.
- 40 10. A method as claimed in claim 9 wherein said other aqueous system treatment material comprises corrosion inhibiting treatments, deposit inhibiting treatments and mixtures thereof.
11. A method as claimed in claim 10 wherein said corrosion inhibiting treatments, deposit inhibiting treatments and mixtures thereof comprise phosphates, phosphonates, acrylic monopolymers, acrylic copolymers, chelants, oximes, biocides and mixtures thereof.
- 45 12. A method as claimed in claim 9, 10 or 11, wherein said halo-benzotriazole comprises mono-halo-benzotriazoles, di-halo-benzotriazoles and mixtures thereof.

50

55



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 30 4911

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WO 96 29449 A (BETZ LABORATORIES) 26 September 1996 * page 8, line 14-18; claims 1-7; examples 4-11 *	1-12	C23F11/08 C23F11/10
X	US 4 184 991 A (SCHEURMAN CLARENCE III) 22 January 1980 * page 4, line 5; claim 1 * * page 5, line 7 * * page 6, line 36-41 *	1-12	
X	EP 0 478 247 A (CALGON CORP) 1 April 1992 * page 4, line 36; claim 1 * * page 5, line 47-53 *	1-12	
X	EP 0 481 667 A (CALGON CORP) 22 April 1992 * claims 1,5 *	1-12	
A	DATABASE WPI Section Ch, Week 7417 Derwent Publications Ltd., London, GB; Class E13, AN 74-31998V XP002083198 & JP 49 014056 B (KK MATSUI SHIKISO KAGAKU), 4 April 1974 * abstract *		TECHNICAL FIELDS SEARCHED (Int.Cl.6) C23F
A	ZAK E.G.: "The Mechanism of the protective action of halogen derivatives of benzotriazole in preventing the corrosion of metals" WERKSTOFFE UND KORROSION., vol. 30, no. 10, pages 740-741, XP002083292 WEINHEIM DE		
A	US 5 503 775 A (RAO NARASIMHA M ET AL) 2 April 1996 -/-		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 November 1998	Examiner Torfs, F
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/82 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 30 4911

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A,D	HOLLANDER O ET AL: "THE CHEMISTRY OF AZOLE COPPER CORROSION INHIBITORS IN COOLING WATER" CORROSION, vol. 41, no. 1, 1 January 1985, pages 39-45, XP002008378 ---		
A,D	LU F ET AL: "EFFECT OF HALOGENATION ON YELLOW METAL CORROSION: INHIBITION BY TRIAZOLES" CORROSION, vol. 50, no. 6, 1 June 1994, pages 422-431, XP000457454 -----		
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 November 1998	Examiner Torfs, F
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 30 4911

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-11-1998

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9629449 A	26-09-1996	AU 692089 B	28-05-1998
		AU 5255596 A	08-10-1996
		AU 7399298 A	27-08-1998
		CA 2211868 A	26-09-1996
		EP 0815288 A	07-01-1998
		US 5772919 A	30-06-1998
		US 5773627 A	30-06-1998
US 4184991 A	22-01-1980	NONE	
EP 0478247 A	01-04-1992	US 5217686 A	08-06-1993
		AT 132207 T	15-01-1996
		AU 639603 B	29-07-1993
		AU 8470891 A	26-03-1992
		CA 2051883 A	25-03-1992
		DE 69115820 D	08-02-1996
		DE 69115820 T	08-08-1996
		ES 2081440 T	01-03-1996
		JP 1982074 C	25-10-1995
		JP 5106069 A	27-04-1993
		JP 7013309 B	15-02-1995
		US 5236626 A	17-08-1993
EP 0481667 A	22-04-1992	US 5141675 A	25-08-1992
		AT 147444 T	15-01-1997
		AU 639835 B	05-08-1993
		AU 8582491 A	16-04-1992
		CA 2053157 A	16-04-1992
		DE 69124057 D	20-02-1997
		DE 69124057 T	17-04-1997
		JP 2736293 B	02-04-1998
		JP 5086488 A	06-04-1993
US 5503775 A	02-04-1996	NONE	