

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 069 177 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
17.01.2001 Bulletin 2001/03

(51) Int. Cl.⁷: **C11D 17/04**, A47L 25/00,
A45D 34/04

(21) Application number: **00111978.3**

(22) Date of filing: **19.06.2000**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **12.07.1999 EP 99113435**

(71) Applicant:
**The Procter & Gamble Company
Cincinnati, Ohio 45202 (US)**

(72) Inventors:
• **Sandbach, David Roy
3090 Overijse (BE)**
• **Wevers, Jean
1840 Steenhuffel (BE)**

(74) Representative:
**Hirsch, Uwe Thomas et al
Procter & Gamble European Service GmbH,
Sulzbacher Strasse 40-50
65824 Schwalbach am Taunus (DE)**

(54) **Fabric treatment applicator**

(57) The present invention relates to an applicator for a fabric treatment composition and its application. More specifically the invention relates to a versatile convenient to carry and to apply fabric treatment applicator. Claimed and described is an applicator comprising a nib (10) and further comprising bleach and surfactant. The present invention combines effective mechanical stain removal and effective chemical stain removal.

EP 1 069 177 A1

DescriptionField of the invention

5 **[0001]** The present invention relates to an applicator for a fabric treatment composition and its application. More specifically the invention relates to a convenient to carry fabric treatment applicator comprising a nib for application and a fabric treatment composition comprising a surfactant and a peroxide bleach.

Background of the invention

10 **[0002]** Portable stain removers for a liquid composition, for pre laundry application, post laundry application or application on fresh stains, are known articles of manufacture. Similarly, portable applicators for the application of other liquid compositions are known, for example in the field of ink removal. Prior art in this field includes the following documents:

15 **[0003]** US 5,288,420 discloses a stain removal composition provided in form of a solid stick, which can be applied to selected areas of a fabric in laundry preparations. Various compositions are disclosed comprising surfactants, enzymes and glycols. US 3,748,268 discloses a stain removal composition especially for carpets and upholstery comprising a surfactant for an aerosol formulation. EP 0 205 999 discloses the provision of a laundry preparation composition in the form of a solid stick. WO 85/00782 discloses a kit comprising coloured fluids and an eradicator for these
20 fluids, which can be used on various materials including clothing. DE 2422191 discloses a solution to be used on stains provided in an applicator with a felt insert. DE 19536714 discloses an applicator for a stain removal fluid which takes the form of a pen. WO 99/02769 discloses an impregnated towelette to clean stains from clothes and upholstery, comprising surfactant.

25 **[0004]** None of the above fabric treatment compositions comprises bleach. Moreover, these patents do not give details how the various applicators should be used.

[0005] Applicators comprising bleach are known in fields other than fabric treatment: US 5,324,131 discloses an applicator for a liquid bleaching agent to be used to eradicate or remove an emphasising ink. The applicator may be provided with a felt tip or roller. US 5,611,687 discloses an oral fluid, e.g. for the teeth or the gum, and an applicator for it comprising a broad fibre tip or a roller ball.

30 **[0006]** Prior art documents which address the application of the respective compositions in some detail include the following documents:

[0007] US 5,765,407 describes an on-the-spot stain removal kit, comprising four sponges, and teaches a four step stain removal procedure for satisfactory results.

35 **[0008]** US 5,122,158 discloses an applicator for an enzyme-containing liquid detergent for the application in laundry preparation. The applicator comprises a porous body made of a synthetic plastic material. The heat resulting from the friction produced by the applicator during application to a fabric is assumed to contribute to a more rapid enzymatic reaction.

[0009] Fabric treatment applicators which comprise bleach and surfactant are known from the following documents:

40 **[0010]** WO 97/20099 discloses an applicator for the post-laundry treatment of fabrics comprising bleach and surfactant. The applicator is designed for in-house use, in a preferred embodiment comprising an open channel for liquid delivery. A two step process is taught which involves the use of an iron on one side of the fabric and the use of an absorbent layer on the other side of the fabric. The application of heat and/or pressure by means of an iron is believed to affect the physical characteristics of the stained fabric, such as its viscosity.

45 **[0011]** US 5,872,090 discloses a stamp like applicator for a fabric treatment composition comprising bleach and surfactant, which is to be applied to a fabric in a rocking motion. The treatment is preferably done on a table top and preferably using an absorbent stain remover situated beneath the fabric and followed by a post treatment process in a hot air cloth dryer.

[0012] In view of the above prior art it remains a challenge to provide an efficient stain removal applicator, especially for convenient transport and immediate application to fresh stains, which is also suitable for some very delicate fabrics.

50 **[0013]** It is hence a main objective of the present invention to provide an applicator for a fabric treatment composition, which allows effective mechanical stain removal.

[0014] It is a further main objective of the present invention to provide an applicator for a fabric treatment composition, which can be successfully used on a large variety of stains and fabrics.

55 **[0015]** It is a further objective of the present invention to provide an applicator for a fabric treatment composition, which is easy to use.

[0016] It is another objective of the present invention to provide an applicator for a fabric treatment composition, which is convenient to store and to carry.

[0017] It is yet another objective of the present invention to provide an applicator for a fabric treatment composition,

which does not dry out when stored over extended periods of time.

[0018] It is yet a further objective of the present invention to provide an applicator for a fabric treatment composition, which allows single step application.

5 [0019] It is yet even a further objective of the present invention to provide an applicator for a fabric treatment composition, which has self cleaning properties.

[0020] It is still an additional objective of the present invention to provide an applicator for a fabric treatment composition, which does not leave residues even when no rinsing or other post treatment of the fabric is undertaken.

[0021] These and other objectives, as apparent from the following description, are addressed by the present invention.

10

Summary of the invention

[0022] The present invention relates to an applicator for a fabric treatment composition and its application. More specifically the invention relates to a versatile convenient to carry and to apply fabric treatment applicator. Claimed and described is an applicator comprising a nib (10) and further comprising a fabric treatment composition comprising bleach and surfactant.

15

Brief description of the drawings

20 [0023] It is believed that the invention will be better understood from the foregoing description in conjunction with the following drawings:

Figure 1 is a perspective view of a fabric treatment applicator according to the present invention.

25

Figure 2 is an enlarged view of the nib of the fabric treatment applicator according to Figure 1.

Detailed description of the invention

[0024] The present invention combines an advantageous fabric treatment applicator with an advantageous fabric treatment composition. According to the present invention the fabric treatment applicator comprises a nib (10). The preferred fabric treatment composition comprises bleach and surfactant.

30

[0025] It has now been found that superior fabric treatment and particularly stain removal can be achieved by effective mechanical stain removal in combination with effective chemical stain removal. According to the present invention effective mechanical stain removal is accomplished by the incorporation of a nib (10) into the fabric treatment applicator.

35

This allows the use of fabric friendly chemical compounds at low levels, thus making the present invention suitable also for delicate fabrics including silk.

[0026] In another aspect of the present invention the fabric treatment applicator has been found to have self cleaning properties. The nib (10) if present in a conventional fabric treatment applicator tends to acquire dirt and stain material stemming in particular from treated stains. Such stain material is potentially redeposited onto fabrics treated later.

40

As has now been found such stain material can be effectively removed and/or made less visible by incorporating a bleach into the fabric treatment composition. This largely improves the functioning, the aesthetic appearance and consumer acceptance of the fabric treatment applicator.

Preferred fabric treatment compositions

45

[0027] Fabric treatment compositions according to the present invention comprise a bleach and a surfactant. They may also comprise numerous other components as listed below. Importantly, the fabric treatment compositions are optimised to leave minimal residues.

50

[0028] One problem associated with known fabric treatment compositions hereinafter referred to as stain removal compositions is their tendency to leave visible residues on fabric surfaces. Such residues are problematic and are preferably to be avoided herein since the present process does not involve conventional immersion or rinse steps. Accordingly, the stain removal compositions herein should, most preferably, be substantially free of various polyacrylate-based emulsifiers, polymeric anti-static agents, inorganic builder salts and other residue-forming materials, except at low levels of 0.1% - 0.3%, and preferably 0%, of the final compositions (% as used herein, denotes % by weight of 100% active). Water used in the compositions should preferably be distilled, deionized or otherwise rendered free of residue-forming materials.

55

[0029] Accordingly, in a preferred aspect of this invention there are provided stain removal compositions which are substantially free of materials which leave visible residues on the treated fabrics. This necessarily means that the pre-

ferred stain removal compositions are formulated to contain a high level of volatile materials, preferably water, preferably 95%, a cleaning solvent such as BPP at a low, but effective, level, typically 1% to 4%, preferably 2%, hydrogen peroxide at a level from 1% to 3%, preferably 2%, and surfactant at levels of 0.1% to 1%. Advantageously, when thus formulated such compositions exist as phase-stable aqueous solutions rather than as suspensions or emulsions. Thus, such compositions do not require use of additional emulsifiers, thickening agents, suspending agents, and the like, all of which can contribute to the formation of undesirable visible residues on the fabric.

[0030] Indeed, as an overall proposition, the chemical compositions which are used to provide the stain removal and the overall cleaning and/or refreshment functions herein comprise ingredients which are safe and effective for their intended use, and, as noted above, do not leave unacceptable amounts of visible residues on the fabrics. While conventional laundry detergents are typically formulated to provide good cleaning on cotton and cotton/polyester blend fabrics, the compositions herein must be formulated to also safely and effectively clean and refresh fabrics such as wool, silk, rayon, rayon acetate, and the like. In addition, the compositions herein comprise ingredients which are specially selected and formulated to minimize dye removal or migration from the stain site of fugitive, unfixed dye from the fabrics being cleaned. The preferred compositions herein are formulated to minimize or avoid these problems.



[0031] The dye removal attributes of the present compositions can be compared with art-disclosed cleaners using photographic or photometric measurements, or by means of a simple, but effective, visual grading test, the dye removal test described below.

[0032] In addition to the foregoing considerations, the compositions used herein are preferably formulated such that they are easily dispensed and not so viscous or self-adhesive in nature that they render the stain removal applicator unhandy or difficult to use. Preferably the fabric treatment compositions described herein are formulated as liquid fabric treatment compositions. In one alternative they may be provided as a gel. A stain removal composition according to the present invention comprises:

(a) Bleach - The compositions herein comprise from 0.001% to 99.99%, preferably 0.001% to 7%, by weight, of bleach, preferably peroxide bleach, most preferably hydrogen peroxide. More preferred spot cleaners will comprise 0.5% to 3% hydrogen peroxide. It will be appreciated that peroxide sources other than H_2O_2 can be used herein. Thus, various per-acids, per-salts, per-bleaches and the like known from the detergency art can be used. However, such materials are expensive, difficult to formulate in liquid products, can leave residues on fabrics and offer no special advantages over H_2O_2 when used in the present manner.

(b) Surfactant - The compositions herein comprise from 0.001% to 99.99%, preferably 0.05% to 5%, more preferably 0.05% to 2% by weight of surfactants, such as ethoxylated alcohols or alkyl phenols, alkyl sulfates, NaAES, NH4AES, amine oxides, and mixtures thereof. As noted above, use of surfactants limited to the lower end of the range is preferred for some dyes and fabric types. Typically, the weight ratio of BPP solvent:surfactant(s) is in the range of from about 10:1 to about 1:1. One preferred composition comprises 2% BPP/0.8% AES. Also, nonionics such as the ethoxylated C10-C16 alcohols, e.g., NEODOL 23-6.5, can be used in the compositions. The alkyl sulfate surfactants which may be used herein as cleaners and to stabilize aqueous compositions are the C8-C18 primary ("AS"; preferred C10-C14, sodium salts), as well as branched-chain and random C10-C20 alkyl sulfates, and C10-C18 secondary (2,3) alkyl sulfates of the formula $CH_3(CH_2)_x(CHOSO_3-M^+)$ CH_3 and $CH_3(CH_2)_y(CHOSO_3-M^+)CH_2CH_3$ where x and (y + 1) are integers of at least 7, preferably at least 9, and M is a water-solubilizing cation, especially sodium, as well as unsaturated sulfates such as oleyl sulfate. Alkyl ethoxy sulfate (AES) surfactants used herein are conventionally depicted as having the formula $R(EO)_xSO_3Z$, wherein R is C10-C16 alkyl, EO is - CH_2CH_2-O- , x is 1-10 and can include mixtures which are conventionally reported as averages, e.g., (EO)2.5, (EO)6.5 and the like, and Z is a cation such as sodium ammonium or magnesium (MgAES). The C12-C16 alkyl dimethyl amine oxide surfactants can also be used.

(c) Solvent - The compositions herein may comprise from 0% to 99.99% preferably from 0% to 10% by weight, of butoxy propoxy propanol (BPP) solvent or other solvents as described herein. Organic solvents are preferred for use in the present compositions. Preferred spot cleaners will comprise 1 - 4% BPP which is available in commercial quantities as a mixture of isomers in about equal amounts. The isomers, and mixtures thereof, are useful herein. The isomer structures are as follows:



Other useful solvents are hydrotropes such as sodium toluene sulfonate and sodium cumene sulfonate, short-chain alcohols such as ethanol and isopropanol, and the like. They can be present in the compositions as only solvents or in combination with other solvents.

(d) Water - The preferred, low residue compositions herein may comprise from 0% to 99.99%, preferably from 70% to 99.99%, more preferably 90% to 99.9%, most preferably from 94.0% to 99.0%, by weight, of water and hence are preferably aqueous solutions. Water used in the compositions should preferably be distilled, deionized or otherwise rendered free of residue-forming materials.

(e) Other Optionals - The compositions herein may comprise minor amounts of various optional ingredients, including enzymes, preservatives, anti-static agents, fragrances, odor absorbing components, and the like. If used, such optional ingredients will typically comprise from 0.0001% to 10%, more preferably from 0.01% to 2%, by weight, of the compositions, having due regard for residues on the cleaned fabrics. Preferred optionals are namely the following:

Chelator -The chelating agent is selected from those which, themselves, are stable in aqueous H_2O_2 and which stabilize the H_2O_2 by chelating vagrant metal ions. Such chelating agents are typically already present at low, peroxide-stabilizing amounts (0.01%-1%) in commercial sources of hydrogen peroxide.

Enzymes - Besides the optional surfactants in the stain removal compositions herein can contain enzymes to further enhance cleaning performance. Lipases, amylases and protease enzymes, or mixtures thereof, can be used. If used, such enzymes will typically comprise from 0.001% to 5%, preferably from 0.01% to 1%, by weight, of the composition. Commercial detergent enzymes such as LIPOLASE, ESPERASE, ALCALASE, SAVINASE and TERMAMYL (all ex. NOVO) and MAXATASE and RAPIDASE (ex. International Bio-Synthesis, Inc.) can be used.

Preservatives - The compositions herein can optionally be preserved for storage using conventional preservatives such as KATHON[®] at a level of 0.0001%-1%, by weight.

Anti-static agents - If an antistatic benefit is desired, the compositions used herein can contain an anti-static agent. If used, such anti-static agents will typically comprise at least 0.5%, typically from 2% to 8%, by weight, of the compositions. Preferred anti-stats include the series of sulfonated polymers available as VERSAFLEX 157, 207, 1001, 2004 and 7000, from National Starch and Chemical Company

Fragrances - The odor absorbing composition of the present invention can also optionally provide a "scent signal" in the form of a pleasant odor which signals the removal of malodor from fabrics. The scent signal is designed to provide a fleeting perfume scent, and is not designed to be overwhelming or to be used as an odor masking ingredient. When perfume is added as a scent signal, it is added only at very low levels, e.g., from 0% to 0.5%, preferably from 0.003% to 0.3%, more preferably from 0.005% to 0.2%, by weight of the usage composition.

Perfume can also be added as a more intense odor in product and on surfaces. When stronger levels of perfume are preferred, relatively higher levels of perfume can be added. Any type of perfume can be incorporated into the composition of the present invention.

Odor absorbing components - The compositions of the present invention may further comprise an optional cyclodextrin. This will impart the composition with odour absorbing properties, which is especially useful for application on inanimate surfaces to control the malodour.

As used herein, the term "cyclodextrin" includes any of the known cyclodextrins such as unsubstituted cyclodextrins containing from six to twelve glucose units, especially, alpha-cyclodextrin, beta-cyclodextrin, gamma-cyclodextrin and/or their derivatives and/or mixtures thereof. The preferred cyclodextrins are available, e.g., from Cerestar USA, Inc. and Wacker Chemicals (USA), Inc.

Typical levels of cyclodextrin in usage compositions for usage conditions are from 0.01% to 5%, preferably from 0.1% to 4%, more preferably from 0.2% to 2% by weight of the composition.

[0033] The preselected pH range of the stain removal compositions assists in stabilising the hydrogen peroxide present and is typically in the acid-slightly basic range from about 3 to about 8, preferably about 6.

[0034] A stain removal composition comprising water, surfactant and bleach is efficient in treating a large variety of stains. It is known that various greasy stains are best treated with a surfactant whereas other common stains as from grass, tomato sauce or wine are best treated with bleach, while water soluble stains can normally effectively removed with water.

[0035] While referring to stain removal compositions, the compositions disclosed herein may also favourably be used in other contexts, for example for bleaching and/or sanitation of non-stained fabrics.

Examples of stain removal compositions

[0036] Having due regard to the foregoing considerations, the following illustrates preferred examples of stain removal compositions, but is not intended to be limiting thereof.

Example 1

[0037]

	% (wt) of 100% active component formula range
BPP	1.0-2.0
Hydrogen peroxide	1.5-3.0
Alkyl sulfate surfactant	0.3-1.0
Perfume	0.005-0.01
Ethanol	0.3-1.0
EDTA	<0.01
Water	Balance

Example 2

[0038]

	% (wt) of 100% active component formula range
BPP	1.0-2.0
Hydrogen peroxide	1.5-3.0

(continued)

	% (wt) of 100% active component formula range
LIPOLASE	0.3-0.5
Alkyl sulfate surfactant	0.3-1.0
Perfume	0.005-0.01
Ethanol	0.3-1.0
EDTA	<0.01
Water	Balance

Applicators

[0039] Generally any applicator comprising a nib (10) is within the scope of the present invention. The choice of a particular applicator will largely depend on the usage envisaged. One preferred applicator is shown in Figures 1 and 2.

[0040] Such applicators comprise a housing (30) comprising a reservoir for the storage of a composition. Such a housing (30) may be a bottle of any shape or size. Preferred shapes for such housings (30) are hollow barrel shapes, most preferably having a diameter to length ratio from 1:30 to 1:2, so as to be convenient to hold in the user's hand, use and store. More preferred are housings (30) of a diameter to length ratio from 1:20 to 1:5, which resemble in shape a pen, e.g. a ball point pen or a highlighter pen, and which are herein referred to as pen-shaped. The reservoir may be filled with an absorbent material, such as a wadding or a cartridge style device such as those commonly found in ink pens which is able to release liquid on demand. The housing (30) may be made of any solid material, which may also be flexible, such as glass or any plastic material. A preferred material is polypropylene.

[0041] The housing (30) may have one or more application devices. The term application device, as used herein, is a device which in use is in contact with the surface on which the fabric treatment applicator is used and delivers the fabric treatment composition to that surface. According to the present invention at least one application device is a nib (10). Other preferred application devices include any sponge, or foam insert, for example in the form of a porous pad, for example made of felt or a non-woven material. Another preferred application device is a roller ball. Other preferred application devices are all those used to apply a writing fluid to paper, e.g. as used in a fountain pen. Applicators comprising no application device other than a nib are preferred.

[0042] In other applicator embodiments according to the present invention the housing may comprise more than one reservoir, preferably two, three or four reservoirs. Not all of these reservoirs need to comprise fabric treatment compositions which comprise a bleach and a surfactant. For example one reservoir may comprise a bleach or another heat-activatable compound and another reservoir may comprise a surfactant. Preferably the reservoir comprising a bleach does not comprise a surfactant and the reservoir comprising a surfactant does not comprise a bleach. Further reservoirs, if present, may comprise other fabric treatment compositions known in the art.

[0043] While each reservoir may be an integral part of the housing (30), in one preferred embodiment of the present invention the reservoirs are provided in the form of replaceable cartridges.

[0044] An applicator comprising such a plurality of reservoirs may comprise a single application device or a plurality of application devices. A plurality of reservoirs may be in liquid communication with a single application device and a plurality of reservoirs may each be in liquid communication with a single application device.

[0045] One preferred embodiment of the present invention is an applicator with two reservoirs and one application device. One of these reservoirs comprises a fabric treatment composition comprising bleach and the other reservoir comprises a fabric treatment composition comprising a surfactant but no bleach. Both are in liquid communication with the same application device, e.g. a nib (10).

[0046] Another preferred embodiment of the present invention is an applicator with two reservoirs and two application devices. One of these reservoirs comprises a fabric treatment composition comprising bleach and the other reservoir comprises a fabric treatment composition comprising a surfactant and no bleach.

[0047] Each of the two reservoirs is in liquid communication with one of the two application devices. This allows to use the applicator selectively on different types of stains, but makes it unnecessary to carry more than one applicator.

[0048] The term nib (10) as used according to the present invention does not comprise nibs (10) which comprise a single opening or channel to deliver the fabric treatment composition. Such an opening or channel does not allow the delivery of the fabric treatment composition in a controlled manner as a nib (10). Hence, either insufficient composition will be delivered for effective cleaning or unnecessary large amounts of composition may be delivered, the latter leading

to longer drying times for the treated fabric or in some cases possibly even to residues. Moreover, an opening or channel leading to the reservoir promotes the evaporation of volatile compounds of the composition stored therein and may further induce leaking when the fabric treatment applicator is transported. The same disadvantages are associated with a porous application device, e.g. a porous pad. Hence, a nib (10) in accordance with the present invention has an average pore size of less than 300 μm . Preferably pores which may be present in the nib (10) according to the present invention have an average size from 1 μm to 200 μm , more preferably from 5 μm to 100 μm , more preferably from 10 μm to 50 μm .

[0049] Preferably the nib (10) is cone-shaped as defined below. A cone-shaped nib (10) allows the exertion of pressure on a relatively narrow area, which is beneficial for mechanical stain removal, without leading to damage of the nib (10), which is thicker and hence more stable closer to the housing (30). A cone-shaped nib (10) also enables the application of the fabric treatment composition to a small selected area as beneficial for low moistening of the fabric and low residues.

[0050] The term cone-shaped as used with regard to the nib (10) is to be understood from the following definitions: The centre of the contact area, defined as given below, is referred to as contact point. A line connecting this contact point with the centre of mass of the fabric treatment applicator defines a vertical axis. A horizontal cross section is a cross section along any plane perpendicular to the vertical axis. The horizontal cross section of the nib (10) which is closest to the housing (30), but does not comprise any portion of the housing (30) is referred to as rod cross section. The surface area of the nib (10) in the rod cross section, referred to as rod area, is to be compared with the contact area of the nib (10). A nib (10) is cone-shaped if the contact area of the nib (10) is less than 80% of the rod area. For a preferred nib (10) the rod area is less than 60%, more preferably less than 40%, yet more preferably less than 20% of the rod area. The nib (10) may have any shape, cone style or 'wedge shape' being preferred for the nib (10). A particular preferred cone-shaped nib (10) is wedge-shaped, as depicted in Figure 2.

[0051] The nib (10) and any other application device should be in contact with the reservoir, directly or indirectly, so as to allow transfer of the fabric treatment composition to the nib (10) during use. The nib (10) may be made of any synthetic or man-made or natural materials such as felt, open cell foam, closed cell foams, polyethylene, nylon etc. A preferred material for the nib (10) is felt, most preferably provided from synthetic fibres. The nib (10) while being held by the housing (30) has a section external to the housing (30), this section preferably measures from 3.0 cm to 0.1 cm, more preferably from 1.0 cm to 0.25 cm, most preferably from 0.75 cm to 0.5 cm in length. Preferably the maximum diameter measured in the rod cross section of the nib (10) (as defined above) is from 1 mm to 20 mm, more preferably from 3 mm to 10 mm, most preferably from 5 mm to 8 mm.

[0052] The contact area - measured as given below - between the nib (10) and a flat surface preferably is from 0.25mm² to 400mm², more preferably from 1mm² to 100mm², most preferably from 4mm² to 10mm². Such a contact area ensures optimal mechanical stain removal and allows for application of the fabric treatment composition to small selected areas.

[0053] Preferred application devices according to the present invention also exhibit a certain delivery volume efficiency - measured as described below. The delivery volume efficiency is defined as the amount of fluid (ml) delivered to the fabric per unit time per unit area ($\text{s}^{-1}\text{mm}^{-2}$). The right delivery volume efficiency ensures that a sufficient but not too high amount of fabric treatment composition is delivered giving the benefits of a sufficient and constant flow rate and further the benefit of avoiding drying out of the nib (10) or the reservoir in between uses. The delivery volume efficiency is preferably from 0.0005 ml mm⁻² s⁻¹ to 0.1 ml mm⁻² s⁻¹ and more preferably from 0.001 ml mm⁻² s⁻¹ to 0.01 ml mm⁻² s⁻¹.

[0054] The applicator may also comprise a cap (20) to prevent evaporation of the composition and to prevent any unattended contact of the nib (10) with objects when not used.

[0055] Figure 1 shows an applicator (100) with a pen-shaped housing (30) comprising a cap (20). As best seen from Figure 2 the nib (10) has a preferred wedge shape.

Preferred methods of application

[0056] The compositions disclosed herein may find usage on any surface of a material in direct or indirect contact with the human body, which inter alia are all encompassed by the term fabric. Those surfaces are typically soft surfaces comprised by materials such as soft plastic materials, leather and textile fabrics. Textile fabrics namely are found in clothing, including shirts, ties, blouses, socks, skirts, trousers, jackets, underwear, watch straps etc.

[0057] Moreover these compositions can be used on fabrics comprised by carpets, curtains or upholstery and the like.

[0058] The use of any applicator with any composition disclosed herein will depend on the applicator itself and also on the object on which the applicator is to be used.

[0059] For a fabric treatment applicator as shown in Figure 1 comprising a housing (30) and an application device a cap (20) covering the application device, if present, is removed before application. The application device is then

brought in contact with a selected area of an object. For some application devices exertion of pressure may be needed to release the composition from the applicator. The pressure initially needed for this purpose may be higher than the pressure needed to keep up the flow of composition. Wiping or otherwise moving the application device over the selected application area may be required to deliver the composition to all parts of this area and may help to uniformly apply the composition. Rubbing, i.e. wiping while exerting pressure towards the object, may help in the mechanical removal of stains.

[0060] The application of any composition disclosed herein, may be one step of a more comprehensive treatment of an object, namely a fabric. For example, the application of a stain removal composition may be followed by the application of a pre-laundry composition, by laundry, or may be followed by a rinsing or drying step. A rinsing step may be carried out with a dedicated rinsing composition such as alcohol, glycol or pure water. However, due to the water content of the composition of the present invention such an additional rinsing step is normally not needed. A drying step may be a treatment with a dry or slightly moist wipe or an absorbent pad. However, a drying step is normally not needed, since the compositions disclosed herein promote quick drying and the applicators disclosed herein allow application to small areas.

Test Methods

Dye removal test

[0061] An expert panel assists in visual grading. Thus, in one such test, swatches of fabric are individually dyed with a dye from a representative dye category such as from reactive dyes, sulphur dyes, vat dyes, direct dyes and azoic dyes. A swatch of fabric is prepared with a dye from each category. A measured area within each swatch is treated with the fabric treatment composition and allowed to dry. Any dye removal in the treated swatch is assessed visually by comparing the treated area of the swatch with the surrounding untreated area of the swatch. Numerical units ranging from: (0) 'no difference between both fabrics', (1) 'I think there is a difference', (2) 'I'm sure there is a difference', (3) 'there is a big difference', (4) 'there is a huge difference' are assigned by panelists. The test is repeated three times of any swatch and an average value is calculated.

Measurement of contact area

[0062] Measurements of the contact area of the nib (10) are carried out with a fabric treatment applicator which contains a dry nib (10) and no treatment composition. The dry nib (10) is inked by pressing it against an ink stamp pad and then clamping the fabric treatment applicator to the load arm of a Plint dual axis reciprocating rig (such as model TE75R, MRPRA RUBBER CONSULTANTS). A mark on a contact surface which is representative of the contact area of the nib (10) is obtained by controlled lowering and raising of the Plint load arm towards and away from the contact surface. The angle of the fabric treatment applicator relative to the contact surface is adapted to maximise the contact area. Angles of the fabric treatment applicator relative to the contact surface for which the angle between the vertical axis of the fabric treatment applicator (as defined above) and the contact surface less than 45° are not considered (since they are not typical for a consumer preferred application method). The contact time should be approximately 1s while a 3N load should be applied on the nip (10). The contact area can then be calculated from the mean length and width of the mark determined using a magnifying lens with a graticule. Measurements with the nib (10) in final measuring position are repeated three times to check reproducibility.

Measurement of Delivery Volume Efficiency

[0063] The nib (10) is firmly inserted through the bottom of a standard liquid container (such as a 50ml centrifuge tube available from Corning No. 25330-50). To ensure a secure arrangement, the size of the orifice through which the nib (10) is inserted is cut to the size of the nib (10) and a silicone based sealant used. This unit is then clamped into position beneath a compressor unit (such as a Lloyd LR5K Compression meter). This arrangement provides a consumer realistic vertical load of 3N. The nib (10) is placed in contact with an absorbent pad comprised of a bicomponent synthetic fibre top layer above a fluffy pulp base layer. The pad allows rapid transport away from the point of delivery so as not to reduce the concentration gradient and hence reduce flow. The container is then filled with the stain removing solution (such as Example 1) to a level of 20 ml. The amount of fluid that flows per unit time is measured by noting the loss of fluid from the reservoir over a fixed period. The delivery volume efficiency is then calculated by normalising the flow rate with respect to the total surface area of contact (mm²) between the nib (10) and the fabric. Measurements are repeated three times to check reproducibility.

Claims

- 5
1. A fabric treatment applicator comprising a housing (30) and an application device comprising a nib (10), said housing (30) comprising a fabric treatment composition, said fabric treatment composition comprising at least one bleach and at least one surfactant.
 2. A fabric treatment applicator according to Claim 1, wherein said bleach comprises a peroxide bleach.
 - 10 3. A fabric treatment applicator according to any one of the preceding claims, wherein said fabric treatment composition comprises butoxy propoxy propanol or alkyl ethoxy sulfate or a mixture of both.
 4. A fabric treatment applicator according to any one of the preceding claims wherein said fabric treatment composition further comprises at least 70% of water.
 - 15 5. A fabric treatment applicator according to any one of the preceding claims wherein said fabric treatment composition comprises from 0.5% to 3% bleach and from 0.05% to 2% surfactant
 6. An fabric treatment applicator according to any one of the preceding claims, wherein said nib (10) comprises synthetic fibres.
 - 20 7. An fabric treatment applicator according to any one of the preceding claims, wherein said nib (10) is cone-shaped.
 8. An fabric treatment applicator according to any one of the preceding claims, wherein said nib (10) comprises pores having a pore size of from 1 μm to 200 μm .
 - 25 9. An fabric treatment applicator according to any one of the preceding claims, wherein said housing (30) is pen-shaped.
 - 30 10. A fabric treatment applicator comprising a housing (30), the housing (30) comprising at least two reservoirs and at least one application device, each of said reservoirs being in liquid communication with at least one application device, characterised in that at least one of said reservoirs comprises a bleach and at least one of said reservoirs comprises a surfactant.
 - 35 11. A fabric treatment applicator according to Claim 10, comprising at least two application devices, characterised in that each of said reservoirs is in liquid communication with one application device.
- 40
- 45
- 50
- 55



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 11 1978

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 157 653 A (PUREX CORPORATION) 9 October 1985 (1985-10-09) * page 19, line 25 - page 20, line 9 * * figures * * page 16, line 3 - page 18, line 13 * ---	1-6	C11D17/04 A47L25/00 A45D34/04
A	US 5 122 158 A (KURODA ET. AL.) 16 June 1992 (1992-06-16) * column 1, line 43 - column 2, line 3 * * figures * ---	1,7-9	
A	WO 99 29590 A (MINNESOTA MINING & MFG) 17 June 1999 (1999-06-17) * abstract; figures * ---	1,10	
A	US 5 662 827 A (STEIGER ET. AL.) 2 September 1997 (1997-09-02) * column 4, line 26 - column 5, line 9 * ---	1-4	
A	EP 0 266 200 A (UNILEVER PLC) 4 May 1988 (1988-05-04) * abstract; examples * ---	1-3	
D,A	WO 99 02769 A (S.C. JOHNSON & SON, INC.) 21 January 1999 (1999-01-21) * page 2, line 24 - page 6, line 11 * ---	1,3,4	
D,A	DE 195 36 714 A (J. BOCK) 3 April 1997 (1997-04-03) * the whole document * ---	1	
P,A	WO 99 57028 A (YUGEN KAISHA SANSEI KOGYO ;OTSUKA KATSUMI (JP); KARISU INTERNATION) 11 November 1999 (1999-11-11) * abstract; figures * ---	1	
-/--			
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
THE HAGUE		6 November 2000	Ketterer, M
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone		T : theory or principle underlying the invention	
Y : particularly relevant if combined with another document of the same category		E : earlier patent document, but published on, or after the filing date	
A : technological background		D : document cited in the application	
O : non-written disclosure		L : document cited for other reasons	
P : intermediate document		& : member of the same patent family, corresponding document	

EPO FORM 1509 08.02 (P/4C01)



European Patent Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 11 1978

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
P,A	EP 0 949 325 A (PROCTER & GAMBLE) 13 October 1999 (1999-10-13) * claims *	1	
A	US 5 765 407 A (CHOO ET. AL.) 16 June 1998 (1998-06-16) * the whole document *	1,7-9	
A	DATABASE WPI Week 9826 Derwent Publications Ltd., London, GB; AN 1998-290466'26! XP002126705 T. NORIHIRO ET. AL.: "Detergent, bleach liquid applicator for cleaning stains in clothes" & JP 10 099769 A (LION CORP.), 21 April 1998 (1998-04-21) * abstract *	1,6	
A	WO 98 57544 A (FOX RODNEY THOMAS ;HARRISON NEALE MARK (GB); THACKER SIMON (GB); G) 23 December 1998 (1998-12-23) * page 3, line 16 - line 26 *	1,10,11	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	US 5 611 687 A (WAGNER) 18 March 1997 (1997-03-18) * the whole document *	1,7-9	
A	EP 0 318 470 A (WARWICK INTERNATIONAL LTD.) 31 May 1989 (1989-05-31) * the whole document *	1,2	
A	US 5 872 090 A (YOU ET.AL.) 16 February 1999 (1999-02-16) * claim 1; figures *	1-5	
-/--			
The present search report has been drawn up for all claims			
Place of search	Date of completion of the search	Examiner	
THE HAGUE	6 November 2000	Ketterer, M	
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		& : member of the same patent family, corresponding document	

EPO FORM 1500 03.82 (P04C01)



European Patent Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 11 1978

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
D,A	US 5 324 131 A (GARDNER, III) 28 June 1994 (1994-06-28) * abstract; figures * ---	7-9	
D,A	DE 24 22 191 A (W. SCHLÜTER) 27 November 1975 (1975-11-27) * the whole document * -----	1,7-9	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search	Date of completion of the search	Examiner	
THE HAGUE	6 November 2000	Ketterer, M	
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention	
X : particularly relevant if taken alone		E : earlier patent document, but published on, or after the filing date	
Y : particularly relevant if combined with another document of the same category		D : document cited in the application	
A : technological background		L : document cited for other reasons	
O : non-written disclosure		
P : intermediate document		& : member of the same patent family, corresponding document	

EPO FORM 1503 03.02 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 11 1978

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-11-2000

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 157653	A	09-10-1985	US 4563186	A 07-01-1986
			AU 4071585	A 10-10-1985
			JP 61000166	A 06-01-1986
			US 4636328	A 13-01-1987
			US 4720351	A 19-01-1988
US 5122158	A	16-06-1992	JP 1599269	C 31-01-1991
			JP 58012697	A 24-01-1983
			JP 62016671	B 14-04-1987
			AU 562240	B 04-06-1987
			AU 8606182	A 20-01-1983
			CA 1177765	A 13-11-1984
WO 9929590	A	17-06-1999	US 5954230	A 21-09-1999
			AU 7475198	A 28-06-1999
			EP 1040053	A 04-10-2000
US 5662827	A	02-09-1997	US 5399746	A 21-03-1995
			AU 2791095	A 21-08-1995
			BR 9505773	A 27-02-1996
			EP 0694028	A 31-01-1996
			JP 8511560	T 03-12-1996
			WO 9521150	A 10-08-1995
			US 5705681	A 06-01-1998
			ZA 9500972	A 25-10-1995
EP 266200	A	04-05-1988	US 4911860	A 27-03-1990
WO 9902769	A	21-01-1999	US 5895504	A 20-04-1999
			AU 8479698	A 08-02-1999
			EP 0994977	A 26-04-2000
			ZA 9806042	A 28-01-1999
DE 19536714	A	03-04-1997	NONE	
WO 9957028	A	11-11-1999	NONE	
EP 0949325	A	13-10-1999	AU 2850599	A 01-11-1999
			AU 2951099	A 01-11-1999
			EP 0949326	A 13-10-1999
			EP 0988362	A 29-03-2000
			WO 9953006	A 21-10-1999
			WO 9953007	A 21-10-1999
US 5765407	A	16-06-1998	WO 9950494	A 07-10-1999

EPO FORM P0469

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 11 1978

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-11-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 10099769 A	21-04-1998	NONE	
WO 9857544 A	23-12-1998	AU 8026098 A GB 2326340 A ZA 9805228 A	04-01-1999 23-12-1998 04-03-1999
US 5611687 A	18-03-1997	NONE	
EP 318470 A	31-05-1989	AU 1889788 A EP 0301722 A	12-01-1989 01-02-1989
US 5872090 A	16-02-1999	BR 9712669 A EP 0937129 A JP 2000504371 T WO 9817771 A	19-10-1999 25-08-1999 11-04-2000 30-04-1998
US 5324131 A	28-06-1994	US 5427278 A	27-06-1995
DE 2422191 A	27-11-1975	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82