

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 076 088 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

14.02.2001 Bulletin 2001/07

(51) Int Cl.7: **C11D 3/16**, C11D 3/04,

C11D 3/10, C11D 1/38

// C11D1:62

(21) Application number: **99119749.2**

(22) Date of filing: **06.10.1999**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: **07.08.1999 KR 9932449**

(71) Applicant: **Dow Corning Taiwan, Ltd.
Taipei (TW)**


(72) Inventors:

- **Mei, Wang Ping**
Chung-Ho, Taipei, R.O.C. (TW)
- **Wu, Peter S.**
Chungli, R.O.C. (TW)
- **Chiang, Samuel N.**
Singapore (SG)

(74) Representative: **Patentanwälte
Ruff, Beier und Partner
Willy-Brandt-Strasse 28
70173 Stuttgart (DE)**

(54) **Process for cleaning textile**

(57) This invention relates to a process for cleaning textiles, which comprises applying a composition comprising a low molecular weight linear siloxane represented by the formula:



wherein n is an integer from 1 to 7, and a cationic surfactant to stained textiles and heating it in the presence of an inorganic base compound at a temperature below which the textiles are deteriorated.

EP 1 076 088 A1

DescriptionFIELD OF THE INVENTION

[0001] The present invention relates to a process for cleaning textiles, especially for removal of any oily and /or greasy stains from textiles and for removal of silicones retained on textiles.

BACKGROUND OF THE INVENTION

[0002] Historically, any oily/greasy stains have been removed from textiles by various manners for cleaning purposes. On the other hand, silicone fluids have been used as textile treating agents to impart smoothness, softness, and the like. However, the presence of such silicone treating agents on textiles adversely affects re-dyeing of the textiles, so they must be removed before re-dyeing. Therefore, a product referred to as a "stripping agent", produced by the combination of cationic surfactants, is commercially available but is not entirely satisfactory, especially for aminosilicone textile treating agents.

[0003] A low molecular weight siloxane known as "volatile siloxane" has been used for cleaning a substrate including textile. It is often used in combination with a surfactant. These are disclosed in the following patents which are incorporated herein by reference. The cyclic siloxanes employed in these prior art patents do not work in the present invention.


[0004] US 4,654,041 discloses a process for removing silicone from fibers, yarns or two-dimensional textile materials by the action of aqueous preparations, which may contain surfactive equilibration catalyst for organosiloxanes, and optionally detergents, wetting agents and alkali carbonates.

[0005] US 4,685,930 discloses a method for cleaning textiles which comprises applying a liquid composition consisting essentially of a cyclic siloxane and surfactant such as anionic, non-ionic, zwitterionic or ampholytic surfactant to a textile soiled with oil, grease or sebum, and removing from the textile a combination comprising cyclic siloxane and oil, grease or sebum.

[0006] DE 3739711A1 discloses a cleaning agent comprising cyclosiloxane and an anionic, cationic and/or ionic surfactant, which is used for cleaning fabrics.

SUMMARY OF THE INVENTION

[0007] The present invention relates to a process for cleaning textiles, which comprises applying a composition comprising a low molecular weight linear siloxane represented by the formula:




wherein n is an integer from 1 to 7, and a cationic surfactant to stained textiles in the presence of an inorganic base compound and heating the textiles at a temperature below which the textiles are deteriorated.

[0008] The method of the present invention can remove any oily and/or greasy stains from textiles and silicones retained on textiles.


DETAILED DESCRIPTION OF THE INVENTION

[0009] The process of the present invention for cleaning textiles comprises applying a composition comprising a low molecular weight linear siloxane represented by the formula:



wherein n is an integer from 1 to 7, and a cationic surfactant to stained textiles and heating the textiles in the presence of an inorganic base compound at a temperature below which the textiles are deteriorated.

[0010] The low molecular weight linear siloxanes of the present invention represented by the formula



wherein n is an integer from 1 to 7, are well known in the art. The siloxanes suitable for the invention should have

viscosity less than about 5cs. The siloxanes having more than about 5 cs. cannot be employed in the present invention. Preferred siloxanes include dimers, trimers and tetramers. As shown in the comparative example, a cyclic siloxane cannot be used in this invention. The silicone stains would become swelled after absorbing the siloxanes of this invention and easier to be cut into small fragments by strong bases carried by the cationic surfactants, and the fragments can be dissolved in the siloxane fluid. When the low molecular weight siloxane is applied together with a cationic surfactant and a base, it can promote the "cutting" efficiency because it can behave as a solvent to swell silicone and allow hydroxy ion to penetrate into the inner part of an oil spot more easily.

[0011] The cationic surfactant employed in the present invention can be a quaternary ammonium salt. Preferably, it can be selected from the group consisting of trialkylmethylammonium salts, dialkyldimethylammonium salts and mixtures thereof. The quaternary ammonium salts wherein the alkyl radical contains from 8 or less to 16 or more carbon atoms and the salt is chloride or bromide, are commercially available. Trilaurylmethyl ammonium chloride and dicyldimethylammonium chloride are most preferable. These ammonium salts are used individually or as mixtures thereof or in combination with other ammonium salts such as alkylbenzyldimethylammonium salts. Cationic surfactants alone can neutralize the negative charges on fabric surfaces and enable strong bases closing to and reacting with silicone oil spots (cutting polysiloxanes into small fragments) to remove them from fabric surfaces. The base is a real silicone stripper and the cationic surfactant is an auxiliary which helps the base penetrate more easily.

[0012] The base compounds suitable for the present invention depend on the materials of textiles. Preferred inorganic base compounds of the present invention are NaOH, KOH, Na_2CO_3 , NaHCO_3 and the like. Depending on the materials of textiles, for example, NaOH is good for cotton fabrics but not for wools. Na_2CO_3 or NaHCO_3 is preferred for wools.

[0013] The composition of the present invention can further comprise other ingredients. For example, a non-ionic surfactant may be added to the composition, which is used to stabilize the composition of the present invention. Since the composition is generally added to an aqueous system, it is preferably used in form of an emulsion. Persons skilled in the art know that any non-ionic surfactant is useful to meet this requirement. In addition, biocides can be used as preservatives for emulsions.

[0014] The proportions of the components are not critical to the composition of the present invention. However, generally, the ratio of the low molecular weight linear siloxane to the cationic surfactant is in the range of from about 1:25 to 25:1. The ratio of the sum of the low molecular weight linear siloxane plus the cationic surfactant to the base compound (on the basis of effective ingredient) is in the range of from about 16:1 to 16:20.

[0015] The order of addition of the components is not critical. It is preferred to previously produce a cleaning composition comprising the low molecular weight linear siloxane and cationic surfactants in the form of an aqueous emulsion, and add the cleaning composition and the inorganic base to a cleaning bath where water and a stained textile are loaded in, and then heat the cleaning bath at a temperature above the room temperature. The upper limit of the temperature may be the temperature under which the textile can be exposed without thermal deterioration. The temperature varies depending on the length of heating time. For example, the temperature is preferably from about 80 to 100 degrees C, and the time is preferably from about 30 minutes to 3 hours. The lower temperature can be used, but more time will be needed. After the cleaning treatment, the textile may be neutralized with a weak acid such as acetic acid.

[0016] The efficacy of the process of the invention is further illustrated by the following examples which are provided for illustration but not for limitation of the scope of the invention.

EXAMPLES

(A) The following examples demonstrate the removal of oil spots from textiles by the process of the invention.

[0017] Various cleaning compositions were prepared by mixing the cationic surfactants and the non-ionic surfactants with water and then adding a low molecular weight siloxane to the composition under stirring. The quantities (unit: grams) of the components are described in Table 1.

TABLE I

<u>Components</u>	<u>Composition</u>								
	I	II	III	IV	V	VI	VII	VIII	IX
Siloxane (1)	-	-	-	-	-	-	-	-	-
Siloxane (2)	0.66	0.66	0.66	0.66	0.86	0.26	0.63	0.66	0.63
Siloxane (3)	-	-	-	-	-	-	-	-	-
Cationic Surfactant(a)	0.19	-	0.095	0.06	0.03	0.12	0.06	0.06	0.16
Cationic Surfactant(b)	-	0.19	0.095	0.03	0.02	0.06	0.03	0.03	0.03
Cationic Surfactant(c)	-	-	-	0.1	0.05	0.2	0.1	0.1	-
Cationic Surfactant(d)	-	-	-	-	-	-	-	-	-
Non-Ionic Surfactants(1)	0.06	0.06	0.06	0.06	0.08	0.02	0.01	0.05	-
Non-Ionic Surfactants(2)	0.31	0.31	0.31	0.31	0.15	0.62	0.31	-	-
Non-Ionic Surfactants (3)	0.103	0.103	0.103	0.103	0.15	0.006	0.003	0.1	-
Water	0.49	0.49	0.49	0.49	0.5	0.48	0.24	0.813	0.563
Original Solvents	0.187	0.187	0.187	0.187	0.16	0.234	0.117	0.187	0.117
TOTAL	2	2	2	2	2	2	1.5	2	1.5

TABLE 1 (Continued)

Components	Composition									
	X	XI	XII	XIII	XIV	XV	XVI	XVII		
Siloxane (1)	0.62	-	-	-	-	-	-	-		
Siloxane (2)	-	0.63	0.66	0.66	0.66	1.06	-	-		
Siloxane (3)	-	-	-	-	-	-	-	0.62		
Cationic Surfactant(a)	0.06	0.06	-	-	-	-	0.12	0.06		
Cationic Surfactant(b)	0.03	0.03	-	-	0.095	-	0.06	0.03		
Cationic Surfactant(c)	0.1	0.1	0.19	-	0.095	-	0.2	0.1		
Cationic Surfactant(d)	-	-	-	0.19	-	-	-	-		
Non-Ionic Surfactants(1)	0.01	-	0.06	0.06	0.06	0.1	0.02	0.01		
Non-Ionic Surfactants(2)	0.31	-	0.31	0.31	0.31	-	0.62	0.31		
Non-Ionic Surfactants (3)	0.003	-	0.103	0.103	0.103	0.2	0.006	0.003		
Water	0.37	0.563	0.49	0.49	0.49	0.5	0.74	0.37		
Original Solvents	0.117	0.117	0.187	0.187	0.187	0.14	0.234	0.117		
TOTAL	1.62	1.5	2	2	2	2	2	1.62		

TABLE 1 (Continued)

Siloxane (1)	Hexamethyldisiloxane (0.65 cs)
Siloxane (2)	Decamethyltetrasiloxane (1.5 cs)
Siloxane (3)	Cyclic octamethyltetrasiloxane
Cationic Surfactant (a)	Trilauryltrimethylammonium chloride
Cationic Surfactant (b)	Didecyltrimethylammonium chloride
Cationic Surfactant (c)	Alkylbenzyltrimethylammonium chloride
Cationic Surfactant (d)	Cetyl trimethyl ammonium chloride
Non-ionic Surfactants (1)	2,6,8-trimethyl-4-nonyloxypolyethylene-oxyethanol
Non-ionic Surfactants (2)	alpha-(C ₁₂ -C ₁₅ sec-alkyl)omega-hydroxy poly(oxyethylene)
Non-ionic Surfactants (3)	alpha-(C ₁₂ -C ₁₄ sec-alkyl)omega-hydroxy poly-(xyethylene)
Organic solvents:	Isopropanol or ethylene glycol and unknown solvent residue of the surfactants.

[0018] On a piece (6 grams) of cotton textile to be tested containing 0.2 percent by weight (by weight of fabric) of silicone softener (polydimethylmethyl(aminoethylamino-isobutyl)siloxane with viscosity of 1,500 cs.), 0.1 gram of the same silicone softener was spread to form an oil circle.

[0019] In a cleaning vessel 80 grams of water was loaded first. Then the stained textile, the cleaning composition and 0.2 grams of 50% NaOH were loaded, and stirred for 60 minutes at a temperature of 90 degrees C. The cleaning solution was drained off, the textile was rinsed with water, and 0.093 grams of 60% acetic acid was added to neutralize the textile. The textile was again rinsed with water and dried at a temperature of 180 degrees C. for two minutes.

[0020] After drying, the cleaned textiles were observed by dropping water. When the oil spot was completely removed, it was rated as 5, and when the oil spot was not removed, it was rated as 0. The results are as shown in Table 2.

TABLE 2

Working Examples	Cleaning Compositions	Cleaning Rated
Working Example 1	Composition 1	5
Working Example 2	Composition II	3
Working Example 3	Composition III	5
Working Example 4	Composition IV	5
Working Example 5	Composition V	5
Working Example 6	Composition VI	3
Working Example 7	Composition VII	5
Working Example 8	Composition VIII	5
Working Example 9	Composition IX	4
Working Example 10	Composition X	5
Working Example 11	Composition XI	3
Comparative Example 1	Composition XII	1
Comparative Example 2	Composition XIII	1
Comparative Example 3	Composition XIV	2
Comparative Example 4	Composition XV	0-1
Comparative Example 5	Composition XVI	1
Comparative Example 6	Composition XVII	0-1

[0021] It is apparent that the process of the invention is more effective to remove the oil spot from the textile than the known process.

(B) The following examples demonstrate the removal of silicone retained onto the textiles by the process of the invention (for a re-dyeing process).

[0022] 0.3 grams of a cleaning composition in the form of an emulsion was prepared by mixing the cationic surfactants (Cationic Surfactant (a) 0.018 grams; Cationic Surfactant (b) 0.009 grams; Cationic Surfactant (c) 0.030 grams) and the non-ionic surfactants (Non-ionic Surfactant (1) 0.003 grams; Non-ionic Surfactant (2) 0.093 grams; Non-ionic Surfactant (3) 0.001 gram) with 0.072 grams of water and 0.035 grams of miscellaneous organic solvent and then adding the low molecular weight siloxane (Siloxane (2) 0.039 grams) to the composition under stirring.


[0023] Onto a piece (6 grams) of dyed cotton textile to be tested, 0.2 percent by weight (by weight of fabric) of silicone softener (polydimethylmethyl (aminoethylamino-isobutyl)siloxane with viscosity of 1,500 cs.) was treated.

[0024] In a cleaning vessel 80 grams of water was loaded first. Then the dyed textile treated with the softener, 0.3 grams of the cleaning composition and 0.03 grams of 50% NaOH were loaded, and stirred for 60 minutes at a temperature of 90 degrees C. The cleaning solution was drained off and the textile was rinsed with water. 0.014 grams of 60% acetic acid was added to neutralize the fabric. The textile was again rinsed with water and dried.

[0025] The dried textile was observed to find complete removal of the silicone softener by dropping water, and no difference between the fresh dyed textile and the redyed textile after removal of the silicone softener.

Claims

1. A process for cleaning textiles which comprises applying a composition comprising a low molecular weight linear siloxane of the formula:



wherein n is an integer from 1 to 7, and a cationic surfactant to stained textiles and heating the textiles in the presence of an inorganic base compound at a temperature below which the textiles are deteriorated.

2. The process of claim 1, wherein the cationic surfactant is a quaternary ammonium salt.
3. The process of claim 1, wherein the cationic surfactant is selected from the group consisting of trialkylmethylammonium salts, dialkyldimethylammonium salts, and mixtures thereof.
4. The process of claim 1, wherein the cationic surfactant is selected from the group consisting of trilaurylmethyl ammonium chloride and didecyldimethyl ammonium chloride.
5. The process of claim 3, wherein the composition further comprises alkylbenzyldimethylammonium salts in combination with the cationic surfactant.
6. The process of claim 1, wherein the inorganic base compound is selected from the group consisting of NaOH, KOH, Na_2CO_3 , and NaHCO_3 .
7. The process of claim 1, wherein the siloxane is selected from the group consisting of dimers, trimers and tetramers.
8. The process of claim 1, wherein the composition further comprises a non-ionic surfactant.
9. The process of claim 1, wherein the composition further comprises an organic solvent.
10. The process of claim 1, wherein the composition is in the form of an emulsion.
11. The process of claim 1, wherein the low molecular weight linear siloxane and the cationic surfactant are present in amounts such that a ratio of low molecular weight siloxane: cationic surfactant is in the range of about 1:25 to 25:1.
12. The process of claim 1, wherein the low molecular weight linear siloxane, the cationic surfactant, and the base compound are present in amounts such that a ratio of a sum of the amounts of the low molecular weight siloxane plus the cationic surfactant: the base compound is in the range of about 16:1 to 16:20.
13. The process of claim 1, wherein the temperature is above the room temperature.
14. The process of claim 13, wherein the temperature is in the range of about 80 to 100 degrees C.
15. The process of claim 1, wherein the textiles are heated for about 30 minutes to 3 hours.
16. The process of claim 1, wherein any oily and/or greasy stains are removed from the textiles.
17. The process of claim 1, wherein silicone retained onto the textiles is removed from the textiles.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 11 9749

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
E	DE 199 48 186 A (DOW CORNING TAIWAN LTD) 13 July 2000 (2000-07-13) * the whole document *	1-17	C11D3/16 C11D3/04 C11D3/10 C11D1/38 //C11D1:62
D,A	US 4 654 041 A (NICKEL FRIEDHELM) 31 March 1987 (1987-03-31) * claims * * examples * * column 2, line 59 - column 3, line 5 *	1-6,10, 13-17	
A	EP 0 458 969 A (TOKYO SHIBAURA ELECTRIC CO) 4 December 1991 (1991-12-04) * claims 1,5-7 * * examples 9-17 * * page 3, line 10 - line 14 * * page 4, line 45 - line 53 * * page 6, line 37 - page 7, line 53 *	1-5,7-9	
A	US 2 710 843 A (DOW CORNING CORP.) 14 June 1955 (1955-06-14) * claims * * column 1, line 45 - line 61 *	1,6,9, 13-15	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
D,A	US 4 685 930 A (KASPRZAK KENNETH A) 11 August 1987 (1987-08-11) * claims * * examples *	1,7,8, 10,16,17	C11D
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 24 October 2000	Examiner Neys, P
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03 82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 11 9749

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

24-10-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19948186 A	13-07-2000	JP 2000119690 A	25-04-2000
US 4654041 A	31-03-1987	DE 3515077 C EP 0199227 A	19-06-1986 29-10-1986
EP 0458969 A	04-12-1991	DE 69031030 D DE 69031030 T KR 9307226 B RU 2104331 C US 5977040 A US 5443747 A CA 2034488 A,C CA 2151846 A CA 2151847 A CA 2151848 A CA 2151849 A CN 1095410 A CN 1103113 A,B EP 0673995 A EP 0673996 A HK 1001094 A JP 2963406 B JP 9176697 A JP 2752352 B JP 9188897 A WO 9106621 A JP 2949201 B JP 7216569 A JP 2656450 B JP 7216387 A SG 47816 A SG 47130 A US 5728228 A US 5741365 A US 5985810 A US 5716456 A US 5741367 A CN 1051196 A,B JP 2651453 B SG 47860 A	14-08-1997 11-12-1997 04-08-1993 10-02-1998 02-11-1999 22-08-1995 27-04-1991 27-04-1991 27-04-1991 27-04-1991 27-04-1991 23-11-1994 31-05-1995 27-09-1995 27-09-1995 22-05-1998 18-10-1999 08-07-1997 18-05-1998 22-07-1997 16-05-1991 13-09-1999 15-08-1995 24-09-1997 15-08-1995 17-04-1998 20-03-1998 17-03-1998 21-04-1998 16-11-1999 10-02-1998 21-04-1998 08-05-1991 10-09-1997 17-04-1998
US 2710843 A	14-06-1955	NONE	
US 4685930 A	11-08-1987	AU 585906 B AU 4981785 A CA 1239326 A	29-06-1989 22-05-1986 19-07-1988

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 11 9749

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

24-10-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4685930 A		DE 3583377 D	08-08-1991
		EP 0182583 A	28-05-1986
		JP 1502875 C	28-06-1989
		JP 61119765 A	06-06-1986
		JP 63050463 B	07-10-1988
