

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 101 152 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:

10.03.2004 Bulletin 2004/11

(21) Application number: **99937676.7**

(22) Date of filing: **29.07.1999**

(51) Int Cl.7: **G03G 15/00**, G03G 15/20

(86) International application number:
PCT/US1999/017333

(87) International publication number:
WO 2000/007074 (10.02.2000 Gazette 2000/06)

(54) **SEPARATION FINGERS FOR ELECTRO PHOTOGRAPHIC DEVICES**

TRENNFINGER FÜR ELEKTROFOTOGRAFISCHE GERÄTE

DOIGTS SEPARATEURS DESTINES A DES DISPOSITIFS ELECTROPHOTOGRAPHIQUES

(84) Designated Contracting States:
DE FR GB IT NL

(30) Priority: **30.07.1998 JP 21600098**

(43) Date of publication of application:
23.05.2001 Bulletin 2001/21

(73) Proprietor: **E.I. DUPONT DE NEMOURS AND
COMPANY**
Wilmington, Delaware 19898 (US)

(72) Inventors:
• **GEORGE, Daniel, Eugene**
Chadds Ford, PA 19317 (US)
• **NAKAGAWA, Shinichi**
Utsunomiya-shi, Tochigi 321-09262 (JP)
• **YOKOYAMA, Akira**
Utsunomiya-shi, Tochigi 321-0864 (JP)

(74) Representative: **Abitz, Walter, Dr.-Ing. et al**
Patentanwälte Abitz & Partner,
Poschingerstrasse 6
81679 München (DE)

(56) References cited:
US-A- 4 687 696

- **PATENT ABSTRACTS OF JAPAN** vol. 1997, no. 11, 28 November 1997 (1997-11-28) & JP 09 190104 A (NTN CORP), 22 July 1997 (1997-07-22)
- **PATENT ABSTRACTS OF JAPAN** vol. 016, no. 341 (P-1391), 23 July 1992 (1992-07-23) & JP 04 102883 A (TORAY IND INC), 3 April 1992 (1992-04-03) cited in the application
- **PATENT ABSTRACTS OF JAPAN** vol. 018, no. 228 (P-1730), 25 April 1994 (1994-04-25) & JP 06 019360 A (TORAY IND INC), 28 January 1994 (1994-01-28) cited in the application

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 1 101 152 B1

Description**BACKGROUND OF THE INVENTION**

[0001] Development has been done previously to realize a separation finger that will prevent the occurrence of paper jams caused by, for example, the adhesion of the toner.

[0002] There are separation fingers molded from a polyimide resin which has a coating of a tetrafluoroethylene-perfluoroalkylvinyl ether copolymer at least for the tip portion which the copying paper touches (Published Unexamined Application No.: Hei 1-72182), and a separation finger molded of a polyamideimide resin or polyphenylene sulfide resin that have a coat of a multilayer structure consisting of a primer layer and top layer of a fluoro resin.

[0003] In addition to the technology to coat a fluoro resin on the surfaces of separation fingers, separation fingers for Electro graphic devices made by compression-molding and sintering blends consisting of 40 to 90 wt % polyimide resin and 60 to 10 wt % fluoro resin such as polytetrafluoroethylene resin (PTFE) (Published Unexamined Application No. Hei 4-102883), and separation fingers made by compression-molding blends of 30 to 90 wt % polyimide resin and 70 to 10 wt % tetrafluoroethylene-perfluoroalkyl-vinyl ether copolymer to obtain a compressed powder product for Separation fingers having configurations of 70 μ m or less in finger tips' inscribed circle diameter, and then sintering the powder product (Published Unexamined Application No. Hei 6-19360), have also been developed.

[0004] However, the improvement of the quality and life of copying equipment and other electro photographic devices, as well as the recent trend toward wider use of recycled paper, have made it necessary to improve separation fingers in non-adhesion to toner and wear resistance under the conditions of friction caused by toner and paper dust, and also to minimize the diameters of the tips of separation fingers. Thus, the object of this invention is to solve such problems and offer separation fingers for Electro photographic devices that have sharper tips and better wear resistance, non-adhesion of toner, and durability, without requiring fluoro resin coating. Moreover, the separation fingers of this invention have outstanding durability, capable of retaining non-adhesion of toner even when their surfaces have worn.

SUMMARY OF THE INVENTION

[0005] After working actively on research to solve the above-mentioned problems, these inventors found that it was possible to provide separation fingers having improved wear resistance and non-adhesion of toner by using polytetrafluoroethylene resin (PTFE) powder falling into certain ranges of weight-average molecular weight and average particle size, polyimide resin powder.

[0006] The separation fingers for electrophotographic devices of this invention developed to solve the above problems were characteristically obtained by compression-molding, and then sintering, blends obtained by blending polyimide resin powder and polytetrafluoroethylene resin (PTFE) powder which is 500,000 to 1,000,000 in weight-average molecular weight and 5 to 20 μ m in average particle size, at weight-based ratios of 70:30 to 95:5.

[0007] Other separation fingers of this invention are the above mentioned separation fingers that are characterized by their tips being 50 μ m or less in diameter.

[0008] Still other separation fingers of this invention are either of the above types that are characterized by the water-repelling angles of the separating finger surfaces being 100° or more and such surface water-repelling angles being at least 90° even when the surfaces of the separation fingers have worn to 50 μ m.

DETAILED DESCRIPTION OF THE INVENTION

[0009] The polyimide resin powder used in this invention is a condensation polymer, copolymer, etc, of one or more acids selected from a group consisting of pyromellitic dianhydride, 3,3',4,4'-biphenyltetra-carboxylic dianhydride, and 3,3',4,4'-benzophenonetetra-carboxylic dianhydride, and one or more diamines selected from a group consisting of 4,4'-diaminodiphenyl ether, 1,3-phenylenediamine, and 1,4-phenylene diamine. A condensation which is a copolymer of 3,3',4,4'-biphenyltetra-carboxylic dianhydride and 1,3'-phenylenediamine and 1,4'-phenylenediamine, is preferable because its thermal distortion temperature is quite high, at 340°C, and its strength and elongation are well balanced. A condensation polyimide of 4,4'-diaminodiphenyl ether and pyromellitic dianhydride is especially preferable.

[0010] The polytetrafluoroethylene resin (PTFE) powder used in this invention is 500,000 to 1,000,000 in weight-average molecular weight and 5-20 μ m in average particle size. Polytetrafluoroethylene resin (PTFE) can easily withstand the sintering temperature of any of the above polyimide resin powders because it has a high melting point; whereas, other known fluoro resins decompose when the polyimide resin powder is sintered.

[0011] The weight-average molecular weight of the polytetrafluoroethylene resin (PTFE) powder is preferably 600,000 to 800,000, and more preferably 600, 000 to 700,000. Its average particle size is preferably 5 to 15 μ m, and more preferably 7 to 12 μ m. If its weight-average molecular weight is less than 500,000, the powder thermally decomposes at the sintering temperature of the polyimide resin, and the separation finger's performance becomes uneven.

On the other hand, if the weight-average molecular weight is greater than 1,000,000, PTFE with high molecular weight melts at 327°C and sintering temperature of the polyimide in the range of 380 to 500°C, the melt viscosity is very high and the melt flow is very low, and its spread over the separation finger's surface becomes insufficient. Also, an average particle size either smaller than 5µm or larger than 20µm would result in poor dispersion and thence inability to obtain a having a good surface.

[0012] The blending ratio of the polyimide resin powder and polytetrafluoroethylene resin powder is 70:30 to 95:5 based on weight. It is preferably 80:20 to 90:10, and more preferably 85:15. If the polytetrafluoroethylene resin powder is blended at a ratio of less than 5, the powder's non-adhesion of toner would be insufficient, and if it is blended at a ratio of greater than 30, the tip strength of the separation finger would be reduced excessively.

[0013] In this invention, graphite can be blended, along with the polytetrafluoroethylene resin powder, into the polyimide resin powder to the extent that it will not affect the separation finger's performance capability. The separation finger of this invention is obtained by blending polyimide resin powder and polytetrafluoroethylene resin powder, 500,000 to 1,000,000 in weight-average molecular weight and 5 to 20 in average particle size, at a weight-based ratio of 70:30 to 95:5, and then sintering the compound. The polyimide resin and polytetrafluoroethylene resin (PTFE) powders are dry-blended. The blending must be accomplished under a set of conditions that will not cause excessive working of the polyimide resin powder. The compression-molding is normally done at a compression surface pressure of at least 40,000 psi, and the sintering is normally done at a temperature of 380 to 500°C for four hours or longer to achieve complete conversion to polyimide. It is preferable to wash and barrel-grind (tumble) the material with an abrasive media after sintering so that the separation fingers have a smoother surface.

[0014] The tip diameter of the separation finger of this invention is preferably not greater than 50µm, and more preferably not greater than 30µm. When a fluoro resin is coated over a separation finger made of a polyimide resin, it is extremely difficult to obtain a less-than-50µm tip diameter; whereas, in this invention, it is easier to ensure the precision of the molded article because no coating is applied.

[0015] In this invention, the water-repelling angle of the separation finger surface was used as an indicator of the non-adhesion of toner to the finger surface. Water-repelling angle was measured by dropping approx. 0.4 µl of distilled water on to the surface of the separation finger using a hypodermic needle and then measuring the contact angle using an image-processing type contact angle meter (Model CA-X 150, made by Kyowa Interface Science Co., Ltd.).

[0016] The water-repelling angle of the surface of a separation finger obtained by compression-molding and sintering a blend obtained by blending polyimide resin powder and polytetrafluoroethylene resin powder, 500,000 to 1,000,000 in weight-average molecular weight and 5 to 20µm in average particle size, at a weight-based ratio of 70:30 to 95:5 is at least 100°, and the separation finger's surface retains a water-repelling angle of at least 90° even when it has worn to 50µm. When a fluoro resin is coated over a separation finger, the coat thickness is 30 to 50µm. By contrast, in the case of the separation fingers of this invention, the finger surface not only has non-adhesion of toner without requiring coating, but also retains non-adhesion of toner even when the surface layer has worn, and thus is more durable than a coated separating finger.

[0017] This invention is further explained below by citing examples of use; however, the applicability of this invention is not limited to these examples of use.

EXAMPLES 1-2 AND COMPARATIVE EXAMPLES 1-4

[0018] Polyimide resin powder (VespeI(registered trademark) Si'-1, made by DuPont), which is a condensation polymer of 4, 4'-diaminodiphenyl ether and pyromellitic anhydride, and polytetrafluoroethylene resin powder having the weight-average molecular weight and average particle sizes shown in Table-1 were dry-blended at a weight-based ratio of 90:10, filled into a mold for separation fingers compressed at pressures of 40,000 psi or higher, and sintered at 380 to 500°C temperature for four hours or longer. The material was washed and barrel-grind(tumble with an abrasive media) after sintering to make separation finger approx. 30µm in tip diameter. A separation finger was made under the same manufacturing conditions but using the same polyimide resin powder alone as a control.

[0019] The surfaces of the separation fingers obtained were visually observed. The results are shown in Table-1.

[Table-1]

	PTFE Wt-average Molecular wt.	PTFE Ave. particle Size (µm)	Visually observed finger surface conditions
Example 1	600,000-700,000	7-12	A
Example 2	1,000,000	20	B
Comparative Example 1	80,000-90,000	2.5-4.5	C

EP 1 101 152 B1

[Table-1] (continued)

	PTFE Wt-average Molecular wt.	PTFE Ave. particle Size (μm)	Visually observed finger surface conditions
Comparative Example 2	400,000-500,000	8-15	C
Comparative Example 3	110,000	4-12	C
Comparative Example 4	150,000-200,000	8-15	C
A: Virtually equal to Control 1 in surface smoothness. B: Has some surface defects (swelling, void, etc.) compared with Control 1. C: Has serious defects compared with Control 1.			

[0020] When Examples 1 and 2 are compared with Comparative Example 1, it is found that no separation finger having a smooth surface is not obtainable if the weight-average molecular weight and average particle size of the polytetrafluoroethylene powder deviate from the ranges of this invention.

[0021] Also, when Examples 1 and 2 are compared with Comparative Examples 2 to 4, it is found that a separation finger having a smooth surface is not obtainable if the weight-average molecular weight of the polytetrafluoroethylene powder deviates from the range of this invention, even when the powder's average particle size is within the range of this invention, because of poor dispersion of the polytetrafluoroethylene resin powder.

EXAMPLES 3-6

[0022] Polyimide resin powder (VespeI (registered trademark) SP-1, made by DuPont), which is a condensation polymer of 4,4'-diaminodiphenyl ether and pyromellitic dianhydride, and polytetrafluoroethylene resin powder having a weight-average molecular weight of 600,000 to 700,000 and average particle size of 7 to 12 μm were dry-blended at the weight-based ratios shown in Table-2, filled into a mold for separation fingers, compressed at pressures of 40,000 psi or higher, and sintered at a temperature of 380 to 500°C for four hours or longer. The material was washed and tumbled with an abrasive media (barrel-grind) after sintering to make separation fingers approx. 30 μm in tip diameter. The tip strength of the separation fingers so obtained and that of the separation finger of Control-1 were measured. Specifically, the tip strength of the separation fingers was obtained by fixing the separation finger on the base of a compression tester so that its paper-running surface would be perpendicular to the base, applying a load on the finger tip from the vertical direction, and measuring the load when the tip broke. The test results are shown in Table-2.

[Table-2]

	PI:PTFE	Tip strength at normal temp. (kgf)	Tip strength at 200°C ambient temp. (kgf)
Example 3	70:30	0.5 (-74%)	0.4 (-69%)
Example 4	80:20	0.8 (-58%)	0.6 (-54%)
Example 5	85:15	1.1 (-42%)	0.9 (-31%)
Example 6	95:5	1.2 (-37%)	1.0 (-23%)
Control 1	100:0	1.9	1.3

[0023] The numbers in () represent the drops in tip strength in the various examples of use compared with the tip strength of Control 1.

[0024] When Examples 3 to 6 are compared with Control 1, it is found that the tip strength drops more when more polytetrafluoroethylene resin powder is blended, when tested either at normal temperature or at elevated temperature.

EXAMPLE 7 AND COMPARATIVE EXAMPLES 5-6

[0025] Polyimide resin powder (VespeI® SP-1, made by DuPont), which is a condensation polymer of 4,4'-diaminodiphenyl ether and pyromellitic dianhydride, and polytetrafluoroethylene resin powder having a weight-average molecular weight of 600,000 to 700,000 and average particle size of 7 to 12 μm were dry-blended at a ratio of 85:15, filled into a mold for separation fingers, compressed at pressure of 40,000 psi or higher, and sintered at 380°C to 500°C temperature for four hours or longer. The material was washed and barrel-ground (tumbled with an abrasive media) after sintering to make separation fingers approx. 30 μm in tip diameter. This was measured by dropping approx. 0.4 μl

of distilled water on to the surface of the separating finger so obtained, using a hypodermic needle, and then measuring the contact angle using an image processing type contact angle meter (Model CA-X 150, made by Kyowa Interface Science Co., Ltd.). Further, after the surface was ground to 50 μ m, using 1,000 mesh water-resistant abrasive paper, the angle of contact with water was measured in a similar manner to obtain the water-repelling angle.

[0026] Also, polyimide resin powder (Vespel® SP-1, made by DuPont), which is a condensation polymer of 4,4'-diaminodiphenyl ether and pyromellitic dianhydride, was filled into a mold for separation fingers compressed at compression surface pressures of 40,000 psi or higher, and sintered at 380°C to 500°C temperature for four hours or longer. The material was washed and barrel-ground (tumbled with an abrasive media) after sintering. The water-repelling angle of the paper scrapper was similarly measured to obtain Comparative Example 5.

[0027] A coating layer -- consisting of a primer layer 10 μ m in average coat thickness and a top layer 20 μ m in average coat thickness -- was formed by applying and drying a primer of a tetrafluoroethylene/perfluoroalkylvinyl ether copolymer over the surface of a separation finger made in a similar manner as Comparative Example 5, and further spray-coating, and then sintering, a top coat of dispersed (average particle size: 0.2 to 0.4 μ m) tetrafluoroethylene/perfluoroalkylvinyl ether copolymer over it. The product was used as Comparative Example 6.

[0028] The water-repelling angle of the separation finger surface so obtained was similarly measured. Then, as with Example 7, the water-repelling angle of the surface was measured after grinding it to 50 μ m using 1,000-mesh water resistant abrasive paper. The water-repelling angle test was run three time for each to obtain the average value. The results are shown in Table-3.

[Table-3]

	Water-repelling angle (contact angle of water) (deg.)	Water-repelling angle of surface after 50 μ m grinding (deg.)
Example 7	107.4	100.9
Comparative Example 5	81.7	-
Comparative Example 6	107.3	74.7

[0029] When Example 7 and Comparative Example 5 are compared, it is found that the blending of polytetrafluoroethylene resin powder results in higher water repellency of the surface of the separation finger. This is believed to indicate improved non adhesion of toner.

[0030] When Example 7 and Comparative Example 6 are compared, it is found that the surface of the separation finger of this invention has equal non-adhesion of toner as when a fluoro-resin is coated. It is also found that the separation finger of this invention retains outstanding non-adhesion of toner even when its surface is ground to 50 μ m, but that a separation finger coated with a fluoro-resin loses its non-adhesion because the maximum possible coat thickness of such a finger is approximately 50 μ m.

EXAMPLE 8

[0031] A paper running test was conducted by installing the separation finger of Example 1 on a commercially available medium-speed photocopying device and running size A-4 copying paper at a rate of 30 sheets/min. No troubles such as toner adhesion or tip wear occurred with the finger even when 100,000 sheets had been run, nor did the tip cause any scratches on the fixed roll which it touches directly.

Claims

1. A separation finger for Electro photographic devices, being formed by compression-molding a blend of polyimide and polytetrafluoroethylene resin powders, followed by sintering the blend, the weight-based blending ratio of said polyimide resin powders and polytetrafluoroethylene resin powders being 70:30 to 95:5 and said polytetrafluoroethylene resin powder being 500,000 to 1,000,000 in weight-average molecular weight and 5 to 20 μ m in average particle size.
2. The separation finger of Claim 1 wherein diameters of the separation finger tips are 50 μ m or less.
3. The separation finger of Claim 1 or 2 wherein the water-repelling angles of the surfaces of the separation finger are 100° or more and such surface water-repelling angles being at least 90° even when the surface of the separation finger has worn to 50 μ m.

Patentansprüche

1. Trennfinger für elektrofotografische Geräte, hergestellt durch Formpressen eines Gemischs aus Polyimid- und Polytetrafluorethylenharzpulvern und anschließendes Sintern des Gemischs, wobei das massebezogene Mischungsverhältnis der Polyimidharzpulver zu den Polytetrafluorethylenharzpulvern 70:30 bis 95:5 beträgt und das Polytetrafluorethylenharzpulver ein massegemittelttes Molekulargewicht von 500 000 bis 1 000 000 und eine mittlere Teilchengröße von 5 bis 20 µm aufweist.
2. Trennfinger nach Anspruch 1, wobei die Durchmesser der Trennfingerspitzen 50 µm oder weniger betragen.
3. Trennfinger nach Anspruch 1 oder 2, wobei die Wasserabweisungswinkel der Trennfingeroberflächen 100° oder mehr betragen und diese Wasserabweisungswinkel auch dann, wenn die Oberfläche des Trennfingers auf 50 µm abgenutzt ist, mindestens 90° betragen.

Revendications

1. Doigt de séparation pour dispositifs électro photographiques, formés par moulage sous compression d'un mélange de poudres de résines de polyimide et de polytétrafluoroéthylène, opération suivie d'un frittage du mélange, le rapport de mélange, sur une base pondérale, desdites poudres de résines de polyimide et desdites poudres de résines de polytétrafluoroéthylène étant de 70:30 à 95:5 et ladite poudre de résine de polytétrafluoroéthylène ayant une valeur de 500 000 à 1 000 000 en poids moléculaire en poids et une valeur de 50 à 20 µm en taille moyenne de particule.
2. Doigt de séparation selon la revendication 1, dans lequel les diamètres d'embouts du doigt de séparation sont de 50 µm ou moins.
3. Doigt de séparation selon la revendication 1 ou 2, dans lequel les angles hydrofuges des surfaces du doigt de séparation sont de 100° ou plus, les angles hydrofuges des surfaces de ce genre étant au moins de 90°, même si la surface du doigt de séparation s'est usée à 50 µm.