



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 145 965 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

Note: Bibliography reflects the latest situation

(15) Correction information:
Corrected version no 1 (W1 A1)
INID code(s) 72

(51) Int Cl.7: **B65C 7/00**

(48) Corrigendum issued on:
27.02.2002 Bulletin 2002/09

(43) Date of publication:
17.10.2001 Bulletin 2001/42

(21) Application number: **01302632.3**

(22) Date of filing: **21.03.2001**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Goto, Akihiro**
Nagoya-shi, Aichi (JP)
• **Ueno, Hideyuki**
Yokohama-shi, Kanagawa (JP)

(30) Priority: **21.03.2000 JP 2000078707**


(74) Representative: **Dealtry, Brian**
Eric Potter Clarkson, Park View House, 58 The
Ropewalk
Nottingham NG1 5DD (GB)

(71) Applicants:
• **Kotec's Co. Ltd.**
Tokyo (JP)
• **Sanyo Seisakusho Co., Ltd.**
Midori-ku, Nagoya-shi, Aichi (JP)

(54) **Fastening element**

(57) It is an object to provide a fastening element (20) with less generation of jamming at the time of operation. Because a fastening element comprises a plurality of a unit fastening element arranged adjacently, the unit fastening element comprising a filament section (5), an inserting head section (19) equipped with a suitable engagement section located at one end of the filament section, and a socket section (8) equipped with a hole (10) for irreversibly passing the inserting head section (19) located at the other end of the filament section, the fastening element characterized in that a plurality of the socket sections (8) or their vicinities arranged adjacent to each other are temporarily fixed to the connection bar section individually installed, respectively, and a plurality of optional filament sections (11) adjacent to each other are separably fixed temporarily, jamming is less generated when the operator couples the fastening element by the coupler gun.

Fig. 1



EP 1 145 965 A8