



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 173 672 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:  
**12.04.2006 Bulletin 2006/15**

(21) Application number: **00928401.9**

(22) Date of filing: **27.04.2000**

(51) Int Cl.:  
**F02M 61/16** <sup>(2006.01)</sup> **F02M 61/18** <sup>(2006.01)</sup>

(86) International application number:  
**PCT/US2000/011176**

(87) International publication number:  
**WO 2000/065226 (02.11.2000 Gazette 2000/44)**

(54) **FUEL INJECTOR WITH A TRANSITION REGION**

BRENNSTOFFEINSPRITZVORRICHTUNG MIT EINEM ÜBERGANGSBEREICH  
INJECTEUR DE CARBURANT AVEC ZONE DE TRANSITION

(84) Designated Contracting States:  
**DE FR GB IT**

(30) Priority: **27.04.1999 US 131251 P**

(43) Date of publication of application:  
**23.01.2002 Bulletin 2002/04**

(73) Proprietor: **Siemens VDO Automotive Corporation**  
**Auburn Hills, MI 48326-2980 (US)**

(72) Inventors:  
• **IMOEHL, William, James**  
**Williamsburg, VA 23185 (US)**

• **HALL, Bryan**  
**Newport News, VA 23602 (US)**

(74) Representative: **Payne, Janice Julia et al**  
**Siemens AG,**  
**Postfach 22 16 34**  
**80506 München (DE)**

(56) References cited:  
**GB-A- 2 029 508** **GB-A- 2 073 954**

• **PATENT ABSTRACTS OF JAPAN** vol. 009, no. 139  
**(M-387), 14 June 1985 (1985-06-14) & JP 60 019957**  
**A (NIHON DENSHI KIKI KK), 1 February 1985**  
**(1985-02-01)**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

## Description

### Cross Reference to Co-Pending Application

[0001] This application claims priority to U.S. Provisional Application No. 60/131,251, filed April 27, 1999.

### Field of the Invention

[0002] This invention relates to a fuel injector assembly, and more particularly to a high-pressure fuel injector assembly which includes a seat having a number of features for minimizing the formation of combustion chamber deposits on the seat. This invention also relates to the arrangement and manufacture of a fuel injector seat.

### Background of the Invention

[0003] Fuel injectors are conventionally used to provide a measured flow of fuel into an internal combustion engine. In the case of direct injection systems, a high-pressure injector extends into the combustion chamber. Consequently, a downstream face of the fuel injector's seat is prone to the formation of combustion chamber deposits. It is desirable to minimize this formation of deposits in order to maintain the intended operation of the fuel injector.

[0004] For the intended operation, it is critical for the seat to provide a sealing surface for engaging a displaceable closure member, e.g., a needle of a conventional fuel injector assembly. In a first position of the closure member relative to the seat, i.e., when the closure member contiguously engages the seat, fuel flow through the injector is prohibited. In a second position of the closure member relative to the seat, i.e., when the closure member is separated from the seat, fuel flow through the injector is permitted.

[0005] In order to provide the sealing surface, it is known to provide the seat with a conical portion having a desired included angle. Conventionally, grinding tools with a conical shape are used to grind the conical portion. It is also known that the quality of a surface finish is related to the grinding velocity. In the case of conical shape grinding tools, the grinding velocity decreases toward the apex of the tools.

[0006] In the case of fuel injector seats having a small orifice, the velocity of the grinding tool at the edge of the orifice is insufficient. Thus, conventional grinding operations cannot provide a selected finish on conventional conical portions.

[0007] JP-A-60 019 957 describes a nozzle for a fuel injector valve which is made with a coupling section to prevent burrs during manufacture at the intersection of the valve seat surface and the injection hole surface.

### Summary of the Invention

[0008] The present invention overcomes the disadvantages

of the seats in conventional fuel injectors, and provides a number of features for minimizing the formation of combustion chamber deposits.

[0009] According to the present invention, a transition portion is interposed between the conventional conical portion and the orifice, thus providing an additional volume in which the apex of the conventional grinding tool rotates.

[0010] However, excess sac volume, i.e., the volume of the fuel flow passage between the sealing band (i.e., the needle-to-seat seal) and the orifice, adversely affects the formation of combustion chamber deposits on the downstream seat. Thus, according to the present invention, the transition portion also minimizes sac volume.

[0011] Moreover, according to the present invention, a fuel injector seat is evaluated as to the necessity and configuration of a transition portion. This evaluation is based on different factors including orifice size and the included angle defined by the conical sealing portion.

[0012] Also, according to the present invention, an interface between the downstream face and the orifice is defined by a sharp edge. This facilitates dislodging combustion chamber deposits that may accumulate near the edge.

[0013] Additionally, according to the present invention, a fuel injector seat has a coating to control the formation of combustion chamber deposits in a first set of critical areas, and is uncoated in a second set of critical areas to facilitate the attachment and operation of the seat.

[0014] The present invention provides a fuel injector having an inlet, an outlet, and a passageway providing a fuel flow conduit from the inlet to the outlet. The fuel injector comprises a needle positionable in the passageway between a first position occluding the passageway and a second position permitting fuel flow; and a fuel injector seat contiguously engaging the needle in the first position, the seat having an upstream face, a downstream face spaced from the upstream face, and a passage extending along an axis between the upstream face and the downstream face. The passage defines a portion of the passageway and includes an orifice portion proximate the downstream face and a sharp edge formed at an interface of the downstream face and the orifice portion; wherein the orifice portion has a first transverse cross-sectional area relative to the axis; the orifice portion extending along the axis a prescribed length and including a right circular cylindrical section having a prescribed diameter, and wherein a ratio of the prescribed length over the prescribed diameter is at least 0.3; a needle sealing portion proximate the upstream face and having a second transverse cross-sectional area relative to the axis that decreases at a first rate in a downstream direction from a first area to a second area; and a transition portion interposed between the orifice portion and the needle sealing portion and a transition portion configured to minimize sac volume interposed between the orifice portion and the needle-sealing portion having a third transverse cross-sectional area relative to the axis that

decreases at a second rate in the downstream direction from the second area to the first transverse cross-sectional area; and wherein a selected finish is formed on the needle-sealing portion by applying a coating to certain surfaces of the seat and ensuring that critical surfaces of the seat are uncoated.

**[0015]** The present invention additionally provides a method of forming a fuel injector seat having an upstream face, a downstream face, and a passage extending along an axis between the upstream face and the downstream face. The method comprises forming within the passage an orifice portion proximate the downstream face and a sharp edge formed at an interface of the downstream face and the orifice portion; wherein the orifice portion has a first transverse cross-sectional area relative to the axis; the orifice portion extending along the axis a prescribed length and including a right circular cylindrical section having a prescribed diameter, and wherein a ratio of the prescribed length over the prescribed diameter is at least 0.3; forming within the passage a sealing portion proximate the upstream face and having a second transverse cross-sectional area relative to the axis that decreases at a first rate in a downstream direction from a first area to a second area; and forming within the passage a transition portion configured to minimise sac volume interposed between the orifice portion and the sealing portion and having a third transverse cross-sectional area relative to the axis that decreases at a second rate in the downstream direction from the second area to the first transverse cross-sectional area, wherein the forming the needle-sealing portion (612) comprises forming a selected finish by applying a coating to certain surfaces of the seat (64) and ensuring that critical surfaces of the seat are uncoated.

**[0016]** As it is used herein, the term "axis" is defined as a center line to which parts of a body or an area may be referred. This term is not limited to straight lines, but may also include curved lines or compound lines formed by a combination of curved and straight segments.

**[0017]** As it is used herein, the term "rate" is defined as a value that describes the changes of a first quality relative to a second quality. For example, in the context of describing a volume, rate can refer to changes in the transverse cross-sectional area of the volume relative to changes in position along the axis of the volume. The term "rate" is not limited to constant values, but may also include values that vary.

**[0018]** As it is used herein, the phrase "included angle" is defined as a measurement of the angular relationship between two segments of a body, when viewing a cross-section of the body in a plane including the axis of the body. Generally, the axis bifurcates the included angle.

#### Brief Description of the Drawings

**[0019]** The accompanying drawings, which are incorporated herein and constitute part of this specification, illustrate presently preferred embodiments of the inven-

tion, and, together with the general description given above and the detailed description given below, serve to explain features of the invention.

Figure 1 is a cross-sectional view of a fuel injector assembly of the present invention taken along its longitudinal axis; and

Figure 2 is an enlarged portion of the cross-sectional view of the fuel injector assembly shown in Figure 1 which illustrates a seat and a swirl generator according to the present invention.

Figure 3 is a graph illustrating engine flow decrease as a function of the ratio of orifice length over orifice diameter for different examples of fuel injectors.

Figure 4 is a detail view of a seat portion that is indicated by IV in Figure 2.

**[0020]** Figure 5 is a schematic illustration of the seat according to the present invention indicating the critical areas of the seat that are coated and the critical areas of the seat that are uncoated.

#### **Detailed Description of the Preferred Embodiment (s)**

**[0021]** Figure 1 illustrates a fuel injector assembly 10, such as a high-pressure, direct-injection fuel injector assembly 10. The fuel injector assembly 10 has a housing, which includes a fuel inlet 12, a fuel outlet 14, and a fuel passageway 16 extending from the fuel inlet 12 to the fuel outlet 14 along a longitudinal axis 18. The housing includes an overmolded plastic member 20 cincturing a metallic support member 22.

a fuel inlet member 24 with an inlet passage 26 is disposed within the overmolded plastic member 20. The inlet passage 26 serves as part of the fuel passageway 16 of the fuel injector assembly 10. a fuel filter 28 and an adjustable tube 30 are provided in the inlet passage 26. The adjustable tube 30 is positionable along the longitudinal axis 18 before being secured in place, thereby varying the length of an armature bias spring 32. In combination with other factors, the length of the spring 32, and hence the bias force against the armature, control the quantity of fuel flow through the injector. The overmolded plastic member 20 also supports a socket 20a that receives a plug (not shown) to operatively connect the fuel injector assembly 10 to an external source of electrical potential, such as an electronic control unit (not shown). An elastomeric O-ring 34 is provided in a groove on an exterior of the inlet member 24. The O-ring 34 is supported by a backing ring 38 to sealingly secure the inlet member 24 to a fuel supply member (not shown), such as a fuel rail

**[0022]** The metallic support member 22 encloses a coil assembly 40. The coil assembly 40 includes a bobbin 42 that retains a coil 44. The ends of the coil assembly 40 are electrically connected to pins 40a mounted within the socket 20a of the overmolded plastic member 20. An armature 46 is supported for relative movement along the axis 18 with respect to the inlet member 24. The ar-

mature 46 is supported by a spacer 48, a body shell 50, and a body 52. The armature 46 has an armature passage 54 in fluid communication with the inlet passage 26.

**[0023]** The spacer 48 engages the body shell 50, which engages the body 52. An armature guide eyelet 56 is located on an inlet portion 60 of the body 52. An axially extending body passage 58 connects the inlet portion 60 of the body 52 with an outlet portion 62 of the body 52. The armature passage 54 of the armature 46 is in fluid communication with the body passage 58 of the body 52. a seat 64, which is preferably a metallic material, is mounted at the outlet portion 62 of the body 52.

**[0024]** The body 52 includes a neck portion 66 that extends between the inlet portion 60 and the outlet portion 62. The neck portion 66 can be an annulus that surrounds a needle 68. The needle 68 is operatively connected to the armature 46, and can be a substantially cylindrical needle 68. The cylindrical needle 68 is centrally located within and spaced from the neck portion so as to define a part of the body passage 58. The cylindrical needle 68 is axially aligned with the longitudinal axis 18 of the fuel injector assembly 10.

**[0025]** Operative performance of the fuel injector assembly 10 is achieved by magnetically coupling the armature 46 to the end of the inlet member 26 that is closest to the inlet portion 60 of the body 52. Thus, the lower portion of the inlet member 26 that is proximate to the armature 46 serves as part of the magnetic circuit formed with the armature 46 and coil assembly 40. The armature 46 is guided by the armature guide eyelet 56 and is responsive to an electromagnetic force generated by the coil assembly 40 for axially reciprocating the armature 46 along the longitudinal axis 18 of the fuel injector assembly 10. The electromagnetic force is generated by current flow from the electronic control unit (not shown) through the coil assembly 40. Movement of the armature 46 also moves the operatively attached needle 68 to positions that are either separated from or contiguously engaged with the seat 64. This opens or closes, respectively, the seat passage 70 of the seat 64, which permits or inhibits, respectively, fuel from flowing through the fuel outlet 14 of the fuel injector 10. The needle 68 includes a curved surface 78, which can have a partial spherical shape for contiguously engaging with a conical portion 72 of the seat passage 70. Of course, other contours for the tip of the needle 68 and the seat passage 70 may be used provided that, when they are engaged, fuel flow through the seat 64 is inhibited.

**[0026]** Referring to Figures 1 and 2, an optional swirl generator 74 can be located proximate to the seat 64 in the body passage 58. The swirl generator 74 allows fuel to form a swirl pattern on the seat 64. For example, fuel can be swirled on the conical portion 72 of the seat passage 70 in order to produce a desired spray pattern. The swirl generator 74, preferably, is constructed from a pair of flat disks, a guide disk 76 and a swirl disk 78. The swirl generator 74 defines a contact area between the seat 64 and the body 52. The guide disk 76 provides a support

for the needle 68.

**[0027]** The needle 68 is guided in a central aperture 80 of the guide disk 76. The guide disk 76 has a plurality of fuel passage openings that supply fuel from the body passage 58 to the swirl disk 78. The swirl disk 78 receives fuel from the fuel passage openings in the guide disk 76 and directs the flow of fuel tangentially toward the seat passage 70 of the seat 64. The guide disk 76 and swirl disk 78 that form the swirl generator 74 are secured to an upstream face 602 of the seat 64, preferably, by laser welding.

**[0028]** Fuel that is to be injected from the fuel injector 10 is communicated from the fuel inlet source (not shown), to the fuel inlet 12, through the fuel passageway 16, and exits from the fuel outlet 14. The fuel passageway 16 includes the inlet passage 26 of the inlet member 24, the armature passage 54 of the armature 46, the body passage 58 of the body 52, the guide disk 78 and the swirl disk 80 of the swirl generator 74, and the seat passage 70 of the seat 64. In a high-pressure, direct injection system, fuel is supplied from the inlet source in an operative range approximately between 700 psi and 2000 psi.

**[0029]** Referring to Figure 2 in particular, the seat passage 70 of the seat 64 extends between the upstream face 602 of the seat 64 and a downstream face 604 of the seat 64. The seat passage 70 includes an orifice portion 608, a needle sealing portion 612, and a transition portion 614. The needle sealing portion 612 is disposed proximate to the first face 602, the orifice portion 608 is disposed proximate to the downstream face 604, and the transition portion 614 is interposed between the orifice portion 608 and the needle sealing portion 612.

**[0030]** The orifice portion 608 has a first transverse cross-sectional area relative to the longitudinal axis 18. That is to say, the first cross-sectional area can be measured in each of the imaginary planes that are oriented orthogonally to the longitudinal axis 18 as it extends through the orifice portion 608, or it can be measured in each of the imaginary planes within the orifice portion 608 that are parallel to the downstream face 604. It is most frequently the case that the downstream face 604 is oriented substantially orthogonal to the longitudinal axis 18, and the longitudinal axis 18 consists of a straight line extending throughout the entire fuel injector assembly 10. Consequently, the first cross-sectional area can be measured in each of the imaginary planes that are both oriented orthogonally to the longitudinal axis 18 and parallel to the downstream face 604.

**[0031]** The first transverse cross-sectional area can be substantially uniform throughout the orifice portion 608. For example, the first transverse cross-sectional area can be a circle having a diameter D and orifice portion 608 can extend along the longitudinal axis 18 a distance L. Thus, in the most frequent case described above, the orifice portion 608 comprises a right circular cylinder. Through experimentation, it has been determined that desirable operating characteristics for the fuel injector assembly 10 are achieved when the ratio of the length L

to diameter D, i.e.,  $L/D$ , for the orifice portion 608 approaches, but is not less than, 0.3. Figure 3 is an empirical data plot of flow changes due to deposit formation as a function of the  $L/D$  ratio.

**[0032]** The needle sealing portion 612 has a second transverse cross-sectional area relative to the longitudinal axis 18. That is to say, the second cross-sectional area can be measured in each of the imaginary planes that are oriented orthogonally to the longitudinal axis 18 as it extends through the needle sealing portion 612, or it can be measured in each of the imaginary planes within the needle sealing portion 612 that are parallel to the upstream face 602. It is most frequently the case that the upstream face 602 is oriented substantially orthogonal to the longitudinal axis 18, and the longitudinal axis 18 consists of a straight line extending throughout the entire fuel injector assembly 10. Consequently, the second cross-sectional area can be measured in each of the imaginary planes that are both oriented orthogonally to the longitudinal axis 18 and parallel to the upstream face 602.

**[0033]** The needle sealing portion 612 is formed by a grinding tool so as to provide a selected finish. The contour of the needle sealing portion 612 can be described by the shape of each second transverse cross-sectional area and the rate that the second transverse cross-sectional area decreases throughout the needle sealing portion 612. The second transverse cross-sectional area can have a first area in the imaginary plane that is proximate to the upstream face 602, and decrease at a first rate to a second area in the imaginary plane that is distal from the upstream face 602. As discussed above, this rate may be constant or variable. In the case where the shape of each second transverse cross-sectional area is a circle having a diameter that decreases at a constant rate, as is illustrated in Figure 2, the shape of the needle sealing portion 612 is that of a truncated right cone with an included angle 624. Of course, different shapes for the needle sealing portion 612 can be obtained by varying the shape of the second transverse cross-sectional areas or by varying the rate at which the second transverse cross-sectional areas change.

**[0034]** The transition portion 614 has a third transverse cross-sectional area relative to the longitudinal axis 18. That is to say, the third cross-sectional area can be measured in each of the imaginary planes that are oriented orthogonally to the longitudinal axis 18 as it extends through the transition portion 614, or it can be measured in each of the imaginary planes within the transition portion 614 that are parallel to the upstream face 602. It is most frequently the case that the upstream face 602 is oriented substantially orthogonal to the longitudinal axis 18, and the longitudinal axis 18 consists of a straight line extending throughout the entire fuel injector assembly 10. Consequently, the third cross-sectional area can be measured in each of the imaginary planes that are both oriented orthogonally to the longitudinal axis 18 and parallel to the upstream face 602.

**[0035]** The transition portion 614 can be formed by a

grinding tool, a drill bit, etc. The contour of the transition portion 614 can be described by the shape of each third transverse cross-sectional area and the rate that the third transverse cross-sectional area decreases throughout the transition portion 614. The third transverse cross-sectional area can decrease at a second rate from the second area of the second transverse cross-sectional area to the first transverse cross-sectional area of the orifice portion 608. As discussed above, this rate may be constant or variable. In the case where the shape of each third transverse cross-sectional area is a circle having a diameter that decreases at a constant rate, as is illustrated in Figure 2, the shape of the transition portion 614 is that of a truncated right cone with an included angle 626. Of course, different shapes for the transition portion 614 can be obtained by varying the shape of the second transverse cross-sectional areas or by varying the rate at which the second transverse cross-sectional areas change.

**[0036]** The transition portion 614 provides a volume which receives the tip of the grinding tool forming the needle sealing portion 612. Thus, only portions of the grinding tool that are driven at a sufficient grinding velocity contact the needle sealing portion 612, thereby producing at least a minimum selected finish over the entire surface of the needle sealing portion 612.

**[0037]** When the transition portion 614 is conically shaped, the included angle 624 of the needle sealing portion 612 is preferably greater than the included angle 626 of the transition portion 614. The included angle 624 can be approximately  $15^\circ$  greater than the included angle 626, e.g., the included angle 624 of the needle sealing portion 612 can be approximately  $105^\circ$  and the included angle 626 of the transition portion 614 can be approximately  $90^\circ$ . Of course, different combinations of included angles can be used provided that the needle sealing portion 612 sealingly conforms to the surface 78 of the needle 68, and the transition portion 614 facilitates providing a selected finish on the needle sealing portion 612. For example, it has been found that when the included angle 624 is approximately  $104^\circ$  and the included angle 626 is approximately  $85^\circ$ , flow stability is improved. If the included angle 626 is increased into the range of approximately  $95^\circ$  to  $100^\circ$ , flow stability decreases and deposit removal, perhaps as a result of cavitation, improves.

**[0038]** In addition to providing a transition between the needle sealing portion 612 and the orifice portion 608, the transition portion 614 minimizes the sac volume, i.e., the volume of the seat passage 70 from where the surface 78 of the needle 68 contiguously engages the needle sealing portion 612 to the orifice portion 608. For example, a transition portion 614 having the shape of a right circular cylinder would undesirably increase the sac volume as compared to a right cone, such as illustrated in Figure 2.

**[0039]** Referring now to Figures 2 and 4, the interface at the junction of the downstream face 604 and the orifice portion 608 can be a sharp edge to facilitate the dislodg-

ing of combustion chamber deposits that form on the downstream face 604. In particular, a sharp edge prevents the formation of combustion chamber deposits on the downstream face 604 from continuing to accumulate on the orifice portion 608. That is to say, the pattern of deposit formation does not extend from the substantially flat surface of the downstream face 604 onto the substantially cylindrical surface of the orifice portion 608. Instead, a continued build-up of the deposits at the interface of the downstream face 604 and the orifice portion 608 results in a formation that can be readily dislodged by the high pressure spray of fuel passing through the orifice portion 608. According to the present invention, a sharp edge can be defined by an interface comprising an annular chamfered edge 606 connecting the perpendicular surfaces of the downstream face 604 and the orifice portion 608. The chamfered edge 606 can extend for approximately 0.02 millimeters and be oriented at 45° with respect to each of these perpendicular surfaces.

**[0040]** Referring to Figure 5, coatings that lower surface energy or reduce surface reactivity can also control the formation of combustion chamber deposits. Certain surfaces of the seat 64 can be coated, however, the presence of a coating can adversely affect certain critical surfaces of the seat 64. For example, coatings can reduce the effectiveness of the seat to needle seal, or can hinder the connection of the seat 64 with respect to the body 52. An injector seat blank, i.e., a seat 64 comprising the upstream face 602, the downstream face 604, and the rough passage 70 (prior to grinding the needle sealing portion 612), is coated or plated. Masking can be used to prevent applying the coating on an outer circumferential surface of the seat 64. Masking can also be used to prevent the application of the coating to a portion of the downstream face 604 that is proximate to the outer circumferential surface. These masked areas can subsequently be used for attaching the seat 64 with respect to the body 52. Grinding for the needle sealing portion 612 removes the applied coating in the area of the critical sealing band. Thus, the seat 64 is coated in the areas most necessary to inhibit deposit formation, and is uncoated in the critical sealing band area and in seat attachment area. The coating can be a carbon based coating, such as that sold under the trade name SICON, which can be applied by conventional vapor deposition techniques. The coating can also be fluoro-polymer based, aluminum based, or a ceramic. The contiguously engaging needle 68 can also be coated or can be uncoated.

**[0041]** The method of forming the fuel injector assembly 10 includes forming the seat 64 having the upstream face 602, the downstream face 604, and the seat passage 70 extending between the upstream face 602 and the downstream face 604. The method further comprises forming the orifice portion 608 and the transition portion 614 within the passage 70. Before applying a coating to the seat 64, the needle-sealing portion 612 can be rough formed and the sharp edge interface 606 can be formed between the downstream face 604 and the orifice portion

608. The orifice portion 608, the rough formed needle-sealing portion 612, and the transition portion 614 can be formed in any order, and by any technique, e.g., drilling, turning, etc. Moreover, any combination of the orifice portion 608, the rough formed needle-sealing portion 612, and the transition portion 614 can be formed concurrently by one operation, or all can be formed in a single operation. Next, the seat 64 can be masked and the coating applied to the seat 64. Thereafter, the seat 64 can be unmasked, and the selected finish on the needle sealing portion 612 can be formed by grinding. Alternatively, the needle sealing portion 612 can be formed with the selected finish in a single step, i.e., without separately rough forming the needle sealing portion 612. The transition portion 614 provides the volume for the grinding tool that is necessary to form the selected finish on the needle-sealing portion 612. And as discussed above, the transition portion also minimizes sac volume. The seat 64 is now ready to be mounted with respect to the body 52 of the fuel injector assembly 10.

**[0042]** A number of factors are evaluated to determine the necessity of providing the transition portion 614 between the orifice portion 608 and the needle sealing portion 612. These factors include the first transverse cross-sectional area of the orifice portion 608, the included angle of the needle-sealing portion 612, and the selected finish to be provided on the needle-sealing portion 612.

**[0043]** The finish, or surface texture, of a material is a measurement of roughness, which is specified as a value that is the arithmetic average deviation of minute surface irregularities from a hypothetical perfect surface. Roughness is expressed in micrometers.

**[0044]** For a rotating grinding tool, linear velocity varies as a function of the radial distance from the axis of rotation. Therefore, if the finish produced by a rotating grinding tool at a radial distance corresponding to the edge of the first transverse cross-sectional area is too rough, a transition portion 614 according to the present invention is necessary.

**[0045]** The transition portion 614 provides a volume that is relatively near to the axis of rotation for a rotating grinding tool, and in which the grinding tool does not contact the seat 64. Thus, only those diameters of a rotating grinding tool that move with a sufficient grinding velocity are used to provide the selected finish on the needle-sealing portion 612.

**[0046]** According to the present invention, for a needle-sealing portion 612 having an included angle of approximately 105°, a transition portion 614 is necessary when the ratio of the first transverse cross-sectional area over the first area of the second transverse cross-sectional area is less than 0.5.

**[0047]** Of course, if the needle-sealing portion 612 is to be formed by a technique using something other than a rotating grinding tool, or the shape of the second transverse cross-sectional areas are not circular, the necessity of a transition portion 614 will be determined by evaluating the quality of the surface finish at the interface

between the needle-sealing portion 612 and the orifice portion 608.

**[0048]** While the present invention has been disclosed with reference to certain preferred embodiments, numerous modifications, alterations, and changes to the described embodiments are possible without departing from the sphere and scope of the present invention, as defined in the appended claims. Accordingly, it is intended that the present invention not be limited to the described embodiments, but that it have the full scope defined by the language of the following claims, and equivalents thereof

## Claims

1. A fuel injector having an inlet, an outlet, and a passageway (16) providing a fuel flow conduit from the inlet to the outlet, the fuel injector comprising:

a needle (68) positionable in the passageway between a first position occluding the passageway and a second position permitting fuel flow; and

a fuel injector seat (64) contiguously engaging the needle (68) in the first position; the seat having an upstream face (602); a downstream face (604) spaced from the upstream face; and a passage (70) extending along an axis (18) between the upstream face and the downstream face, the passage defining a portion of the passageway (16) and including:

an orifice portion (608) proximate the downstream face and a sharp edge formed at an interface of the downstream face and the orifice portion; wherein the orifice portion has a first transverse cross-sectional area relative to the axis (18); the orifice portion extending along the axis a prescribed length and including a right circular cylindrical section having a prescribed diameter, and wherein a ratio of the prescribed length over the prescribed diameter is at least 0.3;

a needle-sealing portion (612) proximate the upstream face (602) and having a second transverse cross-sectional area relative to the axis that decreases at a first rate in a downstream direction from a first area to a second area; and

a transition portion (614) configured to minimise sac volume interposed between the orifice portion (608) and the needle-sealing portion (612) and having a third transverse cross-sectional area relative to the axis (18) that decreases at a second rate in the downstream direction from the second area to the first transverse cross-sectional area;

wherein a selected finish is formed on the needle-sealing portion (612) by applying a coating to certain surfaces of the seat (64) and ensuring that critical surfaces of the seat are uncoated.

2. A fuel injector according to claim 1, wherein the transition portion (614) provides a volume for a grinding tool to form the selected finish on the needle-sealing portion (612) by grinding the applied coating.
3. A fuel injector according to claim 2, wherein the volume of the transition portion (614) minimises passage volume downstream of the needle-sealing portion (612).
4. A fuel injector according to claim 1, wherein the needle-sealing portion (612) comprises a first conical section defining a first included angle (624), and the transition portion (614) comprises a second conical section defining a second included angle (626), and wherein the first included angle is greater than the second included angle.
5. A fuel injector according to claim 1, wherein the transition portion (614) induces cavitation.
6. A fuel injector according to claim 1, wherein the first, second, and third transverse cross-sectional areas are orthogonal to the axis (18).
7. A method of forming a fuel injector seat (64), the seat having an upstream face (602), a downstream face (604), and a passage (70) extending along an axis (18) between the upstream face and the downstream face, the method comprising:

forming within the passage an orifice portion (608) proximate the downstream face; forming a sharp edge at an interface of the downstream face (604) and the orifice portion; wherein the orifice portion has a first transverse cross-sectional area relative to the axis; the orifice portion extending along the axis a prescribed length and including a right circular cylindrical section having a prescribed diameter, and wherein a ratio of the prescribed length over the prescribed diameter is at least 0.3;

forming within the passage a sealing portion (612) proximate the upstream face (602) and having a second transverse cross-sectional area relative to the axis that decreases at a first rate in a downstream direction from a first area to a second area; and

forming within the passage (70) a transition portion (614) configured to minimise sac volume interposed between the orifice portion (608) and the sealing portion (612) and having a third transverse cross-sectional area relative to the

axis that decreases at a second rate in the downstream direction from the second area to the first transverse cross-sectional area; and,

wherein the forming the needle-sealing portion (612) comprises forming a selected finish by applying a coating to certain surfaces of the seat (64) and ensuring that critical surfaces of the seat are uncoated.

8. A method according to claim 7, wherein the forming the selected finish comprises grinding the needle sealing portion with the grinding tool. 10
9. A method according to claim 7, wherein the forming the transition portion (614) provides a volume for the grinding tool. 15
10. The method according to claim 7, wherein the forming the sealing portion (612) forms a first included angle (624), and the forming the transition portion (614) forms a second included angle (626) that is less than the first included angle. 20

#### Patentansprüche 25

1. Brennstoffeinspritzventil, das einen Eintrittsbereich, einen Austrittsbereich und einen Durchflusspfad (16) aufweist, der eine Durchleitung des Brennstoffflusses vom Eintrittsbereich zum Austrittsbereich bereitstellt, wobei das Brennstoffeinspritzventil umfasst: 30

eine Nadel (68), die in dem Durchflusspfad angeordnet werden kann zwischen einer ersten Stellung, die den Durchflusspfad blockiert, und einer zweiten Stellung, die den Brennstofffluss ermöglicht; und 35

einen Brennstoffeinspritzventilsitz (64), auf dem die Nadel (68) in der ersten Stellung schlüssig aufsitzt; wobei der Ventilsitz eine in Strömungsrichtung vorgelagerte Fläche (602) aufweist; eine in Strömungsrichtung nachgelagerte Fläche (604), die in einem Abstand zu der in Strömungsrichtung vorgelagerten Fläche angeordnet ist; und einen Kanal (70), der entlang einer Achse (18) zwischen der in Strömungsrichtung vorgelagerten Fläche und der in Strömungsrichtung nachgelagerten Fläche verläuft, wobei der Kanal einen Teil des Durchflusspfads (16) definiert und umfasst: 40

einen Bohrbereich (608) nahe der in Strömungsrichtung nachgelagerten Fläche und eine scharfe Kante, die an einer Kontur von der in Strömungsrichtung nachgelagerten Fläche und dem Bohrbereich ausgebildet ist; wobei der Bohrbereich ei- 45

ne erste Querschnittsfläche aufweist, die quer zur Achse (18) verläuft; wobei der Bohrbereich mit einer vorgegebenen Länge entlang der Achse verläuft und einen rechtwinkligen Kreiszylinderbereich mit einem vorgegebenen Durchmesser umfasst, und wobei ein Quotient aus der vorgegebenen Länge und dem vorgegebenen Durchmesser mindestens 0,3 beträgt; einen Nadeldichtbereich (612) nahe der in Strömungsrichtung vorgelagerten Fläche (602), der eine zweite Querschnittsfläche aufweist, die quer zur Achse verläuft und in einem ersten Verhältnis in einer in Strömungsrichtung nachgelagerten Richtung von einem ersten Bereich zu einer zweiten Fläche kleiner wird; und einen Übergangsbereich (614), der so ausgelegt ist, dass er das Auslaufvolumen minimiert, das zwischen dem Bohrbereich (608) und dem Nadeldichtbereich (612) angeordnet ist, und der eine dritte Querschnittsfläche aufweist, die quer zur Achse (18) verläuft und in einem zweiten Verhältnis in einer in Strömungsrichtung nachgelagerten Richtung vom zweiten Bereich zur ersten quer verlaufenden Querschnittsfläche kleiner wird;

wobei eine gewählte Oberflächenbeschaffenheit auf dem Nadeldichtbereich (612) hergestellt wird, indem eine Beschichtung auf bestimmte Flächen des Ventilsitzes (64) aufgebracht wird und sichergestellt wird, dass wesentliche Flächen des Ventilsitzes unbeschichtet sind.

2. Brennstoffeinspritzventil nach Anspruch 1, wobei der Übergangsbereich (614) ein Bearbeitungsvolumen für ein Schleifwerkzeug bietet, um die gewählte Oberflächenbeschaffenheit auf dem Nadeldichtbereich (612) durch Schleifen der aufgetragenen Beschichtung herzustellen.
3. Brennstoffeinspritzventil nach Anspruch 2, wobei das Bearbeitungsvolumen des Übergangsbereichs (614) das Durchlaufvolumen minimiert, das dem Nadeldichtbereich (612) in Strömungsrichtung nachgelagert ist.
4. Brennstoffeinspritzventil nach Anspruch 1, wobei der Nadeldichtbereich (612) einen ersten konischen Bereich umfasst, der einen ersten Öffnungswinkel (624) definiert, und der Übergangsbereich (614) einen zweiten konischen Bereich umfasst, der einen zweiten Öffnungswinkel (626) definiert, und wobei der erste Öffnungswinkel größer als der zweite Öffnungswinkel ist.

5. Brennstoffeinspritzventil nach Anspruch 1, wobei der Übergangsbereich (614) Kavitation auslöst.
6. Brennstoffeinspritzventil nach Anspruch 1, wobei die erste, die zweite und die dritte quer verlaufende Querschnittsfläche orthogonal zur Achse (18) sind.
7. Verfahren zur Herstellung eines Brennstoffeinspritzventilsitzes (64), wobei der Ventilsitz eine in Strömungsrichtung vorgelagerte Fläche (602), eine in Strömungsrichtung nachgelagerte Fläche (604) und einen Kanal (70) umfasst, der entlang einer Achse (18) zwischen der in Strömungsrichtung vorgelagerten Fläche und der in Strömungsrichtung nachgelagerten Fläche verläuft, wobei das Verfahren folgende Schritte umfasst:

in dem Kanal Herstellen eines Bohrungsbereichs (608) nahe der in Strömungsrichtung nachgelagerten Fläche; Herstellen einer scharfen Kante an einer Kontur von der in Strömungsrichtung nachgelagerten Fläche (604) und dem Bohrungsbereich; wobei der Bohrungsbereich eine erste Querschnittsfläche aufweist, die quer zur Achse verläuft; wobei der Bohrungsbereich mit einer vorgegebenen Länge entlang der Achse verläuft und einen rechtwinkligen Kreiszylinderbereich mit einem vorgegebenen Durchmesser umfasst, und wobei ein Quotient aus der vorgegebenen Länge und dem vorgegebenen Durchmesser mindestens 0,3 beträgt;

in dem Kanal Herstellen eines Nadeldichtbereichs (612) nahe der in Strömungsrichtung vorgelagerten Fläche (602), der eine zweite Querschnittsfläche aufweist, die quer zur Achse verläuft und in einem ersten Verhältnis in einer in Strömungsrichtung nachgelagerten Richtung von einem ersten Bereich zu einer zweiten Fläche kleiner wird; und

in dem Kanal (70) Herstellen eines Übergangsbereichs (614), der so ausgelegt ist, dass er das Auslaufvolumen minimiert, das zwischen dem Bohrungsbereich (608) und dem Nadeldichtbereich (612) angeordnet ist, und der eine dritte Querschnittsfläche aufweist, die quer zur Achse verläuft und in einem zweiten Verhältnis in einer in Strömungsrichtung nachgelagerten Richtung vom zweiten Bereich zur ersten quer verlaufenden Querschnittsfläche kleiner wird; und

wobei das Herstellen des Nadeldichtbereichs (612) das Herstellen einer gewählten Oberflächenbeschaffenheit umfasst, indem eine Beschichtung auf bestimmte Flächen des Ventilsitzes (64) aufgebracht wird und sichergestellt wird, dass wesentliche Flächen des Ventilsitzes unbeschichtet sind.

8. Verfahren nach Anspruch 7, wobei das Herstellen

der gewählten Oberflächenbeschaffenheit das Bearbeiten des Nadeldichtbereichs mit dem Schleifwerkzeug umfasst.

9. Verfahren nach Anspruch 7, wobei das Herstellen des Übergangsbereichs (614) ein Bearbeitungsvolumen für das Schleifwerkzeug bietet.
10. Verfahren nach Anspruch 7, wobei das Herstellen des Dichtbereichs (612) einen ersten Öffnungswinkel (624) ausbildet, und das Herstellen des Übergangsbereichs (614) einen zweiten Öffnungswinkel (626) ausbildet, der kleiner als der erste Öffnungswinkel ist.

## Revendications

1. Injecteur de carburant comportant une entrée, une sortie et une voie de passage (16) ménageant un conduit d'écoulement de carburant de l'entrée à la sortie, l'injecteur de carburant comprenant:

une aiguille (68) déplaçable dans la voie de passage entre une première position obturant la voie de passage et une seconde position permettant l'écoulement de carburant, et un siège d'injecteur de carburant (64) en contact contigu avec l'aiguille (68) dans la première position, le siège comportant une face amont (602), une face aval (604) espacée par rapport à la face amont, et un passage (70) s'étendant suivant un axe (18) entre la face amont et la face aval, le passage définissant une partie de la voie de passage (16) et comprenant :

une partie formant orifice (608) à proximité de la face aval et une arête vive réalisée à une interface de la face aval et de la partie formant orifice, la partie formant orifice ayant une première aire de section transversale relativement à l'axe (18), la partie formant orifice s'étendant suivant l'axe sur une longueur prescrite et comprenant une section cylindrique circulaire droite ayant un diamètre prescrit, et un rapport de la longueur prescrite sur le diamètre prescrit étant au moins de 0,3 ;

une partie d'obturation par aiguille (612) à proximité de la face amont (602) et ayant une deuxième aire de section transversale relativement à l'axe qui décroît à un premier taux en direction de l'aval d'une première aire à une seconde aire, et une partie formant transition (614) configurée pour minimiser le volume creux interposée entre la partie formant orifice (608) et la partie d'obturation par aiguille (612) et

- ayant une troisième aire de section transversale relativement à l'axe (18) qui décroît à un second taux en direction de l'aval de la deuxième aire à la première aire de section transversale, 5  
dans lequel une finition choisie est réalisée sur la partie d'obturation par aiguille (612) en appliquant un revêtement sur certaines surfaces du siège (64) et en s'assurant que des surfaces critiques du siège ne sont pas revêtues. 10
2. Injecteur de carburant selon la revendication 1, dans lequel la partie formant transition (614) ménage un volume pour un outil de rodage pour réaliser la finition choisie sur la partie d'obturation par aiguille (612) en rodant le revêtement appliqué. 15
3. Injecteur de carburant selon la revendication 2, dans lequel le volume de la partie formant transition (614) minimise le volume du passage en aval de la partie d'obturation par aiguille (612). 20
4. Injecteur de carburant selon la revendication 1, dans lequel la partie d'obturation par aiguille (612) comprend une première section conique définissant un premier angle inclus (624) et la partie formant transition (614) comprend une seconde section conique définissant un second angle inclus (626), et dans lequel le premier angle inclus est plus grand que le second angle inclus. 25 30
5. Injecteur de carburant selon la revendication 1, dans lequel la partie formant transition (614) induit une cavitation. 35
6. Injecteur de carburant selon la revendication 1, dans lequel la première, la deuxième et la troisième aires de section transversale sont orthogonales à l'axe (18). 40
7. Procédé de réalisation d'un siège d'injecteur de carburant (64), le siège comportant une face amont (602), une face aval (604) et un passage (70) s'étendant suivant un axe (18) entre la face amont et la face aval, le procédé consistant à : 45
- réaliser à l'intérieur du passage une partie formant orifice (608) à proximité de la face aval, réaliser une arête vive à une interface de la face aval (604) et de la partie formant orifice, la partie formant orifice ayant une première aire de section transversale relativement à l'axe, la partie formant orifice s'étendant suivant l'axe sur une longueur prescrite et comprenant une section cylindrique circulaire droite ayant un diamètre prescrit, et un rapport de la longueur prescrite sur le diamètre prescrit étant au moins de 0,3 ; 50 55
- réaliser à l'intérieur du passage une partie d'obturation (612) à proximité de la face amont (602) et ayant une deuxième aire de section transversale relativement à l'axe qui décroît à un premier taux en direction de l'aval d'une première aire à une seconde aire, et  
réaliser à l'intérieur du passage (70) une partie formant transition (614) configurée pour minimiser le volume creux interposée entre la partie formant orifice (608) et la partie d'obturation (612) et ayant une troisième aire de section transversale relativement à l'axe qui décroît à un second taux en direction de l'aval de la seconde aire à la première aire de section transversale, et  
dans lequel la réalisation de la partie d'obturation par aiguille (612) consiste à réaliser une finition choisie en appliquant un revêtement sur certaines surfaces du siège (64) et en s'assurant que des surfaces critiques du siège ne sont pas revêtues.
8. Procédé selon la revendication 7, dans lequel la réalisation de la finition choisie consiste à roder la partie d'obturation par aiguille avec l'outil de rodage.
9. Procédé selon la revendication 7, dans lequel la réalisation de la partie formant transition (614) aménage un volume pour l'outil de rodage.
10. Procédé selon la revendication 7, dans lequel la réalisation de la partie d'obturation (612) forme un premier angle inclus (624) et la réalisation de la partie formant transition (614) forme un second angle inclus (626) qui est inférieur au premier angle inclus.




FIG. 1




Figure 2




Fig. 3




Fig. 4




Fig. 5