

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 187 901 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
02.08.2006 Bulletin 2006/31

(21) Application number: **00942965.5**

(22) Date of filing: **20.06.2000**

(51) Int Cl.:
C11D 11/00 ^(2006.01) **C11D 17/06** ^(2006.01)

(86) International application number:
PCT/US2000/016914

(87) International publication number:
WO 2000/078907 (28.12.2000 Gazette 2000/52)

(54) **PROCESSES FOR MAKING GRANULAR DETERGENT IN A FLUIDIZED BED GRANULATOR HAVING RECYCLING OF IMPROPERLY SIZED PARTICLES**

VERFAHREN ZUR HERSTELLUNG VON REINIGUNGSMITTELGRANULATEN IN EINEM WIRBELSCHICHTGRANULATOR MIT RÜCKFÜHRUNG VON UNPROPORTIONIERTEN TEILCHEN

PROCEDE DE FABRICATION DE DETERGENT GRANULAIRE DANS UN GRANULATEUR A LIT FLUIDISE DOTE D'UN RECYCLAGE POUR PARTICULES DE TAILLES IRRÉGULIÈRES

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**

(30) Priority: **21.06.1999 US 140079 P**

(43) Date of publication of application:
20.03.2002 Bulletin 2002/12

(73) Proprietor: **THE PROCTER & GAMBLE COMPANY**
Cincinnati, Ohio 45202 (US)

(72) Inventors:
• **BEIMESCH, Wayne, Edward**
Covington, KY 41015 (US)
• **CAPECI, Scott, William**
North Bend, OH 45052 (US)

- **SPONTAK, G., Gregory**
Loveland, OH 45140 (US)
- **WASSERMAN, Matthew, Israel**
Cincinnati, OH 45208 (US)
- **WELCH, Robert, Gary**
Cincinnati, OH 45231 (US)

(74) Representative: **Peet, Jillian Wendy et al**
Patent Department
Procter & Gamble Technical Centres Limited
Whitley Road
Longbenton
Newcastle Upon Tyne, NE12 9TS (GB)

(56) References cited:
US-A- 4 726 908 **US-A- 4 797 271**
US-A- 5 779 945 **US-A- 5 861 179**

EP 1 187 901 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

DescriptionFIELD OF THE INVENTION

[0001] The present invention relates to an improved process for making granular detergent compositions which have superior solubility, especially in cold temperature laundering solutions (i.e., less than about 30°C), excellent flow properties (even after storage), and aesthetics/appearance. More particularly, the present process relates to the manufacture of detergent compositions via the use of a fluidized bed granulator having recycle of improperly sized particles.

BACKGROUND OF THE INVENTION

[0002] Recently, there has been considerable interest within the detergent industry for laundry detergents which have the convenience, aesthetics and solubility of liquid laundry detergent products, but retain the cleaning performance and cost of granular detergent products. The problems, however, associated with past granular detergent compositions with regard to aesthetics, solubility, flowability after standard storage conditions and user convenience are formidable. Such problems have been exacerbated by the advent of "compact" or low dosage granular detergent products which typically do not dissolve in washing solutions as well as their liquid laundry detergent counterparts. These low dosage detergents are currently in high demand as they conserve resources and can be sold in small packages which are more convenient for consumers prior to use, but less convenient upon dispensing into the washing machine as compared to liquid laundry detergent which can be simply poured directly from the bottle as opposed to "scooped" from the box and then dispensed into the washing solution.

[0003] As mentioned, such low dosage or "compact" detergent products unfortunately experience dissolution problems, especially in cold temperature laundering solutions (i.e., less than about 30°C). More specifically, poor dissolution results in the formation of "clumps" which appear as solid white masses remaining in the washing machine or on the laundered clothes after conventional washing cycles. These "clumps" are especially prevalent under cold temperature washing conditions and/or when the order of addition to the washing machine is laundry detergent first, clothes second and water last (commonly known as the "Reverse Order Of Addition" or "ROOA"). Such undesirable "clumps" are also formed if the consumer loads the washing machine in the order of clothes, detergent and then water. Similarly, this clumping phenomenon can contribute to the incomplete dispensing of detergent in washing machines equipped with dispenser drawers or in other dispensing devices, such as a granulette. In this case, the undesired result is undissolved detergent residue in the dispensing device.

[0004] It has been found that the at least a portion of the dissolution profile of a granular detergent composition is impacted by the process used to manufacture that detergent. For instance, the dissolution profile of a detergent composition may be impacted by the uniformity of the particles in the composition with respect to both density and size of the particles. This uniformity in turn is dictated in large part by the process by which the detergent is manufactured. However, to date manufacturing processes have been largely unsatisfactory in delivering compositions of the desired uniformity.

[0005] Accordingly, the need remains for a process for the manufacture of detergent compositions which can provide compositions of the desired uniformity and as such exhibits improved solubility, is more aesthetically pleasing to consumers, has improved flowability and exhibits improved cleaning performance.

SUMMARY OF THE INVENTION

[0006] This need has been met by the present invention wherein a process for the manufacture of a detergent composition in a fluidized bed granulator with selected recycle of the improperly sized particles is provided. The present invention meets the aforementioned needs by controlling the size of the particles within the process to a greater extent than current detergent manufacturing processes. Via the present invention the amount of undersized particles or fines present in a detergent composition are reduced via the use of fluidized bed granulation and the amount of oversized particles are also reduced via the screening and re-introduction of these oversized particles to the process. The result is a detergent composition with improved solubility or dissolution in laundering solutions, especially in solutions kept at cold temperatures (i.e., less than about 30°C), is aesthetically pleasing to consumers and has improved flowability.

[0007] In accordance with a first aspect of present invention, a process for making a granular detergent composition as defined in claim 1 is provided.

The process may comprise various alternative scenarios such as re-introduction to any combination of the fluid bed or when present, to a premixer or finishing step. The oversized particles may be optionally milled or ground before re-introduction to the process. Undersized particles may be removed from the fluidized bed and re-introduced to the process such as to the premixer or fluidized bed or may be re-circulated within the fluid bed via the use of an internally recycling fluidized bed.

[0008] Accordingly, it is an advantage of the invention to provide a process for making granular detergent compositions which exhibit improved solubility, are more aesthetically pleasing to consumers, have improved flowability and exhibit improved cleaning performance. It is a further advantage of the present invention to provide a process for making a granular detergent composition wherein selected recycle of improperly sized particles is employed to provide a more uniform detergent composition.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0009] As used herein, the word "particles" means the entire size range of a detergent final product or component or the entire size range of discrete particles, agglomerates, or granules in a final detergent product or component admixture. It specifically does not refer to a size fraction (i.e., representing less than 100% of the entire size range) of any of these types of particles unless the size fraction represents 100% of a discrete particle in an admixture of particles. For each type of particle component in an admixture, the entire size range of discrete particles of that type have the same or substantially similar composition regardless of whether the particles are in contact with other particles. For agglomerated components, the agglomerates themselves are considered as discrete particles and each discrete particle may be comprised of a composite of smaller primary particles and binder compositions.

[0010] As used herein, the phrase "geometric mean particle diameter" means the geometric mass median diameter of a set of discrete particles as measured by any standard mass-based particle size measurement technique, preferably by dry sieving. As used herein, the phrase "geometric standard deviation" or "span" of a particle size distribution means the geometric breadth of the best-fitted log-normal function to the above-mentioned particle size data which can be accomplished by the ratio of the diameter of the 84.13 percentile divided by the diameter of the 50th percentile of the cumulative distribution ($D_{84.13}/D_{50}$); See Gotoh et al, *Powder Technology Handbook*, pp. 6-11, Marcel Dekker 1997.

[0011] As used herein, the phrase "builder" means any organic or inorganic material having "builder" performance in the detergency context, and specifically, organic or inorganic material capable of removing water hardness from washing solutions and/or having dispersion or peptization properties. As used herein, the term "bulk density" refers to the uncompressed, untapped powder bulk density, as measured by pouring an excess of powder sample through a funnel into a smooth metal vessel (e.g., a 500 ml volume cylinder), scraping off the excess from the heap above the rim of the vessel, measuring the remaining mass of powder and dividing the mass by the volume of the vessel.

[0012] As used herein, "composition" and "granular detergent composition" are intended to include both final products and additives/components of a detergent composition. That is, the compositions produced by the processes claimed herein may be complete laundry detergent compositions or they may be additives that are used along with other detergent ingredients for laundering fabrics and the like.

[0013] The present invention is directed toward the use of selected recycle streams of improperly sized particles to advantageously produce a detergent that is more uniform in appearance and presents improved dissolution and aesthetic features as well. Via the use of a fluidized bed to control undersized particles and screening and reintroduction of oversized particles superior detergent compositions are produced.

[0014] In general, the process of the present invention comprises the addition of a granular feed stream into a fluidized bed granulator to achieve at least partial granulation of the feed stream. Of course, one of ordinary skill in the art will recognize that multiple feed streams are possible within the scope of the present invention. The feed stream of the present invention may comprise granules of conventional detergent adjunct ingredients, wet detergent agglomerates, dry detergent agglomerates or spray-dried detergent granules. Detergent adjunct ingredients includes but is not limited to, carbonates, phosphates, sulfates, zeolites or the like. Of course, other conventionally known ingredients may be included as well. Spray-dried detergent granules include those particles which are manufactured via a conventional spray-drying technique wherein a slurry of detergent materials is prepared and sprayed downward into a upwardly flowing stream of gas to dry the particles. A dry free flowing material is produced from the process. Wet detergent agglomerates includes those particles that are manufactured via a granulation type process wherein detergent adjunct ingredients such as described above are admixed with a liquid binder material such as a surfactant or precursor thereof in a mixer or series of mixer to form granules of detergent materials. These particles are known as "wet agglomerates" until dried and as dry agglomerates upon exiting a drying and optionally a conditioning stage. The conditioning stage may include sizing, grinding and cooling stages in any combination. Granulation processes are well known in the detergent art. Some non-limiting examples include the process as described in U.S. Patent Nos. 5,489,392; 5,516,448 to Capece et al.

[0015] Accordingly, the present invention entails the introduction of both raw material ingredients to form a detergent agglomerate or the introduction of previously formed detergent granules for continued processing of the granules. In a preferred embodiment of the present invention, the granular feed stream comprises at least two of the differing types of granules such as spray-dried granules and wet or dry detergent agglomerates. In one highly preferred embodiment, the feed stream is comprised of spray-dried detergent granules, dry detergent agglomerates and detergent adjunct ingredients.

[0016] Optionally, the granular feed stream may be processed to remove particles having geometric mean particle

diameter of from 500 microns to 1500 microns with a geometric standard deviation of from 1 to 2. These "in-spec" particles can be fed directly to the resulting granular detergent composition. The processing of the feed streams can be accomplished by, for example "screening", to remove the particles that have the desired geometric mean particle diameter. By feeding these "in-spec" particles directly to the resulting granular detergent composition, the granular detergent making process is by-passed. This reduces the load on the granular detergent making equipment and increases the yield of particles within the desired size range.

[0017] The fluidized bed granulator comprises a fluid bed dryer into which a detergent binder is added to agglomerate particles within the fluid bed. As stated earlier, the fluid bed of the present invention contributes to the overall uniformity of the detergent of the present invention via the granulation of the undersized particles. Undersized or "fine particles" are defined as particles that have a geometric mean particle diameter that is less than 1.65 standard deviations below the chosen geometric mean particle diameter of the granular detergent composition at a given span or geometric standard deviation. Oversized or large particles may also exist wherein "large particles" are defined as particles that have a geometric mean particle diameter that is greater than 1.65 standard deviations above the chosen geometric mean particle diameter of the granular detergent composition at a given span or geometric standard deviation.

[0018] While not wishing to be bound by theory, it is believed that the undersized particles of the present invention are significantly reduced via the use of fluid bed granulation. Undersized particles are fluidized and circulated within the bed where they come into contact with the liquid binder material sprayed into the fluid bed. As the undersized particles circulate within the bed at a higher rate than other particles, these undersized particles come into contact with the binder material at a higher rate. Accordingly, the undersized particles are agglomerated or bound to other particles thereby reducing the total number of undersized particles. Via the use of fluidized bed granulation, the amount of undersized particles are reduced by as much as 10% more preferably 25% than conventional detergent processing techniques.

[0019] Undersized particles remaining after the fluid bed granulation step of the present invention may then be separated from the granular detergent during the process and re-introduced to the process. The undersized particles may be extracted from the process via elutriation from the exhaust gases of the fluidized bed or via other conventional processing means such as an air lift or screen. These undersized particles may then be added to any unit operation in the process. These unit operation may include a premixer or series of premixers, fluid bed granulator, fluid bed coater, fluid bed or bulk heat exchanger for cooling, grinder or milling equipment for oversize and screens used for sieving. In this manner, the process may be controlled for optimum reduction of undersized particles by selectively re-introducing the particles to various processing steps where they may be agglomerated to build size of the particles. Alternatively, undersized particles are controlled via the use of an internally recirculating fluidized bed wherein undersized particles are captured before exiting the fluidized bed and remain within the bed until agglomerated to acceptable sizes.

[0020] Preferably, the fluid bed granulator of the present invention has multiple internal "stages" or "zones". A stage or zone is any discrete area within the fluid bed, and these terms are used interchangeably herein. The process conditions within a stage may be different or similar to the other stages in the fluid bed. It is understood that two adjacent fluid beds are equivalent to a single bed having multiple stages. The granular feed stream is at least partially agglomerated within the fluid bed via the addition of a liquid binder material to the fluid bed. The granular feed stream or streams can be sized and split if desired and added at different stages, depending on, for example, the particle size and moisture level of the feed stream. Feeding different streams to different stages can minimize the load on the fluid bed, and optimize the particle size and shape as defined herein. Liquids are typically added to a bed through nozzles above or within the product flowing through the bed, and the nozzles can spray upward, across or downward depending on their position within the fluid bed. Manufacturers of such fluidized beds include Niro, Bepex, Spray Systems and Glatt.

[0021] The liquid binder material is added for purposes of enhancing granulation by providing a "binding" or "sticking" agent for the detergent components such as undersized particles. The binder is preferably selected from the group consisting of water, anionic surfactants and their precursors, nonionic surfactants, polyethylene glycol, polyvinyl pyrrolidone, polyacrylates, citric acid and mixtures thereof. Other suitable binder materials including those listed herein are described in Beerse et al, U.S. Patent No. 5,108,646 (Procter & Gamble Co.).

[0022] Typical conditions within a fluidized bed granulator of the present invention include (i) from 1 to 20 minutes of mean residence time, (ii) from 100 to 600 mm of depth of unfluidized bed, (iii) a droplet spray size of less than 2 times the particles size, preferably not more than 100, more preferably not more 50 micron, (iv) from 150 to 1600 mm of spray height from the fluid bed plate, (v) from 0.1 to 4.0 m/s of fluidizing velocity, preferably 1.0 to 3.0 m/s and (vi) from 12 to 200 °C of bed temperature, more preferably 15-100 °C. Once again, one of ordinary skill in the art will recognize that the conditions in the fluid bed may vary depending on a number of factors.

[0023] The fluid bed granulator of the present invention is preferably operated such that it has a flux number of from 2.5 to 4.5. Flux number (FN) is a ratio of the excess velocity (U_e) of the fluidization gas and the particle density (ρ_p) relative to the mass flux (q_{liq}) of the liquid sprayed into the bed at a normalized distance (D_0) of the spraying device. The flux number provides an estimation of the operating parameters of a fluidized bed to control granulation within the bed. The flux number may be expressed either as the mass flux as determined by the following formula:

$$FN_m = \log_{10}[\{P_p U_e\}/q_{liq}]$$

or as the volume flux as determined by the formula:

$$FN_v = \log_{10}[\{U_e\}/q_{vliq}]$$

where q_{vliq} is the volume of spray into the fluid bed. Calculation of the flux number and a description of its usefulness is fully described in WO 98/58046.

[0024] In addition, the fluid bed granulator of the present invention is operated such that it has a Stokes number of less than one (1), more preferably from 0.1 to 0.5. The Stokes number is a measure of particle coalescence for describing the degree of mixing or agglomerating occurring to particles in a piece of equipment such as the fluid bed. The Stokes number is measured by the formula:

$$\text{Stokes number} = 4pvd/9u$$

wherein p is the apparent particle density, v is the excess velocity, d is the mean particle diameter and u is the viscosity of the binder. The Stokes number and a description of its usefulness is described in detail in WO 99/03964.

[0025] Optionally, the feed stream of present invention can be processed in at least one pre-mixer before the addition of the feed stream to the fluidized bed granulator to form detergent premix. The pre-mixer may be one or a series of low, moderate or high speed mixers as is conventionally known in the art. The particular mixer used in the present process should preferably include pulverizing or grinding and granulation tools although such tools are not required. To that end, it has been found that the preferred process of the present invention employs as a pre-mixer a Lodige KM™ (Ploughshare) moderate speed mixer, Lodige CB™ high speed mixer, or mixers made by Fukae, Drais, Schugi or similar brand mixer. The Lodige KM™ (Ploughshare) moderate speed mixer, which is a preferred mixer for use in the present invention, comprises a horizontal, hollow static cylinder having a centrally mounted rotating shaft around which several plough-shaped blades are attached. Preferably, the shaft rotates at a speed of from 15 rpm to 140 rpm, more preferably from 80 rpm to 120 rpm. The grinding or pulverizing is accomplished by cutters, generally smaller in size than the rotating shaft, which preferably operate at 3600 rpm. Other mixers similar in nature which are suitable for use in the process include the Lodige Ploughshare™ mixer and the Drais® K-T 160 mixer. Generally, in the process of the present invention, the shear will be no greater than the shear produced by a Lodige KM mixer with a tip speed of the ploughs below 30 m/s or even below 10 m/s or even lower.

[0026] The detergent agglomerates from the fluidized bed granulator may be further processed, if necessary to dry or cool the agglomerated particles.

[0027] Preferably, the mean residence time of the various detergent ingredients in the low, moderate or high speed mixer is preferably in range from 0.1 seconds to 30 minutes, most preferably the residence time is 0.1 seconds to 5 minutes. In this way, the density of the resulting detergent agglomerates is at the desired level.

[0028] The processes of this invention may comprise the step of spraying an additional binder material as hereinbefore described in the pre-mixer or series of pre-mixers in order to enhance granulation of the various materials in the feed stream.

[0029] In an optional embodiment of the present invention, the process may additionally include a finishing step including but not limited to, admix and/or spray-on of additional ingredients such as enzymes, bleach perfumes, etc or a packaging step.

[0030] Upon exiting from the fluid bed granulator (or any suitable stage therein), the detergent agglomerates may be sized to separate oversized particles from detergent agglomerates in the desired range. The oversized particles may be sized according to conventionally known technology such as via screening. The oversized particles are then re-introduced into the process at appropriate locations in order to achieve the more uniform detergent composition as disclosed herein. Via the control of oversized particles in conjunction with the undersized particles as described hereinbefore, a detergent process for producing a superior performing detergent composition is controlled. As mentioned previously, the control of these oversized particles leads to better overall properties of the composition such as particle

density and span as described herein which contribute to the overall superiority of the detergent composition.

[0031] Preferably, but by no means required, the oversized particles may be optionally milled or ground before re-introduction to the process. The milling or grinding may be preformed in conventional grinding equipment as is well known in the art of detergent processing. The oversized particles may be re-introduced to the process to any desired stage suitable for control of the process such as the fluid bed, the pre-mixer or series of pre-mixers or the finishing step, when present. The oversized particle stream may be split and particles re-introduced into a combination of locations disclosed above. In preferred embodiments of the present invention, the oversized particles are passed through a grinding step where the ground product is once again sized and acceptable particles passed through to a coating step as described herein or to the resulting final detergent composition while the improperly sized particles are re-introduced to process as described above. In preferred embodiments, the oversized particles are re-introduced into the pre-mixer or series of pre-mixers.

[0032] In an optional embodiment, the feed stream may be sized as well before entering the fluid bed granulator. When an optional pre-mixer or series of pre-mixers is present, the sizing may occur before or after any or all of the pre-mixers. Thus, oversized particles may be removed at any stage of the process. These oversized particles may then be combined for re-introduction into the process, particularly after a preferred grinding or milling step. Of course, one of ordinary skill in the art will recognize that by re-introduction into a mixer of the present invention for both undersized and oversized particles, it is intended to include re-introduction to the feed streams entering the mixer or granulator in question as well re-introduction directly into the mixer or granulator.

[0033] The particles of this invention may be further processed in an optional step by adding a coating agent to improve the particle color, increase the particle "whiteness", or improve the particle flowability after the particles exit the mixer or the dryer to obtain the granular detergent composition produced by the present invention. Coating agents herein may include dry inorganic materials such as zeolites, carbonates, sulfates etc. Alternatively, the coating process may include the spray of a liquid coating agents such as anionic surfactant, slurries or solutions of inorganic or organic salts, and various other materials. Those skilled in the art will appreciate that a wide variety of methods may be used to dry as well as cool the exiting detergent particles without departing from the scope of the invention. Since the mixer can be operated at relatively low temperatures, the need for cooling apparatus is not required by the present process, which thereby further reduces manufacturing costs of the final product.

[0034] Another optional processing step includes continuously adding a coating agent such as zeolites and fumed silica to the mixer to facilitate free flowability of the resulting detergent particles and to prevent over granulation.

[0035] The granular detergent composition achieves the desired benefits of solubility, improved aesthetics and flowability via the process of the present invention and the control or selection of the geometric mean particle diameter of certain levels of particles in the composition. By "improved aesthetics", it is meant that the consumer prefers a granular detergent product which has a more uniform appearance of particles as opposed to past granular detergent products which contained particles of varying size and composition. To that end, at least 50%, more preferably at least 75%, even more preferably at least 90%, and most preferably at least 95%, by weight of the total particles in the detergent product, have the selected mean particle size diameter. In this way, a substantial portion of the granular detergent product will have the uniform size so as to provide the aesthetic appearance desired by consumers.

[0036] Preferably, the geometric mean particle diameter of the particles is from 500 microns to 1500 microns, more preferably from 600 microns to 1200 microns, and most preferably from 600 microns to 1000 microns. The particle size distribution is defined by a relative tight geometric standard deviation or "span" so as not to have too many particles outside of the target size. Accordingly, the geometric standard deviation is preferably from 1 to 2, more preferably is from 1.0 to 1.7, even more preferably is from 1.0 to 1.4, and most preferably is from 1.0 to 1.2. The bulk density of the particles is preferably in the range of from 400 g/L to 850g/L, more preferably from 550 g/l to 800 g/l and even more preferably from 600 g/L to 750 g/L. As can be recognized by one of ordinary skill in the art, the control of improperly sized particles via the present invention contributes to the tight span of the composition produced by the present invention.

[0037] While not intending to be bound by theory, it is believed that solubility and compositional quality are enhanced as a result of the particles in the detergent composition being more of the same size. Specifically, as a result of the particles being more uniform in size, the actual "contact points" among the particles in the detergent composition is reduced which, in turn, reduces the "bridging effect" commonly associated with the "lump-gel" dissolution difficulties of granular detergent compositions. Previous granular detergent compositions contained particles of varying sizes which leads to more contact points among the particles. For example, a large particle could have many smaller particles in contact with it rendering the particle site ripe for lump-gel formation. The level and uniform size of the particles in the granular detergent composition of the present invention avoids such problems.

[0038] By "a portion" of the particles, it is meant that at least some particles in the detergent composition contain a deterative surfactant and/or a detergent builder to provide the fundamental building blocks of a typical detergent composition. The various surfactants and builders as well as their respective levels in the composition are set forth hereinafter. Typically, the detergent composition will contain from 1% to 50% by weight of a deterative surfactant and from 1% to 75% by weight of a detergent builder.

[0039] A particularly important attribute of detergent powders is color. Color is usually measured on a Hunter Colorimeter and reported as three parameters "L", "a" and "b". Of particular relevance to the powdered detergent consumer is the whiteness of the powder determined by the equation L-3b. In general, whiteness values below 60% are considered poor. Whiteness can be improved by a number of means known to those of ordinary skill in the art. For example, coating granules with Titanium Dioxide.

[0040] Preferably the granular detergents of this invention have whitenesses of 60-100, preferably 75-100, more preferably, 85-100 and most preferably 92-100. Also preferred are granular detergents where all components have a whiteness difference (maximum - minimum) of less than 40, preferably less than 30, more preferably less than 20 and most preferably less than 10.

[0041] Another important attribute of the granular detergent products of this invention is the shape of the individual particles. Shape can be measured in a number of different ways known to those of ordinary skill in the art. One such method is using optical microscopy with Optimus (V5.0) image analysis software. Important calculated parameters are:

"Circularity" which is defined as (measured perimeter length of the particle image)²/(measured area of the particle image). The circularity of a perfectly smooth sphere (minimum circularity) is 12.57; and

"Aspect Ratio" which is defined as the length/width of the particle image.

[0042] Each of these attributes is important and can be averaged over the bulk granular detergent composition. And the combination of the two parameters as defined by the product of the parameters is important as well (i.e. both must be controlled to get a product with good appearance). Preferably, the granular detergent compositions produced by the process of the present invention have circularities less than 50, preferably less than 30, more preferably less than 23, most preferably less than 18. Also preferred are granular detergent compositions with aspect ratios less than 2, preferably less than 1.5, more preferably less than 1.3 most preferably less than 1.2.

[0043] Additionally, it is preferred to have a uniform distribution of shapes among the particles in the composition. Specifically, the granular detergent compositions of this invention have a standard deviation of the number distribution of circularity less than 20, that is preferably less than 10, more preferably less than 7 most preferably less than 4. And the standard deviation of the number distribution of aspect ratios is preferably less than 1, more preferably less than 0.5, even more preferably less than 0.3, most preferably less than 0.2.

[0044] In an especially preferred process of the present invention, granular detergent compositions are produced wherein the product of circularity and aspect ratio is less than 100, preferably less than 50, more preferably less than 30, and most preferably less than 20. Also preferred are granular detergent compositions with the standard deviation of the number distribution of the product of circularity and aspect ratio of less than 45, preferably less than 20, more preferably less than 7 most preferably less than 2.

Detergent Components

[0045] The detergent composition of the present invention, preferably include surfactants such as anionic, nonionic, zwitterionic, ampholytic and cationic classes and compatible mixtures thereof. Detergent surfactants are described in U.S. Patent 3,664,961. Norris, issued May 23, 1972, and in U.S. Patent 3,919,578, Laughlin et al., issued December 30, 1975). Cationic surfactants include those described in U.S. Patent 4,222,905, Cockrell, issued September 16, 1980, and in U.S. Patent 4,239,659, Murphy, issued December 16, 1980.

[0046] Nonlimiting examples of surfactant systems include the conventional C₁₁-C₁₈ alkyl benzene sulfonates ("LAS") and primary, branched-chain and random C₁₀-C₂₀ alkyl sulfates ("AS"), the C₁₀-C₁₈ secondary (2,3) alkyl sulfates of the formula CH₃(CH₂)_x(CHOSO₃⁻M⁺) CH₃ and CH₃(CH₂)_y(CHOSO₃⁻M⁺) CH₂CH₃ where x and (y + 1) are integers of at least 7, preferably at least 9, and M is a water-solubilizing cation, especially sodium, unsaturated sulfates such as oleyl sulfate, the C₁₀-C₁₈ alkyl alkoxy sulfates ("AE_xS"; especially EO 1-7 ethoxysulfates), C₁₀-C₁₈ alkyl alkoxy carboxylates (especially the EO 1-5 ethoxycarboxylates), the C₁₀-18 glycerol ethers, the C₁₀-C₁₈ alkyl polyglycosides and their corresponding sulfated polyglycosides, and C₁₂-C₁₈ alpha-sulfonated fatty acid esters. If desired, the conventional nonionic and amphoteric surfactants such as the C₁₂-C₁₈ alkyl ethoxylates ("AE") including the so-called narrow peaked alkyl ethoxylates and C₆-C₁₂ alkyl phenol alkoxyates (especially ethoxylates and mixed ethoxy/propoxy), C₁₂-C₁₈ betaines and sulfobetaines ("sultaines"), C₁₀-C₁₈ amine oxides, and the like, can also be included in the surfactant system. The C₁₀-C₁₈ N-alkyl polyhydroxy fatty acid amides can also be used. Typical examples include the C₁₂-C₁₈ N-methylglucamides. See WO 9,206,154. Other sugar-derived surfactants include the N-alkoxy polyhydroxy fatty acid amides, such as C₁₀-C₁₈ N-(3-methoxypropyl) glucamide. The N-propyl through N-hexyl C₁₂-C₁₈ glucamides can be used for low sudsing. C₁₀-C₂₀ conventional soaps may also be used. If high sudsing is desired, the branched-chain C₁₀-C₁₆ soaps may be used. Mixtures of anionic and nonionic surfactants are especially useful. Other conventional useful surfactants are listed in standard texts.

[0047] The detergent composition can, and preferably does, include a detergent builder. Builders are generally selected

from the various water-soluble, alkali metal, ammonium or substituted ammonium phosphates, polyphosphates, phosphonates, polyphosphonates, carbonates, silicates, borates, polyhydroxy sulfonates, polyacetates, carboxylates, and polycarboxylates. Preferred are the alkali metal, especially sodium, salts of the above. Preferred for use herein are the phosphates, carbonates, silicates, C₁₀₋₁₈ fatty acids, polycarboxylates, and mixtures thereof. More preferred are sodium tripolyphosphate; tetrasodium pyrophosphate; citrate, tartrate mono- and di-succinates, sodium silicate, and mixtures thereof (see below).

[0048] Specific examples of inorganic phosphate builders are sodium and potassium tripolyphosphate, pyrophosphate, polymeric metaphosphate having a degree of polymerization of from 6 to 21, and orthophosphates. Examples of polyphosphonate builders are the sodium and potassium salts of ethylene diphosphonic acid, the sodium and potassium salts of ethane 1-hydroxy-1, 1-phosphonic acid and the sodium and potassium salts of ethane, 1,1,2-triphosphonic acid. Other phosphorus builder compounds are disclosed in U.S. Patents 3,159,581; 3,213,030; 3,422,021; 3,422,137; 3,400,176 and 3,400,148.

[0049] Examples of nonphosphorus, inorganic builders are sodium and potassium carbonate, bicarbonate, sesquicarbonate, tetraborate decahydrate, and silicates having a weight ratio of SiO₂ to alkali metal oxide of from 0.5 to 4.0, preferably from 1.0 to 2.4. Water-soluble, nonphosphorus organic builders useful herein include the various alkali metal, ammonium and substituted ammonium polyacetates, carboxylates, polycarboxylates and polyhydroxy sulfonates. Examples of polyacetate and polycarboxylate builders are the sodium, potassium, lithium, ammonium and substituted ammonium salts of ethylene diamine tetraacetic acid, nitrilotriacetic acid, oxydisuccinic acid, mellitic acid, benzene polycarboxylic acids, and citric acid.

[0050] Polymeric polycarboxylate builders are set forth in U.S. Patent 3,308,067, Diehl, issued March 7, 1967. Such materials include the water-soluble salts of homo- and copolymers of aliphatic carboxylic acids such as maleic acid, itaconic acid, mesaconic acid, fumaric acid, aconitic acid, citraconic acid and methylenemalononic acid. Some of these materials are useful as the water-soluble anionic polymer as hereinafter described, but only if in intimate admixture with the nonsoap anionic surfactant.

[0051] Other suitable polycarboxylates for use herein are the polyacetal carboxylates described in U.S. Patent 4,144,226, issued March 13, 1979 to Crutchfield et al., and U.S. Patent 4,246,495, issued March 27, 1979 to Crutchfield et al.. These polyacetal carboxylates can be prepared by bringing together under polymerization conditions an ester of glyoxylic acid and a polymerization initiator. The resulting polyacetal carboxylate ester is then attached to chemically stable end groups to stabilize the polyacetal carboxylate against rapid depolymerization in alkaline solution, converted to the corresponding salt, and added to a detergent composition. Particularly preferred polycarboxylate builders are the ether carboxylate builder compositions comprising a combination of tartrate mannosuccinate and tartrate disuccinate described in U.S. Patent 4,663,071, Bush et al., issued May 5, 1987.

[0052] Water-soluble silicate solids represented by the formula SiO₂•M₂O. M being an alkali metal, and having a SiO₂: M₂O weight ratio of from 0.5 to 4.0. are useful salts in the detergent granules of the invention at levels of from 2% to 15% on an anhydrous weight basis, preferably from 3% to 8%. Anhydrous or hydrated particulate silicate can be utilized, as well.

[0053] Any number of additional ingredients can also be included as components in the granular detergent composition. These include other detergency builders, bleaches, bleach activators, suds boosters or suds suppressors, anti-tarnish and anti-corrosion agents, soil suspending agents, soil release agents, germicides, pH adjusting agents, nonbuilder alkalinity sources, chelating agents, smectite clays, enzymes, enzyme-stabilizing agents and perfumes. See U.S. Patent 3,936,537, issued February 3, 1976 to Baskerville, Jr. et al..

[0054] Bleaching agents and activators are described in U.S. Patent 4,412,934, Chung et al., issued November 1, 1983, and in U.S. Patent 4,483,783, Hartman, issued November 20, 1984. Chelating agents are also described in U.S. Patent 4,663,071, Bush et al., from Column 17, line 54 through Column 18, line 68, incorporated herein by reference. Suds modifiers are also optional ingredients and are described in U.S. Patents 3,933,672, issued January 20, 1976 to Bartoletta et al., and 4,136,045, issued January 23, 1979 to Gault et al..

[0055] Suitable smectite clays for use herein are described in U.S. Patent 4,762,645, Tucker et al., issued August 9, 1988, Column 6, line 3 through Column 7, line 24. Suitable additional detergency builders for use herein are enumerated in the Baskerville patent, Column 13, line 54 through Column 16, line 16, and in U.S. Patent 4,663,071, Bush et al., issued May 5, 1987.

EXAMPLES

[0056] The following examples are presented for illustrative purposes only and are not to be construed as limiting the scope of the appended claims in any way.

EXAMPLE 1.

[0057] This example illustrates a process according to the present invention which produces uniform, free flowing detergent granules with good dissolution profiles. Two feed streams of spray dried granules and dry agglomerates are continuously fed to a Lodige KM-600 moderate speed mixer at a rate of 600 Kg/hr at equal parts. 50 kg/hr of a solution of PEG 4000, 35 wt. % solids is added to the KM. The resulting granules are fed into a fluid bed granulator, dryer, cooler with a gas fluidization velocity of approximately 1.5 m/s². An additional 50 kg/hr of PEG 4000, 35 wt. % solids is sprayed in the fluid bed. The fluid bed is operated with a superficial velocity of 2.0 m/s² at the plate and a disengagement velocity of 1.4 m/s². Approximately, 50 kg/hr of undersized material is elutriated in the fluid bed, collected in a baghouse and re-introduced to the KM-600 pre-mixer. Following the fluid bed, the product is passed through a Morgensen screener set up to remove particle larger than 1200 microns. The oversized particles are then ground in a mill and returned to the fluid bed granulator. The resulting product has a geometric mean particle diameter of 600 microns and a span of 1.4.

[0058] Having thus described the invention in detail, it will be obvious to those skilled in the art that various changes may be made without departing from the scope of the invention and the invention is not to be considered limited to what is described in the specification.

Claims

1. A process for making a granular detergent composition **characterized by** the steps of:

- a) providing at least one granular feed stream;
- b) passing said granular feed stream into a fluidized bed granulator, wherein the fluidized bed granulator is operated at a Stokes Number of less than one, and wherein the conditions in the fluid bed granulator include:

- (i) from 1 to 20 minutes of mean residence time;
- (ii) from 100 to 600 mm of depth of unfluidized bed;
- (iii) a droplet spray size of less than 2 times the particles size;
- (iv) from 150 to 1600 mm of spray height from the fluid bed plate;
- (v) from 1.0 to 3.0 m/s of fluidizing velocity; and
- (vi) from 15 to 150°C of bed temperature;

c) at least partially agglomerating said feed stream in said fluidized bed granulator to form detergent agglomerates via the addition of a liquid binder material to the fluid bed;

- d) sizing said detergent agglomerates to separate oversized particles from said detergent agglomerates; and
- e) re-introducing said oversized particles to said process,

wherein the resultant particles have a geometric mean particle diameter of from 600 micrometers to 1,000 micrometers, and have a particle size distribution such that the geometric standard deviation is from 1.0 to 1.2.

2. A process according to Claim 1, further **characterized by** the step of milling said oversized particles before re-introduction into said process.

3. A process according to any of Claims 1-2, wherein said oversized particles are re-introduced into any unit operation in said process or into said fluid bed granulator.

4. A process according to any of Claims 1-3, further **characterized by** the step of passing said granular feed stream through at least one pre-mixer before introduction into said fluid bed granulator and re-introducing at least a portion of said undersized particles to said at least one pre-mixer.

5. A process according to any of Claims 1-4, wherein said fluidized bed granulator is an internally re-circulating fluid bed and undersized particles are re-circulated internally within the fluidized bed.

6. A process according to any of Claims 1-5, further **characterized by** the step of screening said granular feed stream upon exiting said pre-mixer to separate oversized particles and re-introducing said oversized particles to the process.

7. A process according to any of Claims 1-6, further **characterized by** the step of passing said granular feed stream through at least two pre-mixers, screening said feed streams upon exiting either or both of said pre-mixers to separate

oversized particles and re-introducing at least a portion of said oversized particles in either or both of said pre-mixers.

8. A process according to any of Claims 1-7, wherein said fluidized bed granulator is operated at a flux number within the range of from 2.5 to 4.5.

Patentansprüche

1. Verfahren zur Herstellung einer granulösen Waschmittelzusammensetzung, **gekennzeichnet durch** die folgenden Schritte:

- a) Bereitstellen mindestens eines granulösen Zulaufs;
- b) Leiten des granulösen Zulaufs in einen Fließbettgranulator, wobei der Fließbettgranulator mit einer Stokes-Zahl von weniger als eins betrieben wird und wobei die Bedingungen in dem Fließbettgranulator Folgendes einschließen:

- (i) eine mittlere Verweilzeit von 1 bis 20 Minuten;
- (ii) eine Tiefe des nicht fluidisierten Betts von 100 bis 600 mm;
- (iii) eine Tröpfchensprühgröße von weniger als dem 2-fachen der Teilchengröße;
- (iv) eine Sprühhöhe von der Fließbettplatte von 150 bis 1 600 mm;
- (v) eine Wirbelgeschwindigkeit von 1,0 bis 3,0 m/s; und
- (vi) eine Betttemperatur von 15 bis 150 °C;

- c) mindestens teilweises Agglomerieren des Zulaufs in dem Fließbettgranulator zur Bildung von Waschmittelagglomeraten **durch** Zugabe eines flüssigen Bindemittelmaterials zu dem Fließbett;
- d) Bestimmung der Größe der Waschmittelagglomerate, um zu große Teilchen von den Waschmittelagglomeraten zu trennen; und
- e) Wiedereinführen der zu großen Teilchen in das Verfahren,

wobei die resultierenden Teilchen einen mittleren geometrischen Teilchendurchmesser von 600 Mikrometern bis 1 000 Mikrometern aufweisen und eine solche Teilchengrößenverteilung aufweisen, dass die geometrische Standardabweichung von 1,0 bis 1,2 beträgt.

2. Verfahren nach Anspruch 1, ferner **gekennzeichnet durch** den Schritt des Mahlens der zu großen Teilchen vor der Wiedereinführung in das Verfahren.

3. Verfahren nach einem der Ansprüche 1-2, wobei die zu großen Teilchen in eine beliebige Grundoperation in dem Verfahren oder in den Fließbettgranulator wieder eingeführt werden.

4. Verfahren nach einem der Ansprüche 1-3, ferner **gekennzeichnet durch** den Schritt des Leitens des granulösen Zulaufs **durch** mindestens einen Vormischer vor der Einführung in den Fließbettgranulator und des Wiedereinführens mindestens eines Teils der zu kleinen Teilchen in den mindestens einen Vormischer.

5. Verfahren nach einem der Ansprüche 1-4, wobei der Fließbettgranulator ein intern rezirkulierendes Fließbett ist und zu kleine Partikel innerhalb des Fließbetts intern rezirkuliert werden.

6. Verfahren nach einem der Ansprüche 1-5, ferner **gekennzeichnet durch** den Schritt des Siebens des granulösen Zulaufs beim Austreten aus dem Vormischer, um zu große Teilchen abzutrennen, und des Wiedereinführens der zu großen Teilchen in das Verfahren.

7. Verfahren nach einem der Ansprüche 1-6, ferner **gekennzeichnet durch** den Schritt des Leitens des granulösen Zulaufs **durch** mindestens zwei Vormischer, des Siebens der Zuläufe beim Austreten aus einem oder beiden der Vormischer, um zu große Teilchen abzutrennen, und des Wiedereinführens mindestens eines Teils der zu großen Teilchen in einen oder beide der Vormischer.

8. Verfahren nach einem der Ansprüche 1-7, wobei der Fließbettgranulator mit einer Flusszahl innerhalb des Bereichs von 2,5 bis 4,5 betrieben wird.

Revendications

1. Processus de fabrication d'une composition détergente granulaire, **caractérisé par** les étapes consistant à:

- a) fournir au moins un courant d'alimentation granulaire;
- b) faire passer ledit courant d'alimentation granulaire dans un granulateur à lit fluidisé, où le granulateur à lit fluidisé est utilisé à un nombre de Stokes de plus d'un, et où les conditions dans le granulateur à lit fluidisé incluent:

- (i) de 1 à 20 minutes de temps de séjour moyen;
- (ii) de 100 à 600 mm de profondeur de lit fluidisé;
- (iii) une taille de pulvérisation des gouttelettes de moins de 2 fois la taille des particules;
- (iv) de 150 à 1600 mm de hauteur de pulvérisation depuis la plaque de lit fluidisé;
- (v) de 1,0 à 3,0 m/s de vitesse de fluidisation; et
- (vi) de 15 à 150 °C de température du lit;

- c) agglomérer au moins partiellement ledit courant d'alimentation dans ledit granulateur à lit fluidisé pour former des agglomérats détergents via l'addition d'un matériau liant liquide au lit fluidisé;
- d) calibrer lesdits agglomérats détergents pour séparer les particules surdimensionnées desdits agglomérats détergents; et
- e) réintroduire lesdites particules surdimensionnées dans ledit processus.

dans lequel les particules obtenues ont un diamètre moyen géométrique de particules allant de 600 micromètres à 1000 micromètres, et ont une granulométrie telle que l'écart-type géométrique va de 1,0 à 1,2.

2. Processus selon la revendication 1, **caractérisé en outre par** l'étape consistant à broyer lesdites particules surdimensionnées avant la réintroduction dans ledit processus.

3. Processus selon l'une quelconque des revendications 1 à 2, dans lequel lesdites particules surdimensionnées sont réintroduites au cours de n'importe quelle opération unitaire dans ledit processus ou dans ledit granulateur à lit fluidisé.

4. Processus selon l'une quelconque des revendications 1 à 3, **caractérisé en outre par** l'étape consistant à faire passer ledit courant d'alimentation granulaire à travers au moins un prémélangeur avant l'introduction dans ledit granulateur à lit fluidisé et à réintroduire au moins une partie desdites particules sous-dimensionnées dans ledit au moins un prémélangeur.

5. Processus selon l'une quelconque des revendications 1 à 4, dans lequel ledit granulateur à lit fluidisé est un lit fluidisé à recyclage interne et les particules sous-dimensionnées sont recyclées de manière interne dans le lit fluidisé.

6. Processus selon l'une quelconque des revendications 1 à 5, **caractérisé en outre par** l'étape consistant à cribler ledit courant d'alimentation granulaire lors de la sortie dudit prémélangeur pour séparer les particules surdimensionnées et à réintroduire lesdites particules surdimensionnées dans le processus.

7. Processus selon l'une quelconque des revendications 1 à 6, **caractérisé en outre par** l'étape consistant à faire passer le courant d'alimentation granulaire à travers au moins deux prémélangeurs, à cribler lesdits courants d'alimentation lors de la sortie de l'un ou des deux desdits prémélangeurs pour séparer les particules surdimensionnées et à réintroduire au moins une partie desdites particules surdimensionnées dans l'un ou les deux desdits prémélangeurs.

8. Processus selon l'une quelconque des revendications 1 à 7, dans lequel ledit granulateur à lit fluidisé est utilisé à un nombre de flux dans la gamme de 2,5 à 4,5.