(11) **EP 1 236 883 A3**

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3: **26.11.2003 Bulletin 2003/48**

(51) Int Cl.⁷: **F02M 47/02**, F02M 63/00

(43) Date of publication A2: **04.09.2002 Bulletin 2002/36**

(21) Application number: 02251468.1

(22) Date of filing: 01.03.2002

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU

MC NL PT SE TR

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 02.03.2001 GB 0105193

(71) Applicant: **Delphi Technologies**, **Inc. Troy**, **MI 48007 (US)**

(72) Inventor: Stringfellow, Christopher Sittingbourne, Kent ME10 4TY (GB)


(74) Representative: Keltie, David Arthur et al David Keltie Associates Fleet Place House 2 Fleet Place London EC4M 7ET (GB)

(54) Fuel system

(57) A fuel system comprising a fuel injector (10) having a delivery chamber (22) which is arranged to receive fuel from a source (34) of high pressure fuel and from which fuel is delivered to a combustion space upon initiation of injection, comprising first and second control chambers (26, 44) for receiving a control fluid, a three way control valve arrangement (32) which is operable to control fluid pressure within the first control chamber (26) so as to control fuel injection timing, and to control fluid pressure within the second chamber (44), and a shut-off valve arrangement (46) operable in response to fluid pressure variations within the second control chamber (44) so as to control the flow of fuel between the

source (34) of high pressure fuel and the delivery chamber (22) of the injector. The three way control valve arrangement (32) is actuable between a first position in which the first control chamber (26) communicates with a source (34; 61) of control fluid at relatively high pressure and a second position in which the first control chamber (26) communicates with a low pressure control fluid reservoir (38; 60).

The invention provides the advantage that leakage of fuel into the engine cylinder or other combustion space of the associated engine is reduced as the flow of high pressure fuel into the delivery chamber (22) is terminated between successive injections of fuel.





EUROPEAN SEARCH REPORT

Application Number

EP 02 25 1468

Category	Citation of document with indication	on, where appropriate,	Relevant	CLASSIFICATION OF THE	
X	of relevant passages DE 27 59 255 A (BOSCH (12 July 1979 (1979-07-17 page 9, line 15 - page 15 page 1	12)	1-4,8	F02M47/02 F02M63/00	
A	EP 1 036 931 A (DELPHI 20 September 2000 (2000 * paragraph [0011] - pa figure 1 *	9-09-20)	1,2,6-8		
A	DE 196 12 721 A (AVL VI MESSTECH) 2 October 199 * abstract; figures 2,4	96 (1996-10-02)	1,3-8		
				TECHNICAL FIELDS SEARCHED (Int.Cl.7)	
				F02M	
	The present search report has been d	rawn up for all claims Date of completion of the search		Examiner	
MUNICH		6 October 2003	Ko1	land, U	
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background		E : earlier patent d after the filing d D : document cited L : document cited	T: theory or principle underlying the in E: earlier patent document, but publish after the filing date D: document cited in the application L: document cited for other reasons		

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 02 25 1468

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-10-2003

	Patent documer cited in search rep		Publication date		Patent fam member(s	ily s)	Publication date
DE	2759255	Α	12-07-1979	DE	2759255	A1	12-07-197
EP	1036931	Α	20-09-2000	EP US	1036931 2002148905		20-09-200 17-10-200
DE	19612721	Α	02-10-1996	AT DE			25-08-199 02-10-199
			Official Journal of the E				