



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 269 838 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**
Note: Bibliography reflects the latest situation

(15) Correction information:
Corrected version no 1 (W1 A2)
INID code(s) 30

(51) Int Cl.7: **A01K 89/00**

(48) Corrigendum issued on:
02.04.2003 Bulletin 2003/14

(43) Date of publication:
02.01.2003 Bulletin 2003/01

(21) Application number: **02394057.0**

(22) Date of filing: **07.05.2002**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(71) Applicant: **Shimano Inc.**
Osaka 590-8577 (JP)

(72) Inventor: **Furomoto, Yoshiyuki**
Kishiwada-shi, Osaka 596-0814 (JP)

(30) Priority: **18.05.2001 JP 2001148818**
18.05.2001 JP 2001148817
18.05.2001 JP 2001148816

(74) Representative: **Purdy, Hugh Barry et al**
Murgitroyd & Company,
373 Scotland Street
Glasgow G5 8QA (GB)

(54) **Spinning-reel spool**

(57) A spool (4,104) has drag mechanism (8,108), spool body (7,107), cover member (9,109), first sealing member (61), and second sealing member (62). The spool body has tubular bobbin trunk portion (7a,107a), and front/rear flange portions provided on the front/rear of the bobbin trunk portion. The drag mechanism includes: drag-handling unit (70,170) that screws onto the fore end of the spool shaft; and friction unit disposed so as to contact the rear face of the rear flange. The rear-

ward movement of the first friction unit (71,171) is restricted by spool shaft. Cover member (9,109) is installed on spool body to cover first friction unit from rear. First sealing member (61) is fitted in between cover member (9,109) and rear flange portion. Second sealing member (62) is fitted in between spool shaft and cover member. Spool can control fluctuations in drag force due to liquids that seep into drag mechanism.

EP 1 269 838 A8