

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 346 119 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
08.02.2006 Bulletin 2006/06

(21) Application number: **01991641.0**

(22) Date of filing: **14.11.2001**

(51) Int Cl.:
E04H 15/20 (2006.01)

(86) International application number:
PCT/ZA2001/000175

(87) International publication number:
WO 2002/064917 (22.08.2002 Gazette 2002/34)

(54) **INFLATABLE STRUCTURE**

AUFBLASBARE KONSTRUKTION

STRUCTURE GONFLABLE

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**

(30) Priority: **14.11.2000 ZA 200006289**

(43) Date of publication of application:
24.09.2003 Bulletin 2003/39

(73) Proprietor: **Visser, Etienne Douw
7600 Stellenbosch (ZA)**

(72) Inventor: **Visser, Etienne Douw
7600 Stellenbosch (ZA)**

(74) Representative: **Galgut, John et al
79 Coleraine Road
Blackheath
London SE3 7PF (GB)**

(56) References cited:
**FR-A- 2 697 045 GB-A- 2 090 622
US-A- 2 938 526 US-A- 3 502 091
US-A- 4 120 024 US-A- 4 723 382
US-A- 4 932 169**

EP 1 346 119 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] This invention relates to an inflatable structure.

[0002] The applicant is the patentee in respect of ZA 9 705 569 - Inflatable tent frame - which describes a frame comprising at least three tubular legs each constituting a separately sealed chamber that is capable of being inflated with a fluid such as air or gas to constitute a frame structure for a tent or canopy.

[0003] Conventionally, inflatable structures such as inflatable boats, inflatable life rafts and the like are manufactured from airtight fabrics. These fabrics conventionally consist of a polyvinyl chloride (PVC) fabric reinforced with woven polyester. The fabric is cut and welded, either with the use of heat welding or with adhesives, to obtain the desired shapes.

[0004] However, tubes that are relatively long and narrow tend to distort, particularly if they are unsupported. Thus for example to endeavour to deal with this problem large numbers of inflatable tubes are used in an arrangement as shown in French Patent No. 2697045 (A.S. Semmel). This is complex and expensive.

[0005] This kind of problem normally does not arise with inflatable water craft since these craft utilise relatively short, large diameter tubes and normally include rigid or semi-rigid structures to which the tubes are attached.

[0006] In the known inflatable tent technology it is very difficult to construct a frame that is fully free standing, unsupported by anchors and anchor ropes. Stability is normally achieved by utilising relatively large diameter tubes combined with an anchoring system, making the tent relatively heavy and expensive, limiting the application potential to relative small-specialised market sectors. The arrangement of tubes in tetrahedron formation is disclosed in British Patent No. 2090622. Here the ends of all three tubes engage the ground. There is no learning that these tubes can be connected together.

[0007] Frame structures as typically utilised in a tent or canopy, utilise structural intersections that are typically too complex and difficult to manufacture with the current state of art in inflatable tube manufacturing.

[0008] In conventional tent construction where the frame is constructed out of solid structural elements such as metal tubing or spring steel rods, a fare amount of labour and knowledge and time is needed to construct the tent. These tents, even in their simplest form still comprise different parts that need assembly. In US Patent 3,502,091 (Corbin) there is shown a tent supporting frame comprising a ridge struts which are hinged together and to side struts. In order for the frame to take up a support position, a complicated hub with an extendable rod therethrough is provided and cable system including lock means is provided to draw the ridge struts into the desired position.

[0009] In US Patent No. 2,938,526 (Harrison III, et al) there is described an inflatable shelter including an arrangement of tubes some of which are arranged in tet-

rahedron formation wherein a cap portion is provided to which twelve inflatable struts are connected. Although this may seem to be theoretically possible, it is doubted whether this can be provided in practice. The cap portion is too complicated to be practically possible to manufacture. Furthermore the arrangement in this specification, ropes are required to connect the ends of the formations to permit the structure to be erected. In addition there are provided spoke-like tubes between the formation leading to the cap portion. This will means that webbing members on either side of each spoke-like tube will be inclined to one another making for a complex internal shape.

[0010] It is an object of this invention to provide tubular structural elements that address these deficiencies and to provide structures that utilise such structural elements.

Statement of the invention.

[0011] According to this invention there is provided a structure comprising a plurality of structural units each consisting of three inflatable legs, two of which constitute support legs and the third constituting an apical leg, each leg having a free end and an inner end, the inner ends of the three legs being joined at a centrepoin, the legs being arranged to define a tetrahedron with the three legs lying on three adjacent edges of the tetrahedron and with adjacent pairs of legs lying in planes of three sides of the tetrahedron, and the free ends of the legs define the fourth side of the tetrahedron; the free ends of the units being closed and the apical legs of the units being connected to corresponding legs of the other units at a join position.

[0012] The three legs of each unit are preferably of the same length although two of the legs are of the same length and the third leg is of a different length. Preferably each leg is straight. Each leg preferably comprises a plastic reinforced by a woven fabric. The warp of the fabric is conveniently aligned with the tube axis.

[0013] A connector unit is conveniently provided at the free end of at least one of the legs whereby it may be connected to a similar leg of another structural unit.

[0014] Being polyhedral, the structural element of the invention will yield, in combination with similar structural elements, a variety of geodesic structures. In such structures, the apical legs of the structural elements may be secured to the apical legs of adjacent, similar structural elements. In the same way the support legs of the structural elements may be secured to the support legs of adjacent, similar structural elements.

[0015] The apical leg of each structural element may be provided with mating connector formations to permit easy connection and disconnection to the apical legs of adjacent structural elements. In the same way the support legs of each structural element may be provided with mating connector formations to permit easy connection and disconnection to the support legs of adjacent structural elements.

[0016] In the preferred form of the invention, the con-

connector constitutes the mating track and slider formations that can be inter engaged with one another to connect the structural elements together.

[0017] The tube ends of each structural element is geometrically shaped along the natural complimentary lines along the intersecting surfaces of the adjacent structural element. The connectors are fixed along their relative axial angles.

[0018] Connecting adjacent structural elements in this manner is simple yet it results in a very strong and supportive joint, utilising the inherent strength of the inflatable tube.

[0019] Structural elements connected together into a composite structure in this way form a very stable inflated structure.

Brief description of the drawings

[0020] In the drawings:

Figure 1 is a diagrammatic isometric view of a tetrahedral structural element according to this invention;

Figure 2 is a diagrammatic plan view of a simple inflatable structure made up of four of the structural elements of Figure 1;

Figure 3 is a diagrammatic end elevation of the structure of Figure 2;

Figure 4 is a diagrammatic plan view on the point of connection of the structural elements in the structure of Figures 2 and 3;

Figure 5 is a diagrammatic sectional side elevation illustrating a novel lighting arrangement for structures according to the invention;

Figures 6, 7 and 8 are diagrammatic plan view, end elevation and side elevation respectively of a structure that combines the structural element of Figure 1 with a number of similar and dissimilar units to provide a more complex geodesic dome structure than that illustrated in Figures 2 and 3.

Description of embodiments of the invention

[0021] The inflatable structure of the invention is more of a construction system than a simple structure. The system relies on the use of an inflatable polyhedral structural element as its basic unit of construction. By combining such a structural element with similar structural elements or with similarly polyhedral structural elements, a large variety of structures can be created as will be illustrated below.

[0022] The structural element 10 illustrated in Figure 1 has an essentially straight sided tetrahedral shape. A tetrahedron, being a polyhedron with four triangular

sides, the structural element is made of three inflatable relatively narrow tubes 10.1, 10.2, 10.3, each lying on an edge of the tetrahedron. Three of the triangular sides of the tetrahedron are constituted by the triangular planes included between the three legs and the fourth triangular side is constituted by the plane defined by the free ends of the legs.

[0023] Seen differently, the structural element constitutes an inverted Y shaped support element.

[0024] The legs 10.1 and 10.2 lie on the inverted arms of the Y and constitute support legs. The remaining leg 10.3 defines the stem of the Y, which is angled relatively to the legs 10.1, 10.2 to define a support beam in structures to be erected with the use of the structural element 10.

[0025] The tubes making up the legs 10.1, 10.2, 10.3 of the structural support element are made from airtight PVC fabric reinforced with woven polyester.

[0026] The woven polyester reinforcing fabric is arranged with the warp thereof aligned longitudinally with the principal axis of each of the tubular legs 10.1, 10.2, and 10.3. This gives the tubes a high resistance to bending.

[0027] If it is desired to permit curvature of the tubes to provide a more dome shaped tetrahedron, the polyester reinforcing fabric may be arranged on the bias (with the warp at an angle to the tube axis) to a greater or lesser degree, depending on the curvature that will be permitted.

[0028] The airtight fabric is double welded along the length of each tube. In practice, the fabric is welded along axially extending seams with a separate strip of fabric welded internally along each of the seams to provide enhanced sealing.

[0029] The tubes making up the legs 10.1, 10.2 and 10.3 are interconnected at their inner ends 10.5 across a joint 12 through which the pressurising fluid can flow freely during inflation and deflation of the structural element 10. The closed end 10.4 of each leg 10.1, 10.2 and 10.3 is geometrically shaped along the natural complimentary lines along the intersecting surfaces of the adjacent structural element.

[0030] The structural element 10 is inflated and deflated by means of an inflation valve (illustrated diagrammatically at 14). The inflatable tubes are airtight and once it is filled with compressed gas to the desired pressure and sealed off, will maintain its rigidity and support strength without any further addition of compressed air.

[0031] The most convenient pressurising fluid would be compressed air obtained from a blower or compressor, or from a pressurised gas canister, but alternative pressurising fluids such as motor vehicle exhaust gas could also be used, provided the appropriate inflation fittings are used.

[0032] The structural element 10 of the invention can be combined into relatively complex structures that, because of the tetrahedral shape of the unit 10, will have the characteristics of geodesic domes.

[0033] The simple structure 100 illustrated in Figures 2 and 3 provides an example of the structure building capabilities of the basic structural element 10.

[0034] In the structure 100, four of the units 10 are interconnected to form a four-sided structural frame.

[0035] The apical legs 10.3 of the units 10 are connected to one another at the join position at apex 102 of the structure 100 by means of connectors that will be described below.

[0036] The support legs 10.1 and 10.2 of the structural elements 10 extend down to the ground and are connected to one another by means of connectors that will be described below.

[0037] The structure 100 may now be clad with a fabric cover (not shown).

[0038] Once the structure 100 is clad with a fabric cover and fastened to a groundsheet, it is completely free standing and needs no pegs or anchor ropes to keep it stable. Very little experience or knowledge is now required to pitch the tent. The energy that pitches the tent is supplied by the compressed gas and the whole process is done in a fraction of the normal time. There is also no assembly needed to pitch the tent. The unit only needs to be unfolded and inflated to pitch the tent. The same applies when putting the tent down. The valves in the tubes are opened to let the compressed gas out and the whole structure collapses. It is then folded as a unit in the normal way. There is thus no poles or other structural elements to account for.

[0039] The structure 100 provides a high degree of wind resistance but, if required, the structure can be pegged to the ground.

[0040] It will be seen that the structure 100 is erected using four separate structural elements 10 that are connected to one another.

[0041] Figure 4 illustrates two of the metal connectors 15 that are used to interconnect the structural element ends 10.4 of the structural elements 10 (the free ends of the legs 10.1, 10.2 and 10.3 of the structural elements 10). The ends 10.4 of the structural elements 10 are shaped complementary to permit interconnection of the structural elements along the axial angle of the completed structure. Each such leg end 10.4 is finished off with a flat end weld 13 that is double welded and inserted between the flat strips of metal making up the connectors 15.

[0042] Each structural element 10 is provided, at its leg ends 10.4 with a connector 15 that comprises a slider 16 and track formation 18, the slider 16 being adapted to slide into the track 18 of an adjacent connector 15. The slider and track formations 16, 18 are dimensioned to provide a secure friction fit once interconnected. The connectors are fixed along their relative axial angles at the vertex of the polyhedron.

[0043] The utilisation of the connector 15 on each tube end has the advantage that two or more tube ends can be interconnected in a very strong and stable bond alleviating the need for a complex welded joint.

[0044] The entire connector 15 is riveted together with blind rivets. This has the advantage that the connector formations 16, 18 can be removed to permit reopening of the tube ends and the servicing of the tubes.

5 **[0045]** In certain situations it might be appropriate to insert a gasket within the sealing arrangement constituted by the connector 15 and the welded end of the tube in order to enhance the sealing effect.

10 **[0046]** The structure 100 illustrated in Figures 2 and 3 are a relatively simple structure that utilises only the basic structural element 10 illustrated in Figure 1. However, the basic structural unit 10 can be used in conjunction with similar yet slightly more complex structural elements to provide more complex structures as is illustrated in

15 Figures 6, 7 and 8.

[0047] The structure 200 shown in these drawings utilises three of the basic structural elements 10 at each of its short ends.

20 **[0048]** The apex and long sides of the structure 200 are defined by a pair of opposed structural elements 204, each of which incorporates a pair of support legs 204.1 and a pair of apical legs 204.2 that extend upwardly towards an apical beam 206 that defines the apex of the structure 200. The apical legs 10.3 of the elements 10 at

25 each end of the structure 200 are connected to the ends of the beam 206 by means as described above.

[0049] It will be noted that the structural element 10 will yield, in combination with similar structural elements, a variety of geodesic structures. In such structures, the apical legs of the structural elements may be secured to the apical legs of adjacent, similar structural elements. In the same way the support legs of the structural elements may be secured to the support legs of adjacent, similar structural elements. If desired the basic structural

30 elements 10 may be flanked by a slightly modified structural element, each of which differs from the basic structural element 10 only in the fact that it has an asymmetrical tetrahedral shape.

[0050] The structures of the invention, being inflatable, lend themselves to novel uses. For instance, the structure could be internally lit using light fittings 20 fitted to the insides of the tubes making up the structural elements. In this kind of an application, the fabric of the tubes and the structure as a whole will be chosen for translucency to enhance the lighting effect.

45 **[0051]** In addition, the structures need not be confined to land. Being inflatable, the structures will float on water to provide a novel staging facility for events and advertising.

Claims

- 50 1. A structure (100 and 200) comprising a plurality of structural units (10) each consisting of three inflatable legs constituting two support legs (10.1 and 10.2) and an apical leg (10.3), each leg having a free end (10.4) and an inner end

(10.5), the inner ends of the three legs being joined at a centrepoint (12),

the legs being arranged to define a tetrahedron with the three legs lying on three adjacent edges of the tetrahedron and with adjacent pairs of legs lying in planes of three sides of the tetrahedron, and the free ends of the legs defining the fourth side of the tetrahedron;

the free ends (10.4) of the units being closed and the apical legs (10.3) of the units being connected to corresponding legs of the other units at a join position (102).

2. A structure as claimed in claim 1 **characterised in that** the three legs (10.1, 10.2 and 10.3) of each unit (10) are of the same length.
3. A structure as claimed in claim 1 **characterised in that** two of the legs (10.1 and 10.2) are of the same length and the third leg (10.3) is of a different length.
4. A structure as claimed in claim 1, 2 or 3 **characterised in that** one support leg (10.1) of a unit is connected to the other support leg (10.2) of an adjacent unit.
5. A structure as claimed in any one of the preceding claims **characterised in that** each leg comprises a plastic reinforced by a woven fabric.
6. A structure as claimed in claims 4 and 5 **characterised in that** the warp of the fabric is aligned with the tube axis.
7. A structure as claimed in any one of the preceding claims **characterised in that** a connector unit (15) is provided at the free end of at least one of the legs (10.3) of each element.
8. A structure as claimed in any one of the preceding claims **characterised in that** the apical legs (10.3) are all connected directly together.
9. A structure as claimed in any one of claims 1 to 7 **characterised in that** some of the apical legs (10.3) are connected to other apical legs (10.3) through an intermediate beam (206).
10. A structure as claimed in any one of the preceding claims **characterised in that** the outer ends of the legs are shaped complementary to permit interconnection of the structural elements along the axial angle of the completed structure.

Patentansprüche

1. Ein Aufbau (100 und 200) bestehend aus mehreren

Konstruktionseinheiten (10), von denen jede aus drei aufblasbaren Beinen besteht, die zwei Stützbeine (10.1 und 10.2) und ein Firstbein (10.3) bilden, wobei jedes Bein ein freies Ende (10.4) und ein inneres Ende (10.5) hat, und die inneren Enden der drei Beine an einem Zentralpunkt (12) zusammen befestigt sind. Die Beine sind so zusammengestellt, dass sie ein Tetraeder bilden, wobei die drei inneren Beine an den drei angrenzenden Kanten des Tetraeders liegen und die angrenzenden Beinpaare auf den Flächen der drei Seiten des Tetraeders liegen, und die freien Enden der Beine die vierte Seite des Tetraeders bilden; die freien Enden (10.4) der Einheiten sind geschlossen und die Firstbeine (10.3) der Einheiten sind mit den entsprechenden Beinen der anderen Einheiten an einem Befestigungspunkt (102) verbunden.

2. Eine Konstruktion, auf die wie in Ziffer 1 Anspruch erhoben wird, die sich **dadurch** auszeichnet, dass die drei Beine (10.1, 10.2 und 10.3) einer jeden Einheit (10) gleich lang sind.
3. Eine Konstruktion, auf die wie in Ziffer 1 Anspruch erhoben wird, die sich **dadurch** auszeichnet, dass zwei der drei Beine (10.1 und 10.2) gleich lang sind, wobei das dritte Bein (10.3) eine andere Länge aufweist.
4. Eine Konstruktion, auf die wie in Ziffer 1, 2 oder 3 Anspruch erhoben wird, die sich **dadurch** auszeichnet, dass ein Stützbein (10.1) einer Einheit mit dem anderen Stützbein (10.2) einer angrenzenden Einheit verbunden ist.
5. Eine Konstruktion, auf die wie in jeder der vorstehenden Ziffern Anspruch erhoben wird, die sich **dadurch** auszeichnet, dass jedes Bein einen Kunststoff verstärkt mit gewebtem Stoff beinhaltet.
6. Eine Konstruktion, auf die wie in Ziffer 4 und 5 Anspruch erhoben wird, die sich **dadurch** auszeichnet, dass die Krümmung des Stoffs auf die Röhrenachse ausgerichtet ist.
7. Eine Konstruktion, auf die wie in jeder der vorstehenden Ziffern Anspruch erhoben wird, die sich **dadurch** auszeichnet, dass eine Verbindungseinheit (15) am freien Ende von mindestens einem der Beine (10.3) eines jeden Elements gegeben ist.
8. Eine Konstruktion, auf die wie in jeder der vorstehenden Ziffern Anspruch erhoben wird, die sich **dadurch** auszeichnet, dass die Firstbeine (10.3) alle direkt miteinander verbunden sind.
9. Eine Konstruktion, auf die wie in jeder der Ziffern 1 bis 7 Anspruch erhoben wird, die sich **dadurch** aus-

zeichnet, dass einige der Firstbeine (10.3) mit anderen Firstbeinen (10.3) durch einen Zwischenbalken (206) verbunden sind.

10. Eine Konstruktion, auf die wie in jeder der vorstehenden Ziffern Anspruch erhoben wird, die sich **dadurch** auszeichnet, dass die äußeren Enden der Beine entsprechend geformt sind, um die Verbindung der Konstruktivselemente untereinander im Achsenwinkel des fertigen Aufbaus zu ermöglichen.

Revendications

1. Structure (100 et 200) comportant une pluralité d'unités structurelles (10) chacune composées de trois jambes gonflables constituant deux jambes de soutien (10.1 et 10.2) et une jambe sommitale (10.3), chaque jambe ayant une extrémité libre (10.4) et une extrémité intérieure (10.5), les extrémités intérieures des trois jambes étant jointes en un point central (12), les jambes étant chargées de définir un tétraèdre avec les trois jambes correspondant aux trois arêtes adjacentes du tétraèdre et avec des paires adjacentes de jambes se situant dans les plans des trois faces du tétraèdre, et les extrémités libres des jambes définissant la quatrième face du tétraèdre; les extrémités libres (10.4) des unités étant fermées et les jambes sommitales (10.3) des unités étant reliées aux jambes correspondantes des autres unités au niveau d'une position de jonction.
2. Structure selon la revendication 1, **caractérisée en ce que** les trois jambes (10.1, 10.2 et 10.3) de chaque unité (10) sont de même longueur.
3. Structure selon la revendication 1, **caractérisée en ce que** deux des jambes (10.1 et 10.2) sont de même longueur et que la troisième jambe (10.3) est de longueur différente.
4. Structure selon les revendications 1, 2 ou 3, **caractérisée en ce qu'**une jambe d'un soutien (10.1) d'une unité est reliée à l'autre jambe de soutien (10.2) d'une unité adjacente.
5. Structure selon l'une quelconque des revendications précédentes, **caractérisée en ce que** chaque jambe est constituée de plastique renforcé par de la toile tissée.
6. Structure selon les revendications 4 et 5, **caractérisée en ce que** la chaîne de la toile est alignée avec l'axe de tube.
7. Structure selon l'une quelconque des réclamations précédentes, **caractérisée en ce qu'**une unité de

connecteur (15) est prévue à l'extrémité libre d'au moins une des jambes (10.3) de chaque élément.

8. Structure selon l'une quelconque des réclamations précédentes, **caractérisée en ce que** les jambes sommitales (10.3) sont toutes reliées directement ensemble.
9. Structure selon l'une quelconque des revendications de 1 à 7, **caractérisée en ce que** certaines des jambes sommitales (10.3) sont reliées à d'autres jambes sommitales (10.3) par une poutre intermédiaire (206).
10. Structure selon l'une quelconque des réclamations précédentes, **caractérisée en ce que** les extrémités externes des jambes sont de forme complémentaire pour permettre l'interconnexion des éléments structurels le long de l'angle axial de la structure réalisée.





