



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 371 721 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
17.12.2003 Bulletin 2003/51

(51) Int Cl.7: **C11D 17/00, C11D 1/83**

(21) Application number: **03076742.0**

(22) Date of filing: **04.06.2003**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR**
Designated Extension States:
AL LT LV MK

(30) Priority: **11.06.2002 EP 02077269**
07.08.2002 EP 02078247

(71) Applicants:
• **UNILEVER N.V.**
3013 AL Rotterdam (NL)
Designated Contracting States:
**AT BE BG CH LI CZ DE DK EE ES FI FR GR HU
IT LU MC NL PT RO SE SK TR**
• **UNILEVER PLC**
London EC4P 4BQ (GB)
Designated Contracting States:
GB IE

(72) Inventors:
• **Appel, Peter W., c/o Unilever R & D Vlaardingen
3133 AT Vlaardingen (NL)**
• **Van Doorn, D. A., c/o Unilever R & D Vlaardingen
3133 AT Vlaardingen (NL)**
• **Nauta, Lammert, c/o Unilever R & D Vlaardingen
3133 AT Vlaardingen (NL)**

(74) Representative: **Joppe, Hermina L. P. et al**
Unilever N.V.
Patent Division
P.O. Box 137
3130 AC Vlaardingen (NL)

(54) **Detergent tablets**

(57) Method of producing a cleaning tablet which has a plurality of discrete regions with differing compositions, characterised in that at least one first region of the tablet is a smooth region and at least one second region of the tablet is a solid region of compacted particulate material and wherein said method comprises the steps of

- (a) Preparation of a smooth first tablet;
- (b) Compression of the particulate material to form a second tablet of compacted particulate material;
- (c) Assembling the first tablet and the second tablet.

EP 1 371 721 A1

Description

[0001] This invention relates to cleaning compositions in the form of tablets. For use in fabric washing or machine dishwashing. The invention also relates to a process for the preparation of a cleaning composition in the form of tablets.

[0002] Detergent compositions in tablet form have advantages over powdered products in that they do not require measuring and are thus easier to handle and dispense into the washload.

[0003] Tablets of a cleaning composition are generally made by compressing or compacting a quantity of the composition in particulate form.

[0004] Tablets comprising two or more separate regions have also been described. For example WO 01/42416 describes the production of multi-phase moulded bodies comprising a combination of core moulded bodies and a particulate premix. WO 00/61717 describes a detergent tablet which is characterised in that at least part of its outer surface is semi-solid. WO 00/04129 describes a multi-phase detergent tablet comprising a first phase in the form of a shaped body having at least one mould therein and a second phase in the form of a particulate solid compressed within said mould. WO 99/24549 describes a detergent tablet comprising a compressed solid body and a non-compressed gelatinous portion mounted in a mold of said body.

[0005] There have been a number of proposals for tablets which are subdivided into separate regions (e.g. layers) which differ in their composition.

[0006] WO 99/35225 relates to moulded bodies with two solid phases wherein one phase of no more than 40 vol% of the moulded body contains more than 80wt% of the total of an active substance contained in the moulded body with an ingredient from the group of surfactants.

[0007] The present invention aims to provide an alternative multi-phase cleaning tablet with good dispersing properties, which allows a wide range of formulations and which can easily be prepared at low cost. In a particular the present invention is advantageous in that the alternative multi-phase tablets do not require the presence of preprepared molds in the tablet surface and hence can be easily prepared without the need of a specific equipment for the formation of such a mold.

[0008] According to the present invention there is provided a cleaning tablet which has a plurality of discrete regions with differing compositions, characterised in that at least one first region of the tablet is a smooth region and at least one second region of the tablet is a solid region of compacted particulate material.

[0009] Preferably tablets of the invention are of cylindrical shape wherein the two main surfaces (upper side and bottom side) are substantially flat.

[0010] The regions of the tablet are possibly separate layers within a tablet. However, a discrete region of a tablet could also have other forms for example one or more core(s) or insert(s). In a first preferred embodiment

the first region is a smooth layer and the second region is a layer of compacted particulate material. In a further advantageous embodiment the first region is a core or insert of smooth material embedded in the second region which is a layer of compacted particulate material.

[0011] Preferably the first region has a weight of from 2 to 20 grammes, more preferred from 3 to 10 grammes. Preferably the second region has a weight of 10 to 50 grammes, more preferred 15 to 30 grammes.

[0012] The first region of the tablet is a smooth region. For the purpose of this invention the term smooth phase refers to compositions which are on the one hand solid enough to retain their shape at ambient temperature and on the other hand smooth in appearance. Smooth textures are generally of low or no porosity and have -at normal viewing distance- the appearance of a continuous phase for example as opposed to porous and particulate appearance of a compacted particulate material.

[0013] WO99/24549 describes the use of non-compressed gelatinous portions mounted in a mold as a smooth phase. These tablets must be made with specific equipment to ensure the appropriate mold formation. WO 00/61717 describes (in the example) the preparation of a compressed particulate tablet on top of which a (non-compressed) layer was made by pouring a mixture of nonionic and PEG followed by hardening. This method of preparation is disadvantageous because it requires a very long hardening step in the tablet mould, during which the tablet mould cannot be used for further production, therewith significantly increasing the cost of production.

[0014] Preferably the smooth region is a semi-solid region. For the purpose of this invention the term semi-solid refers to compositions which are on the one hand solid enough to retain their shape at ambient temperature but which are neither completely solid.

[0015] A suitable test to check if a composition can be considered as semi-solid can be described as follows:

[0016] A cylindrical tablet with a diameter of 45 mm and a height of 20 mm is compressed radially between the plates of a material testing machine until the tablet fractures. At the starting position the plates contact the tablet but do not apply force to it. Force is applied, to compress the tablet, the vertical speed of the upper plate is 25 mm/minute. The testing machine measures the applied force (F), and also the displacement (x) of the plates towards each other as the tablet is compressed. The distance (y) between the plates before force is applied, which is the diameter of the tablet, is also known. At failure, the tablet cracks and the applied force needed to maintain the displacement drops. Measurement is discontinued when the applied force needed to maintain the displacement has dropped by 25% from its maximum value. The displacement at failure (x_f) is also measured.

[0017] A graph of force (F) against displacement (x) can be made. The maximum force is the force at failure

(F_f). The break energy is the area under the graph of force against displacement, up to the point of break and is given by the equation:

$$E_b = \int_{0-x_f} F(x) dx$$

wherein E_b is the break energy in mJoules, x is the displacement in metres and F is the applied force in Newtons at displacement x and x_f is the displacement at failure.

[0018] Semi-solid compositions are characterised by a ratio of F_f to E_b of less than 1.0, more preferred from 0.1 to 0.9, most preferred from 0.2 to 0.6, while traditional tablets of compacted particulate materials are generally characterised by a ratio of F_f to E_b of more than 1, more generally more than 1.25 or even more than 1.5 up to say 6.

[0019] In an advantageous embodiment of the invention said first region comprises from 40-100 wt% of surfactants (based on the total weight of the first region), more preferred from 50-95 wt%, most preferred the first region is predominantly constituted by surfactants e.g. more than 60 wt% for example 70 to 90 wt%. It has been found that the combination of a separate smooth or semi-solid first region and these high surfactant levels provide very good dispersing and cleaning properties to the tablet.

[0020] Preferably the surfactants in the first region comprise a combination of anionic surfactants and non-soap non-ionic surfactants in a weight ratio of from 5 : 1 to 1 : 5, more preferred 3 : 1 to 1 : 3, more preferred 2 : 1 to 1 : 2. Further surfactants, for example cationic surfactants may equally be present for example at a level of 0.1 to 10 wt% based on the weight of the smooth or semi-solid part. Also advantageously the smooth or semi-solid region may comprise soap for example at a level of 0.1 to 10 wt% based on the weight of the smooth or semi-solid part.

[0021] Also advantageously the smooth or semi-solid region of the tablet may comprise diluent materials for example polyethyleneglycol or (mono-)propyleneglycol. Preferable the level of these diluents is from 0 to 40 wt%, more preferred 2 to 30, most preferred 10-25 wt% based on the weight of the semi-solid region.

[0022] The smooth or semi-solid phase preferably comprises no or only low levels of water. Preferably the level of water is less than 20 wt % based on the weight of the semi-solid phase, more preferred less than 15 wt%, most preferred from 5 to 12 wt%. Most preferably the semi-solid phases are substantially free from water, which means that apart from low levels of moisture (e.g. for neutralisation or as crystal water) no additional added water is present.

[0023] Preferably the total weight of surfactants in the first region is from 2 to 20 grammes, more preferred from 3 to 10 grammes.

[0024] In a preferred embodiment of the invention the second region comprises no or only low levels of surfactants. Preferably the level of surfactants in the second region is less than 10 wt% (based on the total weight of the second region), more preferred from 0 to 9 wt%, most preferred from 1 to 8 wt%.

[0025] The second region of the tablet is a solid region, for example prepared by compression of a particulate composition.

[0026] Although the second region may comprise surfactant materials, this region preferably comprises ingredients of the tablet other than surfactants. Examples of these ingredients are for example builders, bleach system, enzymes etc. Preferably the builders in the tablet are predominantly present in the second region. Preferably the bleach system is predominantly present in the second region. Preferably the enzymes are predominantly present in the second region. For the purpose of this invention, unless stated otherwise, the term "predominantly present" refers to a situation wherein at least 90 wt% of an ingredient is present in the second region, more preferred more than 98 wt%, most preferred substantially 100 wt%.

[0027] The above description of the tablet has been given with reference to a tablet constituted by two regions. It will however be understood that each of the regions may be composed of a limited number of discrete regions. For example the first smooth or semi-solid region may be a single discrete part of the tablet but may also be a limited number (say 1-5) discrete semi-solid parts. Preferably each of these semi-solid parts are at least 1 gramme, also preferably each of these semi-solid parts is substantially of the same composition. If reference is made to the composition or weight of the first region it is understood that this concerns the total weight and composition of these smooth or semi-solid parts.

[0028] Similarly the solid second region may be composed a limited number (say 1-5) of solid parts e.g. separate layers in the tablet. Preferably each of these parts has a weight of at least 10 grammes, also preferably each of the solid parts are substantially of the same composition. If reference is made to the composition or weight of the second region it is understood that this concerns the total weight and composition of these solid parts.

[0029] In addition to the smooth or semi-solid first region and the solid second region the cleaning tablets of the invention may optionally comprise further regions, for example the tablet may be partly or wholly coated.

[0030] Cleaning tablets according to the invention are preferably manufactured by a process comprising the steps of:

(a) inserting a particulate composition into a tablet mould

(b) inserting one or more smooth parts into said tablet mould

(c) co-compression of the particulate composition and smooth parts to form a compressed tablet comprising discrete regions, wherein the first region is formed by said compressed smooth part(s) and the second region is formed by said compressed particulate composition.

[0031] Steps (a) and (b) can be in any order, although a preferred embodiment the particulate composition is first introduced into the tablet mould, followed by positioning of the smooth or semi-solid part(s) in said mould. Optionally the particulate composition may be flattened or pre-compressed before introducing the smooth or semi-solid part(s).

[0032] In a preferred embodiment of the invention the particulate composition is pre-compressed at a force of 0.1 to 20 kN/cm² between steps (a) and (b). In another preferred embodiment the particulate composition is flattened between steps (a) and (b).

[0033] Preferably the (co-)compression of the combination of the semi-solid and the solid region(s) takes place at a force of from 0.1 to 20 kN/cm². Especially if the solid region has been pre-compressed the co-compression in step (c) can advantageously be at a force of 0.01- 10 kN/cm², more preferred 0.2 to 5 kN/cm². If the solid region has not been pre-compressed, the co-compression preferably takes place at a force of 1-100 kN/cm², more preferred 2-50 kN/cm², most preferred 2-10 kN/cm².

[0034] Another preferred method for the manufacture of cleaning tablets according to the invention comprises the steps of

(a) compression of particulate composition to form a pre-compressed tablet

(b) production of a smooth or semi-solid tablet, preferably by casting of a smooth or semi-solid material;

(c) assembling the final tablet by combining the pre-compressed tablet and the smooth or semi-solid tablet, preferably under the application of a co-compression force.

[0035] Preferably the pressure for preparing the pre-compressed tablet is from 0.1 to 20 kN/cm². Preferably the pressure for preparing the smooth or semi-solid tablet is preferably from 0 to 5 kN/cm² more preferred 0.01 to 5 kN/cm². Preferably the pressure for assembling the product is from 0.01 to 5 kN/cm². Especially preferably the smooth or semi-solid tablet is made by casting.

[0036] One advantage of the preferred methods of the present invention is that the co-compression step of (c) leads to good adherence of the first region to the second region and avoids the need of applying an adhesive material between the semi-solid and solid region. Another advantage of the method of the invention is that it can be carried out in a normal tablet press without the need

of adaptation of the shape of the pressing surfaces and without long waiting times e.g for hardening.

[0037] A tablet of this invention may be intended for use in machine dishwashing. Such a tablet is likely to contain surfactant in a low concentration such as 0.5 to 2 wt% based on the whole tablet, although higher concentrations ranging up to 10 wt% may be used. Such will typically contain salts, such as over 60 wt%, often over 85 wt% of the tablet.

[0038] Water soluble salts typically used in machine dishwashing compositions are phosphates (including condensed phosphates) carbonates and silicates, generally as alkali metal salts. Water soluble alkali metal salts selected from phosphates, carbonates and silicates may provide 60 wt% or more of a dishwashing composition.

[0039] Another preferred possibility is that a tablet of this invention will be intended for fabric washing. In this event the tablet will be likely to contain at least 2 wt%, probably at least 5 wt%, up to 40 or 50 wt% surfactant based on the whole tablet, and from 5 to 80 wt% detergent builder, based on the whole tablet.

[0040] Materials which may be used in tablets of this invention will now be discussed in more detail.


Surfactant Compounds

[0041] Compositions which are used in tablets of the invention will contain one or more detergent surfactants. In a fabric washing composition, these preferably provide from 5 to 50% by weight of the overall tablet composition, more preferably from 8 or 9% by weight of the overall composition up to 40% or 50% by weight. Surfactant may be anionic (soap or non-soap), cationic, zwitterionic, amphoteric, nonionic or a combination of these.


[0042] Anionic surfactant may be present in an amount from 0.5 to 50% by weight, preferably from 2% or 4% up to 30% or 40% by weight of the tablet composition.

[0043] Synthetic (i.e. non-soap) anionic surfactants are well known to those skilled in the art. Examples include alkylbenzene sulphonates, particularly sodium linear alkylbenzene sulphonates having an alkyl chain length of C₈-C₁₅; olefin sulphonates; alkane sulphonates; dialkyl sulphosuccinates; and fatty acid ester sulphonates.

[0044] Primary alkyl sulphate having the formula



in which R is an alkyl or alkenyl chain of 8 to 18 carbon atoms especially 10 to 14 carbon atoms and M⁺ is a solubilising cation, is commercially significant as an anionic surfactant. Linear alkyl benzene sulphonate of the formula



where R is linear alkyl of 8 to 15 carbon atoms and M⁺ is a solubilising cation, especially sodium, is also a commercially significant anionic surfactant.

[0045] Frequently, such linear alkyl benzene sulphonate or primary alkyl sulphate of the formula above, or a mixture thereof will be the desired anionic surfactant and may provide 75 to 100 wt% of any anionic non-soap surfactant in the composition.

[0046] In some forms of this invention the amount of non-soap anionic surfactant lies in a range from 5 to 20 wt% of the tablet composition.

[0047] It may also be desirable to include one or more soaps of fatty acids. These are preferably sodium soaps derived from naturally occurring fatty acids, for example, the fatty acids from coconut oil, beef tallow, sunflower or hardened rapeseed oil.

[0048] Suitable nonionic surfactant compounds which may be used include in particular the reaction products of compounds having a hydrophobic group and a reactive hydrogen atom, for example, aliphatic alcohols, acids, amides or alkyl phenols with alkylene oxides, especially ethylene oxide.

[0049] Specific nonionic surfactant compounds are alkyl (C₈₋₂₂) phenol-ethylene oxide condensates, the condensation products of linear or branched aliphatic C₈₋₂₀ primary or secondary alcohols with ethylene oxide, and products made by condensation of ethylene oxide with the reaction products of propylene oxide and ethylene-diamine.

[0050] Especially preferred are the primary and secondary alcohol ethoxylates, especially the C₉₋₁₁ and C₁₂₋₁₅ primary and secondary alcohols ethoxylated with an average of from 5 to 20 moles of ethylene oxide per mole of alcohol.

[0051] In some fabric washing tablets of this invention, the amount of nonionic surfactant lies in a range from 4 to 40%, better 4 or 5 to 30% by weight of the whole tablet.

[0052] Many nonionic surfactants are liquids. These may be absorbed onto particles of the composition.


[0053] In a machine dishwashing tablet the surfactant may be wholly nonionic, in an amount below 5 wt% of the whole tablet although it is known to include some anionic surfactant and to use up to 10 wt% surfactant in total.

Detergency Builder

[0054] A composition which is used in tablets of the invention will contain from 5 to 80%, more usually 15 to 60% by weight of detergency builder. This may be provided wholly by water soluble materials, or may be pro-

vided in large part or even entirely by water-insoluble material with water-softening properties. Water-insoluble detergency builder may be present as 5 to 80 wt%, better 5 to 60 wt% of the composition.

[0055] Alkali metal aluminosilicates are strongly favoured as environmentally acceptable water-insoluble builders for fabric washing. Alkali metal (preferably sodium) aluminosilicates may be either crystalline or amorphous or mixtures thereof, having the general formula:



[0056] These materials contain some bound water (indicated as "xH₂O" and are required to have a calcium ion exchange capacity of at least 50 mg CaO/g. The preferred sodium aluminosilicates contain 1.5-3.5 SiO₂ units (in the formula above). Both the amorphous and the crystalline materials can be prepared readily by reaction between sodium silicate and sodium aluminate, as amply described in the literature.

[0057] Suitable crystalline sodium aluminosilicate ion-exchange detergency builders are described, for example, in GB 1429143 (Procter & Gamble). The preferred sodium aluminosilicates of this type are the well known commercially available zeolites A and X, the novel zeolite P described and claimed in EP 384070 (Unilever) and mixtures thereof.

[0058] Conceivably a water-insoluble detergency builder could be a layered sodium silicate as described in US 4664839.

NaSKS-6 is the trademark for a crystalline layered silicate marketed by Hoechst (commonly abbreviated as "SKS-6"). NaSKS-6 has the delta-Na₂SiO₅ morphology form of layered silicate. It can be prepared by methods such as described in DE-A-3,417,649 and DE-A-3,742,043. Other such layered silicates, such as those having the general formula NaMSi_xO_{2x+1}·yH₂O wherein M is sodium or hydrogen, x is a number from 1.9 to 4, preferably 2, and y is a number from 0 to 20, preferably 0 can be used.

[0059] Water-soluble phosphorous-containing inorganic detergency builders, include the alkali-metal orthophosphates, metaphosphates, pyrophosphates and polyphosphates. Specific examples of inorganic phosphate builders include sodium and potassium tripolyphosphates, orthophosphates and hexameta-phosphates.

[0060] Non-phosphorous water-soluble builders may be organic or inorganic. Inorganic builders that may be present include alkali metal (generally sodium) carbonate; while organic builders include polycarboxylate polymers, such as polyacrylates, acrylic/maleic copolymers, and acrylic phosphonates, monomeric polycarboxylates such as citrates, gluconates, oxydisuccinates, glycerol mono- di- and trisuccinates, carboxymethoxysuccinates, carboxymethoxymalonates, dipicolinates

and hydroxyethyliminodiacetates.

[0061] At least one region (preferably the second region) of a fabric washing tablet preferably include polycarboxylate polymers, more especially polyacrylates and acrylic/maleic copolymers which can function as builders and also inhibit unwanted deposition onto fabric from the wash liquor.

Bleach System

[0062] Tablets according to the invention may contain a bleach system in at least one region of a tablet, preferably in the second region. This preferably comprises one or more peroxy bleach compounds, for example, inorganic persalts or organic peroxyacids, which may be employed in conjunction with activators to improve bleaching action at low wash temperatures. If any per-oxygen compound is present, the amount is likely to lie in a range from 10 to 25% by weight of the composition.

[0063] Preferred inorganic persalts are sodium perborate monohydrate and tetrahydrate, and sodium percarbonate, advantageously employed together with an activator. Bleach activators, also referred to as bleach precursors, have been widely disclosed in the art. Preferred examples include peracetic acid precursors, for example, tetraacetyethylene diamine (TAED), now in widespread commercial use in conjunction with sodium perborate; and perbenzoic acid precursors. The quaternary ammonium and phosphonium bleach activators disclosed in US 4751015 and US 4818426 (Lever Brothers Company) are also of interest. Another type of bleach activator which may be used, but which is not a bleach precursor, is a transition metal catalyst as disclosed in EP-A-458397, EP-A-458398 and EP-A-549272. A bleach system may also include a bleach stabiliser (heavy metal sequestrant) such as ethylenediamine tetramethylene phosphonate and diethylenetriamine pentamethylene phosphonate.

[0064] As indicated above, if a bleach is present and is a water-soluble inorganic peroxygen bleach, the amount may well be from 10% to 25% by weight of the composition.

Other Detergent Ingredients

[0065] The detergent tablets of the invention may also contain (preferably in the second region) one of the detergency enzymes well known in the art for their ability to degrade and aid in the removal of various soils and stains. Suitable enzymes include the various proteases, cellulases, lipases, amylases, and mixtures thereof, which are designed to remove a variety of soils and stains from fabrics. Examples of suitable proteases are Maxatase (Trade Mark), as supplied by Gist-Brocades N.V., Delft, Holland, and Alcalase (Trade Mark), and Savinase (Trade Mark), as supplied by Novo Industri A/S, Copenhagen, Denmark. Detergency enzymes are commonly employed in the form of granules or

marumes, optionally with a protective coating, in amount of from about 0.1% to about 3.0% by weight of the composition; and these granules or marumes present no problems with respect to compaction to form a tablet.

[0066] The detergent tablets of the invention may also contain (preferably in the second region) a fluorescer (optical brightener), for example, Tinopal (Trade Mark) DMS or Tinopal CBS available from Ciba-Geigy AG, Basel, Switzerland. Tinopal DMS is disodium 4,4'-bis-(2-morpholino-4-anilino-s-triazin-6-ylamino) stilbene disulphonate; and Tinopal CBS is disodium 2,2'-bis-(phenyl-styryl) disulphonate.

[0067] An antifoam material is advantageously included (preferably in the second region), especially if a detergent tablet is primarily intended for use in front-loading drum-type automatic washing machines. Suitable antifoam materials are usually in granular form, such as those described in EP 266863A (Unilever). Such antifoam granules typically comprise a mixture of silicone oil, petroleum jelly, hydrophobic silica and alkyl phosphate as antifoam active material, absorbed onto a porous absorbed water-soluble carbonate-based inorganic carrier material. Antifoam granules may be present in an amount up to 5% by weight of the composition.

[0068] It may also be desirable that a detergent tablet of the invention includes an amount of an alkali metal silicate, particularly sodium ortho-, meta- or disilicate. The presence of such alkali metal silicates at levels, for example, of 0.1 to 10 wt%, may be advantageous in providing protection against the corrosion of metal parts in washing machines, besides providing some measure of building and giving processing benefits in manufacture of the particulate material which is compacted into tablets.

[0069] A tablet for fabric washing will generally not contain more than 15 wt% silicate. A tablet for machine dishwashing will often contain more than 20 wt% silicate. Preferably the silicate is present in the second region of the tablet.

[0070] Further ingredients which can optionally be employed in a region of a fabric washing detergent of the invention tablet (preferably the second region) include anti-redeposition agents such as sodium carboxymethylcellulose, straight-chain polyvinyl pyrrolidone and the cellulose ethers such as methyl cellulose and ethyl hydroxyethyl cellulose, fabric-softening agents; heavy metal sequestrants such as EDTA; perfumes; and colorants or coloured speckles.

[0071] Further ingredients which can optionally be used in tablets of the invention, preferably in the second region are dispersing aids. Examples of suitable dispersing aids are water-swellaible polymers (e.g. SCMC) highly soluble materials (e.g. sodium citrate, potassium carbonate or sodium acetate) or sodium tripolyphosphate with preferably at least 40% of the anhydrous phase I form.

Particle Size and Distribution

[0072] The second region of a detergent tablet of this invention, is a preferably a matrix of compacted particles.

[0073] Preferably the particulate composition has an average particle size in the range from 200 to 2000 μm , more preferably from 250 to 1400 μm . Fine particles, smaller than 180 μm or 200 μm may be eliminated by sieving before tableting, if desired, although we have observed that this is not always essential.

[0074] While the starting particulate composition may in principle have any bulk density, the present invention is especially relevant to tablets made by compacting powders of relatively high bulk density, because of their greater tendency to exhibit disintegration and dispersion problems. Such tablets have the advantage that, as compared with a tablet derived from a low bulk density powder, a given dose of composition can be presented as a smaller tablet.

[0075] Thus the starting particulate composition may suitably have a bulk density of at least 400 g/litre, preferably at least 500 g/litre, and perhaps at least 600 g/litre.

[0076] Tableting machinery able to carry out the manufacture of tablets of the invention is known, for example suitable tablet presses are available from Fette and from Korch.

[0077] Tableting may be carried out at ambient temperature or at a temperature above ambient which may allow adequate strength to be achieved with less applied pressure during compaction. In order to carry out the tableting at a temperature which is above ambient, the particulate composition is preferably supplied to the tableting machinery at an elevated temperature. This will of course supply heat to the tableting machinery, but the machinery may be heated in some other way also.

[0078] The size of a tablet will suitably range from 10 to 160 grams, preferably from 15 to 60 g, depending on the conditions of intended use, and whether it represents a dose for an average load in a fabric washing or dishwashing machine or a fractional part of such a dose. The tablets may be of any shape. However, for ease of packaging they are preferably blocks of substantially uniform cross-section, such as cylinders or cuboids. The overall density of a tablet preferably lies in a range from 1040 or 1050gm/litre up to 1600gm/litre.

Method of manufacture

[0079] Cleaning tablets are preferably prepared by separately preparing a second (pre-) tablet of compacted powdered composition and a first smooth tablet followed by an assembly process to prepare the multi-phase cleaning tablet.

[0080] Accordingly in a preferred method to prepare the cleaning tablet of the invention -which has a plurality of discrete regions with differing compositions wherein

the tablet is

characterised in that at least one first region of the tablet is a smooth region and at least one second region of the tablet is a solid region of compacted particulate material-comprises the steps of

- (a) Preparation of a smooth first tablet;
- (b) Compression of the particulate material to form a second tablet of compacted particulate material;
- (c) Assembling the first tablet and the second tablet.

[0081] Preferably the second tablet is manufactured by inserting a particulate composition into a tablet mould followed by compression of the particulate composition part(s) to form a compressed tablet.

[0082] Preferably the first tablet is manufactured by a casting process. Suitable casting process involve the liquidising of the composition of the smooth phase for example by heating followed by inserting the composition into mold, followed by solidification for example by ageing or cooling.

[0083] Especially preferably the casting involves the heating of the composition of the second tablet, filling the composition into a mold and cooling.

[0084] The assembly process for combining the first and the second tablet can be any suitable process for example the co-compression or the adhering of the two phases into one tablet.

[0085] Preferably the diameter of the first tablet is substantially the same as the diameter of the second tablet. For the purpose of the invention "substantially the same diameter" means that the diameter of the first tablet differs less than 5 mm with the diameter of the second tablet, more preferably less than 3mm or even less than 1mm. This allows for ease of assembly and resulting in a multi-phase cleaning tablet wherein each of the phases is present as a separate layer of the tablet. If appropriate adhesive materials may be used to improve the connection between the phases of the multi-phase cleaning tablet.

Example 1

[0086] A detergent powder was made of the following composition by pregranulating the granule ingredients, followed by post-dosing the rest of the ingredients

Ingredient	Parts by weight
granules	
Na-las	1.1
Nonionic 7EO	0.5
Soap (C16-C18)	0.1
Zeolite A24	2.4
NaAc3aq	0.3
Light soda ash	0.4
SCMC (68%)	0.1

(continued)

<i>Ingredient</i>	<i>Parts by weight</i>
granules	
Moisture/minors	0.4
Post-dose	
EAG (17% silicone)	3.0
Fluorescer (15%)	2.2
STP HPA	28.3
STP LV	34.0
Na-disilicate (80%)	3.8
TAED (83%)	4.3
Percarbonate	16.9
Dequest 2047	1.9
Minors/ enzymes/colour	to 100

[0087] Smooth or semi-solid parts were prepared of the following composition:

<i>Ingredient</i>	<i>Parts by weight</i>
Na-las	39.1
Nonionic 7EO	33.5
C12 soap	7.3
Monopropyleenglycol	to 100

[0088] The mixture was heated to 80°C and casted into moulds and cooled to 20°C to form firm, 5 grammes smooth, semi-solid parts of 32mm or 45mm diameter.

[0089] The tablets were made in 3 different ways:

(I) 25grammes of the powder are inserted into a 45 mm die of a tableting machine, optionally followed by a flattening step, followed by addition of a single semi-solid part on top of the powder bed. After addition of the semi-solid onto the powder bed or flattened powder, the whole material is compressed at 6kN/cm² into a single tablet, followed by ejection of the tablet. This results in a tablet with a compressed smooth or semi-solid part embedded in the cleaning tablet.

(II) Another way of making a tablet with a smooth or semi-solid part is to put a single semi-solid part as above onto 25 grammes of the (optionally pre-compressed at 4 kN/cm²) powdered composition in a die of 45 mm diameter followed by a final compression step at 0.8 kN/cm². During the final compression step, the smooth or semi-solid part flows by the compaction forces to form a 3.4 mm smooth or semi-solid layer adhered on top of the particulate layer. The height of the powdered part after compression is 11 mm.

(III) Another way of making a tablet with a smooth

or semi-solid part is to pre-prepare a tablet by pre-compression of 25 grammes of the powdered composition at 4 kN/cm². in a tablet mold having a diameter of 45 mm. A smooth part having substantially the same diameter as the pre-compressed powdered tablet is then applied to the top of the tablet e.g. by gentle compression or by applying an adhesive.

[0090] Tablets prepared according the above methods provide good adherence of the smooth or semi-solid part to the rest of the tablet. Furthermore the tablets of the invention show fast dispersing of the compacted powder region during the washing process therewith allowing the early release of e.g. builder components into the washing liquor. The smooth or semi-solid part shows delayed dispersing therewith providing the surfactants at a later stage during the washing process.

Claims

1. Method of producing a cleaning tablet which has a plurality of discrete regions with differing compositions, **characterised in that** at least one first region of the tablet is a smooth region and at least one second region of the tablet is a solid region of compacted particulate material and wherein said method comprises the steps of

- Preparation of a smooth first tablet;
- Compression of the particulate material to form a second tablet of compacted particulate material;
- Assembling the first tablet and the second tablet.

2. A method according to claim 1, wherein the smooth first tablet region is a semi-solid tablet.

3. A method to prepare a cleaning tablet according to claim 1 or 2 wherein the second tablet is manufactured by inserting a particulate composition into a tablet mould followed by compression of the particulate composition part(s) to form a compressed tablet.

4. A method to prepare a cleaning tablet according to one or more of the preceding claims, wherein the first tablet is manufactured by a casting process.

5. A method according to claim 4, wherein the casting involves the heating of the composition of the first tablet, filling the composition into a mold and cooling.

6. A method according to one or more of the preceding claims wherein the diameter of the first tablet is sub-

stantially the same as the diameter of the second tablet.

7. A method according to one or more of the preceding claims wherein an adhesive is used between the first and second tablet. 5
8. Use of a cleaning tablet obtained by a process of one or more of claims 1-5 as a fabric washing detergent. 10
9. Tablet obtained by a process according to claim 1, said tablet being of cylindrical shape wherein the regions are separate layers. 15
10. Tablet according to claim 9 wherein the first smooth region has a weight of from 2 to 20 grammes and the second compacted particulate region has a weight of from 15 to 30 grammes. 20

25

30

35

40

45

50

55



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 07 6742

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X,D	WO 00 61717 A (PROCTER & GAMBLE (US)) 19 October 2000 (2000-10-19)	8-10	C11D17/00 C11D1/83
A	* page 35, line 1 - line 35; claims; examples * * page 4, line 22 - line 33 * * page 6, line 4 - page 7, line 31 *	1-7	
X,D	WO 99 24549 A (PROCTER&GAMBLE) 20 May 1999 (1999-05-20)	8-10	
A	* claims; examples 1-3 * * page 2, line 5 - page 3, line 17 * * page 35 * * page 4, line 10-33 *	1-7	
X	WO 99 06522 A (PROCTER&GAMBLE) 11 February 1999 (1999-02-11)	8-10	
A	* page 4, paragraph 2 - page 6, paragraph 1; claims; examples * * page 8 - page 9 * * page 16, paragraph 4 *	1-7	
A	EP 1 104 805 A (PROCTER & GAMBLE) 6 June 2001 (2001-06-06) * page 2, line 45 - page 3, line 55; claims *	1	TECHNICAL FIELDS SEARCHED (Int.Cl.7) C11D
A	WO 99 27064 A (PROCTER&GAMBLE) 3 June 1999 (1999-06-03) * claims; examples 1-3 * * page 2, line 10 - page 5, line 4 *	1-10	
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 29 September 2003	Examiner Loloiu, C
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 07 6742

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

29-09-2003

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 0061717	A	19-10-2000	EP	1043390 A1	11-10-2000
			AU	3571400 A	14-11-2000
			EP	1169426 A1	09-01-2002
			WO	0061717 A1	19-10-2000

WO 9924549	A	20-05-1999	AT	244296 T	15-07-2003
			AT	241003 T	15-06-2003
			AT	234913 T	15-04-2003
			BR	9813201 A	29-08-2000
			BR	9814021 A	26-09-2000
			BR	9814022 A	26-09-2000
			CA	2296354 C	27-05-2003
			CA	2309251 A1	20-05-1999
			CA	2309252 A1	20-05-1999
			CA	2309614 A1	20-05-1999
			DE	69812403 D1	24-04-2003
			DE	69814911 D1	26-06-2003
			DE	69816112 D1	07-08-2003
			EP	1032642 A1	06-09-2000
			EP	1032643 A1	06-09-2000
			EP	1032644 A1	06-09-2000
			ES	2190120 T3	16-07-2003
			JP	2001522933 T	20-11-2001
			JP	2001522934 T	20-11-2001
			JP	2001524552 T	04-12-2001
			WO	9924547 A1	20-05-1999
			WO	9924548 A1	20-05-1999
			WO	9924549 A1	20-05-1999
			WO	9924550 A1	20-05-1999
			US	6274538 B1	14-08-2001
			US	6413928 B1	02-07-2002
			US	6440927 B1	27-08-2002
			US	6486117 B1	26-11-2002

WO 9906522	A	11-02-1999	GB	2327949 A	10-02-1999
			AT	226626 T	15-11-2002
			BR	9815605 A	20-11-2001
			CN	1272875 T	08-11-2000
			DE	29823752 U1	05-01-2000
			DE	29824535 U1	06-09-2001
			DE	69808885 D1	28-11-2002
			DE	69808885 T2	18-06-2003
			DK	960187 T3	24-02-2003
			EP	1134281 A1	19-09-2001
			EP	1162258 A2	12-12-2001
			EP	0960187 A1	01-12-1999

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 07 6742

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

29-09-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9906522 A		ES 2142782 T1	01-05-2000
		JP 2001512177 T	21-08-2001
		PT 960187 T	31-03-2003
		WO 9906522 A1	11-02-1999
		US 6451754 B1	17-09-2002

EP 1104805 A	06-06-2001	DE 29923876 U1	30-08-2001
		EP 1104805 A2	06-06-2001
		EP 1327676 A2	16-07-2003
		AT 242312 T	15-06-2003
		AT 242311 T	15-06-2003
		AT 241004 T	15-06-2003
		AT 212660 T	15-02-2002
		AT 211503 T	15-01-2002
		AT 215985 T	15-04-2002
		AT 213767 T	15-03-2002
		AT 243737 T	15-07-2003
		AU 762815 B2	03-07-2003
		AU 4964299 A	07-02-2000
		AU 761595 B2	05-06-2003
		AU 4964399 A	07-02-2000
		AU 4964499 A	07-02-2000
		AU 4968699 A	07-02-2000
		AU 4978599 A	07-02-2000
		AU 5093599 A	07-02-2000
		AU 5093699 A	07-02-2000
		BR 9912150 A	10-04-2001
		BR 9912157 A	10-04-2001
		BR 9912833 A	09-10-2001
		BR 9912834 A	02-05-2001
		BR 9912836 A	02-05-2001
		BR 9912838 A	02-05-2001
		CA 2333388 A1	27-01-2000
		CA 2333468 A1	27-01-2000
		CA 2333894 A1	27-01-2000
		CA 2337401 A1	27-01-2000
		CA 2337402 A1	27-01-2000
		CA 2337408 A1	27-01-2000
		CA 2337427 A1	27-01-2000
		CN 1309692 T	22-08-2001
		CN 1309693 T	22-08-2001
		CN 1337997 T	27-02-2002
		CN 1309694 T	22-08-2001
		DE 29911484 U1	24-02-2000
		DE 29911486 U1	18-11-1999
		DE 29923872 U1	30-08-2001

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 07 6742

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

29-09-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 1104805 A		DE 29923873 U1	26-07-2001
		DE 29923874 U1	30-08-2001
		DE 69900736 D1	28-02-2002
		DE 69900736 T2	29-08-2002
		DE 69900833 D1	14-03-2002
		DE 69900833 T2	31-10-2002
		DE 69900931 D1	04-04-2002
		DE 69900931 T2	07-11-2002
		DE 69901211 D1	16-05-2002
		DE 69901211 T2	14-11-2002
WO 9927064 A	03-06-1999	BR 9815064 A	20-11-2001
		CA 2311503 A1	03-06-1999
		EP 1034247 A1	13-09-2000
		JP 2001524590 T	04-12-2001
		WO 9927064 A1	03-06-1999
		US 6391845 B1	21-05-2002