



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 377 012 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

Note: Bibliography reflects the latest situation

(15) Correction information:
Corrected version no 1 (W1 A1)
INID code(s) 72

(51) Int Cl.7: **H04N 1/00**

(48) Corrigendum issued on:
28.04.2004 Bulletin 2004/18

(43) Date of publication:
02.01.2004 Bulletin 2004/01

(21) Application number: **03077733.8**

(22) Date of filing: **30.08.2001**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**

(30) Priority: **01.09.2000 JP 2000265475**
22.09.2000 JP 2000288801
22.09.2000 JP 2000288802
22.09.2000 JP 2000288804
11.10.2000 JP 2000310823
11.10.2000 JP 2000310824
11.10.2000 JP 2000310825
17.10.2000 JP 2000316510
19.10.2000 JP 2000319898
20.10.2000 JP 2000321675

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
01307376.2 / 1 187 447

(71) Applicant: **CANON KABUSHIKI KAISHA**
Tokyo (JP)

(72) Inventors:
• **Nakao, Nuneki**
Shimomaruko Ohta-ku Tokyo (JP)

- **Takeda, Tomoyuki**
Shimomaruko Ohta-ku Tokyo (JP)
- **Nakamura, Naomi**
Shimomaruko Ohta-ku Tokyo (JP)
- **Okamura, Koji**
Shimomaruko Ohta-ku Tokyo (JP)
- **Mikuni, Makoto**
Shimomaruko Ohta-ku Tokyo (JP)
- **Izumi, Michihiro**
Shimomaruko Ohta-ku Tokyo (JP)
- **Hirai, Yoshiyuki**
Shimomaruko Ohta-ku Tokyo (JP)

(74) Representative:
Beresford, Keith Denis Lewis et al
BERESFORD & Co.
16 High Holborn
London WC1V 6BX (GB)

Remarks:
This application was filed on 01 - 09 - 2003 as a
divisional application to the application mentioned
under INID code 62.

(54) **Communication apparatus capable of communication with other apparatuses through
wireless communication, communication system having the same communication
apparatus, and method for controlling the same**

(57) Wireless mode between a scanner and an im-
age communication apparatus is changed when the
scanner completes read of an image, when the image
is sent from the scanner to the image communication
apparatus by the operation of the scanner, or depending

on presence or absence of read original, and for exam-
ple, low power consumption mode and communication
mode are switched to each other.

EP 1 377 012 A8

FIG. 1

