



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

Note: Bibliography reflects the latest situation

(15) Correction information:
Corrected version no 1 (W1 A1)
INID code(s) 72

(51) Int Cl.7: **F25B 6/04**, F25B 39/04,
F25B 41/06, F25B 43/00,
F25B 41/04, B60H 1/32,
F28D 1/053

(48) Corrigendum issued on:
30.06.2004 Bulletin 2004/27

(43) Date of publication:
31.03.2004 Bulletin 2004/14

(21) Application number: **03023626.9**

(22) Date of filing: **25.04.2001**

(84) Designated Contracting States:
DE FR GB IT

(30) Priority: **26.04.2000 JP 2000126161**
14.09.2000 JP 2000279956
09.01.2001 JP 2001001535
20.02.2001 JP 2001043971
26.02.2001 JP 2001050923

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
01109493.5 / 1 150 076

(71) Applicant: **Denso Corporation**
Kariya-city, Aichi-pref., 448-8661 (JP)

(72) Inventors:
• **Ito, Shigeki**
Kariya-city, Aichi-pref. 448-8661 (JP)
• **Yamasaki, Kurato**
Kariya-city, Aichi-pref. 448-8661 (JP)

• **Hotta, Teruyuki**
Kariya-city, Aichi-pref. 448-8661 (JP)
• **Yamanaka, Yasushi**
Kariya-city, Aichi-pref. 448-8661 (JP)
• **Inaba, Atsushi**
Kariya-city, Aichi-pref. 448-8661 (JP)

(74) Representative:
Klingseisen, Franz, Dipl.-Ing. et al
Patentanwälte,
Dr. F. Zumstein,
Dipl.-Ing. F. Klingseisen,
Postfach 10 15 61
80089 München (DE)

Remarks:

This application was filed on 16 - 10 - 2003 as a
divisional application to the application mentioned
under INID code 62.

(54) **Refrigerant cycle system**

(57) A condenser (2) of a refrigerant cycle system includes a first heat exchange unit (2a) into which refrigerant discharged from a compressor (1) flows, a second heat exchange unit (2b) disposed at a downstream of the first heat exchange unit in a refrigerant flow direction, and a gas-liquid separator (2c) disposed between the first and second heat exchange units in the refrigerant flow direction. In the refrigerant cycle system, at least gas refrigerant separated in the gas-liquid separator flows into the second heat exchange unit so that an amount of liquid refrigerant stored in the gas-liquid separator is changed in accordance with a super-heating degree of refrigerant discharged from the compressor.

FIG. 25

