



(19) Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

EP 1 411 734 A8

(12)

## CORRECTED EUROPEAN PATENT APPLICATION

Note: Bibliography reflects the latest situation

(15) Correction information:

**Corrected version no 1 (W1 A1)**  
**INID code(s) 30**

(51) Int Cl.:

**H04N 9/804<sup>(1995.01)</sup>**

(48) Corrigendum issued on:

**08.03.2006 Bulletin 2006/10**

(43) Date of publication:

**21.04.2004 Bulletin 2004/17**

(21) Application number: **03078856.6**

(22) Date of filing: **23.06.1995**

(84) Designated Contracting States:  
**DE GB**

(30) Priority: **24.06.1994 JP 14341194**  
**08.08.1994 JP 18603594**

(60) Divisional application:  
**05075237.7 / 1 531 631**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:  
**02024773.0 / 1 282 317**  
**01125502.3 / 1 189 459**

(71) Applicant: **MITSUBISHI DENKI KABUSHIKI KAISHA**  
**Tokyo 100 (JP)**

(72) Inventor: **Nagasawa, Masato,**  
**c/o Mitsubishi Denki K.K.**  
**Nagaokakyō-shi**  
**Kyoto 617 (JP)**

(74) Representative: **Whitlock, Holly Elizabeth Ann et al**  
**R G C Jenkins,**  
**26 Caxton Street**  
**London SW1H 0RJ (GB)**

Remarks:

This application was filed on 05 - 12 - 2003 as a divisional application to the application mentioned under INID code 62.

### (54) Optical disk and method of playback

(57) In an optical disk storing digital image information in the form of a succession of blocks, each comprising a plurality of frames comprising I-, P- and B-pictures, the disk comprises a plurality of recording sectors, each sector being associated with an address recorded on said optical disk; and a plurality of tracks, each track including a plurality of recording sectors; wherein the image information block includes a video attribute data region (50) preceding the I-picture data (53-55), the P-picture data (57,58), and the B-picture data thereof, said video attribute data region (50) containing picture position information (61), which indicates a position of coded pictures

in the corresponding image information block on accessing during playback to read at least I-picture data (53-55) of the digital image information in the corresponding image information block, and jump destination information (65), which indicates an address of the next image information block to be played back during said playback to read at least I-picture data (53-55); and wherein the video attribute data region (50) has an address (49) on the head thereof, and the address of the next image information block (49) is an address of the video attribute data region (50) in the next image information block.