



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

Note: Bibliography reflects the latest situation

(15) Correction information:
Corrected version no 1 (W1 A2)
INID code(s) 22

(51) Int Cl.7: **E21B 33/10**, E21B 7/08,
E21B 29/06, E21B 23/06,
E21B 23/04, E21B 33/12,
E21B 33/127, E21B 43/10,
E21B 7/06

(48) Corrigendum issued on:
20.10.2004 Bulletin 2004/43

(43) Date of publication:
16.06.2004 Bulletin 2004/25

(21) Application number: **04075738.7**

(22) Date of filing: **12.05.1999**

(84) Designated Contracting States:
DE FR GB NL

(30) Priority: **28.05.1998 US 86716**

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
99303716.7 / 0 961 007

(71) Applicant: **Halliburton Energy Services, Inc.**
Dallas, Texas 75381-9052 (US)

(72) Inventors:
• **Gano, John C.**
Carrollton, Texas 75007 (US)

- **Freeman, Tommie**
Flower Mound, Texas 75028 (US)
- **Longbottom, Jim R.**
Magnolia, Texas 77353 (US)
- **Bowling, John S.**
Missouri City, Texas 77459 (US)

(74) Representative: **Curtis, Philip Anthony et al**
A.A. Thornton & Co.,
235 High Holborn
London WC1V 7LE (GB)

Remarks:

This application was filed on 05 - 03 - 2004 as a
divisional application to the application mentioned
under INID code 62.

(54) **Expandable wellbore junction**

(57) A method of interconnecting first and second wellbores. The method comprises the steps of: forming a radially enlarged cavity (20) in the first wellbore (12) below casing (14) lining the first wellbore (20); positioning a wellbore connector (22) within the cavity (20), the wellbore connector (22) being configurable in expanded and contracted configurations; and expanding the wellbore connector (22) within the cavity (20).




FIG. 1A