



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 429 571 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

published in accordance with Art. 158(3) EPC

Note: Bibliography reflects the latest situation

(15) Correction information:
Corrected version no 1 (W1 A1)
INID code(s) 54

(51) Int Cl.7: **H04Q 7/36**

(86) International application number:
PCT/JP2002/008590

(48) Corrigendum issued on:
22.09.2004 Bulletin 2004/39

(87) International publication number:
WO 2003/021994 (13.03.2003 Gazette 2003/11)

(43) Date of publication:
16.06.2004 Bulletin 2004/25

(21) Application number: **02762865.0**

(22) Date of filing: **26.08.2002**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
IE IT LI LU MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **ITO, Tadayoshi, c/o SANYO ELECTRIC CO., LTD.**
Moriguchi-shi, Osaka 570-8677 (JP)
• **DOI, Yoshiharu, c/o SANYO ELECTRIC CO., LTD.**
Moriguchi-shi, Osaka 570-8677 (JP)

(30) Priority: **31.08.2001 JP 2001263514**
18.09.2001 JP 2001283380
19.09.2001 JP 2001284401

(74) Representative: **Glawe. Delfs. Moll**
Patentanwälte
Postfach 26 01 62
80058 München (DE)

(71) Applicant: **Sanyo Electric Co., Ltd.**
Moriguchi-shi, Osaka-fu 570-8677 (JP)

(54) **RADIO BASE APPARATUS, COMMUNICATION CHANNEL ALLOCATION METHOD, AND ALLOCATION PROGRAM**

(57) A signal transmitted and received at an adaptive array base station (1000) is divided into a plurality of frames each including a control slot for a control channel and a plurality of communication slots for speech. Adaptive array base station (1000) includes a reception

level sensing unit (50) for monitoring a signal level of a control slot from a peripheral base station, and a channel allocation computing unit (70) for allocating the control slot for information communication in response to a sensing result of reception level sensing unit (50) when a link channel is requested from a terminal device.

FIG.1

