



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

Note: Bibliography reflects the latest situation

(15) Correction information:
Corrected version no 1 (W1 A2)
INID code(s) 22,84

(51) Int Cl.7: **A47D 11/00**, A47D 7/04,
A47D 13/06, A47D 5/00

(48) Corrigendum issued on:
17.11.2004 Bulletin 2004/47

(43) Date of publication:
18.08.2004 Bulletin 2004/34

(21) Application number: **04009139.9**

(22) Date of filing: **26.10.2000**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

(30) Priority: **19.04.2000 US 552331**
22.05.2000 WOPCT/US00/14086

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
00309438.0 / 1 147 727

(71) Applicant: **Arms Reach Concepts, Inc.**
Malibu, CA 90265 (US)

(72) Inventors:
• **Tharalson, Douglas**
Agoura, California (US)

• **Tharalson, Diana**
Agoura, California (US)
• **Martin, Bruce**
Malibu, California 90265 (US)

(74) Representative:
Fox-Male, Nicholas Vincent Humbert et al
Eric Potter Clarkson
Park View House
58 The Ropewalk
Nottingham NG1 5DD (GB)

Remarks:

This application was filed on 16 - 04 - 2004 as a
divisional application to the application mentioned
under INID code 62.

(54) **Multi-level multiple purpose convertible playpen**

(57) A co-sleeper convertibly adapted for use as a bassinet or changing table comprising: a frame comprising left and right side rails (58,62) and a rear rail (54), said rails being substantially horizontal and supported by a plurality of vertical supports, said left and right side rails forming a top plane, said frame further comprising a plurality of support rails (90,94), said support rails being substantially horizontal and located on a plane lower than said top plane; an upper front rail (50), said front rail being engagable at a height below said top plane or at a height wherein said upper front rail is substantially coplanar with said top plane; an enclosure (14), said enclosure being sized to fit substantially within the frame and comprising an open top (18) and a bottom panel (22), said open top having a perimeter substantially co-extensive with said left and right side rails and said rear rail, said enclosure further comprising left, right and rear walls (34,38,30) extending from said perimeter to said bottom panel, said left and right walls each having a first

edge joined to said rear wall, and a second edge opposite from said first edges, said enclosure further comprising a front portion (26), said front portion comprising a flap of sufficient length to allow said flap to be engaged to said upper front rail when said upper front rail is engaged to said frame at a height wherein said upper front rail is substantially coplanar with said top plane, said flap further comprising left and right edges having means for selectively joining said left and right edges to said left and right side walls, respectively, along said second edges to allow a front wall of varying height to be formed; wherein said bottom panel of said enclosure rests on said support rails when said enclosure is disposed within said frame, and further wherein said front portion is selectively joined to said left and right walls and to said upper front rail when said upper front rail is engaged to said frame; and a securing strap assembly for securing the co-sleeper to a parental bed.

